

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250260734

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Atarius; Roozbeh

---

### SERVICE OPERATIONS FOR APPLICATION PROGRAMMING INTERFACES (APIs)

---

#### Abstract

Various aspects of the present disclosure relate to service operations for Application Programming Interfaces (APIs). A first network equipment (NE) transmits, to a second NE, a request message for a service operation, the request message including a resource Uniform Resource Identifier (URI) for a Hypertext Transfer Protocol (HTTP) POST method, and the service operation includes one or more of an initial Application Programming Interface (API) configuration, an API configuration update, or an API invocation associated with an API provider. The first NE receives, from the second NE, a response message including a result of the service operation.

---

**Inventors:** Atarius; Roozbeh (La Jolla, CA)

**Applicant:** Lenovo (Singapore) Pte. Limited (Singapore, SG)

**Family ID:** 1000008487168

**Assignee:** Lenovo (Singapore) Pte. Limited (Singapore, SG)

**Appl. No.:** 19/048388

**Filed:** February 07, 2025

#### Related U.S. Application Data

us-provisional-application US 63553621 20240214

---

#### Publication Classification

**Int. Cl.:** H04L67/02 (20220101); G06F9/54 (20060101)

**U.S. Cl.:**

**CPC** H04L67/02 (20130101); G06F9/547 (20130101);

---

## **Background/Summary**

RELATED APPLICATION [0001] This application claims priority to U.S. Provisional Application Ser. No. 63/553,621, filed 14 Feb. 2024 entitled “SERVICE OPERATIONS FOR APPLICATION PROGRAMMING INTERFACES (APIs),” the disclosure of which is incorporated by reference herein in its entirety.

### **TECHNICAL FIELD**

[0002] The present disclosure relates to wireless communications, and more specifically to utilizing Application Programming Interfaces (APIs) in wireless communications.

### **BACKGROUND**

[0003] A wireless communications system may include one or multiple network communication devices, which may be otherwise known as network equipment (NE), supporting wireless communications for one or multiple user communication devices, which may be otherwise known as user equipment (UE), or other suitable terminology. The wireless communications system may support wireless communications with one or multiple user communication devices by utilizing resources of the wireless communication system (e.g., time resources (e.g., symbols, slots, subframes, frames, or the like) or frequency resources (e.g., subcarriers, carriers, or the like)). Additionally, the wireless communications system may support wireless communications across various radio access technologies including third generation (3G) radio access technology, fourth generation (4G) radio access technology, fifth generation (5G) radio access technology, among other suitable radio access technologies beyond 5G (e.g., sixth generation (6G)).

### **SUMMARY**

[0004] An article “a” before an element is unrestricted and understood to refer to “at least one” of those elements or “one or more” of those elements. The terms “a,” “at least one,” “one or more,” and “at least one of one or more” may be interchangeable. As used herein, including in the claims, “or” as used in a list of items (e.g., a list of items prefaced by a phrase such as “at least one of” or “one or more of” or “one or both of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” cannot be construed as a reference to a closed set of conditions. For example, an example step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” can be construed in the same manner as the phrase “based at least in part on”. Further, as used herein, including in the claims, a “set” may include one or more elements.

[0005] Some implementations of the method and apparatuses described herein may further include a NE for wireless communication to transmit, to a second NE, a request message for a service operation, the request message including a resource Uniform Resource Identifier (URI) for a Hypertext Transfer Protocol (HTTP) POST method, and the service operation including one of an initial Application Programming Interface (API) configuration or an API configuration update; and receive, from the second NE, a response message including a result of the service operation.

[0006] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more

data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReq; the at least one processor is configured to cause the first NE to receive, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo; the first NE includes a Vertical Application Layer (VAL) server; the second NE includes a Network Slice Capability Exposure (NSCE) Server; the service operation pertains to one or more network slice APIs.

[0007] Some implementations of the method and apparatuses described herein may further include a method performed by a NE, the method including transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; and receiving, from the second NE, a response message including a result of the service operation.

[0008] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReq; In some aspects, the techniques described herein relate to a method, further including receiving, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0009] Some implementations of the method and apparatuses described herein may further include a NE for wireless communication to receive, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0010] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReq; the at least one processor is configured to cause the second NE to transmit, to the first NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0011] Some implementations of the method and apparatuses described herein may further include a method performed by a NE, the method including receiving, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; performing the service operation; and transmitting, to the first NE, a response message including a result of the service operation.

[0012] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReq; In some aspects, the techniques described herein relate to a method, further including transmitting, to the first NE, a

response including slice API information; the response includes {apiRoot}/nsce-sai/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0013] Some implementations of the method and apparatuses described herein may further include a NE for wireless communication to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; and receive, from the second NE, a response message including a result of the service operation.

[0014] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the operation URI includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0015] Some implementations of the method and apparatuses described herein may further include a method performed by a NE, the method including transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; and receiving, from the second NE, a response message including a result of the service operation.

[0016] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the operation URI includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0017] Some implementations of the method and apparatuses described herein may further include a NE for wireless communication to receive, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0018] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the at least one processor is configured to cause the second NE to one or more of: verify, based at least in part on the information of the one or more data types, an identity of the first NE; or determine, based at least in part on the information of the one or more data types, whether the first NE is authorized to request the API invocation; the response includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; to perform the service operation, the at least one processor is configured to cause the second NE to translate the API invocation to a service API invocation; to translate the API invocation to the service API invocation, the at least one processor is configured to cause the second NE to map a network slice for the API invocation to the service API; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0019] Some implementations of the method and apparatuses described herein may further include a method performed by a NE, the method including transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; and receiving, from the second NE, a response message including a result of the service operation.

[0020] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the operation URI includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0021] Some implementations of the method and apparatuses described herein may further include a NE for wireless communication to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; and receive, from the second NE, a response message including a result of the service operation.

[0022] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration, the API configuration update, or the API invocation; the operation URI includes one or more of {apiRoot}/nscc-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; the at least one processor is configured to cause the first NE to receive, from the second NE, a response including slice API information; the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0023] Some implementations of the method and apparatuses described herein may further include a method performed by a NE, the method including transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; and receiving, from the second NE, a response message including a result of the service operation.

[0024] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration, the API configuration update, or the API invocation; the operation URI includes one or more of {apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nscc-sam/<apiVersion>/ApiInvoc; In some aspects, the techniques described herein relate to a method, further including receiving, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sam/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0025] Some implementations of the method and apparatuses described herein may further include a NE for wireless communication to receive, from a first NE, a request message for a service operation, the request message including an operation URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; perform the service operation; and

transmit, to the first NE, a response message including a result of the service operation.

[0026] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {{apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; the at least one processor is configured to cause the second NE to transmit, to the first NE, a response including slice API information; the response comprises {apiRoot}/nscc-sam/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0027] Some implementations of the method and apparatuses described herein may further include a method performed by a NE, the method including receiving, from a first NE, a request message for a service operation, the request message including an operation URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; performing the service operation; and transmitting, to the first NE, a response message including a result of the service operation.

[0028] In some implementations of the method and apparatuses for a NE described herein, the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the response message includes one or more of {{apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; In some aspects, the techniques described herein relate to a method, further including transmitting, to the first NE, a response including slice API information; the response includes {apiRoot}/nsce-sam/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0029] FIG. 1 illustrates an example of a wireless communications system in accordance with aspects of the present disclosure.

[0030] FIG. 2 illustrates an example signaling diagram for initial slice API configuration.

[0031] FIG. 3 illustrates an example signaling diagram for slice API configuration update based on a trigger event.

[0032] FIG. 4 illustrates an example signaling diagram for slice API translation based on an initial configuration.

[0033] FIG. 5 illustrates an example resource URI structure in accordance with aspects of the present disclosure.

[0034] FIG. 6 illustrates an example resource URI structure in accordance with aspects of the present disclosure.

[0035] FIG. 7 illustrates an example resource URI structure in accordance with aspects of the present disclosure.

[0036] FIG. 8 illustrates an example of a NE in accordance with aspects of the present disclosure.

[0037] FIG. 9 illustrates an example of a processor in accordance with aspects of the present disclosure.

[0038] FIG. 10 illustrates a flowchart of a method in accordance with aspects of the present disclosure.

[0039] FIG. **11** illustrates a flowchart of a method in accordance with aspects of the present disclosure.

[0040] FIG. **12** illustrates a flowchart of a method in accordance with aspects of the present disclosure.

[0041] FIG. **13** illustrates a flowchart of a method in accordance with aspects of the present disclosure.

[0042] FIG. **14** illustrates a flowchart of a method in accordance with aspects of the present disclosure.

[0043] FIG. **15** illustrates a flowchart of a method in accordance with aspects of the present disclosure.

## DETAILED DESCRIPTION

[0044] Wireless communications systems such as 5G networks can utilize network slicing to enable network operators to divide a single physical network into multiple distinct virtual connections, each tailored to specific types of traffic. Virtual slices can provide different types and amounts of resources that enable diverse functionality. To enable network slice configuration and expose functionality and services of network slices, APIs can be utilized. However, creating APIs and related resources (e.g., URIs) and data models for network slicing presents a number of challenges.

[0045] Accordingly, aspects of the disclosure are directed to a framework for defining API-related services including service operations for which methods and associated resources (e.g., URIs) and related data types can be defined. The described solutions can thus provide more efficient wireless network slicing and enable more robust exposure of wireless network slice-related services.

[0046] Aspects of the present disclosure are described in the context of a wireless communications system.

[0047] FIG. **1** illustrates an example of a wireless communications system **100** in accordance with aspects of the present disclosure. The wireless communications system **100** may include one or more NE **102**, one or more UE **104**, and a core network (CN) **106**. The wireless communications system **100** may support various radio access technologies. In some implementations, the wireless communications system **100** may be a 4G network, such as an LTE network or an LTE-Advanced (LTE-A) network. In some other implementations, the wireless communications system **100** may be a NR network, such as a 5G network, a 5G-Advanced (5G-A) network, or a 5G ultrawideband (5G-UWB) network. In other implementations, the wireless communications system **100** may be a combination of a 4G network and a 5G network, or other suitable radio access technology including Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20. The wireless communications system **100** may support radio access technologies beyond 5G, for example, 6G. Additionally, the wireless communications system **100** may support technologies, such as time division multiple access (TDMA), frequency division multiple access (FDMA), or code division multiple access (CDMA), etc.

[0048] The one or more NE **102** may be dispersed throughout a geographic region to form the wireless communications system **100**. One or more of the NE **102** described herein may be or include or may be referred to as a network node, a base station, a network element, a network function, a network entity, a radio access network (RAN), a NodeB, an eNodeB (eNB), a next-generation NodeB (gNB), or other suitable terminology. An NE **102** and a UE **104** may communicate via a communication link, which may be a wireless or wired connection. For example, an NE **102** and a UE **104** may perform wireless communication (e.g., receive signaling, transmit signaling) over a Uu interface.

[0049] An NE **102** may provide a geographic coverage area for which the NE **102** may support services for one or more UEs **104** within the geographic coverage area. For example, an NE **102** and a UE **104** may support wireless communication of signals related to services (e.g., voice, video, packet data, messaging, broadcast, etc.) according to one or multiple radio access technologies. In some implementations, an NE **102** may be moveable, for example, a satellite associated with a non-

terrestrial network (NTN). In some implementations, different geographic coverage areas associated with the same or different radio access technologies may overlap, but the different geographic coverage areas may be associated with different NE **102**.

[0050] The one or more UEs **104** may be dispersed throughout a geographic region of the wireless communications system **100**. A UE **104** may include or may be referred to as a remote unit, a mobile device, a wireless device, a remote device, a subscriber device, a transmitter device, a receiver device, or some other suitable terminology. In some implementations, the UE **104** may be referred to as a unit, a station, a terminal, or a client, among other examples. Additionally, or alternatively, the UE **104** may be referred to as an Internet-of-Things (IoT) device, an Internet-of-Everything (IoE) device, or machine-type communication (MTC) device, among other examples.

[0051] A UE **104** may be able to support wireless communication directly with other UEs **104** over a communication link. For example, a UE **104** may support wireless communication directly with another UE **104** over a device-to-device (D2D) communication link. In some implementations, such as vehicle-to-vehicle (V2V) deployments, vehicle-to-everything (V2X) deployments, or cellular-V2X deployments, the communication link may be referred to as a sidelink. For example, a UE **104** may support wireless communication directly with another UE **104** over a PC5 interface.

[0052] An NE **102** may support communications with the CN **106**, or with another NE **102**, or both. For example, an NE **102** may interface with other NE **102** or the CN **106** through one or more backhaul links (e.g., S1, N2, N6, or other network interface). In some implementations, the NE **102** may communicate with each other directly. In some other implementations, the NE **102** may communicate with each other indirectly (e.g., via the CN **106**). In some implementations, one or more NE **102** may include subcomponents, such as an access network entity, which may be an example of an access node controller (ANC). An ANC may communicate with the one or more UEs **104** through one or more other access network transmission entities, which may be referred to as a radio heads, smart radio heads, or transmission-reception points (TRPs).

[0053] The CN **106** may support user authentication, access authorization, tracking, connectivity, and other access, routing, or mobility functions. The CN **106** may be an evolved packet core (EPC), or a 5G core (5GC), which may include a control plane entity that manages access and mobility (e.g., a mobility management entity (MME), an access and mobility management functions (AMF)) and a user plane entity that routes packets or interconnects to external networks (e.g., a serving gateway (S-GW), a packet data network (PDN) gateway (P-GW), or a user plane function (UPF)). In some implementations, the control plane entity may manage non-access stratum (NAS) functions, such as mobility, authentication, and bearer management (e.g., data bearers, signal bearers, etc.) for the one or more UEs **104** served by the one or more NE **102** associated with the CN **106**.

[0054] The CN **106** may communicate with a packet data network over one or more backhaul links (e.g., via an S1, N2, N6, or other network interface). The packet data network may include an application server. In some implementations, one or more UEs **104** may communicate with the application server. A UE **104** may establish a session (e.g., a protocol data unit (PDU) session, or the like) with the CN **106** via an NE **102**. The CN **106** may route traffic (e.g., control information, data, and the like) between the UE **104** and the application server using the established session (e.g., the established PDU session). The PDU session may be an example of a logical connection between the UE **104** and the CN **106** (e.g., one or more network functions of the CN **106**).

[0055] In the wireless communications system **100**, the NEs **102** and the UEs **104** may use resources of the wireless communications system **100** (e.g., time resources (e.g., symbols, slots, subframes, frames, or the like) or frequency resources (e.g., subcarriers, carriers)) to perform various operations (e.g., wireless communications). In some implementations, the NEs **102** and the UEs **104** may support different resource structures. For example, the NEs **102** and the UEs **104** may support different frame structures. In some implementations, such as in 4G, the NEs **102** and the UEs **104** may support a single frame structure. In some other implementations, such as in 5G



and among other suitable radio access technologies, the NEs **102** and the UEs **104** may support various frame structures (i.e., multiple frame structures). The NEs **102** and the UEs **104** may support various frame structures based on one or more numerologies.

[0056] One or more numerologies may be supported in the wireless communications system **100**, and a numerology may include a subcarrier spacing and a cyclic prefix. A first numerology (e.g.,  $\mu=0$ ) may be associated with a first subcarrier spacing (e.g., 15 kHz) and a normal cyclic prefix. In some implementations, the first numerology (e.g.,  $\mu=0$ ) associated with the first subcarrier spacing (e.g., 15 kHz) may utilize one slot per subframe. A second numerology (e.g.,  $\mu=1$ ) may be associated with a second subcarrier spacing (e.g., 30 kHz) and a normal cyclic prefix. A third numerology (e.g.,  $\mu=2$ ) may be associated with a third subcarrier spacing (e.g., 60 kHz) and a normal cyclic prefix or an extended cyclic prefix. A fourth numerology (e.g.,  $\mu=3$ ) may be associated with a fourth subcarrier spacing (e.g., 120 kHz) and a normal cyclic prefix. A fifth numerology (e.g.,  $\mu=4$ ) may be associated with a fifth subcarrier spacing (e.g., 240 kHz) and a normal cyclic prefix.

[0057] A time interval of a resource (e.g., a communication resource) may be organized according to frames (also referred to as radio frames). Each frame may have a duration, for example, a 10 millisecond (ms) duration. In some implementations, each frame may include multiple subframes. For example, each frame may include 10 subframes, and each subframe may have a duration, for example, a 1 ms duration. In some implementations, each frame may have the same duration. In some implementations, each subframe of a frame may have the same duration.

[0058] Additionally or alternatively, a time interval of a resource (e.g., a communication resource) may be organized according to slots. For example, a subframe may include a number (e.g., quantity) of slots. The number of slots in each subframe may also depend on the one or more numerologies supported in the wireless communications system **100**. For instance, the first, second, third, fourth, and fifth numerologies (i.e.,  $\mu=0$ ,  $\mu=1$ ,  $\mu=2$ ,  $\mu=3$ ,  $\mu=4$ ) associated with respective subcarrier spacings of 15 kHz, 30 kHz, 60 kHz, 120 kHz, and 240 kHz may utilize a single slot per subframe, two slots per subframe, four slots per subframe, eight slots per subframe, and 16 slots per subframe, respectively. Each slot may include a number (e.g., quantity) of symbols (e.g., Orthogonal Frequency Division Multiplexing (OFDM) symbols). In some implementations, the number (e.g., quantity) of slots for a subframe may depend on a numerology. For a normal cyclic prefix, a slot may include 14 symbols. For an extended cyclic prefix (e.g., applicable for 60 KHz subcarrier spacing), a slot may include 12 symbols. The relationship between the number of symbols per slot, the number of slots per subframe, and the number of slots per frame for a normal cyclic prefix and an extended cyclic prefix may depend on a numerology. It should be understood that reference to a first numerology (e.g.,  $\mu=0$ ) associated with a first subcarrier spacing (e.g., 15 kHz) may be used interchangeably between subframes and slots.

[0059] In the wireless communications system **100**, an electromagnetic (EM) spectrum may be split, based on frequency or wavelength, into various classes, frequency bands, frequency channels, etc. By way of example, the wireless communications system **100** may support one or multiple operating frequency bands, such as frequency range designations FR1 (410 MHz-7.125 GHz), FR2 (24.25 GHz-52.6 GHz), FR3 (7.125 GHz-24.25 GHz), FR4 (52.6 GHz-114.25 GHz), FR4a or FR4-1 (52.6 GHz-71 GHz), and FR5 (114.25 GHz-300 GHz). In some implementations, the NEs **102** and the UEs **104** may perform wireless communications over one or more of the operating frequency bands. In some implementations, FR1 may be used by the NEs **102** and the UEs **104**, among other equipment or devices for cellular communications traffic (e.g., control information, data). In some implementations, FR2 may be used by the NEs **102** and the UEs **104**, among other equipment or devices for short-range, high data rate capabilities.

[0060] FR1 may be associated with one or multiple numerologies (e.g., at least three numerologies). For example, FR1 may be associated with a first numerology (e.g.,  $\mu=0$ ), which includes 15 kHz subcarrier spacing; a second numerology (e.g.,  $\mu=1$ ), which includes 30 kHz

subcarrier spacing; and a third numerology (e.g.,  $\mu=2$ ), which includes 60 kHz subcarrier spacing. FR2 may be associated with one or multiple numerologies (e.g., at least 2 numerologies). For example, FR2 may be associated with a third numerology (e.g.,  $\mu=2$ ), which includes 60 kHz subcarrier spacing; and a fourth numerology (e.g.,  $\mu=3$ ), which includes 120 kHz subcarrier spacing.

[0061] According to implementations, different NE **102** and the CN **106** can implement various entities such as VAL servers, NSCE servers, API providers, etc. For instance, VAL servers and NSCE servers can interact as part of network slicing in the context of the wireless communications system **100** to enable functionality such as slice API configuration, slice API configuration updating, slice API invocation, etc., to configure and expose functionality and services of network slice APIs.

[0062] With reference to utilization of APIs in network slices, clause 9.3 of 3GPP Technical Specification (TS) 23.435 specifies stage 2 of slice API configuration and translation functionality which is provided to the vertical application layer (VAL) and configures the exposure of APIs in a slice-tailored manner. (See 3GPP TS 23.435, Release 18, Version 18.1.0, Jan. 5, 2024, titled “Procedures for Network Slice Capability Exposure for Application Layer Enablement Service,” hereinafter referred to as “3GPP TS 23.435”, which is hereby incorporated by reference herein in its entirety) It can be assumed that the VAL server is not initially aware of the API exposure capabilities and information for the given slice based on the Service Level Agreement (SLA), and NSCE can assist in configuring and translating a slice API based on the per slice requirements to service APIs. Further, clause 9.3 of 3GPP TS 23.435 lists two procedures on slice API configuration and one procedure on slice API translation.

[0063] With reference to initial configuration procedures for slice API configuration, a VAL server can initially provide an application parameter to enabler server including the service Key Performance Indicators (KPIs) and the subscribed/preferred slices. The slice enabler can then configure the mapping of the VAL application to a slice API which can be a combination and/or bundling of northbound APIs, such as from both management and control plane. A slice API can include telco-provided and/or platform dependent service APIs (e.g., Network Exposure Function (NEF), Operations, Administration and Management/Maintenance (OAM), Service Enabler Architecture Layer for Verticals (SEAL), etc.), and can provide an abstraction and/or simplification of the service APIs.

[0064] FIG. 2 illustrates an example signaling diagram **200** for initial slice API configuration. The signaling diagram **200**, for instance, is based on FIG. 9.3.2.1.2-1 in 3GPP TS 23.435. In the signaling diagram **200**: (1) The VAL server sends a VAL application requirement request to the NSCE server; (2) The NSCE server maps the VAL application requirement to a slice API which includes a list of APIs which is to be consumed as part of this service capability exposure. The NSCE server may also store the mapping of the slice API to the service API list and per service API information (e.g. data encoding, transport technology, API protocol and versions); (3) The NSCE server registers to consume the corresponding APIs from the 5GS (NEF and OAM) and SEAL service producers. The NSCE server registers to the following: to consume NEF monitoring events as specified in 3GPP TS 29.522 clause 5 e.g., network monitoring, slice status, analytics exposure, etc.; to consume Performance Monitoring (PM) services and KPI monitoring from OAM (see 3GPP TS 29.522, Release 18, Version 18.4.0, Dec. 18, 2023, titled “5G System; Network Exposure Function Northbound APIs; Stage 3,” hereinafter referred to as “3GPP TS 29.522”, which is hereby incorporated by reference herein in its entirety); to consume SEAL services based on 3GPP TS 23.434 (see 3GPP TS 23.434, Release 18, Version 18.7.0, Jan. 5, 2024, titled “Service Enabler Architecture Layer for Verticals (SEAL); Functional architecture and information flows,” hereinafter referred to as “3GPP TS 23.434”, which is hereby incorporated by reference herein in its entirety); (4) The NSCE server sends a VAL application requirement response to notify on the result of the request and indicate whether the configuration of slice API is possible or not; and (5)

The NSCE server sends the slice API information notification to the VAL server.

[0065] Regarding configuration updates procedures, a VAL server-initiated configuration update procedure can cover a scenario where a trigger event occurs (e.g., QoS degradation, slice load) and the mapping configuration or the slice API configuration are to be changed. In such scenarios, a slice enabler updates the configuration of the API and provides a notification to the VAL server.

[0066] FIG. 3 illustrates an example signaling diagram 300 for slice API configuration update based on a trigger event. The signaling diagram 300, for instance, is based on FIG. 9.3.2.1.3-1 in 3GPP TS 23.435. In the signaling diagram 300: (1) The VAL server sends a VAL server-initiated configuration update request to the NSCE server; (2) The NSCE server processes the trigger event and checks the feasibility of such change and updates the mapping of service APIs to the slice APIs. One criterion for the update of the mapping is to avoid changing the slice API configuration, which can be achieved by the re-mapping of the underlying service APIs; (3) The NSCE server updates the subscription/registration to the underlying 5GS and SEAL service producers, if an update on the service APIs (e.g., NEF APIs, SEAL APIs, OAM provided APIs) is to be performed; and (4) The NSCE server sends a VAL server-initiated configuration update response, including the new slice API information, if an update has been carried out by the NSCE server.

[0067] FIG. 4 illustrates an example signaling diagram 400 for slice API translation based on an initial configuration. The signaling diagram 400, for instance, is based on FIG. 9.3.2.2-1 in 3GPP TS 23.435. The signaling diagram 400 describes how a slice API invocation request is translated to service API invocations after the slice API configuration mapping. In the signaling diagram 400, for instance, the NSCE server initially receives a slice API invocation request from the vertical application. Then, the NSCE server fetches the service APIs to be invoked based on the slice API configuration and performs invocation requests to the corresponding service API providers.

[0068] In the signaling diagram 400: (1) The VAL server sends a slice API invocation request to the NSCE server; (2) The NSCE server checks that the user is authenticated and authorized to perform the slice API invocation and maps the requested slice API to a service APIs. If Common API Framework (CAPIF) is used, the NSCE server acts as API Exposing Function (AEF), and the authorization is obtained by CAPIF Core Function (CCF); (3) The NSCE server generates a trigger for service API invocation requests to the service APIs within the slice API; (4) The NSCE server performs the corresponding service API invocation procedures based on CAPIF or via performing requests to the corresponding service API providers, which are mapped to the slice API.

[0069] If CAPIF is used, the requests are sent to the corresponding AEFs of the API provider's domain, and the authorization is obtained by CCF; and (5) The NSCE server sends a slice API invocation response to the VAL server, based on the result of the service API invocation response(s) of step 4.

[0070] Accordingly, the present disclosure provides solutions for different slice API-related services including API configuration, API update, and API invocation.

[0071] Regarding slice API configuration, implementations provide a slice API configuration service that can be exposed by an NSCE server. For instance, a NSCE\_SliceApiConfiguration service can represent an extension of clause 9.3 of 3GPP TS 23.435. The slice API configuration service can provide various functionality including enabling a service consumer to request to map a VAL application parameter to a slice API for initial slice API configuration, request to update a slice API configuration, and notify the service consumer of an updated slice API configuration.

[0072] Table 1 below provides examples operations defined for a slice API configuration service.

TABLE-US-00001 TABLE 1 Service Operations for a Slice Configuration Service

Operation Name	Description	Initiated by
Val_Application_Requirement	This service operation is VAL Server used to map the VAL application requirement to a slice API as a part of a service API list.	Val
Val_Configuration_Update	This service operation is VAL Server used to update the slice API configuration.	Val
Slice_Api_Notify	This service operation is NSCE used to provide Server information about the initial or the updated configured slice API.	NSCE

[0073] Regarding the service operation Val\_Application\_Requirement, this service operation can be used by the VAL server to provide the NSCE Server with the VAL application parameter which is to be mapped to a slice API as a part of a service API list. The service API list is used to expose the 5GS/SEAL services by the applications associated to the slice. Upon success or failure of the slice API initial configuration, the NSCE Server can inform the VAL server about the status.

[0074] Implementations can request to map a VAL application requirement to a slice API by using Val\_Application\_Requirement. To configure a slice API with the VAL application requirement, the VAL Server can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nsce-sac/<apiVersion>/reqt” and with a body including data type ReqReq, such as defined in clause 5.2.6.2.2.

[0075] Upon receipt of the HTTP POST request, the NSCE Server can (1) verify the identity of the VAL server and determine if the VAL server is authorized to request for the slice API initial configuration; and (2) if the VAL server (a) is not authorized, the NSCE Server can respond to the VAL server with an appropriate error status code; or (b) the VAL server is authorized, the NSCE Server: (i) can map the VAL application requirement to a slice API which includes a list of APIs, consumed as part of the service capability exposure; and (ii) may store the mapped slice API to the service API list per service API information, and respond to the VAL server with an HTTP “200 OK” status code, with the response body including the ReqRes data structure (e.g., as defined in clause 5.2.6.2.3) including the result of the slice API configuration and a configuration error.

[0076] Regarding the service operation Val\_Configuration\_Update, this service operation can be used by the VAL server to request the NSCE server to update the slice API configuration. To request to update a slice API configuration by using Val\_Configuration\_Update, the VAL Server can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nsce-sac/<apiVersion>/UpdReq” and with a body including data type UpdReq, such as defined in clause 5.2.6.2.4. Upon receipt of the HTTP POST request, the NSCE Server can (1) verify the identity of the VAL server and determine if the VAL server is authorized to update the slice API configuration; and (2) if the VAL server: (a) is not authorized, the NSCE Server can respond to the VAL server with an appropriate error status code; or (b) if the VAL server is authorized, the NSCE Server can: (i) update the mapping of service APIs to the slice API; and (ii) update the subscription or registration to the underlying service, and respond to the VAL server with an HTTP “200 OK” status code, with the response body including the UpdRes data structure (e.g., as defined in clause 5.2.6.2.5) including the result of the updated slice API configuration and the updated slice API information and/or a configuration error.

[0077] Regarding the service operation Slice\_Api\_Notify, this service operation can be used by the NSCE server to notify the VAL server with information of the initial slice API configuration and/or the updated slice API configuration. For instance, to notify with information about a slice API configuration by using Slice\_Api\_Notify, the NSCE Server can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nsce-sac/<apiVersion>/apiInfo” and with a body including data type ApiInfo, such as defined in clause 5.2.6.2.6. Upon receipt of the HTTP POST request, the VAL Server can respond to NSCE Server with: (1) if the request is successfully processed, a “204 No Content” status code and process the event notification; or (2) if errors occur when processing the request, an appropriate error response, such as specified in clause 5.2.7.

[0078] According to implementations a slice API configuration service can use a slice API configuration API. For instance, an NSCE\_SliceApiConfiguration service can use a NSCE\_SliceApiConfiguration API. In such implementations the request URIs used in HTTP requests from the VAL server towards the NSCE server can have a Resource URI structure (e.g., as defined in clause 5.2.4 of 3GPP TS 29.122) with the following clarifications: [0079] The <apiName> can be “nsce-sac”. [0080] The <apiVersion> can be “v1”. [0081] The <apiSpecificSuffixes> can be set as described in clause 5.2.4.

[0082] (Sec 3GPP TS 29.122, Release 18, Version 18.4.0, Dec. 18, 2024, titled “T8 reference point

for Northbound APIs,” hereinafter referred to as “3GPP TS 29.122”, which is hereby incorporated by reference herein in its entirety). Regarding usage of HTTP and common API related aspects, the provisions of clause 5.2 of 3GPP TS 29.122 can apply for the NSCE\_SliceApiConfiguration API. The following discussion provides example details for structures for resource URIs and the resources and methods that can be used for a slice API configuration API.

[0083] FIG. 5 illustrates an example resource URI structure 500 in accordance with aspects of the present disclosure. The resource URI structure 500, for instance, represents a resource URI structure of an NSCE\_SliceApiConfiguration API.

[0084] Table 2 below provides an overview of resources and HTTP methods for a slice API configuration API.

TABLE-US-00002 TABLE 2 Resources and Methods Overview HTTP method or Resource name  
Resource URI custom operation Description Slice API /apiInfo POST Provides the slice information API information notification.

[0085] A slice API information resource can be used for a NSCE server to notify a VAL server about the slice API information. An example Resource URI is: [0086] {apiRoot}/nsce-sac/<apiVersion>/apiInfo

[0087] A slice API information resource can support resource URI variables such as defined in Table 3, below.

TABLE-US-00003 TABLE 3 Resource URI Variables Name Data Type Definition apiRoot string  
See clause 5.2.3

[0088] A slice API information resource can utilize a POST method which can enable a NSCE server to notify a VAL server with slice API information. This method can support the URI query parameters specified in Table 4, below.

TABLE-US-00004 TABLE 4 URI query parameters supported by the POST method on the Slice API Information Resource Name Data type P Cardinality Description

[0089] The POST method can support the request data structures specified in Table 5 and the response data structures and response codes specified in Table 6, below.

TABLE-US-00005 TABLE 5 Data structures supported by the POST Request Body on the Slice API Information Resource Data type P Cardinality Description SApiInfo M 1 Notification on slice API information in: initial configuration procedure; or configuration update procedure.

TABLE-US-00006 TABLE 6 Data structures supported by the POST Response Body on this resource Data type P Cardinality Response codes Description n/a 204 No Content Notification for the slice API information is accepted. NOTE: The HTTP error status codes for the HTTP POST method listed in table 5.2.6-1 of 3GPP TS 29.122 may apply.

[0090] Implementations also support custom operations without associated resources, such as described in Table 7, below.

TABLE-US-00007 TABLE 7 Custom operations without associated resources Mapped Custom Custom HTTP operation name operation URI method Description Requirement /Reqt POST Provides VAL application requirements which are to be mapped to a slice API as a part of a service API list Updated /UpdReqt POST Requests for an update of requirement the slice API configuration.

[0091] The Requirement operation can be used by the VAL server to provide the NSCE server with the VAL application requirement which is to be mapped by the NSCE server to a slice API as a part of a service API list.

[0092] The Requirement operation can support the request data structures specified in Table 8 and the response data structures and response codes specified in Table 9, below.

TABLE-US-00008 TABLE 8 Data structures supported by the POST Request Body Data type P Cardinality Description ReqtReq M 1 Provides requirement which is to be mapped to a slice API as a part of a slice API list.

TABLE-US-00009 TABLE 9 Data structures supported by the POST Response Body Response

Data type P Cardinality codes Description ReqReq M 1 200 OK The network slice adaptation request is successfully received and processed. NOTE: The mandatory HTTP error status codes for the HTTP POST method listed in table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0093] The custom operation Updated requirement can be used by the VAL server to request the NSCE server an update of the slice API configuration. This custom operation can support the request data structures specified in Table 10 the response data structures and response codes specified in Table 11, below.

TABLE-US-00010 TABLE 10 Data structures supported by the POST Request Body Data type P Cardinality Description UpdReq M 1 Requests an update of the slice API configuration

TABLE-US-00011 TABLE 11 Data structures supported by the POST Response Body Response Data type P Cardinality codes Description UpdRes M 1 200 OK Whether the result of the update of the slice API configuration was successful or not. NOTE: The mandatory HTTP error status codes for the HTTP POST method listed in table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0094] The following discusses aspects of an application data model supported by the slice configuration API for instance, Table 12 specifies the data types defined for the NSCE\_SliceApiConfiguration API.

TABLE-US-00012 TABLE 12 NSCE\_SliceApiConfiguration API specific Data Types Clause Data type defined Description Applicability AccToken 5.2.6.2.9 Indicates access token standard claims, specified in 3GPP TS 33.122.

[0095] Table 13 specifies data types re-used by the NSCE\_SliceApiConfiguration API from other specifications, including a reference to their respective specifications and optionally, a short description of their use within the NSCE\_SliceApiConfiguration API.

TABLE-US-00013 TABLE 13 NSCE\_SliceApiConfiguration API re-used Data Types Data type Reference Comments Applicability NetSliceId 3GPP TS 29.435 Identifies the Single Network Slice Selection Assistance Information (S-NSSAI) TimeWindow 3GPP TS 29.122 A time window.

[0096] The following provides a discussion of structures that can be used in resource representations. For instance, Table 14 provides a definition of the type ReqReq.

TABLE-US-00014 TABLE 14 Definition of type ReqReq Attribute name Data type P Cardinality Description Applicability srvReqs array M 1 . . . N VAL application requirements (ValSrvReq) pertaining to one or more slices. timeValidity TimeWindow O 0 . . . 1 The time validity of the request.

[0097] Note: Data type ValSrvReq is according to table 9.1.1.2-1 of 3GPP TS 23.435.

[0098] Table 15 provides a definition of the type ReqRes.

TABLE-US-00015 TABLE 15 Definition of type ReqRes Attribute name Data type P Cardinality Description Applicability confRslt boolean M 1 Indicates on the result of the request for VAL application requirement that the slice API configuration: if set to “1”, is possible; or if set to “0”, is not possible. confErr ConfErr O 0 . . . 1 Indicates the reason for the configuration error.

[0099] Table 16 provides a definition of the type UpdReq.

TABLE-US-00016 TABLE 16 Definition of type UpdReq Attribute name Data type P Cardinality Description Applicability trigEvt TrigEvt M 1 Indicates trigger event causing an indication for slice API configuration update. netSliceId NetSliceId O 0 . . . 1 Identifier of the network slice for which the API configuration is requested.

[0100] Table 17 provides a definition of the type UpdRes.

TABLE-US-00017 TABLE 17 Definition of type UpdRes Attribute name Data type P Cardinality Description Applicability confUpdRslt boolean M 1 Indicates on the result of the request for update the slice API configuration: if set to “1”, is updated; or if set to “0”, is not updated. slApiInfoUpd SlApiInfo M 1 Indicates the updated slice API information if the slice API configuration is updated. confErr ConfErr O 0 . . . 1 Indicates the reason for the configuration update error if the slice API configuration is not updated.

[0101] Table 18 provides a definition of the type ApiInfo.

TABLE-US-00018 TABLE 18 Definition of type ApiInfo Attribute name Data type P Cardinality  
Description Applicability slApiInfo SlApiInfo M 1 Indicates the slice API information  
[0102] For the slice configuration API (e.g., NSCE\_SliceApiConfiguration API), HTTP error responses can be supported as specified in clause 5.2.6 of 3GPP TS 29.122. Protocol errors and application errors specified in clause 5.2.6 of 3GPP TS 29.122 can be supported for the HTTP status codes specified in table 5.2.6-1 of 3GPP TS 29.122.  
[0103] Further, the requirements in the following clauses are applicable for the slice configuration API.  
[0104] Application Errors: Example application errors defined for the slice configuration API are listed in Table 19.

TABLE-US-00019 TABLE 19 Application errors Application Error HTTP status code Description Applicability

[0105] Table 20 lists example supported features for feature negotiation.

TABLE-US-00020 TABLE 20 Supported Features Feature number Feature Name Description  
[0106] Regarding security the provisions of clause 6 of 3GPP TS 29.122 can apply for the slice configuration API.  
[0107] The following presents example YAML code for a slice API configuration API, e.g., NSCE\_SliceApiConfiguration API.

TABLE-US-00021

```
openapi: 3.0.0 info: title: NSCE_SliceApiConfiguration version: 1.0.0-alpha.1 description: | NSCE Server Slice API Configuration Service. © <2024>, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC). All rights reserved. externalDocs: description: > 3GPP TS 29.435 V0.2.0; Service Enabler Architecture Layer for Verticals (SEAL); NSCE Server Services; Stage 3. url: http://www.3gpp.org/ftp/Specs/archive/29_series/29.435/ servers: - url: '{apiRoot}/nsce-sac/v1' variables: apiRoot: default: https://example.com description: apiRoot as defined in clause 6.5 of 3GPP TS 29.549 security: - { } - oAuth2ClientCredentials: [ ] paths: /Req: post: summary: Slice API configuration maps VAL application to a slice API of service APIs. operationId: SliceAPIConfiguration tags: - Slice API configuration requestBody: required: true content: application/json: schema: $ref: '#/components/schemas/ReqReq' responses: '200': description: > The slice API configuration request has been successfully received and processed and the result of the requested slice API configuration is in the response body. content: application/json: schema: type: array items: $ref: '#/components/schemas/ReqRes' minItems: 1 '307': $ref: 'TS29122_CommonData.yaml#/components/responses/307' '308': $ref: 'TS29122_CommonData.yaml#/components/responses/308' '400': $ref: 'TS29122_CommonData.yaml#/components/responses/400' '401': $ref: 'TS29122_CommonData.yaml#/components/responses/401' '403': $ref: 'TS29122_CommonData.yaml#/components/responses/403' '404': $ref: 'TS29122_CommonData.yaml#/components/responses/404' '411': $ref: 'TS29122_CommonData.yaml#/components/responses/411' '413': $ref: 'TS29122_CommonData.yaml#/components/responses/413' '415': $ref: 'TS29122_CommonData.yaml#/components/responses/415' '429': $ref: 'TS29122_CommonData.yaml#/components/responses/429' '500': $ref: 'TS29122_CommonData.yaml#/components/responses/500' '503': $ref: 'TS29122_CommonData.yaml#/components/responses/503' default: $ref: 'TS29122_CommonData.yaml#/components/responses/default' /UpdReq: post: summary: Update the slice API configuration of the mapping the slice configuration. operationId: UpdateSliceAPIConfiguration tags: -
```

```

Update slice API configuration requestBody: required: true content:
  application/json: schema: $ref:
'#/components/schemas/UpdReq' responses: '200': description: >
  Update for the slice API configuration request has been successfully received and
  processed and the result of the requested update for the slice API configuration
  is in the response body. content: application/json:
    schema: type: array items:
      $ref: '#/components/schemas/UpdRes' minItems: 1
    '307': $ref: 'TS29122_CommonData.yaml#/components/responses/307'
    '308': $ref: 'TS29122_CommonData.yaml#/components/responses/308'
    '400': $ref: 'TS29122_CommonData.yaml#/components/responses/400'
    '401': $ref: 'TS29122_CommonData.yaml#/components/responses/401'
    '403': $ref: 'TS29122_CommonData.yaml#/components/responses/403'
    '404': $ref: 'TS29122_CommonData.yaml#/components/responses/404'
    '411': $ref: 'TS29122_CommonData.yaml#/components/responses/411'
    '413': $ref: 'TS29122_CommonData.yaml#/components/responses/413'
    '415': $ref: 'TS29122_CommonData.yaml#/components/responses/415'
    '429': $ref: 'TS29122_CommonData.yaml#/components/responses/429'
    '500': $ref: 'TS29122_CommonData.yaml#/components/responses/500'
    '503': $ref: 'TS29122_CommonData.yaml#/components/responses/503'
    default: $ref: 'TS29122_CommonData.yaml#/components/responses/default'
/apiInfo: post: summary: Notifies with slice API information. operationId:
SliceAPIInfoNotification tags: - Slice API information notification
requestBody: required: true content: application/json:
  schema: $ref: '#/components/schemas/SlApiInfo'
responses: '204': description: No Content, Notification was succesfull
    '307': $ref: 'TS29122_CommonData.yaml#/components/responses/307'
    '308': $ref: 'TS29122_CommonData.yaml#/components/responses/308'
    '400': $ref: 'TS29122_CommonData.yaml#/components/responses/400'
    '401': $ref: 'TS29122_CommonData.yaml#/components/responses/401'
    '403': $ref: 'TS29122_CommonData.yaml#/components/responses/403'
    '404': $ref: 'TS29122_CommonData.yaml#/components/responses/404'
    '411': $ref: 'TS29122_CommonData.yaml#/components/responses/411'
    '413': $ref: 'TS29122_CommonData.yaml#/components/responses/413'
    '415': $ref: 'TS29122_CommonData.yaml#/components/responses/415'
    '429': $ref: 'TS29122_CommonData.yaml#/components/responses/429'
    '500': $ref: 'TS29122_CommonData.yaml#/components/responses/500'
    '503': $ref: 'TS29122_CommonData.yaml#/components/responses/503'
    default: $ref: 'TS29122_CommonData.yaml#/components/responses/default'
components: securitySchemes: oAuth2ClientCredentials: type: oauth2 flows:
  clientCredentials: tokenUrl: '{tokenUrl}' scopes: { }
schemas: # # STRUCTURED DATA TYPES # ReqtReq: description: >
Represents the slice API configuration request. type: object properties:
srvReqs: type: array items: $ref:
'#/components/schemas/ValSrvReq' minItems: 1 timeValidity:
$ref: 'TS29122_CommonData.yaml#/components/schemas/TimeWindow' required:
- srvReqs Note: Data type ValSrvReq is according to table 9.1.1.2-1 of 3GPP TS
23.435. ReqtRes: description: > Represents result of the successfully
processed slice API configuration. type: object properties: confRlt:
  type: boolean confErr: $ref: '#/components/schemas/ConfErr'

```



required:	- confRlt	Note: Data type can include failure in 5GS/SEAL or other
(e.g. server internal error).	UpdReq:	description: >
configuration update request.	type: object	properties:
\$ref: '#/components/schemas/TrigEvt'		trigEvt:
'TS29435_NSCE_PolicyManagement.yaml#/components/schemas/NetSliceId'		\$ref:
- trigEvt	UpdRes:	required:
	description: >	Represents result of the
successfully processed slice API configuration update.	type: object	properties:
confUpdRslt:	type: boolean	slApiInfoUpd:
'#/components/schemas/SlApiInfo'	confErr:	\$ref:
'#/components/schemas/ConfErr'	required:	- confUpdRlt
slApiInfoUpd	Note: Data type ConfErr can include no change was needed, failure of changing in	
5GS/SEAL, or other (e.g. server	internal error).	ApiInfo:
Represents the slice notification information.	type: object	description: >
slApiInfo:	\$ref: '#/components/schemas/SlApiInfo'	properties:
- slApiInfo		required:

[0108] Regarding slice API invocation, the present disclosure provides a slice API invocation service (e.g., NSCE\_SliceApiInvocation service) that enables a service consumer to request a slice API invocation. The slice invocation service (e.g., corresponding to clause 9.3 of 3GPP TS 23.435) can be exposed by the NSCE server.

[0109] Table 21 includes examples of service operations defined for a slice API invocation service. TABLE-US-00022

TABLE 21	NSCE_SliceApiInvocation	Service Operations
Service Operation	Name	Description
Initiated by Slice_Api_Invocation	This service operation is used	VAL Server for slice API invocation.

[0110] The Slice\_Api\_Invocation service operation can be used by the VAL Server to request the NSCE Server for the slice API invocation to be further translated to the service API invocation. To request the slice API invocation, the VAL Server can send an HTTP POST request with a Request-URI (e.g., according to the pattern "{apiRoot}/nsce-sai/<apiVersion>/ApiInvoc") and with a body including data type InvocReq such as defined in clause 5.2.6.2.2.

[0111] Upon receipt of the HTTP POST request, the NSCE Server can: (1) verify the identity of the VAL server and determine if the VAL Server is authorized to request the slice API invocation; and (2) if the VAL server: (a) is not authorized, the NSCE Server can respond to the VAL server with an appropriate error status code; or (b) if the VAL server is authorized, the NSCE Server can: (i) map the requested slice API for invocation to the service APIs for the further translation to the service API invocations; and (ii) perform corresponding service API invocation procedures, and respond to the VAL Server with an HTTP "200 OK" status code, with the response body including the InvocRes data structure including the result of the slice API invocation and/or configuration error.

[0112] Implementations provide a slice API invocation API, e.g., NSCE\_SliceApiInvocation API. For the slice API invocation API, the request URIs used in HTTP requests from the VAL server towards the NSCE server can have a Resource URI structure (e.g., as defined in clause 5.2.4 of 3GPP TS 29.122) with the following clarifications: [0113] The <apiName> can be "nsce-sai".

[0114] The <apiVersion> can be "v1". [0115] The <apiSpecificSuffixes> can be set as described in clause 5.2.4.

[0116] For usage of HTTP and common API-related aspects the provisions of clause 5.2 of 3GPP TS 29.122 can apply for the slice API invocation API.

[0117] FIG. 6 illustrates an example resource URI structure 600 in accordance with aspects of the present disclosure. The resource URI structure 600, for instance, represents a custom operations URI structure of an NSCE\_SliceApiInvocation API.

[0118] Table 22 illustrates example custom operations associated with a slice API invocation API without associated resources.

TABLE-US-00023

TABLE 22	Custom operations without associated resources
Custom	Custom

Mapped operation operation HTTP name URI method Description ApiInvoc /ApiInvoc POST  
Requests for a slice API invocation.

[0119] The custom operation ApiInvoc can be used by the VAL server to request the NSCE server for slice API invocation.

[0120] This custom operation ApiInvoc can support the request data structures specified in Table 23 the response data structures and response codes specified in Table 24.

TABLE-US-00024 TABLE 23 Data structures supported by the POST Request Body Data type P Cardinality Description InvocReq M 1 Requests slice API invocation

TABLE-US-00025 TABLE 24 Data structures supported by the POST Response Body Response Data type P Cardinality codes Description InvocRes M 1 200 OK Whether the result of the slice API invocation was successful or not. NOTE: The mandatory HTTP error status codes for the HTTP POST method listed in table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0121] The following discusses an application data model supported by the slice API invocation API. For instance, Table 25 specifies data types defined for the NSCE\_SliceApiInvocation API.

TABLE-US-00026 TABLE 25 NSCE\_SliceApiInvocation API specific Data Types Clause Data type defined Description Applicability AccToken 5.2.6.2.4 Indicates access token standard claims, specified in 3GPP TS 33.122.

[0122] Table 26 specifies data types re-used by the NSCE\_SliceApiInvocation API from other specifications, including a reference to their respective specifications and a short description of their use within the NSCE\_SliceApiInvocation API.

TABLE-US-00027 TABLE 26 NSCE\_SliceApiInvocation API re-used Data Types Data type Reference Comments Applicability NetSliceId 3GPP TS 29.435 Identifies the S-NSSAI.

[0123] The following discusses structured data types to be used in resource representations. For instance, Table 27 illustrates example definitions of the data type InvocReq, Table 28 illustrates example definitions of the data type InvocRes, and Table 29 illustrates example definitions of the data type AccToken.

TABLE-US-00028 TABLE 27 Definition of type InvocReq Attribute name Data type P Cardinality Description Applicability netsliceId NetSliceId M 1 Identifier of the network slice for which the API invocation is requested. authInfo AccToken O 0 . . . 1 Authorization information to request for the slice API invocation.

TABLE-US-00029 TABLE 28 Definition of type InvocRes Attribute name Data type P Cardinality Description Applicability invocRslt boolean M 1 Indicates on the result of the request for slice API invocation that the slice API invocation: if set to “1”, is performed; or if set to “0”, is not performed. invocErr InvocErr O 0 . . . 1 Indicates the reason for the slice API invocation failure, if it fails.

TABLE-US-00030 TABLE 29 Definition of type AccToken Attribute name Data type P Cardinality Description Applicability timeValidity TimeWindow M 1 Indicates the validity time. srvList array(string) M 1 Indicates the list of services the access token is valid.

[0124] Regarding error handling for the NSCE\_SliceApiInvocation API, HTTP error responses can be supported as specified in clause 5.2.6 of 3GPP TS 29.122. Protocol errors and application errors specified in clause 5.2.6 of 3GPP TS 29.122 can be supported for the HTTP status codes specified in table 5.2.6-1 of 3GPP TS 29.122. Further, the requirements in the following clauses can be applicable for the NSCE\_SliceApiInvocation API.

[0125] Application errors defined for the NSCE\_SliceApiInvocation API are listed in Table 30 and Table 31 lists supported features for feature negotiation.

TABLE-US-00031 TABLE 30 Application errors Application Error HTTP status code Description Applicability

TABLE-US-00032 TABLE 31 Supported Features Feature number Feature Name Description

[0126] Regarding security, the provisions of clause 6 of 3GPP TS 29.122 can apply for the NSCE\_SliceApiInvocation API.

[0127] The following presents example YAML code for a slice invocation API, e.g., NSCE\_SliceApiInvocation API.

```

TABLE-US-00033 openapi: 3.0.0 info:   title: NSCE_SliceApiInvocation   version: 1.0.0-alpha.1
  description: |     NSCE Server Slice API Invocation Service.     © <2024>, 3GPP
Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).     All rights reserved.
externalDocs:   description: >     3GPP TS 29.435 V0.2.0; Service Enabler Architecture Layer
for Verticals (SEAL);     NSCE Server Services; Stage 3.   url:
http://www.3gpp.org/ftp/Specs/archive/29_series/29.435/ servers:   - url: '{apiRoot}/nsce-sai/v1'
  variables:     apiRoot:     default: https://example.com     description:
apiRoot as defined in clause 6.5 of 3GPP TS 29.549 security:   - { }   - oAuth2ClientCredentials:
[ ] paths:   /ApiInvoc:     post:     summary: Slice API invocation to invoke service APIs
based on the slice API configuration.     operationId: SliceAPIInvocation     tags:
- Slice API invocation     requestBody:     required: true     content:
  application/json:     schema:     $ref:
'#/components/schemas/InvocReq'     responses:     '200':     description: >
    The slice API invocation request has been successfully received and processed
    and the result of the requested slice API invocation is in the response body.
  content:     application/json:     schema:
type: array     items:     $ref:
'#/components/schemas/InvocRes'     minItems: 1     '307':
$ref: 'TS29122_CommonData.yaml#/components/responses/307'     '308':
$ref: 'TS29122_CommonData.yaml#/components/responses/308'     '400':
$ref: 'TS29122_CommonData.yaml#/components/responses/400'     '401':
$ref: 'TS29122_CommonData.yaml#/components/responses/401'     '403':
$ref: 'TS29122_CommonData.yaml#/components/responses/403'     '404':
$ref: 'TS29122_CommonData.yaml#/components/responses/404'     '411':
$ref: 'TS29122_CommonData.yaml#/components/responses/411'     '413':
$ref: 'TS29122_CommonData.yaml#/components/responses/413'     '415':
$ref: 'TS29122_CommonData.yaml#/components/responses/415'     '429':
$ref: 'TS29122_CommonData.yaml#/components/responses/429'     '500':
$ref: 'TS29122_CommonData.yaml#/components/responses/500'     '503':
$ref: 'TS29122_CommonData.yaml#/components/responses/503'     default:
$ref: 'TS29122_CommonData.yaml#/components/responses/default' components:
securitySchemes:   oAuth2ClientCredentials:     type: oauth2     flows:
clientCredentials:     tokenUrl: '{tokenUrl}'     scopes: { }     schemas: # #
STRUCTURED DATA TYPES #   InvocReq:     description: >     Represents the
slice API invocation request.     type: object     properties:     netSliceId:
    $ref: 'TS29435_NSCE_PolicyManagement.yaml#/components/schemas/NetSliceId'
  authInfo:     $ref: '#/components/schemas/AccToken'     required:
- netSliceId   InvocRes:     description: >     Represents result of the
successfully processed slice API invocation request.     type: object     properties:
  invocRslt:     type: boolean     invocErr:     $ref:
'#/components/schemas/InvocErr'     required:     - invocRslt   AccToken:
description: >     Represents the authorization token for services.     type: object
  properties:     timeValidity:     $ref:
'TS29122_CommonData.yaml#/components/schemas/TimeWindow'     srvList:
    type: array     items:     type: string     minItems: 1
    description: List of service identifiers.     required:     - timeValidity
- srvList:

```

[0128] The present disclosure also provides an integrated API for slice configuration and slice

invocation (e.g., translation), which in some implementations can be referred to as a NSCE\_SliceApiManagement API. For instance, a slice API management service can be exposed by an NSCE server and can enable a service consumer to request to map a VAL application requirement to a slice API for initial slice API configuration, request to update a slice API configuration, request for a slice API invocation, and notify the service consumer of an updated slice API configuration.

[0129] Regarding service operations for a slice API management service, Table 32 lists example service operations defined for the NSCE\_SliceApiManagement service.

TABLE-US-00034 TABLE 32 NSCE\_SliceApiManagement Service Operations

Service Operation Name	Description	Initiated by
Val_Application_Requirement	This service operation is used to map the VAL Server VAL application requirement to a slice API as a part of a service API list.	Val_Application_Requirement
Val_Configuration_Update	This service operation is used to update the VAL Server slice API configuration.	Val_Configuration_Update
Slice_Api_Notify	This service operation is used to provide NSCE Server information about the initial or the updated configured slice API.	Slice_Api_Notify
Slice_Api_Invocation	This service operation is used for slice API VAL Server invocation.	Slice_Api_Invocation

Val\_Configuration\_Update This service operation is used to update the VAL Server slice API configuration. Slice\_Api\_Notify This service operation is used to provide NSCE Server information about the initial or the updated configured slice API. Slice\_Api\_Invocation This service operation is used for slice API VAL Server invocation.

[0130] The following discusses aspects of the example service operations of the NSCE\_SliceApiManagement service.

[0131] The Val\_Application\_Requirement can be used by the VAL server to provide the NSCE Server the VAL application requirement which is to be mapped to a slice API as a part of a service API list. The service API list is used to expose the 5GS/SEAL services by the applications associated to the slice. Upon success or failure of the slice API initial configuration, the NSCE Server can inform the VAL server about the status.

[0132] To configure the slice API with the VAL application requirement, the VAL Server can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nsce-sam/<apiVersion>/ReqReq” and with a body including data type ReqReq.

[0133] Upon receipt of the HTTP POST request, the NSCE Server can: (1) verify the identity of the VAL server and determine if the VAL server is authorized to request for the slice API initial configuration; and (2) if the VAL server: (a) is not authorized, the NSCE Server can respond to the VAL server with an appropriate error status code; or (b) if the VAL server is authorized, the NSCE Server: (i) can map the VAL application requirement to a slice API which includes a list of APIs, consumed as part of the service capability exposure; and (ii) may store the mapped slice API to the service API list per service API information, and respond to the VAL server with an HTTP “200 OK” status code, with the response body including a ReqRes data structure as defined herein, including the result of the slice API configuration and/or a possible configuration error.

[0134] The Val\_Configuration\_Update service operation can be used by the VAL server to request the NSCE server to update the slice API configuration. For instance, to update the slice API configuration, the VAL Server can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nsce-sam/<apiVersion>/UpdReq” and with a body including data type UpdReq. Upon receipt of the HTTP POST request, the NSCE Server can: (1) verify the identity of the VAL server and determine if the VAL server is authorized to update the slice API configuration; and (2) if the VAL server: (a) is not authorized, the NSCE Server can respond to the VAL server with an appropriate error status code; or (b) is authorized, the NSCE Server, if feasible, can: (i) update the mapping of service APIs to the slice API; and (ii) update the subscription or registration to the underlying service, and respond to the VAL server with an HTTP “200 OK” status code, with the response body including the UpdRes data structure such as defined herein, including the result of the updated slice API configuration and the updated slice API information and/or a possible configuration error.

[0135] The Slice\_Api\_Notify service operation can be used by the NSCE server to notify the VAL server with information of the initial slice API configuration or the updated slice API configuration. To notify the VAL server with the information about the slice API configuration, the NSCE Server

can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nsce-sam/<apiVersion>/apiInfo” and with a body including data type ApiInfo such as defined herein. Upon receipt of the HTTP POST request, the VAL Server can respond to NSCE Server can: (1) if the request is successfully processed, a “204 No Content” status code and process the event notification; or (2) if errors occur when processing the request, an appropriate error response such as specified herein.

[0136] The Slice\_Api\_Invocation service operation can be used by the VAL Server to request the NSCE Server for the slice API invocation and further translation to the service API invocation. To request the slice API invocation, the VAL Server can send an HTTP POST request with a Request-URI according to the pattern “{apiRoot}/nscc-sam/<apiVersion>/ApiInvoc” and with a body including data type InvocReq such as defined herein. Upon receipt of the HTTP POST request, the NSCE Server can: (1) verify the identity of the VAL server and determine if the VAL Server is authorized to request the slice API invocation; and (2) if the VAL server: (a) is not authorized, the NSCE Server can respond to the VAL server with an appropriate error status code; or (b) if the VAL server is authorized, the NSCE Server, can: (i) map the requested slice API for invocation to the service APIs for the further translation to the service API invocations; and (ii) perform the corresponding service API invocation procedures, and respond to the VAL Server with an HTTP “200 OK” status code, with the response body including the InvocRes data structure as defined herein including the result of the slice API invocation and/or a possible configuration error.

[0137] According to implementations a slice API management service can a slice API management API. For instance, the NSCE\_SliceApiManagement service can use the NSCE\_SliceApiManagement API. In implementations the request URIs used in HTTP requests from the VAL server towards the NSCE server can use the Resource URI structure as defined in clause 5.2.4 of 3GPP TS 29.122 with the following clarifications: [0138] The <apiName> can be “nsce-sam”. [0139] The <apiVersion> can be “v1”. [0140] The <apiSpecificSuffixes> can be set as described in clause 5.3.3.

[0141] Regarding usage of HTTP and common API related aspects, the provisions of clause 5.2 of 3GPP TS 29.122 can apply for the NSCE\_SliceApiManagement API.

[0142] The following discussion presents the structure for the Resource URIs and the resources and methods used for the slice API management service.

[0143] FIG. 7 illustrates an example resource URI structure **700** in accordance with aspects of the present disclosure. The resource URI structure **700**, for instance, represents a custom operation URI structure of the NSCE\_SliceApiManagement API. Table 33 provides an overview of the resources and applicable HTTP methods for the NSCE\_SliceApiManagement API.

TABLE-US-00035

TABLE 33	Resources and methods overview
HTTP method	or custom
Resource name	Resource URI
operation	Description
Slice API information	/apiInfo
POST	Provides the slice API information notification.

[0144] The Slice API information resource can be used for a NSCE server to notify a VAL server about the slice API information. An example resource URI is: [0145] {apiRoot}/nsce-sam/<apiVersion>/apiInfo

[0146] The Slice API information resource can support resource URI variables such as defined in Table 34.

TABLE-US-00036

TABLE 34	Resource URI variables	
Name	Data Type	Definition
apiRoot	string	

[0147] The Slice API information resource can utilize a POST method with can enable a NSCE server to notify the VAL server with the slice API information. This method can support the URI query parameters specified in Table 35.

TABLE-US-00037

TABLE 35	URI query parameters supported by the POST method			
Name	Data type	P	Cardinality	Description

[0148] Further, the POST method can support the request data structures specified in Table 36 and the response data structures and response codes specified in Table 37.

TABLE-US-00038 TABLE 36 Data structures supported by the POST Request Body Data type P  
Cardinality Description SIApiInfo M 1 Notification on slice API information in: initial  
configuration procedure; or configuration update procedure.

TABLE-US-00039 TABLE 37 Data structures supported by the POST Response Body Response  
Data type P Cardinality codes Description n/a 204 No Content Notification for the slice API  
information is accepted. NOTE: The HTTP error status codes for the HTTP POST method listed in  
table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0149] Table 38 lists example custom operations without associated resources.

TABLE-US-00040 TABLE 38 Custom operations without associated resources Custom Custom  
Mapped operation operation HTTP name URI method Description VAL /Reqt POST Provides VAL  
application application requirements which are to be Requirement mapped to a slice API as a part  
of a service API list Updated VAL /UpdReqt POST Requests for an update of application the slice  
API configuration. requirement Slice API /ApiInvoc POST Requests for a slice API invocation  
invocation.

[0150] The VAL application Requirement represents a custom operation that can be used by the  
VAL server to provide the NSCE server with the VAL application requirement which is to be  
mapped by the NSCE server to a slice API as a part of a service API list. The VAL application  
Requirement can support the request data structures specified in Table 39 the response data  
structures and response codes specified in Table 40.

TABLE-US-00041 TABLE 39 Data structures supported by the POST Request Body Data type P  
Cardinality Description ReqtReq M 1 Provides requirement which is to be mapped to a slice API as  
a part of a slice API list.

TABLE-US-00042 TABLE 40 Data structures supported by the POST Response Body Response  
Data type P Cardinality codes Description ReqtRes M 1 200 OK The network slice adaptation  
request is successfully received and processed. NOTE: The HTTP error status codes for the HTTP  
POST method listed in table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0151] The Updated VAL application requirement custom operation can be used by the VAL server  
to request the NSCE server an update of the slice API configuration. This custom operation can  
support the request data structures specified in Table 41 the response data structures and response  
codes specified in Table 42.

TABLE-US-00043 TABLE 41 Data structures supported by the POST Request Body Data type P  
Cardinality Description UpdReq M 1 Requests an update of the slice API configuration

TABLE-US-00044 TABLE 42 Data structures supported by the POST Response Body Data  
Response type P Cardinality codes Description UpdRes M 1 200 OK Whether the result of the  
update of the slice API configuration was successful or not. NOTE: The HTTP error status codes  
for the HTTP POST method listed in table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0152] The Slice API invocation application requirement custom operation can be used by the VAL  
server to request the NSCE server for slice API invocation. This custom operation can support the  
request data structures specified in Table 43 the response data structures and response codes  
specified in Table 44.

TABLE-US-00045 TABLE 43 Data structures supported by the POST Request Body Data type P  
Cardinality Description InvocReq M 1 Requests slice API invocation

TABLE-US-00046 TABLE 44 Data structures supported by the POST Response Body Data  
Response type P Cardinality codes Description InvocRes M 1 200 OK Whether the result of the  
slice API invocation was successful or not. NOTE: The mandatory HTTP error status codes for the  
HTTP POST method listed in table 5.2.6-1 of 3GPP TS 29.122 can also apply.

[0153] Regarding the application data model supported by the slice management API, Table 45  
specifies the data types defined for the NSCE\_SliceApiManagement API and Table 46 specifies  
data types re-used by the NSCE\_SliceApiManagement API from other specifications, including a  
reference to their respective specifications and a short description of their use within the

NSCE\_SliceApiManagement API.

TABLE-US-00047 TABLE 45 NSCE\_SliceApiManagement API specific Data Types Data Clause  
Applica- type defined Description bility AccToken 5.3.6.2.9 Indicates access token standard claims,  
specified in 3GPP TS 33.122.

TABLE-US-00048 TABLE 46 NSCE\_SliceApiManagement API re-used Data Types Data type  
Reference Comments Applicability NetSliceId 3GPP TS 29.435 Identifies the S-NSSAI.

TimeWindow 3GPP TS 29.122 A time window. Uri 3GPP TS 29.122 Represents a URI.

[0154] The following discussion details structured data types for use in resource representations  
including ReqReq detailed in Table 47, ReqRes detailed in Table 48, UpdReq detailed in Table 49,  
UpdRes detailed in Table 50, ApiInfo detailed in Table 51, InvocReq detailed in Table 52, InvocRes  
detailed in Table 53, and AccToken detailed in Table 54.

TABLE-US-00049 TABLE 47 Definition of type ReqReq Attribute name Data type P Cardinality  
Description Applicability srvReqs array(ValSrvReq) M 1 . . . N VAL application requirements  
pertaining to one or more slices. timeValidity TimeWindow O 0 . . . 1 The time validity of the  
request.

TABLE-US-00050 TABLE 48 Definition of type ReqRes Attribute name Data type P Cardinality  
Description Applicability confRslt boolean M 1 Indicates on the result of the request for VAL  
application requirement that the slice API configuration: if set to “1”, is possible; or if set to “0”, is  
not possible. confErr ConfErr O 0 . . . 1 Indicates the reason for the configuration error.

TABLE-US-00051 TABLE 49 Definition of type UpdReq Attribute name Data type P Cardinality  
Description Applicability trigEvt TrigEvt M 1 Indicates trigger event causing an indication for  
slice API configuration update. netSliceId NetSliceId O 0 . . . 1 Identifier of the network slice for  
which the API configuration is requested.

TABLE-US-00052 TABLE 50 Definition of type UpdRes Attribute name Data type P Cardinality  
Description Applicability confUpd boolean M 1 Indicates on the result of the request for update the  
slice API configuration: if set to “1”, is updated; or if set to “0”, is not updated. slApiInfoUpd  
SlApiInfo M 1 Indicates the updated slice API information if the slice API configuration is  
updated. confErr ConfErr O 0 . . . 1 Indicates the reason for the configuration update error if the  
slice API configuration is not updated.

TABLE-US-00053 TABLE 51 Definition of type ApiInfo Attribute Data Applica- name type P  
Cardinality Description bility slApiInfo SlApiInfo M 1 Indicates the slice API information

TABLE-US-00054 TABLE 52 Definition of type InvocReq Attribute name Data type P Cardinality  
Description Applicability netsliceId NetSliceId M 1 Identifier of the network slice for which the  
API invocation is requested. authInfo AccToken O 0 . . . 1 Authorization information to request for  
the slice API invocation.

TABLE-US-00055 TABLE 53 Definition of type InvocRes Attribute name Data type P Cardinality  
Description Applicability invocRslt boolean M 1 Indicates on the result of the request for slice API  
invocation that the slice API invocation: if set to “1”, is performed; or if set to “0”, is not  
performed. invocErr InvocErr O 0 . . . 1 Indicates the reason for the slice API invocation failure, if  
it fails.

TABLE-US-00056 TABLE 54 Definition of type AccToken Attribute name Data type P Cardinality  
Description Applicability timeValidity TimeWindow M 1 Indicates the validity time. srvList  
SrvList M array(string) Indicates the list of services the access token is valid.

[0155] For the NSCE\_SliceApiManagement API, HTTP error responses can be supported as  
specified in clause 5.2.6 of 3GPP TS 29.122. Protocol errors and application errors specified in  
clause 5.2.6 of 3GPP TS 29.122 can be supported for the HTTP status codes specified in table  
5.2.6-1 of 3GPP TS 29.122. In addition, the requirements in the following clauses can be applicable  
for the NSCE\_SliceApiManagement API.

[0156] Example application errors defined for the NSCE\_SliceApiManagement API are listed in  
Table 55 and supported features for feature negotiation are listed in Table 56.

TABLE-US-00057 TABLE 55 Application errors Application Error HTTP status code Description  
Applicability

TABLE-US-00058 TABLE 56 Supported Features Feature number Feature Name Description  
[0157] Regarding security, the provisions of clause 6 of 3GPP TS 29.122 can apply for the  
NSCE\_SliceApiManagement API.

[0158] The following presents example YAML code for a slice API management API, e.g.,  
NSCE\_SliceApiManagement API.

```
TABLE-US-00059 openapi: 3.0.0 info:   title: NSCE_SliceApiManagement   version: 1.0.0-  
alpha.1   description: |   NSCE Server Slice API Management Service.   © <2024>, 3GPP  
Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).   All rights reserved.  
externalDocs:   description: >   3GPP TS 29.435 V0.2.0; Service Enabler Architecture Layer  
for Verticals (SEAL);   NSCE Server Services; Stage 3.   url:  
http://www.3gpp.org/ftp/Specs/archive/29_series/29.435/ servers:   - url: '{apiRoot}/nsce-sac/v1'  
   variables:   apiRoot:   default: https://example.com   description:  
apiRoot as defined in clause 6.5 of 3GPP TS 29.549 security:   - { }   - oAuth2ClientCredentials:  
[ ] paths:   /Req:   post:   summary: Slice API configuration maps VAL application to a  
slice API of service APIs.   operationId: SliceAPIConfiguration   tags:   - Slice  
API configuration   requestBody:   required: true   content:  
application/json:   schema:   $ref: '#/components/schemas/ReqReq'  
   responses:   '200':   description: >   The slice API  
configuration request has been successfully received and processed   and the result of  
the requested slice API configuration is in the response body.   content:  
application/json:   schema:   type: array  
items:   $ref: '#/components/schemas/ReqRes'   minItems:  
1   '307':   $ref: 'TS29122_CommonData.yaml#/components/responses/307'  
   '308':   $ref: 'TS29122_CommonData.yaml#/components/responses/308'  
   '400':   $ref: 'TS29122_CommonData.yaml#/components/responses/400'  
   '401':   $ref: 'TS29122_CommonData.yaml#/components/responses/401'  
   '403':   $ref: 'TS29122_CommonData.yaml#/components/responses/403'  
   '404':   $ref: 'TS29122_CommonData.yaml#/components/responses/404'  
   '411':   $ref: 'TS29122_CommonData.yaml#/components/responses/411'  
   '413':   $ref: 'TS29122_CommonData.yaml#/components/responses/413'  
   '415':   $ref: 'TS29122_CommonData.yaml#/components/responses/415'  
   '429':   $ref: 'TS29122_CommonData.yaml#/components/responses/429'  
   '500':   $ref: 'TS29122_CommonData.yaml#/components/responses/500'  
   '503':   $ref: 'TS29122_CommonData.yaml#/components/responses/503'  
   default:   $ref: 'TS29122_CommonData.yaml#/components/responses/default'  
   /UpdReq:   post:   summary: Update the slice API configuration of the mapping the  
slice configuration.   operationId: UpdateSliceAPIConfiguration   tags:   -  
Update slice API configuration   requestBody:   required: true   content:  
application/json:   schema:   $ref:  
'#/components/schemas/UpdReq'   responses:   '200':   description: >  
Update for the slice API configuration request has been successfully received and  
processed and the result of the requested update for the slice API configuration  
is in the response body.   content:   application/json:  
   schema:   type: array   items:  
   $ref: '#/components/schemas/UpdRes'   minItems: 1  
   '307':   $ref: 'TS29122_CommonData.yaml#/components/responses/307'  
   '308':   $ref: 'TS29122_CommonData.yaml#/components/responses/308'  
   '400':   $ref: 'TS29122_CommonData.yaml#/components/responses/400'
```



```

    '401': $ref: 'TS29122_CommonData.yaml#/components/responses/401'
    '403': $ref: 'TS29122_CommonData.yaml#/components/responses/403'
    '404': $ref: 'TS29122_CommonData.yaml#/components/responses/404'
    '411': $ref: 'TS29122_CommonData.yaml#/components/responses/411'
    '413': $ref: 'TS29122_CommonData.yaml#/components/responses/413'
    '415': $ref: 'TS29122_CommonData.yaml#/components/responses/415'
    '429': $ref: 'TS29122_CommonData.yaml#/components/responses/429'
    '500': $ref: 'TS29122_CommonData.yaml#/components/responses/500'
    '503': $ref: 'TS29122_CommonData.yaml#/components/responses/503'
    default: $ref: 'TS29122_CommonData.yaml#/components/responses/default'
  /apiInfo:
    post:
      summary: Notifies with slice API information.
      operationId: SliceAPIInfoNotification
      tags: - Slice API information notification
      requestBody:
        required: true
        content: application/json
        schema: $ref: '#/components/schemas/SlApiInfo'
      responses:
        '204':
          description: No Content, Notification was succesfull
        '307': $ref: 'TS29122_CommonData.yaml#/components/responses/307'
        '308': $ref: 'TS29122_CommonData.yaml#/components/responses/308'
        '400': $ref: 'TS29122_CommonData.yaml#/components/responses/400'
        '401': $ref: 'TS29122_CommonData.yaml#/components/responses/401'
        '403': $ref: 'TS29122_CommonData.yaml#/components/responses/403'
        '404': $ref: 'TS29122_CommonData.yaml#/components/responses/404'
        '411': $ref: 'TS29122_CommonData.yaml#/components/responses/411'
        '413': $ref: 'TS29122_CommonData.yaml#/components/responses/413'
        '415': $ref: 'TS29122_CommonData.yaml#/components/responses/415'
        '429': $ref: 'TS29122_CommonData.yaml#/components/responses/429'
        '500': $ref: 'TS29122_CommonData.yaml#/components/responses/500'
        '503': $ref: 'TS29122_CommonData.yaml#/components/responses/503'
        default: $ref: 'TS29122_CommonData.yaml#/components/responses/default'
  /ApiInvoc
    post:
      summary: Slice API invocation to invoke service APIs based on the
      slice API configuration.
      operationId: SliceAPIInvocation
      tags: - Slice API
      invocation
      requestBody:
        required: true
        content: application/json
        schema: $ref: '#/components/schemas/InvocReq'
      responses:
        '200':
          description: > The slice API
          invocation request has been successfully received and processed and the result of the
          requested slice API invocation is in the response body.
          content: application/json
          schema:
            type: array
            items: $ref: '#/components/schemas/InvocRes'
            minItems: 1
          '307': $ref:
            'TS29122_CommonData.yaml#/components/responses/307'
            '308': $ref:
            'TS29122_CommonData.yaml#/components/responses/308'
            '400': $ref:
            'TS29122_CommonData.yaml#/components/responses/400'
            '401': $ref:
            'TS29122_CommonData.yaml#/components/responses/401'
            '403': $ref:
            'TS29122_CommonData.yaml#/components/responses/403'
            '404': $ref:
            'TS29122_CommonData.yaml#/components/responses/404'
            '411': $ref:
            'TS29122_CommonData.yaml#/components/responses/411'
            '413': $ref:
            'TS29122_CommonData.yaml#/components/responses/413'
            '415': $ref:
            'TS29122_CommonData.yaml#/components/responses/415'
            '429': $ref:
            'TS29122_CommonData.yaml#/components/responses/429'
            '500': $ref:
            'TS29122_CommonData.yaml#/components/responses/500'
            '503': $ref:
            'TS29122_CommonData.yaml#/components/responses/503'
            default: $ref:

```

```

'TS29122_CommonData.yaml#/components/responses/default' components: securitySchemes:
  oAuth2ClientCredentials: type: oauth2 flows: clientCredentials:
    tokenUrl: '{tokenUrl}' scopes: { } schemas: # # STRUCTURED DATA
TYPES # ReqtReq: description: > Represents the slice API configuration
request. type: object properties: srvReqs: type: array
  items: $ref: '#/components/schemas/ValSrvReq' minItems: 1
  timeValidity: $ref:
'TS29122_CommonData.yaml#/components/schemas/TimeWindow' required: -
srvReqs ReqtRes: description: > Represents result of the successfully
processed slice API configuration. type: object properties: confRlt:
  type: boolean confErr: $ref: '#/components/schemas/ConfErr'
  required: - confRlt UpdReq: description: > Represents the
slice API configuration update request. type: object properties: trigEvt:
  $ref: '#/components/schemas/TrigEvt' netSliceId: $ref:
'TS29435_NSCE_PolicyManagement.yaml#/components/schemas/NetSliceId' required:
- trigEvt UpdRes: description: > Represents result of the
successfully processed slice API configuration update. type: object properties:
  confUpdRslt: type: boolean slApiInfoUpd: $ref:
  '#/components/schemas/SlApiInfo' confErr: $ref:
  '#/components/schemas/ConfErr' required: - confUpdRslt -
slApiInfoUpd ApiInfo: description: > Represents the slice notification
information. type: object properties: slApiInfo: $ref:
  '#/components/schemas/SlApiInfo' required: - slApiInfo InvocReq:
description: > Represents the slice API invocation request. type: object
properties: netSliceId: $ref:
'TS29435_NSCE_PolicyManagement.yaml#/components/schemas/NetSliceId' authInfo:
  $ref: '#/components/schemas/AccToken' required: - netSliceId
InvocRes: description: > Represents result of the successfully processed slice API
invocation request. type: object properties: invocRslt: type:
boolean invocErr: $ref: '#/components/schemas/InvocErr' required:
- invocRslt AccToken: description: > Represents the authorization
token for services. type: object properties: timeValidity: $ref:
'TS29122_CommonData.yaml#/components/schemas/TimeWindow' srvList:
  type: array items: type: string minItems: 1
  description: List of service identifiers. required: - timeValidity
  - srvList:

```

[0159] FIG. 8 illustrates an example of a NE **800** in accordance with aspects of the present disclosure. The NE **800** may include a processor **802**, a memory **804**, a controller **806**, and a transceiver **808**. The processor **802**, the memory **804**, the controller **806**, or the transceiver **808**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of the present disclosure as described herein. These components may be coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more interfaces. The NE **800** can represent various devices such as a VAL server, an NSCE server, 5GS, SEAL service, API providers, etc.

[0160] The processor **802**, the memory **804**, the controller **806**, or the transceiver **808**, or various combinations or components thereof may be implemented in hardware (e.g., circuitry). The hardware may include a processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), or other programmable logic device, or any combination thereof configured as or otherwise supporting a means for performing the functions described in the present disclosure.

[0161] The processor **802** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, a CPU, an ASIC, an FPGA, or any combination thereof). In some implementations, the processor **802** may be configured to operate the memory **804**. In some other implementations, the memory **804** may be integrated into the processor **802**. The processor **802** may be configured to execute computer-readable instructions stored in the memory **804** to cause the NE **800** to perform various functions of the present disclosure.

[0162] The memory **804** may include volatile or non-volatile memory. The memory **804** may store computer-readable, computer-executable code including instructions when executed by the processor **802** cause the NE **800** to perform various functions described herein. The code may be stored in a non-transitory computer-readable medium such as the memory **804** or another type of memory. Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that may be accessed by a general-purpose or special-purpose computer.

[0163] In some implementations, the processor **802** and the memory **804** coupled with the processor **802** may be configured to cause the NE **800** to perform one or more of the functions described herein (e.g., executing, by the processor **802**, instructions stored in the memory **804**). For example, the processor **802** may support wireless communication at the NE **800** in accordance with examples as disclosed herein.

[0164] The NE **800** may be configured to or operable to support a means for transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; and receiving, from the second NE, a response message including a result of the service operation.

[0165] Additionally, the NE **800** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReqt; In some aspects, the techniques described herein relate to a method, further including receiving, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0166] Additionally, or alternatively, the NE **800** may support at least one memory (e.g., the memory **804**) and at least one processor (e.g., the processor **802**) coupled with the at least one memory and configured to cause the NE to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; and receive, from the second NE, a response message including a result of the service operation.

[0167] Additionally, the NE **800** may be configured to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReqt; the at least one processor is configured to cause the first NE to receive, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0168] The NE **800** may be configured to or operable to support a means for receiving, from a first NE, a request message for a service operation, the request message including a resource URI for a

HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; performing the service operation; and transmitting, to the first NE, a response message including a result of the service operation.

[0169] Additionally, the NE **800** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nscc-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReqt; In some aspects, the techniques described herein relate to a method, further including transmitting, to the first NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0170] Additionally, or alternatively, the NE **800** may support at least one memory (e.g., the memory **804**) and at least one processor (e.g., the processor **802**) coupled with the at least one memory and configured to cause the NE to receive, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0171] Additionally, the NE **800** may be configured to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReqt; the at least one processor is configured to cause the second NE to transmit, to the first NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0172] The NE **800** may be configured to or operable to support a means for transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; and receiving, from the second NE, a response message including a result of the service operation.

[0173] Additionally, the NE **800** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the operation URI includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0174] Additionally, or alternatively, the NE **800** may support at least one memory (e.g., the memory **804**) and at least one processor (e.g., the processor **802**) coupled with the at least one memory and configured to cause the NE to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; and receive, from the second NE, a response message including a result of the service operation.

[0175] Additionally, the NE **800** may be configured to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for

which the API invocation is requested or authorization information for the API invocation; the operation URI includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0176] The NE **800** may be configured to or operable to support a means for receiving, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; performing the service operation; and transmitting, to the first NE, a response message including a result of the service operation.

[0177] Additionally, the NE **800** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; In some aspects, the techniques described herein relate to a method, further including one or more of: verifying, based at least in part on the information of the one or more data types, an identity of the first NE; or determining, based at least in part on the information of the one or more data types, whether the first NE is authorized to request the API invocation; the response message includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; performing the service operation includes translating the API invocation to a service API invocation; translating the API invocation to the service API invocation includes mapping a network slice for the API invocation to the service API; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0178] Additionally, or alternatively, the NE **800** may support at least one memory (e.g., the memory **804**) and at least one processor (e.g., the processor **802**) coupled with the at least one memory and configured to cause the NE to receive, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0179] Additionally, the NE **800** may be configured to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the at least one processor is configured to cause the second NE to one or more of: verify, based at least in part on the information of the one or more data types, an identity of the first NE; or determine, based at least in part on the information of the one or more data types, whether the first NE is authorized to request the API invocation; the response includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; to perform the service operation, the at least one processor is configured to cause the second NE to translate the API invocation to a service API invocation; to translate the API invocation to the service API invocation, the at least one processor is configured to cause the second NE to map a network slice for the API invocation to the service API; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0180] The NE **800** may be configured to or operable to support a means for transmitting, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one or more of an initial API

configuration, an API configuration update, or an API invocation associated with an API provider; and receiving, from the second NE, a response message including a result of the service operation. [0181] Additionally, the NE **800** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration, the API configuration update, or the API invocation; the operation URI includes one or more of {apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; In some aspects, the techniques described herein relate to a method, further including receiving, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sam/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0182] Additionally, or alternatively, the NE **800** may support at least one memory (e.g., the memory **804**) and at least one processor (e.g., the processor **802**) coupled with the at least one memory and configured to cause the NE to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; and receive, from the second NE, a response message including a result of the service operation.

[0183] Additionally, the NE **800** may be configured to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration, the API configuration update, or the API invocation; the operation URI includes one or more of {apiRoot}/nscc-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; the at least one processor is configured to cause the first NE to receive, from the second NE, a response including slice API information; the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0184] The NE **800** may be configured to or operable to support a means for receiving, from a first NE, a request message for a service operation, the request message including an operation URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; performing the service operation; and transmitting, to the first NE, a response message including a result of the service operation.

[0185] Additionally, the NE **800** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the response message includes one or more of {{apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; In some aspects, the techniques described herein relate to a method, further including transmitting, to the first NE, a response including slice API information; the response includes {apiRoot}/nsce-sam/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0186] Additionally, or alternatively, the NE **800** may support at least one memory (e.g., the memory **804**) and at least one processor (e.g., the processor **802**) coupled with the at least one memory and configured to cause the NE to receive, from a first NE, a request message for a service operation, the request message including an operation URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration

update, or an API invocation associated with an API provider; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0187] Additionally, the NE **800** may be configured to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {{apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReq, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; the at least one processor is configured to cause the second NE to transmit, to the first NE, a response including slice API information; the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0188] The controller **806** may manage input and output signals for the NE **800**. The controller **806** may also manage peripherals not integrated into the NE **800**. In some implementations, the controller **806** may utilize an operating system such as iOS®, ANDROID®, WINDOWS®, or other operating systems. In some implementations, the controller **806** may be implemented as part of the processor **802**.

[0189] In some implementations, the NE **800** may include at least one transceiver **808**. In some other implementations, the NE **800** may have more than one transceiver **808**. The transceiver **808** may represent a wireless transceiver. The transceiver **808** may include one or more receiver chains **810**, one or more transmitter chains **812**, or a combination thereof.

[0190] A receiver chain **810** may be configured to receive signals (e.g., control information, data, packets) over a wireless medium. For example, the receiver chain **810** may include one or more antennas to receive a signal over the air or wireless medium. The receiver chain **810** may include at least one amplifier (e.g., a low-noise amplifier (LNA)) configured to amplify the received signal. The receiver chain **810** may include at least one demodulator configured to demodulate the received signal and obtain the transmitted data by reversing the modulation technique applied during transmission of the signal. The receiver chain **810** may include at least one decoder for decoding the demodulated signal to receive the transmitted data.

[0191] A transmitter chain **812** may be configured to generate and transmit signals (e.g., control information, data, packets). The transmitter chain **812** may include at least one modulator for modulating data onto a carrier signal, preparing the signal for transmission over a wireless medium. The at least one modulator may be configured to support one or more techniques such as amplitude modulation (AM), frequency modulation (FM), or digital modulation schemes like phase-shift keying (PSK) or quadrature amplitude modulation (QAM). The transmitter chain **812** may also include at least one power amplifier configured to amplify the modulated signal to an appropriate power level suitable for transmission over the wireless medium. The transmitter chain **812** may also include one or more antennas for transmitting the amplified signal into the air or wireless medium.

[0192] FIG. **9** illustrates an example of a processor **900** in accordance with aspects of the present disclosure. The processor **900** may be an example of a processor configured to perform various operations in accordance with examples as described herein. The processor **900** may include a controller **902** configured to perform various operations in accordance with examples as described herein. The processor **900** may optionally include at least one memory **904**, which may be, for example, an L1/L2/L3 cache. Additionally, or alternatively, the processor **900** may optionally include one or more arithmetic-logic units (ALUs) **906**. One or more of these components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more interfaces (e.g., buses).

[0193] The processor **900** may be a processor chipset and include a protocol stack (e.g., a software stack) executed by the processor chipset to perform various operations (e.g., receiving, obtaining, retrieving, transmitting, outputting, forwarding, storing, determining, identifying, accessing,

writing, reading) in accordance with examples as described herein. The processor chipset may include one or more cores, one or more caches (e.g., memory local to or included in the processor chipset (e.g., the processor **900**) or other memory (e.g., random access memory (RAM), read-only memory (ROM), dynamic RAM (DRAM), synchronous dynamic RAM (SDRAM), static RAM (SRAM), ferroelectric RAM (FeRAM), magnetic RAM (MRAM), resistive RAM (RRAM), flash memory, phase change memory (PCM), and others).

[0194] The controller **902** may be configured to manage and coordinate various operations (e.g., signaling, receiving, obtaining, retrieving, transmitting, outputting, forwarding, storing, determining, identifying, accessing, writing, reading) of the processor **900** to cause the processor **900** to support various operations in accordance with examples as described herein. For example, the controller **902** may operate as a control unit of the processor **900**, generating control signals that manage the operation of various components of the processor **900**. These control signals include enabling or disabling functional units, selecting data paths, initiating memory access, and coordinating timing of operations.

[0195] The controller **902** may be configured to fetch (e.g., obtain, retrieve, receive) instructions from the memory **904** and determine subsequent instruction(s) to be executed to cause the processor **900** to support various operations in accordance with examples as described herein. The controller **902** may be configured to track memory addresses of instructions associated with the memory **904**. The controller **902** may be configured to decode instructions to determine the operation to be performed and the operands involved. For example, the controller **902** may be configured to interpret the instruction and determine control signals to be output to other components of the processor **900** to cause the processor **900** to support various operations in accordance with examples as described herein. Additionally, or alternatively, the controller **902** may be configured to manage flow of data within the processor **900**. The controller **902** may be configured to control transfer of data between registers, ALUs **906**, and other functional units of the processor **900**.

[0196] The memory **904** may include one or more caches (e.g., memory local to or included in the processor **900** or other memory, such as RAM, ROM, DRAM, SDRAM, SRAM, MRAM, flash memory, etc. In some implementations, the memory **904** may reside within or on a processor chipset (e.g., local to the processor **900**). In some other implementations, the memory **904** may reside external to the processor chipset (e.g., remote to the processor **900**).

[0197] The memory **904** may store computer-readable, computer-executable code including instructions that, when executed by the processor **900**, cause the processor **900** to perform various functions described herein. The code may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. The controller **902** and/or the processor **900** may be configured to execute computer-readable instructions stored in the memory **904** to cause the processor **900** to perform various functions. For example, the processor **900** and/or the controller **902** may be coupled with or to the memory **904**, the processor **900**, and the controller **902**, and may be configured to perform various functions described herein. In some examples, the processor **900** may include multiple processors and the memory **904** may include multiple memories. One or more of the multiple processors may be coupled with one or more of the multiple memories, which may, individually or collectively, be configured to perform various functions herein.

[0198] The one or more ALUs **906** may be configured to support various operations in accordance with examples as described herein. In some implementations, the one or more ALUs **906** may reside within or on a processor chipset (e.g., the processor **900**). In some other implementations, the one or more ALUs **906** may reside external to the processor chipset (e.g., the processor **900**). One or more ALUs **906** may perform one or more computations such as addition, subtraction, multiplication, and division on data. For example, one or more ALUs **906** may receive input operands and an operation code, which determines an operation to be executed. One or more ALUs



**906** may be configured with a variety of logical and arithmetic circuits, including adders, subtractors, shifters, and logic gates, to process and manipulate the data according to the operation. Additionally, or alternatively, the one or more ALUs **906** may support logical operations such as AND, OR, exclusive-OR (XOR), not-OR (NOR), and not-AND (NAND), enabling the one or more ALUs **906** to handle conditional operations, comparisons, and bitwise operations.

[0199] The processor **900** may support wireless communication in accordance with examples as disclosed herein. The processor **900** may be configured to or operable to support at least one controller (e.g., the controller **902**) coupled with at least one memory (e.g., the memory **904**) and configured to cause the processor to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; and receive, from the second NE, a response message including a result of the service operation.

[0200] Additionally, the processor **900** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReqt; the at least one controller is configured to cause the processor to receive, from the second NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0201] The processor **900** may support wireless communication in accordance with examples as disclosed herein. The processor **900** may be configured to or operable to support at least one controller (e.g., the controller **902**) coupled with at least one memory (e.g., the memory **904**) and configured to cause the processor to receive, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0202] Additionally, the processor **900** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sac/<apiVersion>/Reqt or {apiRoot}/nsce-sac/<apiVersion>/UpdReqt; the at least one controller is configured to cause the processor to transmit, to the first NE, a response including slice API information; the response includes {apiRoot}/nsce-sac/<apiVersion>/apiInfo}; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0203] The processor **900** may support wireless communication in accordance with examples as disclosed herein. The processor **900** may be configured to or operable to support at least one controller (e.g., the controller **902**) coupled with at least one memory (e.g., the memory **904**) and configured to cause the processor to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; and receive, from the second NE, a response message including a result of the service operation.

[0204] Additionally, the processor **900** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the operation URI includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; the first

NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0205] The processor **900** may support wireless communication in accordance with examples as disclosed herein. The processor **900** may be configured to or operable to support at least one controller (e.g., the controller **902**) coupled with at least one memory (e.g., the memory **904**) and configured to cause the processor to receive, from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0206] Additionally, the processor **900** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of an identifier for a network slice for which the API invocation is requested or authorization information for the API invocation; the at least one controller is configured to cause the processor to one or more of: verify, based at least in part on the information of the one or more data types, an identity of the first NE; or determine, based at least in part on the information of the one or more data types, whether the first NE is authorized to request the API invocation; the response includes {apiRoot}/nsce-sai/<apiVersion>/ApiInvoc; to perform the service operation, the at least one controller is configured to cause the processor to translate the API invocation to a service API invocation; to translate the API invocation to the service API invocation, the at least one controller is configured to cause the processor to map a network slice for the API invocation to the service API; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to invocation of one or more network slice APIs; the response message includes one or more of a result of the API invocation or an indication of one or more configuration errors.

[0207] The processor **900** may support wireless communication in accordance with examples as disclosed herein. The processor **900** may be configured to or operable to support at least one controller (e.g., the controller **902**) coupled with at least one memory (e.g., the memory **904**) and configured to cause the processor to transmit, to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider; and receive, from the second NE, a response message including a result of the service operation.

[0208] Additionally, the processor **900** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration, the API configuration update, or the API invocation; the operation URI includes one or more of {apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nscc-sam/<apiVersion>/ApiInvoc; the at least one controller is configured to cause the processor to receive, from the second NE, a response including slice API information; the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0209] The processor **900** may support wireless communication in accordance with examples as disclosed herein. The processor **900** may be configured to or operable to support at least one controller (e.g., the controller **902**) coupled with at least one memory (e.g., the memory **904**) and configured to cause the processor to receive, from a first NE, a request message for a service operation, the request message including an operation URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration

update, or an API invocation associated with an API provider; perform the service operation; and transmit, to the first NE, a response message including a result of the service operation.

[0210] Additionally, the processor **900** may be configured to or operable to support any one or combination of where the request message further includes one or more data types for the request message; the one or more data types include information pertaining to one or more of the initial API configuration of the API configuration update; the operation URI includes one or more of {apiRoot}/nsce-sam/<apiVersion>/Reqt, {apiRoot}/nsce-sam/<apiVersion>/UpdReqt, or {apiRoot}/nsce-sam/<apiVersion>/ApiInvoc; the at least one controller is configured to cause the processor to transmit, to the first NE, a response including slice API information; the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo; the first NE includes a VAL server; the second NE includes a NSCE Server; the service operation pertains to one or more network slice APIs.

[0211] FIG. **10** illustrates a flowchart of a method **1000** in accordance with aspects of the present disclosure. The operations of the method may be implemented by a NE as described herein. In some implementations, the NE may execute a set of instructions to control the function elements of the NE to perform the described functions. It should be noted that the method described herein describes a possible implementation, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible.

[0212] At **1002**, the method may include transmitting, from a first NE to a second NE, a request message for a service operation, the request message including a URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update. The operations of **1002** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1002** may be performed by a NE as described with reference to FIG. **8**.

[0213] At **1004**, the method may include receiving, from the second NE, a response message including a result of the service operation. The operations of **1004** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1004** may be performed by a NE as described with reference to FIG. **8**.

[0214] FIG. **11** illustrates a flowchart of a method **1100** in accordance with aspects of the present disclosure. The operations of the method may be implemented by a NE as described herein. In some implementations, the NE may execute a set of instructions to control the function elements of the NE to perform the described functions. It should be noted that the method described herein describes a possible implementation, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible.

[0215] At **1102**, the method may include receiving, at a second NE and from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one of an initial API configuration or an API configuration update. The operations of **1102** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1102** may be performed by a NE as described with reference to FIG. **8**.

[0216] At **1104**, the method may include performing the service operation. The operations of **1104** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1104** may be performed by a NE as described with reference to FIG. **8**.

[0217] At **1106**, the method may include transmitting, to the first NE, a response message including a result of the service operation. The operations of **1106** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1106** may be performed a NE as described with reference to FIG. **8**.

[0218] FIG. **12** illustrates a flowchart of a method **1200** in accordance with aspects of the present disclosure. The operations of the method may be implemented by a NE as described herein. In some implementations, the NE may execute a set of instructions to control the function elements of

the NE to perform the described functions. It should be noted that the method described herein describes a possible implementation, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible.

[0219] At **1202**, the method may include transmitting, from a first NE to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider. The operations of **1202** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1202** may be performed by a NE as described with reference to FIG. 8.

[0220] At **1204**, the method may include receiving, from the second NE, a response message including a result of the service operation. The operations of **1204** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1204** may be performed by a NE as described with reference to FIG. 8.

[0221] FIG. 13 illustrates a flowchart of a method **1300** in accordance with aspects of the present disclosure. The operations of the method may be implemented by a NE as described herein. In some implementations, the NE may execute a set of instructions to control the function elements of the NE to perform the described functions. It should be noted that the method described herein describes a possible implementation, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible.

[0222] At **1302**, the method may include receiving, at a second NE from a first NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including an API invocation associated with an API provider. The operations of **1302** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1302** may be performed by a NE as described with reference to FIG. 8.

[0223] At **1304**, the method may include performing the service operation. The operations of **1304** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1304** may be performed by a NE as described with reference to FIG. 8.

[0224] At **1306**, the method may include transmitting, to the first NE, a response message including a result of the service operation. The operations of **1306** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1306** may be performed a NE as described with reference to FIG. 8.

[0225] FIG. 14 illustrates a flowchart of a method **1400** in accordance with aspects of the present disclosure. The operations of the method may be implemented by a NE as described herein. In some implementations, the NE may execute a set of instructions to control the function elements of the NE to perform the described functions. It should be noted that the method described herein describes a possible implementation, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible.

[0226] At **1402**, the method may include transmitting, from a first NE to a second NE, a request message for a service operation, the request message including a resource URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider. The operations of **1402** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1402** may be performed by a NE as described with reference to FIG. 8.

[0227] At **1404**, the method may include receiving, from the second NE, a response message including a result of the service operation. The operations of **1404** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1404** may be performed by a NE as described with reference to FIG. 8.

[0228] FIG. 15 illustrates a flowchart of a method **1500** in accordance with aspects of the present disclosure. The operations of the method may be implemented by a NE as described herein. In

some implementations, the NE may execute a set of instructions to control the function elements of the NE to perform the described functions. It should be noted that the method described herein describes a possible implementation, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible.

[0229] At **1502**, the method may include receiving, at a second NE and from a first NE, a request message for a service operation, the request message including an operation URI for a HTTP POST method, and the service operation including one or more of an initial API configuration, an API configuration update, or an API invocation associated with an API provider. The operations of **1502** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1502** may be performed by a NE as described with reference to FIG. 8.

[0230] At **1504**, the method may include performing the service operation. The operations of **1504** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1504** may be performed by a NE as described with reference to FIG. 8.

[0231] At **1506**, the method may include transmitting, to the first NE, a response message including a result of the service operation. The operations of **1506** may be performed in accordance with examples as described herein. In some implementations, aspects of the operations of **1506** may be performed a NE as described with reference to FIG. 8.

[0232] The description herein is provided to enable a person having ordinary skill in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to a person having ordinary skill in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

## Claims

1. A first network equipment (NE) for wireless communication, comprising: at least one memory; and at least one processor coupled with the at least one memory and configured to cause the first NE to: transmit, to a second NE, a request message for a service operation, the request message comprising a resource Uniform Resource Identifier (URI) for a Hypertext Transfer Protocol (HTTP) POST method, wherein the service operation comprises an API configuration update; and receive, from the second NE, a response message comprising a result of the service operation.
2. The first NE of claim 1, wherein the request message further comprises one or more data types for the request message.
3. The first NE of claim 2, wherein the one or more data types comprise information pertaining to the API configuration update.
4. The first NE of claim 1, wherein the resource URI comprises {apiRoot}/nsce-sam/<apiVersion>/UpdReqt.
5. The first NE of claim 1, wherein the at least one processor is configured to cause the first NE to receive, from the second NE, a response comprising slice API information.
6. The first NE of claim 5, wherein the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo}.
7. The first NE of claim 1, wherein the first NE comprises a Vertical Application Layer (VAL) server.
8. The first NE of claim 7, wherein the second NE comprises a Network Slice Capability Exposure (NSCE) Server.
9. The first NE of claim 1, wherein the service operation pertains to one or more network slice APIs.
10. A second network equipment (NE) for wireless communication, comprising: at least one memory; and at least one processor coupled with the at least one memory and configured to cause

the second NE to: receive, from a first NE, a request message for a service operation, the request message comprising an operation Uniform Resource Identifier (URI) for a Hypertext Transfer Protocol (HTTP) POST method, wherein the service operation comprises an API configuration update; perform the service operation; and transmit, to the first NE, a response message comprising a result of the service operation.

**11.** The second NE of claim 10, wherein the request message further comprises one or more data types for the request message.

**12.** The second NE of claim 11, wherein the one or more data types comprise information pertaining to the API configuration update.

**13.** The second NE of claim 10, wherein the operation URI comprises {apiRoot}/nsce-sam/<apiVersion>/UpdReqt.

**14.** The second NE of claim 10, wherein the at least one processor is configured to cause the second NE to transmit, to the first NE, a response comprising slice API information.

**15.** The second NE of claim 14, wherein the response comprises {apiRoot}/nsce-sam/<apiVersion>/apiInfo}.

**16.** The second NE of claim 10, wherein the first NE comprises a Vertical Application Layer (VAL) server.

**17.** The second NE of claim 16, wherein the second NE comprises a Network Slice Capability Exposure (NSCE) Server.

**18.** The second NE of claim 10, wherein the service operation pertains to one or more network slice APIs.

**19.** A method performed by a first network equipment (NE), the method comprising: transmitting, to a second NE, a request message for a service operation, the request message comprising a resource Uniform Resource Identifier (URI) for a Hypertext Transfer Protocol (HTTP) POST method, wherein the service operation comprises an API configuration update; and receiving, from the second NE, a response message comprising a result of the service operation.

**20.** A method performed by a second network equipment (NE), the method comprising: receiving, from a first NE, a request message for a service operation, the request message comprising an operation Uniform Resource Identifier (URI) for a Hypertext Transfer Protocol (HTTP) POST method, wherein the service operation comprises an API configuration update; performing the service operation; and transmitting, to the first NE, a response message comprising a result of the service operation.

---