

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250259688

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Fitzpatrick; James et al.

Selective and Dynamic Deployment of Error Correction Code Techniques in Integrated Circuit Memory Devices

Abstract

A memory system configured to dynamically adjust the amount of redundant information stored in memory cells of a wordline on an integrated circuit die based on a bit error rate. For example, in response to a determination that a bit error rate of the wordline is above a threshold, the memory system can store first data items as independent first codewords of an error correction code technique into a first portion of the memory cells of the wordline, generate second data items as redundant information from the first codewords, and store the second data items in a second portion of the memory cells of the wordline. If the bit error rate is below the threshold, third data items can be stored as independent second codewords of the same length as the first codewords in the memory cells of the wordline.

Inventors: Fitzpatrick; James (Laguna Niguel, CA), Nguyen; Phong Sy (Livermore, CA), Nguyen; Dung Viet (San Jose, CA), Parthasarathy; Sivagnanam (Carlsbad, CA)

Applicant: Micron Technology, Inc. (Boise, ID)

Family ID: 1000008572101

Appl. No.: 19/174153

Filed: April 09, 2025

Related U.S. Application Data

parent US continuation 18636901 20240416 parent-grant-document US 12277978 child US 19174153

parent US continuation 17841096 20220615 parent-grant-document US 11984171 child US 18636901

us-provisional-application US 63221886 20210714

Publication Classification

Int. Cl.: **G11C16/34** (20060101); **A63B24/00** (20060101); **G11C16/26** (20060101)

U.S. Cl.:

CPC **G11C16/3404** (20130101); **A63B24/0075** (20130101); **G11C16/26** (20130101);
A63B2024/0068 (20130101); A63B2024/0093 (20130101); A63B2220/836 (20130101);
A63B2230/06 (20130101)

Background/Summary

RELATED APPLICATIONS [0001] The present application is a continuation application of U.S. patent application Ser. No. 18/636,901 filed Apr. 16, 2024, which is a continuation application of U.S. patent application Ser. No. 17/841,096 filed Jun. 15, 2022 and issued as U.S. Pat. No. 11,984,171 on May 14, 2024, which claims priority to Prov. U.S. Pat. App. Ser. No. 63/221,886 filed Jul. 14, 2021, the entire disclosures of which applications are hereby incorporated herein by reference.

TECHNICAL FIELD

[0002] At least some embodiments disclosed herein relate to memory systems in general, and more particularly, but not limited to techniques to reliability in storing multiple bits of data per memory cell.

BACKGROUND

[0003] A memory sub-system can include one or more memory devices that store data. The memory devices can be, for example, non-volatile memory devices and volatile memory devices. In general, a host system can utilize a memory sub-system to store data at the memory devices and to retrieve data from the memory devices.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] The embodiments are illustrated by way of example and not limitation in the figures of the accompanying drawings in which like references indicate similar elements.

[0005] FIG. 1 illustrates an example computing system having a memory sub-system in accordance with some embodiments of the present disclosure.

[0006] FIG. 2 illustrates an integrated circuit memory device having a programming manager configured to program threshold voltages of memory cells to store data according to one embodiment.

[0007] FIG. 3 shows an example of programming memory cells to store multiple bits per memory cell according to one embodiment.

[0008] FIGS. 4 and 5 illustrate techniques generate a data group for programming memory cells at threshold levels determined by a Gray code for improved reliability according to some embodiments.

[0009] FIG. 6 illustrates reliability improvements in reading data programmed using techniques of FIGS. 4 and 5.

[0010] FIG. 7 shows a technique to recover data retrieved from memory cells programmed using the techniques of FIGS. 4 and 5.

[0011] FIG. **8** shows an example of measuring signal and noise characteristics to improve memory operations according to one embodiment.

[0012] FIG. **9** illustrates a data integrity classifier determining the likelihood of data integrity failure in data retrieved from a memory device to dynamically configure the operations of error detection and recovery for the data according to one embodiment.

[0013] FIG. **10** shows a memory device configured with a programming manager according to one embodiment.

[0014] FIG. **11** shows a memory cell with a bitline driver and a wordline driver configured to apply voltage pulses according to one embodiment.

[0015] FIG. **12** illustrates a media structure of a memory device according to one embodiment.

[0016] FIG. **13** shows a technique to improve data reliability for memory cells on a wordline according to one embodiment.

[0017] FIGS. **14** to **23** show various techniques to improve data reliability for memory cells on a wordline according to one embodiment.

[0018] FIG. **24** shows a method to dynamically deploy error correction techniques according to one embodiment.

[0019] FIG. **25** is a block diagram of an example computer system in which embodiments of the present disclosure can operate.

DETAILED DESCRIPTION

[0020] At least some aspects of the present disclosure are directed to techniques to improve reliability of storing data in memory cells in a memory sub-system. Examples of storage devices and memory modules are described below in conjunction with FIG. **1**. In general, a host system can utilize a memory sub-system that includes one or more components, such as memory devices that store data. The host system can provide data to be stored at the memory sub-system and can request data to be retrieved from the memory sub-system.

[0021] Different groups of memory cells in an integrated circuit memory device can have different bit error rates in reading the states of the memory cells and thus the data represented by the states. For example, bit error rates can differ from wordline to wordline, from page type to page type, and/or from die to die. For example, error rate differences can result from variations in manufacturing process, or intrinsic properties of the design or layout of circuits on an integrated circuit die. Certain physical addresses have better error rates, and other addresses have worse. The error rates that dictate reliability consideration are from the worst case stresses the memory device may be subjected to, such as reading and writing at extreme temperatures, or reading after years of being powered off. In general, the worst error rates can be different based on various factors, such as addresses, locations (e.g., wordlines), stress (e.g., operating temperature), usage patterns (e.g., power off periods), etc.

[0022] When the integrated circuit memory device is designed to support the storing of sufficient redundant information for each codeword to allow reliable error recovery for the worst performing group of memory cells, the memory device can have unnecessary memory cells configured for high performance groups of memory cells.

[0023] At least some aspects of the present disclosure address the above and other deficiencies by designing an integrated circuit memory device that has sufficient support for majority of memory cell groups to recover bit errors by decoding codewords, and dynamically deploying an additional level of error correction technique for memory cell groups that have higher bit error rates to improve error recovery capability.

[0024] For example, a memory system can be configured to dynamically adjust the amount of redundant information stored in memory cells of a wordline on an integrated circuit die based on a bit error rate. For example, in response to a determination that a bit error rate of the wordline is above a threshold, the memory system can store first data items as independent first codewords of an error correction code technique into a first portion of the memory cells of the wordline, generate

second data items as redundant information from the first codewords, and store the second data items in a second portion of the memory cells of the wordline. If the bit error rate is below the threshold, third data items can be stored as independent second codewords of the same length as the first codewords in the memory cells of the wordline, as further discussed below in connection with FIGS. 13 to 24.

[0025] An integrated circuit memory cell (e.g., a flash memory cell) can be programmed to store data by the way of its state at a predefined voltage. For example, if the memory cell is configured/programmed in a state that allows a substantial current to pass the memory cell at the predefined voltage, the memory cell is storing a bit of one; and otherwise, the memory cell is storing a bit of zero. Further, a memory cell can store multiple bits of data by being configured/programmed differently at multiple predefined voltages. For example, the memory cell can store multiple bits of data by having a combination of states at the multiple predefined voltages; and different combinations of the states of the memory cell at the predefined voltages can be interpreted to represent different states of bits of data that is stored in the memory cell.

[0026] However, after the states of integrated circuit memory cells are configured/programmed using write operations to store data in the memory cells, the optimized threshold voltage for reading the memory cells can shift due to a number of factors, such as charge loss, read disturb, cross-temperature effect (e.g., write and read at different operating temperatures), etc., especially when a memory cell is programmed to store multiple bits of data.

[0027] Data can be encoded with redundant information to facilitate error detection and recovery. When data encoded with redundant information is stored in a memory sub-system, the memory sub-system can detect errors in data retrieved directly from the memory cells in the memory sub-system and/or recover the original data that is used to generate the data for storing in the memory cells. The recovery operation can be successful (or have a high probability of success) when the data retrieved directly from the memory cells in the memory sub-system contains fewer errors, or the bit error rate in the retrieved data is low. For example, error detection and data recovery can be performed using an error correction code (ECC), such as low-density parity-check (LDPC) code, etc.

[0028] It can be desirable in some instances to store a reduced number of bits (e.g., $N-1$) per memory cell in a memory device that has the circuitry to program the threshold voltages of a group of memory cells to store a predetermined number of bits (e.g., N) per memory cell. Adding separate circuitry optimized to independently program the threshold voltages of the group of memory cells to store the reduced number of bits per memory cell (e.g., $N-1$) can lead to increased complexity and/or cost in the hardware of the memory device. Alternatively, an extra group of dummy data (e.g., all zeros, or all ones) can be supplied to increase the number of bits per cell (e.g., to N) to match the functionality of the existing circuitry of the memory device in programming threshold voltages. However, storing the extra group of dummy data (e.g., all zeros, or all ones) for the given data having the reduced number of bits per memory cell (e.g., $N-1$), such that the total number of bits per memory cell is equal to the predetermined number (e.g., N), can lead to reduced reliability in retrieving data from the memory cells, as compared to programming the memory cells at the reduced number of bits (e.g., $N-1$) per memory cells.

[0029] At least some aspects of the present disclosure address the above and other deficiencies by generating the extra group of data from the given data having the reduced number of bits. The extra group of data can be generated to establish a predetermined relation among the groups of data to improve the reliability in retrieving data from the memory cells programmed at the predetermined number of bits per memory cell (e.g., N).

[0030] For example, the memory device can be configured to map the values of the predetermined number of bits (e.g., N) to a threshold voltage according to a Gray code (also known as reflected binary code or reflected binary) in programming the threshold voltages of memory cells to store data. The extra group of data can be generated based on an exclusive or (XOR) operation on the

reduced number of bits (e.g., $N-1$). Alternatively, the inverse of the result of XOR (corresponding to XNOR on the reduced number of bits) can be used. Programming the extra group of data with the given data at the predetermined number of bits (e.g., N) per memory cell can result in high reliability in data retrieval.

[0031] Different combinations of values of a predetermined number of bits N can be used to represent different numbers from 0 to 2^N-1 . A Gray code is a mapping where one bit and only one bit is changed in the bit values when the number represented by the bit value combination changes to the next larger or smaller number. The threshold voltage of a memory cell can be programmed at one of 2^N levels to represent a combination of the values of the predetermined number (N) of bits. Having the threshold voltage of the memory cell programmed at a voltage level is representative of the memory cell storing the combination of values of the N bits corresponding to the voltage level. When a Gray code is used to map between the bit value combinations and the voltage threshold levels, only one bit changes its value when the threshold level moves up or down by one increment. By generating the extra group of data based on XOR/XNOR, the data set to be programmed has either missing odd numbered voltage threshold levels, or even numbered voltage threshold levels. Such an arrangement increases the gap between possible voltage thresholds representing different data and thus improves the reliability in reading data from the memory cells. Further, when one of the predetermined bits stored in a memory cell is found to be corrupted, it can be recovered from the remaining bits through XOR. Thus, the reliability in retrieving data programmed in such a manner is improved.

[0032] FIG. 1 illustrates an example computing system **100** that includes a memory sub-system **110** in accordance with some embodiments of the present disclosure. The memory sub-system **110** can include media, such as one or more volatile memory devices (e.g., memory device **140**), one or more non-volatile memory devices (e.g., memory device **130**), or a combination of such.

[0033] A memory sub-system **110** can be a storage device, a memory module, or a hybrid of a storage device and memory module. Examples of a storage device include a solid-state drive (SSD), a flash drive, a universal serial bus (USB) flash drive, an embedded multi-media controller (eMMC) drive, a universal flash storage (UFS) drive, a secure digital (SD) card, and a hard disk drive (HDD). Examples of memory modules include a dual in-line memory module (DIMM), a small outline DIMM (SO-DIMM), and various types of non-volatile dual in-line memory module (NVDIMM).

[0034] The computing system **100** can be a computing device such as a desktop computer, a laptop computer, a network server, a mobile device, a vehicle (e.g., airplane, drone, train, automobile, or other conveyance), an internet of things (IoT) enabled device, an embedded computer (e.g., one included in a vehicle, industrial equipment, or a networked commercial device), or such a computing device that includes memory and a processing device.

[0035] The computing system **100** can include a host system **120** that is coupled to one or more memory sub-systems **110**. FIG. 1 illustrates one example of a host system **120** coupled to one memory sub-system **110**. As used herein, “coupled to” or “coupled with” generally refers to a connection between components, which can be an indirect communicative connection or direct communicative connection (e.g., without intervening components), whether wired or wireless, including connections such as electrical, optical, magnetic, etc.

[0036] The host system **120** can include a processor chipset (e.g., processing device **118**) and a software stack executed by the processor chipset. The processor chipset can include one or more cores, one or more caches, a memory controller (e.g., controller **116**) (e.g., NVDIMM controller), and a storage protocol controller (e.g., PCIe controller, SATA controller). The host system **120** uses the memory sub-system **110**, for example, to write data to the memory sub-system **110** and read data from the memory sub-system **110**.

[0037] The host system **120** can be coupled to the memory sub-system **110** via a physical host interface. Examples of a physical host interface include, but are not limited to, a serial advanced

technology attachment (SATA) interface, a peripheral component interconnect express (PCIe) interface, a universal serial bus (USB) interface, a fibre channel, a serial attached SCSI (SAS) interface, a double data rate (DDR) memory bus interface, a small computer system interface (SCSI), a dual in-line memory module (DIMM) interface (e.g., DIMM socket interface that supports double data rate (DDR)), an open NAND flash interface (ONFI), a double data rate (DDR) interface, a low power double data rate (LPDDR) interface, or any other interface. The physical host interface can be used to transmit data between the host system **120** and the memory sub-system **110**. The host system **120** can further utilize an NVM express (NVMe) interface to access components (e.g., memory devices **130**) when the memory sub-system **110** is coupled with the host system **120** by the PCIe interface. The physical host interface can provide an interface for passing control, address, data, and other signals between the memory sub-system **110** and the host system **120**. FIG. 1 illustrates a memory sub-system **110** as an example. In general, the host system **120** can access multiple memory sub-systems via a same communication connection, multiple separate communication connections, and/or a combination of communication connections.

[0038] The processing device **118** of the host system **120** can be, for example, a microprocessor, a central processing unit (CPU), a processing core of a processor, an execution unit, etc. In some instances, the controller **116** can be referred to as a memory controller, a memory management unit, and/or an initiator. In one example, the controller **116** controls the communications over a bus coupled between the host system **120** and the memory sub-system **110**. In general, the controller **116** can send commands or requests to the memory sub-system **110** for desired access to memory devices **130**, **140**. The controller **116** can further include interface circuitry to communicate with the memory sub-system **110**. The interface circuitry can convert responses received from the memory sub-system **110** into information for the host system **120**.

[0039] The controller **116** of the host system **120** can communicate with the controller **115** of the memory sub-system **110** to perform operations such as reading data, writing data, or erasing data at the memory devices **130**, **140** and other such operations. In some instances, the controller **116** is integrated within the same package of the processing device **118**. In other instances, the controller **116** is separate from the package of the processing device **118**. The controller **116** and/or the processing device **118** can include hardware such as one or more integrated circuits (ICs) and/or discrete components, a buffer memory, a cache memory, or a combination thereof. The controller **116** and/or the processing device **118** can be a microcontroller, special purpose logic circuitry (e.g., a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), etc.), or another suitable processor.

[0040] The memory devices **130**, **140** can include any combination of the different types of non-volatile memory components and/or volatile memory components. The volatile memory devices (e.g., memory device **140**) can be, but are not limited to, random access memory (RAM), such as dynamic random access memory (DRAM) and synchronous dynamic random access memory (SDRAM).

[0041] Some examples of non-volatile memory components include a negative-and (or, NOT AND) (NAND) type flash memory and write-in-place memory, such as three-dimensional cross-point (“3D cross-point”) memory. A cross-point array of non-volatile memory can perform bit storage based on a change of bulk resistance, in conjunction with a stackable cross-gridded data access array. Additionally, in contrast to many flash-based memories, cross-point non-volatile memory can perform a write in-place operation, where a non-volatile memory cell can be programmed without the non-volatile memory cell being previously erased. NAND type flash memory includes, for example, two-dimensional NAND (2D NAND) and three-dimensional NAND (3D NAND).

[0042] Each of the memory devices **130** can include one or more arrays of memory cells. One type of memory cell, for example, single level cells (SLC) can store one bit per cell. Other types of memory cells, such as multi-level cells (MLCs), triple level cells (TLCs), quad-level cells (QLCs),

and penta-level cells (PLCs) can store multiple bits per cell. In some embodiments, each of the memory devices **130** can include one or more arrays of memory cells such as SLCs, MLCs, TLCs, QLCs, PLCs, or any combination of such. In some embodiments, a particular memory device can include an SLC portion, an MLC portion, a TLC portion, a QLC portion, and/or a PLC portion of memory cells. The memory cells of the memory devices **130** can be grouped as pages that can refer to a logical unit of the memory device used to store data. With some types of memory (e.g., NAND), pages can be grouped to form blocks.

[0043] Although non-volatile memory devices such as 3D cross-point type and NAND type memory (e.g., 2D NAND, 3D NAND) are described, the memory device **130** can be based on any other type of non-volatile memory, such as read-only memory (ROM), phase change memory (PCM), self-selecting memory, other chalcogenide based memories, ferroelectric transistor random-access memory (FeTRAM), ferroelectric random access memory (FeRAM), magneto random access memory (MRAM), spin transfer torque (STT)-MRAM, conductive bridging RAM (CBRAM), resistive random access memory (RRAM), oxide based RRAM (OxRAM), negative-or (NOR) flash memory, and electrically erasable programmable read-only memory (EEPROM).

[0044] A memory sub-system controller **115** (or controller **115** for simplicity) can communicate with the memory devices **130** to perform operations such as reading data, writing data, or erasing data at the memory devices **130** and other such operations (e.g., in response to commands scheduled on a command bus by controller **116**). The controller **115** can include hardware such as one or more integrated circuits (ICs) and/or discrete components, a buffer memory, or a combination thereof. The hardware can include digital circuitry with dedicated (e.g., hard-coded) logic to perform the operations described herein. The controller **115** can be a microcontroller, special purpose logic circuitry (e.g., a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), etc.), or another suitable processor.

[0045] The controller **115** can include a processing device **117** (e.g., processor) configured to execute instructions stored in a local memory **119**. In the illustrated example, the local memory **119** of the controller **115** includes an embedded memory configured to store instructions for performing various processes, operations, logic flows, and routines that control operation of the memory sub-system **110**, including handling communications between the memory sub-system **110** and the host system **120**.

[0046] In some embodiments, the local memory **119** can include memory registers storing memory pointers, fetched data, etc. The local memory **119** can also include read-only memory (ROM) for storing micro-code. While the example memory sub-system **110** in FIG. **1** has been illustrated as including the controller **115**, in another embodiment of the present disclosure, a memory sub-system **110** does not include a controller **115**, and can instead rely upon external control (e.g., provided by an external host, or by a processor or controller separate from the memory sub-system).

[0047] In general, the controller **115** can receive commands or operations from the host system **120** and can convert the commands or operations into instructions or appropriate commands to achieve the desired access to the memory devices **130**. The controller **115** can be responsible for other operations such as wear leveling operations, garbage collection operations, error detection and error-correcting code (ECC) operations, encryption operations, caching operations, and address translations between a logical address (e.g., logical block address (LBA), namespace) and a physical address (e.g., physical block address) that are associated with the memory devices **130**. The controller **115** can further include host interface circuitry to communicate with the host system **120** via the physical host interface. The host interface circuitry can convert the commands received from the host system into command instructions to access the memory devices **130** as well as convert responses associated with the memory devices **130** into information for the host system **120**.

[0048] The memory sub-system **110** can also include additional circuitry or components that are

not illustrated. In some embodiments, the memory sub-system **110** can include a cache or buffer (e.g., DRAM) and address circuitry (e.g., a row decoder and a column decoder) that can receive an address from the controller **115** and decode the address to access the memory devices **130**.

[0049] In some embodiments, the memory devices **130** include local media controllers **150** that operate in conjunction with the memory sub-system controller **115** to execute operations on one or more memory cells of the memory devices **130**. An external controller (e.g., memory sub-system controller **115**) can externally manage the memory device **130** (e.g., perform media management operations on the memory device **130**). In some embodiments, a memory device **130** is a managed memory device, which is a raw memory device combined with a local controller (e.g., local media controller **150**) for media management within the same memory device package. An example of a managed memory device is a managed NAND (MNAND) device.

[0050] The controller **115** and/or a memory device **130** can include a programming manager **113** configured to program threshold voltages of memory cells to store a predetermined number of bits per memory cell by generating extra data from a dataset that has a reduced number of bits per memory cell. In some embodiments, the controller **115** in the memory sub-system **110** and/or the controller **150** in the memory device **130** can include at least a portion of the programming manager **113**. In other embodiments, or in combination, the controller **116** and/or the processing device **118** in the host system **120** includes at least a portion of the programming manager **113**. For example, the controller **115**, the controller **116**, and/or the processing device **118** can include logic circuitry implementing the programming manager **113**. For example, the controller **115**, or the processing device **118** (e.g., processor) of the host system **120**, can be configured to execute instructions stored in memory for performing the operations of the programming manager **113** described herein. In some embodiments, the programming manager **113** is implemented in an integrated circuit chip disposed in the memory sub-system **110**. In other embodiments, the programming manager **113** can be part of firmware of the memory sub-system **110**, an operating system of the host system **120**, a device driver, or an application, or any combination therein.

[0051] For example, the programming manager **113** implemented in the controller **115** and/or the controller **150** can receive a reduced number (e.g., $N-1$) of data groups (e.g., pages) for programming into the memory cells in the memory device **130** that stores a predetermined number (e.g., N) of bits per memory cells. The programming manager **113** generates an extra group (e.g., page) of data by applying an XOR (or XNOR) operation on the reduced number of data groups. A combination of the extra group and the reduced number of groups provides the predetermined number of groups for storing into the group of memory cells. When the memory device **130** has the predetermined number of data groups, the memory device **130** programs threshold voltages of a group of memory cells to store the predetermined number of data groups at the predetermined number of bits per memory cell, using a mapping between the threshold voltage levels and the bit value combinations that is in accordance with a Gray code. As result, the reliability of retrieving data from the memory cells is improved.

[0052] FIG. 2 illustrates an integrated circuit memory device having a programming manager configured to program threshold voltages of memory cells to store data according to one embodiment. For example, the memory devices **130** in the memory sub-system **110** of FIG. 1 can be implemented using the integrated circuit memory device **130** of FIG. 2.

[0053] The integrated circuit memory device **130** can be enclosed in a single integrated circuit package. The integrated circuit memory device **130** includes multiple groups **131**, . . . , **133** of memory cells that can be formed in one or more integrated circuit dies. A typical memory cell in a group **131** (or group **133**) can be programmed to store one or more bits of data.

[0054] Some of the memory cells in the integrated circuit memory device **130** can be configured to be operated together for a particular type of operations. For example, memory cells on an integrated circuit die can be organized in planes, blocks, and pages. A plane contains multiple blocks; a block contains multiple pages; and a page can have multiple strings of memory cells. For

example, an integrated circuit die can be the smallest unit that can independently execute commands or report status; identical, concurrent operations can be executed in parallel on multiple planes in an integrated circuit die; a block can be the smallest unit to perform an erase operation; and a page can be the smallest unit to perform a data program operation (to write data into memory cells). Each string has its memory cells connected to a common bitline; and the control gates of the memory cells at the same positions in the strings in a block or page are connected to a common wordline. Control signals can be applied to wordlines and bitlines to address the individual memory cells.

[0055] The integrated circuit memory device **130** has a communication interface **147** to receive a command having an address **135** from the controller **115** of a memory sub-system **110**, retrieve memory data **144** from memory cells identified by the memory address **135**, and provide at least the memory data **144** as part of a response to the command. Optionally, the memory device **130** may decode the memory data **144** (e.g., using an error-correcting code (ECC) technique) and provide the decoded data as part of a response to the command. An address decoder **141** of the integrated circuit memory device **130** converts the address **135** into control signals to select a group of memory cells in the integrated circuit memory device **130**; and a read/write circuit **143** of the integrated circuit memory device **130** performs operations to determine the memory data **144** stored in the memory cells at the address **135**.

[0056] The integrated circuit memory device **130** has a set of latches **145** to hold memory data **144** temporarily while the read/write circuit **143** is programming the threshold voltages of a memory cell group (e.g., **131** or **133**). For example, the read/write circuit **143** can program the threshold voltages of memory cells in a memory cell group **131** to store N bits per memory cell. The memory cell group (e.g., **131** or **133**) has M memory cells. The latches **145** are configured to store N.Math.M bits of data in the form of N data groups. Each of the data group has M bits of data to be stored respectively into M memory cells in the memory cell group (e.g., **131** or **133**).

[0057] When the latches **145** have N data groups to be stored into a memory cell group (e.g., **131**), the programming manager **113** is configured to determine and program threshold voltage levels of memory cells in the memory cell group (e.g., **131**). The threshold voltage levels are according to the values of bits in the memory data **144** and a Gray code that maps bit value combinations to threshold levels, such that any two combinations of bit values represented by two successive threshold levels differ by and only by one bit.

[0058] In one embodiment, when the memory device **130** receives N-1 data groups for storing in a memory cell group (e.g., **131**), the programming manager **113** generates the Nth data group by applying XOR (or XNOR) on the N-1 data groups. Since the programming manager **113** programs the threshold voltages of the memory cell group (e.g., **131**) according to the Gray code, the threshold voltages of the memory cells in the group (e.g., **131**) are automatically optimized for high reliability, as illustrated in the example of FIG. 6.

[0059] In another embodiment, the programming manager **113** implement in the controller **115** of the memory sub-system **110** is configured to generate the Nth data group such that N groups of data, provided in the latches **145** for storing into the memory cell group (e.g., **131**), are related to each other through XOR (or XNOR). In such a scenario, it is not necessary for the read/write circuit **143** to be aware of the generation of the Nth data group, or the relation among the N data groups. The memory device **130** can program the N XOR-related (or XNOR-related) groups of data in the latches **145** in the same way N independent groups of data are programmed. By programming the N data group generated by the controller **115** of the memory sub-system **110** to have the XOR/XNOR relation, the reliability of retrieving data from the memory cell group (e.g., **131**) is automatically improved, as illustrated in the example of FIG. 6.

[0060] In a further embodiment, a programming manager **113** implemented in the host system **120** is configured to generate the N data groups that are related to each other via XOR or XNOR. When such a set of N data groups is provided into the latches **145** as memory data **144** for programming

into a memory cell group (e.g., **131** or **133**) according to a Gray code, the reliability of retrieving data from the memory cell group (e.g., **131**) is automatically improved.

[0061] FIG. **3** shows an example of programming memory cells to store multiple bits per memory cell according to one embodiment. For example, the example of FIG. **3** can be implemented in the memory device **130** of FIG. **1** and/or FIG. **2**.

[0062] In FIG. **3**, a memory cell group **131** has memory cells **137**, . . . , **139**. A number of data groups **151**, **157**, . . . , **159** provide data bits to be stored into the memory cells **137**, . . . , **139**. The number of bits provided in each data group (e.g., **157**, **159**, or **151**) equals to the number of memory cells **137** to **139** in the memory cell group **131**. Each memory cell (e.g., **139** or **137**) stores a set of bits, one from each of the data groups **151**, **157**, . . . , and **159**.

[0063] For example, the data bits **161**, **163**, . . . , **165** from the data groups **151**, **157**, . . . , **159** are stored into one memory cell **137**; and the voltage threshold of the memory cell **137** is programmed by the read/write circuit **143** at a level that represents the values of the data bits **161**, **163**, . . . , **165**. Similarly, the data bits **171**, **173**, . . . , **175** from the data groups **151**, **157**, . . . , **159** are stored into another memory cell **139** and represented by the level of the voltage threshold of the memory cell **139**.

[0064] Optionally, the data bits in a data group can be organized in codeword **153**, . . . codeword **155** according to an error detection and data recovery technique, such as error correction code (ECC), low-density parity-check (LDPC) code, etc.

[0065] For example, a codeword **153** in the data group **151** can include data bit **161** to data bit **162**. When one of data bit in the codeword **153** is in error, the error can be detected and corrected (e.g., using a technique of low-density parity-check (LDPC)).

[0066] When the data groups **151**, **157**, . . . , **159** are stored in the latches **181**, **183**, . . . , **185**, the read/write circuit **143** can program **149** thresholds of the memory cells **137**, . . . , **139** such that the voltage thresholds of the memory cells **137**, . . . , **139** represent the values of the respective data bits from the data groups **151**, **157**, . . . , **159**.

[0067] A combination of the values of the data bits (e.g., **161**, **163**, . . . , **165**) to be stored in a memory cell (e.g., **137**) is mapped to the level of a voltage threshold of the memory cell (e.g., **137**) based on a Gray code. For example, a read/write circuit **143** can include a table of a Gray code (e.g., as illustrated by the table of FIG. **6**) to map between the values of a set of bits (e.g., **161**, **163**, . . . , **165**) of a memory cell (e.g., **137**) and a threshold level of the memory cell (e.g., **137**) that represents the values of the set of bits (e.g., **161**, **163**, . . . , **165**).

[0068] When it is desirable to store a reduced number of data groups (e.g., **157** to **159**) in the memory cell group **131**, an extra data group (e.g., **151**) can be computed based on an XOR (or XNOR) operation, such that the reliability of the memory data **144** stored in the memory cells (e.g., **137** to **139**) in the form of their programmed voltage thresholds according to a Gray code is automatically improved and/or optimized.

[0069] FIGS. **4** and **5** illustrate techniques generate a data group for programming memory cells at threshold levels determined by a Gray code for improved reliability according to some embodiments.

[0070] In FIG. **4**, data bit **161** is calculated by applying XOR operation **201** to data bits **163** to **165**. For example, after computing the result of exclusive or of two of the data bits **163** to **165**, an updated result can be obtained from the exclusive or of the result and another of the data bits **163** to **165** until all of the data bits **163** to **165** have participated in the exclusive or computations once. As a result, data bits **161**, **163**, . . . , **165** form an exclusive or relation, where any of the data bit (e.g., **161** or **163**) is equal to the result of applying XOR operation **201** to the other data bits.

[0071] For example, to store data groups **157** to **159** into a memory cell group **131** using the read/write circuit **143** of FIG. **3**, an extra data group **151** is calculated from the exclusive or of the data groups **151**, **157** to **159**. Each data bit (e.g., **161**) in the data group **151** is obtained by applying XOR operation **201** the corresponding data bits (e.g., **163**, . . . , **165**) in the given data groups **157**, .

... , **159**.

[0072] As a result, each codeword (e.g., **153**) in the data group **151** is also the result of bitwise exclusive or of the corresponding codewords in the given data groups **157**, ... , **159**; and the codewords in the data groups **151**, **157**, ... , **159** form the exclusive or relation, where any codeword in a data group (e.g., **157**) is equal to the exclusive or of the corresponding codeword from the remaining data groups (e.g., **151**, **159**, ...). Such a property/relation can be used to recover a codeword in a data group when the codeword fails to decode in ECC/LDPC operations.

[0073] FIG. 4 illustrates an example of using XOR operation **201** to generate an extra data group **151**. Similarly, FIG. 5 illustrates another example of using XNOR operation **202** to generate an extra data group **151**. The extra data group **151** computed using XNOR operation **202** is equal to the bitwise not of the corresponding data group **151** computed using XNOR operation **202**. When the XNOR operation **202** is used to generate the extra data group **151**, the codewords in the data groups **151**, **157**, ... , **159** form the XNOR relation, where any codeword in a data group (e.g., **157**) is equal to the XNOR of the corresponding codeword from the remaining data groups (e.g., **151**, **159**, ...). Such a property/relation can also be used to recover a codeword in a data group when the codeword fails to decode in ECC/LDPC operations.

[0074] In FIGS. 4 and 5, the set of data bits **161**, **163**, ... , **165** having the XOR or XNOR relation is used in Gray code based mapping **203** to determine threshold level **205** to be programmed for a memory cell **137**. After threshold programming **207** of the memory cell **137** to reach the threshold level **205**, the memory cell **137** has a threshold voltage **209** that can be detected/tested via the read/write circuit **143**; and the values of the data bits **161**, **163**, ... , **165** can be determined/inferred from the threshold voltage **209** of the memory cell **137**.

[0075] The XOR or XNOR relation among the data groups **151**, **157**, ... , **159** not only allows the recovery of a failed codeword in a data group from other data groups, but also improves the reliability of determining of the threshold levels (e.g., **205**) of the memory cells (e.g., **137**) and thus the reading of the memory data **144** represented by the programmed threshold voltages (e.g., **209**), as further illustrated in FIG. 6.

[0076] FIG. 6 illustrates reliability improvements in reading data programmed using techniques of FIGS. 4 and 5.

[0077] FIG. 6 illustrates an example of data programming in a QLC mode where the threshold voltage of a memory cell (e.g., **137**) is programmed to represent the values of four bits. A page of memory cells is programmed (written into) together. Since each cell stores four bits, the page of memory cells can store four data pages of data bits, where the number of data bits in a data page is equal to the number of memory cells in a memory cell page. For example, each data page is an example of a data group illustrated in FIG. 3; and the memory cell page is an example of a memory cell group illustrated in FIG. 3.

[0078] Conventionally and/or for convenience, the four data pages for a QLC mode are named as lower page (LP), upper page (UP), extra page (XP), and top page (TP) respectively. A memory cell (e.g., **137**) stores one bit from each of the four pages. Since the values of the four bits stored in a memory cell (e.g., **137**) has 16 different combinations, as illustrated in the table shown in FIG. 6, the threshold voltage **209** of the memory cell (e.g., **137**) is programmed to one of 16 threshold levels to represent a corresponding combinations of bit values.

[0079] The table shown in FIG. 6 illustrates an example Gray code that maps between the values of the four bits (e.g., **161**, **163**, ... , **165**) stored in a QLC memory cell (e.g., **137**) and the threshold level **205** of the memory cell (e.g., **137**). For example, when the memory cell (e.g., **137**) is determined to have a threshold level of 0, the memory cell (e.g., **137**) is considered to store 1 as the TP bit, 1 as the XP bit, 1 as the UP bit, and 1 as the LP bit. Similarly, to store 0, 1, 1, and 1 as TP, XP, UP and LP bits in the memory cell (e.g., **137**), the threshold voltage is programmed to level 1. An increasing threshold level represents an increasing threshold voltage **209** to be programmed for the memory cell (e.g., **137**).

[0080] A Gray code (e.g., as illustrated in the table of FIG. 6) has the characteristics/propriety where one and only one bit value changes between two successive threshold levels. For example, when threshold level changes from 0 to 1, only the TP bit changes from 1 to 0 in the table of FIG. 6. Similarly, when threshold level changes between 1 and 2 (or, 2 and 3, 3 and 4, 4 and 5, etc.), only the LP bit changes (or, the TP bit, the UP bit, the TP bit, etc. respectively).

[0081] In general, different Gray codes can be used to map the combinations of bit values to threshold levels. For example, by inverting the bits in the table of FIG. 6, we obtain an alternative Gray code for mapping bit values to threshold levels. The techniques of the present disclosures are not limited to the use of a particular Gray code.

[0082] In generally, after the read/write circuit 143 completes its operation to program the threshold voltage 209 of a memory cell 137 according to a threshold level 205, the threshold voltage 209 of the memory cell 137 may not be at an exact predetermined voltage. After the threshold programming 207, the threshold voltage 209 of the memory cell 137 is most likely at a predetermined voltage, with reduced probability at other voltages away from the predetermined voltage.

[0083] For example, when the memory cell 137 is programmed to threshold level 0, the threshold voltage 209 of the memory cell 137 being at the voltage $V_{sub.0}$ has the highest probability. The probability distribution of the threshold voltage 209 of the memory cell 137 being at voltages near $V_{sub.0}$ is illustrated by the curve 211.

[0084] Similarly, the probability distribution of the threshold voltage 209 of the memory cell 137 being at voltages near $V_{sub.1}$ when the memory cell 137 is programmed to threshold level 1 is illustrated by the curve 213.

[0085] In the voltage region 219, the probability distribution curve 211 and curve 213 overlap with each other, which indicates that when the threshold voltage 209 of the memory cell 137 is found to be within the region 219, there is an ambiguity as to whether the memory cell 137 is programmed at threshold level 0 to represent one set of bit values, or at threshold level 1 to represent another set of bit values. Since the bit values represented by threshold level 0 and threshold level 1 differ by one bit (e.g., TP bit when the Gray code as illustrated in the table of FIG. 6 is used), there is a small probability that this bit, determined based on the threshold voltage of the memory cell 137, is read incorrectly. An error in such a bit can be typically detected and corrected via ECC/LDPC decoding of a codeword (e.g., 153) in a data group (e.g., 151) that contains the bit.

[0086] When the TP, XP, UP and LP bits are known to have an XOR relation, the combination of bit values corresponding to threshold level 1 in the table of FIG. 6 is not possible. For example, the combination of bit values corresponding to threshold level 1 does not have the XOR relation and thus is eliminated from a possible data item given for storing in the memory cell 137. Thus, the closest distribution curve 215 to the curve 211 is for threshold level 2 and is better separated from the curve 211 by a wide margin in voltage threshold. This reduces/eliminates the probability of reading error when the threshold voltage of the memory cell 137 is found to be in the voltage region 219. Similarly, the use of a Gray code and the XOR relation eliminates the combinations of bit values corresponding to other odd numbered threshold levels (e.g., 3, 5, . . . , 15). Thus, the possible distribution curves 211, 215, etc., are well separated for improved data reliability.

[0087] Similarly, when the TP, XP, UP and LP bits are configured to have an XNOR relation, the combinations of bit values corresponding to even threshold levels (e.g., 0, 2, . . . , 14) are eliminated. Thus, the possible distribution curves 213, 217, etc., are also well separated for improved data reliability.

[0088] Therefore, FIG. 6 shows that, by configuring the TP, XP, UP and LP bits to have an XOR or XNOR relation, the reliability of retrieving the TP, XP, UP and LP bits through the determination of the level of the threshold voltage 209 of the memory cell 137 is improved.

[0089] In general, the separation of distribution curves can be achieved with any Gray code for data bits having an XOR relation or an XNOR relation. Thus, the improvement is not limited to the use

of a particular Gray code illustrated in the table of FIG. 6. Further, the separation is not limited to QLC memory cells. For example, the technique can be applied to TLC memory cells, or PLC memory cells.

[0090] The threshold voltages of memory cells can change due to a number of factors, such as charge loss, read disturb, cross-temperature effect (e.g., write and read at different operating temperatures). Such changes and/or other factors can cause errors in reading the memory cells. Such errors can typically be discovered and/or corrected during the decoding of a codeword using ECC/LDPC techniques. However, when a codeword fails to decode, the XOR relation (or the XNOR relation) can be used to recover the codeword in a way as illustrated in FIG. 7.

[0091] FIG. 7 shows a technique to recover data retrieved from memory cells programmed using the techniques of FIGS. 4 and 5.

[0092] In FIG. 7, one of the codewords **153**, **154**, . . . , and **156** can encounter a failure **223** during the operation of decoding **221** using ECC/LDPC techniques, after the codewords are read from the memory cell group **131**. For example, a codeword **154** may fail to decode. Since the codewords **153**, **154**, . . . , **156** correspond to respective codewords in the data groups **151**, **157**, . . . , **159** that have an XOR (or XNOR) relation, a replacement of the codeword **154** can be found during recovery **225** by applying the corresponding operation **210** (e.g., XOR or XNOR) to the remaining codewords **153** to **156**.

[0093] In an example, a method is provided to write data into memory cells according to some embodiments. The methods can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software/firmware (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the method is performed at least in part by the controller **115** of FIG. 1, or processing logic in the memory device **130** of FIG. 2. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0094] For example, the methods can be performed in a memory sub-system **110** illustrated in FIG. 1 using an integrated circuit memory device **130** of FIG. 2 with data programming techniques of FIGS. 3 to 7.

[0095] In the method, first groups (e.g., **157**, . . . , **159**) of data bits (e.g., **163**, . . . , **173**, **165**, . . . , **175**) are received for storing into a memory cell group (e.g., **131**) of a memory device **130**. The memory device **130** can program more groups of data bits into the memory cell group (e.g., **131**) than the first groups (e.g., **157**, . . . , **159**).

[0096] In the method, a second group (e.g., **151**) of data bits (e.g., **161**, . . . , **162**, . . . , **171**) is generated from the first groups (e.g., **157**, . . . , **159**) to form a plurality of data groups (e.g., **151**, **157**, . . . , **159**). The plurality of data groups (e.g., **151**, **157**, . . . , **159**) includes the first groups (e.g., **157**, . . . , **159**) and the second group (e.g., **151**) and has a predetermined relation among the data groups (e.g., **151**, **157**, . . . , **159**).

[0097] For example, the predetermined relation can be an XOR relation such that any of the data groups (e.g., **151**, **157**, . . . , **159**) is equal to the XOR of the remaining groups. Alternatively, the predetermined relation can be an XNOR relation such that any of the data groups (e.g., **151**, **157**, . . . , **159**) is equal to the XNOR of the remaining groups.

[0098] Each respective data bit (e.g., **161**) in the second group (e.g., **151**) can be based on exclusive or (XOR) of a data bit set (e.g., **163**, . . . , **165**) having a data bit from each of the first groups (e.g., **157**, . . . , **159**).

[0099] For example, the respective data bit (e.g., **161**) is equal to, and/or be calculated from,

exclusive or (XOR) of data bits (e.g., **163**, . . . , **165**) in the data bit set having a data bit from each of the first groups (e.g., **157**, . . . , **159**).

[0100] Alternatively, the respective data bit (e.g., **161**) is equal to the inverse of exclusive or (XOR) of data bits (e.g., **163**, . . . , **165**) in the data bit set having a data bit from each of the first groups (e.g., **157**, . . . , **159**). For example, the respective data bit (e.g., **161**) can be computed as the XNOR of the data bits (e.g., **163**, . . . , **165**) in the data bit set having a data bit from each of the first groups (e.g., **157**, . . . , **159**).

[0101] For example, the second group (e.g., **151**) can be generated from bitwise XOR, or bitwise XNOR, of the first groups (e.g., **157**, . . . , **159**).

[0102] In the method, the memory device **130** determines threshold levels (e.g., **205**) of a memory cell group (e.g., **131**) based on a predetermined mapping between bit value combinations and threshold levels (e.g., as illustrated via the Gray code shown in the table of FIG. **6**). Each respective memory cell in the group of memory cells is determined to have a respective threshold level representing a bit value combination with one bit from each of the plurality of data group; and values of data bits represented by any two successive threshold levels in the predetermined mapping differ by and only by one bit, as in a Gray code (also known as a reflected binary code).

[0103] In the method, the memory device **130** programs threshold voltages (e.g., **209**) of memory cells (e.g., **137**) in the memory cell group (e.g., **131**) according to the threshold levels (e.g., **205**) determined by the predetermined mapping to store the plurality of data groups (e.g., **151**, **157**, . . . , **159**).

[0104] For example, by generating the second group (e.g., **151**) from three first groups (e.g., **157**, . . . , **159**), the threshold voltages (e.g., **209**) of the memory cells (e.g., **137**) in the memory cell group (e.g., **131**) can be programmed in a quad-level cell (QLC) mode to store four bits per memory cell with high reliability.

[0105] In general, XOR or XNOR can be used to generate an Nth data group from N-1 data groups to store the N data groups in a memory cell group with N bits per memory cell.

[0106] As an example, the plurality of data groups can include a third group (e.g., **157**) and fourth groups (e.g., **151**, **159**, . . .). When the memory data **144** is retrieved from the memory cell group **131** based on testing the threshold voltages of memory cells (e.g., **137**) in the memory cell group (e.g., **131**), the third group (e.g., **157**) can include a first codeword (**154**) in the third group (e.g., **157**) that fails to decode in an ECC/LDPC decoder. In response, second codewords (e.g., **153**, . . . , **156**) in the fourth groups (e.g., **151**, **159**, . . .) can be used to compute a replacement version of the first codeword (**154**).

[0107] A memory sub-system can have a data integrity classifier configured to determine an error rate classification of data retrieved from memory cells, which allows the memory sub-system to dynamically adjust error detection and recovery operations based on the error rate classification.

[0108] An integrated circuit memory cell (e.g., a flash memory cell) can be programmed to store data by the way of its state at a threshold voltage. For example, if the memory cell is configured/programmed in a state that allows a substantial current to pass the memory cell at the threshold voltage, the memory cell is storing a bit of one; and otherwise, the memory cell is storing a bit of zero. Further, a memory cell can store multiple bits of data by being configured/programmed differently at multiple threshold voltages. For example, the memory cell can store multiple bits of data by having a combination of states at the multiple threshold voltages; and different combinations of the states of the memory cell at the threshold voltages can be interpreted to represent different states of bits of data that is stored in the memory cell.

[0109] However, after the states of integrated circuit memory cells are configured/programmed using write operations to store data in the memory cells, the optimized threshold voltage for reading the memory cells can shift due to a number of factors, such as charge loss, read disturb, cross-temperature effect (e.g., write and read at different operating temperatures), etc., especially when a memory cell is programmed to store multiple bits of data.

[0110] Data can be encoded with redundancy information to facilitate error detection and recovery. When data encoded with redundancy information is stored in a memory sub-system, the memory sub-system can detect errors in raw, encoded data retrieved from the memory sub-system and/or recover the original, non-encoded data that is used to generate encoded data for storing in the memory sub-system. The recovery operation can be successful (or have a high probability of success) when the raw, encoded data retrieved from the memory sub-system contains less than a threshold amount of errors, or the bit error rate in the encoded data is lower than a threshold. For example, error detection and data recovery can be performed using techniques such as error correction code (ECC), low-density parity-check (LDPC) code, etc.

[0111] Some error detection and data recovery operations can be successful in identifying error-free results with the encoded data having a relatively large amount of errors at the cost of a relatively large amount of power consumption and/or a relatively long computing time. Other error detection and data recovery operations can recover a relatively small amount of errors with less power consumption and/or a short computing time.

[0112] Conventional calibration circuitry has been used to self-calibrate a memory region in applying read level signals to account for shift of threshold voltages of memory cells within the memory region. During the calibration, the calibration circuitry is configured to apply different test signals to the memory region to count the numbers of memory cells that output a specified data state for the test signals. Based on the counts, the calibration circuitry determines a read level offset value as a response to a calibration command.

[0113] At least some aspects of the present disclosure address the above and other deficiencies by dynamically configuring error detection and data recovery operations based on a data integrity classification, or a bit error rate classification, generated from signal and noise characteristics measured by a memory device for memory cells in the memory device.

[0114] For example, a predictive model can be generated through machine learning to classify or predict the error rate in the raw data received from a set of memory cells. The classification can be generated by the predictive model based on signal and noise characteristics measured by the memory device during the reading of the raw data from the memory cells in the memory device. When the error rate is classified to be in a low category, the memory sub-system uses a low power ECC decoder and/or skip ECC decoding. When the error rate is classified to be in a high category, the memory sub-system uses a high power ECC decoder. For example, the high power ECC decoder can use not only the hard bit data but also soft bit data in recovering error-free original data being stored in the memory cells. For example, the hard bit data is the encoded data read from the memory cells at optimized, or controller-specified, read voltages; and the soft bit data is the encoded data read at voltages having predetermined offsets from the optimized, or controller-specified read voltages.

[0115] For example, counts measured by calibration circuitry and/or its associated data can be used as the signal and noise characteristics for the predictive model. Further, such signal and noise characteristics can be measured for sub-regions in parallel to reduce the total time for measuring the signal and noise characteristics.

[0116] The controller **115** can include a data integrity classifier **313** that can use the signal and noise characteristics measured by the memory devices **130** for memory cells to classify, predict, estimate, or determine the degree of error rate in raw data retrieved from the memory cells. In some embodiments, the controller **115** in the memory sub-system **110** includes at least a portion of the data integrity classifier **313**. In other embodiments, or in combination, the controller **116** and/or the processing device **118** in the host system **120** includes at least a portion of the data integrity classifier **313**. For example, the controller **115**, the controller **116**, and/or the processing device **118** can include logic circuitry implementing the data integrity classifier **313**. For example, the controller **115**, or the processing device **118** (processor) of the host system **120**, can be configured to execute instructions stored in memory for performing the operations of the data integrity

classifier **313** described herein. In some embodiments, the data integrity classifier **313** is implemented in an integrated circuit chip disposed in the memory sub-system **110**. In other embodiments, the data integrity classifier **313** can be part of firmware of the memory sub-system **110**, an operating system of the host system **120**, a device driver, or an application, or any combination therein.

[0117] The data integrity classifier **313** can receive signal and noise characteristics measured and provided by a memory device **130** for the memory cells in the memory device **130** and process the signal and noise characteristics to generate a classification that is indicative of the level of errors in the raw data retrieved from memory cells in the memory device **130**. Based on the classification, the controller **115** can dynamically adjust the error detection and recovery operations to improve the performance of the memory sub-system **110** (e.g., with reduced power consumption, and/or reduced latency in read operations).

[0118] The integrated circuit memory device **130** has a calibration circuit **345** configured to determine measurements of signal and noise characteristics **339** of memory cells in a group (e.g., **131**, . . . , or **133**) and provide the signal and noise characteristics **339** to the controller **115** of a memory sub-system **110** via the communication interface **147**.

[0119] In at least some embodiments, the calibration circuit **345** also provides, to the controller **115** via the communication interface **147**, the signal and noise characteristics **339** measured to determine the read level offset value. In some embodiments, the read level offset value can be used to understand, quantify, or estimate the signal and noise characteristics **339**. In other embodiments, the statistics of memory cells in a group or region that has a particular state at one or more test voltages can be provided as the signal and noise characteristics **339**.

[0120] For example, the calibration circuit **345** can measure the signal and noise characteristics **339** by reading different responses from the memory cells in a group (e.g., **131**, . . . , **133**) by varying operating parameters used to read the memory cells, such as the voltage(s) applied during an operation to read data from memory cells.

[0121] For example, the calibration circuit **345** can measure the signal and noise characteristics **339** on the fly when executing a command to read the memory data **337** from the address **135**. Since the signal and noise characteristics **339** is measured as part of the operation to read the memory data **337** from the address **135**, the signal and noise characteristics **339** can be provided from the integrated circuit memory device **130** to the controller **115** with reduced or no penalty on the latency in the execution of the command to read the memory data **337** from the address **135**.

[0122] The data integrity classifier **313** of the controller **115** of the memory sub-system **110** is configured to use the signal and noise characteristics **339** to generate an error rate classification of the memory data **337**.

[0123] For example, the data integrity classifier **313** can use a predictive model, trained via machine learning, to predict the likelihood of the memory data **337** retrieved from a memory cell group (e.g., **131** or **133**) failing a test of data integrity. For example, when the memory data **337** fails to decode, it fails the test of data integrity. The prediction can be actually made based on the signal and noise characteristics **339**. Before the test is made using error-correcting code (ECC) and/or low-density parity-check (LDPC) code, or even before the memory data **337** is transferred to a decoder, the data integrity classifier **313** uses the signal and noise characteristics **339** to predict the result of the test. Based on the predicted result of the test, an optimized operation can be selected and performed for error detection and/or recovery with reduced power consumption and/or latency.

[0124] For example, based on the predicted result, one of several conditional paths for the processing of the memory data **337** can be taken.

[0125] For example, in one conditional path, when the memory data **337** is classified in a category of likely to fail the test (e.g., for having a high error rate), the memory data **337** can be discarded; and the memory device **130** can be instructed to retry reading the memory data **337** from the

address with a further optimized read voltage.

[0126] For example, in another conditional path, when the memory data **337** is classified in a category of likely to pass the test (e.g., for having a low error rate), the memory data **337** can be passed to a decoder that uses the hard bit data to provide the original data that is encoded to be stored in the memory device **130**.

[0127] For example, in further conditional path, when the memory data **337** is classified in a category of likely to need soft bit data to pass the test (e.g., for having a middle error rate), the memory data **337** can be passed to a decoder that uses both the hard bit data and the soft bit data to recover the original data that is encoded to be stored in the memory device **130**. If the soft bit data is not already available, the memory device **130** can be instructed to read the soft bit data to supplement the memory data **337** for the decoder.

[0128] Thus, when the predictive model predicts a failure, the memory sub-system **110** can initiate the read retry or read calibration without having to wait for the completion of the ECC and/or LDPC operations; and the memory sub-system **110** can skip the transfer of the data to be coded, skip the decoding operation, and/or abort the ongoing decoding operation. As a result, the overall performance of the memory sub-system **110** is improved.

[0129] The predictive model can be configured to use the signal and noise characteristics **339** of a memory cell group (e.g., **131** or **133**) measured by the calibration circuit **345** during the read operation performed on the memory cell group (e.g., **131** or **133**). For example, the predictive model can be pre-trained using data collected from similar memory devices and optionally further trained in the field for the memory sub-system via reinforcement learning based on the results of ECC and/or LDPC operations. For example, when the prediction result is different from the actual test result generated from ECC and/or LDPC operations, a reinforcement learning technique can be applied to train the predictive model to generate a prediction that matches with the actual test result.

[0130] Optionally, the predictive model and/or the data integrity classifier **313** can be configured on the memory device **130**. When an ECC and/or LDPC failure is predicted, the memory device **130** can suggest read-retry to the controller **115** and predictively initiate the read retry without having to wait for a confirmation from the controller **115**. Such a predictive operation to initiate the read retry can reduce the latency of read retry and improve the performance of the memory sub-system **110**.

[0131] In general, the data integrity classifier **313** can be implemented in the controller **115** and/or the memory devices **130**. The prediction generated by the data integrity classifier **313** based on signal and noise characteristics can be used to initiate various processing paths where each path can be configured as an atomic operation. For example, a read-retry can be executed immediately be prior to another command occupying the die in which the memory cell group (e.g., **131** or **133**) is formed.

[0132] For example, based on the signal and noise characteristics **339**, the data integrity classifier **313** can use its predictive model to classify the bit error rate in the retrieved raw memory data **337** as low, medium, or high. If the classified bit error rate is low, the raw memory data **337** can be transferred to an LDPC decoder that operates on hard bit data. Such an LDPC decoder has relatively low complexity and correction capability. In some implementations, multiple decoders can be provided to decode the hard bit data without using soft bit data; the decoders can have different correction capabilities and power consumption; and the classified bit error rate can be further used to select one of the decoders that is likely to be successful in decoding the hard bit data with least power consumption. If the classified bit error rate is medium, the memory device **130** can immediately start to read the soft bit data; and another LDPC decoder that operates on hard bit data and soft bit data can be used.

[0133] If the classified bit error rate is high, the memory device **130** can immediately start to read-retry, and/or automatic read calibration with a read of both hard bit data and soft bit data to use an

LDPC decoder that has relatively high complexity and correction capability.

[0134] In some embodiments, the data integrity classifier **313** generates not only a classification of the bit error rate of the memory data **337** but also a confidence level indicator of the classification being correct. The confidence level indicator can also be used in the selection of a path from multiple conditional processing paths.

[0135] FIG. **8** shows an example of measuring signal and noise characteristics **339** to improve memory operations according to one embodiment.

[0136] In FIG. **8**, the calibration circuit **345** applies different read voltages $V_{\text{sub.A}}$, $V_{\text{sub.B}}$, $V_{\text{sub.C}}$, $V_{\text{sub.D}}$, and $V_{\text{sub.E}}$ to read the states of memory cells in a group (e.g., **131**, . . . , or **133**). In general, more or less read voltages can be used to generate the signal and noise characteristics **339**.

[0137] As a result of the different voltages applied during the read operation, a same memory cell in the group (e.g., **131**, . . . , or **133**) may show different states. Thus, the counts $C_{\text{sub.A}}$, $C_{\text{sub.B}}$, $C_{\text{sub.C}}$, $C_{\text{sub.D}}$, and $C_{\text{sub.E}}$ of memory cells having a predetermined state at different read voltages $V_{\text{sub.A}}$, $V_{\text{sub.B}}$, $V_{\text{sub.C}}$, $V_{\text{sub.D}}$, and $V_{\text{sub.E}}$ can be different in general. The predetermined state can be a state of having substantial current passing through the memory cells, or a state of having no substantial current passing through the memory cells. The counts $C_{\text{sub.A}}$, $C_{\text{sub.B}}$, $C_{\text{sub.C}}$, $C_{\text{sub.D}}$, and $C_{\text{sub.E}}$ can be referred to as bit counts.

[0138] The calibration circuit **345** can measure the bit counts by applying the read voltages $V_{\text{sub.A}}$, $V_{\text{sub.B}}$, $V_{\text{sub.C}}$, $V_{\text{sub.D}}$, and $V_{\text{sub.E}}$ one at a time on the group (e.g., **131**, . . . , or **133**) of memory cells.

[0139] Alternatively, the group (e.g., **131**, . . . , or **133**) of memory cells can be configured as multiple subgroups; and the calibration circuit **345** can measure the bit counts of the subgroups in parallel by applying the read voltages $V_{\text{sub.A}}$, $V_{\text{sub.B}}$, $V_{\text{sub.C}}$, $V_{\text{sub.D}}$, and $V_{\text{sub.E}}$. The bit counts of the subgroups are considered as representative of the bit counts in the entire group (e.g., **131**, . . . , or **133**). Thus, the time duration of obtaining the counts $C_{\text{sub.A}}$, $C_{\text{sub.B}}$, $C_{\text{sub.C}}$, $C_{\text{sub.D}}$, and $C_{\text{sub.E}}$ can be reduced.

[0140] In some embodiments, the bit counts $C_{\text{sub.A}}$, $C_{\text{sub.B}}$, $C_{\text{sub.C}}$, $C_{\text{sub.D}}$, and $C_{\text{sub.E}}$ are measured during the execution of a command to read the memory data **337** from the address **135** that is mapped to one or more memory cells in the group (e.g., **131**, . . . , or **133**). Thus, the controller **115** does not need to send a separate command to request for the signal and noise characteristics **339** that is based on the bit counts $C_{\text{sub.A}}$, $C_{\text{sub.B}}$, $C_{\text{sub.C}}$, $C_{\text{sub.D}}$, and $C_{\text{sub.E}}$.

[0141] The differences between the bit counts of the adjacent voltages are indicative of the errors in reading the states of the memory cells in the group (e.g., **131**, . . . , or **133**).

[0142] For example, the count difference $D_{\text{sub.A}}$ is calculated from $C_{\text{sub.A}} - C_{\text{sub.B}}$, which is an indication of read threshold error introduced by changing the read voltage from $V_{\text{sub.A}}$ to $V_{\text{sub.B}}$. Similarly, $D_{\text{sub.B}} = C_{\text{sub.B}} - C_{\text{sub.C}}$; $D_{\text{sub.C}} = C_{\text{sub.C}} - C_{\text{sub.D}}$; and $D_{\text{sub.D}} = C_{\text{sub.D}} - C_{\text{sub.E}}$.

[0143] The curve **357**, obtained based on the count differences $D_{\text{sub.A}}$, $D_{\text{sub.B}}$, $D_{\text{sub.C}}$, and $D_{\text{sub.D}}$, represents the prediction of read threshold error E as a function of the read voltage. From the curve **357** (and/or the count differences), the optimized read voltage $V_{\text{sub.O}}$ (**351**) can be calculated as the point **353** that provides the lowest read threshold error $D_{\text{sub.MIN}}$ (**355**) on the curve **357**.

[0144] In one embodiment, the calibration circuit **345** computes the optimized read voltage $V_{\text{sub.O}}$ and causes the read/write circuit **143** to read the memory data **337** from the address **135** using the optimized read voltage $V_{\text{sub.O}}$.

[0145] Alternatively, the calibration circuit **345** can provide, via the communication interface **147** to the controller **115** of the memory sub-system **110**, the count differences $D_{\text{sub.A}}$, $D_{\text{sub.B}}$, $D_{\text{sub.C}}$, and $D_{\text{sub.D}}$ and/or the optimized read voltage $V_{\text{sub.O}}$ calculated by the calibration circuit **345**.

[0146] FIG. **8** illustrates an example of generating a set of statistical data (e.g., bit counts and/or

count differences) for reading at an optimized read voltage $V_{sub.O}$. In general, a group of memory cells can be configured to store more than one bit in a memory cell; and multiple read voltages are used to read the data stored in the memory cells. A set of statistical data can be similarly measured for each of the read voltages to identify the corresponding optimize read voltage, where the test voltages in each set of statistical data are configured in the vicinity of the expected location of the corresponding optimized read voltage. Thus, the signal and noise characteristics **339** measured for a memory cell group (e.g., **131** or **133**) can include multiple sets of statistical data measured for the multiple threshold voltages respectively.

[0147] For example, the controller **115** can instruct the memory device **130** to perform a read operation by providing an address **135** and at least one read control parameter. For example, the read control parameter can be a suggested read voltage.

[0148] The memory device **130** can perform the read operation by determining the states of memory cells at the address **135** at a read voltage and provide the memory data **337** according to the determined states.

[0149] During the read operation, the calibration circuit **345** of the memory device **130** generates the signal and noise characteristics **339**. The memory data **337** and the signal and noise characteristics **339** are provided from the memory device **130** to the controller **115** as a response. Alternatively, the processing of the signal and noise characteristics **339** can be performed at least in part using logic circuitry configured in the memory device **130**. For example, the data integrity classifier **313** can be implemented partially or entirely using the processing logic configured in the memory device **130**. For example, the processing logic can be implemented using complementary metal-oxide-semiconductor (CMOS) circuitry formed under the array of memory cells on an integrated circuit die of the memory device **130**. For example, the processing logic can be formed, within the integrated circuit package of the memory device **130**, on a separate integrated circuit die that is connected to the integrated circuit die having the memory cells using through-silicon vias (TSVs) and/or other connection techniques.

[0150] The signal and noise characteristics **339** can be determined based at least in part on the read control parameter. For example, when the read control parameter is a suggested read voltage for reading the memory cells at the address **135**, the calibration circuit **345** can compute the read voltages $V_{sub.A}$, $V_{sub.B}$, $V_{sub.C}$, $V_{sub.D}$, and $V_{sub.E}$ that are in the vicinity of the suggested read voltage.

[0151] The signal and noise characteristics **339** can include the bit counts $C_{sub.A}$, $C_{sub.B}$, $C_{sub.C}$, $C_{sub.D}$, and $C_{sub.E}$. Alternatively, or in combination, the signal and noise characteristics **339** can include the count differences $D_{sub.A}$, $D_{sub.B}$, $D_{sub.C}$, and $D_{sub.D}$.

[0152] Optionally, the calibration circuit **345** uses one method to compute an optimized read voltage $V_{sub.O}$ from the count differences $D_{sub.A}$, $D_{sub.B}$, $D_{sub.C}$, and $D_{sub.D}$; and the controller **115** uses another different method to compute the optimized read voltage $V_{sub.O}$ from the signal and noise characteristics **339** and optionally other data that is not available to the calibration circuit **345**.

[0153] When the calibration circuit **345** can compute the optimized read voltage $V_{sub.O}$ from the count differences $D_{sub.A}$, $D_{sub.B}$, $D_{sub.C}$, and $D_{sub.D}$ generated during the read operation, the signal and noise characteristics can optionally include the optimized read voltage $V_{sub.O}$. Further, the memory device **130** can use the optimized read voltage $V_{sub.O}$ in determining the hard bit data in the memory data **337** from the memory cells at the address **135**. The soft bit data in the memory data **337** can be obtained by reading the memory cells with read voltages that are a predetermined offset away from the optimized read voltage $V_{sub.O}$. Alternatively, the memory device **130** uses the controller-specified read voltage provided in the read control parameter in reading the memory data **337**.

[0154] The controller **115** can be configured with more processing power than the calibration circuit **345** of the integrated circuit memory device **130**. Further, the controller **115** can have other

signal and noise characteristics applicable to the memory cells in the group (e.g., **131**, . . . , or **133**). Thus, in general, the controller **115** can compute a more accurate estimation of the optimized read voltage $V_{sub.O}$ (e.g., for a subsequent read operation, or for a retry of the read operation). [0155] In general, it is not necessary for the calibration circuit **345** to provide the signal and noise characteristics **339** in the form of a distribution of bit counts over a set of read voltages, or in the form of a distribution of count differences over a set of read voltages. For example, the calibration circuit **345** can provide the optimized read voltage $V_{sub.O}$ calculated by the calibration circuit **345**, as signal and noise characteristics **339**.

[0156] The calibration circuit **345** can be configured to generate the signal and noise characteristics **339** (e.g., the bit counts, or bit count differences) as a byproduct of a read operation. The generation of the signal and noise characteristics **339** can be implemented in the integrated circuit memory device **130** with little or no impact on the latency of the read operation in comparison with a typical read without the generation of the signal and noise characteristics **339**. Thus, the calibration circuit **345** can determine signal and noise characteristics **339** efficiently as a byproduct of performing a read operation according to a command from the controller **115** of the memory sub-system **110**. [0157] In general, the calculation of the optimized read voltage $V_{sub.O}$ can be performed within the memory device **130**, or by a controller **115** of the memory sub-system **110** that receives the signal and noise characteristics **339** as part of enriched status response from the memory device **130**.

[0158] FIG. **9** illustrates a data integrity classifier **313** determining the likelihood of data integrity failure in data retrieved from a memory device to dynamically configure the operations of error detection and recovery for the data according to one embodiment. For example, the data integrity classifier **313** can be implemented in the controller **115** of the memory sub-system **110** of FIG. **1**, or in an integrated circuit memory device **130** of FIG. **2**, using the signal and noise characteristics **339** measured according to FIG. **8**.

[0159] In FIG. **9**, when a memory device **130** receives an address **135** to retrieve memory data **337** from its memory cells, the memory device **130** measures signal and noise characteristics **339** associated with the memory data **337**. For example, the calibration circuit **345** of the memory device **130** can generate statistics, such as bit counts, count differences, and/or results derived from the statistics, such as the optimize read voltage, in a way as illustrated in FIG. **8**.

[0160] The memory data **337** retrieved from the memory cells of the memory device is in an encoded format that allows error detection and recovery **363** (e.g., using techniques such as error correction code (ECC), low-density parity-check (LDPC) code). The signal and noise characteristics **339** can be provided as input to a data integrity classifier **313** to evaluate the likelihood of the memory data **337** having too many errors for success decoding the memory data **337** by some or all the processing paths/modules/options in error detection and recovery **363**.

[0161] For example, the memory sub-system **110** can include a low power ECC **371**, a full power ECC **373**, an LDPC decoder **375** that does not use soft bit data, an LDPC decoder **377** that uses both hard bit data and soft bit data in decoding. In general, available paths/modules/options for decoding the memory data **337** in a memory sub-system **110** are not limited to the examples (e.g., low power ECC **371**, full power ECC **373**, LDPC decoder **375**, LDPC decoder **377**) illustrated in FIG. **9**; different processing paths/modules/options (e.g., low power ECC **371**, full power ECC **373**, LDPC decoder **375**, LDPC decoder **377**) can implemented; and the different processing paths/modules/options have different power consumption levels, different capabilities in recovering error-free original/non-encoded data from the retrieve raw memory data **337**, and/or different processing latency.

[0162] The data integrity classifier **313** can be trained (e.g., through machine learning) to predict the likelihood **361** of data integrity failure of the memory data **337** based on the associated signal and noise characteristics **339**.

[0163] For example, the likelihood **361** of data integrity failure of the memory data **337** can be in

the form of an estimated bit error rate in the memory data **337**.

[0164] For example, the likelihood **361** of data integrity failure of the memory data **337** can be in the form of a prediction of whether the memory data **337** can be successfully decoded (e.g., via ECC or LDPC) by any of the processing paths/modules/options and if so, which of the processing paths/modules/options is or are predicted to be able to successfully decode the memory data **337** having the associated signal and noise characteristics **339**.

[0165] Based on the predicted likelihood **361** of data integrity failure of the memory data **337**, the memory sub-system **110** can select one of the processing paths/modules/options with reduced power consumption, reduced processing latency, and/or a high probability of success in decoding.

[0166] In some embodiments, the data integrity classifier **313** is trained to directly provide a prediction of an optimized processing path/module to process the encoded memory data **337** retrieved from the memory cells of the memory device **130**.

[0167] In some embodiments, the data integrity classifier **313** is trained to provide a prediction of a prioritized list of processing paths/modules/options that can successfully decode the encoded memory data **337**. Further, the data integrity classifier **313** can further provide an indication of the confidence levels of the selected listed processing paths/modules/options in successfully decoding the memory data **337**.

[0168] Optionally, the data integrity classifier **313** can also be trained to evaluate the confidence levels of the prediction(s); and the confidence levels can be used in the selection of an option from the available paths/modules/options for the processing of the encoded memory data **337** received from the memory cells in the memory device **130**.

[0169] In general, the data integrity classifier **313** can be implemented in the memory device **130** and/or in the controller **115** of the memory sub-system **110**. For example, one data integrity classifier **313** can be implemented in the memory device **130** and customized for operation decisions to be made in the memory device **130**; and another data integrity classifier **313** can be implemented in the controller **115** and customized for operation decisions to be made in the controller **115**. For example, the data integrity classifier **313** implemented in the controller **115** can use not only the signal and noise characteristics **339** received from the memory device **130** for the memory data **337** but also other information that may not be available in the memory device **130**, such as charge loss, read disturb, cross-temperature effect, program/erase, data retention, etc. For example, the data integrity classifier **313** implemented in the controller **115** and the data integrity classifier **313** implemented in the memory device **130** can have different complexity, and/or different levels of accuracy in their predictions. Optionally, the memory device **130** provides its prediction to the controller **115** as part of enriched status report for retrieving the memory data **337**; and the controller **115** uses the prediction generated by the memory device **130** to select a path/module/option for decoding the memory data **337**. In some embodiments, the error detection and recovery **363** (or some of the paths/modules/options) are implemented in the memory device **130**. For example, the processing logic of the error detection and recovery **363** and the data integrity classifier **313** can be implemented using complementary metal-oxide-semiconductor (CMOS) circuitry formed under the array of memory cells on an integrated circuit die of the memory device **130**. For example, the processing logic can be formed, within the integrated circuit package of the memory device **130**, on a separate integrated circuit die that is connected to the integrated circuit die having the memory cells using through-silicon vias (TSVs) and/or other connection techniques.

[0170] For example, when the data integrity classifier **313** is implemented in the memory device **130**, the output of the data integrity classifier **313** can be used in controlling the retrieval of the memory data **337**.

[0171] For example, when the output of the data integrity classifier **313** indicates that the encoded memory data **337** is likely to be decoded using a decoder (e.g., **377**) that uses soft bit data, the memory device **130** can automatically further read the soft bit data in addition to reading the hard

bit data. However, if the data integrity classifier **313** indicates that the encoded memory data **337** can be decoded using a decoder (e.g., **375**) that does not require soft bit data as input, the memory device **130** can skip the operations to read soft bit data and/or the operations to transmit the soft bit data to the controller **115**.

[0172] For example, when the output of the data integrity classifier **313** indicates that none of the available paths/modules/options is likely to be successful in decoding the memory data **337**, the memory device **130** can automatically perform a read-retry to search for an improved read voltage without waiting for a command from the controller **115**. Further, the memory device **130** can optionally skip reading the memory data **337** when the output of the data integrity classifier **313** indicates that none of the available paths/modules/options is likely to be successful in decoding the memory data **337**.

[0173] In another example, a method is provided for a memory sub-system **110** to control data integrity operations based on classification of signal and noise characteristics **339** associated with memory data **337** retrieved from memory cells. The method can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software/firmware (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the method is performed at least in part by the controller **115** of FIG. **1**, or processing logic in the memory device **130** of FIG. **2**. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0174] For example, the method can be implemented in a computing system of FIG. **1** with a memory device of FIG. **2** and signal noise characteristics illustrated in FIG. **8** with the operations illustrated in FIG. **9**.

[0175] In the method, a processing device (e.g., controller **115**) in a memory sub-system **110** transmits a command to a memory device **130** of the memory sub-system **110** to retrieve encoded memory data **337** from an address **135**.

[0176] For example, memory data **337** can be in an encoded form for storing in the memory cells of the memory device **130** for improved reliability. The encoded memory data **337** has redundancy information, which allows a decoder to detect errors and/or recovery the original data without error when the amount of errors in the retrieved, encoded memory data **337** is no more than a threshold. For example, the data can be encoded/decoded via an error correction code, or a low-density parity-check code.

[0177] In the method, in response to the command and during execution of the command in the memory device **130**, a calibration circuit **345** of the memory device **130** enclosed in an integrated circuit package measures signal and noise characteristics **339** of a group (e.g., **131** or **133**) of memory cells formed on an integrated circuit die.

[0178] For example, the calibration circuit **345** is formed at least in part on the integrated circuit die, or another integrated circuit die enclosed in the integrated circuit package.

[0179] For example, the signal and noise characteristics **339** can include statistical data of memory cells at varying operating parameters, such as different voltages applied to read memory cells in the group (e.g., **131** or **133**).

[0180] For example, the statistical data can include bit counts (e.g., C.sub.A, C.sub.B, C.sub.C, C.sub.D, and/or C.sub.E) of memory cells in the group (e.g., **131** or **133**) having a predetermined state when the different voltages (e.g., V.sub.A, V.sub.B, V.sub.C, V.sub.D, and/or V.sub.E) are applied on the group of memory cells. Alternatively, or in combination, the statistical data can include bit differences (e.g., D.sub.A, D.sub.B, D.sub.C, and/or D.sub.D), where each bit difference

is a difference between a first bit count (e.g., C.sub.A) of memory cells in the group having a predetermined state when a first read voltage (e.g., V.sub.A) is applied on the group of memory cells, and a second bit count (e.g., C.sub.B) of memory cells in the group having the predetermined state when a second read voltage (e.g., V.sub.B) is applied on the group of memory cells.

[0181] For example, the predetermined state of a memory cell can be a state where the memory cell is substantially conductive (e.g., having a substantially current passing through the memory cell) when a corresponding read voltage is applied on the memory cell. Alternatively, the predetermined state of a memory cell can be a state where the memory cell is substantially non-conductive (e.g., having no substantially current passing through the memory cell) when a corresponding read voltage is applied on the memory cell.

[0182] In the method, a data integrity classifier **313** configured in the memory sub-system **110** generates a prediction based on the signal and noise characteristics **339**.

[0183] In the method, the memory sub-system **110** selects, based on the prediction, an option from a plurality of options to decode the memory data **337**.

[0184] For example, the prediction can be based on machine learning to identify a level of bit error rate in the encoded memory data **337**, to identify the option, and/or to identify a likelihood of an option of failing or succeeding in decoding the encoded memory data **337** retrieved from the memory device. The prediction can include a confidence level of the prediction.

[0185] In the method, the encoded data is decoded using the selected option.

[0186] For example, the plurality of options can include decoders having different levels of complexity, taking different inputs, using different amounts of power in decoding, and/or having different amounts of latency in decoding. The plurality of options can include instructing the memory device **130** to retry read at the address **135** without decoding the encoded memory data **337**, without transmitting the encoded memory data **337**, and/or without reading the memory data **337** from memory cells in the memory device **130**.

[0187] For example, the plurality of options can include the use of a first decoder and the use of a second decoder that consumes more energy than the first decoder in operation.

[0188] The different decoders can use different amounts of data in their decoding operations. For example, the second decoder (e.g., LDPC decoder **377**) uses both hard bit data determined from the group of memory cells at read voltages and soft bit data determined from the group of memory cells at voltages having predetermined offsets from the read voltages; and the first decoder (e.g., LDPC decoder **375**) uses the hard bit data without using the soft bit data.

[0189] Optionally, the calibration circuit **345** is configured to compute the read voltages (e.g., V.sub.O) for determination of the hard bit data based on the signal and noise characteristics **339**. Alternatively, the read voltages for determination of the hard bit data can be calculated and/or specified by the controller **115** of the memory sub-system **110**.

[0190] A data integrity classifier **313** can be implemented in the controller **115** of the memory sub-system **110** and/or in the memory device **130**.

[0191] When a data integrity classifier **313** is implemented in the memory device **130**, the memory device **130** can determine whether or not to perform the operations to read the soft bit data based on a prediction generated by its data integrity classifier **313**.

[0192] When a data integrity classifier **313** is implemented via a processing device **117** of the memory sub-system **110**, the memory sub-system **110** can be configured to instruct the memory device **130** to perform a read-retry when the prediction indicates a failure of decoders available in the memory sub-system **110** in decoding the encoded memory data **337**, without waiting for the result from a decoder and/or without sending the encoded data to any decoder.

[0193] When a data integrity classifier **313** is implemented via a processing device (e.g., controller **115**) of the memory sub-system **110**, the memory sub-system **110** can be configured to instruct the memory device **130** to provide the soft bit data when the prediction indicates that the second decoder (e.g., processing device **117**) is to be used to decode the encoded data.

[0194] The data integrity classifier **313** can include instructions configured as software and/or firmware. For example, the processing device **117** can execute the data integrity classifier **313** to perform the above discussed methods.

[0195] A non-transitory computer storage medium can be used to store instructions of the firmware of a memory sub-system (e.g., **110**). When the instructions are executed by the controller **115** and/or the processing device **117**, the instructions cause the controller **115** and/or the processing device **117** to perform the methods discussed above.

[0196] FIG. **10** shows a memory device configured with a programming manager according to one embodiment. For example, the memory device **130** illustrated in FIG. **1** can be implemented using a memory device of FIG. **10** with a cross-point memory; and the local media controller **150** in FIG. **1** can be implemented using the controller **231** in FIG. **10**.

[0197] In FIG. **10**, the memory device **130** includes an array **132** of memory cells, such as a memory cell **101**.

[0198] The memory device **130** of FIG. **10** includes a controller **231** that operates bitline drivers **237** and wordline drivers **235** to access the individual memory cells (e.g., **101**) in the array **132**.

[0199] For example, each memory cell (e.g., **101**) in the array **132** can be accessed via voltages driven by a pair of a bitline driver **247** and a wordline driver **245**, as illustrated in FIG. **11**.

[0200] The controller **231** includes a programming manager **233**. For example, the programming manager **233** can be implemented via logic circuits and/or microcodes/instructions to select, based on parameters about past usages of the array of memory cells, a mode of programming a set of memory cells to store a data item. For example, the usage parameters can include the ratio of read and write operations performed in the array of memory cells, a count of read operations in the array, a count of write operations in the array, a time to the last/previous write operation in the array, etc.

[0201] Since memory cells in different locations in the array **132** can have different bit error rates under the same usage, the programming manager **233** can select the programming for the set of memory cells based on attributes of the memory cells in the set, such as a location or address of the memory cell **101** in the memory device, the electrical distance of the memory cell **101** to its voltage drivers, a write timing parameter or its range of the memory cell **101**, etc.

[0202] FIG. **11** shows a memory cell **101** with a bitline driver **247** and a wordline driver **245** configured to apply voltage pulses according to one embodiment. For example, the memory cell **101** can be a typical memory cell **101** in the memory cell array **132** of FIG. **10**.

[0203] The bitline driver **247** and the wordline driver **245** of FIG. **11** are controlled by the programming manager **233** of the controller **231** to selectively apply one or more voltages pulses to program the threshold voltage of the memory cell **101** to store data, or to determine the voltage region of the threshold voltage of the memory cell **101** to retrieve the data.

[0204] For example, based on a mode selected to program the memory cell **101**, the bitline driver **247** and the wordline driver **245** can be instructed or controlled by the programming manager **233** to program the memory cell **101** a single level cell (SLC) mode to store one bit per cell, or program the memory cell **101** in a multi-level cell (MLC) mode to store more than one bit per cell. In some implementations, a typical memory cell **101** can be programmed in a mode to store an average of 1.5 bits per cell; and in other implementations, a typical memory cell **101** can be programmed in a mode to store two or more bits per cell.

[0205] The bitline driver **247** and the wordline driver **245** can apply voltages of different polarities on the memory cell **101**.

[0206] For example, in applying one polarity of voltage (e.g., positive polarity), the bitline driver **247** drives a positive voltage relative to the ground on a bitline **241** connected to a row of memory cells in the array **132**; and the wordline driver **245** drives a negative voltage relative to the ground on a wordline **243** connected to a column of memory cells in the array **132**.

[0207] In applying the opposite polarity of voltage (e.g., negative polarity), the bitline driver **247**

drives a negative voltage on the bitline **241**; and the wordline driver **245** drives a positive voltage on the wordline **243**.

[0208] The memory cell **101** is in both the row connected to the bitline **241** and the column connected to the wordline **243**. Thus, the memory cell **101** is subjected to the voltage difference between the voltage driven by the bitline driver **247** on the bitline **241** and the voltage driven by the wordline driver **245** on the wordline **243**.

[0209] In general, when the voltage driven by the bitline driver **247** is higher than the voltage driven by the wordline driver **245**, the memory cell **101** is subjected to a voltage in one polarity (e.g., positive polarity); and when the voltage driven by the bitline driver **247** is lower than the voltage driven by the wordline driver **245**, the memory cell **101** is subjected to a voltage in the opposite polarity (e.g., negative polarity).

[0210] To program the voltage threshold of the memory cell **101**, the bitline driver **247** and the wordline driver **245** can drive a pulse of voltage onto the memory cell **101** in one polarity (e.g., positive polarity) to snap the memory cell **101** such that the memory cell **101** is in a conductive state. While the memory cell **101** is conductive, the bitline driver **247** and the wordline driver **245** continue driving the programming pulse to change the threshold voltage of the memory cell **101** towards a voltage region that represents the data or bit value(s) to be stored in the memory cell **101**.

[0211] The controller **231** can be configured in an integrated circuit having a plurality of decks of memory cells. Each deck can be sandwiched between a layer of bitlines, a layer of wordlines; and the memory cells in the deck can be arranged in an array **132**. Adjacent decks of memory cells may share a layer of bitlines (e.g., **241**) or a layer of wordlines (e.g., **243**). Bitlines are arranged to run in parallel in their layer in one direction; and the wordlines are arranged to run in parallel in their layer in another direction orthogonal to the direction of the bitlines. Each of the bitlines is connected to a row of memory cells in the array; and each of the wordlines is connected to a column of memory cells in the array. Bitline drivers **237** are connected to bitlines in the decks; and wordline drivers **235** are connected to wordlines in the decks. Thus, a typical memory cell **101** is connected to a bitline driver **247** and a wordline driver **245**.

[0212] Optionally, the memory cell **101** is implemented using a selector/memory device. The selector/memory device has a chalcogenide (e.g., chalcogenide material and/or chalcogenide alloy). For example, the chalcogenide material can include a chalcogenide glass such as, for example, an alloy of selenium (Se), tellurium (Te), arsenic (As), antimony (Sb), carbon (C), germanium (Ge), and silicon (Si). A chalcogenide material can primarily have selenium (Se), arsenic (As), and germanium (Ge) and be referred to as SAG-alloy. SAG-alloy can include silicon (Si) and be referred to as SiSAG-alloy. In some embodiments, the chalcogenide glass can include additional elements such as hydrogen (H), oxygen (O), nitrogen (N), chlorine (Cl), or fluorine (F), each in atomic or molecular forms. The selector/memory device has a top side and a bottom side. A top electrode is formed on the top side of the selector/memory device for connecting to a bitline **241**; and a bottom electrode is formed on the bottom side of the selector/memory device for connecting to a wordline **243**. For example, the top and bottom electrodes can be formed of a carbon material. For example, a chalcogenide material of the memory cell **101** can take the form of a crystalline atomic configuration or an amorphous atomic configuration. The threshold voltage of the memory cell **101** can be dependent on the ratio of the material in the crystalline configuration and the material of the amorphous configuration in the memory cell **101**. The ratio can change under various conditions (e.g., having currents of different magnitudes and directions going through the memory cell **101**).

[0213] FIG. **12** illustrates a media structure of a memory device **130** according to one embodiment. For example, the memory device **130** of FIG. **1** can have memory cells organized in a structure as in FIG. **12**.

[0214] For example, the memory device **130** of FIG. **12** can have multiple integrated circuit dies **250**, . . . , **260**. Each of the integrated circuit dies (e.g., **250** or **260**) can have multiple planes (e.g.,

251, . . . , 253, or 261, . . . , 263) of memory cells (e.g., 101). Each of the planes (e.g., 251, or 263) can have multiple blocks (e.g., 255, . . . , 257, or 265, . . . , 267) of memory cells (e.g., 101). Each of the blocks (e.g., 255, 257, 265, or 267) can have multiple pages of memory cells (e.g., 101). The memory cells in each page are configured to be programmed to store/write/commit data together in an atomic operation; and the memory units in each block (e.g., 255) is configured to be erased data together in an atomic operation. Different commands can be issued to different dies 250, . . . , 260 for parallel execution; and a same command can be issued to multiple planes (e.g., 251, . . . , 253) in a die (e.g., 250) for parallel execution.

[0215] FIG. 13 shows a technique to improve data reliability for memory cells on a wordline according to one embodiment.

[0216] In the example of FIG. 13, each memory cell 101 is programmed to have a threshold voltage representing four bits: a top page bit, an extra page bit, an upper page bit, a lower page bit. For example, the technique of FIG. 6 to program a memory cell to store a four-bit data item can be used. Other techniques can also be used. FIG. 13 illustrates the technique using an example of programming four bits per memory cell. In general, the technique can be applied to programming data with a different number of bits per memory cell, such as three bits per memory cell, or higher than four bits per memory cell.

[0217] A number of memory cells connected to a wordline 243 can be used to store a codeword 271, which includes bits for the data item and bits for parity that provides redundant information for the data item to enable error recovery using an error correction code technique (e.g., low-density parity-check (LDPC)).

[0218] For example, a plane of memory cells in the memory device 130 can have memory cells connected to a wordline 243 and having the capacity to store a plurality of codewords (e.g., 271). The codewords in the plane and on the wordline 243 can be in one or more pages, with each page to be programmed together, and one or more blocks, with each block to be erased together.

[0219] Further, the memory device 130 can have multiple planes for the wordline 243. The planes have the same structure such that a same operation (e.g., read) can be performed in parallel in the multiple plane.

[0220] In general, to meet a performance level in error recovery, the number of bits used for the parity increases when the bit error rate in the data read as the codeword 271 from the memory cells increase. To meet the performance level requirement of a worst performing memory cell group, the number of bits for the parity can be too high for the majority of memory cell groups and thus reduce the overall storage efficiency of the memory device 130.

[0221] When the memory device 130 is designed to have the number of parity bits suitable for the desirable performance level in the majority of memory cell groups, some memory cell groups connected to a wordline 243 may not be able to meet the desirable performance level using the number of parity bits designed for the memory device 130. To improve the performance level, additional redundant information can be stored in the storage capability provided in some of the memory cells that are typically used to store a codeword for a separate data when the additional redundant information is not necessary.

[0222] For example, when the set of memory cells connected to the wordline 243 in the planes have a bit error rate below a threshold, the lower page bits of memory cells corresponding to the codeword 275 can be used to store a data item not related to other data items stored in the planes on the wordline 243. When at least some of the set of memory cells has a high bit error rate, a portion of the storage capacity of the set of memory cells, such as the storage capacity corresponding to the codeword 275, can be used to store additional redundant information to improve error recovery capability. It is not necessary to store the additional redundant information in the storage capacity (e.g., corresponding to the codeword 275) having a low bit error rate. It can be desirable to store the additional redundant information in the storage capacity (e.g., corresponding to the codeword 275) having a relatively high bit error rate such that the host data is stored with a relatively low bit error

rate.

[0223] For example, when the set of memory cells connected to the wordline **243** in the planes have a bit error rate above the threshold, the storage capacity of the codeword **275** can be used to store redundant information of some of the codewords (e.g., **271**, **273**, . . .) to improve the error recovery capability for the codewords (e.g., **271**, **273**, . . .).

[0224] For example, an XOR operation **201** can be applied to the codewords **271**, . . . , **273** to generate a codeword **275**. By storing the codeword **275** that is an XOR of the codewords **271**, . . . , **273**, additional redundant information is available to assist the recovery of a codeword (e.g., **271**) that would fail to recovery without the additional redundant information. The codewords **271**, . . . , **273** can be distributed into different planes that can be read in parallel. By aligning the timing of the reading of the codewords **271**, . . . , **273** in the different planes, the latency to retrieve the codewords **271**, . . . , **273** for error recovery via the additional redundant information provided by the codeword **275** can be reduced. Alternatively, in other implementations, some or all of the codewords **271**, . . . , **273** (and/or **275**) linked with the additional redundant information are configured within a same plane.

[0225] The codewords **271**, . . . , **273** combined to generate the redundant codeword **275** can be from different planes formed using different page types (e.g., top page bits, extra page bits, upper page bits, lower page bits). Since the bit error rates can vary among different page types, mixing the codewords **271**, . . . , **273** from different page types in generating the redundant codeword **275** can average the bit error rates among the combined codewords **271**, . . . , **273**, and thus avoid a scenario of combining codewords **271**, . . . , **273** having the worst high bit error rates.

[0226] Other techniques to generate and store redundant information for the codewords (e.g., **271**, **273**) can be used to improve the error recovery capability for the wordline **243**.

[0227] For example, a parity bit of the codeword **271** in a plane (or some or all of the codewords in the plane) can be computed and stored in a bit provided by the storage capacity of the codeword **275** in another plane.

[0228] For example, a parity bit of combined/linked codewords **271**, . . . , **273** in some of the planes can be computed and stored in a bit provided in the storage capacity of the codeword **275** of a plane.

[0229] For example, one or more parity bits can be added to each codeword (e.g., **271**); and the bits of the enlarged codewords can be redistributed among the storage spaces provided by the memory cells on the wordline **243**. For example, the number of top page bits of the set memory cells on the wordline **243** is designed to accommodate a number of codewords each having the number of bits of data and the number of bits of parity as the codeword **271**, such that the boundaries of codewords are aligned with the boundaries of pages, blocks, and planes. When the number of parity bits is increased, the number of codewords that can be stored in the same number of top page bits is reduced; and at least some of the boundaries of the enlarged codewords will be misaligned with the boundaries of pages, blocks, and/or planes.

[0230] When the redundant information stored in the storage space for the codeword **275** is linked to multiple codewords in pages, blocks, and/or planes, a change to one of the codewords can lead to a change in the redundant information in the storage space of the codeword **275**. Thus, it is preferred that the multiple codewords in pages, blocks, and/or planes are used together to avoid excessive write amplification for the memory cells providing the storage space for the codeword **275**.

[0231] In some implementations, the write amplification can be distributed across the pages, blocks, and/or planes having the linked codewords (e.g., **271**, **273**). For example, when the codewords **271**, . . . , **273**, are XOR'ed to generate the redundant codeword **275**, any of the codewords **271**, . . . , **273** and **275** is the XOR of the remaining codewords and thus can be considered the redundant codeword; and a controller (e.g., **115** or **150**) can rotate the role of the storage spaces of the codewords **271**, . . . , **273**, and **275** as the storage space for the redundant

codeword and thus spreading the write amplification across the pages, blocks and/or planes.

[0232] In some implementations, the host system **120** provides data to the memory sub-system **110** containing the memory device **130** for storing in the unit of a predetermined block size (e.g., corresponding to a data unit for a logical block address (LBA)). When a controller (e.g., **115** or **150**) uses the storage space of the codeword **275** to store redundant information, a storage block that previously has the capacity to store the entire data unit has a reduced storage capacity. The controller (e.g., **115** or **150**) can spread the data unit for storing in multiple storage blocks of reduced storage capacity. Alternatively, the controller (e.g., **115** or **150**) can allocate an entire storage block, corresponding to the storage requirement of an LBA block of data, for storing redundant information, such as the redundant codeword **275**.

[0233] In some implementations, the projection of whether a wordline needs extra parity protection can be determined by measuring the sensitivity of the memory cells to stress (e.g., typically retention time & temperature). The stress can determine whether extra ECC is needed for some potential future condition. If the projected error rate will be too high, extra ECC will be needed on the memory cells. Some dies can be more sensitive to data retention (which is a function of the temperature) than other die. Further, on dies with greater sensitivity it is observed that the worst wordlines on the die suffer more loss of margin, or increase in bit error rate, than the average wordline on the same die. So, while the current bit error rate of a wordline is insufficient in determining whether extra ECC will be needed in case of power loss (followed by retention), a pattern of changes in bit error rates of a wordline can be used to predict whether the wordline needs extra parity protection. The calibration circuit **345** can measure the signal and noise characteristics **339** of data stored in the memory cells connected to the wordline to determine whether the bit error rate of the memory cells is above a threshold; and if the bit error rate is above the threshold, the controller (e.g., **115** or **150**) uses a portion of the storage capacity of the memory cells to store redundant information (e.g., codeword **275** that is generated by applying an XOR operation **201** on the codewords **271**, . . . , **273**), in addition to the predetermined number of parity bits for each codeword.

[0234] For example, the bit error rate of the memory cells can be measured or predicted using the technique of FIG. **8** and FIG. **9**. Other techniques can also be used (e.g., by comparing the data written into the memory cells and data represented by the threshold voltages determined through reading operations).

[0235] For example, when the memory cells age or experience of a number of program and erasure cycles, the bit error rate of data represented by the threshold voltages of the memory cells can change. Based on the measured bit error rate, the controller (e.g., **115** or **150**) can selectively and/or dynamically to determine whether to store an XOR of the codewords **271**, . . . , **273**, or use the storage space of the codeword **275** to store additional data unrelated to the codewords **271**, . . . , **273**.

[0236] For example, when the operating temperate of the memory cells changes, the bit error rate can change. In response, additional redundant information can be selectively stored in response to reduce or minimize data corruption/loss.

[0237] In some implementations, the wordlines (e.g., **243**) that are likely to have high bit error rates under various conditions can be determined from similar memory devices. Based on the conditions, the wordlines can be configured to store additional redundant information for improved error recovery capability with reduced storage capacity for storing independent data items.

[0238] FIGS. **14** to **23** show various techniques to improve data reliability for memory cells on a wordline according to one embodiment.

[0239] As illustrated in FIG. **14**, a wordline **243** can be driven by at least one wordline driver **245**. The wordline **243** is connected to a plurality of memory cell groups **501**, **503**, . . . , **505**. The memory cells connected to the wordline **243** can be connected to bitline drivers **237** via respective bitlines (e.g., **241**). The memory cells on the wordline **243** can be read in parallel.

[0240] Each memory cell group (e.g., **501**, **503**, or **505**) has a predetermined number of memory cells (e.g., **511**, **513**, . . . , **515**; **531**, **533**, . . . , **535**; or **551**, **553**, . . . , **555**). Each memory cell (e.g., **551**) can be programmed to have a threshold voltage representative of a predetermined bits (e.g., **601**, **603**, . . . , **605**). For example, when the memory cell **511** is programmed to store four bits (QLC mode), the data bits **601**, **603**, . . . , **605** corresponds to top page bit, extra page bit, upper page bit, and lower page bit.

[0241] The set of bits of a same page type (e.g., bits **601**, **611**, . . . , **621**, **631**, **641**, **651**, . . . , **661**, **671**, . . . , **681**) corresponds to the bits of the page type (e.g., top page bits, extra page bits, upper page bits, lower page pages for QLC mode). Thus, the set of bits **603**, **613**, . . . , **623**, **633**, **643**, . . . , **653**, . . . , **663**, **673**, . . . , **683** corresponds another page type; and the set of bits **605**, **615**, . . . , **625**, **635**, **645**, . . . , **655**, . . . , **665**, **675**, . . . , **685** corresponds a further page type.

[0242] The memory cell groups **501**, **503**, . . . , **505** can be formed on multiple pages, multiple blocks (e.g., **255**, . . . , **257**), and/or multiple planes **251**, . . . , **253** on a same integrated circuit die **250**.

[0243] In general, the memory cell groups **501**, **503**, . . . , **505** can be a portion of the entire set of memory cell groups on the wordline **243**, or a subset of the memory cell groups on the wordline **243**. When the memory cell groups **501**, **503**, . . . , **505** are on multiple planes **251**, . . . , **253**, the cell groups **501**, **503**, . . . , **505** form a same structure for each of the planes.

[0244] Each memory cell group (e.g., **501**) can be configured to store a number of data bits and another number of parity bits in each page type. In general, each memory cell group (e.g., **501**) can include one or more independent codewords.

[0245] When the bit error rate of the data bits **601** to **685** is above a threshold, a portion of the memory cells in the memory cell groups **501**, **503**, . . . , **505** is used to store redundant information to assist error recovery.

[0246] FIG. **15** illustrates an example of using the data bits **601**, **611**, . . . , **621** in a memory cell group **501** to store the XOR of the corresponding data bits of other groups **503**, . . . , **505**. For example, data bits **631**, **641**, . . . , **651** in the memory cell group **503** represent a codeword **504**; and data bits **661**, **671**, . . . , **681** in the memory cell group **505** represent another codeword **506**. The XOR operation **201** of the codewords **504**, . . . , **506** generates a codeword **502** having the data bits **601**, **611**, . . . , **621**. For example, the data bit **601** is the XOR operation **201** of the corresponding data bits **631**, . . . , **661** in the memory cell groups **503**, . . . , **505**; the data bit **611** is the XOR operation **201** of the corresponding data bits **641**, . . . , **671** in the memory cell groups **503**, . . . , **505**; and the data bit **621** is the XOR operation **201** of the corresponding data bits **651**, . . . , **681** in the memory cell groups **503**, . . . , **505**. Storing the codeword **502** in the memory cell group **501** can improve the capability of recovering from random bit errors in the codewords **504**, . . . , **506**. Without the redundant information provided by the codeword **502**, the memory device **130** and/or the memory sub-system **110** may fail to decode one or more of the codewords **504** from the data bits **631** to **681** read from the memory cells in the groups **503**, . . . , **505**.

[0247] Codewords from different plane types can be mixed in generating the codeword **502** to provide additional redundant information, as illustrated in FIG. **16**.

[0248] In FIG. **16**, a codeword **504** of one page type is XOR with a codeword **506** of a different page type to generate the redundant codeword **502**. The codewords **504**, **506**, and **502** can be distributed in different page types in the memory cell groups **503**, . . . , **505**, and **501** to avoid linking the worse performing codewords together.

[0249] FIG. **17** illustrates an example of storing redundant information in the form of a parity bit of a codeword **504** having data bits **631**, **641**, . . . , **651** in the memory cell group **503**. In some implementations, the data bit **621** provides an extra bit of parity information such that the combination of the data bits **631**, **641**, . . . , **651** and **621** provides an enlarged codeword having improved error recovery capability. For example, the data bit **621** can be the XOR of a subset of the data bits **631**, **641**, . . . , **651** according to a LDPC technique.

[0250] FIG. 18 illustrates an example of using the data bits 621, . . . , 611 of a memory cell group 501 to store the extra parity bits for the codewords 504, . . . , 506 in the other memory cell groups 503, . . . , 505.

[0251] The extra bit stored in the memory cell group for a codeword in another memory cell group can be distributed over different page types, as illustrated in FIG. 19.

[0252] In FIG. 19, the codeword 506 having the data bits 661, 671, . . . , 681 of one page type in a memory cell group 505 can be expanded to have an additional parity bit 605 of another page type in the memory cell group 501.

[0253] In some implementations, more than one codeword can be linked to share an expanded parity bit, as illustrated in FIG. 20.

[0254] In FIG. 20, the codewords 504, . . . , 506 of a page type from at least some of the memory cell group 503, . . . , 505 are combined via a link operation 507, and the combined codeword is expanded to have an extra parity bit 601.

[0255] The codewords from the group 503 and 505 and the extra parity for the linked codewords can be distributed across different page types, as illustrated in FIG. 21.

[0256] In FIG. 21, the codewords 504, . . . , 506 of different page types from at least some of the memory cell group 503, . . . , 505 are combined via a link operation 507, and the combined codeword is expanded to have an extra parity bit 601 of a further page type.

[0257] FIG. 22 illustrates an example of adding a parity bit for each codeword (e.g., 502 or 504), and distributing the bits of enlarged codewords across the memory cell groups 501, 503, . . . , 505. Since the codeword (e.g., 502) is enlarged, the codewords (e.g., 502, or 504) can span across memory groups, across boundaries of pages, blocks, and/or planes. For example, the codeword 502 includes not only the data bits 601, 611, . . . , 621 from the memory cell group 501, but also an extra bit 631 from the next memory cell group 503. The extra bit 631 can be the XOR of a subset of the data bits 601, 611, . . . , 621 according to a LDPC technique.

[0258] Further, the expanded codewords can use data bits of different types, as illustrated in FIG. 23.

[0259] In FIG. 23, an expended codeword 502 includes data bits 601, 611, . . . , 621 of a page type from the memory cell group 501, and a data bit 633 of another page type from another memory cell group 503.

[0260] FIGS. 13 to 23 illustrate examples of generating redundant information using XOR operations 201. Alternatively, XNOR operations can be used.

[0261] FIG. 24 shows a method to dynamically deploy error correction techniques according to one embodiment. The methods can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software/firmware (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the method is performed at least in part by the controller 115 of FIG. 1, or processing logic in the memory device 130 of FIG. 2. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0262] At block 701, a memory sub-system 110 having a memory device 130 identifies a first wordline 243 connected to a plurality of groups 501, 503, . . . , 505 of first memory cells (e.g., 511 to 555) based on a determination that data bits (e.g., 601 to 685) represented by threshold voltages (e.g., 209) of the first memory cells and determined in a read operation have a bit error rate above a threshold.

[0263] For example, a data integrity classifier 313 can dynamically estimate the bit error rate based

on signal and noise characteristics **339** of first memory cells. Alternatively, the bit error rate can be estimated based on a pattern of bit error rates of memory cells on different wordlines, based on the usage history of the memory device **130** (e.g., experienced number of cycles of program and erasure), the current operating condition of the memory device **130** (e.g., temperature), the predicted operating condition of the memory device **130** in a subsequent period of time during which the first memory cells are to be read to retrieve their stored data, etc.

[0264] In response to the bit error rate is determined or predicted to be above the threshold, the memory sub-system **110** performs operations in blocks **703**, **705** and **707** to use a portion of the storage capacity of the first memory cells to store redundant information of data stored in the remaining portion of the storage capacity of the first memory cells. As a result, the storage capacity of the first memory cells to store independent data is reduced; and the error recovery capability for the data stored in the first memory cells is improved to accommodate the elevated bit error rate.

[0265] In contrast, when the bit error rate is determined or predicted to be below the threshold, the portion used to store the redundant information can be used to store separate data independent of the data stored in the remaining portion of the storage capacity of the first memory cells. As a result, the usage of the storage capacity of the first memory cells is improved without comprising the error recovery capability for the data stored in the first memory cells.

[0266] At block **703**, the memory sub-system **110** stores first data items as independent first codewords of an error correction code technique into a first portion of the first memory cells, such as memory cell groups **503**, . . . , **505**. The first codewords have a same length, each having a predetermined number of data bits and another predetermined number of parity bits.

[0267] At block **705**, the memory sub-system **110** generates second data items as redundant information from the first codewords.

[0268] For example, each of the second data item can be generated from a subset of the first codewords; and each of the second data item can be generated from an XOR operation (or an XNOR operation) applied on the subset of the first codewords. The number of first codewords used to compute a second data item can vary based on the bit error rates of memory cells used to store the first codewords. When the bit error rates in the memory cells are high, a small number of first codewords can be used to compute a second data item to improve the error recovery capability to a level matching the high bit error rates. When the bit error rates in the memory cells are low, the large number of first codewords can be used to compute a second data item to reduce the use of storage capacity for addition redundant information, in view of the reduced need for error recovery capability corresponding to a level matching the low bit error rates. When the error recovery capability of the first codewords are sufficient for the bit error rates of the memory cells, the storing of a second data item can be skipped so that the storage capacity of such a second data item can be used for storing additional independent data.

[0269] At block **707**, the memory sub-system **110** stores the second data items in a second portion of the first memory cells, such as a memory cell group **501**.

[0270] For example, at least a portion of the subset of the first codewords can be distributed across different page types (e.g., top page, extra page, upper page, lower page when the first memory cells are programmed in a QLC mode).

[0271] For example, at least a portion of the subset of the first codewords can be distributed across different planes.

[0272] For example, the second portion can be in a plane that is different from at least some of the planes of the first portion.

[0273] At block **709**, in response to a determination that the bit error rate becomes lower than the threshold, the memory sub-system **110** stores third data items as independent second codewords of the same length in the first portion of the first memory cells and the second portion of the first memory cells.

[0274] Since both the first portion of the first memory cells and the second portion of the first

memory cells are used to store the independent second codewords when the bit error rate is low, the first memory cells can be used to store more independent data than when the bit error rate is high. [0275] Different wordlines in the memory device **130** can have different bit error rates and be used differently in whether or not to use a portion of the memory cells in a wordline to store additional redundant information. For example, the memory sub-system **110** can identify a second wordline connected to a plurality of groups of second memory cells based on a determination that data bits represented by threshold voltages of the second memory cells and determined in a read operation have a bit error rate below the threshold; and in response, the memory sub-system **110** can store third data items as independent third codewords into the second memory cells, without generating redundant information from the third codewords for storing into the second memory cells. The third codewords have the same length as the first codewords.

[0276] Since the amount of redundant information stored in the memory device **130** is selectively adjusted and/or dynamically adjusted based on bit error rates, the overall average number of bits of independent information stored in the memory device **130** is improved and/or optimized. It's improved or optimized compared to allocating the same amount of parity on all wordlines and/or on all dies. Applying the extra ECC where it is needed (e.g., based on individual wordlines) can achieve a much lower cost solution than allocating the space for parity based upon the absolute weakest wordline in a population of a die, and applying the same application to all of the wordlines on the die.

[0277] FIG. **25** illustrates an example machine of a computer system **400** within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, can be executed. In some embodiments, the computer system **400** can correspond to a host system (e.g., the host system **120** of FIG. **1**) that includes, is coupled to, or utilizes a memory sub-system (e.g., the memory sub-system **110** of FIG. **1**) or can be used to perform the operations of a programming manager **113** (e.g., to execute instructions to perform operations corresponding to the programming manager **113** described with reference to FIGS. **1-24**). In alternative embodiments, the machine can be connected (e.g., networked) to other machines in a LAN, an intranet, an extranet, and/or the Internet. The machine can operate in the capacity of a server or a client machine in client-server network environment, as a peer machine in a peer-to-peer (or distributed) network environment, or as a server or a client machine in a cloud computing infrastructure or environment.

[0278] The machine can be a personal computer (PC), a tablet PC, a set-top box (STB), a personal digital assistant (PDA), a cellular telephone, a web appliance, a server, a network router, a switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while a single machine is illustrated, the term "machine" shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

[0279] The example computer system **400** includes a processing device **402**, a main memory **404** (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM) or Rambus DRAM (RDRAM), static random access memory (SRAM), etc.), and a data storage system **418**, which communicate with each other via a bus **430** (which can include multiple buses).

[0280] Processing device **402** represents one or more general-purpose processing devices such as a microprocessor, a central processing unit, or the like. More particularly, the processing device can be a complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or a processor implementing other instruction sets, or processors implementing a combination of instruction sets. Processing device **402** can also be one or more special-purpose processing devices such as an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital

signal processor (DSP), network processor, or the like. The processing device **402** is configured to execute instructions **426** for performing the operations and steps discussed herein. The computer system **400** can further include a network interface device **408** to communicate over the network **420**.

[0281] The data storage system **418** can include a machine-readable medium **424** (also known as a computer-readable medium) on which is stored one or more sets of instructions **426** or software embodying any one or more of the methodologies or functions described herein. The instructions **426** can also reside, completely or at least partially, within the main memory **404** and/or within the processing device **402** during execution thereof by the computer system **400**, the main memory **404** and the processing device **402** also constituting machine-readable storage media. The machine-readable medium **424**, data storage system **418**, and/or main memory **404** can correspond to the memory sub-system **110** of FIG. **1**.

[0282] In one embodiment, the instructions **426** include instructions to implement functionality corresponding to a programming manager **113** (e.g., the programming manager **113** described with reference to FIGS. **1-24**). While the machine-readable medium **424** is shown in an example embodiment to be a single medium, the term “machine-readable storage medium” should be taken to include a single medium or multiple media that store the one or more sets of instructions. The term “machine-readable storage medium” shall also be taken to include any medium that is capable of storing or encoding a set of instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present disclosure. The term “machine-readable storage medium” shall accordingly be taken to include, but not be limited to, solid-state memories, optical media, and magnetic media.

[0283] Some portions of the preceding detailed descriptions have been presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the ways used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of operations leading to a desired result. The operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

[0284] It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. The present disclosure can refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage systems.

[0285] The present disclosure also relates to an apparatus for performing the operations herein. This apparatus can be specially constructed for the intended purposes, or it can include a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program can be stored in a computer readable storage medium, such as, but not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions, each coupled to a computer system bus.

[0286] The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems can be used with programs in accordance with the teachings herein, or it can prove convenient to construct a more specialized

apparatus to perform the method. The structure for a variety of these systems will appear as set forth in the description below. In addition, the present disclosure is not described with reference to any particular programming language. It will be appreciated that a variety of programming languages can be used to implement the teachings of the disclosure as described herein.

[0287] The present disclosure can be provided as a computer program product, or software, that can include a machine-readable medium having stored thereon instructions, which can be used to program a computer system (or other electronic devices) to perform a process according to the present disclosure. A machine-readable medium includes any mechanism for storing information in a form readable by a machine (e.g., a computer). In some embodiments, a machine-readable (e.g., computer-readable) medium includes a machine (e.g., a computer) readable storage medium such as a read only memory (“ROM”), random access memory (“RAM”), magnetic disk storage media, optical storage media, flash memory components, etc.

[0288] In this description, various functions and operations are described as being performed by or caused by computer instructions to simplify description. However, those skilled in the art will recognize what is meant by such expressions is that the functions result from execution of the computer instructions by one or more controllers or processors, such as a microprocessor.

Alternatively, or in combination, the functions and operations can be implemented using special purpose circuitry, with or without software instructions, such as using application-specific integrated circuit (ASIC) or field-programmable gate array (FPGA). Embodiments can be implemented using hardwired circuitry without software instructions, or in combination with software instructions. Thus, the techniques are limited neither to any specific combination of hardware circuitry and software, nor to any particular source for the instructions executed by the data processing system.

[0289] In the foregoing specification, embodiments of the disclosure have been described with reference to specific example embodiments thereof. It will be evident that various modifications can be made thereto without departing from the broader spirit and scope of embodiments of the disclosure as set forth in the following claims. The specification and drawings are, accordingly, to be regarded in an illustrative sense rather than a restrictive sense.

Claims

1. A device, comprising: a plurality of groups of memory cells, each of the plurality of groups configured to store a plurality of first codewords of an error correction code, the first codewords having a same first size; and a controller coupled to the memory cells and operable to reconfigure the plurality of groups to store a plurality of second codewords having a same second size larger than the first size; wherein each respective codeword in the second codewords has a first portion stored in a first group of the plurality of groups and a second portion stored in a second group of the plurality of groups, the second group being different from the first group.
2. The device of claim 1, wherein each of the memory cells is configured to store a plurality of bits.
3. The device of claim 2, wherein the respective codeword has one bit stored in each memory cell in the first group and the second group.
4. The device of claim 3, wherein the first portion and the second portion are stored in bits of a same type in the first group and the second group.
5. The device of claim 4, wherein the type is one of: top page bit; extra page bit; upper page bit; and lower page bit.
6. The device of claim 3, wherein the first portion is stored in bits of a first type in the first group; and the second portion is stored in bits of a second type, different from the first type, in the second group.
7. The device of claim 6, wherein the first type and the second type are different ones of: top page bit; extra page bit; upper page bit; and lower page bit.

- 8.** The device of claim 3, wherein the plurality of groups of memory cells are connected to a same wordline.
- 9.** A method, comprising: configuring each of a plurality of groups of memory cells to store a plurality of first codewords of an error correction code, the first codewords having a same first size; reaching a determination that a bit error rate of the memory cells is below a threshold; and reconfiguring, in response to the determination, the plurality of groups to store a plurality of second codewords having a same second size larger than the first size; wherein each respective codeword in the second codewords has a first portion stored in a first group of the plurality of groups and a second portion stored in a second group of the plurality of groups, the second group being different from the first group.
- 10.** The method of claim 9, wherein each of the memory cells is configured to store a plurality of bits.
- 11.** The method of claim 10, wherein the respective codeword has one bit stored in each memory cell in the first group and the second group.
- 12.** The method of claim 11, wherein the first portion and the second portion are stored in bits of a same type in the first group and the second group.
- 13.** The method of claim 12, wherein the type is one of: top page bit; extra page bit; upper page bit; and lower page bit.
- 14.** The method of claim 11, wherein the first portion is stored in bits of a first type in the first group; and the second portion is stored in bits of a second type, different from the first type, in the second group.
- 15.** The method of claim 14, wherein the first type and the second type are different ones of: top page bit; extra page bit; upper page bit; and lower page bit.
- 16.** The method of claim 11, wherein the plurality of groups of memory cells are connected to a same wordline.
- 17.** A device, comprising: a wordline; a plurality of bitlines; a plurality of memory cells connected to the wordline and the plurality of bitlines; and a controller configured to: store, prior to a bit error rate of the memory cells falling below a threshold, a plurality of first codewords of an error correction code in each of a plurality of groups of the memory cells, the first codewords having a same first size; and storing, after a determination that a bit error rate of the memory cells is below the threshold, the plurality of groups to store a plurality of second codewords having a same second size larger than the first size; wherein each respective codeword in the second codewords has a first portion stored in a first group of the plurality of groups and a second portion stored in a second group of the plurality of groups, the second group being different from the first group.
- 18.** The device of claim 17, wherein each of the memory cells is configured to store a plurality of bits.
- 19.** The device of claim 18, wherein the respective codeword has one bit stored in each memory cell in the first group and the second group.
- 20.** The device of claim 19, wherein each of the plurality of bits is one of: top page bit; extra page bit; upper page bit; and lower page bit.
-