

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255372

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

MUHLENFELD; Stephanie K. et al.

ARTICLE OF APPAREL

Abstract

A bra including a closure system, the closure system including a first layered fabric body, a second layered fabric body, a loop assembly secured to the first layered fabric body, and a hook assembly secured to the second layered fabric body. The hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body, and the first layered fabric body includes a flexible supporting layer, where the flexible supporting layer is configured to provide rigidity to the second layered fabric body such that the second layered fabric body maintains a flat configuration when it is secured to the first layered fabric body.

Inventors: MUHLENFELD; Stephanie K. (Portland, OR), MITCHELL; Kozet (Tygh Valley, OR)

Applicant: adidas AG (Herzogenaurach, DE)

Family ID: 1000008574762

Appl. No.: 19/196445

Filed: May 01, 2025

Related U.S. Application Data

parent US continuation 18441574 20240214 parent-grant-document US 12290121 child US 19196445

parent US continuation 18050728 20221028 parent-grant-document US 11903435 child US 18441574

parent US continuation 16659263 20191021 parent-grant-document US 11484076 child US 18050728

Publication Classification

Int. Cl.: A41F1/00 (20060101); A41C3/00 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 18/441,574, filed Feb. 14, 2024, which is a continuation application of U.S. patent application Ser. No. 18/050,728, filed Oct. 28, 2022, now U.S. Pat. No. 11,903,435, which is a continuation of U.S. patent application Ser. No. 16/659,263, filed Oct. 21, 2019, now U.S. Pat. No. 11,484,076. All of these applications are incorporated herein in their entirety by reference thereto.

FIELD

[0002] The present disclosure relates to articles of apparel. In particular, the present disclosure relates to bras.

BACKGROUND

[0003] Closures for securing the back panels of bras are typically difficult to clasp. These closures generally include very small fastening components which cannot easily be clasped together, particularly if a wearer cannot see the closure. Accordingly, bras often need to be put on backwards and clasped in the front of the wearer's body, such that the wearer can see the closure, before being turned around. Because bras tend to fit snugly, turning a clasped bra around the torso can cause uncomfortable rubbing against the skin. Furthermore, the tensile stresses applied to these small fastening components can cause the closures to wear out quickly, or even tear, since the stresses are concentrated in such small areas. To improve the stress distribution across the closure systems, additional fastening components can be included in the closures. However, a greater number of closure components can cause the closure system to be even more difficult to clasp.

[0004] Additionally, bras commonly incorporate a variety of construction techniques to shape and stabilize breast tissue. One of the most common construction techniques is the incorporation of underwire structures into the bras to assist with fit and to help create a consistent breast shape. These underwire structures often have a continuous, narrow width, and circumscribe the sides and lower edges of the wearer's breast tissue. This can restrict movement of the breast tissue, but does not stabilize or shape the breast tissue that is enveloped by the bra cups. Any shaping of the breast tissue is achieved by compression of the breasts within the cups. However, shaping of the breast tissue within the cups is heavily reliant on the proper fit of the cup. If the breast tissue does not completely fill the cup, the tissue may pool at the bottom of the cup and overlap the underwire creating an undesirable shape. Furthermore, the underwire structures have many other disadvantages, such as rubbing and poking, which causes discomfort to the wearer.

BRIEF SUMMARY OF THE INVENTION

[0005] The present disclosure is directed to bras, particularly sports bras, that include closure systems that are easier to clasp than conventional bra closure systems. In some embodiments, a closure system includes a hook assembly attached to a rigid supporting layer. In some embodiments, the closure system further includes a loop assembly including enlarged loops.

[0006] Some embodiments are directed to a bra including a closure system, the closure system including a first layered fabric body, a second layered fabric body, a loop assembly secured to the first layered fabric body, and a hook assembly secured to the second layered fabric body, where the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body, where the second layered fabric body comprises a flexible supporting layer, and where the flexible supporting layer is configured to provide rigidity to the

second layered fabric body such that the second layered fabric body maintains a flat configuration when it is secured to the first layered fabric body.

[0007] Some embodiments are directed to a closure system for a bra, the closure system including a loop assembly secured to a first layered fabric body, the first layered fabric body including a top fabric layer, a top adhesive layer disposed on a bottom face of the top fabric layer, a bottom fabric layer, a bottom adhesive layer disposed on a top face of the bottom fabric layer, and a cushioning layer disposed between the top adhesive layer and the bottom adhesive layer, where the top adhesive layer and the bottom adhesive layer are configured to secure the flexible supporting layer between the top fabric layer and the bottom fabric layer; and a hook assembly secured to a second layered fabric body, the second layered body including a top fabric layer, a top adhesive layer disposed on a bottom face of the top fabric layer, a bottom fabric layer, a bottom adhesive layer disposed on a top face of the bottom fabric layer, and a flexible supporting layer disposed between the top adhesive layer and the bottom adhesive layer, where the top adhesive layer and the bottom adhesive layer are configured to secure the flexible supporting layer between the top fabric layer and the bottom fabric layer, and where the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body.

[0008] Some embodiments are directed to a bra including a closure system, the closure system including a first layered fabric body, a second layered fabric body, a loop assembly secured to the first layered fabric body, the loop assembly including a plurality of loops, where each of the hooks has an aspect ratio of at least 2:1, a hook assembly secured to the second layered fabric body, the hook assembly including a plurality of hooks, where each of the hooks has an aspect ratio of at least 1:1, where the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body, where the second layered fabric body includes a flexible supporting layer, and where each of the loops extends perpendicularly outward from a top surface of the first layered fabric body.

Description

BRIEF DESCRIPTION OF THE DRAWINGS/FIGURES

[0009] FIG. 1A illustrates a bra according to the prior art.

[0010] FIG. 1B illustrates the bra of FIG. 1A in use.

[0011] FIG. 2A illustrates a bra according to some embodiments.

[0012] FIG. 2B illustrates the bra of FIG. 2A in use.

[0013] FIG. 3A illustrates a top view of a loop assembly of a closure system for a bra according to some embodiments.

[0014] FIG. 3B illustrates a bottom view of the loop assembly of FIG. 3A.

[0015] FIG. 3C illustrates a side view of the loop assembly system of FIG. 3A.

[0016] FIG. 3D illustrates an exploded view of the loop assembly of FIG. 3A.

[0017] FIG. 4A illustrates a top view of a loop assembly of a closure system for a bra according to some embodiments.

[0018] FIG. 4B illustrates a bottom view of the loop assembly of FIG. 4A.

[0019] FIG. 4C illustrates a side view of the loop assembly system of FIG. 4A.

[0020] FIG. 4D illustrates an exploded view of the loop assembly of FIG. 4A.

[0021] FIG. 5A illustrates a top view of a hook assembly of a closure system for a bra according to some embodiments.

[0022] FIG. 5B illustrates a bottom view of the hook assembly of FIG. 5A.

[0023] FIG. 5C illustrates a side view of the hook assembly system of FIG. 5A.

[0024] FIG. 5D illustrates an exploded view of the hook assembly of FIG. 5A.

[0025] FIG. 6A illustrates a top view of a hook assembly of a closure system for a bra according to

some embodiments.

[0026] FIG. **6B** illustrates a bottom view of the hook assembly of FIG. **6A**.

[0027] FIG. **7A** is a front view of a bra according to some embodiments.

[0028] FIG. **7B** is a side view of a the bra of FIG. **7A**.

[0029] FIG. **8** is a front view of a bra according to some embodiments.

[0030] FIG. **9** is an exploded view of a construction of a moldable contour structure according to some embodiments.

[0031] FIG. **10A** illustrates a pattern for a moldable contour shaper according to some embodiments.

[0032] FIG. **10B** illustrates a moldable contour shaper cut from the pattern of FIG. **10A**.

[0033] FIG. **11A** is a perspective view of a mold head used to shape a moldable contour shaper according to some embodiments.

[0034] FIG. **11B** is a side view of the mold head of FIG. **11A**.

[0035] FIG. **12** is an exploded view of a molding assembly according to some embodiments.

[0036] FIG. **13A** is a front view of a molded moldable contour shaper according to some embodiments.

[0037] FIG. **13B** is a perspective view of the molded moldable contour shaper of FIG. **13A**.

[0038] FIG. **14A** is a front view of a molded moldable contour shaper according to some embodiments.

[0039] FIG. **14B** is a perspective view of the molded moldable contour shaper of FIG. **13A**.

[0040] FIG. **15A** is a front view of a molded bra cup according to some embodiments.

[0041] FIG. **15B** is a front view of the molded bra cup of FIG. **18A** after removal of excess fabric.

[0042] FIG. **16** is an inside view of stretched bra cups according to some embodiments.

[0043] FIG. **17** is an inside view of relaxed bra cups according to some embodiments.

[0044] FIG. **18** illustrates a top view of a contour of a bra against a body according to some embodiments.

DETAILED DESCRIPTION OF THE INVENTION

[0045] The present invention(s) will now be described in detail with reference to embodiments thereof as illustrated in the accompanying drawings. References to “some embodiments”, “one embodiment”, “an embodiment”, “an exemplary embodiment”, etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to affect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements. Additionally, generally, the left-most digit(s) of a reference number identifies the drawing in which the reference number first appears.

[0046] The closure systems typically included on bras are difficult for wearers to clasp for a number of reasons. For example, FIGS. **1A** and **1B**, which are meant to be exemplary only, show a bra **100** including a conventional closure system **110**. As shown in FIG. **1B**, in order for a wearer **120** to fasten bra panels **102** and **104** together, she must grasp hook assembly **112** at its end such that she is holding the entirety of hook assembly **112** in her hand. This causes at least two problems—first, the wearer's thumb can get in the way of the hooks and can contort the hook assembly making alignment difficult, and second, it causes the wearer's arm to be positioned awkwardly such that her shoulder is strained. However, if she were to hold hook assembly **112** any further away from its edge, she would not have sufficient control to align and couple together the hooks with eyes **116** within loop assembly **114**. Consequently, there exists a need for a bra having a closure system that is easy for the wearer to clasp without straining her arm.

[0047] Accordingly, in some embodiments described herein, a bra having a closure system designed to be easily clasped is provided. For example, in contrast to the bra shown in FIGS. 1A and 1B, the bra shown in FIGS. 2A and 2B may allow a wearer 220 to grasp hook assembly 212 at a point much closer to the side of her body. This may be accomplished by providing rigidity to hook assembly 212 through incorporation of a flexible supporting layer within hook assembly 212. Because hook assembly 212 is rigid, the wearer does not need to provide support with her hand while fastening panels 202 and 204 together, which prevents her thumb from getting in the way of the hooks and reduces the strain on her shoulder. Furthermore, the hooks in hook assembly 212 and the loops 216 in loop assembly 214 may be much larger than, for example, the hooks and loops included in conventional closure system 110. This size increase may facilitate alignment of the hooks with the loops, and it may also reduce the tensile stresses across the closure system, since the stresses are distributed across larger areas. By reducing these applied stresses, the life of the bra may be extended.

[0048] For example, in one embodiment, as shown in FIGS. 2A and 2B, bra 200 includes a closure system 210 configured to connect together a first bra panel 202 and a second bra panel 204. In some embodiments, closure system 210 includes a hook assembly 212 and a loop assembly 214. Loop assembly 214 may be secured to a first layered fabric body configured to be coupled to first bra panel 204, for example as shown in FIGS. 3D and 4D, and hook assembly 212 may be secured to a second layered fabric body configured to be coupled to a second bra panel 202, for example as shown in FIG. 3D. The layered fabric bodies may be formed as tabs or flaps. In some embodiments, hook assembly 212 is configured to interface with loop assembly 214 to secure first bra panel 204 to second bra panel 202 in order to fasten the bra. In some embodiments, the first layered fabric body and the second layered fabric body overlap when hook assembly 212 interfaces with loop assembly 214. FIGS. 3A-3D show details of a loop assembly 300, which may correspond to loop assembly 214, according to some embodiments. For example, as shown in FIGS. 3A and 3B, loop assembly 300 may include a plurality of elongated loops 310 coupled to a top face 302 of loop assembly 300. Loop assembly 300 may further include a bottom face 304 opposite top face 302, which may contact a wearer's skin. In some embodiments, loops 310 are assembled in rows, and are evenly spaced apart along the length of loop assembly 300.

[0049] In some embodiments, loops 310 have an aspect ratio of at least 2:1. As used herein, "aspect ratio" means the ratio between the length and the width of a component. For example, in some embodiments, length 314 of loops 310 is at least twice as long as width 312 of loops 310. In some embodiments, length 314 is at least 1 cm, which is double the length of a typical eye used in conventional bra closure systems. In some embodiments, width 310 is 0.5 cm.

[0050] As shown in FIGS. 3C and 3D, loop assembly 300 may be a layered fabric body. For example, in some embodiments, loop assembly 300 includes a top body fabric layer 320 on which loops 310 are disposed, and a bottom body fabric layer 350, and a foam layer 360 disposed between top body fabric layer 320 and bottom body fabric layer 350. Top adhesive layer 330 may connect top body fabric layer 320 to a top face of foam layer 360, and bottom adhesive layer 340 may connect bottom body fabric layer 350 to a bottom face foam layer 360. In some embodiments, foam layer 360 provides cushioning to ensure comfort of the wearer. Foam layer 360 may also provide stiffness to loop assembly 300.

[0051] In some embodiments, an angle 318 between a top face of loops 310 and top face of loop assembly 302 is $90^\circ \pm 5^\circ$. In some embodiments, loops 310 extend perpendicularly outward from a top face 302.

[0052] In some embodiments, an angle between a top face of the loops and the top face of the loop assembly may be smaller than 90° , and greater than 30° . For example, as shown in FIGS. 4A-4D, an angle 418, between a top face of loops 410 and a top face 402 of loop assembly 400, may be 85° , 80° , 75° , 70° , 65° , 60° , 55° , 50° , 45° , 40° , or 35° , or within a range having any two of these values as endpoints, inclusive of the endpoints. Ensuring that the loops are raised away from the

top face of the loop assembly prevents the need for the wearer to bend the loop assembly in order to lift the loops away from the top face such that the hooks may be inserted. This increases ease of fastening. Furthermore, bending the loops to an angle allows for the loops to be set into a traditional seam on loop assembly **400**, which enables loop assembly **400** to be manufactured using existing industry machinery, thereby reducing production costs. Alternatively, loop assembly **400** may be manufactured using modified existing industry machinery, which may be optimized for production of the loop assembly. Or, loop assembly **400** may be manufactured using apparel or soft goods industry machinery that is not typically used to produce women's undergarments such that typical machinery for manufacturing bras is not necessary. Accordingly, additional equipment may not need to be purchased in order to manufacture the loop assembly, thereby reducing production costs.

[0053] Loop assembly **400** may also include a bottom face **404**. In some embodiments, loop assembly **400** is a layered fabric body, similar to loop assembly **300**. For example, loop assembly **400** may include a top body fabric layer **420**, a bottom body fabric layer **450**, and a foam layer **460** disposed between top body fabric layer **420** and bottom body fabric layer **450**. Top adhesive layer **430** may connect top body fabric layer **420** to foam layer **460**, and bottom adhesive layer **440** may connect bottom body fabric layer **450** to foam layer **460**. However, in some embodiments, loop assembly **400** is reinforced by stitching **406** around the perimeter of loop assembly **400**, and over the ends of loops **410**, thereby securing the loops to the loop assembly.

[0054] An aspect ratio of loops **410** may be similar to the aspect ratio of loops **310**. For example, loops **410** may have an aspect ratio of at least 2:1 such that, in some embodiments, length **414** of loops **410** is at least twice as long as width **412** of loop **410**. In some embodiments, length **414** is at least 1 cm. In some embodiments, width **410** is 0.5 cm.

[0055] FIGS. 5A-5D show details of a hook assembly **500**, which may correspond to hook assembly **212**, shown in FIG. 2. Hook assembly **500** may include a plurality of hooks disposed on a bottom face **504** of hook assembly **500**. Hook assembly **500** may further include a top face **502**, which may be the outermost facing surface of hook assembly **500**. In some embodiments a design may be included on top face **502**. For example, in some embodiments, top face **502** includes at least one of a logo, a brand name, a monogram, or any other desired design. In some embodiments the design is either screen printed, embroidered, embossed, debossed, heat set, or laminated onto top surface **502**. However, any method suitable to add a design to a fabric may be used.

[0056] In some embodiments, hook assembly **500** is a layered fabric body. For example, hook assembly **500** may include a top fabric layer **520**, a bottom fabric layer **550**, and a flexible supporting layer **560** disposed between top fabric layer **520** and bottom fabric layer **550**. In some embodiments, hooks **510** extend through a plurality of slits within top fabric layer **520**. In some embodiments, top body fabric layer is attached to supporting layer **560** by top adhesive layer **530**, and bottom body fabric layer is attached to supporting layer **560** by bottom adhesive layer **540**. In some embodiments, for example as shown in FIGS. 6A and 6B, top fabric layer **520** and bottom fabric layer **550** are sewn together. Stitching **606** may reinforce hook assembly **500** and provide additional durability. However, in some embodiments, top fabric layer **520** and bottom fabric layer **550** are joined by bonding, lamination, or ultrasonic attachment, or through any other process suitable for joining two layers of fabric.

[0057] Flexible supporting member **560** may provide rigidity to hook assembly **500**, which allows for hook assembly **500** to have a length **506** which is significantly greater than a length of a conventional hook assembly typically used in bras. In some embodiments, a length **508** of flexible supporting member **560** is in a range of 5 cm to 20 cm, including subranges. For example, flexible supporting member **560** may have a length of 5 cm, 6 cm, 7 cm, 8 cm, 9 cm, 10 cm, 11 cm, 12 cm, 13 cm, 14 cm, 15 cm, 16 cm, 17 cm, 18 cm, 19 cm, 20 cm, or within a range having any of these values as endpoints, inclusive of the endpoints. In some embodiments, a width **507** of flexible supporting member **560** is in a range of 1 cm to 20 cm, including subranges. For example, flexible

supporting member **560** may have a width of 1 cm, 1.7 cm, 2 cm, 3 cm, 4 cm, 5 cm, or 6 cm, 7 cm, 8 cm, 9 cm, 10 cm, 11 cm, 12 cm, 13 cm, 14 cm, 15 cm, 16 cm, 17 cm, 18 cm, 19 cm, or 20 cm, or within a range having any two of these values as endpoints, inclusive of the endpoints. The rigidity provided by flexible supporting member **560** may also enable hook assembly **500** to maintain a flat configuration when coupled with a loop assembly. This flat configuration may help ensure comfort of the wearer and may provide a sleek, neat look.

[0058] In some embodiments, flexible supporting member **560** includes a plurality of slots, or perforations, **562**. Slots **562** may reduce the weight of flexible supporting member **560** for enhanced comfort of the wearer.

[0059] In some embodiments, for example as shown in FIG. 5C, hooks **510** are fixed into flexible supporting layer **560**. Coupling hooks **510** with supporting layer **560** in this way provides enhanced stability and rigidity to the hooks, which may improve the ease of clasping the closure system, since the wearer does not need to worry about the hooks bending or warping.

[0060] In some embodiments, flexible supporting layer **560** is made from a flexible polymer. For example, flexible supporting layer **560** may be made from a thermoplastic polyurethane (TPU), a thermoplastic rubber (TPR), a thermoplastic elastomer (TPE), nylon, a carbon-based material, fiber glass, or any other material suitable for injection molding.

[0061] In some embodiments, flexible supporting layer **560** is disposed between top fabric layer **520** and bottom fabric layer **550**. However, alternative configurations may be used. For example, in some embodiments, flexible supporting layer **560** is disposed on an outer surface of top fabric layer **520** such that flexible supporting layer **560** is the topmost layer of hook assembly **500**. Similarly, in some embodiments, flexible supporting layer **560** is disposed on an outer surface of bottom fabric layer **550** such that flexible supporting layer **560** is the bottommost layer of hook assembly **500**.

[0062] As discussed above, hooks **510** are significantly larger than the hooks typically used in bra closure systems. Because of the large size of hooks **510**, fewer hooks are necessary to clasp the closure system, which simplifies alignment of the hooks with the loops. For example, while typical closure systems require three to four hooks, the closure systems described herein may only utilize two hooks. However, the closure systems may alternatively include 3 hooks or 4 hooks, depending on the desired design.

[0063] In some embodiments, hooks **510** have an aspect ratio of at least 1:1. For example, in some embodiments, length **514** of hooks **510** is approximately equal to width **512** of hooks **510**. In some embodiments, hooks **510** have a length **514** of at least 1 cm, and a width **512** of at least 1 cm. In some embodiments, width **512** is in a range of 25% to 30% of a width **505** of hook assembly **500**.

[0064] Width **512** of hooks **510** may correspond to a length of a loop, for example length **312** of loop **300**, shown in FIGS. 3A-3D. In some embodiments, hooks **510** have a flat portion **511** and a curved portion **513**, for example as shown in FIG. 5C. In some embodiments, a length **514** of flat portion **511** is greater than a length **516** of curved portion **513**. For example, length **514** may be at least two times greater than length **516**. In some embodiments, length **516** corresponds to a height of a loop, for example loop **310**, described above.

[0065] As described previously, the addition of a flexible supporting layer, in conjunction with the large sizes of the loops and the hooks, may increase the ease of fastening the closure system and eliminate the need to put the bra on backwards, fasten it, and then turn it around. The rigidity provided by the flexible supporting layer within the hook assembly may enable the wearer to grasp the hook assembly at a point closer to her side because she would not need to provide stability to the hook assembly with her hand. Furthermore, the large loops and hooks may facilitate alignment, which may also prevent the need for the wearer to grasp the hook assembly at a point close to its end, since it may be unnecessary for the wearer's fingers to guide the hooks into the loops.

[0066] In some embodiments, the bra and the fabric layers of the loop assembly and the eye assembly are made from the same fabric. However, the bra may be made from a first material, while the fabric layers of the loop assembly and the hook assembly may be made from a second

material. In some embodiments, the fabric layers of the loop assembly and the hook assembly are configured to stretch in at least two directions. In some embodiments, the bra and the fabric layers are made from natural materials, for example a single-knit cotton, multi-knit cotton, or hemp; man-made fibers, for example nylon, polyester, suede, microsuede, microfiber, or 3D printed materials; recycled materials, for example plastics or recycled polyesters, or any other material suitable for creating articles of apparel. In some embodiments, the bra and fabric layers are made from a combination of any of the materials described herein.

[0067] In some embodiments, the adhesive layers described herein are glue film layers. In some embodiments, the adhesive layers are made from a heat-activated adhesive. In some embodiments, the glue film layers are applied to each body fabric layer using a large glue roll manufacturing assembly. In some embodiments, the glue film layers are applied to each body fabric layer by hand.

[0068] In some embodiments the hooks are made from a first material, and the loops are made from a second material. In some embodiments, the hooks and the loops are made from the same material. In some embodiments, the loops and the hooks are made from a metal, for example a metal alloy, a plastic, or any other material suitable for incorporation into an article of apparel.

[0069] In embodiments, a bra, including the bras disclosed herein, may also include a moldable contour shaper instead of, or in addition to, underwire structures that are typically included in bras to support and shape breast tissue. As discussed, above, typical underwire structures are formed from a rigid material and have a thin, continuous width. These underwire structures circumscribe the sides and lower edges of the breast tissue. When the underwire structures are flush with the wearer's body, they secure the breast tissue, which aids in restricting movement and keeps the cups of the bra in a desired shape, which helps shape the breast tissue. However, this requires the bra to fit nearly perfectly, because if the breast tissue does not fill the bra cups entirely, the breast tissue will likely sag and pool in the bottom of the cup. This may cause a gap between the breast tissue and the top of the cups, which is visible through clothing. The pooled breast tissue may also overlap the underwire, thereby creating an undesirable shape at the bottom of the breast.

Furthermore, these underwire structures often cause discomfort of the wearer because they dig into the wearer's skin, and when the bra becomes worn out over time, the underwire structures can poke through the fabric and poke the wearer.

[0070] The moldable contour shapers described herein mitigate the problems caused by conventional underwire structures. For example, the moldable contour shapers described herein may be molded, three-dimensional structures that are configured to bend during wear, and contour the breast tissue without being contoured to the wearer's chest wall. This flexibility may allow a bra to accommodate variations in the bodies of different wearers who may all require the same size bra. The moldable contour shapers may also be thicker than conventional underwire structures, and may accordingly have increased surface areas in relation to conventional underwire structures, which may result in a more even distribution of pressure across the chest of the wearer, which may be particularly beneficial for wearers having increased breast tissue mass.

[0071] In embodiments, as shown in FIGS. 7A, 7B, and 8, bra **200** may include bra cups **230** with a moldable contour shaper **240** included therein. Moldable contour shaper **240** may be positioned underneath the breast tissue of wearer **220**, and may extend upwardly around the sides of the breasts. In some embodiments, moldable contour shaper **240** is a unitary structure, for example as shown in FIG. 8. However, in some embodiments, each bra cup **230** is outfitted individually with a moldable contour shaper **240**. The shape and number of moldable contour shapers **240** included in a bra depends on the type of bra and the desired function of the moldable contour shapers. For example, a moldable contour shaper having a unitary structure may be beneficial for use in a sports bra, where a high level of tissue support is desired, since a unitary structure may provide increased stability to the bra. However, bra cups individually including moldable contour shapers may be beneficial for use in a push-up bra, where increased lift is desired, or where one breast requires greater lift than the other due to natural unevenness of the breast tissue.

[0072] Moldable contour shaper **240** may have a tapered design such that it is wider around the outside of the breasts, and narrower as it extends under the breasts and around the insides of the breasts. The tapered design may provide increased support to the breast tissue by restricting lateral movement of the breasts, and may also contour the breast tissue by pushing the breasts toward the center of the body, thereby creating a lifted shape as well as cleavage between the breasts.

[0073] Moldable contour shaper **240** may be formed in the shape of a “W” when it is a unitary structure, or may be formed in the shape of a “U” for use in individual bra cups. The “W” and “U” shapes of moldable contour shaper **240** may follow a desired outline of the breast tissue, and accordingly, may maintain the breasts in a desired position. Moldable contour shaper **240** may alternatively be formed in any shape desirable for maintaining breast tissue in a certain position. For example, moldable contour shaper **240** may have a custom shape that is individualized for a particular wearer's breast tissue and fit preferences.

[0074] In some embodiments, moldable contour shaper **240** has a width in a range of from 0.6 cm to 15 cm, including subranges. For example, contour shaper **240** may have a width of 0.6 cm, 1 cm, 2 cm, 3 cm, 4 cm, 5 cm, 6 cm, 7 cm, 8 cm, 9 cm, 10 cm, 11 cm, 12 cm, 13 cm, 14 cm, 15 cm, or within a range having any two of these values as endpoints, inclusive of the endpoints.

[0075] In some embodiments, for example as shown in FIG. 9, moldable contour shaper **240** may be made from a plurality of plies **900**. Each ply **910** may be made of a different material; however, in some embodiments all of the plies **910** are made of the same material. Each ply **910** may be made from woven carbon, woven nylon, knit nylon, resin, polyurethane, fiberglass, combinations thereof, or any other thermally activated or chemically activated semi-rigid stiffening material that is suitable for use in articles of apparel. In some embodiments, each ply **910** is configured to be placed in an injection mold, and be covered by a resin or an injection molded material during an injection molding process. In some embodiments, one or more of the materials used to make each of the plies **910** is perforated or breathable. The plurality of plies **900** may be created as an initial composite, for example as shown in FIG. 10A, from which a pattern **920** of a moldable contour shaper may be cut, for example into a layered strip or strips.

[0076] Pattern **920** may be W-shaped, or U-shaped, for example to create the W-shaped and U-shaped moldable contour shapers described above. However, pattern **920** may be any desirable shape for contouring the breast tissue. For example, pattern **920** may have a half-moon shape, which may be optimized to lift the breast tissue by providing a high level of support underneath the breast.

[0077] Plies **900** may then be cut, placed in a mold, heated, chemically activated, or placed in an injection mold to activate the thermally-activated properties of each individual ply **910**, and then cooled to set the shape of the resulting moldable contour shaper **240**, for example as shown in FIG. 10B. After molding, the shape of moldable contour shaper **240** may shift from having a substantially flat configuration, for example as shown in FIG. 10A to a three-dimensional configuration, for example as shown in FIG. 10B. The three-dimensional shape of molded moldable contour shaper **240** allows for moldable contour shaper **240** to follow the shape of the bra cups, thereby providing rigidity to the bra cups, which may enhance the bra's ability to hold the breast tissue in a desired position. The curvature of moldable contour shaper **240** may be dependent upon the shape of the mold used.

[0078] FIGS. 11A and 11B illustrate a mold assembly **1100** which may be used to thermoform plies **900**. For example, the cut plies may be placed on a bottom mold **1120**, which may be formed in the shape of breasts. Top mold **1110** may be placed on top of bottom mold **1120**, thereby sandwiching the plies between each mold, and creating the desired final shape of the resulting moldable contour shaper **240**. Mold assemblies of various shapes and sizes may be used to accommodate bras having different styles and sizes. The plies may alternatively be shaped by an injection mold, a 3D printed mold, or an open mold assembly.

[0079] In some embodiments, mold assembly **1100** is a mold assembly that may be used for

manufacturing the bra cups. By using the same mold for production of both the moldable contour shaper and the bra cups, the cost of specific mold creation is reduced, and the moldable contour shaper is guaranteed to fit perfectly into the cups. For example, as shown in FIG. 12, moldable contour shaper **240** may be disposed between two foam layers **1102**, which are in between two fabric layers **1104**. The same mold assembly **1100** used to form the moldable contour shaper may be used to form the foam layers **1102** into cups with moldable contour shaper(s) **240** incorporated therein.

[0080] As discussed above, in some embodiments moldable contour shaper **240** includes two individual structures, for example as shown in FIGS. 13A and 13B. The individual moldable contour shapers **240** may be the same size, or may have different sizes to accommodate for uneven breast tissue. However, in some embodiments moldable contour shaper **240** is a single, continuous structure configured to support both breasts, for example as shown in FIGS. 14A and 14B.

[0081] After molding, excess fabric **260** may be cut from cups **230** to create a finalized cup structure for incorporation into a bra, for example as shown in FIGS. 15A and 15B.

[0082] The bras described herein may be configured to stretch to fit a wearer's body. For example, FIG. 16 illustrates an inside view of bra cups **230** in an unstretched state, while FIG. 17 illustrates the bra cups **230** in a stretched configuration.

[0083] In some embodiments, bra cups **230** include a high impact absorber foam **232** disposed beneath moldable contour shaper **240**. The high impact absorber foam **232** may provide cushioning beneath the breast tissue to decrease impact during physical activity, thereby increasing comfort of the wearer. High impact absorber foam may be made from a dense foam, a compressed foam, an open cell foam, a closed cell foam, or any other foam suitable for use in an article of apparel.

[0084] In some embodiments, bra cups **230** may also include a high stretch recovery foam **238** disposed at the top of the cups. High stretch recovery foam **236** may provide cushioning to the wearer, and may also be configured to stretch up to 50% of its original length and up to 50% of its original width.

[0085] In some embodiments, bra cups **230** include flared contouring **234** at the underarm. Flared contouring **234** may be designed to provide enhanced comfort of the wearer by preventing cups **230** from extending into the wearer's underarms.

[0086] In some embodiments, bra cups **230** include high center front anchors **236**, extending from the high impact absorber foam **232**. Front anchors **236** may be configured to better cushion the chest and aid in impact absorption between the breasts.

[0087] In some embodiments, when bra cups **230** are stretched to fit the body, for example as shown in FIG. 18, moldable contour shaper **240** may sit against the chest of wearer **220**, and the tapered structure of moldable contour shaper **240** may push the breast tissue **222** of wearer **220** into the cups **230**, thereby filling the entire volume of the cups. By filling the entire volume of the cups **230** with the breast tissue **222**, the breasts may follow the shape of the cups, resulting in a contoured appearance.

[0088] Although the bra cups described herein have been described in the context of a bra, they could be incorporated into other articles of apparel, for example bathing suits, shirts, compression garments, or other garments.

[0089] Some embodiments are directed to a bra including a closure system, the closure system including a first layered fabric body, a second layered fabric body, a loop assembly secured to the first layered fabric body, and a hook assembly secured to the second layered fabric body, where the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body, where the second layered fabric body comprises a flexible supporting layer, and where the flexible supporting layer is configured to provide rigidity to the second layered fabric body such that the second layered fabric body maintains a flat configuration when it is secured to the first layered fabric body.

[0090] In any of the various embodiments discussed herein, the hook assembly is coupled to the

flexible supporting layer.

[0091] In any of the various embodiments discussed herein, the loop assembly includes a plurality of loops, where each of the loops has an aspect ratio of at least 2:1.

[0092] In any of the various embodiments discussed herein, the hook assembly includes a plurality of hooks, wherein each of the hooks has an aspect ratio of at least 1:1.

[0093] In any of the various embodiments discussed herein, the second layered fabric body is configured to overlap the first layered fabric body.

[0094] In any of the various embodiments discussed herein, the loop assembly comprises a plurality of loops, wherein each of the loops extends perpendicularly outward from a top surface of the first layered fabric body.

[0095] Some embodiments are directed to a closure system for a bra, the closure system including a loop assembly secured to a first layered fabric body, the first layered fabric body including a top fabric layer, a top adhesive layer disposed on a bottom face of the top fabric layer; a bottom fabric layer; a bottom adhesive layer disposed on a top face of the bottom fabric layer, and a cushioning layer disposed between the top adhesive layer and the bottom adhesive layer, where the top adhesive layer and the bottom adhesive layer are configured to secure the flexible supporting layer between the top fabric layer and the bottom fabric layer; and a hook assembly secured to a second layered fabric body, the second layered body including a top fabric layer, a top adhesive layer disposed on a bottom face of the top fabric layer, a bottom fabric layer, a bottom adhesive layer disposed on a top face of the bottom fabric layer, and a flexible supporting layer disposed between the top adhesive layer and the bottom adhesive layer, where the top adhesive layer and the bottom adhesive layer are configured to secure the flexible supporting layer between the top fabric layer and the bottom fabric layer, and where the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body.

[0096] In any of the various embodiments discussed herein, the flexible supporting layer has a length in a range of 5 cm to 20 cm.

[0097] In any of the various embodiments discussed herein, the flexible supporting layer has a width in a range of 1 cm to 20 cm.

[0098] In any of the various embodiments discussed herein, the loop assembly includes a plurality of loops assembled in rows evenly spaced apart along the length of the first layered fabric body.

[0099] In any of the various embodiments discussed herein, the top fabric layer of the first layered fabric body and the bottom fabric layer of the first layered fabric body are sewn together, bonded together, laminated together, or ultrasonically attached to each other.

[0100] In any of the various embodiments discussed herein, the top fabric layer of the second layered fabric body and the bottom fabric layer of the second layered fabric body are sewn together, bonded together, laminated together, or ultrasonically attached to each other.

[0101] In any of the various embodiments discussed herein, the hook assembly includes a plurality of hooks extending through slits in the top fabric layer of the second layered fabric body.

[0102] In any of the various embodiments discussed herein, each of the top fabric layer of the first layered fabric body, the bottom fabric layer of the first layered fabric body, the top fabric layer of the second layered fabric body, and the bottom fabric layer of the second layered fabric body are configured to stretch in at least two directions.

[0103] In any of the various embodiments discussed herein, the flexible supporting layer is perforated.

[0104] In any of the various embodiments discussed herein, the flexible supporting layer is made of TPU.

[0105] Some embodiments are directed to a bra, including a closure system, the closure system including a first layered fabric body, a second layered fabric body, a loop assembly secured to the first layered fabric body, the loop assembly including a plurality of loops, wherein each of the loops comprises an aspect ratio of at least 2:1, a hook assembly secured to the second layered fabric

body, the hook assembly including a plurality of hooks, wherein each of the hooks comprises an aspect ratio of at least 1:1, where the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body, where the second layered fabric body comprises a flexible supporting layer, and where each of the loops extends perpendicularly outward from a top surface of the first layered fabric body.

[0106] In any of the various embodiments discussed herein, the hook assembly is coupled to the flexible supporting layer in a fixed way.

[0107] In any of the various embodiments discussed herein, each of the hooks has a width within a range of 25% to 30% of a width of the second layered fabric body.

[0108] In any of the various embodiments discussed herein, each of the hooks has a flat portion and a curved portion, and where each of the flat portions has a length greater than a length of each of the curved portions.

[0109] In any of the various embodiments discussed herein, the loop assembly and the hook assembly each are made of a metal alloy.

[0110] It is to be appreciated that the Detailed Description section, and not the Summary and Abstract sections, is intended to be used to interpret the claims. The Summary and Abstract sections may set forth one or more but not all exemplary embodiments of the present invention(s) as contemplated by the inventor(s), and thus, are not intended to limit the present invention(s) and the appended claims in any way.

[0111] The present invention(s) have been described above with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined so long as the specified functions and relationships thereof are appropriately performed.

[0112] The foregoing description of the specific embodiments will so fully reveal the general nature of the invention(s) that others can, by applying knowledge within the skill of the art, readily modify and/or adapt for various applications such specific embodiments, without undue experimentation, without departing from the general concept of the present invention(s). Therefore, such adaptations and modifications are intended to be within the meaning and range of equivalents of the disclosed embodiments, based on the teaching and guidance presented herein. It is to be understood that the phraseology or terminology herein is for the purpose of description and not of limitation, such that the terminology or phraseology of the present specification is to be interpreted by the skilled artisan in light of the teachings and guidance.

[0113] The breadth and scope of the present invention(s) should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

Claims

1. A bra, comprising a first panel and a second panel; and a closure system configured to join the first panel and the second panel, the closure system comprising: a first layered fabric body comprising a top layer, a middle layer, and a bottom layer; a second layered fabric body; a loop assembly secured to the first layered fabric body, wherein the loop assembly comprises loops, wherein a first portion of each loop is disposed between the top layer and the middle layer, and wherein a second portion of each loop extends through the top layer; and a hook assembly secured to the second layered fabric body, wherein the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body.
2. The bra of claim 1, wherein the first portion of each loop is angled relative to the second portion of each loop.
3. The bra of claim 2, wherein the first portion is parallel to the top layer, and wherein the second

portion is angled between about 30° and about 90° relative to the top layer.

4. The bra of claim 1, further comprising a first bra cup, the first bra cup comprising a moldable contour shaper.

5. The bra of claim 1, wherein the top layer comprises fabric, the middle layer comprises foam, and the bottom layer comprises fabric.

6. The bra of claim 1, wherein the bottom layer is a skin-contact layer.

7. The bra of claim 1, wherein the hook assembly comprises hooks configured to engage with the loops.

8. The bra of claim 7, wherein the second layered fabric body comprises a top layer comprising fabric, a middle layer, and a bottom layer comprising fabric.

9. The bra of claim 8, wherein the hooks extend through the top layer of the second layered fabric body.

10. The bra of claim 8, wherein middle layer is a flexible supporting layer, and wherein the hook assembly comprises hooks fixed to the middle layer.

11. The bra of claim 10, wherein the flexible supporting layer comprises slots or perforations.

12. A bra, comprising a first panel and a second panel; and a closure system configured to join the first panel and the second panel, the closure system comprising: a first layered fabric body comprising a top layer, a middle layer, and a bottom layer; a second layered fabric body; a loop assembly secured to the first layered fabric body, wherein the loop assembly comprises loops having an aspect ratio of 2:1 and extending perpendicular outward from the top layer, wherein each loop comprises a first end and a second end, and wherein each loop is coupled the top layer at the first end and at the second end, a hook assembly secured to the second layered fabric body, wherein the hook assembly is configured to interface with the loop assembly to secure the first layered fabric body to the second layered fabric body.

13. The bra of claim 12, wherein the loops are evenly spaced along a length of the loop assembly.

14. The bra of claim 12, wherein the loops are arranged in rows along the length of the loop assembly.

15. The bra of claim 12, wherein the hook assembly comprises hooks configured to be inserted into the loops between the first end and the second end of the loops.

16. A bra, comprising: a first fabric layer and a second fabric layer that define a first bra cup and a second bra cup; a moldable contour shaper configured to contour to a wearer's breast tissue, wherein the moldable contour shaper is disposed between the first fabric layer and the second fabric layer, wherein a width of the moldable contour shaper at a first portion is greater than a width of the moldable contour shaper at a second portion.

17. The bra of claim 16, further comprising a second moldable contour shaper disposed between the first fabric layer and the second fabric layer, wherein the moldable counter shaper is disposed in the first bra cup and the second moldable contour shaper is disposed in the second bra cup.

18. The bra of claim 17, wherein the moldable contour shaper and the second moldable contour shaper are continuous with each other.

19. The bra of claim 17, wherein the moldable contour shaper and the second moldable contour shaper are independently moldable.

20. The bra of claim 16, wherein the moldable contour shaper does not contour to the wearer's chest wall.
