

US Patent & Trademark Office

Patent Public Search | Text View

| | |
|----------------------|-----------------------|
| United States Patent | 12386209 |
| Kind Code | B2 |
| Date of Patent | August 12, 2025 |
| Inventor(s) | Wang; Yueqiang et al. |

Eyeglasses

Abstract

The present disclosure provides eyeglasses including: an eyeglass rim; an eyeglass temple, the eyeglass temple comprising a control circuit or a battery; a rotating shaft, the rotating shaft being configured to connect the eyeglass rim and the eyeglass temple, so that the eyeglass rim and the eyeglass temple are relatively rotated around the rotating shaft, and the rotating shaft being disposed with a rotating shaft wiring channel along an axial direction; and a speaker, the speaker comprising an earphone core, the speaker being connected to the eyeglass temple, the control circuit or battery in the eyeglass temple driving the earphone core to vibrate through the connection wire, wherein the earphone core vibrates to generate a driving force to drive a housing panel of the speaker to vibrate, and a straight line of the driving force being not parallel to a normal line of the housing panel.

Inventors: Wang; Yueqiang (Shenzhen, CN), Zhang; Haofeng (Shenzhen, CN), Li; Yongjian (Shenzhen, CN), Chen; Yunbin (Shenzhen, CN), You; Fen (Shenzhen, CN), Zhang; Lei (Shenzhen, CN)

Applicant: SHENZHEN SHOKZ CO., LTD. (Guangdong, CN)

Family ID: 1000008748364

Assignee: SHENZHEN SHOKZ CO., LTD. (Shenzhen, CN)

Appl. No.: 18/424728

Filed: January 26, 2024

Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20240168316 A1 | May. 23, 2024 |

Foreign Application Priority Data

| | | |
|----|----------------|---------------|
| CN | 201810975515.1 | Aug. 24, 2018 |
| CN | 201910009904.3 | Jan. 05, 2019 |

Related U.S. Application Data

continuation parent-doc US 18150785 20230105 US 11899284 child-doc US 18424728
 continuation parent-doc US 17138909 20201231 US 11906817 child-doc US 18150785
 continuation parent-doc WO PCT/CN2019/102407 20190824 PENDING child-doc US 17138909

Publication Classification

Int. Cl.: **G02C11/00** (20060101); **G02C5/14** (20060101); **G02C5/22** (20060101); **G02C11/06** (20060101); **H04R1/02** (20060101); **H04R1/04** (20060101); **H04R1/06** (20060101); **H04R1/10** (20060101); **H04R1/28** (20060101); **H04R9/02** (20060101); **H04R9/06** (20060101); **H04R25/00** (20060101); **H05K1/02** (20060101); **H05K1/18** (20060101)

U.S. Cl.:

CPC **G02C11/10** (20130101); **G02C5/14** (20130101); **G02C5/143** (20130101); **G02C5/22** (20130101); **G02C5/2254** (20130101); **G02C11/06** (20130101); **H04R1/02** (20130101); **H04R1/028** (20130101); **H04R1/04** (20130101); **H04R1/06** (20130101); **H04R1/10** (20130101); **H04R1/1008** (20130101); **H04R1/1033** (20130101); **H04R1/1041** (20130101); **H04R1/1075** (20130101); **H04R1/1083** (20130101); **H04R1/28** (20130101); **H04R9/02** (20130101); **H04R9/025** (20130101); **H04R9/06** (20130101); **H04R25/65** (20130101); **H05K1/028** (20130101); **H05K1/189** (20130101); **H04R2460/13** (20130101); **H05K2201/05** (20130101)

Field of Classification Search

CPC: G02C (11/10); G02C (5/14); G02C (5/143); G02C (5/22); G02C (5/2254); G02C (11/06); H04R (1/02); H04R (1/028); H04R (1/04); H04R (1/06); H04R (1/10); H04R (1/1008); H04R (1/1033)

USPC: 351/158

References Cited

U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name | U.S. Cl. | CPC |
|--------------|-------------|-----------------|----------|---------------|
| 4564955 | 12/1985 | Birch et al. | N/A | N/A |
| 4564988 | 12/1985 | Norrod | N/A | N/A |
| 10699691 | 12/2019 | Ye | N/A | G10K 11/17881 |
| 11310601 | 12/2021 | Zheng et al. | N/A | N/A |
| 2003/0228023 | 12/2002 | Burnett et al. | N/A | N/A |
| 2008/0074609 | 12/2007 | Ifergan | N/A | N/A |
| 2009/0290730 | 12/2008 | Fukuda et al. | N/A | N/A |
| 2011/0037663 | 12/2010 | Huang | N/A | N/A |
| 2011/0200204 | 12/2010 | Horigome et al. | N/A | N/A |
| 2012/0268326 | 12/2011 | Kai et al. | N/A | N/A |
| 2014/0334658 | 12/2013 | Wang et al. | N/A | N/A |

| | | | | |
|--------------|---------|------------|-----|-----|
| 2016/0234613 | 12/2015 | Westerkull | N/A | N/A |
|--------------|---------|------------|-----|-----|

FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC |
|-------------------|-------------------------|----------------|------------|
| 2090132 | 12/1990 | CN | N/A |
| 2733650 | 12/2004 | CN | N/A |
| 1722910 | 12/2005 | CN | N/A |
| 201163822 | 12/2007 | CN | N/A |
| 101453048 | 12/2008 | CN | N/A |
| 201499303 | 12/2009 | CN | N/A |
| 102141688 | 12/2010 | CN | N/A |
| 202001741 | 12/2010 | CN | N/A |
| 102457794 | 12/2011 | CN | N/A |
| 102523546 | 12/2011 | CN | N/A |
| 202306037 | 12/2011 | CN | N/A |
| 202353788 | 12/2011 | CN | N/A |
| 102647649 | 12/2011 | CN | N/A |
| 102769170 | 12/2011 | CN | N/A |
| 102938529 | 12/2012 | CN | N/A |
| 102623837 | 12/2012 | CN | N/A |
| 203801057 | 12/2013 | CN | N/A |
| 104023288 | 12/2013 | CN | N/A |
| 203851271 | 12/2013 | CN | N/A |
| 204230492 | 12/2014 | CN | N/A |
| 204289177 | 12/2014 | CN | N/A |
| 204425593 | 12/2014 | CN | N/A |
| 204465795 | 12/2014 | CN | N/A |
| 204929250 | 12/2014 | CN | N/A |
| 205039969 | 12/2015 | CN | N/A |
| 205336486 | 12/2015 | CN | N/A |
| 205669789 | 12/2015 | CN | N/A |
| 106252981 | 12/2015 | CN | N/A |
| 205790353 | 12/2015 | CN | N/A |
| 205793173 | 12/2015 | CN | N/A |
| 205946108 | 12/2016 | CN | N/A |
| 205987287 | 12/2016 | CN | N/A |
| 106792418 | 12/2016 | CN | N/A |
| 206292473 | 12/2016 | CN | N/A |
| 106954152 | 12/2016 | CN | N/A |
| 206340466 | 12/2016 | CN | N/A |
| 107046666 | 12/2016 | CN | N/A |
| 206481427 | 12/2016 | CN | N/A |
| 206563855 | 12/2016 | CN | N/A |
| 207039852 | 12/2017 | CN | N/A |
| 207070280 | 12/2017 | CN | N/A |
| 207070282 | 12/2017 | CN | N/A |
| 207266241 | 12/2017 | CN | N/A |
| 207427462 | 12/2017 | CN | N/A |
| 207995381 | 12/2017 | CN | N/A |
| 108776393 | 12/2017 | CN | N/A |

| | | | |
|-------------|---------|----|-----|
| 208079380 | 12/2017 | CN | N/A |
| 208273206 | 12/2017 | CN | N/A |
| 109151638 | 12/2018 | CN | N/A |
| 109495809 | 12/2018 | CN | N/A |
| 109511065 | 12/2018 | CN | N/A |
| 208780926 | 12/2018 | CN | N/A |
| 209267805 | 12/2018 | CN | N/A |
| 209358728 | 12/2018 | CN | N/A |
| 210868165 | 12/2019 | CN | N/A |
| 2797343 | 12/2013 | EP | N/A |
| 2013162452 | 12/2012 | JP | N/A |
| 2016158131 | 12/2015 | JP | N/A |
| 20090036497 | 12/2008 | KR | N/A |
| 20160147687 | 12/2015 | KR | N/A |

OTHER PUBLICATIONS

International Search Report in PCT/CN2019/102407 mailed on Nov. 8, 2019, 7 pages. cited by applicant

Written Opinion in PCT/CN2019/102407 mailed on Nov. 8, 2019, 10 pages. cited by applicant

First Office Action in Chinese Application No. 201810975515.1 mailed on Apr. 13, 2023, 23 pages. cited by applicant

“AfterShokz Trekz Titanium bone conduction headphones officially released in China”, Web Page<<http://it.people.com.cn/n1/2015/1219/c203889-27950331.html>>, Dec. 19, 2015. cited by applicant

“AfterShokz Trekz Titanium Bone Conduction Earphones”, Web Page<<http://www.cnmn.com.cn/ShowNews1.aspx?id=341792>>, Mar. 28, 2016. cited by applicant

“Sports Aesthetics AfterShokz Trekz Titanium Bone Conduction Headphones Experience”, Web Page<<http://www.jiguo.com/article/article/13045.html>>, Mar. 29, 2016. cited by applicant

“The “nightmare” of sports earphone manufacturers, Trekz titanium alloy bone conduction earphone experience”, Web Page<<http://m.jiguo.com/article/article/15678.html>>, Apr. 3, 2016. cited by applicant

“AfterShokz AS600 Trekz Titanium TM Bone Conduction Sports Earphone Crowd Testing Invitation and 10 Crowd Testing Reports Submitted by Crowd Testing Users”, Web Page<<http://test.smzdm.com/pingce/4070/>>, May 25, 2016 to Jun. 5, 2016. cited by applicant

“[Review] Favorite Black Technology—Trekz Titanium Bone Conduction Bluetooth Headset AS600”, Web Page<http://www.sohu.com/a/114223691_487951>, Sep. 12, 2016. cited by applicant

“Disassembly report: Shokz Trekz Titanium bone conduction sports headphones”, Web Page<<http://www.52audio.com/archives/40477.html>>, Apr. 1, 2020. cited by applicant

Qin, Datong et al., Modern Handbook Of Mechanical Design vol. 1, Chemical Industry Press, 2011, 12 Pages. cited by applicant

China Employment Training Technical Guidance Center of the Ministry of Labor and Social Security et al., Mechanisms & Mechanical Parts, China Central Radio and Television University Press, 2005, 22 Pages. cited by applicant

Primary Examiner: Stoffa; Wyatt A

Assistant Examiner: Gagnon; Grant A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 18/150,785, filed on Jan. 5, 2023, which is a continuation of U.S. patent application Ser. No. 17/138,909, filed on Dec. 31, 2020, which is a continuation of International Application No. PCT/CN2019/102407 filed on Aug. 24, 2019, which claims priority of Chinese Patent Application No. 201810975515.1 filed on Aug. 24, 2018, Chinese Patent Application No. 201910009904.3 filed on Jan. 5, 2019, and Chinese Patent Application No. 201920031804.6 filed on Jan. 5, 2019, the contents of each of which are hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates to the field of eyeglasses, and more specifically relates to eyeglasses having a speaker.

BACKGROUND

(2) With the development of speaker technology, electronic products (e.g., earphones, MP3, etc.) have been widely used. Speakers may have different product forms. For example, a speaker may be integrated on eyeglasses (e.g., sunglasses, swimming eyeglasses, etc.) or fixed inside an ear or near the ear of a user through a special structure (e.g., an ear hook). As the functions of the products become more diverse, there may be more and more internal modules and wiring of the speaker, and the wiring may be more and more complicated. The complicated wiring may greatly occupy an internal space of the product, and an unreasonable wiring distribution may cause wires to affect each other, which may cause an abnormal sound and affect the sound quality of the speaker. Therefore, it may be necessary to provide a more efficient wiring technology, so as to simplify a wiring approach of the speaker and improve the sound quality of the speaker.

SUMMARY

(3) An embodiment of the present specification may provide eyeglasses. The eyeglasses may include an eyeglass rim; an eyeglass temple, the eyeglass temple comprising a control circuit or a battery; a rotating shaft, the rotating shaft being configured to connect the eyeglass rim and the eyeglass temple, so that the eyeglass rim and the eyeglass temple are relatively rotated around the rotating shaft, and the rotating shaft is disposed with a rotating shaft wiring channel along an axial direction; a connection wire, the connection wire passing through the rotating shaft wiring channel and extending to the eyeglass rim and the eyeglass temple, respectively; and a speaker, the speaker comprising an earphone core, the speaker being connected to the eyeglass temple, the control circuit or battery in the eyeglass temple driving the earphone core to vibrate through the connection wire, wherein the earphone core vibrates to generate a driving force to drive a housing panel of the speaker to vibrate, and a straight line of the driving force is not parallel to a normal line of the housing panel.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure is further described in terms of exemplary embodiments. These exemplary embodiments are described in detail with reference to the drawings. These embodiments are non-limiting exemplary embodiments, in which like reference numerals represent similar structures, and wherein:

- (2) FIG. 1 is a block diagram illustrating a structure of a speaker according to some embodiments of the present disclosure;
- (3) FIG. 2 is a schematic diagram illustrating a structure of a flexible circuit board according to some embodiments of the present disclosure;
- (4) FIG. 3 is an exploded diagram illustrating a partial structure of a speaker according to some embodiments of the present disclosure;
- (5) FIG. 4 is a partial sectional view illustrating a structure of a speaker according to some embodiments of the present disclosure;
- (6) FIG. 5 is a partial sectional diagram illustrating a speaker according to some embodiments of the present disclosure;
- (7) FIG. 6 is a partial enlarged diagram illustrating part F of a speaker in FIG. 5 according to some embodiments of the present disclosure;
- (8) FIG. 7 is an exploded view illustrating a speaker according to some embodiments of the present disclosure;
- (9) FIG. 8 is a schematic diagram illustrating a structure of a nose pad cover in a speaker according to some embodiments of the present disclosure;
- (10) FIG. 9 is a partial sectional view illustrating an eyeglass rim and a spectacle lens in a speaker according to some embodiments of the present disclosure;
- (11) FIG. 10 is an enlarged view illustrating part A of a speaker in FIG. 9 according to some embodiments of the present disclosure;
- (12) FIG. 11 is a partial structural diagram illustrating a connection wire in a speaker according to some embodiments of the present disclosure;
- (13) FIG. 12 is a partial structural schematic diagram illustrating part B of a speaker in FIG. 7 according to some embodiments of the present disclosure;
- (14) FIG. 13 is an enlarged sectional view illustrating a partial structure of eyeglasses in a speaker according to some embodiments of the present disclosure;
- (15) FIG. 14 is a schematic structural diagram illustrating a rotating shaft component and a connection wire in a speaker according to some embodiments of the present disclosure;
- (16) FIG. 15 is a schematic structural diagram illustrating a first rotating shaft in a speaker according to some embodiments of the present disclosure;
- (17) FIG. 16 is a partial exploded view illustrating a speaker according to some embodiments of the present disclosure;
- (18) FIG. 17 is a schematic structural diagram illustrating an eyeglass rim and a spectacle lens in a speaker according to some embodiments of the present disclosure;
- (19) FIG. 18 is a schematic diagram illustrating a partial structure of an eyeglass temple in a speaker according to some embodiments of the present disclosure;
- (20) FIG. 19 is a structural diagram and an application scenario of a bone conduction speaker according to some embodiments of the present disclosure;
- (21) FIG. 20 is a schematic diagram illustrating a direction of an included angle according to some embodiments of the present disclosure;
- (22) FIG. 21 is a structural diagram of a bone conduction speaker acting on human skin and bones according to the present disclosure;
- (23) FIG. 22 is a diagram illustrating an angle-relative displacement relationship of a bone conduction speaker according to some embodiments of the present disclosure;
- (24) FIG. 23 is a schematic diagram illustrating frequency response curves of a bone conduction speaker in a low-frequency part correspond to different angles θ according to some embodiments in the present disclosure; and.
- (25) FIG. 24 is a schematic diagram of transmitting a sound through air conduction according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

(26) In the following detailed description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant disclosure. Obviously, drawings described below are only some examples or embodiments of the present disclosure. Those skilled in the art, without further creative efforts, may apply the present disclosure to other similar scenarios according to these drawings. It should be understood that the purposes of these illustrated embodiments are only provided to those skilled in the art to practice the application, and not intended to limit the scope of the present disclosure. Unless obviously obtained from the context or the context illustrates otherwise, the same numeral in the drawings refers to the same structure or operation.

(27) As used in the disclosure and the appended claims, the singular forms “a,” “an,” and “the” may include plural referents unless the content clearly dictates otherwise. In general, the terms “comprise” and “include” merely prompt to include steps and elements that have been clearly identified, and these steps and elements do not constitute an exclusive listing. The methods or devices may also include other steps or elements. The term “based on” is “based at least in part on.” The term “one embodiment” means “at least one embodiment;” the term “another embodiment” means “at least one other embodiment.” Related definitions of other terms will be given in the description below. In the following, without loss of generality, the “eyeglasses” or “sunglasses” may be used when illustrating related technologies of conduction in the present disclosure. The illustration is only a form of conductive application. For those skilled in the art, “eyeglasses” or “sunglasses” may also be replaced with other similar words, such as “eye protection device,” “eye wearable device,” or the like. In fact, various implementations in the present disclosure may be easily applied to other hearing devices belonging to non-speaker component. For example, for those skilled in the art, after understanding the basic principles of eyeglasses, it may be possible to make various modifications and changes in the form and details of the specific methods and operations of implementing eyeglasses without departing from the principles. In particular, an environmental sound collection and processing function may be added to the eyeglasses to enable the eyeglasses to implement the function of a hearing aid. For example, a microphone may collect environmental sounds of a user/wearer, process the sounds using a certain algorithm and transmit the processed sound (or generated electrical signal) to a speaker. That is, the eyeglasses may be modified to include the function of collecting the environmental sounds, and after a certain signal processing, the sound may be transmitted to the user/wearer via the speaker, thereby implementing the function of the hearing aid. As an example, the algorithm mentioned herein may include noise cancellation, automatic gain control, acoustic feedback suppression, wide dynamic range compression, active environment recognition, active noise reduction, directional processing, tinnitus processing, multi-channel wide dynamic range compression, active howling suppression, volume control, or the like, or any combination thereof.

(28) FIG. 1 is a block diagram illustrating a structure of a speaker according to some embodiments of the present disclosure.

(29) A speaker **100** may include at least an earphone core **102**, an auxiliary function module **104**, and a flexible circuit board **106**.

(30) In some embodiments, the earphone core **102** may receive electrical audio signal(s) and convert the audio signal(s) into the sound signal(s). The flexible circuit board **106** may facilitate electrical connection(s) between different modules/components. For example, the flexible circuit board **106** may facilitate an electrical connection between the earphone core **102** and an external control circuit and an electrical connection between the earphone core **102** and the auxiliary function module **104**.

(31) In some embodiments, the earphone core **102** may include at least a magnetic circuit component, a vibration component, and a bracket that accommodates the magnetic circuit component and the vibration component. The magnetic circuit component may be used to provide a magnetic field. The vibration component may be used to convert an electrical signal input to the

vibration component into a mechanical vibration signal so as to generate a sound. In some embodiments, the vibration component may include at least a coil and an inner lead. In some embodiments, the earphone core **102** may also include an external wire. The external wire may be capable of transmitting an audio current to the coil in the vibration component. One end of the external wire may be connected to the inner lead of the earphone core, and the other end may be connected to the flexible circuit board of the speaker. In some embodiments, the bracket may have a wiring groove. The external wire and/or the inner lead may be partially disposed of the wiring groove described in detail in other parts of the present disclosure.

(32) In some embodiments, the auxiliary function module **104** may be used to receive auxiliary signal(s) and perform auxiliary function(s). The auxiliary function module **104** may be a module different from the earphone core and may be used for receiving the auxiliary signal(s) and performing the auxiliary function(s). In the present disclosure, the conversion of the audio signal into the sound signal may be considered as a main function of the speaker **100**, and other functions different from the main function may be considered as the auxiliary function(s) of the speaker **100**. For example, the auxiliary function(s) of the speaker **100** may include receiving a user sound and/or an ambient sound through a microphone, controlling a broadcasting process of the sound signal through a key, or the like, and a corresponding auxiliary function module may include a microphone, a key switch, etc., which may be set according to actual needs. The auxiliary signal(s) may be electric signal(s) related to the auxiliary function(s), optical signal(s) related to the auxiliary function(s), acoustic signal(s) related to the auxiliary function(s), vibration signal(s) related to the auxiliary function(s), or the like, or any combination thereof.

(33) The speaker **100** may further include a core housing **108** for accommodating the earphone core **102**, the auxiliary function module **104**, and the flexible circuit board **106**. When the speaker **100** is a bone conduction earphone, an inner wall of the core housing **108** may be directly or indirectly connected to the vibration component in the earphone core. When the user wears the bone conduction earphone, an outer wall of the core housing **108** may be in contact with the user and transmit the mechanical vibration of the vibration component to an auditory nerve through a bone, so that the human body may hear the sound. In some embodiments, the speaker may include the earphone core **102**, the auxiliary function module **104**, the flexible circuit board **106**, and the core housing **108**.

(34) In some embodiments, the flexible circuit board **106** may be a flexible printed circuit board (FPC) accommodated in the inner space of the core housing **108**. The flexible circuit board **106** may have high flexibility and be adapted to the inner space of the core housing **108**. Specifically, in some embodiments, the flexible circuit board **106** may include a first board and a second board. The flexible circuit board **106** may be bent at the first board and the second board so as to adapt to a position of the flexible circuit board in the core housing **108**, or the like. More details may refer to descriptions in other parts of the present disclosure.

(35) In some embodiments, the speaker **100** may transmit the sound through a bone conduction approach. An outer surface of the core housing **108** may have a contact surface. The contact surface may be an outer surface of the speaker **100** in contact with the human body when the user wears the speaker **100**. The speaker **100** may compress the contact surface against a preset area (e.g., a front end of a tragus, a position of a skull, or a back surface of an auricle), thereby effectively transmitting the vibration signal(s) to the auditory nerve of the user through the bone and improving the sound quality of the speaker **100**. In some embodiments, the contact surface may be abutted on the back surface of the auricle. The mechanical vibration signal(s) may be transmitted from the earphone core to the core housing and transmitted to the back of the auricle through the contact surface of the core housing. The vibration signal(s) may then be transmitted to the auditory nerve by the bone near the back of the auricle. In this case, the bone near the back of the auricle may be closer to the auditory nerve, which may have a better conduction effect and improve the efficiency of transmitting the sound to the auditory nerve by the speaker **100**.

(36) In some embodiments, the speaker **100** may further include a fixing mechanism **110**. The fixing mechanism **110** may be externally connected to the core housing **108** and used to support and maintain the position of the core housing **108**. In some embodiments, a battery assembly and a control circuit may be disposed in the fixing mechanism **110**. The battery assembly may provide electric energy to any electronic component in the speaker **100**. The control circuit may control any function component in the speaker **100**. The function component may include, but be not limited to, the earphone core, the auxiliary function module, or the like. The control circuit may be connected to the battery and other functional components through the flexible circuit board or the wire.

(37) In some embodiments, the fixing mechanism **110** may be an eyeglass rim, a hat, a headgear, other headwear accessories, or the like, or any combination thereof. For example, the fixing mechanism **110** may be an eyeglass rim. A cavity may be formed inside the eyeglass rim. The cavity may accommodate the battery assembly, the flexible circuit board, and the control circuit. In this case, the earphone core **102** may be located at the end of the eyeglass temple, which may be located near the ear and provide the sound signal(s) when the user wears the eyeglasses.

(38) FIG. 2 is a schematic diagram illustrating a structure of a flexible circuit board located inside a core housing according to some embodiments of the present disclosure.

(39) In some embodiments, the flexible circuit board may be disposed with a number of pads. Different signal wires (e.g., audio signal wires, auxiliary signal wires) may be electrically connected to different pads through different flexible leads to avoid numerous and complicated internal wires issues, which may occur when both audio signal wires and auxiliary signal wires need to be connected to the earphone core or the auxiliary function module. FIG. 3 is an exploded diagram illustrating a partial structure of a speaker according to some embodiments of the present disclosure. As shown in FIGS. 2 and 3, a flexible circuit board **44** may at least include a number of first pads **45** and a number of second pads (not shown in the figures). In some embodiments, the flexible circuit board **44** in FIG. 2 may correspond to the flexible circuit board **106** in FIG. 1. At least one of the first pads **45** may be electrically connected to auxiliary function module(s). The at least one of the first pads **45** may be electrically connected to at least one of the second pads through a first flexible lead **47** on the flexible circuit board **44**. The at least one of the second pads may be electrically connected to an earphone core (not shown in the figures) through external wire(s) (not shown in the figures). At least another one of the first pads **45** may be electrically connected to auxiliary signal wire(s). The at least another one of first pads **45** and the auxiliary function module(s) may be electrically connected through a second flexible lead **49** on the flexible circuit board **44**. In the embodiment, the at least one of the first pads **45** may be electrically connected to the auxiliary function module(s). The at least one of the second pads may be electrically connected to the earphone core through the external wire(s). The one of the at least one of the first pads **45** may be electrically connected to one of the at least one of the second pads through the first flexible lead **47**, so that the external audio signal wire(s) and the auxiliary signal wire(s) may be electrically connected to the earphone core and the auxiliary function modules at the same time through the flexible circuit board, which may simplify a layout of the wiring.

(40) In some embodiments, the audio signal wire(s) may be wire(s) electrically connected to the earphone core and transmitting audio signal(s) to the earphone core. The auxiliary signal wire(s) may be wire(s) electrically connected to the auxiliary function modules and performing signal transmission with the auxiliary function modules.

(41) In some embodiments, referring to FIG. 2, specifically, the flexible circuit board **44** may be disposed with the number of pads **45** and two pads (not shown in the figure). The two pads and the number of pads **45** may be located on the same side of the flexible circuit board **44** and spaced apart. The two pads may be connected to two corresponding pads **45** of the number of pads **45** through the flexible lead(s) **47** on the flexible circuit board **44**. Further, a core housing **41** may also accommodate two external wires. One end of each of the external wires may be welded to the corresponding pad, and the other end may be connected to the earphone core, so that the earphone

core may be connected to the pads through the external wires. The auxiliary function modules may be mounted on the flexible circuit board **44** and connected to other pads of the number of pads **45** through the flexible lead(s) **49** on the flexible circuit board **44**.

(42) In some embodiments, wires may be disposed in the fixing mechanism **110** of the speaker **100**. The wires may at least include the audio signal wire(s) and the auxiliary signal wire(s). In some embodiments, there may be multiple wires in the fixing mechanism **110**. Such wires may include at least two audio signal wires and at least two auxiliary signal wires. For example, the fixing mechanism **110** may be an eyeglass rim. The eyeglass rim may be connected to the core housing **41**, and the wires may be wires disposed in the eyeglass rim. One end of each of multiple wires in the eyeglass rims may be welded to the flexible circuit board **44** arranged in the core housing **10**, or a control circuit board, and the other end of the wire may enter the core housing **41** and be welded to the pad **45** on the flexible circuit board **44**.

(43) As used herein, one end of each of the two audio signal wires of the multiple wires in the eyeglass rims, which may be located in the core housing **41**, may be welded to the two pads **45** by two flexible leads **47**, and the other end may be directly or indirectly connected to the control circuit board. The two pads **45** may be further connected to the earphone core through the welding of the flexible lead(s) **49** and the two pad **46** and the welding of the two external wires and the pads, thereby transmitting the audio signal(s) to the earphone core.

(44) One end of each of at least two auxiliary signal wires in the core housing **41** may be welded to the pad **45** by the flexible lead(s) **49**, and the other end may be directly or indirectly connected to the control circuit board so as to pass the auxiliary signal(s) received and transformed by the auxiliary function module(s) to the control circuit (not shown in the figure).

(45) In the approach described above, the flexible circuit board **44** may be disposed in the core housing **41**, and the corresponding pads may be further disposed on the flexible circuit board **44**. Therefore, the wires (not shown in the figure) may enter the core housing **41** and be welded to the corresponding pads, and further connected to the corresponding auxiliary function module(s) through the flexible leads **47** and the flexible leads **49** on the pads, thereby avoiding a number of wires directly connected to the auxiliary function module(s) to make the wiring in the core housing **41** complicated. Therefore, the arrangement of the wirings may be optimized, and the space occupied by the core housing **41** may be saved. In addition, when a number of the rim wires are directly connected to the auxiliary function module(s), a middle portion of the rim wires may be suspended in the core housing **41** to easily cause vibration, thereby resulting in abnormal sounds to affect the sound quality of the earphone core. According to the approach, the wires in the eyeglass rim may be welded to the flexible circuit board **44** and further connected to the corresponding auxiliary function module(s), which may reduce a situation that the wires are suspended from effecting the quality of the earphone core, thereby improving the sound quality of the earphone core to a certain extent.

(46) In some embodiments, the flexible circuit board (also referred to as the flexible circuit board **44**) may be further divided. The flexible circuit board may be divided into at least two regions. One auxiliary function module may be disposed on one of the at least two regions, so that at least two auxiliary function modules may be disposed on the flexible circuit board. Wiring between the audio signal wire(s) and the auxiliary signal wire(s) and the at least two auxiliary function modules may be implemented through the flexible circuit board. In some embodiments, the flexible circuit board may include at least a main circuit board and a first branch circuit board. The first branch circuit board may be connected to the main circuit board and extend away from the main circuit board along one end of the main circuit board. The auxiliary function module(s) may include at least a first auxiliary function module and a second auxiliary function module. The first auxiliary function module may be disposed on the main circuit board, and the second auxiliary function module may be disposed on the first branch circuit board. The number of first pads may be disposed on the main circuit board, and the second pads may be disposed on the first branch circuit board. In some

embodiments, the first auxiliary function module may be a key switch. The key switch may be disposed on the main circuit board, and the first pads may be disposed corresponding to the key switch. The second auxiliary function module may be a microphone. The microphone may be disposed on the first branch circuit board, and the second pads corresponding to the microphone may be disposed on the first branch circuit board. The first pads corresponding to the key switch on the main circuit board may be connected to the second pads corresponding to the microphone on the first branch circuit board through the second flexible lead(s). The key switch may be electrically connected to the microphone, so that the key switch may control or operate the microphone.

(47) In some embodiments, the flexible circuit board may further include a second branch circuit board. The second branch circuit board may be connected to the main circuit board. The second branch circuit board may extend away from the main circuit board along the other end of the main circuit board and be spaced from the first branch circuit board. The auxiliary function module(s) may further include a third auxiliary function module. The third auxiliary function module may be disposed on the second branch circuit board. The number of first pads may be disposed on the main circuit board. At least one of the second pads may be disposed on the first branch circuit board, and the other second pads may be disposed on the second branch circuit. In some embodiments, the third auxiliary function module may be a second microphone. The second branch circuit board may extend perpendicular to the main circuit board. The second microphone may be mounted on the end of the second branch circuit board away from the main circuit board. The number of pads may be disposed at the end of the main circuit board away from the second branch circuit board.

(48) Specifically, as shown in FIG. 2 and FIG. 3, the second auxiliary function module may be the first microphone **432a**. The third auxiliary function module may be the second microphone **432b**. As used herein, the first microphone **432a** and the second microphone **432b** may both be MEMS (micro-electromechanical system) microphone **432**, which may have a small working current, relatively stable performance, and high voice quality. The two microphones **432** may be disposed at different positions of the flexible circuit board **44** according to actual needs.

(49) As used herein, the flexible circuit board **44** may include a main circuit board **441** (or referred to the main circuit board), and a branch circuit board **442** (or referred to the first branch circuit board) and a branch circuit board **443** (or referred to the second branch circuit board) connected to the main circuit board **441**. The branch circuit board **442** may extend in the same direction as the main circuit board **441**. The first microphone **432a** may be mounted on one end of the branch circuit board **442** away from the main circuit board **441**. The branch circuit board **443** may extend perpendicular to the main circuit board **441**. The second microphone **432b** may be mounted on one end of the branch circuit board **443** away from the main circuit board **441**. A number of pads **45** may be disposed on the end of the main circuit board **441** away from the branch circuit board **442** and the branch circuit board **443**.

(50) In one embodiment, the core housing **41** may include a peripheral side wall **411** and a bottom end wall **412** connected to one end surface of the peripheral side wall **411**, so as to form an accommodation space with an open end. As used herein, an earphone core may be disposed in the accommodation space through the open end. The first microphone **432a** may be fixed on the bottom end wall **412**. The second microphone **432b** may be fixed on the peripheral side wall **411**.

(51) In the embodiment, the branch circuit board **442** and/or the branch circuit board **443** may be appropriately bent to suit a position of a sound inlet corresponding to the microphone **432** on the core housing **41**. Specifically, the flexible circuit board **44** may be disposed in the core housing **41** in a manner that the main circuit board **441** is parallel to the bottom end wall **412**. Therefore, the first microphone **432a** may correspond to the bottom end wall **412** without bending the main circuit board **441**. Since the second microphone **432b** may be fixed on the peripheral side wall **411** of the core housing **41**, it may be necessary to bend the second main circuit board **441**. Specifically, the branch circuit board **443** may be bent at one end away from the main circuit board **441** so that a

board surface of the branch circuit board **443** may be perpendicular to a board surface of the main circuit board **441** and the branch circuit board **442**. Further, the second microphone **432b** may be fixed at the peripheral side wall **411** of the core housing **41** in a direction facing away from the main circuit board **441** and the branch circuit board **442**.

(52) In one embodiment, the first pads **45**, the second pads, the first microphone **432a**, and the second microphone **432b** may be disposed on the same side of the flexible circuit board **44**. The second pads may be disposed adjacent to the second microphone **432b**.

(53) As used herein, the second pads may be specifically disposed at one end of the branch circuit board **443** away from the main circuit board **441** and have the same direction as the second microphone **432b** and disposed at intervals. Therefore, the second pads may be perpendicular to the direction of the first pads **45** as the branch circuit board **443** is bent. It should be noted that the branch circuit board **443** may not be perpendicular to the board surface of the main circuit board **441** after being bent, which may be determined according to the arrangement between the side wall **411** and the bottom end wall **412**.

(54) Further, another side of the flexible circuit board **44** may be disposed with a rigid support plate **4a** and a microphone rigid support plate **4b** for supporting the first pads **45**. The microphone rigid support plate **4b** may include a rigid support plate **4b1** for supporting the first microphone **432a** and a rigid support plate **4b2** for supporting the second pads and the second microphone **432b** together.

(55) As used herein, the rigid support plate **4a**, the rigid support plate **4b1**, and the rigid support plate **4b2** may be mainly used to support the corresponding pads and the microphone **432**, and thus may need to have certain strengths. The materials of the three may be the same or different. The specific material may be polyimide (PI), or other materials that may provide the strengths, such as polycarbonate, polyvinyl chloride, etc. In addition, the thicknesses of the three rigid support plates may be set according to the strengths of the rigid support plates, and actual strengths required by the first pads **45**, the second pads, the first microphone **432a**, and the second microphone **432b**, and be not specifically limited herein.

(56) As used herein, the rigid support plate **4a**, the rigid support plate **4b1**, and the rigid support plate **4b2** may be three different regions of an entire rigid support plate, or three independent bodies spaced apart from each other, and be not specifically limited herein.

(57) In one embodiment, the first microphone **432a** and the second microphone **432b** may correspond to two microphone components **4c**, respectively (not shown in the figure). In one embodiment, the structures of the two microphone components may be the same. A sound inlet **413** may be disposed on the core housing **41**. Further, the loud speaking device may be further disposed with an annular blocking wall **414** integrally formed on the inner surface of the core housing **41** at the core housing **41**, and disposed at the periphery of the sound inlet **413**, thereby defining an accommodation space (not shown in the figure) connected to the sound inlet **413**.

(58) In one embodiment, the flexible circuit board **44** may be disposed between a rigid support plate (e.g., the rigid support plate **4a**, the rigid support plate **4b1**, and the rigid support plate **4b2**) and the microphone **432**. A sound input **444** may be disposed at a position corresponding to a sound input **4b3** of the microphone rigid support plate **4b**.

(59) Further, the flexible circuit board **44** may further extend away from the microphone **432**, so as to be connected to other functional components or wires to implement corresponding functions. Correspondingly, the microphone rigid support plate **4b** may also extend out a distance with the flexible circuit board in a direction away from the microphone **432**.

(60) Correspondingly, the annular blocking wall **414** may be disposed with a gap matching the shape of the flexible circuit board to allow the flexible circuit board to extend out of the accommodation space **415**. In addition, the gap may be further filled with a sealant to further improve the sealing.

(61) FIG. **4** is a partial sectional view illustrating a structure of a speaker according to some embodiments of the present disclosure. In some embodiments, as shown in FIG. **4**, the flexible

circuit board **44** may include a main circuit board **445** and a branch circuit board **446**. The branch circuit board **446** may extend along an extending direction perpendicular to the main circuit board **445**. As used herein, the number of first pads **45** may be disposed at the end of the main circuit board **445** away from the branch circuit board **446**. A key switch may be mounted on the main circuit board **445**. The second pads **46** may be disposed at the end of the branch circuit boards **446** away from the main circuit board **445**. The first auxiliary function module may be a key switch **431**. The second auxiliary function module may be a microphone **432**.

(62) In the embodiment, a board surface of the flexible circuit board **44** and the bottom end wall **412** may be disposed in parallel and at intervals, so that the key switch may be disposed towards the bottom end wall **412** of the core housing **41**.

(63) As described above, an earphone core (or the earphone core **102**) may include a magnetic circuit component, a vibration component, an external wire, and a bracket. As used herein, the vibration component may include a coil and an inner lead. The external wire may transmit an audio current to the coil in the vibration component. One end of the external wire may be connected to the inner lead of the earphone core, and the other end may be connected to the flexible circuit board of a speaker. The bracket may have a wiring groove. At least a portion of the external wire and/or the inner lead may be disposed in the wiring groove. In some embodiments, the inner lead and the outer wire may be welded to each other. A welding position may be located in the wiring groove.

(64) FIG. 5 is a partial sectional diagram illustrating a speaker according to some embodiments of the present disclosure. FIG. 6 is a partial enlarged diagram illustrating part F of a speaker in FIG. 5 according to some embodiments of the present disclosure. Specifically, referring to FIG. 5 and FIG. 6, an earphone core may include a bracket **421**, a coil **422**, and an external wire **48**. The bracket **421** may be used to support and protect the entire structure of the earphone core. In the embodiment, the bracket **421** may be disposed with a wiring groove **4211** used to accommodate a circuit of the earphone core.

(65) The coil **422** may be disposed on the bracket **421** and have at least one inner lead **423**. One end of the inner lead(s) **423** may be connected to a main circuit in the coil **422** to lead out the main circuit and transmit an audio current to the coil **422** through the inner lead **423**.

(66) One end of the external wire **48** may be connected to the inner lead(s) **423**. Further, the other end of the external wire **48** may be connected to a control circuit (not shown in the figure) to transmit the audio current through the control circuit to the coil **422** through the inner lead **423**.

(67) Specifically, during an assembly stage, the external wire **48** and the inner lead(s) **423** may need to be connected together by means of welding, or the like. Due to structural and other factors, after the welding is completed, a length of the wire may not be exactly the same as a length of a channel, and there may be an excess length part of the wire. And if the excess length part of the wire is not disposed reasonably, it may vibrate with the vibration of the coil **422**, thereby making an abnormal sound and affecting the sound quality of the earphone core.

(68) Further, at least one of the external wire **48** and the inner lead **423** may be wound and disposed in the wiring groove **4211**. In an application scenario, the welding position between the inner lead **423** and the external wire **48** may be disposed in the wiring groove **4211**, so that a portion of the external wire **48** and the inner lead **423** located near the welding position may be wound in the wiring groove **4211**. In addition, in order to maintain stability, the wiring groove **4211** may be further filled with a sealant to further fix the wiring in the wiring groove **4211**.

(69) In the manner described above, the wiring groove **4211** may be disposed on the bracket **421**, so that at least one of the external wire **48** and the inner lead **423** may be wound into the wiring groove **4211** to accommodate the excess length part of the wire, thereby reducing the vibration generated inside the channel, and reducing the influence of the abnormal sound caused by the vibration on the sound quality of the earphone core.

(70) In one embodiment, the bracket **421** may include an annular main body **4212**, a support flange **4213**, and an outer blocking wall **4214**. As used herein, the annular main body **4212**, the support

flange **4213**, and the outer blocking wall **4214** may be integrally formed.

(71) As used herein, the annular main body **4212** may be disposed inside the entire bracket **421** and used to support the coil **422**. Specifically, a cross-section of the annular main body **4212** in a direction perpendicular to the radial direction of a ring of the annular main body **4212** may be consistent with the coil **422**. The coil **422** may be disposed at an end of the annular main body **4212** facing the core housing. The inner side wall and the outer side wall of the annular main body **4212** may be flush with the inner side wall and the outer side wall of the coil **422**, respectively, so that the inner side wall of the coil **422** and the inner side wall of the annular main body **4212** may be coplanar, and the outer side wall of the coil **422** and the outer side wall of the annular main body **4212** may be coplanar.

(72) Further, the support flange **4213** may protrude on the outer side wall of the annular main body **4212** and extend along the outside of the annular main body **4212**. Specifically, the support flange **4213** may extend outward in a direction perpendicular to the outer side wall of the annular main body **4212**. As used herein, the support flange **4213** may be disposed at a position between two ends of the annular main body **4212**. In the embodiment, the support flange **4213** may protrude around the outer side wall of the annular main body **4212** to form an annular support flange **4213**. In other embodiments, the support flange **4213** may also be formed by protruding at a portion of the outer side wall of the annular main body **4212** according to needs.

(73) The outer blocking wall **4214** may be connected to the support flange **4213** and spaced apart from the annular main body **4212** along the side of the annular main body **4212**. As used herein, the outer blocking wall **4214** may be sleeved on the periphery of the annular main body **4212** and/or the coil **422** at intervals. Specifically, the outer blocking wall **4214** may be partially sleeved around the periphery of the annular main body **4212** and the coil **422** according to actual needs, or partially sleeved around the periphery of the annular main body **4212**. It should be noted that, in the embodiment, a portion of the outer blocking wall **4214** close to the wiring groove **4211** may be sleeved on a portion of the periphery of the annular main body **4212**. Specifically, the outer blocking wall **4214** may be disposed on a side of the support flange **4213** away from the core housing. As used herein, the outer side wall of the annular main body **4212**, the side wall of the support flange **4213** away from the core housing, and the inner side wall of the outer blocking wall **4214** may together define the wiring groove **4211**.

(74) In one embodiment, a wiring channel **424** may be disposed on the annular main body **4212** and the support flange **4213**. The inner lead(s) **423** may extend inside the wiring groove **4211** via the wiring channel **424**.

(75) As used herein, the wiring channel **424** may include a sub-wiring channel **4241** on the annular main body **4212** and a sub-wiring channel **4242** on the support flange **4213**. The sub-wiring channel **4241** may be disposed through the inner side wall and the outer side wall of the annular main body **4212**. A wiring port **42411** communicating with one end of the sub-wiring channel **4241** may be disposed on a side of the annular main body **4212** near the coil **422**. A wiring port **42412** communicating with the other end of the sub-wiring channel **4241** may be disposed on a side of the core housing near the support flange **4213** facing the core housing. The sub-wiring channel **4242** may penetrate the support flange **4213** in a direction towards the outside of the core housing. The wiring port **42421** communicating with the end of the sub-wiring channel **4242** may be disposed on a side of the support flange **4213** facing the core housing. The wiring port **42422** communicating with the other end of the sub-wiring channel **4242** may be disposed on a side away from the core housing. As used herein, the wiring port **42412** and the wiring port **42421** may communicate through a space between the support flange **4213** and the annular main body **4212**.

(76) Further, the inner lead(s) **423** may enter the wiring port **42411**, extend along the sub-wiring channel **4241**, exit from the wiring port **42412** to enter a region between the annular main body **4212** and the support flange **4213**, further enter the sub-wiring channel **4242** from the wiring port **42421**, and extend into the wiring groove **4211** after passing through the wiring port **42422**.

(77) In one embodiment, the top of the outer blocking wall **4214** may be disposed with a slot **42141**. The external wire **48** may extend inside the wiring groove **4211** through the slot **42141**.

(78) As used herein, one end of the external wire **48** may be disposed on the flexible circuit board **44**. The flexible circuit board **44** may be specifically disposed on an inner side of the earphone core facing the core housing.

(79) In the embodiment, the support flange **4213** may be further extended to a side of the outer blocking wall **4214** away from the annular main body **4212** to form an outer edge. Further, the outer edge may surround and abut on the inner side wall of the core housing. Specifically, the outer edge of the support flange **4213** may be disposed with a slot **42131**, so that the external wire **48** on the inner side of the earphone core facing the core housing may be extended to the outer side of the support flange **4213** facing the core housing through the slot **42131**, and then to the slot **42141**, and enter the wiring groove **4211** through the slot **42141**.

(80) Further, the inner side wall of the core housing may be disposed with a guide groove **416**. One end of the guide groove **41** may be located on one side of the flexible circuit board **44** and the other end may communicate with the slot **42131** and extend in a direction towards the outside of the core housing, so that the external wire **48** extends from the flexible circuit board to a second wiring groove **3331** by passing through the guide slot **416**.

(81) In one embodiment, the bracket **421** may further include two side blocking walls **4215** spaced along the circumferential direction of the annular main body **4212** and connected to the annular main body **4212**, the supporting flange **4213**, and the outer blocking wall **4214**, thereby defining the wiring groove **4211** between the two side blocking walls **4215**.

(82) Specifically, the two side blocking walls **4215** may be oppositely disposed on the support flange **4213** and protrude towards the outer side of the core housing along the support flange **4213**. As used herein, a side of the two side blocking walls **4215** facing the annular main body **4212** may be connected to the outer side wall of the annular main body **4212**. A side away from the annular main body **4212** may terminate at the outer side wall of the outer blocking wall **4214**. The wiring port **42422** and the slot **42141** may be defined between the two side blocking walls **4215**. Therefore, the inner lead(s) **423** exiting from the wiring port **42422** and the outer wire **48** entering through the slot **42141** may extend into the wiring groove **4211** defined by the two side blocking walls **4215**.

(83) FIG. 7 is a schematic diagram illustrating a structure of a speaker according to some embodiments of the present disclosure.

(84) In some embodiments, the speaker may be eyeglasses. In some embodiments, a fixing mechanism may be an eyeglass frame. The fixing mechanism may have at least one rotating shaft. The rotating shaft(s) may be used to connect an eyeglass rim and an eyeglass temple. The eyeglass rim and the eyeglass temple may rotate around the rotating shaft. The rotating shaft may have a rotating shaft wiring channel disposed along an axis. A connection wire may be disposed in the fixing mechanism. The connection wire may be an electrical connection wire. The connection wire may pass through the rotating shaft wiring channel. Two ends of the connection wire may extend into the eyeglass rim and the eyeglass temple, respectively. In some embodiments, the eyeglass temple at two sides may accommodate a control circuit and a battery component, respectively. The connection wire in the eyeglass rim may be electrically connect to the control circuit and the battery component. The connection wire may include an audio signal wire and an auxiliary signal wire. The connection wire may be electrically connected to a flexible circuit board (i.e., the flexible circuit board **106**) in a core housing (i.e., the core housing **108**), and electrically connected to an earphone core (i.e., the earphone core **102**) and auxiliary function module(s) (i.e., an auxiliary function module **104**) through the flexible circuit board.

(85) In some embodiments, the eyeglasses of the present disclosure may be eyeglasses worn in people's daily life and at work to correct vision and protect eyes, or certain circuit structures and electronic components may be added into the eyeglasses in order to further implement specific

functions through the circuit structures and electronic components. Specifically, the eyeglasses in the present disclosure may be smart eyeglasses, virtual reality eyeglasses, holographic eyeglasses, augmented reality eyeglasses, or eyeglasses with other functional structures (e.g., eyeglasses with a bone conduction earphone or an air conduction earphone).

(86) In some embodiments, as shown in FIG. 7, the eyeglass frame may include an eyeglass rim **11**, a nose pad **12**, a spectacle lens **13**, and an eyeglass temple **15**.

(87) As used herein, the eyeglass rim **11** may be used to carry at least a portion of the spectacle lens **13**. The nose pad **12** may be used to support the eyeglasses on the bridge of the nose of a user when the user wears the eyeglasses.

(88) The nose pad **12** may be disposed in the middle of the eyeglass rim **11** and integrally formed with the eyeglass rim **11**. In the prior art, the eyeglass rim **11** and the nose pad **12** may be usually formed, respectively. The middle portion of the eyeglass rim **11** may be disposed with a structure connected to the nose pad **12**. After molding, the nose pad **12** may be installed on the connection structure of the eyeglass rim **11**. In the embodiment, the eyeglass rim **11** and the nose pad **12** may be integrally formed directly. Specifically, a corresponding mold may be used to implement the integral molding, for example, injection molding, or the like. In the embodiment, the eyeglass rim **11** and the nose pad **12** may not need to be further installed after the molding, thereby simplifying a manufacturing process of eyeglasses.

(89) In addition, the spectacle lens **13** may also be integrally designed, and be fixed by the eyeglass rim **11** and the nose pad **12** in a clamping manner.

(90) Further, the eyeglass rim **11** and the nose pad **12** may be respectively disposed with a structure for clamping the spectacle lens **13**. When the eyeglasses are assembled, the integrally designed spectacle lens **13** may be directly clamped to the integrally formed eyeglass rim **11** and nose pad **12** through the corresponding clamping structures.

(91) In the embodiment, the eyeglass rim **11** and the nose pad **12** may be integrally formed, and the spectacle lens **13** may also be integrally designed. Therefore, the entire structure of the eyeglasses may be simple, and the manufacturing process of the eyeglasses may be simplified.

(92) Referring to FIG. 7, FIG. 7 is an exploded view illustrating the eyeglasses according to an embodiment of the present disclosure. In the embodiment, the spectacle lens **13** may include a top-side edge **131** and two outer edges **132** connected to both ends of the top-side edge **131** and disposed away from the nose pad **12**. Each of the outer edges **132** may be respectively disposed with a first buckle **1321**. The eyeglass rim **11** may be disposed with a first mounting groove **111** for receiving the top-side edge **131** and at least a portion of the outer edges **132**, and a first buckle groove **112** for receiving the first buckle **1321** and communicating with the first mounting groove **111**.

(93) As used herein, when the eyeglasses are in a wearing state, the top-side edge **131** may be located on the upper side of the spectacle lens **13**, the outer edge may be located on both sides of the spectacle lens **13** near ears of the user, and the top-side edge **131** and the two outer edges **132** may be connected to each other. The first mounting groove **111** may be disposed on a side of the eyeglass rim **11** facing the spectacle lens **13**. A size of the first mounting groove **111** may match the top-side edge **131** and the two outer edges **132** of the corresponding spectacle lens **13**, so that the spectacle lens **13** may be mounted on the eyeglass rim **11** by mounting the top-side edge **131** and at least the portion of the outer edge **132** in the first mounting groove **111**.

(94) Further, the first buckle **1321** may be formed by further extending at least a portion of the outer edge **131** of the spectacle lens **13** toward two sides away from the nose pad **12**. The first buckle groove **112** may be formed by recessing a position of the first mounting groove **111** corresponding to the first buckling **1321** in a direction away from the spectacle lens **13**. As used herein, the shape and size of the first buckle groove **112** may match the first buckle **1321**, so that the spectacle lens **13** may be further installed on the eyeglass rim **11** by clamping the first buckle **1321** into the first buckle groove **112**.

(95) It should be noted that at least a portion of the outer edge **132** may be located on the side of the first buckle **1321** away from the top-side edge **131**, so that the first buckle **1321** and a portion of the spectacle lens **13** near the two sides of the edge of the spectacle lens **13** may be accommodated inside the first mounting groove **111**. Therefore, the spectacle lens **13** may be more firmly fixed on the eyeglass rim **11**.

(96) In one embodiment, the spectacle lens **13** may further include an inner edge **133** abutting on the nose pad **12**. The nose pad **12** may be disposed with a second mounting groove **121** for receiving the inner edge **133**.

(97) It should be noted that the spectacle lens **13** may include a left spectacle lens and a right spectacle lens. The inner edge **133** of the spectacle lens **13** may be disposed at a connection between the left spectacle lens and the right spectacle lens and a vicinity of the connection. Accordingly, the second mounting groove **121** and the first mounting groove **111** may be oppositely disposed so that the opposite sides of the spectacle lens **13** may be respectively received and fixed in an accommodation space formed by the eyeglass rim **11** and the nose pad **12**.

(98) In one embodiment, two sides of the inner edge **133** may be respectively disposed with a second buckle **1331**. The nose pad **12** may be further disposed with a second buckle groove **122** connected to the second mounting groove **121** and used to receive the second buckle **1331**.

(99) As used herein, the inner edge **133** may include two portions connected to each other, which may be respectively disposed on a side of the left eyeglass lens facing the right eyeglass lens and a side of the right eyeglass lens facing the left eyeglass lens. The nose pad **12** may also be divided into two portions, which may be respectively supported on the left and right nose bridges of the user when worn by the user. Accordingly, in the embodiment, the count of the second buckle groove **122** and the second buckle **1331** may also be two. The shape and size of the second buckle **1331** may match the corresponding second buckle groove **122** to install the second buckle **1331** in the corresponding second buckle groove **122**.

(100) In addition, the spectacle lens **13** may be disposed with the inner edge **133** near both sides of the second buckle **1331**, which may allow the vicinity of both sides of the second buckle **1331** to be installed in the second mounting groove **121**. Therefore, the spectacle lens **13** may be more firmly fixed on the nose pad **12**.

(101) By the approach, the spectacle lens **13** may be respectively mounted on the eyeglass rim **11** and the nose pad **12** through the top-side edge **131**, the outer edge **132**, the inner edge **133**, the first buckle **1321**, and the second buckle **1331**.

(102) In an application scenario, the spectacle lens **13** may be further disposed with vent holes **134**. Specifically, the count of the vent holes may be two, and respectively disposed on the left and right sides of the spectacle lenses **13** near the top-side edge **131**. The arrangement of the vent holes **134** may facilitate air circulation of the inner and outer sides of the spectacle lens **13** when the user wears the eyeglasses, thereby reducing a phenomenon of fogging of the spectacle lens **13** caused by local overheating due to reasons such as user movement, etc.

(103) Specifically, referring to FIG. 7 and FIG. 8 together, FIG. 7 is an exploded view illustrating a speaker according to some embodiments of the present disclosure, and FIG. 8 is a schematic diagram illustrating a structure of a nose pad cover of eyeglasses according to some embodiments of the present disclosure. In one embodiment, the nose pad **12** may include a connection portion **123** connected to the eyeglass rim **11** on the side of the first mounting groove **111** near the user or away from the user in the wearing state, and two support portions **124** connected to the connection portion **123** in an inverted Y-shaped manner on a side of the connection portion **123** away from the eyeglass rim **11**. The support portions **124** may be used to support the eyeglasses on the nose of the user when wearing.

(104) In an application scenario, the connecting portion **123** may be integrally connected to the eyeglass rim **11**. When the user wears the eyeglasses, the connecting portion **123** may be disposed on a side of the first mounting groove **111** close to the user.

(105) A side of each of the support portions **124** protruding toward the nose bridge of the user may be disposed with I-shaped hook(s) **1241**. The eyeglasses may further include nose pad cover(s) **14** detachably sleeved on the hook(s) **1241**.

(106) As used herein, the nose pad cover **14** may be made of soft rubber. Specifically, the count of the I-shaped hook(s) **1241** may be two, corresponding to the left and right nose bridges of the user, respectively. The nose pad cover **14** may include two cover bodies **141** and a connecting portion **142** connecting to the two cover bodies **141**. As used herein, the connecting portion **142** may be connected with the nose bridge of the user. The cover bodies **141** may be correspondingly disposed with I-shaped accommodation groove(s) **1411** matching the hook(s) **1241**. Sides of the cover bodies **141** facing the nose bridge of the user may further be disposed with an anti-slippery portion **1412** including a number of grooves. In the embodiment, the nose pad cover **14** may be detachably disposed, thereby facilitating cleaning and replacement of the nose pad cover **14**.

(107) Further, in an embodiment, sides of the two support portions **124** back from the hook(s) **1241** may be protruded with strip shaped ribs **1242**. The strip shaped ribs **1242** may cooperate with the two support portions **124** to form the second mounting groove **121** and the second buckle groove **122**.

(108) As used herein, the strip shaped ribs **1242** may be protruded along edges of the two support portions **124** away from the spectacle lens **13**, thereby forming the second mounting groove **121** for receiving the inner edge **133** of the spectacle lens **13**. At a position corresponding to the second buckle **1331** of the spectacle lens **13**, the strip shaped ribs **1242** may be further recessed to form the second buckle groove **122**.

(109) Referring to FIG. 7 together, in one embodiment, the eyeglass rim may further include the eyeglass temple **15**, function component(s) **16**, and a connection wire **17**. As used herein, the eyeglass temple **15** may include a first eyeglass temple **151** and a second eyeglass temple **152**. The function component(s) **16** may include a first function component **161** and a second function component **162**.

(110) Specifically, the first eyeglass temple **151** and the second eyeglass temple **152** may be respectively connected to the eyeglass rim **11**. The first function component **161** and the second function component **162** may be respectively disposed on the first eyeglass temple **151** and the second eyeglass temple **152**. At least one cavity may be disposed on the two eyeglass temples **15** to accommodate the corresponding function components **16**.

(111) The connection wire **17** may be disposed inside the first mounting groove **111** and between the bottom of the first mounting groove **111** and the top-side edge **131** of the spectacle lens **13**, and further extend to the first eyeglass temple **151** and the second eyeglass temple **152** to be electrically connected to the first function component **161** and the second function component **162**.

(112) In the embodiment, the function component(s) **16** respectively disposed in the two eyeglass temples **15** may need to be electrically connected through the connection wire **17** so that the eyeglasses may implement a specific function. Specifically, in an application scenario, the first function component **161** may be a battery component, and the second function component **162** may be a control circuit component. The control circuit component may be connected to the battery component through the connection wire **17**, so that the battery component may provide power to the control circuit component. Therefore, the control circuit component may implement the specific function.

(113) In order to meet requirements of beauty and lightness of the eyeglasses, the connection wire **17** may be disposed in the first mounting groove **111** along the top-side edge **131** of the spectacle lens **13** and accommodated inside a space formed by the first mounting groove **111** and the top-side edge **131** of the spectacle lens **13**, so that the connection wire **17** may be neither exposed on the outer surface of the eyeglasses nor occupy extra space. In an application scenario, the connection wire **17** may further extend along the outer edge **132** of the spectacle lens **13** inside the first mounting groove **111**.

(114) Specifically, the eyeglass rim **11**, the first eyeglass temple **151**, and the second eyeglass temple **152** may respectively be disposed with a wiring channel communicated with each other, so that the connection wire **17** may enter the first eyeglass temple **151** and the second eyeglass temple **152** from the first mounting groove **111** of the eyeglass rim **11** through the corresponding wiring channels, thereby connecting the first function component **161** and the second function component **162**.

(115) In the embodiment, the connection wire **17** may have an electrical connection function. In other embodiments, the connection wire **17** may also have a mechanical connection function.

(116) In the embodiment, the first function component **161** and the second function component **162** may be respectively disposed on the first eyeglass temple **151** and the second eyeglass temple **152**. The connection wire **17** electrically connecting the first function component **161** and the second function component **162** may be disposed inside the first mounting groove **111** on the eyeglass rim **11** to receive the top-side edge **131** of the spectacle lens **13**, so that the connection wire **17** may be disposed between the bottom of the first mounting groove **111** and the top-side edge **131** of the spectacle lens, and further extend to the first eyeglass temple **151** and the second eyeglass temple **152**. Therefore, the connection wire **17** may not be exposed, and extra space may not need for the arrangement of the connection wire **17**, so that the beauty and lightness of the eyeglasses may be maintained.

(117) Referring to FIG. **9**, FIG. **10**, and FIG. **11** together, FIG. **9** is a partial sectional view illustrating an eyeglass rim and a spectacle lens according to an embodiment of the present disclosure, FIG. **10** is an enlarged view illustrating part A in FIG. **9**, and FIG. **11** is a partial structural diagram illustrating a connection wire according to an embodiment of the present disclosure. In the embodiment, the connection wire **17** may include a wire body **171** and a wire protection cover **172** wrapped around the periphery of the wire body **171**. A sectional shape of the wire protection cover **172** may match a sectional shape of the first mounting groove **111**, so that the wire protection cover **172** may be held in the first mounting groove **111** in a surface contact manner.

(118) As used herein, the wire protection cover **172** may be made of soft rubber, so that the connection wire **17** may be bent to match the shape of the first mounting groove **111**. It may be easy to understand that the wire body **171** may be thin. If the wire body **171** is directly installed in the first mounting groove **111**, a contact area with the bottom of the first mounting groove **111** may be small, and it is difficult to be firmly fixed therein. In the embodiment, the wire protection cover **172** may be further wrapped around the periphery of the wire body **171**, which, on the one hand, may play a role of protecting the wire body **171**, and, on the other hand, increase the contact area between the connection wire **17** and the first mounting groove **111** by adjusting the surface area of the wire protection cover **172** to reliably fix the wire body **171** inside the first mounting groove **111**.

(119) Further, the sectional shape of the first mounting groove **111** may be a shape to allow the wire protection cover **172** to be held in the first mounting groove **111** with a large area of surface contact. For example, the shape may be U-shaped, rectangular, or wavy, and be not specifically limited herein. Correspondingly, the shape of a side of the wire protection cover **172** facing the bottom of the first mounting groove **111** may correspond to the shape, so that the wire protection cover **172** may be directly or indirectly fitted to the bottom of the first mounting groove **111**.

(120) In an application scenario, further referring to FIG. **7**, an adhesive layer **18** may be disposed between the wire protection cover **172** and the eyeglass rim **11**, so that the wire protection cover **172** may be fixed in the first mounting groove **111** through the adhesive layer **18**.

(121) As used herein, the adhesive layer **18** may be disposed on the bottom of the first mounting groove **111**, or further extended to both sides and disposed on a side wall near the bottom of the first mounting groove **111**, thereby making the adhesive layer **18** to wrap around the wire protection cover **172** to more firmly fix the connection wire **17** inside the first mounting groove

111.

(122) Specifically, in the application scenario, a section of the first mounting groove **111** may be rectangular. The bottom of the first mounting groove **111** and a side of the wire protection cover **172** facing the bottom of the first mounting groove **111** may be both flat, and the adhesive layer **18** may be a double-sided adhesive layer disposed therebetween.

(123) Further, in one embodiment, a side of the wire protection cover **172** facing the top-side edge **131** of the eyeglass lens **13** may be disposed with a convex portion **1721** corresponding to the wire body **171**. The top-side edge **131** of the spectacle lens **13** may be disposed with a clearance slot **1311** for receiving the convex portion **1721**.

(124) Specifically, the section of the wire body **171** may be circular. The wire protection cover **172** may be flush with the wire body **171** on the side of the wire body **171** facing the bottom of the first mounting groove **111**. The side of the wire body **171** facing away from the bottom of the first mounting groove **111** may still present the shape of the wire body **171**, thereby forming the corresponding convex portion **1721**.

(125) Further, the top-side edge **131** of the spectacle lens **13** may need to be further disposed inside the first mounting groove **111**. In the embodiment, the top-side edge **131** may be further disposed with the clearance slot **1311** for receiving the convex portion **1721**, so that the connection wire **17** installed inside the first mounting groove **111** may be at least partially accommodated in the clearance slot **1311** corresponding to the top-side edge **131**.

(126) Further, the convex portion **1721** may be located in a middle region of the wire protection cover **172** along a width direction of the wire protection cover **172** to form abutting portions **1722** on two sides of the convex portion **1721**. The two abutting portions **1722** may abut on the top-side edges **131** on two sides of the clearance slot **1311**, respectively. As used herein, the width direction of the wire protection cover **172** may refer to a direction perpendicular to a direction of the wire protection cover **172** along the first mounting groove **111**, specifically a direction indicated by W in FIG. 10.

(127) It may be easy to understand that the depth of the first mounting groove **111** may be limited. If the top-side edge **131** of the spectacle lens **13** is flush with the convex portion **1721** of the connection wire **17**, or a side of the wire protection cover **172** and the wire body **171** facing away from the bottom of the first mounting groove **111** is flush with the wire body **171**, an insertion depth of the top-side edge **131** of the spectacle lens **13** in the first mounting groove **111** may be reduced, which may disadvantage the stable installation of the spectacle lens **13** in the eyeglass rim **11**. In the embodiment, the top-side edge **131** of the spectacle lens **13** may avoid a portion of the connection wire **17** through the clearance slot **1311**, so that the top-side edge **131** may further extend towards the bottom of the first mounting groove **111** relative to the clearance slot **1311** and abut on the abutting portions **1722** on the two sides of the protruding portion **1721**. Therefore, the space occupied by the connection wire **17** in the first mounting groove **111** may be reduced to a certain extent, so that the spectacle lens **13** may be installed deeper inside the first mounting groove **111**, thereby improving the stability of the spectacle lens **13** in the eyeglass rim **11**.

(128) In an application scenario, the eyeglass rim **11** may be thin, and at least a portion of the convex portion **1721** may be exposed outside the first mounting groove **111** to reduce the space of the eyeglass rim occupied by the connection wire **17**, thereby reducing the depth of the first mounting groove **111** and improving the stability of the eyeglass rim **11**.

(129) As used herein, further referring to FIG. 2 and FIG. 12, FIG. 12 is a partial structural diagram illustrating part B in FIG. 7 according to some embodiments of the present disclosure. In one embodiment, the first buckle **1321** may include a first sub-edge **13211**, a second sub-edge **13212**, and a third sub-edge **13213**.

(130) As used herein, the first sub-edge **13211** may be disposed adjacent to the top-side edge **131**. The second sub-edge **13212** may be disposed away from the top-side edge **131** and opposite to the first sub-edge **13211**. The third sub-edge **13213** may be connected to the first sub-edge **13211** and

the second sub-edge **13212** on a side of the first sub-edge **13211** and the second sub-edge **13212** away from the spectacle lens **13**.

(131) In the embodiment, the wire protection cover **172** may further extend to the first buckle groove **112** along the first sub-edge **13211**.

(132) In the way, the wire protection cover **172** may be held in the first mounting groove **111** and extend to the first buckle groove **112** to be hidden in the eyeglass rim **11**. Therefore, when a user disassembles the spectacle lens **13** during use, the wire protection cover **172** may not be exposed after the spectacle lens **13** is disassembled to maintain the beauty of the eyeglasses.

(133) Further, when extending towards the first buckle groove **112**, the wire protection cover **172** may end at a connection between the first sub-edge **13211** and the third sub-edge **13213**. Certainly, the wire protection cover **172** may also not end and continue to extend along the wire body **171**, as long as the wire protection cover **172** is not exposed when the spectacle lens **13** is disassembled.

(134) Referring to FIG. **13** together, FIG. **13** is an enlarged sectional view illustrating a partial structure of eyeglasses according to an embodiment of the present disclosure. In the embodiment, the eyeglasses may further include rotating shaft(s) **19**.

(135) As used herein, the count of the rotating shaft(s) **19** may be two, and be respectively used to connect the eyeglass rim **11** and the two eyeglass temples **15** so that the eyeglass rim **11** and the eyeglass temples **15** may rotate relative to the rotating shaft **19**. As used herein, the rotating shaft **19** may be disposed with a rotating shaft wiring channel **191** in an axial direction. The connection wire **17** may be disposed inside the shaft wiring channel **191** and extend to the eyeglass rim **11** and the eyeglass temples **15**, respectively.

(136) Specifically, in the embodiment, after the connection wire **17** passes through the rotating shaft wiring channel **191**, one end of the connection wire **17** may extend directly to one of the eyeglass temples **15**, and the other end of the connection wire **17** may enter the eyeglass rim **11** and further extend to another one of the eyeglass temples **15** along the first mounting groove **111**, thereby electrically connecting the two function components **16** located inside the two eyeglass temples **15**, respectively.

(137) In the embodiment, the connection wire **17** near the rotating shaft wiring channel may not include the wire protection cover **172**. The rotating shaft wiring channel **191** may pass through the rotating shaft **19**.

(138) It may be easy to understand that relative positions of structures near the rotating shaft **19** may change when the eyeglass rim **11** and the eyeglass temple **15** are folded. At this time, if the connection wire **17** located at the connection between the eyeglass rim **11** and the eyeglass temple **15** is directly disposed around the periphery of the rotating shaft **19**, the connection wire **17** herein may be compressed or pulled, even deformed or broken with the folding of eyeglass rim **11** or eyeglass temples **15**, which may affect the stability of the connection wire **17** and shorten the service life of the connection wire **17**.

(139) In the embodiment, the rotating shaft **19** may be disposed with the shaft wiring channel **191** along the axial direction. The connection wire **17** located at the connection between the eyeglass rim **11** and the eyeglass temple **15** may pass through the shaft wiring channel **191**. Therefore, when the eyeglass rim **11** and the eyeglass temple **15** are folded, the connection wire **17** located inside the rotating shaft wiring channel **191** may only generate a certain amount of rotation with the rotation of the rotating shaft **19** to reduce the folding, compressing or pulling of the connection wire **17**, thereby protecting the connection wire **17** to a certain extent, improving the stability of the connection wire **17**, and extending the service life of the connection wire **17**.

(140) As used herein, in the embodiment, an inner diameter of the rotation shaft wiring channel **191** may be larger than an outer diameter of the connection wire **17**. For example, the inner diameter of the shaft wiring channel **191** may be twice the outer diameter of the connection wire **17**.

Accordingly, a binding effect of the inner side wall of the axis wiring channel **191** on the connection wire **17** may be reduced, thereby reducing the rotation of the connection wire **17** when

the eyeglass rim **11** and the eyeglass temple **15** are folded.

(141) Referring to FIG. **13** and FIG. **14** together, FIG. **14** is a schematic structural diagram illustrating a rotating shaft and a connection wire of eyeglasses according to an embodiment of the present disclosure. In the embodiment, the rotating shaft **19** may include a first rotating shaft **192**. Two ends of the first rotating shaft **192** may be respectively connected to the eyeglass rim **11** and the eyeglass temple **15**. The rotating shaft wiring channel **191** may be disposed along an axial direction of the first rotating shaft **192**. The shaft wiring channel **191** may communicate with the outside through a wiring port **1921** disposed on at least one end surface of the first rotating shaft **192**. The connection wire **17** may extend to the eyeglass rim **11** or the eyeglass temples **15** through the wiring port **1921**.

(142) It should be noted that, in the embodiment, the first rotating shaft **192** may be rotatably connected to one of the eyeglass rim **11** and the eyeglass temples **15**, and fixedly connected to another, so that the eyeglass rim **11** and the eyeglass temples **15** may be rotatably connected around the first rotating shaft **192**.

(143) Specifically, in the embodiment, the rotating shaft wiring channel **191** may be disposed inside the first rotating shaft **192**, and further communicate with the outside through the wiring port **1921**.

(144) Specifically, the rotating shaft wiring channel **191** may penetrate at least one end surface of the first rotating shaft **192** to form the wiring port **1921** of the rotating shaft wiring channel **191**. Therefore, the connection wire **17** may extend from the shaft wiring channel **191** through the at least one end surface of the first rotating shaft **192**, and then extend to the eyeglass rim **11** or the eyeglass temples **15**. It may be easy to understand that the periphery of the end surface of the first rotating shaft **192** may have a relatively large movement space. The connection wire **17** extending from the end surface of the first rotating shaft **192** may be accommodated inside the movement space. And if the first rotating shaft **192** at the end face is rotatably connected to the corresponding eyeglass rim **11** or eyeglass temple **15**, when the eyeglass rim **11** and the eyeglass temple **15** fold and rotate, the movement space may be appropriately buffered a twist of the connection wire **17** near the wiring port **1921** on the end surface with the rotation of the first rotating shaft **192**, thereby further reducing the twisting degree of the connection wire **17** and improving the stability of connection wire **17**.

(145) Referring to FIG. **15**, FIG. **15** is a schematic structural diagram illustrating a first rotating shaft of eyeglasses according to an embodiment of the present disclosure. In the embodiment, the wiring port **1921** may include a first wiring port **19211** and a second wiring port **19212** respectively disposed on two ends of the first rotating shaft **192**. The rotating shaft wiring channel **191** may communicate with the outside through the two wiring ports **1921**, so that the connection wire **17** may pass through the two ends of the first rotating shaft **192** and extend to the eyeglass rim **11** and the eyeglass temple **15** through the first wiring port **19211** and the second wiring port **19212**, respectively.

(146) In other words, in the application scenario, the connection wire **17** at the connection between the eyeglass rim **11** and the eyeglass temple **15** may be disposed inside the rotating shaft wiring channel **191** in the first rotating shaft **192**, and extend from the rotating shaft wiring channel **191** through the two ends of the first rotating shaft **192**, respectively. At this time, since large movement spaces exist on the periphery of two end surfaces of the first rotating shaft **192**, the connection wire **17** extending from the two end surfaces of the first rotating shaft **192** may only move or twist slightly without compressing or deforming when the relative rotation occurs between the eyeglass rim **11** and the eyeglass temple **15**.

(147) Referring to FIG. **14**, in the embodiment, the wiring port **1921** may include a first wiring port **19213** and a second wiring port **19214**. As used herein, the first wiring port **19213** may be disposed on an end surface of the first rotating shaft **192**, and the second wiring port **19214** may be disposed on a side wall of the first rotating shaft **192**. Therefore, one end of the shaft wiring channel **191** may penetrate the end surface of the first rotating shaft **192** in the axial direction through the first

wiring port **19213**, and the other end may penetrate the side wall of the first rotating shaft **192** through the second wiring port **19214**, and then communicate with the outside. The connection wire **17** may extend to the eyeglass rim **11** and the eyeglass temple **15** through the first wiring port **19213** and the second wiring port **19214**, respectively.

(148) Similarly, a large movement space may be disposed near the end face of the first rotating shaft **192** of the first wiring port **19213**. When a relative movement occurs between the eyeglass rim **11** and the eyeglass temple **15**, the connection wire **17** near the first wiring port **19213** may only undergo a relative shift, or a small twist.

(149) In an application scenario, the first rotating shaft **192** may be fixedly connected to one of the eyeglass rim **11** and the eyeglass temple **15** disposed near the second wiring port **19214**, and rotatably connected to another of the eyeglass rim **11** and the eyeglass temple **15** disposed near the first wiring port **19213**. That is, the first rotating shaft **192** may be rotatably connected to one of the eyeglass rim **11** or the eyeglass temple **15** at the wiring port **1921** disposed on the end surface. The first rotating shaft **192** may be fixedly connected to another of the eyeglass rim **11** or the eyeglass temple **15** at the wiring port **1921** disposed on the side wall.

(150) In an application scenario, the first rotating shaft **192** may be closed to the eyeglass rim **11** at the first wiring port **19213**, and rotatably connected to the eyeglass rim **11**. The first rotating shaft **192** may be closed to the eyeglass temple **15** at the second wiring port **19214**, and fixedly connected to the eyeglass temple **15**.

(151) It should be noted that, in this application scenario, the first rotating shaft **192** is rotatably connected to the eyeglass rim **11**, and the relative rotation between the eyeglass rim **11** and the eyeglass temple **15** may cause the relative movement of the connection wire **17** at the first wiring port **19213**. However, since the first wiring port **19213** is disposed on the end surface of the first rotating shaft **192**, similar to the embodiment described above, the end surface of the first rotating shaft **192** may have a large movement space. When the eyeglass rim **11** and the eyeglass temple **15** are folded and rotated, and the connection wire **17** near the wiring port **1921** on the end surface is twisted to a certain extent with the rotation of the first rotating shaft **192**, the movement space may be appropriately buffered, and the twist may be turned into a shift or a small twist, without compressing or pulling the connection wire, thereby improving the stability of the connection wire and extending the service life of the connection wire.

(152) In addition, the first rotating shaft **192** may be fixedly connected to the eyeglass temple **15** at the second wiring port **19214**. It may be easy to understand that the eyeglass temple **11** and the first rotating shaft **192** may be synchronized when the relative rotation occurs between the eyeglass rim **11** and the eyeglass temple **15**. Hence, the connection wire **17** in the shaft wiring channel **191** may extend through the second wiring port **19214** into the connection wire **17** of the eyeglass temple **11** without twisting, compressing, or pulling. Therefore, at this time, the second wiring port **19214** may be disposed on the end surface of the first rotating shaft **192** or on the side wall of the first rotating shaft **192**. The relative rotation between eyeglass rim **11** and eyeglass temple **15** may not cause the twisting, compressing, pulling, etc., of the connection wire **17** herein.

(153) In other embodiments, if the first rotating shaft **192** and the eyeglass temple **15** are rotatably connected at the second wiring port **19214**, the relative rotation between thereof may allow the connection wire **17** to move, which may be constrained by the side wall of the first rotating shaft at the second wiring port **19214**, so that the connection wire **17** may be compressed between the side wall of the first rotating shaft and the eyeglass temple **15**.

(154) If the first rotating shaft **192** is near the eyeglass temple **15** at the first wiring port **19213** and rotatably connected to the eyeglass temple **15**, the first rotating shaft **192** may be near the eyeglass rim **11** at the second wiring port **19214** and fixedly connected to the eyeglass rim **11**. For the same reason, when the eyeglass rim **11** and the eyeglass temple **15** are folded, the connection wire **17** inside the rotating shaft wiring channel **191** and near the first wiring port **19213** and the second wiring port **19214** may be still only slightly twisted or moved.

(155) Referring to FIG. 14, in one embodiment, the rotating shaft **19** may further include a second shaft **193** coaxial with and spaced from the first rotating shaft **192**.

(156) In the embodiment, the second rotating shaft **193** may be disposed on a side of the first rotating shaft **192** near the first wiring port **19213**. Certainly, in other embodiments, the second rotating shaft **193** may also be disposed on a side of the first rotating shaft **192** closed to the second wiring port **19214**.

(157) Referring to FIG. 16, FIG. 16 is a partial exploded view illustrating eyeglasses according to an embodiment of the present disclosure. In the embodiment, the eyeglass rim **11** may include first lug(s) **113**. Specifically, the count of the first lug(s) **113** may be two, and be respectively disposed at two ends of the eyeglass rim **11** connecting to the two eyeglass temples **15** and protrude towards the corresponding eyeglass temples **15**.

(158) The eyeglass temple **15** may include a second lug **1501** and a third lug **1502** disposed at intervals. As used herein, the second lug **1501** and the third lug **1502** may face ends of the eyeglass rim **11** connected to the eyeglass temple **15** at which the lugs are located. In addition, when the user wears the eyeglasses, the second lug **1501** and the third lug **1502** may be connected to a side away from the head of the user, thereby making the eyeglasses more overall and more beautiful in appearance. In an application scenario, the second lug **1501** and the third lug **1502** disposed at intervals may be formed by disposing a groove in the middle of an end of the eyeglass temple **15** facing the eyeglass rim **11**.

(159) Further, ends of the first rotating shaft **192** and the second rotating shaft **193** closed to each other may be connected to the first lug **113**. Ends of the first rotating shaft **192** and the second rotating shaft **193** away from each other may be connected to the second lug **1501** and the third lug **1502**, respectively, so as to maintain the first lug **113** between the second lug **1501** and the third lug **1502**.

(160) As used herein, referring to FIG. 14 continuously, in one embodiment, the first wiring port **19213** may be disposed on an end surface of the first rotating shaft **192** near the second rotating shaft **193**. The second wiring port **19214** may be disposed on a side wall of the first rotating shaft near the second lug **1501**. The first rotating shaft may be rotatably connected to the first lug **113** and fixedly connected to the second lug **1501**.

(161) Specifically, in the embodiment, one end of the connection wire **17** inside the rotating shaft wiring channel **191** may extend from the first wiring port **19213** and pass through an interval between the first rotating shaft **192** and the second rotating shaft **193**. Further, in an application scenario, the first lug **113** may be disposed with a wiring channel connected to the first wiring port **19213**, so that the connection wire **17** may further enter the eyeglass rim **11** from the first lug **113**.

(162) In addition, the other end of the connection wire **17** inside the rotating shaft wiring channel **191** may extend from the second wiring port **19214**. Further, in an application scenario, the third lug **1502** may be disposed with a wiring channel communicating with the second wiring port **19214**, so that the connection wire **17** may further enter the eyeglass temple **15** through the wiring channel of the third lug **1502**.

(163) As used herein, the second wiring port **19214** may be a through-hole disposed on a side wall of the first rotating shaft **192**, and communicated with the rotating shaft wiring channel **191** without penetrating an end of the first rotating shaft **192**. In the embodiment, the second wiring port **19214** may be further penetrated along the side wall of the first rotating shaft **192** to an end of the first rotating shaft **192** away from the first wiring port **19213**. It may be easy to understand that, in the embodiment, the second wiring port **19214** may have a larger space. Therefore, when the connection wire **17** is moved for some reason, the restriction on the connection wire **17** may be further reduced, and the damage to the side wall of the first rotating shaft **192** may be further reduced.

(164) Referring to FIG. 16, FIG. 17, and FIG. 18 together, FIG. 17 is a schematic structural diagram illustrating an eyeglass rim and a spectacle lens of eyeglasses according to an embodiment

of the present disclosure, and FIG. 18 is a partial structural schematic diagram illustrating an eyeglass temple of eyeglasses according to an embodiment of the present disclosures. In the embodiment, the first lug **113** and the second lug **1501** may be coaxially disposed with a first accommodating hole **1131** and a second accommodating hole **15011**, respectively. Sizes of the first accommodating hole **1131** and the second accommodating hole **15011** may be set to allow the first rotating shaft **192** to be inserted into the first accommodating hole **1131** from the outside of the eyeglass temple **15** through the second accommodating hole **15011**, such that the first rotating shaft **192** may be in an interference fit with the second accommodating hole **15011** and in a clearance fit with the first accommodating hole **1131**.

(165) Specifically, the second accommodating hole **15011** may be a through-hole penetrating the second lug **1501**. The first accommodating hole **1131** may correspond to the second accommodating hole **15011** and penetrate at least a portion of the first lug **113**. As used herein, an inner diameter of the first accommodating hole **1131** may be larger than the second accommodating hole **15011**. An outer diameter of the first rotating shaft **192** may be between the first accommodating hole **1131** and the second accommodating hole **15011**. Therefore, the first rotating shaft **192** may be fixedly connected to the eyeglass temple **15** and rotatably connected to the eyeglass rim **11** so that the eyeglass rim **11** and the eyeglass temple **15** may be rotated around the first rotating shaft **192** to be folded or unfolded.

(166) Further, in an embodiment, the first lug **113** and the third lug **1502** may be coaxially disposed with a third accommodating hole **1132** and a fourth accommodating hole **15021**, respectively. Sizes of the third accommodating hole **1132** and the fourth accommodating hole **15021** may be set to allow the second rotating shaft **193** to be inserted into the third accommodating hole **1132** from the outside of the eyeglass temple **15** via the fourth accommodating hole **15021**, such that the second rotating shaft **193** may be in an interference fit with the third accommodating hole **1132** and in a clearance fit with the fourth accommodating hole **15021**, or the second rotating shaft **193** may be in a clearance fit with the third accommodating hole **1132** and in an interference fit with the fourth accommodating hole **15021**.

(167) In the embodiment, the third accommodating hole **1132** and the fourth accommodating hole **15021** may be coaxial with both the first accommodating hole **1131** and the second accommodating hole **15011**. As used herein, the third accommodating hole **1132** may penetrate at least a portion of the first lug **113**. In one application scenario, the first accommodating hole **1131** and the third accommodating hole **1132** may be coaxially penetrated. Specifically, as described in the above embodiment, the first lug **113** of the eyeglass rim **11** may be disposed with a wiring channel connected to the first wiring port **19213**. The first accommodating hole **1131** and the third accommodating hole **1132** may be respectively disposed on both sides of the wiring channel located inside the first lug **113** and both pass through the wiring channel. The fourth accommodating hole **15021** may penetrate the third lug **1502**. As used herein, the outer diameter of the second rotating shaft **193** may be between the inner diameter of the third accommodating hole **1132** and the inner diameter of the fourth accommodating hole **15021**. The inner diameter of the third accommodating hole **1132** may be larger than the fourth accommodating hole **15021**. Alternatively, the inner diameter of the fourth accommodating hole **15021** may be larger than the third accommodating hole **1132**. Therefore, the second rotating shaft **193** may be fixedly connected to the eyeglass temple **15** and rotatably connected to the eyeglass rim **11**, or the second rotating shaft **193** may be fixedly connected to the eyeglass rim **11** and rotatably connected to the eyeglass temple **15**, so that the eyeglass rim **11** and the eyeglass temple **15** may be rotated around the first rotating shaft **192** to be folded or unfolded.

(168) In one embodiment, the second rotating shaft **193** may be a solid shaft, and the diameter may be less than that of the first rotating shaft **192**. In the wearing state, the second shaft **193** may be located on the upper side of eyeglass temple **15**, and the first rotating shaft may be located on the lower side of eyeglass temple **15**.

(169) It should be noted that, since the rotating shaft wiring channel **191** may be disposed inside the first rotating shaft **192**, the outer diameter of the first rotating shaft **192** may be larger, which may adversely satisfy aesthetic needs of the user. Therefore, in the embodiment, the second rotating shaft **193** having a smaller outer diameter may be further disposed. Hence, when the user wears the eyeglasses, the second rotating shaft **193** may be disposed on an upper portion that is easily found, and the first rotating shaft **192** may be disposed on a lower portion that is not easily observed. Since the outer diameter of the second rotating shaft **193** is smaller, the overall aesthetic effect of the eyeglasses may be improved to a certain extent.

(170) Certainly, in other embodiments, the first rotating shaft **192** and the second rotating shaft **193** may also be other cases. For example, the second rotating shaft **193** may also be a hollow shaft, and the diameter of the second rotating shaft **193** may be larger than the diameter of the first rotating shaft **192**. Alternatively, in the wearing state, the second rotating shaft **193** may be disposed on a lower side of the eyeglass temple **15**, and the first rotating shaft **192** may be disposed on an upper side of the eyeglass temple **15**, or the like, and be not limited herein.

(171) In addition, referring to FIG. **14**, a connection between an end surface **1922** of the first rotating shaft **192** for disposing the first wiring port **19213** and an inner wall surface **1923** of the first rotating shaft **192** for defining the rotating shaft wiring channel **191** may be arc-shaped. It may be easy to understand that, when the rotation between the eyeglass rim **11** and the eyeglass temple **15** through the rotating shaft **19** occurs, since the first rotating shaft **192** and the eyeglass rim **11** are rotatably connected, the connection wire **17** at the first wiring port **19213** may be moved. In the embodiment, the connection between the end surface **1922** of the first rotating shaft **192** and the inner wall surface **1923** may be arc-shaped. Therefore, when the connection wire **17** at the first wiring port **19213** moves and contacts with the first rotating shaft **192**, the connection wire **17** may be avoided to be cut if the connection is too sharp, thereby further protecting the connection wire **17**.

(172) In an application scenario, a connection between the end surface of the first rotating shaft **192** for disposing the second wiring port **19214** and the inner wall surface **1923** of the first rotating shaft **192** for defining the rotating shaft wiring channel **191** may also be arc-shaped. Similarly, in this way, the connection wire **17** may be further protected.

(173) It should be noted that the above description of the rotating shaft and wiring in the eyeglasses may be only specific examples, and should be not considered as the only feasible implementation. Obviously, for those skilled in the art, after understanding the basic principle of the rotating shaft and wiring in the eyeglasses, it may be possible to make various modifications and changes in the form and details of the specific manner and operation of implementing the rotating shaft and wiring in the eyeglasses without departing from these principles, but these modifications and changes are still within the scope described above. For example, the branch circuit board may also include a third pad and a third flexible circuit board. All such variations may be within the protection scope of the present disclosure.

(174) In some embodiments, as shown in FIG. **1**, a speaker includes an earphone core **102** and a core housing **108**. In an application scenario, the speaker of the eyeglasses may include, but is not limited to, a bone conduction speaker, an air conduction speaker. The following may further illustrate a fitting position on human body based on the bone conduction speaker. It should be known that without departing from the principles, the following illustrations may also be applied to the air conduction speaker.

(175) In some embodiments, the position of the speaker relative to the eyeglass temple **15** may not be fixed. Specifically, the core housing **108** may be rotated to change the position of each speaker relative to the connected eyeglass temple **15**, thus the speaker may fit on different parts of the user's body, and the user may adjust it based on his or her preferences. Due to the vibrations transmitted by different bones are different, users may feel different sound qualities, and it is also convenient for users with different sizes of head. For example, in FIG. **7**, the speaker may be fixed on the ear

by the eyeglass temple **15**, and the speaker may be located behind the ear. In some embodiments, the connecting end of the eyeglass temple **15** and the speaker may be set according to a position that the user is accustomed to. For example, the speaker and the eyeglass temple **15** may be connected by hinged connection, if the user is used to placing the speaker behind the ear, the speaker may be set behind the ear by adjusting a hinge component. It should be noted that, the connection between the eyeglass temple **15** and the speaker **21** is not limited to the connection described above. For example, the eyeglass temple **15** and the speaker may also be connected by clamping. In some embodiments, the speaker may be fitted to any parts of the user's head, such as the top of the head, the forehead, cheeks, sideburns, auricles, the back of auricles, or the like. For example, a bracket spanning the top of the head may be arranged between the eyeglass temples **15** to reduce the supporting force of the nose bridge on the eyeglasses, and the speaker may be arranged on the bracket. In some embodiments, the way the bone conductive earphone fitted to the head may be surface fitted or point fitted. The contact surface may be arranged with a gradient structure, and the gradient structure refers to an area where the height of the contact surface changes. The gradient structure may include a convex/concave structure, a step-like structure, etc., on the outside of the contact surface (the side that is fitted to the user), or on the inside of the contact surface (the side facing away from the user).

(176) It should be noted that the above illustration of the fitting position of the speaker is only a specific example and should not be regarded as the only feasible implementation solution. Obviously, for those skilled in the art, after understanding the basic principles of fitting, it is possible to make various modifications and changes in forms and details to the specific methods and steps of fitting without departing from the principles, but the modifications and changes are still within the scope illustrated above. For example, the position of clamping may be adjusted based on the fitting part of the speaker and the head. Such deformations are all within the protection scope of the present disclosure.

(177) FIG. **19** is a structural diagram and an application scenario of a bone conduction speaker according to some embodiments of the present disclosure. Referring to FIG. **1** and FIG. **19**, the structural diagram in FIG. **19** illustrating a speaker including the earphone core **102** and the core housing **108** in FIG. **1**. The following only takes the bone conduction speaker as an example to illustrate the application scenario and structure of the speaker. In some embodiments, as shown in FIG. **19**, the bone conduction speaker may include a driving component **1901**, a transmission component **1902**, a panel **1903** (the panel **1903** may also be referred to as a housing panel, which is a panel on the core housing facing human), a housing **1904**, or the like. Referring to FIG. **1**, the panel **1903** and the housing **1904** are consistent with the core housing (shown in FIG. **1**). The driving component **1901** and the transmission component **1902** are consistent with the earphone core **102** (shown in FIG. **2**). In some embodiments, the housing **1904** may include a housing back panel and housing side panels. The housing back panel is connected with the panel **1903** through the housing side panels. The driving component **1901** may transmit vibration signal(s) to the panel **1903** and/or the housing **1904** through the transmission component **1902**, so as to transmit a sound to human body by contacting human skin through the panel **1903** or the housing **1904**. In some embodiments, the panel **1903** and/or the housing **1904** may be in contact with human skin at the tragus, so as to transmit a sound to human body. In some embodiments, the panel **1903** and/or the housing **1904** may be in contact with human skin on the back of the auricle.

(178) In some embodiments, a straight line B (or a vibrating direction of a driving device) of a driving force generated by the driving component **1901** and a normal line A of the panel **1903** may form an angle θ . In other words, the straight line B is not parallel to the normal line A.

(179) The panel has an area that contacts or abuts the user's body, such as human skin. It should be understood that when the panel is covered with other materials (such as silicone and other soft materials) to enhance the user's wearing comfortability, the panel and the user's body are not in direct contact, but abut against each other. In some embodiments, when the bone conduction

speaker is worn on the user's body, the whole area of the panel contacts or abuts the user's body. In some embodiments, when the bone conduction speaker is worn on the user's body, a part of the panel contacts or abuts the user's body. In some embodiments, the area of the panel contacting or abutting the user's body may account for more than 50% of the entire area of the panel. More preferably, it may account for more than 60% of the entire area of the panel. In general, the area of the panel contacting or abutting the user's body may be flat or curved.

(180) In some embodiments, when the area of the panel contacting or abutting the user's body is a flat surface, its normal line meets the general definition, that is, a dashed line perpendicular to the flat surface. In some embodiments, when the area contacting or abutting the user's body of the panel is a curved surface, its normal line is the average normal line of the area, wherein, the average normal line is defined as follows:

$$(181) \quad \bar{r} = \frac{\oint_S r ds}{\oint_S ds} \quad (1)$$

(182) where, \bar{r} is the average normal line; $\{r\}$ is the normal line of any point on the curved surface; ds is a surface unit.

(183) Further, the curved surface is a quasi-flat surface that is close to the flat surface. That is, the curved surface is a surface that an angle between a normal line of any point of at least 50% of the area on the curved surface and the average normal line is less than a set threshold. In some embodiments, the set threshold may be less than 10°. In some embodiments, the set threshold may be less than 5°.

(184) In some embodiments, the straight line B of the driving force and the normal line A' of the area of the panel **1903** for contacting or abutting the user's body may form the angle θ . A value range of the angle θ may be $0 < \theta < 180^\circ$. Further, the value range may be $0 < \theta < 180^\circ$ and not equal to 90° . In some embodiments, it is assumed that the straight line B has a positive direction pointing to the outside of the bone conduction speaker, and the normal line A of the panel **1903** (or the normal line A' of a contact surface of the panel **1903** and the human skin) also has a positive direction pointing to the outside of the bone conduction speaker. Thus, the angle θ formed by the normal line A or A' and the straight line B in the positive direction is an acute angle, that is, $0 < \theta < 90^\circ$. More descriptions about the normal line A and A' may be found in FIG. 21 and the descriptions thereof.

(185) FIG. 20 is a schematic diagram illustrating a direction of an included angle according to some embodiments of the present disclosure. As shown in FIG. 20, in some embodiments, a driving force generated by a driving device has a component in a first quadrant and/or a third quadrant of an XOY plane coordinate system. As used herein, the XOY plane coordinate system is a reference coordinate system whose origin O is located on a contact surface between the panel and/or the housing and the human body after the bone conduction speaker is worn on the human body. The X axis is parallel to the coronal axis of the human body, the Y axis is parallel to the sagittal axis of the human body, and the positive direction of the X axis faces the outside of the human body, the positive direction of the Y axis faces the front of the human body. Quadrants should be understood as four regions divided by the horizontal axis (such as X axis) and the vertical axis (such as Y axis) in a rectangular coordinate system. Each region is a quadrant. The quadrant is centered at the origin, and the X axis and Y axis are the dividing lines. The upper right region (the region enclosed by the positive half axis of the X axis and the positive half axis of the Y axis) is the first quadrant, the upper left region (the region enclosed by the negative half axis of the X axis and the positive half axis of the Y axis) is the second quadrant, the lower left region (the region enclosed by the negative half axis of the X axis and the negative half axis of the Y axis) is the third quadrant, and the lower right region (the region enclosed by the positive half axis of the X axis and the negative half axis of the Y axis) is the fourth quadrant. The points on the X axis and the Y axis do not belong to any quadrant. It should be understood that the driving force in the embodiment may be directly located in the first quadrant and/or the third quadrant of the XOY plane coordinate system, or the driving force may point to other directions, but the projection or component in the first quadrant

and/or the third quadrant is not equal to 0 in the XOY plane coordinate system, and the projection or component in a direction of a Z axis may be equal to 0 or not equal to 0. As used herein, the Z axis is perpendicular to the XOY plane and passes through the origin O. In some embodiments, the angle θ between the straight line of the driving force and the normal line of the area contacting or abutting the user's body of the panel may be any acute angle, for example, the range of the angle θ is $5^{\circ}\sim 80^{\circ}$. More preferably, the range is $15^{\circ}\sim 70^{\circ}$. More preferably, the range is $25^{\circ}\sim 60^{\circ}$. More preferably, the range is $25^{\circ}\sim 50^{\circ}$. More preferably, the range is $28^{\circ}\sim 50^{\circ}$. More preferably, the range is $30^{\circ}\sim 39^{\circ}$. More preferably, the range is $31^{\circ}\sim 38^{\circ}$. More preferably, the range is $32^{\circ}\sim 37^{\circ}$. More preferably, the range is $33^{\circ}\sim 36^{\circ}$. More preferably, the range is $33^{\circ}\sim 35.8^{\circ}$. More preferably, the range is $33.5^{\circ}\sim 35^{\circ}$. Specifically, the angle θ may be 26° , 27° , 28° , 29° , 30° , 31° , 32° , 33° , 34° , 34.2° , 35° , 35.8° , 36° , 37° , 38° , etc., wherein the error is controlled within 0.2° . It should be noted that the illustrations of the driving force direction described above should not be interpreted as a limitation of the driving force in the present disclosure. In other embodiments, the driving force may also have component in the second and fourth quadrants of the XOY plane coordinate system, even the driving force may be located on the Y axis, or the like.

(186) FIG. **21** is a structural diagram of a bone conduction speaker acting on human skin and bones according to the present disclosure.

(187) In some embodiments, the straight line of the driving force is collinear or parallel to the straight line of the vibration of the driving device. For example, in a driving device based on the moving-coil principle, the direction of the driving force may be the same as or opposite to the vibrating direction of the coil and/or the magnetic circuit component. The panel may have a flat surface or curved surface, or there are a plurality of protrusions or grooves on the panel. In some embodiments, when the bone conduction speaker is worn on the user's body, the normal line of the area contacting or abutting the user's body of the panel is not parallel to the straight line of the driving force. In general, the area contacting or abutting the user's body of the panel is flat relatively. Specifically, it may have a flat surface, or a quasi-flat plane with little curvature. When the area contacting or abutting the user's body of the panel has a flat surface, the normal line of any point on it may be the normal line of the area. At this time, the normal line A of the panel **1903** may be parallel or coincident to the normal line A' of the contact surface between the panel **1903** and human skin. When the panel used to contact the user's body is non-planar, the normal line of the area may be the average normal line. More detailed definition of the average normal line may be found in FIG. **19** and the descriptions thereof. In some other embodiments, when the panel used to contact the user's body is non-planar, the normal line of the area may also be determined as follows: selecting a certain point in an area when the panel is in contact with human skin, determining a tangent plane of the panel at the selected point, determining a straight line that passes through the point and is perpendicular to the tangent plane, and designating the straight line as the normal line of the panel. When the panel used to contact the user's body is non-planar, different points correspond to different tangent planes of the panel, and the determined normal line may also be different. At this time, the normal line A' is not parallel to the normal line A of the panel.

According to a specific embodiment of the present disclosure, the straight line of the driving force (or the straight line of the vibration of the driving device) and the normal line of the area may form an angle θ , where $0<\theta<180^{\circ}$. In some embodiments, when the straight line of the driving force has a positive direction pointing to the outside of the bone conduction speaker from the panel (or the contact surface between the panel and/or the housing and human skin), and the normal line of the designated panel (or the contact surface between the panel and/or the housing and human skin) has a positive direction pointing to the outside of the bone conduction speaker, the angle formed by the two straight lines in the positive direction is an acute angle.

(188) As shown in FIG. **21**, the bone conduction speaker may include a driving device (also referred to as a transducer in other embodiments), a transmission component **1803**, a panel **1801**, and a housing **1802**. In some embodiments, a coil **1804** and a magnetic circuit component **1807** are

both ring-shaped. In some embodiments, the driving device adopts a moving-coil driving mode, and includes the coil **1804** and the magnetic circuit component **1807**.

(189) In some embodiments, the coil **1804** and the magnetic circuit component **1807** have axes parallel to each other. The axis of the coil **1804** or the magnetic circuit component **1807** is perpendicular to the radial plane of the coil **1804** and/or the magnetic circuit component **1807**. In some embodiments, the coil **1804** and the magnetic circuit component **1807** have the same central axis. The central axis of the coil **1804** is perpendicular to the radial plane of the coil **1804** and passes through the geometric center of the coil **1804**. The central axis of the magnetic circuit component **1807** is perpendicular to the radial plane of the magnetic circuit component **1807** and passes through the geometric center of the magnetic circuit component **1807**. The axis of the coil **1804** or the magnetic circuit component **1807** and the normal line of the panel **1801** may form the angle θ described above.

(190) Merely by way of example, the relationship between the driving force F and the deformation S of the skin will be illustrated below combined with FIG. 21. When the straight line of the driving force generated by the driving device is parallel to the normal line of the panel **1801** (i.e., the angle θ is zero), the relationship between the driving force and the total deformation of the skin is:

$$F_{\text{sub.}\perp} = S_{\text{sub.}\perp} \times E \times A / h \quad (2)$$

(191) where, $F_{\text{sub.}\perp}$ denotes the driving force, $S_{\text{sub.}\perp}$ denotes the total deformation of the skin in the direction perpendicular to the skin, E denotes the elastic modulus of the skin, A denotes the contact area between the panel and the skin, h denotes a total thickness of the skin (i.e., the distance between the panel and the bone).

(192) When the straight line of the driving force generated by the driving device is parallel to the normal line of the area contacting or abutting the user's body of the panel (i.e., the angle θ is 90°), the relationship between the driving force in the vertical direction and the total deformation of the skin may be shown in Equation (3):

$$F_{\text{sub.}\parallel} = S_{\text{sub.}\parallel} \times G \times A / h \quad (3)$$

(193) where, $F_{\text{sub.}\parallel}$ denotes the driving force, $S_{\text{sub.}\parallel}$ denotes the total deformation of the skin in the direction parallel to the skin, G denotes the shear modulus of the skin, A denotes the contact area between the panel and the skin, h denotes total thickness of the skin (i.e., the distance between the panel and the bone).

(194) The relationship between the shear modulus G and the elastic modulus E is:

$$G = E / 2(1 + \gamma) \quad (4)$$

where, γ denotes the Poisson's ratio of the skin $0 < \gamma < 0.5$. Thus the shear modulus G is less than the elastic modulus E , and under the same driving force, the corresponding total deformation of the skin $S_{\text{sub.}\parallel} > S_{\text{sub.}\perp}$. Generally, the Poisson's ratio of the skin is close to 0.4.

(195) When the straight line of the driving force generated by the driving device is not parallel to the normal line of the area contacting or abutting the user's body of the panel, the driving force in the horizontal direction and the driving force in the vertical direction are expressed as the Equation (5) and Equation (6), respectively:

$$F_{\text{sub.}\perp} = F \times \cos(\theta) \quad (5)$$

$$F_{\text{sub.}\parallel} = F \times \sin(\theta) \quad (6)$$

where, the relationship between the driving force F and the deformation S of the skin may be shown in the following equation:

$$(196) \quad S = \sqrt{s_{\perp}^2 + s_{\parallel}^2} = \frac{h}{A} \times F \times \sqrt{(\cos(\theta) / E)^2 + (\sin(\theta) / G)^2} \quad (7)$$

(197) When the Poisson's ratio is 0.4, the descriptions regarding the relationship between the angle θ and the total deformation of the skin may be found elsewhere of the present disclosure.

(198) FIG. 22 is a diagram illustrating an angle-relative displacement relationship of a bone conduction speaker according to some embodiments of the present disclosure. As shown in FIG. 22, the relationship between the angle θ and the total deformation of the skin is that the greater the

angle θ , and the greater the relative displacement, the greater the total deformation S of the skin. The greater the angle θ , and the less the relative displacement, the less the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin. When the angle θ is close to 90° , the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin gradually tends to 0.

(199) The volume of the bone conduction speaker in the low frequency part is positively correlated with the total deformation of the skin S . The larger the S , the larger the volume of the bone conduction speaker in low frequency. The volume of the bone conduction speaker in the high frequency part is positively correlated with the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin. The larger the $S_{\text{sub.}\perp}$, the larger the volume of the bone conduction speaker in low frequency.

(200) When the Poisson's ratio of the skin is 0.4, the detailed illustration of the relationship between the angle θ and total deformation of the skin S , the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin may be found in FIG. 22. As shown in FIG. 22, the relationship between the angle θ and the total deformation of the skin S is that the larger the angle θ and the larger the total deformation of the skin S , the larger the volume of the corresponding bone conduction speaker in the low frequency part. As shown in FIG. 22, the relationship between the angle θ and the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin is that the larger the angle θ and the smaller the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin, the smaller the volume of the corresponding bone conduction speaker in the high frequency part.

(201) It may be seen from Equation (7) and curves in the FIG. 22 that with the increase of the angle θ , the speed at which the total deformation of the skin S increases is different from the speed at which the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin decreases. The speed at which the total deformation of the skin S increases becomes faster at first, and then becomes slower, and the speed at which the deformation $S_{\text{sub.}\perp}$ of the skin in the vertical direction of the skin decreases becomes faster and faster. In order to balance the volume of the bone conduction speaker in the low frequency part and the high frequency part, the angle θ should be at an appropriate value, for example, within a range of θ is $5^\circ\sim 80^\circ$, $15^\circ\sim 70^\circ$, $25^\circ\sim 50^\circ$, $25^\circ\sim 35^\circ$, $25^\circ\sim 30^\circ$, or the like.

(202) FIG. 23 is a schematic diagram illustrating frequency response curves of a bone conduction speaker in a low-frequency part correspond to different angles θ according to some embodiments in the present disclosure. As shown in FIG. 23, the panel is in contact with the skin and transmits vibration to the skin. During this process, the skin may also affect the vibration of the bone conduction speaker, so as to affect the frequency response curve of the bone conduction speaker. From the above analysis, it is found that the larger the included angle, the larger the total deformation of the skin under the same driving force, and for the bone conduction speaker, it is equivalent to that the elasticity of the skin relative to the panel decreases. It may be further understood that when a certain angle θ is formed between the straight line of the driving force generated by the driving device and the normal line of the area contacting or abutting the user's body of the panel. Especially when the angle θ increases, the resonance peak in the low frequency area of the frequency response curve may be adjusted to a lower frequency area, thus making the low frequency to dive deeper and increasing signals in the low frequencies. Compared with other techniques to improve the low frequency components of the sound (e.g., adding a vibration transmission plate to the bone conduction speaker), setting the included angle may suppress the increase of the vibration effectively while increasing the energy of the low frequency, so as to reduce the sense of vibration, which improves the sensitivity of the low frequency of the bone conduction speaker significantly, and improves the sound quality and human experience. It should be noted that, in some embodiments, the increase of the low frequency and the reduction of the vibration may be expressed as when the angle θ increases in the range of $(0, 90^\circ)$, the energy in the

range of the low frequency of the vibration or the sound signal(s) increases, and the sense of vibration also increases, but the degree of energy increase in the low frequency range is greater than the degree of vibration sensation increase. Thus, in relative effect, the vibration sensation is reduced relatively. It may be seen in FIG. 23, when the included angle is relatively large, the resonance peak in the low frequency area may appear in a lower frequency range, which extends the flat part of the frequency curvature, so as to improve the sound quality of the speaker.

(203) It should be noted that the illustration of the bone conduction speaker described above is only a specific example, and should not be regarded as the only feasible implementation. Obviously, for those skilled in the art, after the basic principles of the bone conduction speaker, it may be possible to make various modifications and changes in forms and details of the specific methods and steps for implementing the bone conduction speaker without departing from the principles, but the modifications and changes are still within the scope illustrated above. For example, the minimum angle θ between the straight line of the driving force generated by the driving device and the normal line of the area contacting or abutting the user's body of the panel may be any acute angle. The acute angle herein is not limited to $5^{\circ}\sim 80^{\circ}$ described above. The angle θ may be less than 5° , such as 1° , 2° , 3° , 4° , etc. In other embodiments, the angle θ may be larger than 80° and less than 90° , such as 81° , 82° , 85° , etc. In some embodiments, the specific value of the angle θ may not be an integer (e.g., 81.3° , 81.38°). Such deformations are all within the protection scope of the present disclosure.

(204) In some embodiments, the speaker described above may also transmit the sound to the user through air conduction. When the air condition is used to transmit the sound, the speaker may include one or more sound sources. The sound source may be located at a specific position of the user's head, for example, the top of the head, a forehead, a cheek, a temple, an auricle, the back of an auricle, etc., without blocking or covering an ear canal. FIG. 24 is a schematic diagram illustrating transmitting a sound through air conduction according to some embodiments of the present disclosure.

(205) As shown in FIG. 24, a sound source **2810** and a sound source **2820** may generate sound waves with opposite phases (“+” and “-” in the figure may indicate the opposite phases). For brevity, the sound sources mentioned herein may refer to sound outlets of the speaker that may output sounds. For example, the sound source **2810** and the sound source **2820** may be two sound outlets respectively located at specific positions of the speaker (e.g., the core housing **108**, or the eyeglass temple **15**).

(206) In some embodiments, the sound source **2810** and the sound source **2820** may be generated by the same vibration device **2801**. The vibration device **2801** may include a diaphragm (not shown in the figure). When the diaphragm is driven to vibrate by an electric signal, the front side of the diaphragm may drive air to vibrate. The sound source **2810** may form at the sound output through a sound guiding channel **2812**. The back of the diaphragm may drive air to vibrate, and the sound source **2820** may be formed at the sound output hole through a sound guiding channel **2822**. The sound guiding channel may refer to a sound transmission route from the diaphragm to the corresponding outlet. In some embodiments, the sound guiding channel may be a route surrounded by a specific structure (e.g., the core housing **108** in FIG. 1, or the eyeglass temple **15** in FIG. 7) on the speaker. It should be known that in some alternative embodiments, the sound source **2810** and the sound source **2820** may also be generated by different vibrating diaphragms of different vibration devices, respectively.

(207) Among the sounds generated by the sound source **2810** and the sound source **2820**, one portion may be transmitted to the ear of the user to form the sound heard by the user. Another portion may be transmitted to the environment to form a leaked sound. Considering that the sound source **2810** and the sound source **2820** are relatively close to the ears of the user, for convenience of description, the sound transmitted to the ears of the user may be referred to as a near-field sound. The leaked sound transmitted to the environment may be referred to as a far-field sound. In some

embodiments, the near-field/far-field sounds of different frequencies generated by the speaker may be related to a distance between the sound source **2810** and the sound source **2820**. Generally speaking, the near-field sound generated by the speaker may increase as the distance between the two sound sources increases, while the generated far-field sound (the leaked sound) may increase with increasing the frequency.

(208) For the sounds of different frequencies, the distance between the sound source **2810** and the sound source **2820** may be designed, respectively, so that a low-frequency near-field sound (e.g., a sound with a frequency of less than 800 Hz) generated by the speaker may be as large as possible and a high-frequency far-field sound (e.g., a sound with a frequency greater than 2000 Hz) may be as small as possible. In order to implement the above purpose, the speaker may include two or more sets of dual sound sources. Each set of the dual sound sources may include two sound sources similar to the sound source **2810** and the sound source **2820**, and generate sounds with specific frequencies, respectively. Specifically, a first set of the dual sound sources may be used to generate low frequency sounds. A second set of the dual sound sources may be used to generate high frequency sounds. In order to obtain more low-frequency near-field sounds, the distance between two sound sources in the first set of the dual sound sources may be set to a larger value. Since the low-frequency signal has a longer wavelength, the larger distance between the two sound sources may not cause a large phase difference in the far-field, and not form excessive leaked sound in the far-field. In order to make the high-frequency far-field sound smaller, the distance between the two sound sources in the second set of the dual sound sources may be set to a smaller value. Since the high-frequency signal has a shorter wavelength, the smaller distance between the two sound sources may avoid the generation of the large phase difference in the far-field, and thus the generation of the excessive leaked sounds may be avoided. The distance between the second set of the dual sound sources may be less than the distance between the first set of the dual sound sources.

(209) It should be noted that the above description of the sound conduction manner for changing the air conduction may be only a specific example, and should not be considered as the only feasible implementation. Obviously, for those skilled in the art, after understanding the basic principles of the air conduction, it may be possible to target air conduction speaker of different shapes and structures without departing from these principles, but these changes may still be within the scope of the above description. For example, the sound guiding channel **2822** may be disposed in the eyeglasses according to other descriptions. All such variations are within the protection scope of the present disclosure.

(210) The beneficial effects of the embodiments of the present disclosure may include but be not limited to the following. (1) Through the rotating shaft, the eyeglass rim and eyeglass temple may be connected, thereby protecting the connection wire in the eyeglasses, and extending the life of the connection wire. (2) The flexible circuit board may simplify the wiring manner in the speaker. (3) The user may adjust the fitting position of the speaker according to his or her own preferences and habits, which meets the requirement of the user. (4) The sound quality of the speaker may be improved by adjusting the angle θ between the normal line A of the panel or the normal line A' of the panel contacting human skin and the straight line B of the driving force generated by the driving device. It should be noted that different embodiments may have different beneficial effects. In different embodiments, the possible beneficial effects may be any one or a combination of the above, and may be any other beneficial effects that may be obtained.

(211) Having thus described the basic concepts, it may be rather apparent to those skilled in the art after reading this detailed disclosure that the foregoing detailed disclosure is intended to be presented by way of example only and is not limiting. Various alterations, improvements, and modifications may occur and are intended to those skilled in the art, though not expressly stated herein. These alterations, improvements, and modifications are intended to be suggested by this disclosure, and are within the spirit and scope of the exemplary embodiments of this disclosure.

Claims

1. A pair of eyeglasses, wherein the eyeglasses include: an eyeglass rim; an eyeglass temple; a shaft, the shaft being configured to connect the eyeglass rim and the eyeglass temple; a speaker, the speaker comprising a core housing and an earphone core, the speaker being connected to the eyeglass temple; a first microphone and a second microphone disposed in the eyeglass temple; and a first sound inlet and a second sound inlet disposed on the eyeglass temple, wherein the first microphone and the second microphone collect external sound through the first sound inlet and the second sound inlet, respectively, wherein the shaft includes a first shaft; two ends of the first shaft are respectively connected to the eyeglass rim and the eyeglass temple; the shaft is disposed with a shaft wiring channel disposed along an axial direction of the first shaft; and the shaft wiring channel communicates with an outside through a first wiring port disposed on an end surface of the first shaft and a second wiring port disposed on a side wall of the first shaft, the first shaft is fixedly connected to the eyeglass temple that is disposed near the second wiring port, and rotatably connected to the eyeglass rim that is disposed near the first wiring port, wherein the eyeglasses further include a connection wire, the connection wire extending to the eyeglass rim and the eyeglass temple through the first wiring port and the second wiring port, respectively.
2. The eyeglasses of claim 1, further comprising: a spectacle lens disposed with a vent hole.
3. The eyeglasses of claim 1, wherein the shaft further comprises a second shaft that is coaxial with and spaced from the first shaft; the eyeglass rim includes a first lug, and the eyeglass temple includes a second lug and a third lug disposed at intervals; end portions of the first shaft and the second shaft close to each other are connected to the first lug, end portions of the first shaft and the second shaft away from each other are connected to the second lug and the third lug, respectively, so as to keep the first lug between the second lug and the third lug.
4. The eyeglasses of claim 3, wherein the first wiring port is disposed on an end surface of the first shaft close to the second shaft; the second wiring port is disposed on a side wall of the first shaft close to the second lug; and the first shaft is rotatably connected to the first lug and fixedly connected to the second lug.
5. The eyeglasses of claim 4, wherein the first lug and the second lug are coaxially disposed with a first accommodating hole and a second accommodating hole; and sizes of the first accommodating hole and the second accommodating hole are disposed to allow the first shaft to be inserted into the first accommodating hole from outside of the eyeglass temple via the second accommodating hole and allow the first shaft in an interference fit with the second accommodating hole and in a clearance fit with the first accommodating hole.
6. The eyeglasses of claim 4, wherein the first lug and the third lug are coaxially disposed with a third accommodating hole and a fourth accommodating hole; and sizes of the third accommodating hole and the fourth accommodating hole are disposed to allow the second shaft to be inserted into the third accommodating hole from outside of the eyeglass temple via the fourth accommodating hole and allow the second shaft in an interference fit with the third accommodating hole and in a clearance fit with the fourth accommodating hole, or allow the second shaft in a clearance fit with the third accommodating hole and in an interference fit with the fourth accommodating hole.
7. The eyeglasses of claim 6, wherein the second shaft is a solid shaft; a diameter of the second shaft is less than a diameter of the first shaft; in a wearing state, the second shaft is located at an upper side of the eyeglass temple, and the first shaft is located at a lower side of the eyeglass temple; and a connection between the end surface of the first shaft for disposing the first wiring port and a surface of an inner wall of the first shaft for defining the shaft wiring channel is an arc shape.
8. The eyeglasses of claim 1, wherein the first microphone and the second microphone are disposed at different positions of a circuit board.

9. The eyeglasses of claim 8, wherein the circuit board at least comprises a number of first pads and a number of second pads; at least one of the number of first pads is electrically connected to an audio signal wire of a control circuit, the at least one first pad is electrically connected to at least one of the number of second pads via a first flexible lead on the circuit board, and the at least one second pad is electrically connected to the earphone core via an external wire; and at least another one of the number of first pads is electrically connected to an auxiliary signal wire of the control circuit, and the at least another one first pad is electrically connected to at least one of the first microphone and the second microphone via a second flexible lead on the circuit board.

10. The eyeglasses of claim 9, wherein the circuit board includes at least a main circuit board, a first branch circuit board, and a second branch circuit board; the first branch circuit board is connected to the main circuit board, away from the main circuit board, and extend along one end of the main circuit board; the second branch circuit board is connected to the main circuit board, away from the main circuit board, extends along the other end of the main circuit board, and is spaced apart from the first branch circuit board; the first microphone is disposed on the first branch circuit board; and the second microphone is disposed on the second branch circuit board.

11. The eyeglasses of claim 10, wherein the number of first pads are disposed on the main circuit board; the at least one second pad is disposed on the first branch circuit board; and other second pads of the number of second pads are disposed on the second branch circuit board.

12. The eyeglasses of claim 10, wherein the first branch circuit board extends in a same direction as the main circuit board, and the second branch circuit board extends perpendicular to the main circuit board.

13. The eyeglasses of claim 9, wherein the earphone core includes: a magnetic circuit component configured to provide a magnetic field; a vibration component, the vibration component comprising a coil and an inner lead, wherein the coil is located in the magnetic field, the inner lead is electrically connected to the coil, the coil receives an audio current via the inner lead and converts the audio current into a mechanical vibration signal under an action of the magnetic field, one end of the external wire is electrically connected to the second pad, and the other end of the external wire is electrically connected to the inner lead, and transmitting the audio current to the coil.

14. The eyeglasses of claim 13, wherein a wiring groove is disposed inside the core housing; and the external wire and/or the inner lead line are disposed inside the wiring groove.

15. The eyeglasses of claim 14, wherein the inner lead and the external wire are welded to each other, and a welding position is located inside the wiring groove.

16. The eyeglasses of claim 13, wherein a housing panel of the core housing and the earphone core are in a transmission connection, and all or part of the housing panel is used to contact or abut a user's body to conduct a sound generated by the vibration of the earphone core.

17. The eyeglasses of claim 16, wherein an axis of the coil or a magnetic circuit system is not parallel to a normal line of the housing panel; the axis is perpendicular to a radial plane of the coil and/or the magnetic circuit system.

18. The eyeglasses of claim 16, wherein the earphone core is configured to vibrate to generate a driving force to drive the housing panel of the speaker to vibrate, wherein when a straight line of the driving force has a positive direction pointing to an outside of the speaker from the housing panel and a normal line of the housing panel has a positive direction pointing to the outside of the speaker, an angle between the straight line and the normal line in the positive direction is an acute angle.

19. The eyeglasses of claim 16, wherein a driving force that is configured to drive the housing panel of the speaker to vibrate includes a component in a first quadrant or a third quadrant of an XOY plane coordinate system; wherein: an origin O of the XOY plane coordinate system is on a contact surface between the speaker and a human body, an X axis of the XOY plane coordinate system is parallel to a coronal axis of the human body, a Y axis of the XOY plane coordinate system is parallel to a sagittal axis of the human body, a positive direction of the X axis faces an

outside of the human body, and a positive direction of the Y axis faces a front of the human body.

20. The eyeglasses of claim 16, wherein a region of the housing panel configured to contact or abut the user's body comprises a flat surface or a quasi-flat surface.
