

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250248573

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Wolff; Vincent Andrew et al.

Evacuation Dock With Fluid Management

Abstract

A docking station for a mobile cleaning robot can include a canister and a base configured to receive the mobile cleaning robot thereon, where the base can include a front portion and a back portion opposite the front portion. The base can include a vacuum port extending at least partially through the base. The canister can be connected to the back portion of the base and can be located at least partially above the base. The canister can include a debris bin connected to the vacuum port to receive debris therefrom and a fan compartment connected to a side wall of the debris bin and including a fan system operable to draw debris through the vacuum port and the debris bin.

Inventors: Wolff; Vincent Andrew (Norfolk, MA), Doughty; Brian W. (Framingham, MA), Torrente; Leo (Somerville, MA), Gschrey; Travis (Billerica, MA), Zhang; Jack (Guangzhou, CN), Fox; Levi (Salem, MA), Neumann; Rogelio Manfred (Somerville, MA), Stephens; Celerick (Billerica, MA), Mahoney, JR.; James J. (Hyde Park, MA)

Applicant: iRobot Corporation (Bedford, MA)

Family ID: 80246865

Appl. No.: 19/178433

Filed: April 14, 2025

Related U.S. Application Data

parent US continuation 18602591 20240312 parent-grant-document US 12274412 child US 19178433

parent US continuation 17009856 20200902 parent-grant-document US 11930991 child US 18602591

parent WO continuation PCT/CN2020/109188 20200814 PENDING child US 17009856

Publication Classification

Int. Cl.: A47L9/14 (20060101); A47L9/28 (20060101)

U.S. Cl.:

CPC A47L9/149 (20130101); A47L9/1409 (20130101); A47L9/2873 (20130101);
A47L2201/024 (20130101)

Background/Summary

PRIORITY APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/602,591, filed Mar. 12, 2024, which application is a continuation of U.S. patent application Ser. No. 17/009,856, filed Sep. 2, 2020, issued on Mar. 19, 2024 as U.S. Pat. No. 11,930,991, which application claims the benefit of priority to International Patent Application Serial No. PCT/CN2020/109188, filed Aug. 14, 2020, the contents of which are hereby incorporated by reference in their entireties.

BACKGROUND

[0002] Autonomous mobile robots include autonomous mobile cleaning robots that can autonomously perform cleaning tasks within an environment, such as a home. Many kinds of cleaning robots are autonomous to some degree and in different ways. Some robots can interface with a docking station automatically. The docking station can perform maintenance on the robot such as charging of batteries of the robot and evacuation of debris from a debris bin of the robot.

SUMMARY

[0003] Some autonomous cleaning robots can interface with a docking station for charging of the robot and for evacuation of a debris bin from the robot where debris can be draw from the debris bin of the robot, through the dock and into a container of the dock. In some examples, the docking station can include a replaceable bag configured to receive and retain the debris.

[0004] In some conditions, mobile cleaning robots can encounter water during a cleaning mission or operation. In some cases, the robots can ingest water or liquid into the debris bin while collecting debris from the environment. Then, during evacuation of the debris bin, this water can be evacuated from the debris bin of the mobile cleaning robot into the evacuation station or tower, as a fan or vacuum system pulls the fluid and debris from the mobile robot. In some cases, the transfer of fluid from the mobile cleaning robot to the evacuation station by the vacuum system can cause the fluid to be sprayed within the docking station. If the fluid that enters the docking station is not managed, it can contact electronics within the evacuation station or the mobile robot, which can cause electrical issues.

[0005] This disclosure helps to address these issues by including a side-by-side docking station where a fan system is positioned to the side or adjacent to a debris bin of a canister of the dock. Such placement can help reduce compromising the fan system due to water ingestion while also helping to reduce a height of the canister. This disclosure further helps to address these issues by including bosses having an extended height and configured to receive fasteners that are epoxied to the bosses, which can help limit fluid from escaping the canister and can help direct fluid to a weep hole or drain port of the canister for controlled discharge or drainage of the fluid. Additional features discussed below can help to mitigate or control fluid that enters the canister.

[0006] The above discussion is intended to provide an overview of subject matter of the present patent application. It is not intended to provide an exclusive or exhaustive explanation of the

invention. The description below is included to provide further information about the present patent application.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

[0008] FIG. 1A illustrates an isometric view of a docking station for a mobile cleaning robot.

[0009] FIG. 1B illustrates a top isometric view of a portion of a docking station for a mobile cleaning robot.

[0010] FIG. 1C illustrates a top isometric view of a portion of a docking station for a mobile cleaning robot.

[0011] FIG. 2 illustrates a perspective view of a portion of a docking station for a mobile cleaning robot.

[0012] FIG. 3 illustrates a top perspective view of a portion of a docking station for a mobile cleaning robot.

[0013] FIG. 4 illustrates a perspective view of a fastener for a docking station for a mobile cleaning robot.

[0014] FIG. 5A illustrates an isometric of a portion of a fan housing for a docking station for a mobile cleaning robot.

[0015] FIG. 5B illustrates an isometric of a portion of a fan housing for a docking station for a mobile cleaning robot.

[0016] FIG. 6A illustrates a perspective view of a portion of a docking station for a mobile cleaning robot.

[0017] FIG. 6B illustrates a cross-sectional view of a portion of a docking station for a mobile cleaning robot.

[0018] FIG. 7A illustrates an isometric view of a portion of a docking station for a mobile cleaning robot.

[0019] FIG. 7B illustrates a cross-sectional view of a portion of a docking station for a mobile cleaning robot.

[0020] FIG. 8A illustrates an isometric view of a portion of a docking station for a mobile cleaning robot.

[0021] FIG. 8B illustrates an isometric view of a portion of a docking station for a mobile cleaning robot.

DETAILED DESCRIPTION

[0022] FIG. 1A illustrates an isometric view of a docking station **100** for a mobile cleaning robot **101**. FIG. 1B illustrates a top isometric view of a portion of the docking station **100**. FIGS. 1A and 1B are discussed together below.

[0023] The docking station **100** can include a canister **102** and a base **104**. The canister **102** can include an outer wall **106** and a lid **108** (as shown in FIG. 1A). The base **104** can include a platform **110** having a front portion **112** and a rear portion **114**. The base can also include tracks **116a** and **116b** and a vacuum port **118**. As shown in FIG. 1B, the canister **102** can include a debris bin **120**, a fan compartment **122**, and a side wall **124**. The debris bin **120** can include a bottom wall **126** (or floor), a bag support **128**, and a vacuum inlet **130**. The canister **102** can also include a fan system **132** including a fan housing **134**. FIG. 1A also shows widths **w1** and **w2** and orientation indicators Top, Bottom, Front, and Back.

[0024] The components of the docking station **100** can be rigid or semi-rigid components made of materials such as one or more of metals, plastics, foams, elastomers, ceramics, composites, combinations thereof, or the like. Materials of some components are discussed in further detail below. The mobile robot **101** can be a mobile cleaning robot including wheels, extractor, a debris bin, a controller, and various sensors. The robot **101** can be configured to perform autonomous cleaning missions or routines within an environment.

[0025] The base **104** can be a ramped member including the platform **110** and the tracks **116a** and **116b**, which can be configured to receive the mobile cleaning robot **101** thereon for maintenance, such as charging and emptying debris from the mobile cleaning robot. The tracks **116** can be configured to receive wheels of the robot **101** to guide the robot **101** onto the base **104** for charging and debris evacuation. The front portion **112** can be opposite the back portion **114**, which can connect to the canister **102**. The platform **110** and the tracks **116** can be sloped toward the front portion **112** to help allow the mobile robot **101** to dock on the station **100**.

[0026] When the robot **101** is positioned on the base **104**, such as when wheels of the robot **101** are in wheel wells of the tracks, the vacuum port **118** can be aligned with a vacuum outlet of the robot **101**. The vacuum port **118** can extend through the base **104** and can connect to the vacuum inlet of the debris bin **120**.

[0027] The canister **102** can be an upper portion of the docking station **100** connected to the rear portion **114** of the base **104** and can extend upward therefrom. The outer wall **106** of the canister **102** can have a shape of a substantially rectangular hollow prism with rounded corners where the outer wall **106** can define a top portion of the canister **102** that is open. The outer wall **106** can at least partially enclose the debris bin **120** and the fan compartment **122**. A top portion of the canister **102** can have a width w_1 that is about the same, or substantially the same, as a width w_2 of the back portion **114** of the base **104**, which can help to reduce a height of the docking station, which can allow the docking station to be positioned under furniture having a lower clearance.

[0028] The lid **108** can be connected to the outer wall **106** (such as by hinges or other fasteners), such as at a rear portion of the lid **108**. The lid **108** can be releasably securable to the outer wall **106**, such as at a front portion of the lid **108** and the outer wall **106** (such as via a friction/interference fit, latch, or the like). Removal of the lid **108** or opening of the lid **108** from the top portion of the canister **102** can provide access to both the fan compartment **122** and the debris bin **120**.

[0029] The fan compartment **122** can be formed at least in part by the outer wall **106** and the side wall **124**. The side wall **124** can be a substantially vertical wall extending between the floor **126** and the lid **108**. The fan compartment **122** can be connected to the debris bin **120** by the side wall **124** such that the fan compartment **122** is adjacent to the debris bin **120** and such that the fan compartment **122** is offset from a central axis of the base **104** (as is the debris bin **120**). The fan compartment **122** can support the fan system **132** therein, which can be pneumatically connected to the debris bin **120** via a fan port **136** extending through the side wall **124**. That is, air can flow from the debris bin **120** through the fan port **136** and into the fan compartment **122**, as motivated by the fan system **132**. The fan system **132** can include the fan housing **134**, which can contain the fan (such as an impeller and a motor of the fan system **132**).

[0030] The bottom wall **126** (or floor) of the debris bin, the outer wall **106**, and the side wall **124** can together define a volume of the debris bin **120**. The lid **108** can also define the volume when the lid **108** is secured to the canister **102**. The bag support **128** can be connected to the floor **126** and the outer wall **106** and can be configured to support a vacuum bag within the debris bin **120** where the bag can be pneumatically connected to the vacuum inlet **130** to connect the bag to the vacuum port **118** (and to the mobile robot **101** when the mobile robot **101** is in a docked position).

[0031] FIG. 1C illustrates a top isometric view of a portion of the docking station **100** for the mobile cleaning robot **101**. The docking station **100** can be consistent with the docking station **100** shown in FIGS. 1A and 1B; FIG. 1C shows the docking station **100** with a front panel of the base

removed and the outer wall **106** of the canister **102** removed.

[0032] FIG. **1C** shows that the fan system **132** can include an impeller **138** and a motor **140** within the fan housing **134**. The motor **140** can be operable to motivate or drive the impeller **138** to move air such as from the inlet port **118** through a vacuum duct **142** of the base **104** and the canister **102** through the vacuum inlet **130** and into a bag in the debris bin **120**. The air can then be drawn through the bag and through the fan port **136** and into the fan housing **134** and can be discharged or ejected through the outer wall **106**.

[0033] FIG. **1C** also shows a circuit board **144** that can be connected to the base **104**, such as the rear portion **114** of the base **104**. The circuit board **144** can connect to electrical components within the canister **102**, such as a bag sensor, the motor **140**, etc. Because the circuit board **144** is positioned below the canister **102** it is important to divert fluid or liquid (such as water) that enters the canister **102** away from the circuit board **144** and other sensitive electronics of the docking station **100** or the robot **101**. Components and methods for controlling water or fluid entrainment are discussed in further detail below.

[0034] FIG. **2** illustrates a perspective view of a portion of the docking station **100**. More specifically, FIG. **2** shows a portion of the floor **126** of the debris bin **120** where the floor **126** can include a bore **146** for receiving a wiring harness **148** therethrough. The wiring harness **148** can be connectable to a bag presence sensor, for example, and the circuit board **144** within the base **104**, as shown in FIG. **1C**. The wiring harness **148** can include leads **150** and **152** which can be conduits including wires.

[0035] FIG. **2** also shows a grommet **154**, which can surround the leads **150** and **152** of the wiring harness **148** and can be positioned within the bore **146** to help seal the bore **156**. The grommet **154** can be overmolded to the leads **150** and **152**, which can form a seal between the leads **150** and **152** and the grommet **154**. The grommet **154** can thereby help to seal the bore **146** to help limit water or fluid from escaping the canister **102**, which can help to protect electrical components (such as the circuit board **144**) from fluids and therefore from short circuiting. In some examples, the grommet **154** can be overmolded to a wiring harness of the fan motor **140** to seal a bore of the fan compartment.

[0036] FIG. **3** illustrates a top perspective view of the canister **102** of the docking station **100**, which shows the debris bin **120** and the fan compartment **122** with the side wall and fan system removed. FIG. **3** also shows the bore **146** extending through the debris bin **120** and shows a fan harness bore **156** extending through the fan compartment **122**. The grommet **154** can be used to seal the fan harness bore **156** and a wiring harness extending therethrough.

[0037] FIG. **3** also shows bosses **158**, **160**, and **162** along with other unnumbered bosses. Each boss can extend up from the floor **126** and can include a bore **164** extending through the boss (such as the boss **160**) and the floor **126**. The bore **164** of the boss **162** can be configured to receive a fastener to secure the debris bin **120** to the base **104**. The bore **164** of the boss **160** can be configured to receive a fastener to secure the fan housing **134** to the boss **160** and optionally to the base **104**.

[0038] Each boss can have a height H , as shown with respect to the boss **158**. The bosses can have such a height to help contain water within the canister **102** and to help prevent liquid from escaping through the bores of the bosses, where the bosses can help allow time for the liquid or fluid to evacuate through a weep hole **159** or drain of the canister **102**. In some examples, one or more of the bosses can have a height H between **10** millimeters and **15** millimeters. For example, the height H of each boss can be **10**, **11**, **12**, **13**, **14**, **15**, **16**, or the like millimeters.

[0039] The weep hole **159** can be a small bore extending through the floor **126** or the outer wall **106** to connect a volume of the debris bin **120** (and optionally the fan compartment **122**) with a surrounding environment. The weep hole **159** can be sized to allow fluid to drain without causing an impact on the pneumatic action of drawing debris from the robot (such as the robot **101**) through the debris bin **120** using the fan system **132**. In some examples, the weep hole **159** can have a

diameter of between 2 millimeters and 4 millimeters, such as 3 millimeters. In some examples, the weep hole can include a fluid trap (such as a P-trap or J-trap) to help maintain vacuum pressure within the debris bin **120** during operation of the fan system **132**. In some examples, more than one weep hole can be included in the canister **102**.

[0040] FIG. **4** illustrates a perspective view of a fastener **163** (which can be a screw, nail, rivet, or the like) for a docking station for a mobile cleaning robot. FIG. **4** also shows the boss **160** and the fan housing **134** in a cross-sectional view. The fan housing **134** can include a bore **166** extending therethrough, which can be configured to receive a shank **170** of the fastener therethrough. The shank **170** of the fastener can be threadably secured the bore **164** of the boss (or to a nut or other female fastener) to secure the fan housing **134** to the boss **160** and therefore to the canister **102**.

[0041] The fastener can include a head **168** connected to the shank **170** via a tapered portion **172**. In some examples, a resin **174** can be applied to the head **168**, such as to the tapered portion **172**, and the resin **174** can be cured or polymerized to adhere to the tapered portion **172** and the fan housing **134** or the boss **160**. This assembly can help to seal the bore **164** to help prevent liquid from escaping the debris bin **120** (and the canister **102**), which can help protect electronic components of the base **104** and the robot **101**.

[0042] The resin **174** can be any suitable resin, such as one or more resins chosen from an epoxy resin, an acrylic resin, an acrylate resin, a cyanoacrylate resin, cyano-urethane resin, a polysiloxane resin, a mixture thereof, or the like. The resin **174** can be cured using a thermal curing process, an ultraviolet light curing process, or the like.

[0043] FIG. **5A** illustrates an isometric of a portion of the fan housing **134** for a docking station for a mobile cleaning robot. FIG. **5B** illustrates an isometric of a portion of the fan housing **134** of the docking station **100** for a mobile cleaning robot. FIGS. **5A** and **5B** are discussed together below.

[0044] FIG. **5A** shows a lower portion **134a** of the fan housing **134**, which can include a plate **176** including bosses **166** and a wall **178**. The wall **178** can include a top portion including an outer lap portion **182**.

[0045] The plate **176** can extend outward from the wall **178** and can be configured to secure the fan housing **134** to the canister **102**, such as described with respect to FIGS. **3** and **4** above. The wall **178** can define at least a portion of a housing for the impeller **138** and the motor **140** of the fan system **132**. The wall **178** can have a substantially cylindrical shape that can terminate at the top portion **180**. The outer lap portion **182** can extend upward or vertically from a radially outer portion of the top portion **180** of the wall **178** to at least partially surround a portion of the upper portion **134b** and to form at least a part of the lap seal or lap joint **188** with the upper portion **134b** of the fan housing **134**, as shown in FIG. **5B**.

[0046] That is, FIG. **5B** shows how the top portion **180** can receive a bottom portion **186** of a wall **184** of the upper portion **134b** of the fan housing **134**. FIG. **5B** also shows how the lap portion **182** can extend radially beyond the wall **184** of the upper portion **134b** of the fan housing **134** and shows how the lap portion **182** can extend axially beyond the bottom portion **186** of the wall **184** of the upper portion **134b**. This arrangement can form the lap seal (or lap joint) **188** between the lower portion **134a** and the upper portion **134b** of the fan housing **134**, which can help limit liquid from entering the fan housing **134**. Though FIGS. **5A** and **5B** show the lap as extending from the lower portion **134a**, the upper portion **134b** can include a lapping portion.

[0047] FIG. **5B** also shows a wiring harness **190** of the fan system **132**, which can extend through the canister **102** through a grommet **192**, which can be similar to the grommet **154** discussed above with respect to FIG. **3**. Such a grommet **192** can help prevent liquid from escaping the canister **102** into the base **104** of the docking station **100**.

[0048] FIG. **6A** illustrates a perspective view of a portion of the docking station **100** for a mobile cleaning robot. FIG. **6B** illustrates a cross-sectional view of the portion of a docking station **100** for a mobile cleaning robot. FIGS. **6A** and **6B** are discussed together below. The docking station **100** of FIGS. **6A** and **6B** can be consistent with the docking station **100** discussed above; FIGS. **6A** and **6B**

show additional details of the docking station. For example, FIGS. 6A and 6B show discharge openings **194a-194n** through the outer wall **106** of the fan compartment **122**.

[0049] The discharge openings **194a-194n** can extend through the outer wall **106** and can be spaced apart from each other. The discharge openings **194a-194n** can be positioned near the fan system **132** and can be configured to discharge air from the fan system **132** to a surrounding environment (such as a room in a house). The discharge openings **194a-194n** can be slots as shown in FIG. 6A, but can be channels, bores, or the like.

[0050] As shown in FIG. 6B, the discharge openings **194a-194n** can be angled downward, such as at an angle θ . The angle θ can be between 10 degrees and 80 degrees downward from a horizontal plane. The angle θ can be between 35 degrees and 55 degrees in some examples. The angle θ can be about 45 degrees in some examples.

[0051] During evacuation operations of the robot, fluid can be drawn from the bin of the mobile robot through the debris bin **120** by the fan system **132**, as discussed in detail above. The fluid can be discharge from the fan housing **134** by the impeller **138** and can ultimately be discharged through from the fan compartment **122** through the outer wall **106** by traveling through the discharge openings **194a-194n**. Because the discharge openings **194a-194n** are angled downward, the discharge openings **194a-194n** can help to direct air and fluid towards a floor of the environment. This can help to limit fluid spray on surrounding walls or other items in the environment.

[0052] FIG. 7A illustrates an isometric view of the base **104** of the docking station **100** for a mobile cleaning robot. FIG. 7B illustrates a cross-sectional view of the base **104** and the canister **102** of the docking station **100** for a mobile cleaning robot. FIGS. 7A and 7B are discussed together below.

[0053] The docking station **100** of FIGS. 7A and 7B can be consistent with the docking station **100** discussed above; FIGS. 7A and 7B show additional details of the docking station **100**. For example, FIG. 7A shows that the base **104** can include a front panel **196** (including a top portion **197**) connected to the back portion **114** and extending upward from the platform **110** and shows that the base **104** can include a back panel **198** (including a top portion **199**) connected to the back portion **114** and extending upward from the platform **110**. The front panel **196** and the back panel **198** can be connected to each other such that the top portions **197** and **199** can align or can be planar.

[0054] The front panel **196** can include a lip or projection **200a** extending from the top portion **197**. Similarly, the back or rear panel **198** can include a lip or projection **200b** extending from the top portion **199**. The lips **200a** and **200b** can be in alignment where they meet to form a substantially continuous lip around the top portions **197** and **199** of the panels **196** and **198**. In some examples, the lips **200** can be on an inner portion of the top portions **197** and **199**.

[0055] As shown in FIG. 7B, the floor **126** of the canister **102** can include a recess **202** extending upward from the floor **126**. The recess **202** can be positioned inside the outer wall **106**. The recess **202** can extend around at least a portion of a periphery of a bottom portion of the canister. The recess **202** can be sized and shaped to receive the lip **200** of the top portions **197** and **199** to form a lap joint **203** between the canister **102** and the base **104**. That is, the front lip **200a** can be inserted at least partially within the recess **202** and the back lip **200b** can be inserted at least partially into the recess **202** to form the lap joint **203**.

[0056] The canister **102** can extend outward of the front panel **196** and the back panel **198**, as shown in FIG. 7B. By extending outward of the panels and forming the lap joint **203**, the panels **196** and **198** and the canister **102** can help prevent water or liquid from entering the base **104** during intake of liquid from the robot or discharge of liquid from the fan system **132**.

[0057] FIG. 8A illustrates an isometric view of a portion of a docking station **800** for a mobile cleaning robot. FIG. 8B illustrates an isometric view of a portion of the docking station **800** for a mobile cleaning robot. FIGS. 8A and 8B are discussed together below. The docking station **800** can include a compartment for storing one or more bag refills or spare bags. Any of the previously discussed docking stations can be modified to include such a compartment.

[0058] FIG. 8A shows the docking station **800** and a mobile cleaning robot **801** where a user **50** is operating a tab **809** of a lid **808** of a canister **802** of the docking station **800**. As shown in FIG. 8B, the lid **808** can be attached to the outer wall **806** of the canister **802** by hinges, which can allow the lid **808** to pivot or rotate upward when the user **50** operates (lifts the tab **809**). As shown in FIG. 8A, opening the lid **808** can expose the debris bin **820** and the fan compartment **822**. FIG. 8B shows that a vacuum bag **817** can be connected to the vacuum system (such as to the inlet **130**) within the debris bin **820**.

[0059] The fan compartment **822** can be covered by a storage compartment **813**. The storage compartment **813** can include a wall **815** at a bottom portion of the storage compartment **813** that can cover or substantially cover a fan system (such as the fan system **132**) located within the fan compartment **822**. The storage compartment can be configured to store one or more spare bags **819** therein. When the user **50** removes the vacuum bag **817** (such as when the bag **817** is full or in need of replacement), the user **50** can retrieve the spare bag **819** from the storage compartment **813** and install it within the debris bin **820** before shutting the lid. The **813** compartment can thereby reduce a time required to replace the bag **817**.

NOTES AND EXAMPLES

[0060] The following, non-limiting examples, detail certain aspects of the present subject matter to solve the challenges and provide the benefits discussed herein, among others.

[0061] Example 1 is a docking station for a mobile cleaning robot, the docking station comprising: a base configured to receive the mobile cleaning robot thereon, the base including a front portion and a back portion opposite the front portion; a vacuum port extending at least partially through the base; and a canister connected to the back portion of the base and located at least partially above the base, the canister comprising: a debris bin connected to the vacuum port to receive debris therefrom, the debris bin including a side wall and a floor connected to the side wall, the side wall and the floor together at least partially enclosing the debris bin; and a fan compartment connected to the side wall of the debris bin and including a fan system operable to draw debris through the vacuum port and the debris bin.

[0062] In Example 2, the subject matter of Example 1 optionally includes wherein the fan compartment includes a plurality of discharge openings extending downward through the fan compartment and configured to discharge air from the fan system in a downward direction.

[0063] In Example 3, the subject matter of Example 2 optionally includes wherein the plurality of discharge openings are angled downward between 35 and 55 degrees.

[0064] In Example 4, the subject matter of any one or more of Examples 1-3 optionally include wherein the fan base includes a front panel connected to and extending upward from the back portion of the base and includes a back panel connected to the back portion and connected to the front panel, the back panel extending upward from the back portion of the base, and wherein the canister is connected to the back panel and the front panel at least in part by a lap joint.

[0065] In Example 5, the subject matter of Example 4 optionally includes wherein the canister includes a recess extending around at least a portion of a periphery of a bottom portion of the canister.

[0066] In Example 6, the subject matter of Example 5 optionally includes wherein the front panel includes a front lip extending around at least a portion of a periphery of a top portion of the front panel, wherein the back panel includes a back lip extending around at least a portion of a periphery of a top portion of the back panel, and wherein the lap joint is formed at least in part by the front lip, the back lip, and the recess.

[0067] In Example 7, the subject matter of any one or more of Examples 1-6 optionally include wherein the debris bin includes a boss extending up from the floor, the boss including a bore extending through the boss and the floor, the bore configured to receive a fastener to secure the debris bin to the base.

[0068] In Example 8, the subject matter of Example 7 optionally includes wherein the fastener is

secured to the boss using a resin.

[0069] In Example 9, the subject matter of Example 8 optionally includes wherein the fastener is a screw and the resin is cured or polymerized using ultraviolet light.

[0070] In Example 10, the subject matter of Example 9 optionally includes wherein the boss has a height between 10 millimeters and 15 millimeters.

[0071] In Example 11, the subject matter of any one or more of Examples 1-10 optionally include wherein a top portion of the canister has a width that is substantially the same as a width of the back portion of the base.

[0072] In Example 12, the subject matter of any one or more of Examples 1-11 optionally include wherein removal of a lid from a top of the canister provides access to both the fan compartment and the debris bin.

[0073] In Example 13, the subject matter of Example 12 optionally includes wherein the side wall is a vertical wall that separates the fan compartment and the debris bin.

[0074] In Example 14, the subject matter of any one or more of Examples 12-13 optionally include wherein the fan compartment is offset from a central axis of the base.

[0075] In Example 15, the subject matter of any one or more of Examples 1-14 optionally include a fan compartment wall located in the fan compartment and above the fan system, the fan compartment wall configured to receive a spare vacuum bag and store the spare vacuum bag between the fan compartment wall and a lid connected to the top of the canister when the lid is closed.

[0076] Example 16 is a docking station for a mobile cleaning robot, the docking station comprising: a base configured to receive the mobile cleaning robot thereon, the base including a front portion and a back portion opposite the front portion; a vacuum port extending at least partially through the base; a debris bin connected to the back portion of the base and connected to the vacuum port to receive debris therefrom, the debris bin comprising: a side wall and a floor connected to the side wall, the side wall and the floor together at least partially enclosing the debris bin; and a boss extending up from the floor, the boss including a bore extending through the boss and the floor, the bore configured to receive a fastener to secure the debris bin to the base; a fan compartment connected to the back portion of the base and connected to the side wall of the debris bin; and a fan system located within the fan compartment, the fan system operable to draw debris from the vacuum port through the debris bin.

[0077] In Example 17, the subject matter of Example 16 optionally includes wherein the fastener is secured to the boss using a resin.

[0078] In Example 18, the subject matter of Example 17 optionally includes wherein the fastener is a screw and the resin is cured or polymerized using ultraviolet light.

[0079] In Example 19, the subject matter of Example 18 optionally includes wherein the boss has a height between 10 millimeters and 15 millimeters.

[0080] In Example 20, the subject matter of Example 19 optionally includes wherein debris bin includes a plurality of bosses including the boss, each of the plurality of bosses extending up from the floor.

[0081] In Example 21, the subject matter of any one or more of Examples 16-20 optionally include a bin wiring harness extending through a bin bore of the side wall; and a bin grommet overmolded to the bin wiring harness and located within the bin bore to at least partially seal the bin bore.

[0082] In Example 22, the subject matter of Example 21 optionally includes a fan wiring harness extending through a compartment bore of the fan compartment; and a fan grommet overmolded to the fan wiring harness and located within the compartment bore to at least partially seal the compartment bore.

[0083] In Example 23, the subject matter of any one or more of Examples 16-22 optionally include a weep hole extending through one or more of the side wall and the floor, the weep hole connecting a volume of the bin to a surrounding environment.

[0084] In Example 24, the subject matter of Example 23 optionally includes wherein the weep hole has a diameter between 2 millimeters and 4 millimeters.

[0085] Example 25 is a docking station for a mobile cleaning robot, the docking station comprising: a base configured to receive the mobile cleaning robot thereon, the base including a front portion and a back portion opposite the front portion; a vacuum port extending at least partially through the base; a debris bin connected to the back portion of the base and connected to the vacuum port to receive debris therefrom, the debris bin including a debris bin compartment at least partially enclosing the debris bin; a fan compartment connected to the back portion of the base and connected to the debris bin; and a fan system located within the fan compartment, the fan system comprising: a fan assembly operable to draw debris from the vacuum port through the debris bin; and a fan housing containing the fan assembly, the fan housing comprising: a first portion; and a second portion connected to the first portion by a lap joint.

[0086] In Example 26, the subject matter of Example 25 optionally includes wherein the first portion is an upper portion of the fan housing and wherein the second portion is a lower portion of the fan housing.

[0087] In Example 27, the subject matter of Example 26 optionally includes wherein the lower portion forms an outer portion of the lap joint.

[0088] In Example 28, the subject matter of Example 27 optionally includes wherein the outer portion of the lap joint extends vertically to at least partially surround a portion of the upper portion of the fan housing.

[0089] In Example 29, the subject matter of any one or more of Examples 25-28 optionally include wherein the fan assembly includes an impeller and a motor operable to drive the impeller.

[0090] In Example 30, the subject matter of any one or more of Examples 25-29 optionally include wherein the fan housing includes a plurality of discharge openings extending downward through the fan housing configured to discharge air from the fan assembly in a downward direction.

[0091] In Example 31, the subject matter of Example 30 optionally includes degrees wherein the plurality of discharge openings are angled downward between 35 and 55 degrees.

[0092] Example 32 is a docking station for a mobile cleaning robot, the docking station comprising: a base configured to receive the mobile cleaning robot thereon, the base comprising: a front portion and a back portion opposite the front portion; a front panel connected to the back portion and extending upward from the back portion; and a back panel connected to the back portion and connected to the front panel, the back panel extending upward from the back portion; a vacuum port extending at least partially through the base; and a canister connected to the back panel and the front panel at least in part by a lap joint, the canister comprising: a debris bin connected to the vacuum port to receive debris therefrom; and a fan compartment connected to the debris bin and including a fan system therein.

[0093] In Example 33, the subject matter of Example 32 optionally includes wherein the canister includes a recess extending around at least a portion of a periphery of a bottom portion of the canister.

[0094] In Example 34, the subject matter of Example 33 optionally includes wherein the front panel includes a front lip extending around at least a portion of a periphery of a top portion of the front panel, and the back panel includes a back lip extending around at least a portion of a periphery of a top portion of the back panel, and wherein the lap joint is formed at least in part by the front lip, the back lip, and the recess.

[0095] In Example 35, the subject matter of Example 34 optionally includes wherein the front lip is inserted at least partially within the recess and the back lip is inserted at least partially into the recess to form the lap joint.

[0096] In Example 36, the subject matter of any one or more of Examples 32-35 optionally include wherein the lap joint extends around an entirety of a periphery of the canister.

[0097] In Example 37, the apparatuses or method of any one or any combination of Examples 1-36

can optionally be configured such that all elements or options recited are available to use or select from.

[0098] The above detailed description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the invention can be practiced. These embodiments are also referred to herein as “examples.” Such examples can include elements in addition to those shown or described. However, the present inventors also contemplate examples in which only those elements shown or described are provided. Moreover, the present inventors also contemplate examples using any combination or permutation of those elements shown or described (or one or more aspects thereof), either with respect to a particular example (or one or more aspects thereof), or with respect to other examples (or one or more aspects thereof) shown or described herein.

[0099] In the event of inconsistent usages between this document and any documents so incorporated by reference, the usage in this document controls.

[0100] In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended, that is, a system, device, article, composition, formulation, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

[0101] The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more aspects thereof) may be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing the above description. The Abstract is provided to comply with 37 C.F.R. § 1.72 (b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. Also, in the above Detailed Description, various features may be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter may lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description as examples or embodiments, with each claim standing on its own as a separate embodiment, and it is contemplated that such embodiments can be combined with each other in various combinations or permutations. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

Claims

1. (canceled)

2. A docking station for a mobile cleaning robot, the docking station comprising: a base configured to receive the mobile cleaning robot thereon, the base comprising a front portion and a back portion opposite the front portion; a vacuum port extending at least partially through the base; a canister connected to the back portion of the base and located at least partially above the base, the canister comprising: a debris bin connected to the vacuum port to receive debris therefrom, the debris bin including a floor and a wall; a weep hole extending through the floor and the canister; and a fan compartment separated from the debris bin by the wall, the fan compartment including a discharge;

a fan system operable to generate air flow to draw debris through the vacuum port and the debris bin, the fan system configured to discharge the air flow through the discharge; and a lid configured to open from a top portion of the canister to provide access to both the fan compartment and the debris bin.

3. The docking station of claim 2, wherein the weep hole is sized to allow fluid to drain from the debris bin without impacting pneumatic action of drawing debris from the mobile cleaning robot through the debris bin using the fan system.
4. The docking station of claim 3, wherein the weep hole has a diameter between 2 millimeters and 4 millimeters.
5. The docking station of claim 3, wherein the weep hole has a diameter of 3 millimeters.
6. The docking station of claim 3, wherein the weep hole includes a fluid trap.
7. The docking station of claim 3, wherein the debris bin includes a boss extending up from the floor, the boss including a bore extending through the boss and the floor, the bore configured to receive a fastener to secure the debris bin to the base.
8. The docking station of claim 7, wherein the fastener is threadably secured to the boss.
9. The docking station of claim 7, wherein the fastener includes a tapered portion engageable with the boss, and wherein the tapered portion is secured to the boss using a resin.
10. The docking station of claim 3, wherein the canister includes an outer wall at least partially defining the debris bin and the fan compartment.
11. The docking station of claim 2, wherein the fan compartment is offset from a central axis of the base.
12. A docking station for a mobile cleaning robot, the docking station comprising: a base configured to receive the mobile cleaning robot thereon, the base comprising a front portion and a back portion opposite the front portion; a vacuum port extending at least partially through the base; a canister connected to the back portion of the base and located at least partially above the base, the canister comprising: a debris bin connected to the vacuum port to receive debris therefrom, the debris bin including a floor and a wall; and a fan compartment separated from the debris bin by the wall, the fan compartment including a discharge; a fan system located at least partially in the fan compartment, the fan system including: a fan operable to generate air flow to draw debris through the vacuum port and the debris bin, the fan configured to discharge the air flow through the discharge; a motor operable to drive the fan to rotate; a fan housing at least partially surrounding the fan; and a plate connected to the fan housing and the fan compartment to secure the fan system to the fan compartment; and a lid configured to open from a top portion of the canister to provide access to both the fan compartment and the debris bin.
13. The docking station of claim 12, wherein the fan housing includes an annular wall and wherein the plate is connected to the annular wall.
14. The docking station of claim 13, wherein the fan housing includes an upper wall forming a lap joint with at least a portion of the annular wall to form a seal between the upper wall and the annular wall.
15. The docking station of claim 12, wherein the debris bin includes a boss extending up from the floor, the boss including a bore extending through the boss and the floor, the bore configured to receive a fastener to threadably secure the debris bin to the base.
16. The docking station of claim 15, wherein the fastener includes a tapered portion engageable with the boss, and wherein the tapered portion is secured to the boss using a resin.
17. The docking station of claim 12, comprising: a weep hole extending through the floor and the canister.
18. The docking station of claim 17, wherein the weep hole is sized to allow fluid to drain from the debris bin without impacting pneumatic action of drawing debris from the mobile cleaning robot through the debris bin using the fan system.
19. The docking station of claim 18, wherein the weep hole has a diameter between 2 millimeters

and 4 millimeters.

20. The docking station of claim 18, wherein the weep hole has a diameter of 3 millimeters.

21. The docking station of claim 20, wherein the canister includes an outer wall at least partially defining the debris bin and the fan compartment.
