

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12388895
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Katyal; Dinesh et al.

---

### Multiple server automation for secure cloud reconciliation

---

#### Abstract

In various example embodiments, a system and method for automated data reconciliation processing is presented. The system receives a data movement request with a first status indicator and appends a unique request code to the data movement request. The system causes presentation of the data movement request at a client device and receives a movement response from a second server via a network. The system modifies the first status indicator of the data movement request to a second status indicator to provisionally reflect the receipt of the movement response and verifies the indication of movement from a receiving entity.

---

<b>Inventors:</b>	<b>Katyal; Dinesh (Fremont, CA), Vickers; Matthew John (Wellington, NZ)</b>
<b>Applicant:</b>	<b>Xero Limited (Wellington, NZ)</b>
<b>Family ID:</b>	<b>1000008749496</b>
<b>Assignee:</b>	<b>Xero Limited (Te Aro Wellington, NZ)</b>
<b>Appl. No.:</b>	<b>18/431127</b>
<b>Filed:</b>	<b>February 02, 2024</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240214451 A1	Jun. 27, 2024

#### Related U.S. Application Data

continuation parent-doc US 17808962 20220624 US 11936729 child-doc US 18431127  
continuation parent-doc US 16055926 20180806 US 11399062 child-doc US 17808962  
continuation parent-doc US 15446947 20170301 US 10069917 child-doc US 16055926  
continuation parent-doc US 15011055 20160129 US 9591066 child-doc US 15446947

---

## Publication Classification

**Int. Cl.:** H04L67/1097 (20220101); G06Q20/10 (20120101); G06Q20/40 (20120101);  
H04L67/06 (20220101); H04L67/10 (20220101); H04L67/1095 (20220101);  
H04L67/53 (20220101); H04L67/60 (20220101)

**U.S. Cl.:**

**CPC** H04L67/1097 (20130101); G06Q20/10 (20130101); G06Q20/405 (20130101);  
H04L67/06 (20130101); H04L67/10 (20130101); H04L67/1095 (20130101);  
H04L67/53 (20220501); H04L67/60 (20220501);

## Field of Classification Search

**CPC:** G06Q (20/06); G06Q (20/405); H04L (67/10); H04L (47/783); H04L (63/0892); H04L  
(12/14); G06F (16/24); G06F (16/182); G06F (9/466); G06F (9/4806)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6707915	12/2003	Jobst et al.	N/A	N/A
9591066	12/2016	Katyal et al.	N/A	N/A
10069917	12/2017	Katyal	N/A	N/A
10963868	12/2020	McCauley et al.	N/A	N/A
11399062	12/2021	Katyal et al.	N/A	N/A
2003/0158811	12/2002	Sanders et al.	N/A	N/A
2005/0131813	12/2004	Gallagher et al.	N/A	N/A
2006/0251073	12/2005	Lepel et al.	N/A	N/A
2006/0294005	12/2005	Drepak	N/A	N/A
2007/0061258	12/2006	Neofytides et al.	N/A	N/A
2007/0143398	12/2006	Graham	N/A	N/A
2007/0150411	12/2006	Addepalli et al.	N/A	N/A
2007/0198432	12/2006	Pitroda et al.	N/A	N/A
2007/0255662	12/2006	Tumminaro	N/A	N/A
2008/0021821	12/2007	Katyal et al.	N/A	N/A
2008/0103923	12/2007	Rieck et al.	N/A	N/A
2009/0089194	12/2008	Mathis	705/34	G06Q 20/10
2009/0187980	12/2008	Tung	N/A	N/A
2009/0319421	12/2008	Mathis et al.	N/A	N/A
2011/0184910	12/2010	Love et al.	N/A	N/A
2011/0238483	12/2010	Yoo et al.	N/A	N/A
2012/0054105	12/2011	Seo et al.	N/A	N/A
2012/0116963	12/2011	Klein et al.	N/A	N/A
2013/0006811	12/2012	Mascavage, III et al.	N/A	N/A
2013/0060679	12/2012	Oskolkov et al.	N/A	N/A
2013/0212010	12/2012	Mullen et al.	N/A	N/A
2014/0114825	12/2013	Krikorian et al.	N/A	N/A

2014/0114852	12/2013	Rajagopal et al.	N/A	N/A
2014/0188728	12/2013	Dheer et al.	N/A	N/A
2015/0012426	12/2014	Purves et al.	N/A	N/A
2015/0134699	12/2014	Bhide et al.	N/A	N/A
2015/0379519	12/2014	Schultz	705/345	H04L 67/02
2016/0078448	12/2015	Dorsey et al.	N/A	N/A
2016/0086151	12/2015	Xia et al.	N/A	N/A
2016/0132884	12/2015	Fridman et al.	N/A	N/A
2016/0217258	12/2015	Pitroda et al.	N/A	N/A
2017/0193487	12/2016	Summers	N/A	N/A
2017/0223106	12/2016	Katyal et al.	N/A	N/A
2019/0014177	12/2018	Katyal et al.	N/A	N/A
2022/0400153	12/2021	Katyal et al.	N/A	N/A
2022/0400154	12/2021	Katyal et al.	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
2016379813	12/2017	AU	N/A
103023640	12/2012	CN	N/A
104364792	12/2014	CN	N/A
104683222	12/2014	CN	N/A
108781222	12/2017	CN	N/A
2003044910	12/2002	JP	N/A
2006293500	12/2005	JP	N/A
2012517060	12/2011	JP	N/A
2017091302	12/2016	JP	N/A
2018514874	12/2017	JP	N/A
WO-2017131797	12/2016	WO	N/A

#### **OTHER PUBLICATIONS**

U.S. Appl. No. 15/011,055 U.S. Pat. No. 9,591,066, filed Jan. 29, 2016, Multiple Server Automation for Secure Cloud Reconciliation. cited by applicant

U.S. Appl. No. 15/446,947 U.S. Pat. No. 10,069,917, filed Mar. 1, 2017, Multiple Server Automation for Secure Cloud Reconciliation. cited by applicant

U.S. Appl. No. 16/055,926 U.S. Pat. No. 11,399,062, filed Aug. 6, 2018, Multiple Server Automation for Secure Cloud Reconciliation. cited by applicant

U.S. Appl. No. 17/808,962, filed Jun. 24, 2022, Multiple Server Automation for Secure Cloud Reconciliation. cited by applicant

U.S. Appl. No. 17/808,963, filed Jun. 24, 2022, Multiple Server Automation for Secure Cloud Reconciliation. cited by applicant

“U.S. Appl. No. 15/011,055, Non Final Office Action mailed Jun. 17, 2016”, 16 pgs. cited by applicant

“U.S. Appl. No. 15/011,055, Notice of Allowance mailed Oct. 25, 2016”, 8 pgs. cited by applicant

“U.S. Appl. No. 15/011,055, Response filed Sep. 19, 2016 to Non Final Office Action mailed Jun. 17, 2016”, 22 pgs. cited by applicant

“U.S. Appl. No. 15/446,947, Advisory Action mailed Feb. 23, 2018”, 3 pgs. cited by applicant

“U.S. Appl. No. 15/446,947, Examiner Interview Summary mailed Mar. 28, 2018”, 3 pgs. cited by applicant

“U.S. Appl. No. 15/446,947, Final Office Action mailed Nov. 30, 2017”, 15 pgs. cited by applicant

“U.S. Appl. No. 15/446,947, Non Final Office Action mailed May 19, 2017”, 18 pgs. cited by

applicant

“U.S. Appl. No. 15/446,947, Notice of Allowance mailed Jul. 12, 2018”, 8 pgs. cited by applicant

“U.S. Appl. No. 15/446,947, Response filed Jan. 17, 2018 to Final Office Action mailed Nov. 30, 2017”, 16 pgs. cited by applicant

“U.S. Appl. No. 15/446,947, Response filed Aug. 17, 2017 to Non Final Office Action mailed May 19, 2017”, 22 pgs. cited by applicant

“U.S. Appl. No. 15/446,947 Appeal Brief Filed May 3, 2018.pdf”, 26 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Appeal Brief filed Oct. 20, 2021”, 28 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Decision on Pre-Appeal Brief Request for Review mailed Sep. 8, 2021”, 2 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Final Office Action mailed Apr. 7, 2020”, 13 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Final Office Action mailed May 18, 2021”, 13 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Non Final Office Action mailed Nov. 18, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Non Final Office Action mailed Dec. 22, 2020”, 13 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Notice of Allowance mailed Mar. 22, 2022”, 8 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Pre-Appeal Brief filed Jul. 26, 2021”, 5 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Preliminary Amendment filed Oct. 2, 2018”, 12 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Response filed Mar. 16, 2021 to Non Final Office Action mailed Dec. 22, 2020”, 15 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Response filed Oct. 6, 2020 to Final Office Action mailed Apr. 7, 2020”, 10 pgs. cited by applicant

“U.S. Appl. No. 16/055,926, Response filed Dec. 31, 2019 to Non Final Office Action mailed Nov. 18, 2019”, 10 pgs. cited by applicant

“U.S. Appl. No. 17/808,962 Preliminary Amendment filed Sep. 1, 2022”, 7 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Examiner Interview Summary mailed Oct. 11, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Final Office Action mailed Aug. 22, 2023”, 13 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Non Final Office Action mailed Feb. 7, 2023”, 19 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Notice of Allowance mailed Nov. 29, 2023”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Response filed May 1, 2023 to Non Final Office Action mailed Feb. 7, 2023”, 9 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Response to Final Office Action mailed Aug. 22, 2023 filed Oct. 18, 2023”, 12 pgs. cited by applicant

“U.S. Appl. No. 17/808,962, Supplemental Notice of Allowability mailed Dec. 11, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/808,963, Final Office Action mailed Aug. 21, 2023”, 22 pgs. cited by applicant

“U.S. Appl. No. 17/808,963, Non Final Office Action mailed Feb. 16, 2023”, 25 pgs. cited by applicant

“U.S. Appl. No. 17/808,963, Notice of Allowability mailed Nov. 22, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/808,963, Notice of Allowance mailed Nov. 13, 2023”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/808,963, Preliminary Amendment filed Sep. 7, 2022”. cited by applicant

“U.S. Appl. No. 17/808,963, Response filed May 1, 2023 to Non Final Office Action mailed Feb. 16, 2023”, 16 pgs. cited by applicant

“U.S. Appl. No. 17/808,963, Response to Final Office Action mailed Aug. 21, 2023 filed Oct. 26, 2023”, 18 pgs. cited by applicant

“Australian Application Serial No. 2016379813, First Examination Report mailed Mar. 20, 2018”, 3 pgs. cited by applicant  
“Australian Application Serial No. 2016379813, Response filed Jul. 13, 2018 to First Examination Report mailed Mar. 20, 2018”, 104 pgs. cited by applicant  
“Chinese Application No. 201680083757.9, Notification of First Office Action issued Feb. 3, 2019”, (Feb. 3, 2019), 5 pgs. cited by applicant  
“International Application Serial No. PCT/US2016/020853, International Preliminary Report on Patentability mailed Aug. 9, 2018”, 11 pgs. cited by applicant  
“International Application Serial No. PCT/US2016/020853, International Search Report mailed May 16, 2016”, 2 pgs. cited by applicant  
“International Application Serial No. PCT/US2016/020853, Written Opinion mailed May 16, 2016”, 9 pgs. cited by applicant  
“Japanese Application Serial No. 2018-550797, Notification of Reasons for Rejection mailed Dec. 10, 2018”, W/English Translation, 6 pgs. cited by applicant  
“Singaporean Application Serial No. 11201806316Q, Voluntary Amendment filed Aug. 8, 2018”, W/ English Claims, 15 pgs. cited by applicant

---

*Primary Examiner:* Bayard; Djenane M

*Attorney, Agent or Firm:* Schwegman Lundberg & Woessner, P.A.

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation Application under 35 USC § 120 of U.S. patent application Ser. No. 17/808,962, entitled “Multiple Server Automation for Secure Cloud Reconciliation,” filed on Jun. 24, 2022, which is a Continuation Application under 35 USC § 120 of U.S. patent application Ser. No. 16/055,926, entitled “Multiple Server Automation for Secure Cloud Reconciliation,” filed on Aug. 6, 2018, which is a Continuation Application under 35 USC § 120 of U.S. patent application Ser. No. 15/446,947, entitled “Multiple Server Automation for Secure Cloud Reconciliation,” filed on Mar. 1, 2017, which is a Continuation Application under 35 USC § 120 of U.S. patent application Ser. No. 15/011,055, entitled “Multiple Server Automation for Secure Cloud Reconciliation,” filed on Jan. 29, 2016, and are herein incorporated by reference in their entirety. (2) This application is related by subject matter to U.S. patent application Ser. No. 17/808,963, filed on the same day as patent application Ser. No. 17/808,962 that the instant application is claiming priority from, all of which are incorporated herein by reference in their entirety.

## **TECHNICAL FIELD**

(1) The present disclosure generally relates to automating multiple servers to perform secure cloud reconciliation. More specifically, to systems and methods for automated reconciliation of requests via data from various servers.

## **BACKGROUND**

(2) A sending entity receives a request for data from a receiving entity via email, on paper, or through an online service (via online servers). Such data requests between entities are often performed by third parties and, technically, are often performed using an electronic system.

(3) This process, once considered to be efficient and innovative, is now often a manual way to handle such transfers, particularly in the context of a cloud data management system that must work with millions of data transfers from countless entities simultaneously. To make a transfer, the sending entity connects to a server, manually enters the transfer details, and submits the transfer

request. The relevant transfer is made to the receiving entity's server from the sending entity's server.

(4) To make a similar data transfer via a third party, the sending entity connects to a server associated with the third party, enters the transfer details, and submits the transfer request. The relevant data is transferred from the sending entity's server to the third party server. The third party server then transfers said information to the receiving entity's server.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Some embodiments are illustrated by way of example and not of limitation in the figures of the accompanying drawings.
- (2) FIG. 1 is a block diagram depicting an example single ledger accounting platform, according to some embodiments.
- (3) FIG. 2 is a block diagram depicting an example accounting application framework for the accounting platform, according to some embodiments.
- (4) FIG. 3 is a block diagram depicting an example hosting infrastructure for the accounting platform, according to some embodiments.
- (5) FIG. 4 is a block diagram depicting an example data center system of the accounting platform, according to some embodiments.
- (6) FIG. 5 is a block diagram depicting an example request reconciliation system of the data management system, according to some example embodiments.
- (7) FIG. 6 is a block diagram depicting an example client device for accessing the data management system, according to some embodiments.
- (8) FIG. 7 is a block diagram depicting the flow of data between entities facilitating data movement and reconciliation, according to some embodiments.
- (9) FIG. 8 is a flowchart of an example method for facilitating data movement and reconciliation, according to some embodiments.
- (10) FIG. 9 is a flowchart of an example method for facilitating data movement request processing and reconciliation, according to some embodiments.
- (11) FIG. 10 is a block diagram of a machine in the example form of a computer system within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed, according to some embodiments.

### DETAILED DESCRIPTION

- (12) Example systems and methods to facilitate data movement and reconciliation are described. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of example embodiments. It will be evident, however, to one skilled in the art that the present technology may be practiced without these specific details.
- (13) The technology described herein provides data and message transmission between a one or more servers across differing domains to coordinate multiple parties into automated reconciliation of requests, data provisioning, and responses as part of a single transaction. The data request, provisioning, and reconciliation of responses may form all or part of a reconciliation system. In some embodiments, as described below, the reconciliation system may be used in conjunction with additional software or systems to provide one or more of the methodologies described herein for requesting, provisioning, and reconciling data transfers across distinct domains.
- (14) In some example embodiments, the technology described herein provides online (i.e., cloud based) software services to businesses with features such as a data transfer and reconciliation mechanism available to a business's customers. The data transfer and reconciliation mechanism may drive data elements through a designated server rather than second server of the second

domain (e.g., credit card transaction processors, PayPal, and so on), and perform subsequent automatic recording of that data element matched to the original data movement request within the reconciliation system. A data movement request may be understood as a statement of data elements for which a specified user or server is to perform a predetermined actions with respect to the data element.

(15) For example, the methods and systems described herein may enable transfer and reconciliation of payments between users where the payments are associated with data movement requests (i.e., payment or compensation requests and invoices). The payment initiator may generate an invoice and transmit the invoice to a second server of the second domain for transacting payment between the payment initiator (e.g., payee) and the payer. The payer may be presented with the complete or partial invoice during a network-based communication session (e.g., online banking session), either with the payer's bank or the second server of the second domain. The payer may initiate a payment transaction, handled between the second server of the second domain, the first entity, and the payee's bank. One or more of the first entity, the second server of the second domain, and the second entity provide notifications and invoice payment updates to the data management system which determines reconciliation of the payment and notification to the payee and payer.

(16) The information may be sent from the payment initiator to the institution via the customer (e.g., the payer). For example, the encrypted data may be sent from a web site of the payment initiator to a web browser of the customer running on a customer device. After the payment has been initiated by the institution, a confirmation may be sent to the customer, the payment initiator, the business, or any suitable combination thereof.

(17) FIG. 1 is a block diagram depicting an example single ledger data management system **100**. In some embodiments, the data management system **100** may be a single ledger accounting system **100** providing accounting tools to a particular entity managing accounting for one or more businesses. The example single ledger accounting system **100** may include a practice studio **110** that allows an entity to manage one or more businesses and an organization access module **150** that provides a business with tools for managing accounting data for that particular business. The practice studio **110** may include a practice staff management module **114**, an online training module **116**, a practice management module **118**, a partner resources module **120**, a report packs setup module **122**, and a work papers module **124**. The practice studio **110** may be in communication with core features **130**. The core features **130** may include an data provision module **132**, a community module **134**, a subscription management module **136**, a notifications center module **138**, a user profile management module **140**, and a login module **142**. The organization access module **150** may be in communication with the core features **130**. The practice studio **110** and core features may be accessed by an entity using a login module **142**.

(18) As shown in FIG. 1, features of the accounting system **100** are divided into three areas based on the target user. The features of the practice studio **110** provide a suite of tools for accountants to interact with their clients and manage their practices. The core features **130** provide the core functionality and user tools common to both accountants and businesses. The organization access module **150** provides a user interface for individual businesses to access their data.

(19) Practice studio **110** is the central login for accountants. For example, an accountant with multiple clients, each of which is a small business, can login using practice studio **110** and gain access to the accounting data for the clients, messages from the clients, and so on.

(20) The practice staff management module **114** provides the ability for the manager of an accounting practice to control settings for the staff of the practice. For example, some staff members may have read-only access to data for certain clients, some staff members may have read-write access for certain clients, some staff members may be able to modify the access permissions for other staff members, and so on.

(21) The online training module **116** provides training for accountants and their staff. In some cases, the provided training includes one or more video presentations and one or more online tests.

Notification of passing a test at completion of a training may be provided. For example, a staff member may take a training course and, upon successful completion, the accountant supervising the staff member may receive a notification of the successful completion.

(22) The practice management module **118** provides services for accountants. Access to the features provided by the practice management module **118** may be limited to accountants having a predetermined partner level with the data management platform provider. For example, access to the practice management module **118** may be limited to accountants at silver level or above. The services provided by the practice management module **118** may include workflow tools, customer relationship management (CRM) tools, lead generation tools, job management tools, data movement request generation tools, and so forth.

(23) The partner resources module **120** provides information regarding third-party partners. For example, a third party may provide tools that interact with the system to provide useful functionality beyond that of the system alone. The user can access the partner resources module **120** to learn about available third-party tools. For example, links to third-party websites, documentation, videos, and search tools may all be provided.

(24) The report packs setup module **122** provides tools to allow accountants to create and generate standardized sets of reports. For example, a profit and loss statement and quarterly report could both be added to a pack. The accountant would then be able to easily generate both reports for any selected client, or generate the reports for every client.

(25) The work papers module **124** provides tools for accountants to interactively create financial reports. For example, an accountant can enter known data for a client into the work paper, and then send the work paper to the client with an indication of data needed from the client. After the client enters the missing data into the work paper, the accountant can complete the report.

(26) The core features **130** includes modules that are used both by accountants and organizations. The data provision module **132** provides the general ledger for organizations. The general ledger may be integrated with the organization's payroll, bypassing the separate step of entering payroll data into the general ledger each pay period. The data provision module **132** accesses banking data for each client business. The banking data may be imported into either through a bank feed or a user- or accountant-created document. The data provision module **132** may also communicate with third-party tools via an application protocol interface (API).

(27) The community module **134** provides a forum through which users can communicate. For example, a user with a question may post a topic in the forum and later receive a helpful response from another user. Information taken from the user profile (e.g., the user profile managed via the user profile management module **140**) may appear along with forum posts by the user. For example, a user name, an image of the user, and the user's status as an accountant or member of an organization may each be shown.

(28) The subscription management module **136** allows a user to configure one or more billing accounts for each organization using the system. The system may periodically charge a subscription fee for access (e.g., a monthly or annual subscription fee). The subscription fee may be automatically deducted from the one or more billing accounts. Modules performing various functions of the subscription management module **136**, with respect to direct bank transactions are described with more detail below in FIG. 5.

(29) The notifications center module **138** provides notifications to users. For example, users may send messages to each other, which appear as notifications. Notifications may also be created by the system (e.g., by data provision module **132**) based on events. For example, a minimum account balance for a particular bank account may be set by a user via the data provision module **132**. When the balance for that bank account drops below the minimum account balance, a notification can be generated by the system informing the user.

(30) The user profile management module **140** allows a user to manage the profile of the user's organization and the profiles of others based on permission settings. For example, an accountant



may have permission to manage the profiles of the accountant's clients. The profile may include public-facing information such as a business name and address.

(31) The login module **142** verifies the identity of a user logging into the system (e.g., via user name and password). Based on the user's identity, a user interface is presented that includes a list of organizations that a user has access to. For most small business clients, the list will consist of a single organization.

(32) The organization access module **150** accesses the core features **130** for a single organization. The organization access module **150** presents, after user verification by the login module **142**, a user interface with options for a single organization without the additional features used only by the practice studio **110**.

(33) FIG. 2 is a block diagram depicting an example data management application framework **200** for the data management platform. The data management application framework **200** may be an end-to-end web development framework enabling a “software as a service” (SaaS) product. The data management application framework **200** may include a hypertext markup language (HTML) and/or JavaScript layer **210**, ASP.Net Model-View-Controller (MVC) **220**, extensible stylesheet language transformations (XSLT) **230**, construct **240**, services **250**, object relational model **260**, and database **270**.

(34) The HTML and/or JavaScript layer **210** provides client-side functionality, such as UI generation, receipt of user input, and communication with a server. The client-side code may be created dynamically by the ASP.NET MVC **220** or the XSLT **230**. Alternatively, the client-side code may be statically created or dynamically created using another server-side tool.

(35) The ASP.Net MVC **220** and XSLT **230** provide server-side functionality, such as data processing, web page generation, and communication with a client. Other server-side technologies may also be used to interact with the database **270** and create an experience for the user.

(36) The construct **240** provides a conduit through which data is processed and presented to a user. For example, the ASP.Net MVC **220** and XSLT **230** can access the construct **240** to determine the desired format of the data. Based on the construct **240**, client-side code for presentation of the data is generated. The generated client-side code and data for presentation is sent to the client, which then presents the data.

(37) The services **250** provide reusable tools that can be used by the ASP.Net **220**, the XSLT **230**, and the construct **240** to access data stored in the database **270**. For example, aggregate data generated by calculations operating on raw data stored in the database **270** may be made accessible by the services **250**.

(38) The object relational model **260** provides data structures usable by software to manipulate data stored in the database **270**. For example, the database **270** may represent a many-to-one relationship by storing multiple rows in a table, with each row having a value in common. By contrast, the software may prefer to access that data as an array, where the array is a member of an object corresponding to the common value. Accordingly, the object relational model **260** may convert the multiple rows to an array when the software accesses them and perform the reverse conversion when the data is stored.

(39) FIG. 3 is a block diagram depicting an example hosting infrastructure **300** for the data management platform. The platform may be implemented using one or more pods **310**. Each pod **310** includes application server virtual machines **320** (shown as application server virtual machines **320A-320C** in FIG. 3) that are specific to the pod **310** as well as application server virtual machines (VMs) that are shared between pods **310** (e.g., the internal services VM **330** and the application protocol interface VM **340**). The application server virtual machines **320-340** communicate with clients and third-party applications via a web interface or an API. The application server virtual machines **320-340** are monitored by application hypervisors **350**. An internal firewall **360** ensures that only approved communications are allowed between a database hypervisor **370** and the publicly-accessible virtual machines **320-340**. The database hypervisor **370**

monitors the primary SQL servers **380A** and **380B**. The primary SQL servers **380A** and **380B** access the shared storage layer **450A** or **450B** (shown in FIG. **4**) to read and write data generated by or used by the application server virtual machines **320-340**. The redundant SQL servers **390A** and **390B** provide backup functionality for the primary SQL servers **380A** and **380B**, respectively.

(40) The virtual machines **320-340** can be implemented using Windows 2008 R2, Windows 2012, or another operating system. The application and support servers supporting the virtual machines **320-340** can be built using spares for redundancy. The support servers can be shared across multiple pods **310**. The application hypervisors **350**, internal firewall **360**, and database hypervisor **370** may span multiple pods **310** within a data center. In some example embodiments, each primary SQL server **380** and redundant SQL server **390** is configured to support 30,000-45,000 organizations. Accordingly, in embodiments using two such server pairs per pod **310**, the pod capacity is 60,000-90,000 organizations. The redundant SQL servers **390** may take advantage of the “always on” resilience feature of SQL **2012**.

(41) FIG. **4** is a block diagram depicting an example data center system **400** of the data management platform interacting with other systems over a network. The primary data center **410** services customer requests and is replicated to the secondary data center **420**. The secondary data center **420** may be brought online to serve customer requests in case of a fault in the primary data center **410**. The primary data center **410** communicates over a network **455** with data flow server **460**, third party server **470**, client device **480**, and client device **490**. The data flow server **460** provides banking data (e.g., via the data flow application **465**). The third party server **470** is running third party application **475**. Client devices **480** and **490** interact with the primary data center **410** using web client **485** and programmatic client **495**, respectively.

(42) Within each data center **410** and **420**, a plurality of pods, such as the pod **310** of FIG. **3**, are shown. The primary data center **410** is shown containing pods **440A-440D**. The secondary data center **420** is shown containing pods **440E-440H**. The applications running on the pods of the primary data center are replicated to the pods of the secondary data center. For example, EMC replication (provided by EMC Corporation) in combination with VMWare site recovery manager (SRM) may be used for the application layer replication. The database layer handles replication between the storage layer **450A** of the primary data center and the storage layer **450B** of the secondary data center. Database replication provides database consistency and the ability to ensure that all databases are at the same point in time.

(43) The data centers **410** and **420** use load balancers **430A** and **430B**, respectively, to balance the load on the pods within each data center. The data centers **410** and **420** can be created using identical hardware to ensure that the performance of the secondary data center **420** is the same as the performance of the primary data center **410**. The storage layer **450A** and **450B** may be implemented using one or more storage area networks such as the VNX storage area networks from EMC.

(44) The data flow server **460** interacts with the primary data center **410** to provide bank records for bank accounts of the client. For example, the client may provide account credentials to the primary data center **410**, which the primary data center **410** uses to gain access to the account information of the client. The data flow server **460** can provide the banking records to the primary data center **410** for later reconciliation by the client using the client device **480** or **490**.

(45) The third party server **470** may interact with the primary data center **410** and the client device **480** or **490** to provide additional features to a user of the client device **480** or **490**. For example, a user may authorize the third party server **470** to access the user's data stored in the primary data center **410**. The third party application **475** of the third party server **470** may use the user's data to generate reports, provide macros, or otherwise improve the user's ability to access or manipulate the user's data. The third party application **475** may communicate with the primary data center **410** via the network **455** using an API. The third party application **475** may communicate with the client device **480** or **490** using a web or programmatic interface.

(46) FIG. 5 is a block diagram 500 illustrating components of an data reconciliation system 505 suitable for presentment of data movement requests, data provisioning, and reconciliation of the data movement request with transaction records (e.g., statements) of an associated server (i.e., an institution). As shown in FIG. 5, the data reconciliation system 505 is a part of the data provision module 132, according to some example embodiments. The data reconciliation system 505 is shown as including a receiver module 510, a code management module 520, a movement module 530, a status module 540, a verification module 550, a notification module 560, a presentation module 570, and a communication module 580 all configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of the modules described herein may be implemented using hardware (e.g., a processor of a machine) or a combination of hardware and software. For example, any module described herein may configure a processor to perform the operations described herein for that module. Moreover, any two or more of these modules may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

(47) The receiver module 510 receives data indicative of invoices, transaction records (e.g., responses to batch data movement requests), and other data transmitted to the data reconciliation system 505. The receiver module 510 passes requests or instructions relating to the data movement requests (e.g., invoices) and data transaction records to other modules of the data reconciliation system 505. The receiver module 510 may pass the requests, responses, and instructions to the other modules using the communication module 580. The receiver module 510 is a hardware-implemented module or a module implemented by a combination of hardware and software (e.g., hardware configured by software to perform various functions). An example embodiment of components included in or accessed by the receiver module 510 is described with respect to FIG. 10. Functions of the receiver module 510 are discussed in further detail below.

(48) The code management module 520 receives data indicative of data movement requests from the receiver module 510 and appends request codes to the data movement requests. In some example embodiments, the code management module 520 generates unique request codes (e.g., unique invoice codes identifying an invoice) prior to appending the request codes to the data movement requests. The code management module 520 may pass the data movement request with appended request code to one or more of the status module 540, the verification module 550, and the presentation module 570 using the communication module 580. In some example embodiments, the code management module 520 may store the data movement request and appended request code in a data structure (e.g., data table) within the database 270 for access and modification by one or more of the modules of the data reconciliation system 505. The code management module 520 can be a hardware implemented module or a combination of hardware and software implemented module. An example embodiment of components included in or accessed by the code management module 520 is described with respect to FIG. 10.

(49) The movement module 530 requests and receives movement responses (e.g., indications of payment) during network based communications sessions (e.g., a network-based banking session). For example, in some embodiments where the reconciliation system 505 is reconciling payments, the movement module 530 requests and receives indications of payment during the network-based communications session. The movement module 530 may store the movement responses in the database 270 for access by other modules. In various embodiments, the stored movement responses are associated within the database 270 with user profile information and a data movement request for which the movement request is a response. The movement module 530 is a hardware implemented module or a combination of hardware and software implemented module. An example embodiment of components included in or accessed by the movement module 530 is described with respect to FIG. 10.

(50) The status module **540** identifies and modifies status indicators within invoices to reflect changes in status of movement for the data movement request. The status module **540** accesses and modifies the status indicators of the data movement request stored in the database **270**. The status module **540** may be a hardware implemented module or a combination of hardware and software implemented module. An example embodiment of components included in or accessed by the status module **540** is described with respect to FIG. **10**.

(51) The verification module **550** verifies movement responses from recipients and reconciles data movement requests with data movements passing among servers across domains (e.g., institutions). In various example embodiments, the verification module **550** uses the communication module **580** to transmit batch data movement requests and receive movement notifications including statements of data movement (e.g., transaction records within a date range) from servers across one or more domains (e.g., institutions) associated with users of the data management system **100** in order to verify transaction data relating to movement responses using the data reconciliation system **505** and reconcile data movement requests with the transaction data. The verification module **550** can be a hardware implemented module or a combination of hardware and software implemented module. An example embodiment of components included in or accessed by the verification module **550** is described with respect to FIG. **10**.

(52) The notification module **560** generates notifications of payment for the data reconciliation system **505**. In various example embodiments, the notification module **560** generates presentation notifications verifying presentation of the data movement request and request code at a client device (e.g., the client device **480** or **490**), and various other functions described herein. The notification module **560** can be a hardware implemented module or a combination of hardware and software implemented module. An example embodiment of components included in or accessed by the notification module **560** is described with respect to FIG. **10**.

(53) The presentation module **570** causes presentation of data movement requests and transaction detail information (e.g., statement responses, account information, payment information, and reconciliation information) at client devices (e.g., the client device **480** or **490**). The presentation module **570** can generate a set of user interface elements, screens, frames, or the like for presentation at client devices. The presentation module **570** causes presentation of data movement requests and transaction detail information by transmitting data representative of the data movement requests and the transaction detail information to the client device, via the communication module **580**. The presentation module **570** can be a hardware implemented module or a combination of hardware and software implemented module. An example embodiment of components included in or accessed by the presentation module **570** is described with respect to FIG. **10**.

(54) The communication module **580** may facilitate communication among the receiver module **510**, the code management module **520**, the movement module **530**, the status module **540**, the verification module **550**, the notification module **560**, the presentation module **570**, the client device **480** or **490**, third party server **470**, and the data flow server **460**. In some embodiments, the communication module **580** facilitates or enables communication with a plurality of bank servers, with the data flow server **460** among the plurality of bank servers. The communication module **580** may enable communication among the modules and components described herein via a bus, shared memory, a switch, or any other suitable communication mechanism or method. As such, the communication module **580** may be a configured port, server, or other hardware device configured by software or machine-executable instructions to perform one or more of the communications related methodologies described herein.

(55) FIG. **6** is a block diagram illustrating components of a block diagram **600** (e.g., representing a client device) suitable for mobile banking reconciliation, according to some example embodiments. The client device **480** (or **490**) is shown as including a communication module **610**, a display module **620**, an input module **630**, and a reconciliation module **640**, configured to communicate

with each other (e.g., via a bus, shared memory, or a switch).

(56) The communication module **610** may communicate with the primary data center **410**, the third party server **470**, the network **455**, or any suitable combination thereof. Information received via the communication module **610** may be presented (e.g., displayed on a display device) via the display module **620**. Information may be selected or search queries may be entered by a user of the client device **480** (or **490**).

(57) A user interface is presented by the display module **620**. The input from the user is detected by the input module **630**. Commands received from the user by the input module **630** may be communicated to the primary data center **410** by the communication module **610**. The communication module **610** may receive a response from the primary data center **410** that includes a set of banking records, a set of business records, associations between individual banking records and individual business records that indicate reconciliation between those records, and other data, in any combination.

(58) The reconciliation module **640** can generate requests to the primary data center **410** to indicate that a banking record is reconciled by one or more business records. The request can be communicated to the primary data center **410** via the communication module **610**, over the network **455**.

(59) FIG. 7 is a block diagram depicting the flow of data between entities facilitating a transfer of funds, in an example embodiment. The entities interacting within FIG. 7 are a first device **702** (e.g., a client device **480** or **490** associated with a first user), a first entity **704**, a second server of the second domain **706**, second entity **708**, the data management system **100**, and a second device **710** (e.g., a client device **480** or **490** associated with a second user). In some instances, the first device **702** is associated with a user of the data management system **100**. In context of FIG. 7, and the methodologies described herein, the first user, employing the first device **702** or any other suitable device, is the paying party of the transaction billed by the second user, generating a bill and transaction using the second device **710** or any other suitable device.

(60) The first entity **704** is a institution associated with the first user or the first device **702**. As described herein, the first entity **704** is a bank capable of performing network-based (e.g., online) transactions for and against an account of the first user. However, it should be understood that the first entity **704** may be any suitable institution such as a bank, a credit union, a second server of the second domain drawing on an associated payment account of the first user, or any other institution. In some embodiments the payment account of the first user is associated with the first device **702** accessed through the first device **702**.

(61) The second server of the second domain **706** is a network-based service capable of performing all or part of a payment transaction between two institutions (e.g., the second entity **708** and the first entity **704**). In various embodiments, the second server of the second domain **706** is a third party second server of the second domain (e.g., PayPal, CheckFree, an ACH system, etc.). However, it should be understood that, in some embodiments, the second server of the second domain **706** is affiliated with or a part of the first entity **704**. In these embodiments, transactions, such as billing statements, transmitted to the second server of the second domain **706** are effectively transmitted to the first entity **704**.

(62) The second entity **708** is a institution associated with the second user, and may be associated with the second user through a second user account. The second user may use the second device **710**. In various embodiments, the second entity **708** is a bank capable of performing network-based (e.g., online) transactions for and against an account of the second user, a credit union, a second server of the second domain drawing on an associated payment account (e.g., second user account) of the second user, or any other suitable institution. The second user is a user of the data management system **100** and may access the data management system **100** using the second device **710**.

(63) As shown in FIG. 7, the second user may interact with the data management system **100**, using

the second device **710**, to enroll in one or more service of the data management system **100**, electronically present bills (e.g., ebill) directly to a network enabled (e.g., online) bank account of the first user associated with the first device **702**. In various embodiments, the data management system **100** enrolls second user by a registration function **712** exchanging information between the data management system **100** and the second device **710**. The registration function **712** may create an account or otherwise associate the second user or the second device **710** with the data management system **100** to generate identifiable information for the second user or the second device **710** within the data management system **100**. For example, the registration function **712** may prompt the second user to enter, using the second device **710**, an account name, a password, demographic information, financial information, contact information, and information relating to goods and services for which the second device **710** may generate data movement requests or other records automatically or by interaction between the second user and the second device **710**.

(64) In various embodiments, in function **714**, the data management system **100** registers second user or the second device **710** with one or more of the first entity **704** and the second server of the second domain **706**. Although function **714** is shown in FIG. 7 as extending between the data management system **100** and the second server of the second domain **706**, it should be understood that the function **714** may similarly register the second user or second device **710** with the first entity **704**. In some instances, the function **714** registers the second user or second device **710** with a plurality of institutions. For example, the data management system **100**, via the function **714**, may register the second user or second device **710** with a plurality of institutions with which the data management system **100** is associated or who recognize the data management system **100**. In some instances, the data management system **100** registers the second user or second device **710** automatically, without user interaction from the second user via the second device **710** after the second user enrolls with the data management system **100** via the function **712** using the second device **710**. In some embodiments, completion of the function **712** causes the data management system to automatically perform the function **714** to register the second user or second device **710** with the plurality of institutions.

(65) After the second device **710** has interacted with the data management system **100** via the function **712** to enroll the second user and the data management system **100** has registered the second user or the second device **710** by the function **714**, the second device **710** may generate electronic bills and transmit the electronic bills by the data management system **100** to one or more of the plurality of institutions (e.g., the first entity **704** and the second server of the second domain **706**). Generation of an electronic bill is performed through bill creation function **720**. The bill creation function **720** may include generation and presentment of a user interface (e.g., a set of user interface screens) at the second device **710** to generate and transmit the ebill to the first device **702** (e.g., a client device associated with the first user). For example, the second device **710** may present a set of selectable user interface elements within a graphical user interface prompting or accepting input of various transaction data, such as item or service information, purchase terms, purchase price, payer information, and other data which may form part of a transaction between a merchant and a customer. In various embodiments, the data management system **100** may automatically generate the ebill based on transactions passed to the data management system **100** from the second device **710**. For example, where the second user has an electronic commerce website through which the first user makes a purchase using the first device **702**, the website may pass transaction data to one or more of the second device **710** and the data management system **100**. Receiving the transaction data may trigger the data management system **100** to generate the ebill without further input or interaction by the second user.

(66) The data management system **100** submits the ebill (e.g., an data movement request or invoice) generated via function **720** to the second server of the second domain **706** via function **722**. In some instances, the data management system **100** submits the ebill to the first entity **704**, directly or through the second server of the second domain **706**. The submission of the ebill via

function **722**, as well as billing and payment functions logged or conducted through the data management system **100** are accounting transactions tracked by the data management system **100**. In function **720** or prior to the function **720**, the data management system **100** generates a unique identifier and includes the unique identifier within the data movement request as a part of either a full or partial data movement request presentment at the first device **702**. In some embodiments, the data movement request is presented as a single data movement request, while in some embodiments, a single data movement request may be divided and presented as multiple data movement requests (e.g., an invoice paid on an installment plan). In embodiments where the data movement request is presented as multiple data movement requests, the multiple data movement requests may each receive a unique identifier or may each contain the same unique identifier.

(67) The first device **702** may request ebills (e.g., data movement requests or invoices) from the first entity **704** via a bill request function **724**. In some embodiments, the bill request function **724** is performed in response to interactions between the first user operating the first device **702**. The bill request function **724** may also be automated, such that the first device **702** performs the bill request function **724** based on a scheduled time or one or more monitored conditions. Monitored conditions may include an email having an data movement request, operation of an application on the first device **702** in which a payment function of the application was used, accessing of a purchasing application on the first device **702**, accessing of a commerce website in a browser of the first device **702**, or any other monitored condition. In embodiments where the first device **702** requests ebills using the bill request function **724**, the first user may be required to register (e.g., register the first user or register the first device **702**) via function **726** to receive ebills from the second user generated by one or more of the second device **710** and the data management system **100**. The registration function **726** may be performed similarly to the registration or enrollment processes discussed above. In some instances, the registration function **726** includes enrolling in an online banking service.

(68) As shown in FIG. 7, the second server of the second domain **706** presents the ebill in a presentation function **728**, after registration. In various embodiments, the bill request function **724** is a function involving the data management system **100** and the second server of the second domain **706**, where the data management system **100** has a preexisting relationship with the first entity **704** and the second server of the second domain **706** as established via functions **712** and **714** described above. In some instances, as shown in FIG. 7, the bill request function **724** is a function of the first entity **704** performed during an online communication session between the first entity **704** and the first device **702**.

(69) The first device **702** interacts with the first entity **704** to cause the first entity **704** to perform a payment function **730**. As will be explained in more detail below, the payment function **730** remits payment to the second entity **708** through the second server of the second domain **706**. A portion of the payment function **730** may be part of or trigger the data management system **100** to reconcile accounts for the first user and the second user with respect to the payment and transmit notification of the reconciled accounts to one or more of the first device **702** and the second device **710**. The payment function **730** causes the second server of the second domain **706** to transmit the payment and payment identification **732** to the second entity **708**.

(70) Transmission of the payment and payment identification **732** to the second entity **708** causes (e.g., triggers or includes) transmission of a notification of receipt **734** to the data management system **100**. The notification of receipt includes the unique identifier, as well as a payment identifier generated in function **732**. In various embodiments, the payment identifier is presented within transaction records of the second entity **708**. The payment identifier may be one or more of, but not limited to, ACH descriptors, generated check numbers, or previously supplied data movement request or unique identifier. In response to receiving the notification of receipt **734**, the data management system **100** causes presentation of a notification of receipt **736** at the second device **710**. Matching the notification of receipt **736** to the unique identifier for the transaction, the

data management system **100** verifies via function **738** (e.g., reconciles) the account information matching with payment identifier received in an electronic statement download from second entity as show in function **740**.

(71) The unique identifier and the payment identifier may be generated as numeric strings, alpha-numeric strings, or any suitable uniquely identifiable code. In some embodiments, one or more of the unique identifier and the payment identifier are generated as alpha-numeric strings of at least sixteen characters. In some instances, one or more of the unique identifier and the payment identifier are sequential, building on previous identifiers while maintaining a unique string. In some instances, a portion of an identifier indicates the second server of the second domain **706** and correlates the data movement request with the second server of the second domain **706**. For example, three digits of the identifier may be contain a dedicated code for the second server of the second domain **706**.

(72) FIG. **8** is a flowchart of an example method **800** for facilitating data movement request presentment, data movement, and reconciliation services. Operations in the method **800** may be performed by the data management system **100** using modules and components described above with respect to FIG. **5** and hardware described below with respect to FIG. **10**.

(73) In various embodiments, the method **800** may be initiated with an operation **805**. In operation **805**, the login module **142** in cooperation with one or more of the verification module **550**, the presentation module **570**, and the communication module **580** causes presentation of one or more user interface elements enabling a user of a client device (e.g., the client device **480**, the first device **702**, the second device **710**) to input information and register with one or more of the data management system **100**, the first entity **704**, and the second server of the second domain **706**. The information input into the one or more user interface elements may include demographic information, identification information, or second entity information associated with the user. The login module **142** and one or more of the verification module **550**, the presentation module **570**, and the communication module **580** performs the operation **805** to register a second user (e.g., second user or the second device **710**) and the first user's profile on the data management system **100** with a first entity (e.g., first entity **704**) and a second server of a second domain (e.g., payment service **706**). The registration process enables the data management system **100** to track and reconcile data movement requests received at the data management system **100** for presentation to the first entity (e.g., first entity) and receive the movement response of the data movement request from one or more of the first entity, the second entity, or the second server of the second domain.

(74) In some embodiments, the operation **805** is performed in a graphical user interface of the data management system **100** after the second device **710** transmitted one or more login credentials to the data management system **100**. After registering with one or more of the first entity **704** and the second entity **708**, the data management system **100** may automatically download transaction records from the second entity **708** into the user profile of the data management system **100** and receive transaction notifications from the first entity **704**. In some instances, the data management system **100** may download only indications of the transactions, such as an amount of each transaction, a date of each transaction, and an identifier for each transaction. The data management system **100** may automatically reconcile previous data movement requests with one or more of the transaction records or present the transaction records for manual reconciliation for past data movement requests.

(75) In operation **810**, the receiver module **510** receives a data movement request. The data movement request has a first status indicator representative of a status of the data movement request of the data movement request. The first status indicator represents an unfulfilled status of the data movement request (e.g., an unpaid payment status) of the data movement request. The receiver module **510** may receive the data movement request from the second device **710** of the second user. The receiver module **510** may receive an indication of the second user selecting to generate the data movement request via interaction with the second device **710**. In these instances,



the receiver module **510** may pass the request to generate the data movement request to one or more modules of the data management system **100** or the second device **710** to generate the data movement request. Where the second device **710** generates the data movement request, the second device **710** transmits the data movement request back to the data management system **100**. Once the data movement request has been received by the receiver module **510**, the data movement request is stored in the database **270** of the data management system **100**. In some instances, the data movement request is associated with one or more profile of the first user and the second user, such that modifications of the data movement request or status of the data movement request may be reflected with one or more notifications presented at the second device **710** and the first device **702**.

(76) In various example embodiments, to create an data movement request, the second device **710** presents a user interface including selectable user interface elements configured to generate the data movement request with suitable information for processing by the data management system **100** and the data reconciliation system **505**. For example, the second device **710** may present a create invoice button, operable (e.g., by the second user) to create an data movement request. Upon selection of the create data movement request button (e.g., invoice button), the second device **710** presents a series of user interface screens and user interface elements requesting information including a total amount for the data movement request, a name of the customer (e.g., the first user), a type of invoice, a logo for the business of the second user, an upload data entry field for uploading an image representative of the logo of the business, data entry fields for mailing addresses of each of the first user and the second user, billing information (e.g., a billing account number, a payable bank account, etc.), a metadata field for metadata regarding the data movement request, and item detail data. The metadata field may include fields for an invoice number, a reference name, a goods and services tax (GST) number, an issued date, and a due date. The item detail data may include an item description, a quantity, a unit price, and an amount.

(77) In operation **820**, the code management module **520** appends a unique request code to the data movement request. In various example embodiments, the code management module **520** generates the unique request code, in response to receiving the data movement request, prior to appending the unique request code to the data movement request. The code management module **520** may append the unique request code to a predetermined portion of instructions configured to represent the data movement request in a user interface. The code management may append the unique request code to the data movement request within metadata associated with the data movement request or within the instructions representative of the data movement request. In some embodiments, the instructions or the metadata may be exposed to an API of the data management system **100**, enabling one or more of the metadata and the instructions to be opened and modified to include the unique request code. The unique request code may be presented to the user in a user perceivable format within a graphical representation of the data movement request.

(78) In some example embodiments, the unique request code does not identify the specific data movement request. For example the unique request code may be an account identification for the second user of the data management system **100** or the second device **710** associated with the second user. In these embodiments, the data movement request may have a request identification number in addition to the unique request code. The data management system **100** may use the unique request code (e.g., the account identification) to track the progress of the data movement request and data provision (e.g., payment) of the data movement request within the first entity **704** and the second server of the second domain **706** and provide status modifications, notifications, and other data movement request tracking operations within the data management system **100** and to the second device **710**. In this manner, requests, responses, and notifications among the first entity **704**, the second server of the second domain **706**, and the second entity **708**, routed to the data management system **100** with the associated account identification (e.g., unique request code) may serve as an automated reconciliation system to generate account records within the data

management system **100** to be associated with the accounts of the first user and the second user.

(79) In operation **830**, the presentation module **570** causes presentation of the data movement request at the first device **702** of the first user. In various embodiments, the data movement request is presented during a network based communication session with the second server of the second domain **706** or in a user session of the data management system **100**. Where the data movement request is presented in the network based communication session, the data movement request may initially be presented at the first device **702** within a browser and without navigating away from the network based communication session. Where the data movement request is presented during a communication session of the data management system **100** and the first device **702**, the data management system **100** may cause the first device **702** (e.g., the client device **480** shown in FIG. **6**) to present the data movement request in a dedicated application, an email, an online user session, or any other suitable user session. Where presented as an email, a link contained in the email may, when selected as a user selectable element presented in a graphical user interface, automatically cause a web browser or application to open and prompt entry of user login credentials to view the data movement request. Once in the communication session, the data management system **100** may cause presentation of one or more of a data movement request identifier, a unique URL associated with the data movement request, and one or more detail information of the data movement request (e.g., currency amounts, services rendered, or goods purchased).

(80) In some instances, the data movement request is presented in a communication outside the network based communication session. For example, the data movement request and unique request code may be presented at the first device **702** in the form of an email. In some embodiments, the unique request code may form a link to the second server of the second domain **706** or the first entity **704**. Selecting the link within the email presented at the first device **702** may cause the first device **702** of the first user to be directed to transmit login credentials. For example, the link may cause the first device **702** to present directions for the first user to sign in for a network based communication session with the first entity **704** or the second server of the second domain **706**. The first device **702** may transmit login credentials to the network based communication session to cause presentation of additional information related to the data movement request or make a payment for the data movement request.

(81) In various embodiments, the data movement request includes a payment link. The payment link may include a link to the second server of the second domain **706**. Upon selection of the payment link, the first device **702** present a user interface prompt for an identification of the first entity **704**. Upon selection of the identification of the first entity **704** the browser of the first device **702** of the first user is directed to a second server of the second domain (e.g., the payment service **706**) of a plurality of second servers. The second server of the plurality of second servers is a second server which supports the first entity **704**. In addition to directing the browser of the client device to the selected second servers, selecting the first entity **704** may automatically populate payment information required by the selected second server **706** to perform a transaction in response to the data movement request. In various example embodiments, the data movement request prepopulates an identifier for one or more of the data movement request (e.g., the unique request code, the request identifier, the account identification) and the first user or first device **702**; an amount of the invoice (e.g., a total amount of the invoice, a minimum payment, etc.); and identification of the second user or second device **710**. The first device **702** may then receive selection of a payment button (e.g., a user interface element) to instruct the second server **706** to process the payment among the first entity **704** and the second entity **708**.

(82) In operation **840**, the movement module **530** receives a movement response via the network based communication session. In some instances, the movement response includes payment transaction details indicative of a payment received from the client device by the second server **706**. The movement response may be generated by one or more of the first entity **704** and the second server **706**. Where generated by the first entity **704**, the movement response is an indication

that the payment has been forwarded to the second server **706**. In these embodiments, the movement response is forwarded, along with payment instructions to the second server **706** for further processing of the movement response and the payment instructions. Where the movement response is generated by the second server **706**, the movement response is generated in response to receiving payment instructions from the first entity **704**.

(83) The payment transaction may extend between two or more of the second entity **708**, the first entity **704**, and the second server **706**. In some embodiments, when the payment transaction is processed between the first entity **704** and the second entity **708**, the data management system **100** may receive a notice of the payment (e.g., the movement response) based on registration of one or more of the user and the data management system **100** with the first entity **704** or the second server **706**. In some embodiments, when the first entity **704** transmits payment to the second entity **708**, the transmission of payment causes a payment server of the first entity **704** to parse one or more notification tables to determine one or more entities to whom the movement response will be transmitted. In some instances, registration of the user with the first entity **704** through the data management system **100** causes the payment server to identify the data management system **100** as a recipient of the movement response. The registration of the user with the first entity **704** may be achieved through one or more of the functions **712** and **714**. The movement response may be transmitted in response to the function **722**, presenting the ebill to one or more of the second server **706** and the first entity **704**.

(84) In operation **850**, the status module **540** modifies the first status indicator of the data movement request to a second status indicator to provisionally reflect the receipt of movement response. In some instances, after the data movement request (e.g., the notification of receipt **734**) has been received and stored in the database **270**, the data movement request may include one or more indicator bits. The indicator bits may be modified by the status module **540** to indicate the current status of the data movement request of the data movement request. Upon receiving notifications representing changes in the status of the data movement request, the status module **540** may change the indicator bit, generate a notification of the change in the status of the data movement request, and transmit the notification of the change in status of the data movement request to one or more of the first device **702** and the second device **710**. As described in operation **850**, the status module **540** may perform multiple modifications to the indicator bits based on transaction stages. In some instances, a modification, such as the change from the first status indicator to the second status indicator, may be understood as a provisional change reflecting an expectation of a further modification of the status indicator. For example, the status module **540** may change the indicator bit to a value indicating an data movement request has been partially paid (e.g., a provisional change) or paid (e.g., the further modification of the status indicator.).

(85) In operation **860**, the verification module **550** verifies the movement response from a payment receipt. Verifying the movement response may be understood as reconciling a banking record with the data movement request. In various example embodiments, the operation **860** contains one or more further operations. For example, as shown in FIG. **8**, in operation **862**, the verification module **550** transmits a batch data movement request to one or more of the second entity **708** (e.g., a bank associated with a recipient of the payment, the second server **706**) and the primary data center **410**. The batch data movement request may be transmitted to the second entity **708**, the second server **706**, or the primary data center **410** via the communication module **580** and the network **455**. For example, in some embodiments, the batch data movement request may be transmitted to the primary data center **410** for processing and routing to the second server **706** or the second entity **708**. In some instances, the primary data center will determine payment reconciliation prior to responding to the verification module **550**.

(86) In operation **864**, the verification module **550** receives confirmation of the data movement from one or more entity. In some embodiments, the data movement may be a payment for which confirmation is received and the one or more entity may be a financial institution. For example, the

verification module **550** may receive confirmation from the first entity **704**, the second entity **708**, the second server **706**, or the primary data center **410**. The confirmation may be in the form of a statement of data movement (e.g., a set of transactions falling within a specified date), a payment query response, or any other suitable confirmation. Where the verification module **550** receives confirmation from the first entity **704**, the first entity **704** may transmit an indication that funds have been deducted from the first user account. Where the verification module **550** receives confirmation from the second entity **708**, the second entity **708** may transmit an indication that funds have been received into the second user account. Where the verification module **550** receives confirmation from one or both of the second server **706** or the primary data center **410**, the second server **706** may indicate a completion of processing the payment through the second server **706**. The primary data center **410** may provide confirmation that one or more of the second entity **708**, the first entity **704**, and the second server **706** has performed the above described actions.

(87) In some embodiments, in operation **864**, the receiver module **510** receives a bank statement from the second entity **708** as confirmation of the payment from one or more financial institution. The receiver module **510** may receive the bank statement in response to the batch data movement request. The bank statement is a statement of data movement for the second user and may include one or more of payee account information, payer account information, the payment identifier, the unique transaction identifier, and other transaction details. In some instances, the payment identifier may be stored in an ACH field. In various embodiments, the bank statement is a statement response in the form of an XML document or other structured data format.

(88) The receiver module **510** may pass the bank statement to the verification module **550**. In response to receiving the bank statement and without user interaction, the verification module **550** matches the bank statement to the data movement request. In some instances, the verification module **550** reconciles the account information with the bank statement by matching the payment identifier received in the electronic bank statement with the unique identifier for the data movement request. The verification module **550** may identify the payment identifier within the bank statement stored in the ACH field, parse the payment identifier, and parse one or more unique identifiers included within data movement requests associated with a payee in the data management system **100**. The verification module **550** may match the payment identifier with one of the one or more unique identifiers by determining the values for a unique identifier and the payment identifier are identical.

(89) In embodiments where the verification module **550** receives confirmation from the second server **706** and the bank statement from the second entity **708**. The verification module **550** matches the data movement request to the bank statement and the confirmation from the second server **706** to reconcile the account information with the bank statement and the confirmation from the second server **706**. In some instances, the verification module **550** automatically parses the bank statement and the confirmation from the second server **706** and compares information parsed from the bank statement and the confirmation with the data movement request to match the payment identifier in the electronic bank statement and the payment identifier in the confirmation with the unique identifier for the data movement request.

(90) FIG. **9** is a flowchart of an example method **900** for facilitating data movement request processing and payment reconciliation. Operations of the method **900** may be performed by the data management system **100** using modules and components described above with respect to FIG. **5** and hardware described below with respect to FIG. **10**. As shown in FIG. **9**, the method **900** includes one or more operations of the method **800** described above.

(91) In some instances, the method **900** is initially performed by operation **810**. In various example embodiments, the data movement request includes a detail link. The detail link may be understood and implemented as a hyperlink, a network address, or any other suitable link enabling communication or contact with the second server. In order to initiate the communication relating to the detail link, the first device **702** receives a selection of the detail link in a user interface

representation of the data movement request. The detail link is configured to direct a browser of the client device to request transaction detail information from the server via the network, the transaction detail information including transaction information for the data movement request. (92) In operation **910**, the movement module **530** transmits the data movement request (e.g., the data movement request for the payer), including the unique data movement request code and the detail link, to the second server **706** for presentation during the network based communication session. The movement module **530** may transmit the data movement request, the unique request code, and the detail link using the communication module **580** via the network **455**.

(93) In various example embodiments, the transmission of the data movement request, unique request code, and the detail link is in response to receiving a request for ebill or data movement request information from the first device **702**, via the first entity **704**, to one or more of the second server **706** and the data management system **100**. For example, the request for ebill is received by the second server **706** and transmitted to the data management system **100** storing the data movement request, unique request code, and detail link. In return, the data management system **100** transmits the ebill (e.g., the data movement request, the unique request code, and the detail link) to the second server **706** for presentation at the first device **702**.

(94) In operation **920**, in response to receiving a request for transaction detail, the presentation module **570** causes presentation of the data movement request, the unique request code, and further transaction detail information at the first device **702** associated with the first user. The request for transaction detail may be in the form of the first device **702** receiving a selection of the detail link within the data movement request in the network based communication session and generating an indication of the selection as the request for transaction detail. Selection of the detail link may cause the client device to transmit a request to the second server **706** for forwarding to the data management system **100**. In response to the request, the transaction detail information may be transmitted to the second server **706** from the data management system **100**. The transaction detail may include the data movement request, time of data movement request, itemized charges, goods or services received, and other pertinent information stored on the data management system **100**. In various example embodiments, causing presentation of the transaction detail information is performed by providing the transaction detail information as presented during the network based communication session without navigating away from or interrupting the network based communication session. In some instances, the detail link may navigate or otherwise direct the client device browser to, or open a new window directed to, the data management system **100** for presentation of the transaction detail.

(95) In operation **930**, the movement module **530** receives a presentation notification from the second server **706**. The presentation notification is indicative of presentation of at least the data movement request and unique request code at the client device during the network based communication session. The presentation notification may be automated such that when the data movement request is presented at the first device **702** on the client device, the client device transmits a response through the second server **706** to the data management system **100** indicative of the presentation. The presentation notification may be in the form of user interface instructions configured to generate a user perceivable notification, instructions configured to change a status or other portion of the data movement request on the database **270** of the data management system **100**, or any other suitable presentation notification. In some instances, the presentation notification may be forwarded to the second device **710** or otherwise indicated in a profile of the second user.

(96) In various example embodiments, after receiving the movement response in operation **840**, the movement module **530**, in operation **940**, generates a notification of receipt, the notification containing confirmation of receipt of the movement response from the second server **706**. In some embodiments, where the movement response is an indication of payment, the notification may be a notification of payment received from a payment service in the form of the second server **706**. The notification of receipt may be generated in response to the first device **702** interacting with the first

entity **704** in the network based communication session to set up a payment for the data movement request.

(97) In some instances, the first entity **704** may generate a payment instruction, after interaction with the first device **702**. The first entity **704** may then transmit the payment instruction to the second server **706**. After receiving the payment instruction, the second server **706** may execute the payment instruction against the first user's account at the first entity **704** and transmit the funds, along with a payment identification to the second entity **708**. The second server **706** may also include the payment identification and the unique request code in the movement response transmitted to the data management system **100**. The data management system **100** may store the movement response in the database **270** and associate the movement response with the data movement request.

(98) In operation **950**, the movement module **530** transmits the notification of receipt, including the payment identification and the unique request code, to the second device **710** of the second user via the network **455**. In some instances, the movement module **530** may also transmit the notification of receipt to the first device **702** of the first user as a confirmation of the payment transaction.

(99) In some embodiments, at least a portion of the method **900** may be further performed in the operation **850**, by modifying the first status indicator, and the operation **860**, by verifying the movement response. In operation **960**, in response to verifying the movement response, the status module **540** modifies the second status indicator to a third status indicator to reflect the verification of the movement response for the data movement request. The status module **540** may modify the data movement request within the database **270** and information relating to the data movement request in one or more of the profiles of the first user and the second user. In these embodiments, the first device **702** and the second device **710** may receive a final notification of the status of the data movement request and the status module **540** may close a transaction represented by the data movement request.

(100) Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Modules may constitute either software modules (e.g., processor executable instructions embodied on a non-transitory machine-readable storage medium or in a transmission signal) or hardware modules. A hardware module is a tangible unit capable of performing certain operations and may be configured or arranged in a certain manner. In example embodiments, one or more computer systems (e.g., a standalone, client, or server computer system) or one or more hardware modules of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

(101) In various embodiments, a hardware module may be implemented mechanically or electronically. For example, a hardware module may comprise dedicated circuitry or logic that is permanently configured (e.g., as a special-purpose processor, such as a field programmable gate array (FPGA) or an application-specific integrated circuit (ASIC)) to perform certain operations. A hardware module may also comprise programmable logic or circuitry (e.g., as encompassed within a general-purpose processor or other programmable processor) that is temporarily configured by software to perform certain operations. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations.

(102) Accordingly, the term “hardware module” should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired) or temporarily configured (e.g., programmed) to operate in a certain manner and/or to perform certain operations described herein. Considering embodiments in which hardware modules are temporarily configured (e.g., programmed), each of the hardware modules need not be configured or instantiated at any one instance in time. For example, where the hardware modules comprise a

general-purpose processor configured using software, the general-purpose processor may be configured as respective different hardware modules at different times. Software may accordingly configure a processor, for example, to constitute a particular hardware module at one instance of time and to constitute a different hardware module at a different instance of time.

(103) Hardware modules can provide information to, and receive information from, other hardware modules. Accordingly, the described hardware modules may be regarded as being communicatively coupled. Where multiple of such hardware modules exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) that connect the hardware modules. In embodiments in which multiple hardware modules are configured or instantiated at different times, communications between such hardware modules may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware modules have access. For example, one hardware module may perform an operation, and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware module may then, at a later time, access the memory device to retrieve and process the stored output. Hardware modules may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

(104) The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented modules that operate to perform one or more operations or functions. The modules referred to herein may, in some example embodiments, comprise processor-implemented modules.

(105) Similarly, the methods described herein may be at least partially processor-implemented. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented modules. The performance of certain of the operations may be distributed among the one or more processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processor or processors may be located in a single location (e.g., within a home environment, an office environment or as a server farm), while in other embodiments the processors may be distributed across a number of locations.

(106) The one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a SaaS. For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., APIs).

(107) Example embodiments may be implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations of them. Example embodiments may be implemented using a computer program product, e.g., a computer program tangibly embodied in an information carrier, e.g., in a machine-readable medium for execution by, or to control the operation of, data processing apparatus, e.g., a programmable processor, a computer, or multiple computers.

(108) A computer program can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, subroutine, or other unit suitable for use in a computing environment. A computer program can be deployed to be executed on one computer or on multiple computers at one site or distributed across multiple sites and interconnected by a communication network.

(109) In example embodiments, operations may be performed by one or more programmable processors executing a computer program to perform functions by operating on input data and generating output. Method operations can also be performed by, and apparatus of example embodiments may be implemented as, special purpose logic circuitry (e.g., a FPGA or an ASIC).

(110) The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other. In embodiments deploying a programmable computing system, it will be appreciated that both hardware and software architectures require consideration. Specifically, it will be appreciated that the choice of whether to implement certain functionality in permanently configured hardware (e.g., an ASIC), in temporarily configured hardware (e.g., a combination of software and a programmable processor), or a combination of permanently and temporarily configured hardware may be a design choice. Below are set out hardware (e.g., machine) and software architectures that may be deployed, in various example embodiments.

(111) FIG. 10 is a block diagram of a machine in the example form of a computer system **1000** within which instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed. In alternative embodiments, the machine operates as a standalone device or may be connected (e.g., networked) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client machine in server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine may be a personal computer (PC), a tablet PC, a set-top box (STB), a Personal Digital Assistant (PDA), a cellular telephone, a web appliance, a network router, switch or bridge, or any machine capable of executing instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

(112) Example computer system **1000** includes a processor **1002** (e.g., a central processing unit (CPU), a graphics processing unit (GPU), or both), a main memory **1004**, and a static memory **1006**, which communicate with each other via a bus **1008**. Computer system **1000** may further include a video display device **1010** (e.g., a liquid crystal display (LCD) or a cathode ray tube (CRT)). Computer system **1000** also includes an alphanumeric input device **1012** (e.g., a keyboard), a user interface navigation device **1014** (e.g., a mouse or touch sensitive display), a disk drive unit **1016**, a signal generation device **1018** (e.g., a speaker), and a network interface device **1020**.

(113) Disk drive unit **1016** includes a machine-readable medium **1022** on which is stored one or more sets of instructions and data structures (e.g., software) **1024** embodying or utilized by any one or more of the methodologies or functions described herein. Instructions **1024** may also reside, completely or at least partially, within main memory **1004**, within static memory **1006**, and/or within processor **1002** during execution thereof by computer system **1000**, with main memory **1004** and processor **1002** also constituting machine-readable media.

(114) While machine-readable medium **1022** is shown in an example embodiment to be a single medium, the term “machine-readable medium” may include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more instructions or data structures. The term “machine-readable medium” shall also be taken to include any tangible medium that is capable of storing, encoding or carrying instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present technology, or that is capable of storing, encoding or carrying data structures utilized by or associated with such instructions. The term “machine-readable medium” shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media. Specific examples of machine-readable media include non-volatile memory, including by way of example semiconductor memory devices, e.g., Erasable Programmable Read-Only Memory (EPROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), and flash memory devices; magnetic disks such as internal hard disks and removable disks;



magneto-optical disks; and CD-ROM and DVD-ROM disks.

(115) Instructions **1024** may further be transmitted or received over a communications network **1026** using a transmission medium. Instructions **1024** may be transmitted using network interface device **1020** and any one of a number of well-known transfer protocols (e.g., HTTP). Examples of communication networks include a local area network (LAN), a wide area network (WAN), the Internet, mobile telephone networks, Plain Old Telephone (POTS) networks, and wireless data networks (e.g., WiFi and WiMAX networks). The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such software.

(116) Although an embodiment has been described with reference to specific example embodiments, it will be evident that various modifications and changes may be made to these embodiments without departing from the scope of the technology. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense. The accompanying drawings that form a part hereof, show by way of illustration, and not of limitation, specific embodiments in which the subject matter may be practiced. The embodiments illustrated are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed herein. Other embodiments may be utilized and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. This Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

(117) Such embodiments of the inventive subject matter may be referred to herein, individually and/or collectively, by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept if more than one is in fact disclosed. Thus, although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description.

## Claims

1. A system, comprising: a memory having instructions embodied thereon; and one or more processors configured by the instructions to perform operations comprising: receiving, by a second server having one or more processors and via a network, a data transfer request from a client device providing a second user interface to a second user, the data transfer request being associated with a first user, the first user being associated with a first entity server and the second user being associated with a second entity server; automatically adding a request identifier to the data transfer request, the request identifier uniquely identifying the data transfer request from other requests; automatically sending, from the second server via the network, the data transfer request to a third server, the first user having a first server account registered with a first server and the second user having a second server account registered with the second server; sending the data transfer request from the third server to the first server; presenting the data transfer request in a first user interface to the first user, the first user interface being provided by the first server; when the first user approves the data transfer request in the first user interface, automatically sending a request, from the first server to the third server and via the network, to make a transfer from the first server account in the first entity server to the second server account in the second entity server based on the request identifier; automatically sending a notification to the second server via the network,

from the second entity server, of a completion of the data transfer request; and automatically sending a notification to the first server via the network, from the first entity server, of the completion of the data transfer request, and providing a notification in the second user interface of the second user that the data transfer request was completed.

2. The system of claim 1, wherein the operations further comprise: sending, from the first server to the second server, and identifier associated with a completion of the data transfer request.
3. The system of claim 1, wherein the operations further comprise: after the first user approves the data transfer request, sending the data transfer request from the third server to the first entity server.
4. The system of claim 1, wherein the operations further comprise: after the first user approves the data transfer request, sending the data transfer request from the third server to the second entity server.
5. The system of claim 1, wherein the data transfer request includes a detail link, the detail link configured to direct a browser of the client device to request transaction detail information from the second server via a network, the transaction detail information including transaction information for the data transfer request.
6. The system of claim 5, wherein the operations further comprise: responsive to receiving a request for transaction detail from the detail link, causing presentation of the data transfer request, the request identifier, and the transaction detail information at the client device.
7. A system, comprising: a memory having instructions embodied thereon; and one or more processors configured by the instructions to perform operations comprising: receiving, by a second server having one or more processors and via a network, a data transfer request from a client device providing a second user interface to a second user, the data transfer request being associated with a first user, the first user having a first account with a first entity server and the second user having a second account with a second entity server; automatically adding a request identifier to the data transfer request, the request identifier uniquely identifying the data transfer request from other requests; automatically sending, from the second server via the network, the data transfer request to a first server associated with a first user, the first server **39** providing a first user interface to the first user; presenting, by the first server, the data transfer request in the first user interface to the first user; when the first user approves the data transfer request in the first user interface, automatically sending a request, from the first server to the first entity server and via the network, to make a transfer from the first account in the first server to the second account in the second entity server based on the request identifier; automatically sending a notification to the second server via the network, from the second entity server, of a completion of the data transfer request; automatically sending a notification to the first server via the network, from the first entity server, of the completion of the data transfer request; and providing a notification in the second user interface of the second user that the data transfer request was completed.
8. The system of claim 7, wherein the operations further comprise: presenting, in the second user interface, one or more pending transactions; receiving a selection from the one or more pending transactions; and generating the data transfer request based on the selection.
9. The system of claim 7, wherein the operations further comprise: automatically modifying a status indicator of the data transfer request to reflect receipt of a movement response.
10. The system of claim 7, wherein the operations further comprise: automatically verifying, by the first server, completion of the data transfer request.
11. The system of claim 10, wherein automatically verifying completion of the data transfer request further comprises: transmitting a movement confirmation request to the second entity server; receiving, by the first server, a confirmation notification including the data transfer request and the request identifier; and matching the confirmation notification to the data transfer request.
12. The system of claim 7, wherein the data transfer request includes a detail link, the detail link configured to direct a browser of the client device to request transaction detail information from the first server via a network, the transaction detail information including transaction information for

the data transfer request.

13. The system of claim 12, wherein the operations further comprise: responsive to receiving a request for transaction detail from the detail link, causing presentation of the data transfer request, the request identifier, and the transaction detail information at the client device.

14. A system, comprising: a memory having instructions embodied thereon; and one or more processors configured by the instructions to perform operations comprising: receiving, by a first server having one or more processors and via a network, a data movement request; automatically appending, by the first server, a unique request code to the data movement request, the unique request code uniquely identifying the data movement request from other data movement requests; sending, from the first server via the network, the data movement request and the unique request code to a first entity server; automatically presenting the data movement request at a client device associated with the first entity server; sending, from the first entity server via the network, the data movement request to a third server; automatically receiving, by the first server via the network, a movement response from the third server, the movement response indicating a first interaction between the first entity server and the third server and a second interaction between the third server and a second entity server; automatically modifying a status indicator of the data movement request to reflect receipt of the movement response; and automatically verifying, by the first server, completion of the data movement request, the verifying comprising: transmitting, via the network, a movement confirmation request to the second entity server; receiving, by the first server via the network, a confirmation notification including the data movement request and the unique request code; and matching the confirmation notification to the data movement request.

15. The system of claim 14, wherein the status indicator is representative of an unreconciled status of the data movement request.

16. The system of claim 14, wherein the operations further comprise: responsive to the receiving of the data movement request, generating the unique request code.

17. The system of claim 14, wherein the data movement request includes a detail link, the detail link configured to direct a browser of the client device to request transaction detail information from the first server via a network, the transaction detail information including transaction information for the data movement request.

18. The system of claim 17, wherein the operations further comprise: responsive to receiving a request for transaction detail from the detail link, causing presentation of the data movement request, the unique request code, and the transaction detail information at the client device.

19. The system of claim 14, wherein the operations further comprise: generating a notification of receipt containing confirmation of receipt of the movement response from a second server; and transmitting, by the second server, the notification of receipt to the client device via a network.

20. A non-transitory machine-readable storage medium comprising processor executable instructions that, when executed by a processor of a machine, cause the machine to perform operations comprising: receiving, by a second server having one or more processors and via a network, a data transfer request from a client device providing a second user interface to a second user, the data transfer request being associated with a first user, the first user being associated with a first entity server and the second user being associated with a second entity server; automatically adding a request identifier to the data transfer request, the request identifier uniquely identifying the data transfer request from other requests; automatically sending, from the second server via the network, the data transfer request to a third server, the first user having a first server account registered with a first server and the second user having a second server account registered with the second server; sending the data transfer request from the third server to the first server; presenting the data transfer request in a first user interface to the first user, the first user interface being provided by the first server; when the first user approves the data transfer request in the first user interface, automatically sending a request, from the first server to the third server and via the network, to make a transfer from the first server account in the first entity server to the second

server account in the second entity server based on the request identifier; automatically sending a notification to the second server via the network, from the second entity server, of a completion of the data transfer request; and automatically sending a notification to the first server via the network, from the first entity server, of the completion of the data transfer request; and providing a notification in the second user interface of the second user that the data transfer request was completed.

21. A non-transitory machine-readable storage medium comprising processor executable instructions that, when executed by a processor of a machine, cause the machine to perform operations comprising: receiving, by a second server having one or more processors and via a network, a data transfer request from a client device providing a second user interface to a second user, the data transfer request being associated with a first user, the first user having a first account with a first entity server and the second user having a second account with a second entity server; automatically adding a request identifier to the data transfer request, the request identifier uniquely identifying the data transfer request from other requests; automatically sending, from the second server via the network, the data transfer request to a first server associated with a first user, the first server **39** providing a first user interface to the first user; presenting, by the first server, the data transfer request in the first user interface to the first user; when the first user approves the data transfer request in the first user interface, automatically sending a request, from the first server to the first entity server and via the network, to make a transfer from the first account in the first server to the second account in the second entity server based on the request identifier; automatically sending a notification to the second server via the network, from the second entity server, of a completion of the data transfer request; automatically sending a notification to the first server via the network, from the first entity server, of the completion of the data transfer request; and providing a notification in the second user interface of the second user that the data transfer request was completed.

22. A non-transitory machine-readable storage medium comprising processor executable instructions that, when executed by a processor of a machine, cause the machine to perform operations comprising: receiving, by a first server having one or more processors and via a network, a data movement request; automatically appending, by the first server, a unique request code to the data movement request, the unique request code uniquely identifying the data movement request from other data movement requests; sending, from the first server via the network, the data movement request and the unique request code to a first entity server; automatically presenting the data movement request at a client device associated with the first entity server; sending, from the first entity server via the network, the data movement request to a third server, automatically receiving, by the first server via the network, a movement response from the third server, the movement response indicating a first interaction between the first entity server and the third server and a second interaction between the third server and a second entity server; automatically modifying a status indicator of the data movement request to reflect receipt of the movement response; and automatically verifying, by the first server, completion of the data movement request, the verifying comprising: transmitting, via the network, a movement confirmation request to the second entity server; receiving, by the first server via the network, a confirmation notification including the data movement request and the unique request code; and matching the confirmation notification to the data movement request.

---