

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12386183
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Aburmad; Shimon et al.

---

### Head-mounted image display system

---

#### Abstract

The presently disclosed subject matter aims to a head-mounted display (HMD) system including: (i) an image source configured to project one or more light beams associated with one or more respective images, (ii) a first optical element, including (a) a first receiving surface, (b) a first reflective element, and (c) a first projecting surface, at least one of which possesses optical power; (iii) a second optical element including (d) a second receiving surface, (e) a second reflective element, and (f) a second projecting surface, at least one of which possesses optical power; and (iv) an at least partially reflective element configured to enable the displaying of the one or more produced images to the user's eye while allowing said user to continue seeing the real world.

---

**Inventors:** Aburmad; Shimon (Haifa, IL), Charny; Adi (Haifa, IL), Gil; Yotam (Haifa, IL), Ben Ishai; Liad (Haifa, IL), Toledano; Yaniv (Haifa, IL)

**Applicant:** ELBIT SYSTEMS LTD. (Haifa, IL)

**Family ID:** 1000008749754

**Assignee:** ELBIT SYSTEMS LTD. (Haifa, IL)

**Appl. No.:** 19/054966

**Filed:** February 17, 2025

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20250199318 A1	Jun. 19, 2025

#### Foreign Application Priority Data

IL	305075	Aug. 08, 2023
----	--------	---------------

#### Related U.S. Application Data

Publication Classification

Int. Cl.: G02B27/01 (20060101); G02B17/08 (20060101)

U.S. Cl.:

CPC G02B27/0172 (20130101); G02B17/0856 (20130101);

Field of Classification Search

CPC: G02B (27/0172); G02B (17/0856); G02B (27/01); G02B (27/0101); G02B (27/0103); G02B (27/0149); G02B (27/017); G02B (27/0176); G02B (27/0179); G02B (27/0189); G02B (2027/0105); G02B (2027/0107); G02B (2027/0109); G02B (2027/011); G02B (2027/0112); G02B (2027/0114); G02B (2027/0116); G02B (2027/0118); G02B (2027/012); G02B (2027/0121); G02B (2027/0123); G02B (2027/0125); G02B (2027/0127); G02B (2027/0129); G02B (2027/013); G02B (2027/0132); G02B (2027/0134); G02B (2027/0136); G02B (2027/0138); G02B (2027/0141); G02B (2027/014); G02B (2027/0143); G02B (2027/0145); G02B (2027/0147); G02B (2027/015); G02B (2027/0152); G02B (2027/0154); G02B (2027/0156); G02B (2027/0158); G02B (2027/0159); G02B (2027/0161); G02B (2027/0163); G02B (2027/0165); G02B (2027/0167); G02B (2027/0169); G02B (2027/0174); G02B (2027/0178); G02B (2027/0181); G02B (2027/0183); G02B (2027/0185); G02B (2027/0187); G02B (2027/019); G02B (2027/0192); G02B (2027/0194); G02B (2027/0196); G02B (2027/0198)

USPC: 359/630

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5880888	12/1998	Schoenmakers et al.	N/A	N/A
6147807	12/1999	Droessler et al.	N/A	N/A
6201646	12/2000	Togino et al.	N/A	N/A
6310736	12/2000	Togino	N/A	N/A
6487021	12/2001	Ophey	N/A	N/A
6504658	12/2002	Bignolles et al.	N/A	N/A
2002/0034016	12/2001	Inoguchi et al.	N/A	N/A
2003/0002166	12/2002	Wilmington	359/629	G02B 27/01
2004/0090683	12/2003	Nagata	N/A	N/A
2004/0119664	12/2003	Inoguchi	345/8	G02B 27/0172
2005/0219671	12/2004	Inoguchi et al.	N/A	N/A
2009/0180194	12/2008	Yamaguchi et al.	N/A	N/A
2009/0231722	12/2008	Filipovich et al.	N/A	N/A
2010/0109977	12/2009	Yamazaki et al.	N/A	N/A

2011/0175799	12/2010	Yamada et al.	N/A	N/A
2012/0229367	12/2011	Magyari	N/A	N/A
2014/0160576	12/2013	Robbins	N/A	N/A
2014/0375789	12/2013	Lou et al.	N/A	N/A
2015/0153575	12/2014	Komatsu et al.	N/A	N/A
2015/0168730	12/2014	Ashkenazi et al.	N/A	N/A
2015/0177519	12/2014	Cakmakci et al.	N/A	N/A
2017/0276946	12/2016	Yokoyama	N/A	G02B 5/10
2018/0335628	12/2017	Hung et al.	N/A	N/A
2019/0278088	12/2018	Asaf et al.	N/A	N/A
2020/0018966	12/2019	Komatsu et al.	N/A	N/A
2020/0081235	12/2019	Takahashi et al.	N/A	N/A
2021/0096338	12/2020	Saiga	N/A	N/A
2021/0373338	12/2020	Gao et al.	N/A	N/A
2022/0050299	12/2021	Hua et al.	N/A	N/A
2022/0229300	12/2021	Ashkenazi et al.	N/A	N/A
2022/0276492	12/2021	Yamaguchi	N/A	G02B 17/0856

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
206339785	12/2016	CN	N/A
4137869	12/2022	EP	N/A
2009136393	12/2008	WO	N/A
2016135727	12/2015	WO	N/A
WO-2018223150	12/2017	WO	G02B 27/0103
2020212684	12/2019	WO	N/A

*Primary Examiner:* Duong; Henry

*Attorney, Agent or Firm:* S.J. Intellectual Property Ltd.

## Background/Summary

### TECHNICAL FIELD

(1) The present invention relates to the field of head-mounted image display systems.

### BACKGROUND

(2) In recent years there has been vast development in the field of head-mounted image display systems, which led to the ability to create compact optical systems capable of displaying small-scale images (e.g., a single image or a plurality of images forming a video) at a size visible to a user's eye(s), as the user is wearing the optical system.

(3) Though numerous compact optical systems exist, these systems tend to be subjected to: (i) low efficiency (which requires that said systems be operated at high power, so as to compensate for said efficiency), (ii) occurrences of optical tolerances, (iii) events of chromatic distortion, and the like. Furthermore, these systems tend to be heavy, expensive, and difficult to manufacture, as they include components made of hefty materials such as glass and the like, which make the use of said systems burdensome.

(4) Thus, there is a need in the art for a high-quality, lightweight, and cheap head-mounted image display system.

## GENERAL DESCRIPTION

(5) In accordance with a first aspect of the presently disclosed subject matter, there is provided a head-mounted display (HMD) including at least one optical unit configured to be associated with at least one eye of a user wearing the HMD, the optical unit comprising: (a) an image source configured to project one or more light beams associated with one or more respective images; (b) a first optical element, including: (i) a first receiving surface, (ii) a first reflective element, and (iii) a first projecting surface, wherein at least one of the first projecting surface, the first reflective element, and the first receiving surface possesses optical power; (c) a second optical element including: (i) a second receiving surface, (ii) a second reflective element, and (iii) a second projecting surface, wherein at least one of the second projecting surface, the second reflective element, and the second receiving surface possess optical power; and (d) an at least partially reflective element configured to enable the displaying of the one or more produced images to the user's eye while allowing the user to continue seeing the real world; wherein light beams projected from the image source travel along an optical path extending between the image source and the user's eye, by traveling through the first optical element and then through the second optical element towards the partially reflective element, and wherein the one or more respective images associated with the one or more light beams are reflected from the partially reflective element and are viewed by the user's eye.

(6) In some cases, along the optical path an intermediate image is being formed.

(7) In some cases, the intermediate image is formed in the second optical element.

(8) In some cases, a pseudo-stop is formed in the first optical element, such that a reduction in size of the optical element is achieved.

(9) In some cases, (i) the at least one optical unit further comprising a first lens composed of a first surface and a second surface, and (ii) the first lens is positioned therebetween the first optical element and the image source.

(10) In some cases, (i) the at least one optical unit further comprising a second lens composed of a third surface and a fourth surface, and (ii) the second lens is positioned therebetween the first and second optical elements.

(11) In some cases, (i) the at least one optical unit further comprising a first lens and a second lens positioned therebetween the first optical element and the image source and the first and second optical elements, respectively, (ii) the first lens is composed of a first surface and a second surface, and (iii) the second lens is composed of a third surface and a fourth surface.

(12) In some cases, at least one of the first and second optical elements of the at least one optical unit is a prism.

(13) In some cases, the optical path of the at least one optical unit is extending vertically, along the y-axis.

(14) In some cases, the optical path of the at least one optical unit is extending horizontally, along the x-axis.

(15) In some cases, the first and second reflective surfaces of the at least one optical unit are of bi-conical or freeform form.

(16) In some cases, the first and second optical elements of the at least one optical unit are joined together by coupling the first projecting surface and the second the receiving surface, so as to form a single optical element.

(17) In some cases, the first and second optical elements of the at least one optical unit are found to be at a distance from one another.

(18) In some cases, the first projecting surface, the first reflective surface, and the first receiving surface all possess optical power.

(19) In some cases, the second projecting surface, the second reflective surface, and the second

receiving surface all possess optical power.

(20) In some cases, the at least partially reflective element includes a semi-reflective mirror coating placed on one of the reflective element's surfaces.

(21) In some cases, the at least partially reflective element includes a semi-reflective mirror coating placed between the reflective element's surfaces, such that the semi-reflective mirror enables improved correction of see-through distortions.

(22) In some cases, the at least partially reflective element further includes an intermediate tilted surface capable of reducing the at least partially reflective element's tilt angle so as enable the wearing of an eye wear, while the HMD is worn.

(23) In some cases, the at least partially reflective element is coupled with a variable transmission mechanism enabling the adaptation of the reflective element to changing light conditions.

(24) In some cases, the at least partially reflective element is coated with an electrochromic or photochromatic polymer, enabling the adaptation of the reflective element to changing light conditions.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to understand the presently disclosed subject matter and to see how it may be carried out in practice, the subject matter will now be described, by way of non-limiting examples only, with reference to the accompanying drawings, in which:

(2) FIGS. 1A to 1D are schematic illustrations of an exemplary Head Mounted Display (HMD) system, in accordance with the presently disclosed subject matter;

(3) FIGS. 2A to 2C are schematic illustrations of an exemplary at least partially reflective element of a Head Mounted Display (HMD) system, in accordance with the presently disclosed subject matter; and,

(4) FIG. 3 is a schematic illustration of an exemplary optical element of a Head Mounted Display (HMD) system, in accordance with the presently disclosed subject matter.

### DETAILED DESCRIPTION

(5) In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the presently disclosed subject matter. However, it will be understood by those skilled in the art that the presently disclosed subject matter may be practiced without these specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the presently disclosed subject matter.

(6) In the drawings and descriptions set forth, identical reference numerals indicate those components that are common to different embodiments or configurations.

(7) As used herein, the phrase “for example,” “such as”, “for instance” and variants thereof describe non-limiting embodiments of the presently disclosed subject matter. Reference in the specification to “one case”, “some cases”, “other cases” or variants thereof means that a particular feature, structure or characteristic described in connection with the embodiment(s) is included in a least one embodiment of the presently disclosed subject matter. Thus, the appearance of the phrase “one case”, “some cases”, “other cases” or variants thereof does not necessarily refer to the same embodiment(s).

(8) It is appreciated that, unless specifically stated otherwise, certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the presently disclosed subject matter, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination.

(9) Any reference in the specification to a system should be applied mutatis mutandis to a method

that may be executed by the system and should be applied mutatis mutandis to a non-transitory computer readable medium that stores instructions that may be executed by the system.

(10) Bearing this in mind, attention is drawn to FIG. 1A, showing a schematic illustration of a Head Mounted Display (HMD) system, in accordance with the presently disclosed subject matter.

(11) As shown in the schematic illustration, HMD system **100**, which may be a stand-alone apparatus (e.g., an optical monocular, optical glasses, optical binoculars, and the like) or a component of a headgear (e.g., a helmet, and the like), contains one or more optical units, denoted **102**, which may operate dependently or independently of one another. As illustrated in FIG. 1B, each optical unit **102** may be composed of: (i) an image source **104**, (ii) a first optical element **106**, (iii) a second optical element **108**, and (iv) an at least partially reflective element **110**.

(12) In a first non-limiting example, the HMD system **100** may be an optical monocular composed of a single optical unit **102** mounted in front of a user's eyes. In a second non-limiting example, the HMD system **100** may be an optical binocular composed of two separate optical units **102**, each of which is mounted in front a different eye of the user, enabling displaying to said user's eyes either a fully overlapped output, a partially overlapped output, or a non-overlapped output.

(13) In some cases, HMD system **100** may include an inter-pupillary distance (IPD) adjustment mechanism (not shown) directed to enable mechanical adaptation of the positioning of the one or more optical units **102**, both to the pupil(s) of the user's eye(s) and relative to each other. The inter-pupillary distance (IPD) adjustment mechanism may include a mechanical mean, such as a pulley, and the like, intended to enable said mechanical adaptation's operation.

(14) Attention is now directed to each of components **104** to **110**.

(15) Initially, reference is made to image source **104**. Image source **104**, which may be, for example, a projector such as an LCD projector, an OLED projector, a Micro LED projector, an LCOS projector, and the like, may be directed to produce small-scale images intended to be displayed to the user's eye(s), at a certain visual size and/or distance. As illustrated in FIGS. 1B-1D, the produced small-scale images may be associated with one or more light beams, denoted **112**, directed to travel along an optical path **114**, at the end of which the produced small-scale images are displayed on the user's eye(s) (e.g., the user's eye(s) retina, as will be explained in detail hereinafter).

(16) Image source **104** may be situated on different surfaces of HMD system **100** (e.g., the top surface, the bottom surface, side surfaces, etc.), such that the optical path through which the one or more light beams **112** travel to the user's eye(s) may extend along various spatial axes of the HMD system **100** (e.g., (i) the x-axis, extending between the user's ears, (ii) the z-axis, extending from the HMD system **100** towards the horizon, perpendicular to x-axis, or (iii) the y-axis, extending perpendicular to the x-axis and z-axis), in each of their directions (e.g., top-bottom, bottom-top, left-right, right-left, etc.). In one non-example, as illustrated in FIG. 1A, image source **104** may be situated on the top surface of HMD system **100**, denoted **116**, above the user's eye, such that the small-scale images may be projected to the user's eye(s) vertically, from top to bottom, along the HMD system's y-axis.

(17) In some cases, in addition to its innate projecting capabilities, image source **104** may possess sensing capabilities, enabling it to track the user's eye(s) along similar optical path as the projected light beams and adjust the image projection it produces accordingly.

(18) In other cases, alternatively or additionally to the former, eye-sensing capabilities may be added by exploiting the void inherently generated above the second element **108** (i.e., above second reflective surface **132**, presented hereinafter). In one non-limiting example, as illustrated in FIG. 3, this may be achieved by the second reflective surface **132**, presented hereinafter, being a semi-reflective mirror configured to reflect the visible light while transmitting light in the near IR (NIR) wavelength range. In cases of such type, a NIR light source **302** and a sensor coupled with appropriate optics **304** may be placed within said void so as to capture the eye/iris/pupil and allow eye sensing (e.g., pupil tracking, blinking, and such).

(19) Similarly, in a second non-limiting example, the same can be achieved by converting the first reflective surface **120**, presented hereinafter in relation to the first optical element **106**, to a semi-reflective mirror, and placing a NIR light source and a sensor coupled with appropriate optics behind said surface.

(20) Next, reference is made to the first optical element **106**. First optical element **106**, which may be positioned within a projection range of image source **104**, may be composed of: (i) a first receiving surface **118**, (ii) a first reflective surface **120**, and (iii) a first projecting surface **122**.

(21) Each of said surfaces may possess optical power, originating from the surface's shape (which may be, for example, of concave or convex form), enabling it to cause a change in the propagation direction of the light beams refracting therethrough the first optical element **106** and direct them forward along the optical path **114**. In one non-limiting example, the first optical element **106** may be a bi-conic optical prism composed of surfaces having optical power intended to direct light beams refracting through optical element **106** toward the second optical element **108**.

(22) In some cases, the first optical element **106** may be situated adjacent to the image source **104**, creating little to no space between both elements. In such cases, the little to no space between the image source **104** and the first optical element **106** enables the latter to gather all the light beams transmitted from said image source, thereby enabling maximal energy exploitation.

(23) In other cases, alternatively to the above, as illustrated in FIG. 1C, the space between the image source **104** and the first optical element **106** may be occupied by a first lens **124**, composed of a first surface **126** and a second surface **128**, situated adjacent to the image source **104**. The first lens **124** may be directed to gather all the light beams transmitted from said image source and direct them toward the first optical element **106**.

(24) Aside from preventing any rays from escaping said first optical element **106** (thereby increasing the optical efficiency of the design), adding optical components (e.g., first lens **124**) to the design, at any point of said design, may enhance the image quality.

(25) It is to be of note that the description above serves as a mere example and that the first optical element **106** may include fewer or more surfaces than those described hereinbefore.

(26) Reference is now made to the second optical element **108**. Second optical element **108**, which may be positioned within a projection range of the first optical element **106**, may be composed of: (iv) a second receiving surface **130**, (v) a second reflective surface **132**, and (vi) a second projecting surface **134**. Each of said surfaces may possess optical power, originating from the surface's shape (which can be, for example, of concave or convex form), enabling it to cause a change in the propagation direction of the light beams refracting therethrough the second optical element **108**, and direct them forward along the optical path **114**. In a non-limiting example, the second optical element **108** may be a bi-conic optical prism composed of surfaces having optical power intended to direct light beams refracting through optical element **108**, toward the at least partially reflective element **110**.

(27) In some cases, each of surfaces **130** to **134** may have a relatively large aperture size, allowing for a larger EMB (Eye Motion Box), thereby eliminating the need for the optical unit(s) to be precisely in line with the user's pupil(s). In addition, we define a point within the optical system, where all the rays converge so that they almost cover the same area, as a "pseudo-stop". As illustrated, for example, in FIG. 1B, such a point is realized in area A1. By implementing a pseudo-stop in area A1, a reduction in size of optical element **106** may be achieved. Moreover, a smaller pseudo-stop may improve image quality as well as result in a smaller aperture of surfaces **118** to **122** relative to surfaces **130** to **134**. The reduction in size of first optical element **106** may prevent it from obstructing the user's vision, for example, as the user is looking upwards.

(28) It is to be of note that the description above serves as a mere example and that the second optical element **108** may include fewer or more surfaces than those described hereinbefore.

(29) In some cases, the second optical element **108** may be situated adjacent to the first optical element **106**, creating little to no space between both elements. In such cases, the little to no space

between the first optical element **106** and the second optical element **108** enables the latter to gather all the light beams that traveled from said optical element **106** to it, thereby enabling maximal energy exploitation.

(30) In other cases, alternatively to the above, as illustrated in FIG. 1C, the space between the first optical element **106** and the second optical element **108** may be occupied by a second lens **136**, composed of a third surface **138** and a fourth surface **140**, situated adjacent to the first optical element **106**. The second lens **136** may be directed to gather all the light beams exiting said optical element **106** and direct them towards said optical element **108**, in a relatively straight manner, while preventing the escape of any rays from said second optical element **108** (thereby improving image quality and increasing the optical efficiency of the design).

(31) In additional cases, alternatively to the above, as illustrated in FIG. 1D, the first optical element **106** and the second optical element **108** may be joined together by coupling the first projecting surface **122** to the second receiving surface **130**, so as to form a single unified optical element, denoted **141**.

(32) It is important to note that by using a multi-surface element, such as first optical element **106**, second optical element **108**, and/or single optical element **141**, having a plurality of surfaces fixed to one another as part of the optics manufacturing process, the relative positioning tolerances between said surfaces may be reduced. This feature is enhanced as the number of surfaces increases.

(33) Reference is now made to the at least partially reflective element **110**. The at least partially reflective element **110** (e.g., a visor, and the like), which may be positioned within a first projection range from the second optical element **108** and a second projection range from the user's eye, may be partially reflective and partially transparent, such that it may enable the displaying of the one or more produced images to the user, while allowing said user to continue seeing the real world.

(34) In some cases, as illustrated in FIGS. 2A to 2C, the at least partially reflective element **110** may include a semi-reflective mirror coating **142** placed on either: (i) the surface closer to the user's eye(s) (surface **144**, shown in FIG. 2A), (ii) the surface farther from the user's eye(s) (surface **146**, shown in FIG. 2B), or (iii) between said surfaces (surface **148**, shown in FIG. 2C).

(35) In cases where the semi-reflective mirror is placed on the surface farther from the user's eye(s) (i.e. surface **146**), the light beams **112** may be refracted by surface **144** and then reflected by the semi-reflective mirror at surface **146**. In addition, see-through light beams, denoted **112'**, associated with see-through images of the user's surrounding, may be refracted twice, a first time by surface **144** and a second time by surface **146**. Such a scenario allows the at least partially reflective element **110** to possess a stronger optical effect on the projected image rays (i.e., light beams **112**).

(36) Alternatively, in cases where the semi-reflective mirror coating **142** is placed between the surfaces (i.e., FIG. 2C), in addition to the double refraction attribute described above, the semi-reflective mirror may allow improved correction of see-through distortions, by decoupling the reflection from surface **148** of the projected image, associated with light beams **112**, as well as the see-through images, associated with said see-through light beams. Moreover, including an intermediate tilted surface (i.e., surface **148**) within said at least partially reflective element **110** may allow the reduction of the tilt angle of the whole element (as illustrated by the dashed lines, denoted **150**, in FIG. 2C). Reduced tilt angle may allow a more comfortable use of an eyewear, e.g., eye glasses, night vision goggles, and the like, while wearing the HMD system **100**.

(37) In some cases, the at least partially reflective element **110** may be coupled with a variable transmission mechanism enabling the adaptation of the reflective element to changing conditions, e.g., light conditions. In other cases, the at least partially reflective element **110** may be coated with an electrochromic and/or photochromatic polymer, which may also enable the adaptation of the reflective element to the changing conditions. Both the variable transmission mechanism and the electrochromic and/or photochromatic coating may allow displaying of designated output (e.g., the one or more produced images) to the user's eye without impairing the output's quality in light of the



changing conditions.

(38) Attention is now directed to several non-limiting examples of potential optical paths, each associated with a respective schematic illustration of the schematic illustrations presented hereinbefore in relation to HMD system **100**.

(39) By way of a first non-limiting example (presented merely for purposes of better understanding the disclosed subject matter and not in any way intended to limit its scope), in accordance with the illustration presented in FIG. **1B**, the optical path **114** of one or more light beams **112**, associated with one or more small-scale images produced by the image source **104**, may be as follows: (a) Initially, the one or more light beams **112** travel from the image source **104** toward the first optical element **106**; (b) Upon arrival at the first optical element **106**, the one or more light beams **112** refract into the cavity of the first optical element **106**, through the first receiving surface **118**, and propagate toward the first reflective surface **120**; (c) At the encounter of the one or more light beams **112** with the first reflective surface **120** (denoted “A1”), a pseudo-stop is created on surface **120**, and the one or more light beams **112** are then directed toward the first projecting surface **122**; (d) Upon reaching the first projecting surface **122**, the one or more light beams **112** refract through the first projecting surface **122** and propagate toward the second optical element **108**; (e) With the arrival of the one or more light beams **112** at the second optical element **108**, the one or more light beams **112** refract into the cavity of the second optical element **108**, through the second receiving surface **130** and propagate toward the second reflective surface **132**; (f) At the encounter of the one or more light beams **112** with the second reflective surface **132**, the one or more light beams **112** are directed towards the second projecting surface **134**, and an intermediate image within the second optical element **108** may be formed (denoted “A2”); (g) Upon reaching the second projecting surface **134**, the one or more light beams **112** refract through the second projecting surface **134** and propagate toward the at least partially reflective element **110**; (h) At the encounter of the one or more light beams **112** with the at least partially reflective element **110**, the one or more light beams **112** are reflected toward the user's eye to produce said one or more images associated with said one or more light beams **112** on the user's eye retina.

(40) By way of a second non-limiting example (presented merely for purposes of better understanding the disclosed subject matter and not in any way intended to limit its scope), in accordance with the illustration presented in FIG. **1C**, the optical path **114** of one or more light beams **112**, associated with one or more small-scale images produced by the image source **104**, may be as follows: (i) Initially, the one or more light beams **112** travel from the image source **104** to the first lens **124**; (j) Upon arrival at the first lens **124**, the one or more light beams **112** refract into the cavity of the first lens **124**, through the first surface **126**, and propagate toward the second surface **128**; (k) Once at the second surface **128**, the one or more light beams **112** refract through the second surface **128** and propagate toward the first optical element **106**; (l) Upon arrival at the first optical element **106**, the one or more light beams **112** refract into the cavity of the first optical element **106**, through the first receiving surface **118** and propagate toward the first reflective surface **120**; (m) At the encounter of the one or more light beams **112** with the first reflective surface **120**, a pseudo-stop is created on surface **120**, and the one or more light beams **112** are then directed toward the first projecting surface **122**; (n) Upon reaching the first projecting surface **122**, the one or more light beams **112** refract through the first projecting surface **122** and propagate toward the second lens **136**; (o) Once at the second lens **136**, the one or more light beams **112** refract into the cavity of the second lens **136**, through the third surface **138**, and propagate toward the fourth surface **140**; (p) With the arrival at the fourth surface **140**, the one or more light beams **112** refract through the fourth surface **140** and propagate toward the second optical element **108**; (q) Once at the second optical element **108**, the one or more light beams **112** refract into the cavity of the second optical element **108**, through the second receiving surface **130**, and propagate toward the second reflective surface **132**; (r) At the encounter of the one or more light beams **112** with the second reflective surface **132**, the one or more light beams **112** are directed towards the second

projecting surface **134**, and an intermediate image within the second optical element **108** (similar to FIG. **1B**) may be formed; (s) Upon reaching the second projecting surface **134**, the one or more light beams **112** refract through the second projecting surface **134** and propagate toward the at least partially reflective element **110**; (t) At the encounter of the one or more light beams **112** with the at least partially reflective element **110**, the one or more light **112** beams are reflected toward the user's eye to produce said one or more images associated with the one or more light beams **112** on the user's eye retina.

(41) By way of a third non-limiting example (presented merely for purposes of better understanding the disclosed subject matter and not in any way intended to limit its scope), in accordance with the illustration presented in FIG. **1D**, the optical path **114** of one or more light beams **112**, associated with one or more small-scale images produced by the image source **104**, may be as follows: (u) Initially, the one or more light beams **112** travel from the image source **104** toward the single unified optical element **141**; (v) Upon arriving at the single unified optical element **141**, the one or more light beams **112** refract into the cavity of the single unified optical element **141**, through the first receiving surface **118**, and propagate toward the first reflective surface **120**; (w) At the encounter of the one or more light beams **112** with the first reflective surface **120**, a pseudo-stop is created on surface **120**, and the one or more light beams **112** are then directed toward the second reflective surface **132** of the single unified optical element **141**; (x) At the encounter of the one or more light beams **112** with the second reflective surface **132**, the one or more light beams **112** are directed towards the second projecting surface **134**, and an intermediate image (similar to FIG. **1B**) may be formed; (y) Upon reaching the second projecting surface **134**, the one or more light beams **112** refract through the second projecting surface **134** and propagate toward the at least partially reflective element **110**; (z) At the encounter of the one or more light beams **112** with the at least partially reflective element **110**, the one or more light beams **112** are reflected toward the user's eye to produce said one or more images associated with the one or more light beams **112** on the user's eye retina.

(42) It should be noted, in relation to the non-limiting examples described hereinbefore, that the formation of the intermediate image ("A2") may occur in any stage of the passage of the one or more light beams **112** within the cavity of either the second optical element **108** or the single unified optical element **141** (i.e., prior or after the encounter of the one or more light beams **112** with the second reflective surface **132**).

(43) It should be further noted that the formation of an intermediate image ("A2") as part of the optical path may lead to the elongation of the optical design while maintaining the focal length. Such elongation may assist in (i) reducing the maximal angle of incidence within the system, thereby enabling much more widened potential optomechanical tolerances (thus improving system performance), and (ii) preventing projection optics obscuration to the user's FOV (Field of View).

(44) It should also be noted that, since during the optical path the one or more light beams **112** make a single pass through each of the various surfaces of the system **100**, as each light beam passes in its entirety, the efficiency of the system is maximal.

(45) It is to be understood that the presently disclosed subject matter is not limited in its application to the details set forth in the description contained herein or illustrated in the drawings. The presently disclosed subject matter is capable of other embodiments and of being practiced and carried out in various ways. Hence, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for designing other structures, methods, and systems for carrying out the several purposes of the present presently disclosed subject matter.

## Claims

1. A head-mounted display (HMD) including at least one optical unit configured to be associated with at least one eye of a user wearing the HMD, the optical unit comprising: (a) an image source configured to project one or more light beams associated with one or more respective images; (b) a first optical element, including: (i) a first receiving surface configured to refract light beams into a cavity of said first optical element, (ii) a first reflective surface configured to redirect light beams toward a first projecting surface, and (iii) the first projecting surface configured to refract light beams out of said first optical element's cavity, wherein said (i) to (iii) are fixed to one another, and wherein, of (i) to (iii), at least the first reflective surface possesses optical power; (c) a second optical element including: (iv) a second receiving surface configured to refract light beams into a cavity of said second optical element, (v) a second reflective surface configured to redirect light beams toward a second projecting surface, and (vi) the second projecting surface configured to refract light beams out of said second optical element cavity, wherein said (iv) to (vi) are fixed to one another, and wherein, of (iv) to (vi), at least the second reflective surface possesses optical power; and (d) a partially reflective element positioned to receive said light beams from the second projecting surface and reflect at least a portion of said light beams toward the user's eye to enable the displaying of the one or more produced images to the user's eye while allowing said user to continue seeing the real world; wherein the light beams propagate along the optical path through the first and second optical elements and the partially reflective element to produce one or more images visible to the user.
2. The head-mounted display (HMD) of claim 1, wherein along the optical path an intermediate image is being formed.
3. The head-mounted display (HMD) of claim 2, wherein the intermediate image is formed in the second optical element.
4. The head-mounted display (HMD) of claim 1, wherein (i) the at least one optical unit further comprising a first lens composed of a first surface and a second surface, and (ii) the first lens is positioned therebetween the first optical element and the image source.
5. The head-mounted display (HMD) of claim 1, wherein (i) the at least one optical unit further comprising a second lens composed of a third surface and a fourth surface, and (ii) the second lens is positioned therebetween the first and second optical elements.
6. The head-mounted display (HMD) of claim 1, wherein (i) the at least one optical unit further comprising a first lens and a second lens positioned therebetween the first optical element and the image source and the first and second optical elements, respectively, (ii) the first lens is composed of a first surface and a second surface, and (iii) the second lens is composed of a third surface and a fourth surface.
7. The head-mounted display (HMD) of claim 1, wherein at least one of the first and second optical elements of the at least one optical unit is a prism.
8. The head-mounted display (HMD) of claim 1, wherein the optical path of the at least one optical unit is extending vertically, along a y-axis.
9. The head-mounted display (HMD) of claim 1, wherein the optical path of the at least one optical unit is extending horizontally, along an x-axis.
10. The head-mounted display (HMD) of claim 1, wherein the first and second reflective surfaces of the at least one optical unit are of bi-conical or freeform form.
11. The head-mounted display (HMD) of claim 1, wherein the first and second optical elements of the at least one optical unit are joined together by coupling the first projecting surface and the second the receiving surface, so as to form a single optical element.
12. The head-mounted display (HMD) of claim 1, wherein the first and second optical elements of the at least one optical unit are found to be at a distance from one another.
13. The head-mounted display (HMD) of claim 1, wherein the first projecting surface, the first reflective surface, and the first receiving surface all possess optical power.

14. The head-mounted display (HMD) of claim 1, wherein the second projecting surface, the second reflective surface, and the second receiving surface all possess optical power.
  15. The head-mounted display (HMD) of claim 1, wherein the at least partially reflective element includes a semi-reflective mirror coating placed on one of said reflective element's surfaces.
  16. The head-mounted display (HMD) of claim 1, wherein the at least partially reflective element includes a semi-reflective mirror coating placed between said reflective element's surfaces, such that said semi-reflective mirror enables improved correction of see-through distortions.
  17. The head-mounted display (HMD) of claim 1, wherein the at least partially reflective element further includes an intermediate tilted surface capable of reducing the at least partially reflective element's tilt angle so as enable the wearing of an eye wear, while said HMD is worn.
  18. The head-mounted display (HMD) of claim 1, wherein the at least partially reflective element is coupled with a variable transmission mechanism enabling the adaptation of the reflective element to changing light conditions.
  19. The head-mounted display (HMD) of claim 1, wherein the at least partially reflective element is coated with an electrochromic or photochromatic polymer, enabling the adaptation of the reflective element to changing light conditions.
-