

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250253521

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Hou; XiaoHua et al.

---

### **BASE STATION ANTENNA WITH HIGH PERFORMANCE ACTIVE ANTENNA SYSTEM (AAS) INTEGRATED THEREIN**

---

#### **Abstract**

A base station antenna includes a first antenna having first and second spaced-apart columns of first radiating elements therein, which are configured to operate within a first frequency band. An active antenna system (AAS) is provided, which is configured to operate within a second, typically higher, frequency band. The AAS includes a second antenna within a space between the first and second columns of first radiating elements. These first radiating elements may include tilted feed stalks which support higher integration by enabling the first radiating elements to overhang at least a portion of the second antenna.

---

**Inventors:** Hou; XiaoHua (Richardson, TX), Bisiules; Peter J. (LaGrange Park, IL), Patel; Sammit (Dallas, TX)

**Applicant:** OUTDOOR WIRELESS NETWORKS LLC (Richardson, TX)

**Family ID:** 75223052

**Appl. No.:** 19/189670

**Filed:** April 25, 2025

#### **Related U.S. Application Data**

parent US continuation 18168635 20230214 parent-grant-document US 12315990 child US 19189670

parent US continuation 17203090 20210316 parent-grant-document US 11611143 child US 18168635

us-provisional-application US 62993925 20200324

---

#### **Publication Classification**

**Int. Cl.: H01Q1/24** (20060101); **H01Q1/42** (20060101); **H01Q5/307** (20150101); **H01Q5/48** (20150101); **H01Q9/16** (20060101); **H01Q21/00** (20060101); **H01Q21/26** (20060101); **H04B1/40** (20150101); **H04W88/08** (20090101)

**U.S. Cl.:**

**CPC H01Q1/246** (20130101); **H01Q1/42** (20130101); **H01Q5/307** (20150115); **H01Q5/48** (20150115); **H01Q9/16** (20130101); **H01Q21/0006** (20130101); **H01Q21/0025** (20130101); **H01Q21/26** (20130101); **H04B1/40** (20130101); **H04W88/08** (20130101)

---

## **Background/Summary**

REFERENCE TO PRIORITY APPLICATION [0001] The present application is a continuation of and claims priority to Ser. No. 18/168,635, filed Feb. 14, 2023, which is in turn is a continuation of and claims priority to Ser. No. 17/203,090, filed Mar. 16, 2021, which claims priority to U.S. Provisional Application Ser. No. 62/993,925, filed Mar. 24, 2020, the contents of which are hereby incorporated by reference herein.

### **FIELD OF THE INVENTION**

[0002] The present invention relates to radio communication systems and, more particularly, to multi-beam base station antennas (BSAs) utilized in cellular and other communication systems.

### **BACKGROUND**

[0003] Cellular communications systems are well known in the art. In a cellular communications system, a geographic area is divided into a plurality of regions that are referred to as “cells”, which are served by respective base stations. A base station may include one or more antennas that are configured to provide two-way radio frequency (“RF”) communications with mobile subscribers that are within the cell served by the base station. In many cases, each cell is divided into “sectors.” Typically, the base station antennas are mounted on a tower or other raised structure, and the radiation patterns (also referred to herein as “antenna beams”) generated by the base station antennas are directed outwardly from the tower.

[0004] A common base station configuration is a three-sector configuration in which the cell is divided into three 120° sectors in the azimuth plane to thereby provide 360° coverage. A base station antenna is provided for each sector. In a three sector configuration, the antenna beams generated by each base station antenna typically have a Half Power Beamwidth (“HPBW”) in the azimuth (horizontal) plane of about 65° so that the antenna beams provide good coverage throughout a 120° sector. Typically, each base station antenna will include one or more vertically-extending columns of radiating elements that are typically referred to as “linear arrays.” Each radiating element may have a HPBW of approximately 65°. By providing a column of radiating elements extending along the elevation (vertical) plane, the elevation HP BW of the antenna beam may be narrowed to be significantly less than 65°, with the amount of narrowing typically increasing with the length of the column in the vertical direction. The radiating elements in a linear array are often spaced apart from adjacent radiating elements by a fixed distance that varies based on the operating frequency band of the radiating elements and performance requirements for the array. The number of radiating elements included in the linear array may then be selected so that the linear array will have a length that provides a desired elevation beamwidth.

[0005] The desired elevation beamwidth for a linear array of radiating elements will depend upon the size and geography of the cell in which the base station antenna is deployed. In order to meet cellular operator requirements, base station antenna manufacturers typically sell multiple versions of many base station antenna models that have different array lengths and hence different elevation

beamwidths. For example, in some cases, it may be desirable to have a small elevation beamwidth (e.g., 10-15 degrees) in order to increase the antenna gain and/or to reduce spillover of the antenna beam into adjacent cells (as such spillover appears as interference in the adjacent cells). This requires relatively long linear arrays. In other cases, larger elevation beamwidths are acceptable, allowing the use of shorter linear arrays that have fewer radiating elements.

[0006] In order to accommodate the increasing volume of cellular communications, new frequency bands are being made available for cellular service. Cellular operators now typically deploy multi-band base station antennas that include arrays of radiating elements that operate in different frequency bands to support service in these new frequency bands. For example, most base station antennas now include both “low-band” linear arrays of radiating elements that provide service in some or all of the 617-960 MHz frequency band and “mid-band” linear arrays of radiating elements that provide service in some or all of the 1427-2690 MHz frequency band. There is also interest in deploying base station antennas that include one or more arrays of “high-band” radiating elements that operate in higher frequency bands, such as some or all of the 3.3-4.2 GHz and/or the 5.1-5.8 GHz frequency bands. The high-band arrays are often implemented as multi-column arrays of radiating elements that can be configured to perform active beamforming where the shape of the antenna beam generated by the array can be controlled to form higher directivity antenna beams that support higher throughput. When beamforming arrays are used, a beamforming radio is often mounted directly on the back of the base station antenna in order to reduce RF losses.

[0007] For example, as illustrated by FIG. 1A, a conventional base station antenna unit **10** can include a first base station antenna **12** and a second base station antenna **14**, which may be mounted using adjustable mounting brackets **16a-16c** to a vertically-extending structure, such as a pole **18** or tower, so that the two antennas **12**, **14** are closely aligned in a vertically stacked arrangement. As shown, the first and second base station antennas **12**, **14** include respective housings, which are defined in part by respective first and second radomes **22**, **24**. As will be understood by those skilled in the art, the first radome **22** may have a tube or similar shape that extends around an entire circumference of the first base station antenna **12**. Similarly, the second radome **24** may have a tube or similar shape that extends mostly around a circumference of the second base station antenna **14**, but includes a rear-side opening therein. This opening facilitates the attachment of a radio **20** to a rear surface of an antenna array (not shown) within the second base station antenna **14**. In some cases, this radio may function as a beamforming radio **20**. As shown by FIG. 1B, the radio **20** may include: a conventional transmitter/receiver circuit **32** with bidirectional signal processing and calibration control, a filter array **34** with in-line bandpass filters **34a**, and a calibration board **36** with in-line couplers **36a** and calibration signal feedback to a calibration circuit within the transmitter/receiver circuit **32**. As is further shown in FIG. 1A, the calibration board connects to an array of radiating elements **38a** of a base station antenna.

[0008] Because the requirements for the beamforming antennas are more likely subject to change, and because beamforming antennas may experience higher failure rates, cellular operators may sometimes prefer that the beamforming antennas be implemented as separate antennas. But, there are often disadvantages associated with deploying additional base station antennas. First, a separate charge typically applies for each base station antenna mounted on an antenna tower, and hence increasing the number of antennas typically results in increased installation costs. Second, cellular operators often lease space on antenna towers, and there is typically a separate leasing charge for each item of equipment mounted on the antenna tower. Third, local ordinances and/or zoning regulations may limit the number of base station antennas that can be mounted on an antenna tower, and hence additional antenna towers may need to be erected if the number of base station antennas required exceeds the number permitted by the local zoning ordinances.

[0009] When shorter base station antennas are used, it may be possible to mount two base station antennas in a vertically stacked fashion so that the two base station antennas may appear as a single antenna. For example, as disclosed in U.S. Patent Publication No. 2019/0123426, which is hereby

incorporated herein by reference, first and second base station antennas may be mounted together in a vertically stacked arrangement so that the composite base station antenna unit has the appearance of a single base station antenna. The first base station antenna may comprise, for example, a conventional dual-band base station antenna that includes low-band and mid-band arrays of radiating elements, and may have a height (i.e., the length of the antenna in the vertical direction that is perpendicular to the plane defined by the horizon when the antenna is mounted for use) in a range from about 1.0 meters to about 2.0 meters. The second base station antenna may comprise, for example, a beamforming antenna that operates in, for example, a portion of the 3.3-4.2 GHz or 5.1-5.8 GHz frequency bands. The height of the second base station antenna may be less than about 1.0 meters, for example.

#### SUMMARY

[0010] A radio unit for a base station antenna may include a filter unit having a plurality of filters and a plurality of calibration couplers therein, with the plurality of calibration couplers having respective inputs electrically coupled to corresponding outputs of the plurality of filters. A radio is also provided, which has a plurality of outputs electrically coupled to a corresponding plurality of input terminals of the plurality of filters. This radio includes a calibration circuit responsive to calibration feedback signals generated at a plurality of outputs of the plurality of calibration couplers.

[0011] A radio unit for a base station antenna according to another embodiment of the invention includes a reflector having an array of radiating elements on a front facing surface thereof, and a filter unit having a plurality of filters and a plurality of calibration couplers therein, which extend adjacent a rear facing surface of the reflector. A radio is provided, which has a plurality of outputs electrically coupled to a corresponding plurality of input terminals of the plurality of filters.

[0012] A base station antenna according to another embodiment of the invention includes a first antenna having first and second spaced-apart columns of first radiating elements therein, which are configured to operate within a first frequency band. An active antenna system (AAS) is provided, which is configured to operate within a second frequency band. The AAS includes a second antenna extending at least partially into a space between the first and second columns of first radiating elements. This second antenna includes a reflector having a two-dimensional array of second radiating elements thereon, which are arranged into a plurality of rows and a plurality of columns of the second radiating elements.

[0013] A base station antenna according to another embodiment of the invention includes a first antenna having first radiating elements therein and a first radome covering the first radiating elements. An active antenna system (AAS) is also provided, which includes a second antenna that extends at least partially into a rear-facing opening in the first antenna. The second antenna includes a reflector having a plurality of feed boards on a front facing surface thereof and a two-dimensional array of second radiating elements on the plurality of feed boards.

[0014] According to another embodiment of the invention, a base station antenna is provided, which includes a column of radiating elements supported by at least one feed board. This at least one feed board includes: a first 1-to-N phase shifter thereon having N outputs electrically coupled to a corresponding N pairs of the radiating elements at a first end of the column, and a second 1-to-N phase shifter thereon having N outputs electrically coupled to a corresponding N pairs of the radiating elements at a second end of the column, where N is a positive integer greater than one.

[0015] According to a further embodiment of the invention, a radio unit for a base station antenna includes a filter unit containing: (i) a housing having a plurality of filters and a plurality of calibration couplers therein, (ii) a plurality of radio frequency (RF) signal ports electrically coupled to corresponding outputs of the plurality of filters, and (iii) at least one radio feedback port electrically coupled to corresponding outputs of the plurality of calibration couplers. A reflector is also provided, which has at least one printed circuit feed board thereon. This feed board includes RF feed terminals responsive to signals generated at the plurality of RF signal ports. A plurality of

radiating elements are provided on the at least one printed circuit feed board.

[0016] According to another embodiment, a base station antenna is provided with a first antenna (having first radiating elements therein that are configured to operate within a first frequency band), and an active antenna system (AAS). This AAS is configured to operate within a second frequency band higher than the first frequency band. The AAS includes a filter unit, and this filter unit includes: (i) a housing having a plurality of filters and a plurality of calibration couplers therein, (ii) a plurality of radio frequency (RF) signal ports electrically coupled to corresponding outputs of the plurality of filters, and (ii) at least one radio feedback port electrically coupled to corresponding outputs of the plurality of calibration couplers. A reflector is provided, which has at least one printed circuit feed board thereon. This feed board includes RF feed terminals responsive to signals generated at the plurality of RF signal ports. A plurality of second radiating elements are provided on the at least one printed circuit feed board.

[0017] A base station antenna according to another embodiment of the invention includes a reflector having a plurality of columns of radiating elements on a front-facing surface thereof, and an at least single channel phase shifter, which extends at least a majority of the length of the plurality of columns of radiating elements and on a rear-facing surface of the reflector.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1A is a side perspective view of a pole-mounted base station antenna (BSA) with attached rear-side radio, according to the prior art.

[0019] FIG. 1B is an electrical schematic of a conventional radio unit, which may be used in the BSA of FIG. 1A.

[0020] FIG. 1C is a schematic diagram that illustrates a partitioning of modules within a base station antenna system, along with a plurality of alternative cabling and interconnect examples.

[0021] FIG. 2A is an electrical schematic of an active antenna system (AAS) according to an embodiment of the invention.

[0022] FIG. 2B is a side schematic of a portion of the AAS of FIG. 2A, according to an embodiment of the invention.

[0023] FIG. 3 is a plan view of feed boards that may be used in the AAS of FIG. 2A, according to embodiments of the invention.

[0024] FIG. 4 is an exploded view of an active antenna system (AAS) according to an embodiment of the invention.

[0025] FIG. 5 is an exploded side view of a base station antenna (BSA) with an active antenna system (AAS) according to an embodiment of the invention.

[0026] FIG. 6A is a plan view of a feed board and radiating element layout, which may be used in the AAS of FIGS. 4-5, according to an embodiment of the invention.

[0027] FIG. 6B is a side view of the feed board and radiating element layout of FIG. 6A, taken along lines 6B-6B'.

[0028] FIG. 6C is a plan view of a feed board and radiating element layout, which may be used in the AAS of FIGS. 4-5, according to an embodiment of the invention.

[0029] FIG. 6D is a plan view of a feed board and radiating element layout, which may be used in the AAS of FIGS. 4-5, according to an embodiment of the invention.

[0030] FIG. 6E is a plan view of a feed board and radiating element layout, which may be used in the AAS of FIGS. 4-5, according to an embodiment of the invention.

[0031] FIG. 6F is cross-sectional view of the BSA of FIG. 5, according to another embodiment of the invention.

[0032] FIGS. 7A-7C illustrate plan layout views of equivalent feed boards that may be utilized to

support different configurations of an active antenna system (AAS) within a base station antenna (BSA), according to an embodiment of the invention.

[0033] FIGS. **8A-8B** are end and rear-side perspective views of a base station antenna (BSA) with elongate, dual-channel, phase shifters, according to an embodiment of the invention.

[0034] FIGS. **9A-9B** are a side perspective view and plan view of a bank of filters and calibration boards, according to an embodiment of the invention.

#### DETAILED DESCRIPTION

[0035] The present invention now will be described more fully with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like reference numerals refer to like elements throughout.

[0036] It will be understood that, although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention.

[0037] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the present invention. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprising”, “including”, “having” and variants thereof, when used in this specification, specify the presence of stated features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof. In contrast, the term “consisting of” when used in this specification, specifies the stated features, steps, operations, elements, and/or components, and precludes additional features, steps, operations, elements and/or components.

[0038] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the present invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0039] Referring now to FIG. **1C**, a cascaded partitioning of modules **50** within a base station antenna system is illustrated as including, within a radio frequency (RF) transmission (Tx) path: (i) an active radio circuit **52**, (ii) a filter network **54**, (iii) calibration logic **56**, (iv) a phase shifter network **58**, (v) a feed board signal routing network **60**, and (vi) a dipole radiating array **62**. As shown, in a conventional 8TRX antenna embodiment, the module partition may include four (4) cable interconnect (e.g., coaxial cable) locations, including two locations associated with an RF radio and two locations associated with a conventional antenna configuration. In a conventional 16TRX antenna embodiment, blind mate and cable interconnects are provided with the RF radio and two sets of cable interconnects are provided with the antenna. And, in a conventional 32TRX+ antenna embodiment (i.e., 32TRX or larger), two sets of blind mate interconnects are provided with the RF radio and one set of board-to-board (B-B) interconnects are provided with the antenna.

[0040] In addition, and as described more fully hereinbelow with respect to FIGS. **2-9**, in an active antenna system (AAS) according to a first embodiment, one set of blind mate interconnects are provided between the active radio circuit **52** and the filter network **54**, and one set of board-to-

board (B-B) interconnects are provided between the calibration logic **56** and the phase shifter network **58**. In an active antenna system (AAS) according to a second embodiment, one set of blind mate interconnects are provided between the active radio circuit **52** and the filter network **54**, and one set of board-to-board (B-B) interconnects are provided between the phase shifter network **58** and the feed board signal routing network **60**.

[0041] In an active antenna system (AAS) according to a third embodiment, one set of blind mate interconnects are provided between the active radio circuit **52** and the filter network **54**, and one set of blind mate interconnects are provided between the phase shifter network **58** and the feed board signal routing network **60**. This third configuration enables the radio function to extend to and include the phase shifter network **58**. And, in an active antenna system (AAS) according to a fourth embodiment, one set of blind mate interconnects are provided between the active radio circuit **52** and the filter network **54**, and one set of board-to-board (B-B) interconnects are provided between the calibration logic **56** and the phase shifter network **58**. This fourth configuration enables the radio function to extend to and include the calibration logic **56**.

[0042] Referring now to FIGS. 2A-2B, an active antenna system (AAS) according to an embodiment of the invention is illustrated as including an eight channel transmit/receive (8T8R) radio unit **100**. This radio unit **100** includes: (i) an 8T8R radio **110**, (ii) a pair of highly integrated 4T4R filter/coupler units **120** within respective housings **121**, and (iii) an antenna **130**, which has a plurality of radiating elements **132** for transmitting (Tx) and receiving (Rx) radio frequency (RF) signals. In some embodiments, the antenna **130** may be configured to include four (4) columns of cross-polarized dipole radiating elements **132**, with each column processing two of the 8T8R radio signals at different  $+45^\circ$  and  $-45^\circ$  polarizations, for example. In other embodiments that use a 16T16R radio, the antenna **130** may be configured to include eight (8) columns of cross-polarized dipole radiating elements **132**, with each column processing two of the 16T16R radio signals at different  $+45^\circ$  and  $-45^\circ$  polarizations. In still other embodiments that use a 32T32R radio, the antenna **130** may be configured to include eight (8) columns of cross-polarized dipole radiating elements **132**, with each half-column processing two of the 32T32R radio signals at different  $+45^\circ$  and  $-45^\circ$  polarizations. And, in further embodiments that use a 64T64R radio, the antenna **130** may be configured to include eight (8) columns of cross-polarized dipole radiating elements **132**, with each quarter-column processing two of the 64T64R radio signals at different  $+45^\circ$  and  $-45^\circ$  polarizations.

[0043] As shown by FIG. 2A, the 8T8R radio **110** includes eight transmitters **112**, which generate corresponding RF signals from received baseband data, eight RF receivers **114**, which process RF signals received by the antenna **130**, and a calibration circuit **116**. As will be understood by those skilled in the art, a bidirectional signal routing circuit **118** may be provided for each transmitter **112** and receiver **114** pair. As shown, the routing circuit **118** may include a conventional arrangement of a power amplifier (PA), which supports RF signal transmission to a radio output **113**, and a low noise amplifier (LNA), which amplifies received RF signals prior to demodulation.

[0044] The output of each power amplifier is coupled to a first port of a three port circulator **118**. The second port of each circulator **118** is coupled to a respective one of the radio outputs **113**. The third port of each circulator **118** is coupled to an input of a respective transmit/receive switch **119**. The first output of each transmit/receive switch **119** is coupled to a respective one of the low noise amplifiers (LNA), while the second output is coupled to a terminating load such as a resistor. When the radio **110** is operating in a transmit mode, RF signals output by one of the power amplifiers are passed to its associated circulator **118**, and output the circulator at the second port where they are passed to radio port **113**. When the radio **110** is operating in a receive mode, received RF signals are passed from the antenna elements **132** to radio port **113**, where they are passed to circulator **118**. These received RF signals are output at the third port of the circulator **118** to the RF switch **119**, and the RF switch **119** is set to pass these signals to the low noise amplifier. When the radio **110** is operating in a transmit mode, the RF switch **119** may be set to connect the input port thereof

to the terminating load so that any residual amount of the RF energy of the RF transmit signal is passed to the load in order to protect the low noise amplifier from possible damage.

[0045] Advantageously, each of the 4T4R filter/coupler units **120** is illustrated as including a highly integrated quad-arrangement of band-pass filters **122** having antenna-side terminals/outputs **125**, which are directly coupled to respective calibration couplers **124**. As explained more fully hereinbelow, the output terminals of the calibration couplers **124** can be electrically coupled together and to a respective feedback port **117** associated with each filter/coupler unit **120**. Based on this configuration, calibration feedback signals generated by the calibration couplers **124** may be provided through a single port **117** to a strip line **115** associated with the calibration circuit **116**, in order to support transmitter (Tx) calibration. The calibration circuit **116** may also be configured to inject a respective RF signal through each of calibration couplers **124** in order to support receiver (Rx) calibration. In further embodiments, a combiner/switch matrix (not shown) may also be utilized to transfer the calibration feedback signals.

[0046] As is further shown in FIG. 2A, the calibration circuit **116** is split into two circuits, and these circuits are implemented together with the band-pass filters **122**. As a result, separate cabling connections are not required between the filter units and the calibration board, as was the case in the prior art approach shown in FIG. 1B. Two 4T4R filter/coupler units **120** are provided as this may allow each unit to be located close to its associated radiating elements, allowing the use of lower loss connections between each 4T4R filter/coupler units **120** and its associated radiating elements. Because two 4T4R filter/coupler units **120** are provided, then two connections are also required between the 4T4R filter/coupler units **120** and the calibration circuit **116** in radio **110**, as compared to a single connection in the prior art approach of FIG. 1B. This extra connection, however, is more than made up for by the smaller number of connections required in other parts of the circuit. The calibration circuit **116** may be any conventional calibration circuit that is used to detect phase and/or amplitude variations along each of the paths from the 8T8R radio to the radiating elements and to then digitally compensate for these variations.

[0047] As shown by FIG. 2B, one embodiment of a radio **110** and filter/coupler unit **120** that can be utilized within an active antenna system (AAS) **100** includes a chassis **144** (with heat sink fins **146**). In some embodiments, the radio **110** may be configured so that the circuit components illustrated by FIG. 2A are embodied on a printed circuit board (PCB) **140** within a PCB enclosure **142**. This PCB enclosure **142** may be configured with openings therein that support the inclusion of radio output ports **113** and feedback ports **117**, which are electrically coupled to a plurality of filter/coupler units **120** enclosed within respective housings **121**. While only one filter/coupler unit **120** is shown in FIG. 2B, FIG. 2A shows that four such filter/coupler units **120** may be mounted on chassis **144** in an example embodiment. Each of these filter/coupler units **120** may include a plurality of cavity-type band-pass filters **122**. Each filter **122** has an input electrically coupled to a respective one of the radio output ports **113** and an output that is electrically coupled to a respective one of the antenna-side output terminals **125** (e.g., blind mate connectors).

[0048] Additionally, each filter/coupler unit **120** includes a calibration coupler **124** integrated therein that diverts (i.e., “taps” off) a small amount of the transmitted RF energy to the printed circuit board **140**. Calibration circuitry in the form of combiners on the printed circuit board **140** combine the RF energy output from the calibration couplers **124** included in each filter/coupler unit **120** in order to generate a composite calibration signal that is passed to feedback port **117**, from which it is provided to calibration circuit **116**. Additionally, the calibration circuitry may be further configured so that each calibration coupler **124** injects RF energy into received RF signals to thereby support receiver (Rx) calibration.

[0049] Referring now to FIG. 3, an antenna **130** according to additional embodiments may utilize printed circuit feed boards **200**, which are mounted on a front-side of an antenna reflector (see, e.g., FIG. 4), to route RF feed signals (with desired phases) to radiating elements supported thereon. As shown, a feed board **200a** may be utilized in combination with twelve (12) radiating elements **132**,



which are configured as slant  $-45^\circ/+45^\circ$  cross-polarized dipole radiators **202a**, **202b** and supported on the feed board **200a** by respective feed stalks (not shown). This feed board **200a** also includes a cascaded phase shifter network to provide, in effect, a pair of 1-to-6 phase shifters that collectively support 16T16R (or 8T8R) antenna operation when eight side-by-side feed boards **200a** are used to define eight, 12-row, columns of the antenna **130**.

[0050] This cascaded phase shifter network is illustrated as including a 1-to-2 phase shifter **206a** having an input terminal responsive to  $-45^\circ$  feed signals provided to a first input port **204a** of the feed board **200a** and a pair of output terminals that are electrically coupled to respective input terminals of a corresponding pair of 1-to-3 phase shifters **208a**. As shown, the six output terminals of this first pair of 1-to-3 phase shifters **208a** are electrically coupled to corresponding pairs of slant radiators **202a** that collectively support  $-45^\circ$  radiation patterns across the eight columns. Similarly, the phase shifter network is also illustrated as including a 1-to-2 phase shifter **206b** having an input terminal responsive to  $+45^\circ$  feed signals provided to a second input port **204b** of the feed board **200a** and a pair of output terminals that are electrically coupled to respective input terminals of a corresponding pair of 1-to-3 phase shifters **208b**. And, the six output terminals of this second pair of 1-to-3 phase shifters **208b** are electrically coupled to corresponding pairs of slant radiators **202b** that collectively support  $+45^\circ$  radiation patterns across the eight columns.

[0051] According to another embodiment, a pair of half-length feed boards **200b** may be utilized in combination with the twelve pairs of dipole radiators **202a**, **202b** and two pairs of 1-to-3 phase shifters **208a**, **208b**, to collectively support a 32T32R antenna implementation when eight side-by-side pairs of feed boards **200b** are used to define eight columns of the antenna **130**. In this implementation, each of the pair of feed boards **200b** is responsive to a corresponding pair of feed signals received at the input ports **204a**, **204b**. FIG. 3 also illustrates a 64T64R antenna implementation whereby four, quarter-length, feed boards **200c** are used in each of eight columns, with three pairs of cross-polarized dipole radiators **202a**, **202b** per board **200c**. As shown, each of these quarter-length feed boards **200c** is responsive to a unique pair of feed signals provided to each input port pair **204a**, **204b**. No phase shifters are provided on the feed boards **200c**.

[0052] Referring now to FIG. 4, the 64T64R antenna implementation utilizing eight columns of quarter-length feed boards **200c** (i.e., 32 feed boards **200c** containing 3 radiating elements 132 per board) may be provided within a 64T64R active antenna system (AAS) **400**, which can operate in a relatively high frequency band (e.g., 3.3 GHz-3.8 GHz) as a beamforming antenna, for example. This AAS **400** is illustrated as including a 64T64R radio **410** (i.e., active circuit), which is mounted on an underlying heat sink **412**. According to some embodiments, the 64T64R radio **410** may include similar components to the radio **110** of FIG. 2A, but with a total of 64 pairs of transmitters/receivers (**112**, **114**) included. In addition, a  $4\times 4$  filter/coupler array **408**, which may include 16 (i.e.,  $64/4$ ) independently housed filter/coupler units **120**, is provided between the radio **410** and a rear-facing surface of a reflector **406**. This reflector **406**, which can include an 8 column $\times$ 12 row array **404** of radiating elements **132** and an  $8\times 4$  array of feed boards **200c** thereon, is enclosed by a radome and protective (e.g., waterproof) cover **402**. This AAS may operate as a fully functional and independent antenna, which can be fully calibrated and factory tested to guarantee rated performance.

[0053] Moreover, as shown by FIG. 5, this AAS **400** may be utilized in combination with a larger “passive” base station antenna **440** to thereby yield a highly integrated multi-antenna base station **500** that supports RF communication over multiple frequency bands, but does not typically require a widening of the passive base station antenna **440** to accommodate the AAS **400**. In particular, the AAS **400**, or an alternative AAS, such as a 32T32R AAS **400'**, 16T16R AAS (not shown) or a 8T8R AAS **400''**, may be configured to support: (i) efficient and reliable attachment and integration into a rear-side recess/opening **430** in the base station antenna **440**; (ii) general compatibility with the radiator layout requirements of a lower band antenna (e.g., passive antenna containing larger radiating elements); and (iii) modularized in-the-field removal/repair (or replacement/upgrade)

capability without passive antenna interference.

[0054] Although not shown in FIG. 5, the radome and protective cover **402** of FIG. **4** may be used in combination with a rear-facing protective AAS cover **414**, to provide a watertight and solar protective enclosure surrounding the AAS **400**, upon insertion into and attachment to the base station antenna **440**.

[0055] Advantageously, the degree of integration between the radiating elements **132** within an “active” AAS described herein (e.g., 64T64R, 32T32R, 16T16R, 8T8R) and the radiating elements within the larger “passive” base station antenna **440** may be increased by configuring the AAS and base station antenna **440** so that, upon attachment, the feed boards and radiating elements associated with these devices are closely aligned to each other. For example, as illustrated by FIGS. **6A-6B**, the 64T64R AAS **400** and base station antenna **440** of FIG. **5** may be configured so that, upon attachment, the quarter-length feed boards **200c** and the array **404** of radiating elements **132** thereon, which are mounted on the front surface of the reflector **406** of FIG. **4**, are closely received and “nested” within a rear-side opening in the base station antenna **440**.

[0056] In particular, FIGS. **6A-6B** illustrate 8 columns of radiating elements **132** within the AAS **400**; and each of these columns includes **12** radiating elements **132**, which are arranged into groups of 3 radiating elements **132** per quarter length feed board **200c**. First and second feed boards **442a**, **442b** of the passive base station antenna **440** are also provided, which extend closely adjacent (and are preferably planar with) the feed boards **200c** associated with the first and eighth columns of radiating elements **132** within the AAS **400**. The first and second feed boards **442a**, **442b** are each illustrated as including three (3) cross-dipole radiating elements **444**, which are configured to operate in a frequency band that is lower than the frequency band associated with the AAS **400**, such as, for example, all or part of the 617-960 MHz frequency band. As shown, the radiating elements **444** may include slant  $-45^{\circ}/+45^{\circ}$  dipole radiators **446a**, **446b** and slanted/tilted feed stalks **448**, which extend at acute angles relative to the front-facing surfaces of the feed boards **200c** (and underlying reflector **406**). The use of slanted feed stalks **448** allows for higher integration by supporting the radiators **446a**, **446b** at least partially over the first three and last three columns of the radiating elements **132** within the AAS **400**.

[0057] In this manner, the illustrated integration of the “lower frequency” radiators **446a**, **446b** as extending over the “higher frequency” radiating elements **132** somewhat mimics the configuration of a single reflector having relatively small and large radiating elements highly integrated thereon (and with a relatively compact radiator footprint), and facilitates the manufacture of a multi-antenna base station **500** having a relatively narrow width that is comparable to an otherwise equivalent base station having non-detactable arrays of relatively high band radiating elements therein.

[0058] Nonetheless, as illustrated by FIG. **6E**, the use of slanted feed stalks **448** may not be necessary when asymmetric dipole radiators, such as radiators **446a'**, **446b'** having bent arms (i.e., non-linear longitudinal axes), are utilized as radiating elements **450** on the first and second feed boards **442a**, **442b** to thereby achieve a high level of radiator integration. And, in some further embodiments, the radome **402** illustrated by FIG. **4** may be provided between the radiating elements **132** of the AAS **400** and the radiators **446a**, **446b** and slanted feed stalks **448** (of the radiating elements **444**) within the base station antenna **440**.

[0059] The same arrangement of feed boards illustrated by FIGS. **6A-6B** may also be utilized with respect to the previously described 32T32R AAS **400'** and 16T16R AAS. For example, as illustrated by FIG. **6C**, each of eight columns of 12 radiating elements **132** may be arranged into two groups of 6 radiating elements **132**, which are provided (with phase shifters (not shown)) on two half-length feed boards **200b**. The first and second feed boards **442a**, **442b** and overhanging radiating elements **444** of the base station antenna **440** are also provided, which extend closely adjacent the feed boards **200b** associated with the first and eighth columns of radiating elements **132** within the AAS **400'**, as described with respect to the embodiment of FIGS. **6A-6B**. Finally,

FIG. 6D illustrates an essentially identical configuration of feed boards and radiating elements, as described with respect to FIGS. 6A-6C; however, the feed boards **200a** are full-length feed boards (with cascaded phase shifters (not shown)), as described above with respect to FIG. 3.

[0060] Referring now to FIG. 6F, a base station antenna (BSA) **600** according to another embodiment of the invention is illustrated as including the components of the AAS **400** of FIG. 4 and components of an alternative embodiment of the passive base station antenna **440** of FIG. 5. In particular, FIG. 6F is a cross-sectional view of a BSA **600**, which includes a two-piece radome-type enclosure **602** and an interior radome/cover **604** of a detachable and field replaceable AAS, such as the AAS **400** of FIG. 4. In some embodiments, the enclosure **602** may be configured as a watertight combination of: (i) the rear-facing protective AAS cover **414**, and (ii) a radome of the passive base station antenna **440** of FIG. 5. In addition, the AAS is illustrated in more simplified form as including: a radio **606** within a chassis containing a multi-fin heatsink **608**, a filter array **610** mounted adjacent a rear side of a reflector **612**, and a multi-column array of radiators **614** thereon. And, as described hereinabove with respect to FIGS. 6A-6B, relatively low band radiating elements **616** with slanted feed stalks **618** may also be provided on respective feed boards (not shown), which are mounted to an underlying reflector **624** (that may be coplanar with the AAS reflector **612**). As further shown by FIG. 6F, relatively mid-band radiating elements **620** with slanted feed stalks **622** may be provided in close proximity to the larger radiating elements **616** and slanted feed stalks **618**. Thus, with respect to FIG. 6A, the feed boards **442a**, **442b** may be utilized to include relatively mid and low band radiating elements thereon.

[0061] According to another embodiment, the full-length and half-length feed boards **200a**, **200b** and on-board phase shifters **206a**, **206b**, **208a**, **208b** of FIG. 3 need not always be required, in combination, to implement the above-described 32T32R and 16T16R embodiments of a AAS **400**. For example, as shown by the quarter-length feed board layouts of FIGS. 7A-7C, the same feed board **200c** (i.e., same antenna design) may be used to implement each of the 64T64R, 32T32R and 16T16R radio unit embodiments, by moving the phase shifters (PS) to the radio-side of the reflector **406** shown in FIG. 4 and using blind mate connectors (not shown) to connect the phase shifters PS to the feed boards **200c**.

[0062] For example, referring to FIG. 2A and FIG. 7C, for the 16T/16R embodiment, an input of a phase shifter may be connected to each node **125**. Each phase shifter may have four outputs that are coupled to the four feed boards **200c** that form each of the eight columns of radiating elements **132**. Referring to FIG. 2A and FIG. 7B, for the 32T/32R embodiment, an input of a phase shifter may be connected to each node **125**. Each phase shifter may have two outputs that are coupled to the two feed boards **200c** that form each of the eight upper columns of radiating elements **132** and each of the eight lower columns of radiating elements **132**. As shown in FIG. 7A, in the 64T64R embodiment, the phase shifters may be omitted. Thus, in some embodiments, the phase shifters PS may be moved (and mounted) to a location extending between the 4×4 filter/coupler array **408** and a rear-side of the reflector **406** of FIG. 4.

[0063] FIGS. 8A-8B illustrate a base station antenna **800** according to another embodiment of the invention. In this embodiment a plurality of array-long dual-channel (e.g., -45°, +45°) phase shifters **806** are provided on a rear side **805** of a reflector **804** (with underside RF chokes **812**) to improve performance by at least partially eliminating the use of conventional phase cable interconnects. Nonetheless, relatively small aperture board-to-board (B-B) interconnects (not shown) may be provided, which extend through the reflector **804** to distribute feed signals to front-side feed boards, feed stalks and cross-dipole radiators, which are collectively identified by reference numeral **802**. A filter bank **810** and calibration board **808** are also provided adjacent a rear end of the phase shifters **806**. As illustrated by FIG. 8B, both the filter bank **810** and calibration board **808** are considerably shorter in length (as measured in a column length direction) relative to the phase shifters **806**. And, a spacing “h”, as measured between the calibration board **808** and a rear side **805** of the reflector **804**, may vary as a function of how the phase shifters **806**

are implemented (e.g., stripline, etc.).

[0064] According to another embodiment of the invention illustrated by FIGS. 9A-9B, an 8-wide bank of filters **902**, which may be compatible with an 8-column antenna, such as the 8-column antenna illustrated in the 32T32R AAS **400'** of FIG. 5, may be integrated with a pair of calibration boards **904** that support, among other things, efficient routing of signals between each of the filters **902** and corresponding columns within the 8-column antenna. The calibration circuitry on these boards **904** includes couplers and combiners (not shown) and functions as an electrical bridge to connect the filters **902** to the antenna, as well as adjusting the connector locations to thereby eliminate conventional cable connections.

[0065] As shown by FIG. 9A, two pairs of feed board connectors **906** are provided as board-to-board (B-B) connectors for each column of radiating elements within the 8-column antenna, with each pair being connected to a corresponding pair of input ports (e.g., **204a**, **204b** in FIG. 3) associated with a respective feed board (e.g., **200b** in FIG. 3). And, as shown by FIG. 9B, which is a plan view of the filter bank **902** and calibration boards **904** of FIG. 9A, respective pairs of metal “widening” traces **908** are provided to route signals from corresponding filter output terminals **912** to corresponding calibration board output terminals **910** at the base of each of the feed board connectors **906**, which span the full width “W” of a corresponding calibration board **904**.

[0066] In the drawings and specification, there have been disclosed typical preferred embodiments of the invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

## Claims

1. A base station antenna, comprising: a front radome; a first column of radiating elements positioned behind a right-side portion of the front radome; and a second column of radiating elements laterally spaced apart from the first column of radiating elements and positioned behind a left-side portion of the front radome, wherein at least one of the radiating elements of the first column of radiating elements comprises a titled feed stalk, and wherein at least one of the radiating elements of the second column of radiating elements comprises a titled feed stalk.
2. The base station antenna of claim 1, wherein the first column of radiating elements and the second column of radiating elements each comprise cross-dipole radiators.
3. The base station antenna of claim 1, wherein a rearwardly positioned end portion of the titled feed stalk is positioned laterally outward from a lateral position of a center of the cross-dipole radiator.
4. The base station antenna of claim 1, further comprising a multiple column array of radiating elements operating in a frequency band that is different from the first column of radiating elements and the second column of radiating elements, and wherein the multiple column array of radiating elements is positioned at least partially between the first column of radiating elements and the second column of radiating elements.
5. The base station antenna of claim 1, wherein the first column of radiating elements comprises cross-dipole radiators, and wherein some of the cross-dipole radiators of the first column of radiating elements extend in front of and across some radiators of the multiple column array of radiating elements.
6. The base station antenna of claim 1, further comprising a reflector positioned behind the first column of radiating elements and the second column of radiating elements.
7. The base station antenna of claim 1, wherein the front radome is part of a passive base station antenna housing.
8. The base station antenna of claim 7, wherein the passive base station antenna housing comprises right and left sidewalls that are orthogonal to the front radome and a rear surface that is behind the

front radome and coupled to the right and left sidewalls, wherein the right and left sidewalls have a first dimension along a first segment of the right and left sidewalls and a second dimension along a second segment of the right and left sidewalls, wherein the second segment is longitudinally spaced apart from the first segment and the second dimension is greater than the first dimension.

**9.** The base station antenna of claim 8, further comprising a multiple column array of radiating elements positioned behind the first segment.

**10.** The base station antenna of claim 9, further comprising a first reflector in the passive base station antenna housing in front of the multiple column array of radiating elements and a second reflector behind the multiple column array of radiating elements.

**11.** The base station antenna of claim 1, wherein the at least one tilted feed stalk of each of the first column and the second column of the radiating elements is arranged as a plurality of tilted feed stalks.

**12.** The base station antenna of claim 11, further comprising a third column of radiating elements positioned adjacent the first column of radiating elements, wherein the third column of radiating elements comprises at least one tilted feed stalk.

**13.** The base station antenna of claim 12, wherein the at least one tilted feed stalk of the third column of radiating elements has a front to back distance that is less than a front to back distance of the at least one tilted feed stalk of the first column of radiating elements.

**14.** The base station antenna of claim 12, wherein the first column of radiating elements comprises respective planar radiators, and wherein the third column of radiating elements comprises respective planar radiators that reside behind the respective planar radiators of the first column of radiating elements.

**15.** The base station antenna of claim 1, further comprising a first plurality of longitudinally spaced apart feed boards positioned adjacent a rearward end of the first column of radiating elements and a second plurality of longitudinally spaced apart feed boards positioned adjacent a rearward end of the second column of radiating elements.

**16.** The base station antenna of claim 1, further comprising an active antenna system comprising a multiple column array of radiating elements and a radio positioned behind the multiple column array, and wherein the active antenna system is releasably attached to a rear of a passive base station antenna housing providing the front radome.

**17.** The base station antenna of claim 16, wherein the first and second columns of radiating elements are low-band radiating elements configured to operate in at least a portion of a 617-960 MHz frequency band, and wherein the radiating elements of the multiple column array of radiating elements are higher band radiating elements configured to operate in a higher frequency band than the low-band radiating elements.

**18.** A base station antenna comprising: a first column of radiating elements; and a second column of radiating elements, wherein at least one feed stalk of a respective radiating element of the first column and/or of the second column of radiating elements comprises a feed and a base, with the base positioned rearward of the feed, wherein the feed is offset from the base.

**19.** The base station antenna of claim 18, wherein the offset is a lateral offset.

**20.** The base station antenna of claim 18, wherein the first and second column of radiating elements are cross-dipole radiating elements.

**21.** The base station antenna of claim 20, wherein the cross-dipole radiating elements are low-band radiating elements configured to operate in at least a portion of a 617-960 MHz frequency band, and wherein a third column of radiating elements are positioned behind the first and second columns of radiating elements, wherein the third column of radiating elements comprise radiating elements configured to operate in a frequency band that is greater than the low-band radiating elements.

**22.** The base station antenna of claim 18, wherein cross-dipole radiating elements of the first and second columns of cross-dipole radiating elements each comprise a plurality of arms, and wherein

some columns of a multiple column array reside behind and overlap with one or more of the arms of the cross-dipole radiating elements of the first column of radiating elements or the second column of radiating elements.

---