

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389114
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Tsunoda; Masayoshi et al.

Image pickup device capable of performing image pickup in a plurality of image-pickup modes in parallel and control method thereof

Abstract

An image pickup device having a plurality of lenses with angles of view different from one another, includes at least one memory and at least one processor which function as: an accepting unit configured to accept a switching operation of switching a lens to be used for image pickup when an image is picked up in a first image-pickup mode and a second image-pickup mode in parallel; and a control unit configured to control such that the lens to be used for the image pickup is switched in response to an acceptance of the switching operation of the lens to be used for the image pickup, wherein the control unit controls such that lenses to be used in the first image-pickup mode and the second image-pickup mode are switched such that different lenses are used in the first image-pickup mode and the second image-pickup mode.

Inventors: Tsunoda; Masayoshi (Kanagawa, JP), Matsumoto; Satoru (Tokyo, JP), Miyoshi; Nari (Tokyo, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 1000008747507

Assignee: CANON KABUSHIKI KAISHA (Tokyo, JP)

Appl. No.: 18/298463

Filed: April 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230345121 A1	Oct. 26, 2023

Foreign Application Priority Data

JP	2022-070161	Apr. 21, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: H04N23/667 (20230101); H04N23/63 (20230101); H04N23/69 (20230101);
H04N23/698 (20230101)

U.S. Cl.:

CPC H04N23/667 (20230101); H04N23/632 (20230101); H04N23/633 (20230101);
H04N23/69 (20230101); H04N23/698 (20230101);

Field of Classification Search

CPC: H04N (23/667); H04N (23/632); H04N (23/633); H04N (23/69); H04N (23/698); H04N
(23/631)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2014/0192240	12/2013	Laroia	348/262	H04N 5/265
2019/0289201	12/2018	Nishimura	N/A	H04N 13/239
2022/0053142	12/2021	Manzari	N/A	H04N 23/69

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
08-321981	12/1995	JP	N/A

Primary Examiner: Dagneu; Mekonnen D

Attorney, Agent or Firm: Cowan, Liebowitz & Latman, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

- (1) The present invention relates to an image pickup device and a control method of the image pickup device.
- Description of the Related Art
- (2) Conventionally, an image pickup method of recording a subject by using both an image pickup unit for photographing a still image and an image pickup unit for photographing a moving image provided in an image pickup device at the same time is well known. Recently, in an image pickup device such as a smartphone, a plurality of image pickup units with different focal distances are mounted, whereby recording of a subject by each of the image pickup units at the same time is realized. Furthermore, when an angle of view is to be switched, the smartphone uses an image pickup unit with a focal distance to which the switching is to be performed.
- (3) A Japanese Patent Application Publication No. H08-321981 discloses an art of automatically moving a zoom position of an image pickup device for photographing a moving image in collaboration with a zoom operation of the image pickup device for photographing a still image.

(4) In Japanese Patent Application Publication No. H08-321981, each image pickup device can switch to an arbitrary angle of view by performing an optical zoom by lens drive, respectively. On the other hand, in the smartphone, the angle of view is switched by using a plurality of image pickup units (lenses) with different focal distances. When image pickup is performed by the smartphone in two image-pickup modes for the still image and the moving image in parallel, in order to switch the lens in use for the still image to the lens for the moving image, the use of the image pickup unit for the still image should be stopped once and then, the angle of view for photographing the moving image is switched. Thus, it is difficult to adjust an angle of view seamlessly from a wide angle to telephoto without interrupting the image pickup.

SUMMARY OF THE INVENTION

(5) The present invention provides an image pickup device which switches an angle of view seamlessly from a wide angle to telephoto without interrupting image pickup when image pickup is performed in a plurality of image-pickup modes in parallel.

(6) The image pickup device of the present invention, which has a plurality of lenses with angles of view different from one another, includes at least one memory and at least one processor which function as: an accepting unit configured to accept a switching operation of switching a lens to be used for image pickup when an image is picked up in a first image-pickup mode and a second image-pickup mode in parallel; and a control unit configured to control such that the lens to be used for the image pickup is switched in response to an acceptance of the switching operation of the lens to be used for the image pickup, wherein the control unit controls such that lenses to be used in the first image-pickup mode and the second image-pickup mode are switched such that different lenses are used in the first image-pickup mode and the second image-pickup mode.

(7) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. 1A and 1B are appearance views of a smartphone;
- (2) FIG. 2 is a block diagram illustrating a configuration of the smartphone;
- (3) FIGS. 3A to 3C are diagrams for explaining a view-angle switching operation;
- (4) FIG. 4 is a flowchart exemplifying view-angle switching processing according to a first embodiment;
- (5) FIG. 5 is a flowchart exemplifying the view-angle switching processing according to a second embodiment;
- (6) FIGS. 6A to 6E are diagrams for explaining LV-display switching processing according to a third embodiment;
- (7) FIG. 7 is a flowchart exemplifying the LV-display switching processing according to the third embodiment;
- (8) FIG. 8 is a diagram for explaining zoom-out processing in a still-image LV display;
- (9) FIG. 9A is a flowchart exemplifying zoom-in/zoom-out processing;
- (10) FIG. 9B is a flowchart exemplifying details of the zoom-in processing;
- (11) FIG. 9C is a flowchart exemplifying details of the zoom-out processing;
- (12) FIGS. 10A and 10B are diagrams for explaining moving-image LV superimposed-display processing in the third embodiment; and
- (13) FIG. 11 is a flowchart exemplifying the moving-image LV superimposed-display processing.

DESCRIPTION OF THE EMBODIMENTS

(14) Hereinafter, embodiments of the present invention will be explained by referring to the drawings. FIGS. 1A and 1B are appearance views of a smartphone 100 as an example of an image

pickup device (electronic device) to which the present invention can be applied. FIG. 1A is a front view of the smartphone **100**, and FIG. 1B is a rear view of the smartphone **100**.

(15) A display **105** is a display unit which is provided on a front surface of the smartphone **100** and displays images and various types of information. A touch panel **106a** is a touch-operation member configured integrally with the display **105**, and the smartphone **100** can detect a touch operation to a display surface (operation surface) of the display **105** by using the touch panel **106a**. The smartphone **100** is capable of live-view display (LV display) of an image picked up by an out-camera **114** or an in-camera **115** on the display **105**. The LV display is display of an image shown on a substantially real time basis of a subject, and the LV-displayed image is called an LV-image. The out-camera **114** includes a telephoto lens **114a**, a standard lens **114b**, a wide-angle lens **114c**, which will be described later, and the like.

(16) A power button **106b** is an operation button for switching lighting on/off of the display **105** and power on/off of the smartphone **100**. For example, when a user presses down the power button **106b** for a time shorter than a predetermined time (3 seconds, for example) (pressing down the power button **106b** for a short time), lighting on/off of the display **105** is switched. When the user continues pressing-down on the power button **106b** (pressing down the power button **106b** for a long time), power on/off of the smartphone **100** is switched.

(17) A sound-volume plus button **106c** and a sound-volume minus button **106d** are sound-volume buttons for adjusting a sound volume (volume) of a sound signal output from a sound output terminal **112a** and a sound volume of sound output from a speaker **112b**. When the sound-volume plus button **106c** is pressed down, the sound volume becomes larger, while when the sound-volume minus button **106d** is pressed down, the sound volume becomes smaller. In a photographing standby state when the camera is in use, the sound-volume plus button **106c** and the sound-volume minus button **106d** function as shutter buttons for instructing photographing.

(18) The user can make arbitrary setting so that a specific function is performed when the power button **106b** and the sound-volume minus button **106d** are pressed down at the same time or when the sound-volume minus button **106d** is pressed down quickly several times or the like.

(19) A home button **106e** is an operation button for causing a home screen to be displayed on the display **105**. When the user started and is using various applications on the smartphone **100**, the user can temporarily close the various started applications and cause the home screen to be displayed on the display **105** by pressing down the home button **106e**. The home button **106e** is assumed to be a button which can be physically pressed down in this embodiment, but it may be a touch button (display item) displayed on the display **105** and capable of the touch operation.

(20) The sound output terminal **112a** is an earphone jack and is a terminal which outputs a sound signal to an earphone, an external speaker or the like. A speaker **112b** is a built-in speaker which outputs sound. For example, when the earphone, the external speaker or the like is connected to the sound output terminal **112a**, the sound signal is output from the sound output terminal **112a**. When the earphone, the external speaker or the like is not connected to the sound output terminal **112a**, the sound is output from the speaker **112b**.

(21) FIG. 2 is a block diagram illustrating a configuration example of the smartphone **100**. To an internal bus **150**, a CPU **101**, a memory **102**, a non-volatile memory **103**, an out-camera image processing unit **104**, the display **105**, an operation member **106**, a storage medium I/F **107**, an external I/F **109**, and a communication I/F **110** are connected. Moreover, to the internal bus **150**, a sound output unit **112**, an attitude detection unit **113**, the out-camera **114**, the in-camera **115**, and an in-camera image processing unit **116** are also connected. Each unit connected to the internal bus **150** can exchange data with each other through the internal bus **150**.

(22) The CPU **101** is a control unit which controls the entirety of the smartphone **100** and is constituted by at least one processor or a circuit. The memory **102** is constituted by a RAM (a volatile memory using a semiconductor element or the like), for example. The CPU **101** controls each unit of the smartphone **100** by using the memory **102** as a work memory in accordance with a

program stored in the non-volatile memory **103**, for example. In the non-volatile memory **103**, data such as image data, sound data and others, various programs for the CPU **101** to operate and the like are stored. The non-volatile memory **103** is constituted by a flash memory, a ROM or the like, for example.

(23) The out-camera **114** is a camera disposed on a rear surface (a surface on a side opposite to a surface on which the display **105** is provided) of the smartphone **100**. In the example in FIG. **2**, the out-camera **114** includes an image pickup unit **114s**, an image pickup unit **114t**, an image pickup unit **114u**, a telephoto lens **114a**, a standard lens **114b**, and a wide-angle lens **114c**. In this embodiment, it is assumed that, when the telephoto lens **114a** is used, the image pickup unit **114s** is used, when the standard lens **114b** is used, the image pickup unit **114t** is used, and when the wide-angle lens **114c** is used, the image pickup unit **114u** is used for image pickup, respectively. However, this configuration is not limiting, and it may be so configured that the out-camera **114** has an image pickup unit for a still image and an image pickup unit for a moving image, and photographing can be performed by switching among the telephoto lens, the standard lens, and the wide-angle lens in each of the image pickup units.

(24) The image pickup unit **114s**, the image pickup unit **114t**, and the image pickup unit **114u** are image pickup elements such as a CCD image sensor and a CMOS image sensor, and each of them performs photographing using the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c**. The out-camera **114** can perform three types of image pickup, that is, the image pickup using the telephoto lens **114a**, the image pickup using the standard lens **114b**, and the image pickup using the wide-angle lens **114c** at the same time (in parallel or time division). It is needless to say that the out-camera **114** can perform only two types of the image pickup in the aforementioned three types of the image pickup at the same time or can perform only one type of the image pickup.

(25) A focal distance of the telephoto lens **114a** is longer than the focal distance of the standard lens **114b**, and the image pickup using the telephoto lens **114a** is the image pickup with more telephoto than the image pickup using the standard lens **114b**. The focal distance of the wide-angle lens **114c** is shorter than the focal distance of the standard lens **114b**, and the image pickup using the wide-angle lens **114c** is image pickup with a wider angle than the image pickup using the standard lens **114b**. That is, the focal distance becomes shorter in the order of the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c**, and an angle of view (image pickup range) becomes wider with that. In this embodiment, a zoom magnification (focal distance) of the telephoto lens **114a** is assumed to be a fixed value determined in advance but may be changed by the user.

(26) The smartphone **100** according to this embodiment is capable of image pickup in a plurality of image-pickup modes, and images can be picked up by switching the lens by switching among the image pickup unit **114s**, the image pickup unit **114t**, and the image pickup unit **114u** and by changing the angle of view in each of the image-pickup modes. The plurality of image-pickup modes are a still-image mode for photographing a still image and a moving-image mode for photographing a moving image, for example. When images are picked up in the still-image mode and the moving-image mode in parallel, the smartphone **100** performs photographing by using the different image pickup units in the respective image-pickup modes, that is, by using the different lenses.

(27) The smartphone **100** switches the lens to be used (the telephoto lens **114a**, the standard lens **114b**, the wide-angle lens **114c**) by switching among the image pickup unit **114s**, the image pickup unit **114t**, and the image pickup unit **114u** in each image-pickup mode. In the following explanation, the description that the lens is switched means that the lens is switched by switching the image pickup unit.

(28) The in-camera **115** is a camera disposed on the front surface (on the same surface as the surface on which the display **105** is provided) of the smartphone **100**.

(29) The image picked up by the out-camera **114** and the image picked up by the in-camera **115** can

be both LV-displayed on the display **105**. The user can select the camera by which the image was picked up to be LV-displayed on the display **105** by operating the touch panel **106a**. For example, the user (photographer) selects the out-camera **114** when a sight just before the eyes is to be photographed and selects the in-camera **115** when the user himself/herself is to be photographed. (30) Moreover, when the image picked up by the out-camera **114** is to be LV-displayed on the display **105**, the user can select the lens which was used to pick up the image to be LV-displayed on the display **105** by operating the touch panel **106a**. When the user selects the telephoto lens **114a**, an image enlarged more than the case in which the standard lens **114b** was selected can be LV-displayed on the display **105**. When the standard lens **114b** is selected, an image with a wider angle than the case of selection of the telephoto lens **114a** and enlarged more than the case of selection of the wide-angle lens **114c** can be LV-displayed on the display **105**. When the wide-angle lens **114c** is selected, an image with a wider angle than the case of selection of the telephoto lens **114a** or the standard lens **114b** can be LV-displayed on the display **105**.

(31) The out-camera image processing unit **104** executes various types of image processing and subject-recognition processing by using the image picked up by the out-camera **114** on the basis of control of the CPU **101**. The out-camera image processing unit **104** includes a telephoto-image processing unit **104a**, a standard-image processing unit **104b**, and a wide-angle image processing unit **104c**. The telephoto-image processing unit **104a** executes various types of image processing by using an image picked up by the telephoto lens **114a**. The standard-image processing unit **104b** executes various types of image processing by using an image picked up by the standard lens **114b**. The wide-angle image processing unit **104c** executes various types of image processing by using an image picked up by the wide-angle lens **114c**. These three image processing units can operate at the same time (in parallel or time division).

(32) In this embodiment, the configuration is such that the three image processing units corresponding to the three lenses, respectively, are used, but the number of lenses corresponding to one image processing unit is not particularly limited. One image processing unit may be used for two lenses, or one image processing unit may be used for three lenses. That is, the out-camera image processing unit **104** does not have to include a plurality of image processing units. In that case, too, the out-camera image processing unit **104** may be capable of executing a plurality of pieces of processing at the same time (in parallel or time division) by using each of the plurality of images.

(33) The in-camera image processing unit **116** executes various types of image processing by using the image picked up by the in-camera **115** on the basis of the control of the CPU **101**.

(34) Each image processing unit can execute various types of image processing by using images stored in the non-volatile memory **103** and a storage medium **108**, the images obtained through the external I/F **109**, the images obtained through the communication I/F **110** and the like. The image processing executed by each image processing unit includes A/D conversion processing, D/A conversion processing, encoding processing of image data, compression processing, decoding processing, enlargement/reduction processing (resize), noise reduction processing, color conversion processing and the like. Each of the image processing units may be configured by a dedicated circuit block for executing specific image processing. Moreover, depending on the type of the image processing, the CPU **101** can execute the image processing in accordance with a program without using the various image processing units.

(35) The display **105** displays an image, a GUI screen configuring GUI (Graphical User Interface) and the like on the basis of the control of the CPU **101**. The CPU **101** generates a display control signal in accordance with the program and controls each unit of the smartphone **100** so that an image signal for displaying on the display **105** is generated and output to the display **105**. The display **105** displays an image on the basis of the output image signal. As a configuration included in the smartphone **100** itself, it may be up to the interface for outputting the image signal for displaying on the display **105**, and the display **105** may be configured by an external monitor (TV

or the like).

(36) The operation member **106** is an input device for accepting an operation by the user. The operation member **106** includes a character-information input device such as a keyboard, a pointing device such as a mouse and a touch panel, a button, a dial, a joystick, a touch sensor, a touch pad and the like. The operation member **106** includes operation members such as the touch panel **106a**, the power button **106b**, the sound-volume plus button **106c**, the sound-volume minus button **106d**, the home button **106e** and the like described above.

(37) The storage medium I/F **107** has the storage medium **108** such as a memory card, a CD, and a DVD detachably attached and executes reading of data from the attached storage medium **108** and writing of data in the storage medium **108** on the basis of the control of the CPU **101**. The storage medium **108** may be a built-in storage incorporated in the smartphone **100**. The external I/F **109** is an interface for performing input/output of an image signal and a sound signal by connecting to the external equipment via a wired cable or wirelessly. The communication I/F **110** is an interface for performing transmission/reception of various types of data such as a file and a command by communicating with the external equipment, the Internet **111** and the like.

(38) The sound output unit **112** outputs sound of the moving image data and music data, operation sounds, a ringtone, various notification sounds and the like. The sound output unit **112** includes the sound output terminal **112a** and the speaker **112b** described above. The sound output unit **112** may output sound via wireless communication.

(39) The attitude detection unit **113** detects an attitude (inclination) of the smartphone **100** with respect to the gravity direction and the attitude (inclination) of the smartphone **100** with respect to each axis of yaw, roll, and pitch. On the basis of the attitude detected by the attitude detection unit **113**, whether the smartphone **100** is held laterally, held vertically, faced upward, faced downward, becomes diagonally or the like can be determined. As the attitude detection unit **113**, any one of a plurality of sensors such as an acceleration sensor, a gyro sensor, a geomagnetic sensor, an azimuth sensor, and an altitude sensor can be used. As the attitude detection unit **113**, a combination of two or more of the plurality of sensors can be also used.

(40) As described above, the operation member **106** includes the touch panel **106a**. The touch panel **106a** is an input device configured planarly by being overlapped with the display **105** so that coordinate information corresponding to a contacted position is output. The CPU **101** can detect the following operations or states of the touch panel **106a**. A finger or a pen that has not touched the touch panel **106a** newly touches the touch panel **106a**, that is, start of a touch (hereinafter, referred to as touch-down (Touch-Down)) A state where a finger or a pen is in touch with the touch panel **106a** (hereinafter referred to as touch-on (Touch-On)) A finger or a pen is moving while in touch with the touch panel **106a** (hereinafter referred to as touch-move (Touch-Move)) A finger or a pen having touched the touch panel **106a** leaves the touch panel **106a** (released), that is, end of the touch (hereinafter, referred to as touch-up (Touch-Up)) A state where nothing touches the touch panel **106a** (hereinafter, referred to as touch-off (Touch-Off))

(41) When the touch-down is detected, the touch-on is also detected at the same time. After the touch-down, the touch-on is continuously detected usually unless the touch-up is detected. When the touch-move is detected, too, the touch-on is detected at the same time. Even when the touch-on has been detected, if the touch position has not been moved, the touch-move is not detected. When the touch-up of all the fingers or pens having been in touch was detected, the touch-off is detected.

(42) These operations/states and position coordinates where the finger or the pen is in touch on the touch panel **106a** are notified to the CPU **101** via the internal bus **150**. The CPU **101** determines what operation (touch operation) was performed on the touch panel **106a** on the basis of the notified information. Regarding the touch-move, moving directions of the finger or the pen moving on the touch panel **106a** can be also determined for each of perpendicular component/horizontal component on the touch panel **106a** on the basis of a change in the position coordinates. When the touch-move for a predetermined distance or more is detected, performance of a slide operation is

assumed to be determined. Such an operation that the finger is quickly moved only for some distance while in touch on the touch panel **106a** and then released is called a flick. The flick operation is, in other words, an operation of tracing on the touch panel **106a** quickly like flicking with a finger. When the touch-move for a predetermined distance or more at a predetermined speed or more was detected, and the touch-up was detected after that, it can be determined that a flick was performed (it can be determined that the flick was performed subsequently to the slide operation). Moreover, such a touch operation that a plurality of spots (two points, for example) are touched together (multi-touched) so as to bring the touch positions closer to each other is called pinch-in, while such a touch operation to separate the touch positions away from each other as pinch-out. The pinch-out and the pinch-in are collectively called a pinch operation (or simply as a pinch). As the touch panel **106a**, a touch panel of any method in touch panels of various methods such as a resistive method, a capacitive method, a surface elastic wave method, an infrared method, an electromagnetic induction method, an image recognition method, and an optical sensor method may be used. There are a method of detection that touch was made when there was a contact with the touch panel and a method of detection that touch was made when a finger or a pen approaches the touch panel, but any method may be used.

(43) Each of the following embodiments relates to switching control of an angle of view when the still-image pickup and the moving-image pickup are performed in parallel by the smartphone **100**.
First Embodiment

(44) In a first embodiment, the out-camera **114** includes three lenses with angles of view different from one another, that is, the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c**. The out-camera **114** can pick up images in the plurality of image-pickup modes in parallel by using the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c**. For example, the out-camera **114** picks up images in the moving-image mode by using the standard lens **114b** and picks up images in the still-image mode by using the telephoto lens **114a**.

(45) The out-camera **114** picks up images while switching the lens used in the moving-image mode and the still-image mode, respectively, on the basis of the user's operation. The moving-image mode and the still-image mode share the three lenses (image pickup units), and images are picked up by using the lenses different from each other, when images are picked up in parallel in each of the image-pickup modes.

(46) By referring to FIGS. **3A** to **3C** and FIG. **4**, view-angle switching processing of picked-up images in the moving-image mode and the still-image mode will be explained. FIGS. **3A** to **3C** are diagrams for explaining the view-angle switching operation by the user. FIG. **4** is a flowchart exemplifying the view-angle switching processing by the out-camera **114** and the out-camera image processing unit **104**. The view-angle switching processing in FIG. **4** is realized by the CPU **101** of the smartphone **100** which develops a program recorded in the non-volatile memory **103** to the memory **102** and executes it.

(47) The view-angle switching processing is started when a camera application is started in the smartphone **100**, for example. The view-angle switching processing may be started not only by the camera application but by starting of means of picking up the still images and the moving images in parallel.

(48) At **S401**, the CPU **101** starts image pickup by the out-camera **114** by using the three lenses, that is, the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c**. The image picked up by using each lens is subject to various types of image processing by the telephoto-image processing unit **104a**, the standard-image processing unit **104b**, and the wide-angle image processing unit **104c** of the out-camera image-processing unit **104**.

(49) At **S402**, the CPU **101** LV-displays the picked-up images picked up in the moving-image mode and the still-image mode. The CPU **101** LV-displays the image picked up by using the standard lens **114b** in the moving-image mode and the image picked up by using the telephoto lens **114a** in the still-image mode on the display **105**, for example.

(50) FIG. 3A shows a screen example which LV-displays the image picked up by using the standard lens **114b** in the moving-image mode and the image picked up by using the telephoto lens **114a** in the still-image mode. The display **105** is divided into a main image area **301** which displays the image picked up in the moving-image mode by using the standard lens **114b** and a sub image area **305** which displays the image picked up in the still-image mode by using the telephoto lens **114a**. In FIG. 3A, the main image area **301** is an area displayed substantially on the whole of the display **105**, while the sub image area **305** is an area displayed superimposed at upper right of the main image area **301**.

(51) On the main image area **301**, an index **302**, an indicator **303**, and a moving-image recording button **304** are displayed by being superimposed on the LV image in the moving-image mode. The index **302** indicates a lens which can be switched in the moving-image mode. The indicator **303** indicates the lens in use in the moving-image mode in the index **302**. The example in FIG. 3A indicates that the standard lens **114b** is being used in the moving-image mode. Moreover, the indicator **303** is an operation member (item) for switching the lens to be used. The user can switch the lens to be used by touching the indicator **303** and moving it on the index **302** by touch-move. The item constituted by the index **302** and the indicator **303** is an example of a first item. The moving-image recording button **304** is an operation member (item) for instructing recording start and recording stop of the moving image.

(52) On the sub image area **305**, a still-image photographing button **306** and a lens switching member **307** are displayed by being superimposed on the LV image in the still-image mode. The still-image photographing button **306** is an operation member (item) for photographing a still image. The still-image photographing button **306** can be moved on the picked-up image in the still-image mode and on the picked-up image in the moving-image mode by the touch-move. That is, the still-image photographing button **306** can move from the sub image area **305** to the main image area **301**.

(53) The user can photograph a still image of the picked-up image which is LV-displayed on the main image area **301** by moving the still-image photographing button **306** to the main image area **301** and touching it. When a center of the still-image photographing button **306** is on the picked-up image in the still-image mode of the sub image area **305**, the CPU **101** photographs the still image by the lens used in the still-image mode. When the center of the still-image photographing button **306** is on the picked-up image in the moving-image mode of the main image area **301**, the CPU **101** photographs the still image by the lens used in the moving-image mode. The still-image photographing button **306** is an example of a fourth item.

(54) The lens switching member **307** indicates the lens used in the picked-up image in the still-image mode displayed on the sub image area **305**. The lens switching member **307** is, as will be explained at **S407**, an operation member (item) for changing the lens used in the still image mode.

(55) At **S403**, the CPU **101** determines whether there has been an operation of switching the lens for the moving image used in the moving-image mode. The CPU **101** determines whether a position of the indicator **303** has been changed on the basis of information of the operation detected by the touch panel **106a**. If the indicator **303** at completion of the touch-move selects the lens different from the lens in use, the CPU **101** determines that the operation of switching the lens for the moving image has been performed. Moreover, if the indicator **303** at the completion of the touch-move selects the same lens as the lens in use, the CPU **101** determines that there has not been an operation of switching the lens for the moving image. If the operation of switching the lens for the moving image has been performed, the processing proceeds to **S404**, while if the operation of switching the lens for the moving image has not been performed, the processing proceeds to **S406**.

(56) At **S404**, the CPU **101** switches the lens for the moving image from the lens in the current use to a lens selected by the user at **S403**. When the lens for the moving image is switched, the CPU **101** causes the image picked up by the lens for the moving image after the switching to be LV-displayed on the main image area **301**.

(57) When the lens for the moving image is switched from the standard lens **114b** in the current use to the telephoto lens **114a** used in the still-image mode, for example, the CPU **101** temporarily stops the picked-up image which is LV-displayed on the sub image area **305** in the still-image mode. After the LV-display of the still-image mode is temporarily stopped, the CPU **101** switches the lens for the moving image to the telephoto lens **114a**.

(58) At **S405**, the CPU **101** executes the switching processing of the lens for the still image. When the lens for the moving image is to be switched to the lens in use as the lens for the still image, the CPU **101** switches the lens for the still image to a lens not in use either in the moving-image mode or the still-image mode. For example, the CPU **101** switches the lens for the still image to the wide-angle lens **114c** different from both the standard lens **114b** used in the moving-image mode and the telephoto lens **114a** used in the still-image mode. The CPU **101** causes the picked-up image in the still-image mode by the lens after the switching to be LV-displayed on the sub image area **305**.

(59) At **S404**, when the lens for the moving image is to be switched to a lens not in use as the lens for the still image, at **S405**, the CPU **101** does not change the lens for the still image or does not change the LV-display on the sub image area **305**, either.

(60) In the explanation above, the lens for the moving image is switched at **S404** and then, the lens for the still image is switched at **S405**. However, when the lens for the moving image is to be switched to the lens in use as the lens for the still image, the picked-up image LV-displayed on the sub image area **305** in the still-image mode needs to be temporarily stopped. Therefore, when the lens in use in the still-image mode is to be switched, the processing of switching the lens for the moving image at **S404** may be executed after the switching of the lens for the still image at **S405**. In this case, without temporarily stopping the picked-up image which is LV-displayed on the sub image area **305** in the still-image mode, the lens in each of the still-image mode and the moving-image mode can be switched.

(61) At **S406**, the CPU **101** determines whether the operation of switching the lens for the still image has been performed. The CPU **101** determines whether the lens switching member **307** has been touched on the basis of the information of the operation detected by the touch panel **106a**. If the lens switching member **307** has been touched, the CPU **101** determines that the operation of switching the lens for the still image has been performed. Moreover, if the lens switching member **307** has not been touched, the CPU **101** determines that the operation of switching the lens for the still image has not been performed. If the operation of switching the lens for the still image has been performed, the processing proceeds to **S407**, while if the operation of switching the lens for the still image has not been performed, the processing proceeds to **S410**.

(62) At **S407**, the CPU **101** displays candidates for the lens which can be switched as the lens for the still image. The CPU **101** controls the display of the candidates so that the switching to the currently used lens can be also accepted. FIG. 3B shows a screen example when the operation of switching the lens for the still image was accepted during recording of the moving image displayed on the main image area **301**.

(63) When the lens switching member **307** is touched on the screen of FIG. 3A, the CPU **101** superimposes and displays a popup window **308** including an index **309** and an indicator **310** in the sub image area **305** as shown in FIG. 3B. The index **309** indicates the lens which can be switched in the still-image mode. The indicator **310** indicates the lens in use in the still-image mode in the index **309**. The example in FIG. 3B shows that the standard lens **114b** is used in the moving-image mode, and the telephoto lens **114a** is used in the still-image mode. Moreover, the indicator **310** is the operation member (item) for switching the lens to be used by the touch-move by the user on the index **309**. The item constituted by the index **309** and the indicator **310** is an example of a second item.

(64) The sub image area **305** is displayed larger, as shown in FIG. 3B, than that when the popup window **308** is not displayed, while the popup window **308** is displayed for switching of the lens. As a result, the user can easily check the LV-image of the still image when the lens is to be

switched.

(65) During the recording of the moving image displayed on the main image area **301**, the CPU **101** executes control so that the lens in use in the moving-image mode is not selected in the still-image mode so as not to interrupt the moving-image recording. In the example in FIG. 3B, the standard lens **114b** in use in the moving-image mode is not displayed on the index **309**. That is, the CPU **101** controls so that the switching to the lens in use in the moving-image mode is not accepted and controls so that the lens used in the moving-image mode is not switched during the recording of the moving image. On the other hand, in the case not during the recording of the moving image, the CPU **101** enables selection of the lens in use in the moving-image mode and displays also the lens in use in the moving-image mode on the index **309**.

(66) At **S408**, the CPU **101** switches the lens for the still image to the lens selected by the user at **S407**. When the lens for the still image is switched, the CPU **101** LV-displays the image picked up by the lens for the still image on the sub image area **305** after the switching.

(67) When the lens for the still image is switched from the currently used telephoto lens **114a** to the standard lens **114b** used in the moving-image mode, the CPU **101** temporarily stops the picked-up image which is LV-displayed on the main image area **301** in the moving-image mode. After the temporary stop of the LV-display in the moving-image mode, the CPU **101** switches the lens for the still image to the standard lens **114b**.

(68) At **S409**, the CPU **101** executes the switching processing of the lens for the moving image. When the lens for the still image is to be switched to the lens in use as the moving image, the CPU **101** switches the lens for the moving image to the lens not in use in the moving-image mode or the still-image mode. For example, the CPU **101** switches the lens for the moving image to the wide-angle lens **114c** different from the telephoto lens **114a** used in the still-image mode and the standard lens **114b** used in the moving-image mode. The CPU **101** LV-displays the picked-up image in the moving-image mode by the lens after the switching on the main image area **301**.

(69) At **S408**, when the lens for the still image is to be switched to the lens not used as the lens for the moving image, at **S409**, the CPU **101** does not change the lens for the moving image or change the LV-display on the main image area **301**. Moreover, in the case of during the recording of the moving image, the lens for the still image will not be switched to the lens used as the lens for the moving image and thus, the CPU **101** does not change the lens for the moving image or the LV-display on the main image area **301**.

(70) Moreover, in the aforementioned explanation, after the lens in the still-image mode was switched at **S408**, the lens in the moving-image mode was switched at **S409**. However, when the lens in use in the still-image mode is switched to the lens in the moving-image mode, the LV-display in the moving-image mode needs to be temporarily stopped. Thus, when the lens in the still-image mode is to be switched to the lens in use in the moving-image mode, the processing of switching the lens for the still image at **S407** may be executed after the processing of switching the lens for the moving image at **S409** is executed. In this case, the lens switching can be executed without temporarily stopping the LV-display of the moving-image mode.

(71) At **S410**, the CPU **101** determines whether a moving-image recording operation was performed. The moving-image recording operation is an operation of starting or stopping the moving-image recording. The CPU **101** determines whether the moving-image recording button **304** was touched on the basis of the information of the operation detected on the touch panel **106a**. When the moving-image recording button **304** was touched, the CPU **101** determines that the moving-image recording operation was performed. Moreover, when the moving-image recording button **304** was not touched, the CPU **101** determines that the moving-image recording operation was not performed. When the moving-image recording operation was performed, the processing proceeds to **S411**, while when the moving-image recording operation was not performed, the processing proceeds to **S412**.

(72) At **S411**, the CPU **101** starts or stops the recording of the moving image. If the moving image

is not being recorded, the CPU **101** starts recording of the moving image picked up by the lens for the moving image and displayed on the main image area **301**. Moreover, if the moving image is being recorded, the CPU **101** stops the moving-image recording.

(73) In the case where the standard lens **114b** is used as the lens for the moving image, when the moving-image recording is started, the CPU **101** executes image processing and encoding processing of a video signal output from the standard lens **114b** by the standard-image processing unit **104b**. The CPU **101** stores image contents processed by the standard-image processing unit **104b** in the memory **102**. The CPU **101** generates a moving-image file from the image contents stored in the memory **102** and records it in the non-volatile memory **103** or the storage medium **108** via the storage medium I/F **107**.

(74) when the moving-image recording is stopped, the CPU **101** stops the encoding processing by the standard-image processing unit **104b** and stops the processing of generating the moving-image file from the video contents stored in the memory **102** and recording it in the non-volatile memory **103** or the storage medium **108**.

(75) At **S412**, the CPU **101** determines whether a still-image photographing operation was performed. The CPU **101** determines whether the still-image photographing button **306** was touched on the basis of the information of the operation detected by the touch panel **106a**. If the still-image photographing button **306** was touched, the CPU **101** determines that the still-image photographing operation was performed. Moreover, if the still-image photographing button **306** was not touched, the CPU **101** determines that the still-image photographing operation was not performed. When the still-image photographing operation was performed, the processing proceeds to **S413**, while when the still-image photographing operation was not performed, the processing proceeds to **S414**.

(76) At **S413**, the CPU **101** photographs a still image and records the generated still-image file in the non-volatile memory **103** or the storage medium **108**. When the still-image photographing button **306** is on the sub image area **305**, the CPU **101** generates a still-image file from the picked-up image by the lens for the still image, while when the still-image photographing button **306** is on the main image area **301**, the CPU **101** generates a still-image file from the picked-up image by the lens for the moving image.

(77) For example, when the telephoto lens **114a** is used as the lens for the still image, and the still-image photographing button **306** is on the sub image area **305**, the telephoto-image processing unit **104a** executes the image processing and the encoding processing of the video signal output from the telephoto lens **114a** and generates a still-image file. Moreover, when the standard lens **114b** is used as the lens for the moving image, and the still-image photographing button **306** is on the main image area **301**, the standard-image processing unit **104b** executes the image processing and the encoding processing of the video signal output from the standard lens **114b** and generates a still-image file.

(78) The CPU **101** stores the image contents processed at each unit of the out-camera image processing unit **104** in the memory **102**. The CPU **101** generates a still-image file from the image contents stored in the memory **102** and records it in the non-volatile memory **103** or the storage medium **108** via the storage medium I/F.

(79) At **S414**, the CPU **101** determines whether the moving image is being recorded. If the moving image is being recorded, the processing returns to **S403**, while if the moving image is not being recorded, the processing proceeds to **S415**. When any one of the parts of the out-camera image processing unit **104** is executing the encoding processing of the moving image, the CPU **101** determines that the moving image is being recorded, while when the encoding processing is not being executed, the CPU **101** can determine that the moving image is not being recorded.

(80) At **S415**, the CPU **101** determines whether a photographing standby state has been finished. The photographing standby state is a state where the LV-image in the moving-image mode and the LV-image in the still-image mode are displayed on the display, and recording start of a moving

image or photographing of a still image is waited for. When the photographing standby state is finished, the view-angle switching processing shown in FIG. 4 is finished, while when the photographing standby state is not finished, the processing returns to S403. When the user finishes the camera application, for example, the CPU 101 can determine that the photographing standby state is finished.

(81) The index 302 and the indicator 303 on the main image area 301 explained at S403 and the index 309 and the indicator 310 on the sub image area 305 explained at S407 may be realized by using a common index. In the example shown in FIG. 3C, the index 312, the indicator 313 for the moving image, and the indicator 311 for the still image are superimposed on the LV-image in the moving-image mode in the main image area 301 and displayed. The item constituted by the index 312, the indicator 313, and the indicator 311 is an example of a third item. The user can switch the lens to be used in the moving-image mode and the still-image mode, respectively, by the third item.

(82) The index 312 indicates a lens which can be switched in the moving-image mode on an upper side (center side of the main image area 301) and a lens which can be switched in the still-image mode on a lower side (periphery side of the main image area 301). In the example in FIG. 3C, since the moving image is being recorded by using the standard lens 114b, a scale for selecting the standard lens 114b is not displayed on the lower side of the index 312. If the moving image is not being recorded, a scale for selecting the standard lens 114b is displayed, and the user can select the standard lens 114b.

(83) The indicator 313 is displayed on the upper side of the index 312, and similarly to the indicator 303 in FIG. 3A, it indicates the lens in use in the moving-image mode. The example in FIG. 3C indicates that the standard lens 114b is being used in the moving-image mode. Moreover, the indicator 313 is the operation member (item) for switching the lens to be used in the moving-image mode. The user can switch the lens to be used in the moving-image mode by touching (single-touch) the indicator 313 at one spot and moving it by touch-move on the index 312.

(84) When the indicator 313 is touched and another spot is also touched (multi-touch at two spots or more), as shown in FIG. 3C, the indicator 311 indicating the lens in use in the still-image mode is displayed on the lower side of the index 312. The example in FIG. 3C indicates that the telephoto lens 114a is in use in the still-image mode. Moreover, the indicator 311 is the operation member (item) for switching the lens to be used in the still-image mode. The user can switch the lens to be used in the still-image mode by moving the indicator 311 by touch-move on the index 312 in a state of the multi-touch on the indicator 311.

(85) The indicator 311 and the scale of the lens for the still image of the index 312 may be displayed while the multi-touch is detected with respect to the indicator 313 or the index 312 or may be displayed all the time.

(86) In the first embodiment described above, when the lens for the moving image is to be switched to the lens in use in the still-image mode, the CPU 101 switches the lens for the still image to the lens not in use in the moving-image mode or the still-image mode. On the contrary, when the lens for the still image is to be switched to the lens in use in the moving-image mode, the CPU 101 switches the lens for the moving image to the lens not in use in the moving-image mode or the still-image mode. By controlling the switching of the angle of view as above, the user can seamlessly switch the angle of view from the wide angle to the telephoto without interrupting the image pickup. Moreover, in the case of image pickup in the moving-image mode and the still-image mode in parallel, a labor of switching the angle of view in each image-pickup mode can be reduced.

Second Embodiment

(87) In the first embodiment, except the case where the moving image is being recorded in the moving-image mode, the user can switch the lens for the moving image to the lens in use in the still-image mode or can switch the lens for the still image to the lens in use in the moving-image mode. On the other hand, in the second embodiment, the lens in use in the image-pickup mode with priority in a plurality of the image-pickup modes (hereinafter referred to as a priority image-pickup

mode) is controlled so as not to be used in the other image-pickup modes (hereinafter referred to as a non-priority image-pickup mode). The priority image-pickup mode can be set by the user.

(88) In the second embodiment, detailed explanation of contents similar to those in the first embodiment will be omitted, and contents and processing different from those in the first embodiment will be explained in detail. FIG. 5 is a flowchart exemplifying the view-angle switching processing by the out-camera **114** and the out-camera image processing unit **104**. The view-angle processing in FIG. 5 is realized by the CPU **101** of the smartphone **100** which develops the program recorded in the non-volatile memory **103** to the memory **102** and executes it.

(89) The processing at **S501** and **S502** is similar to **S401** and **S402** and thus, explanation will be omitted. At **S503**, the CPU **101** sets the image-pickup mode selected by the user operation to the priority image-pickup mode. The priority image-pickup mode is not limited to a case set by the user but may be set to the moving-image mode as initial setting, for example. The picked-up image in the priority image-pickup mode is LV-displayed on the main image area **301**, and the picked-up image in the non-priority image-pickup mode is LV-displayed on the sub image area **305**.

(90) An operation of setting the priority image-pickup mode is an operation of the touch-move on the main image area **301** and releasing the finger while keeping in touch with the picked-up image in the still-image mode of a setting target on the sub image area **305**, for example. When the picked-up image in the still-image mode displayed on the sub image area **305** is touch-moved to the main image area **301**, for example, the CPU **101** sets the still-image mode to the priority image-pickup mode and LV-displays the picked-up image in the still-image mode on the main image area **301**.

(91) Moreover, the operation of setting the priority image-pickup mode may be an operation of changing a direction of the display **105** of the smartphone **100**. The direction of the display **105** can be discriminated on the basis of an attitude of the smartphone **100** detected by the attitude detection unit **113**. When the direction of the display **105** becomes vertical, for example, the CPU **101** sets the moving-image mode to the priority image-pickup mode, while when it becomes lateral, the CPU **101** sets the still-image mode to the priority image-pickup mode.

(92) When the priority image-pickup mode is changed, the CPU **101** LV-displays the picked-up image in the priority image-pickup mode on the main image area **301** and displays the picked-up image in the non-priority image-pickup mode on the sub image area **305**. Moreover, when the priority image-pickup mode was changed, the CPU **101** may use the lens having been used in the priority image-pickup mode before the priority image-pickup mode is changed even after the change. In this case, the CPU **101** switches the lens to be used in the non-priority image-pickup mode after the change to the lens not in use in the priority image-pickup mode after the change.

(93) In the following processing, explanation will be made by assuming that the priority image-pickup mode is the moving-image mode, and the non-priority image-pickup mode is the still-image mode. The processing from **S504** to **S507** is similar to the processing from **S403** to **S406** in FIG. 4.

(94) At **S504**, the CPU **101** determines whether an operation of switching the lens used in the moving-image mode set to the priority image-pickup mode (priority lens) was performed. If the operation of switching the priority lens was performed, at **S505**, the CPU **101** switches the priority lens (for the moving-image) to the lens selected by the user at **S504**. When an operation of switching the lens in use as the non-priority lens (for the still image) as the priority lens (for the moving image) was performed at **S504**, the CPU **101** executes the switching processing of the non-priority lens (for the still image) at **S506**. If the lens selected as the priority lens (for the moving image) at **S504** is not the lens in use as the non-priority lens (for the still image), the processing at **S506** is not executed. That is, the non-priority lens (for the still image) is not switched but maintained. Regarding the processing at **S505** and **S506**, **S506** may be executed first and then, **S505** may be executed. At **S507**, the CPU **101** determines whether the operation of switching the non-priority lens (for the still image) has been performed.

(95) At **S508**, the CPU **101** displays candidates for lenses which can be switched as a non-priority

lens (for the still image). In the first embodiment, in the case of the moving-image recording in the moving-image mode, the CPU **101** does not display the standard lens **114b** in use in the moving-image mode as a candidate for the lens for the still image. On the other hand, in the second embodiment, the CPU **101** does not display the standard lens **114b** in use in the moving-image mode with priority as a candidate for the non-priority lens for the still image regardless of whether the moving-image is being recorded. Moreover, if the priority image-pickup mode is the still-image mode, the lens in use in the still-image mode with priority is not displayed as the candidate for the non-priority lens for the moving image. In either mode, control is executed so that the switching to the currently used lens can be accepted.

(96) The processing at **S509** is similar to the processing at **S408** in FIG. **4**. At **S509**, the CPU **101** switches the non-priority lens for the still image to the lens selected by the user at **S508**. The lens in use in the moving-image mode, which is a priority image-pickup mode, is not displayed as a candidate for the non-priority lens (for the still image) at **S508** and thus, after the processing at **S509**, the processing of switching the priority lens (for the moving image) is not executed as in the first embodiment.

(97) The processing at **S510** to **S515** is similar to the processing at **S410** to **S415** in FIG. **4**. At **S510**, the CPU **101** determines whether the moving-image recording operation was performed. At **S511**, the CPU **101** starts or stops the recording of the moving image. At **S512** and **S513**, the CPU **101** determines whether the still-image photographing operation was performed, and if the still-image photographing operation was performed, the still image is photographed.

(98) At **S514**, the CPU **101** determines whether the moving image is being recorded. If the moving image is being recorded, the processing returns to **S503**, while if the moving image is not being recorded, the processing proceeds to **S515**. At **S515**, the CPU **101** determines whether the photographing standby state has been finished. If the photographing standby state has been finished, the view-angle switching processing shown in FIG. **5** is finished, while if the photographing standby state has not been finished, the processing returns to **S503**.

(99) In the second embodiment described above, the switching of the non-priority lens to the lens in use in the priority image-pickup mode is limited. On the other hand, the switching of the priority lens to the lens in use in the non-priority image-pickup mode is not limited. When the priority lens is to be switched to the lens in use in the non-priority image-pickup mode, the CPU **101** switches the non-priority lens to the lens not in use in the priority image-pickup mode or the non-priority image-pickup mode. By switching the angle of view through the lens not in use as described above, the user can seamlessly switch the angle of view from the wide angle to the telephoto without interrupting the image pickup processing executed in parallel. Moreover, when the image is being picked up in the moving-image mode and the still-image mode in parallel, a labor for the user to switch the angle of view in the priority image-pickup mode can be reduced.

(100) The explanation has been made with the example in which the picked-up image in the priority image-pickup mode is LV-displayed on the main image area **301**, but the CPU **101** may use the image-pickup mode on the sub image area **305** as the priority image-pickup mode without changing the area for the LV-display even if the priority image-pickup mode is changed. In this case, the CPU **101** controls so that the lens to be used in the non-priority image-pickup mode on the main image area **301** is not changed to the lens in use in the priority image-pickup mode on the sub image area **305**. Moreover, the change of the priority image-pickup mode can be realized by displaying the item indicating the priority image-pickup mode on either of the main image area **301** and the sub image area **305** and by moving the item by the user by the touch-move between the areas, for example.

Third Embodiment

(101) In a third embodiment, the user can perform the still-image photographing by switching the LV-display for the moving image to the LV-display for the still-image photographing while the recording of the moving image is continued. The out-camera **114** includes the three lenses, that is,

the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c** with angles of view different from one another. The out-camera **114** can pick up images in a plurality of the image-pickup modes in parallel by using the three lenses. In the third embodiment, the display **105** is not divided into areas as in the first embodiment and the second embodiment, but the LV-display in the still-image mode and the LV-display in the moving-image mode can be switched in accordance with the user's operation, instead of the division of the areas as in the first and second embodiment. (102) FIGS. **6A** to **6E** are diagrams for explaining the switching processing of the LV-display in the third embodiment. An LV-display screen **601** in FIG. **6A** is a screen in which a picked-up image picked up in the moving-image mode by using the standard lens **114b** is LV-displayed on the display **105**.

(103) An icon **602** is an icon indicating a display state and indicates that the LV-display screen **601** LV-displays the picked-up image in the moving-image mode. The display state is a state where the picked-up image in the moving-image mode is LV-displayed on the display **105** or a state where the picked-up image in the still-image mode is LV-displayed. An icon **603** is an icon indicating a moving-image recording state and indicates that a recording-start operation of the moving image is on standby. An LV-display switching button **604** is the operation member (item) for the switching operation of switching between the LV-display in the moving-image mode and the LV-display in the still-image mode. The LV-display switching button **604** is an example of a fifth item.

(104) An icon **605** in FIG. **6B** is an icon indicating the moving-image recording state and indicates that an LV-image in the moving-image mode displayed on the display **105** is being recorded. Start and stop of the moving-image recording is executed by an item (not shown) similar to the moving-image recording button **304** explained in FIG. **3A**, for example.

(105) An LV-display screen **611** in FIG. **6C** is a screen in which a picked-up image picked up in the still-image mode by using the telephoto lens **114a** is LV-displayed on the display **105**. An icon **612** is an icon indicating the display state and indicates that the LV-display screen **611** LV-displays the picked-up image in the still-image mode.

(106) An image **621** in FIG. **6D** is a still image generated by a still-image photographing operation from an image on the LV-display screen **611** in FIG. **6C** picked up in the still-image mode by using the telephoto lens **114a**. An image **631** in FIG. **6E** is a still image with the same angle of view as a moving image generated by cutting out one frame from a moving image picked up in the moving-image mode by using the standard lens **114b**.

(107) FIG. **7** is a flowchart exemplifying the LV-display switching processing according to the third embodiment. The LV-display switching processing in FIG. **7** is realized by the CPU **101** of the smartphone **100** which develops the program recorded in the non-volatile memory **103** to the memory **102** and executes it.

(108) At **S701**, the CPU **101** accepts the user operation. If the accepted user operation is the switching operation of the LV-display, the processing proceeds to **S702**. As the switching operation of the LV-display, an operation of touching the LV-display switching button **604** displayed on the display **105** is assumed, but this is not limiting. The switching operation of the LV-display may be the operation of double-tap or the touch-move on the LV-image displayed on the display **105** or may be pressing-down on a physical button. The user can cause a picked-up image in the still-image mode on an area including a subject or a desired position to be LV-displayed by double-tapping the subject or by surrounding the area (position) to be photographed by the touch-move on the LV image, for example.

(109) At **S702**, the CPU **101** determines the display state of the display **105**. The display state is a state where the picked-up image in the moving-image mode is LV-displayed or the picked-up image in the still-image mode is LV-displayed on the display **105**. If the picked-up image in the moving-image mode is LV-displayed, the processing proceeds to **S703**, while if the picked-up image in the still-image mode is LV-displayed, the processing proceeds to **S707**.

(110) At **S703**, the CPU **101** determines which of the telephoto lens **114a**, the standard lens **114b**,

and the wide-angle lens **114c** is the lens in use for the LV-display in the moving-image mode. When the lens in use in the moving-image mode is the wide-angle lens **114c** or telephoto lens **114a**, the processing proceeds to **S704**. When the lens in use in the moving-image mode is the standard lens **114b**, the processing proceeds to **S705**.

(111) At **S704**, the CPU **101** starts image pickup in the still-image mode by using the standard lens **114b**. The CPU **101** can then, LV-display the picked-up image picked up in the still-image mode by using the standard lens **114b** on the display **105** or photograph it as a still image.

(112) At **S705**, the CPU **101** starts image pickup in the still-image mode by using the telephoto lens **114a**. The CPU **101** can then, LV-display the picked-up image picked up in the still-image mode by using the telephoto lens **114a** on the display **105** or photograph it as a still image.

(113) **S703** to **S705** show examples in which the lens for the still image is determined on the basis of whether the lens in use in the moving-image mode is the wide-angle lens **114c**, the telephoto lens **114a** or the standard lens **114b**, but they are not limiting. The lens for the still image only needs to be determined to be a lens different from the lens used in the moving-image mode. For example, the lens used in the still-image mode may be determined so as to be a lens closer to the telephoto side than the lens used in the moving-image mode.

(114) At **S706**, the CPU **101** changes the display of the display **105** from the LV-display in the moving-image mode to the LV-display in the still-image mode. When the moving image is being recorded in the moving-image mode, the CPU **101** LV-displays the picked-up image in the still-image mode while the recording of the moving image is continued. The CPU **101** changes the icon indicating the display state of the display **105** to the icon **612** indicating the LV-display in the still-image mode and returns to **S701**.

(115) At **S707**, the CPU **101** determines which of the telephoto lens **114a**, the standard lens **114b** and the wide-angle lens **114c** is the lens in use for the LV-display in the still-image mode. When the lens in use in the still-image mode is the wide-angle lens **114c**, the processing proceeds to **S708**. When the lens in use in the still-image mode is the telephoto lens **114a** or the standard lens **114b**, the processing proceeds to **S709**.

(116) At **S708**, the CPU **101** starts image pickup in the moving-image mode by using the standard lens **114b**. The CPU **101** can then, LV-display the picked-up image picked up in the moving-image mode by using the standard lens **114b** on the display **105** or record it as the moving image.

(117) At **S709**, the CPU **101** starts image pickup in the moving-image mode by using the wide-angle lens **114c**. The CPU **101** can then, LV-display the picked-up image picked up in the moving-image mode by using the wide-angle lens **114c** on the display **105** or record it as the moving image.

(118) **S707** to **S709** show examples in which the lens for the moving image is determined on the basis of whether the lens in use in the still-image mode is the wide-angle lens **114c**, the telephoto lens **114a** or the standard lens **114b**, but they are not limiting. The lens for the moving image only needs to be determined to be a lens different from the lens used in the still-image mode. For example, the lens used in the moving-image mode may be determined so as to be a lens closer to the wide-angle side than the lens used in the still-image mode.

(119) At **S710**, the CPU **101** changes the display of the display **105** from the LV-display in the still-image mode to the LV-display in the moving-image mode. The CPU **101** changes the icon indicating the display state of the display **105** to the icon **602** indicating the LV-display in the moving-image mode and returns to **S701**.

(120) If the user operation accepted at **S701** is the operation of still-image photographing, the processing proceeds to **S711**. At **S711**, the CPU **101** determines the display state of the display **105**. If the picked-up image in the moving-image mode is LV-displayed on the display **105**, the processing proceeds to **S712**. If the picked-up image in the still-image mode is LV-displayed on the display **105**, the processing proceeds to **S713**.

(121) At **S712**, the CPU **101** photographs a still image by the lens in use in the moving-image mode. The CPU **101** cuts out one frame from the moving image picked up by the lens in use in the

moving-image mode, generates a still image with the same angle of view as that of the moving image as the image **631** shown in FIG. **6E** and returns to **S701**.

(122) At **S713**, the CPU **101** photographs a still image by the lens in use in the still-image mode. Since the lens in use in the still-image mode is different from the lens used in the moving-image mode, the CPU **101** generates a still image with an angle of view different from that of the moving image as the image **621** shown in FIG. **6D** and returns to **S701**.

(123) If the user operation accepted at **S701** is the operation of start/stop the moving-image recording, the processing proceeds to **S714**. At **S714**, the CPU **101** determines the recorded state of the moving image. In the case of standby, the processing proceeds to **S715**, while in the case of recording, the processing proceeds to **S721**.

(124) At **S715**, the CPU **101** determines the display state of the display **105**. If the picked-up image in the moving-image mode is LV-displayed on the display **105**, the processing proceeds to **S716**. If the picked-up image in the still-image mode is LV-displayed on the display **105**, the processing proceeds to **S717**.

(125) At **S716**, the CPU **101** starts the moving-image recording by the lens in use in the moving-image mode. The CPU **101** changes the icon indicating the moving-image recording state to the icon **605** indicating recording and returns to **S701**.

(126) At **S717**, the CPU **101** determines which of the telephoto lens **114a**, the standard lens **114b**, and the wide-angle lens **114c** is the lens in use on the LV-display in the still-image mode. When the lens in use in the still-image mode is the wide-angle lens **114c**, the processing proceeds to **S718**. When the lens in use in the still-image mode is the telephoto lens **114a** or the standard lens **114b**, the processing proceeds to **S719**.

(127) At **S718**, the CPU **101** starts image pickup in the moving-image mode by using the standard lens **114b** and proceeds to **S720**. At **S719**, the CPU **101** starts image-pickup in the moving-image mode by using the wide-angle lens **114c** and proceeds to **S720**.

(128) **S717** to **S719** show examples in which the lens for the moving image is determined on the basis of whether the lens in use in the still-image mode is the wide-angle lens **114c**, the telephoto lens **114a** or the standard lens **114b**, but they are not limiting. The lens for the moving image only needs to be determined to be a lens different from the lens used in the still-image mode. For example, the lens used in the moving-image mode may be determined so as to be a lens closer to the wide-angle side than the lens used in the still-image mode.

(129) At **S720**, the CPU **101** changes the display of the display **105** from the LV-display in the still-image mode to the LV-display in the moving-image mode and starts the moving-image recording. The CPU **101** changes the icon indicating the moving-image recording state to the icon **605** indicating that the moving image is being recorded and returns to **S701**.

(130) If the moving image is being recorded at **S714**, the CPU **101** stops the moving-image recording at **S721**, changes the icon indicating the moving-image recording state to the icon **603** indicating the standby for the recording-start operation of the moving image and returns to **S701**.

(131) If the user operation accepted at **S701** is an operation of finishing the LV, the LV-display switching processing shown in FIG. **7** is finished.

(132) FIG. **8** is a diagram for explaining zoom-out processing in the still-image LV-display. When the display of the display **105** is changed to the LV-display in the still-image mode during recording of the moving image by using the wide-angle lens **114c** and performs zoom-out by the pinch-in operation, such a state is brought about that a wide-end of the standard lens **114b** is zoomed-out the most. That is because the wide-angle lens **114c** is in use in the moving-image mode, and the lens used in the still-image mode is not switched to the wide-angle lens **114c**. On the LV-display screen **801** in FIG. **8**, when the user performs the zoom-out by the pinch-in operation and reaches a wide end of the standard lens **114b**, the CPU **101** displays a notification **802** that “No-more zoom-out possible” on the display **105**.

(133) On the contrary, during the recording of the moving image using the telephoto lens **114a**,

when the display of the display **105** is changed to the LV-display in the still-image mode, and the zoom-in is performed by the pinch-out operation, the tele-end of the standard lens **114b** is brought into a state of zoomed-in the most. That is because the telephoto lens **114a** is used in the moving-image mode, and the lens used in the still-image mode is not switched to the telephoto lens **114a**. In this case, when the user performs the zoom-in by the pinch-out operation and reaches the tele-end of the standard lens **114b**, the CPU **101** displays a notification that “No-more zoom-in possible” on the display **105**.

(134) By referring to FIGS. **9A** to **9C**, zoom-in/zoom-out processing on the still-image LV-display according to the third embodiment will be explained. FIG. **9A** is a flowchart exemplifying the zoom-in/zoom-out processing. FIG. **9B** is a flowchart exemplifying details of the zoom-in processing. FIG. **9C** is a flowchart exemplifying details of the zoom-out processing. The zoom-in/zoom-out processing in FIGS. **9A** to **9C** is realized by the CPU **101** of the smartphone **100** which develops the program which is recorded in the non-volatile memory **103** to the memory **102** and executes it.

(135) At **S900**, the CPU **101** accepts the user operation. If the accepted user operation is the pinch-out operation, the CPU **101** proceeds to **S910**, changes the zoom magnification of the picked-up image by the still-image mode, and executes the zoom-in (enlargement) processing. If the accepted user operation is the pinch-in operation, the CPU **101** proceeds to **S930**, changes the zoom magnification of the picked-up image by the still-image mode, and executes the zoom-out (reduction) processing. If the accepted user operation is an operation of LV end, the zoom-in/zoom-out processing shown in FIG. **9A** is finished.

(136) By referring to FIG. **9B**, details of the zoom-in processing at **S910** will be explained. At **S911**, the CPU **101** determines which of the wide-angle lens **114c**, the standard lens **114b**, and the telephoto lens **114a** is the lens in use for the LV-display in the still-image mode. When the lens in use in the still-image mode is the wide-angle lens **114c**, the processing proceeds to **S912**. When the lens in use in the still-image mode is the standard lens **114b**, the processing proceeds to **S920**, and when the lens in use in the still-image mode is the telephoto lens **114a**, the processing proceeds to **S924**.

(137) At **S912**, the CPU **101** acquires a zoom position (zoom magnification) on the basis of the pinch-out operation by the user. When the zoom position by the pinch-out operation is closer to the wide side (Wide-side, wide-angle side) than the tele-end (Tele-end) of the wide-angle lens **114c**, the processing proceeds to **S913**. When the zoom position by the pinch-out operation is closer to a tele-side (Tele side, telephoto side) than the tele-end of the wide-angle lens **114c** and closer to a wide side than a wide-end (Wide-end) of the telephoto lens **114a**, the processing proceeds to **S914**. When the zoom position by the pinch-out operation is closer to the tele side than the wide-end of the telephoto lens **114a**, the processing proceeds to **S916**.

(138) At **S913**, the CPU **101** executes the zoom-in processing by the wide-angle lens **114c** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-in processing by changing the zoom position to the position acquired at **S912** by digital zoom of the picked-up image by the wide-angle lens **114c**, for example.

(139) At **S914**, the CPU **101** determines whether the moving image is being recorded by the standard lens **114b**. If the moving image is being recorded by the standard lens **114b**, the processing proceeds to **S913**. If the moving image is not being recorded by the standard lens **114b**, the processing proceeds to **S915**.

(140) At **S915**, the CPU **101** changes the lens to be used for the LV-display in the still-image mode to the standard lens **114b** with a smaller angle of view. The CPU **101** executes the zoom-in processing by the standard lens **114b** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-in processing by changing the zoom position to the position acquired at **S912** by digital zoom of the picked-up image by the standard lens **114b**, for example.

(141) At **S916**, the CPU **101** determines whether the moving-image is being recorded by the

telephoto lens **114a**. If the moving image is being recorded by the telephoto lens **114a**, the processing proceeds to **S915**. If the moving image is not being recorded by the telephoto lens **114a**, the processing moves to **S917**. At **S917**, the CPU **101** changes the lens to be used for the LV-display in the still-image mode to the telephoto lens **114a** with a smaller angle of view. The CPU **101** executes the zoom-in processing by the telephoto lens **114a** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-in processing by changing the zoom position to the position acquired at **S912** by digital zoom of the picked-up image by the telephoto lens **114a**, for example. (142) At **S920**, the CPU **101** acquires the zoom position on the basis of the pinch-out operation by the user. If the zoom position by the pinch-out operation is closer to the wide side than the tele-end of the standard lens **114b**, the processing proceeds to **S921**. If the zoom position by the pinch-out operation is closer to the tele side than the tele-end of the standard lens **114b**, the processing proceeds to **S922**.

(143) At **S921**, the CPU **101** executes the zoom-in processing by the standard lens **114b** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-in processing by changing the zoom position to the position acquired at **S920** by digital zoom of the picked-up image by the standard lens **114b**, for example.

(144) At **S922**, the CPU **101** determines whether the moving image is being recorded by the telephoto lens **114a**. If the moving image is being recorded by the telephoto lens **114a**, the processing proceeds to **S921**. If the moving image is not being recorded by the telephoto lens **114a**, the processing proceeds to **S923**.

(145) At **S923**, the CPU **101** changes the lens to be used for the LV-display in the still-image mode to the telephoto lens **114a** with a smaller angle of view. The CPU **101** executes the zoom-in processing by the telephoto lens **114a** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-in processing by changing the zoom position to the position acquired at **S920** by digital zoom of the picked-up image by the telephoto lens **114a**, for example.

(146) At **S924**, the CPU **101** executes the zoom-in processing by the telephoto lens **114a** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-in processing by acquiring the zoom position on the basis of the pinch-out operation by the user and by changing the zoom position to the acquired zoom position by digital zoom of the picked-up image by the telephoto lens **114a**.

(147) By referring to FIG. **9C**, details of the zoom-out processing at **S930** will be explained. At **S931**, the CPU **101** determines which of the wide-angle lens **114c**, the standard lens **114b**, and the telephoto lens **114a** is the lens in use for the LV-display in the still-image mode. When the lens in use in the still-image mode is the telephoto lens **114a**, the processing proceeds to **S932**. When the lens in use in the still-image mode is the standard lens **114b**, the processing proceeds to **S930**, and when the lens in use in the still-image mode is the wide-angle lens **114c**, the processing proceeds to **S935**.

(148) At **S932**, the CPU **101** acquires a zoom position (zoom magnification) on the basis of the pinch-in operation by the user. When the zoom position by the pinch-in operation is closer to the tele side than the wide-end of the telephoto lens **114a**, the processing proceeds to **S933**. When the zoom position by the pinch-in operation is closer to the wide-side than the wide-end of the telephoto lens **114a** and closer to the tele side than a wide-end of the standard lens **114b**, the processing proceeds to **S934**. When the zoom position by the pinch-in operation is closer to the wide side than the wide-end of the standard lens **114b**, the processing proceeds to **S937**.

(149) At **S933**, the CPU **101** executes the zoom-out processing by the telephoto lens **114a** and returns to **S900** in FIG. **9A**. The CPU **101** can execute the zoom-out processing by changing the zoom position to the position acquired at **S932** by digital zoom of the picked-up image by the telephoto lens **114a**, for example.

(150) At **S934**, the CPU **101** determines whether the moving image is being recorded by the standard lens **114b**. If the moving image is being recorded by the standard lens **114b**, the processing

proceeds to S936. If the moving image is not being recorded by the standard lens **114b**, the processing proceeds to S935.

(151) At S935, the CPU **101** changes the lens to be used for the LV-display in the still-image mode to the standard lens **114b** with a wider angle of view. The CPU **101** executes the zoom-out processing by the standard lens **114b** and returns to S900 in FIG. 9A. The CPU **101** can execute the zoom-out processing by changing the zoom position to the position acquired at S932 by digital zoom of the picked-up image by the standard lens **114b**, for example.

(152) At S936, the CPU **101** changes the lens to be used for the LV-display in the still-image mode to the wide-angle lens **114c** with a wider angle of view. The CPU **101** executes the zoom-out processing by the wide-angle lens **114c** and returns to S900 in FIG. 9A. The CPU **101** can execute the zoom-out processing by changing the zoom position to the position acquired at S932 by digital zoom of the picked-up image by the wide-angle lens **114c**, for example.

(153) At S937, the CPU **101** determines whether the moving-image is being recorded by the wide-angle lens **114c**. If the moving image is being recorded by the wide-angle lens **114c**, the lens in use in the still-image mode is not switched to the wide-angle lens **114c**, but the processing proceeds to S938. If the moving image is not being recorded by the wide-angle lens **114c**, the processing proceeds to S936.

(154) At S938, the CPU **101** displays the notification **802** to notify the user that no more zoom-out will be performed on the display **105** as described in FIG. 8 and returns to S900 in FIG. 9A.

(155) At S940, the CPU **101** acquires the zoom position on the basis of the pinch-in operation by the user. When the zoom position by the pinch-in operation is closer to the tele side than the wide-end of the standard lens **114b**, the processing proceeds to S941. When the zoom position by the pinch-in operation is closer to the wide side than the wide-end of the standard lens **114b**, the processing proceeds to S942.

(156) At S941, the CPU **101** executes the zoom-out processing by the standard lens **114b** and returns to S900 in FIG. 9A. The CPU **101** can execute the zoom-out processing by changing the zoom position to the position acquired at S940 by digital zoom of the picked-up image by the standard lens **114b**, for example.

(157) At S942, the CPU **101** determines whether the moving-image is being recorded by the wide-angle lens **114c**. If the moving image is being recorded by the wide-angle lens **114c**, the lens in use in the still-image mode is not switched to the wide-angle lens **114c**, but the processing proceeds to S944. If the moving image is not being recorded by the wide-angle lens **114c**, the processing proceeds to S943.

(158) At S943, the CPU **101** changes the lens to be used for the LV-display in the still-image mode to the wide-angle lens **114c** with a wider angle of view. The CPU **101** executes the zoom-out processing by the wide-angle lens **114c** and returns to S900 in FIG. 9A. The CPU **101** can execute the zoom-out processing by changing the zoom position to the position acquired at S940 by digital zoom of the pick-up image by the wide-angle lens **114c**, for example.

(159) At S944, the CPU **101** displays the notification **802** to notify the user that no more zoom-out will be performed on the display **105** as described in FIG. 8 and returns to S900 in FIG. 9A.

(160) At S945, the CPU **101** acquires the zoom position on the basis of the pinch-in operation by the user. When the zoom position by the pinch-in operation is closer to the tele side than the wide-end of the wide-angle lens **114c**, the processing proceeds to S946. When the zoom position by the pinch-in operation is closer to the wide side than the wide-end of the wide-angle lens **114c**, the processing proceeds to S947.

(161) At S946, the CPU **101** executes the zoom-out processing by the wide-angle lens **114c** and returns to S900 in FIG. 9A. The CPU **101** can execute the zoom-out processing by changing the zoom position to the position acquired at S945 by digital zoom of the picked-up image by the wide-angle lens **114c**, for example.

(162) At S947, the CPU **101** displays the notification **802** to notify the user that no more zoom-out

will be performed on the display **105** as described in FIG. **8** and returns to **S900** in FIG. **9A**.

(163) By referring to FIGS. **10A** and **10B**, processing of superimposing and displaying the picked-up image in the moving-image mode on the picked-up image in the still-image mode, which is LV-displayed (hereinafter, referred to as moving-image LV superimposed-display processing) will be explained. During the moving-image recording, if the display on the display **105** is switched to the LV-display in the still-image mode, when a direction of the camera is changed for photographing a still image, a range to be recorded in the moving image is changed.

(164) Thus, in the third embodiment, by a predetermined operation performed by the user when the picked-up image in the still-image mode is LV-displayed, the CPU **101** causes the LV-image in the moving-image mode to be superimposed and displayed on the LV-image in the still-image mode. The predetermined operation is a panning operation, a tilting operation, a pinch-out operation, a pinch-in operation, a flick operation, or the like, for example.

(165) A still-image LV-display screen **1001** in FIG. **10A** is a screen on which the picked-up image picked up in the still-image mode by using the telephoto lens **114a** is LV-displayed on the display **105**. The icon **605** indicates that the moving image is being recorded in the moving-image mode by using the lens other than the telephoto lens **114a**.

(166) A still-image LV-display screen **1002** in FIG. **10B** is a screen in which an image-pickup range was changed, and a position of the subject was moved from the still-image LV-display screen **1001** in FIG. **10A** by the panning operation of the out-camera **114** by the user.

(167) A sub screen **1003** superimposed and displayed on the still-image LV-display screen **1002** is a screen in which the picked-up image picked up in the moving-image mode by using the standard lens **114b** and is being recorded as the moving image is LV-displayed. Since the picked-up image in the moving-image mode is LV-displayed on the sub screen **1003**, the user can check the image pickup state (recording state) of the moving image.

(168) FIG. **11** is a flowchart exemplifying the moving-image LV superimposed-display processing according to the third embodiment. The moving-image LV superimposed-display processing in FIG. **11** is realized by the CPU **101** of the smartphone **100** which develops the program recorded in the non-volatile memory **103** to the memory **102** and executes it.

(169) At **S1101**, the CPU **101** accepts the user operation. If the accepted user operation is the panning operation or the tilting operation of the out-camera **114**, the processing proceeds to **S1102**. If the accepted user operation is the pinch-in operation or the pinch-out operation, the processing proceeds to **S1105**. If the accepted user operation is the flick operation, the processing proceeds to **S1106**. If the accepted operation is an operation of finishing LV-display in the still-image mode, the processing proceeds to **S1111**.

(170) At **S1102**, the CPU **101** superimposes and displays the sub screen **1003** which LV-displays the picked-up image in the moving-image mode on the still-image LV-display screen **1002** as explained in FIG. **10B**. At **S1103**, the CPU **101** determines whether the predetermined time has elapsed since the sub screen **1003** was superimposed and displayed at **S1102**. If the predetermined time has elapsed, the processing proceeds to **S1104**. If the predetermined time has not elapsed, the CPU **101** returns to **S1103** and is brought into the standby state until the predetermined time has elapsed. When the predetermined time has elapsed, at **S1104**, the CPU **101** erases the sub screen **1003** on which the picked-up image in the moving-image mode is LV-displayed.

(171) At **S1105**, if the CPU **101** accepts the pinch-out operation at **S1101**, it zooms in the LV image in the still-image mode, while at **S1101**, if the CPU **101** accepts the pinch-in operation, it zooms out the LV-image in the still-image mode and proceeds to **S1102**. Since there is a possibility that the image pickup range in the moving-image mode is changed even in the case of zoom-in or zoom-out of the LV-image in the still-image mode, the CPU **101** displays the sub screen **1003** which LV-displays the picked-up image in the moving-image mode.

(172) At **S1106**, the CPU **101** determines a flick direction of the flick operation accepted at **S1101**. If the flick direction is a direction from the end of the touch panel **106a** toward the center, the CPU

101 controls to display the sub screen **1003** which LV-displays the picked-up image in the moving-image mode. On the other hand, if the flick direction is a direction from the center of the touch panel **106a** toward the end, the CPU **101** controls to erase the sub screen **1003** which LV-displays the picked-up image in the moving-image mode similarly to the panning operation case.

(173) If the flick direction is the direction from the end of the touch panel **106a** toward the center, the processing proceeds to **S1107**. If the flick direction is the direction from the center of the touch panel **106a** toward the end, the processing proceeds to **S1109**.

(174) At **S1107**, the CPU **101** determines whether the sub screen **1003** which LV-displays the picked-up image in the moving-image mode is superimposed and displayed on the still-image LV-display screen **1002**. If the sub screen **1003** is displayed, the processing returns to **S1101**. If the sub screen **1003** is not displayed, the processing proceeds to **S1108**. At **S1108**, the CPU **101** superimposes and displays the sub screen **1003** which LV-displays the picked-up image in the moving-image mode on the still-image LV-display screen **1002** and returns to **S1101**.

(175) At **S1109**, the CPU **101** determines whether the sub screen **1003** which LV-displays the picked-up image in the moving-image mode is superimposed and displayed on the still-image LV-display screen **1002**. If the sub screen **1003** is displayed, the processing proceeds to **S1110**. If the sub screen **1003** is not displayed, the processing returns to **S1101**. At **S1110**, the CPU **101** erases the sub screen **1003** which is superimposed and displayed on the still-image LV-display screen **1002** and returns to **S1101**.

(176) If the operation accepted at **S1101** is the operation of finishing the LV-display in the still-image mode, the processing proceeds to **S1111**. The operation of finishing the LV-display in the still-image mode is an operation of switching to the LV-display in the moving-image mode, for example, and is an operation of touching the LV-display switching button **604** in FIG. **10A**. At **S1111**, the CPU **101** finishes the LV-display in the still-image mode, and the moving-image LV superimposed-display processing shown in FIG. **11** is finished.

(177) According to the third embodiment described above, even during the moving-image recording, the user can cause the picked-up image in the still-image mode to be LV-displayed substantially on the whole display **105**. As a result, the user can easily check the subject for which a still image is to be photographed and photograph a desired still image.

(178) Moreover, the user can superimpose and display the sub screen for LV-displaying the moving image being recorded on the LV-display screen in the still-image mode by performing a predetermined operation. Even if the image pickup range in the moving-image mode is changed by the panning operation or the like for the photographing of a still image, the user can check the image pickup state of the moving image by the LV-display in the moving-image mode displayed on the sub screen.

(179) The example in which the out-camera **114** includes a plurality of lenses with angles of view different from one another, and images are picked up by using the different lenses for the moving-image mode and the still-image mode has been explained, but this is not limiting. The out-camera **114** may include a single lens. In this case, the picked-up image in the still-image mode is generated by cutting out one frame from the picked-up image (moving image) by the moving-image mode. When the pinch-out operation or the pinch-in operation is accepted in the still-image mode, the CPU **101** can execute the zoom-in processing or the zoom-out processing by digital zoom of the cut-out image.

(180) According to this disclosure, in the case of image pickup in a plurality of image-pickup modes in parallel, the angle of view can be seamlessly switched from the wide angle to the telephoto without interrupting the photographing.

OTHER EMBODIMENTS

(181) The present invention has been explained in detail on the basis of the preferred embodiments thereof, but the present invention is not limited to these specific embodiments but also includes various forms within a range not departing from the gist of the present invention. A part of the

aforementioned embodiments may be combined as appropriate. The case in which the present invention is applied to the smartphone was explained as an example, but this is not limiting but can be applied to any electronic device having a photographing means capable of photographing images in a plurality of image-pickup modes in parallel by using a plurality of lenses with angles of view different from each other. That is, the present invention can be applied to a digital camera, a tablet terminal, and the like.

(182) Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a ‘non-transitory computer-readable storage medium’) to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

(183) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(184) This application claims the benefit of Japanese Patent Application No. 2022-070161, filed on Apr. 21, 2022, which is hereby incorporated by reference herein in its entirety.

Claims

1. An image pickup device having a plurality of lenses with angles of view different from one another and capable of image pickup in parallel in a first image-pickup mode and a second image-pickup mode, comprising at least one memory and at least one processor which function as: an accepting unit configured to accept a switching operation of switching a lens to be used for image pickup of a picked-up image which is picked up in the first image-pickup mode and displayed on a first image area, or a lens to be used for image pickup of a picked-up image which is picked up in the second image-pickup mode and displayed on a second image area; and a control unit configured to control such that the lens to be used for the image pickup is switched in response to an acceptance of the switching operation of the lens to be used for the image pickup of the picked-up image which is displayed on the first image area or the image pickup of the picked-up image which is displayed on the second image area, wherein the control unit controls such that lenses to be used in the first image-pickup mode and the second image-pickup mode are switched such that different lenses are used in the first image-pickup mode and the second image-pickup mode; and the accepting unit includes a first item which is superimposed and displayed on a picked-up image displayed on the first image area and switches a lens used in the first image-pickup mode and a second item which is superimposed and displayed on a picked-up image displayed on the second image area and switches a lens used in the second image-pickup mode.

2. The image pickup device according to claim 1, wherein when a first lens is used in the first image-pickup mode and a second lens is used in the second image-pickup mode, if the switching operation of switching the lens used in the first image-pickup mode to the second lens is accepted, the control unit controls such that the lens used in the second image-pickup mode is switched to a third lens different from the first lens and the second lens, and the lens used in the first image-pickup mode is switched to the second lens.
3. The image pickup device according to claim 1, wherein when a first lens is used in the first image-pickup mode and a second lens is used in the second image-pickup mode, if the switching operation of switching the lens used in the first image-pickup mode to a third lens different from the first lens and the second lens is accepted, the control unit controls such that the lens used in the first image-pickup mode is switched to the third lens, and the lens used in the second image-pickup mode remains to be the second lens.
4. The image pickup device according to claim 1, wherein when the accepting unit accepts the switching operation of the lens used in the second image-pickup mode, the accepting unit controls such that the switching to the lens in use in the first image-pickup mode is not accepted.
5. The image pickup device according to claim 4, wherein when the accepting unit accepts the switching operation of the lens used in the first image-pickup mode, the accepting unit controls such that the switching to the lens in use in the first image-pickup mode can be also accepted.
6. The image pickup device according to claim 1, wherein when a moving image is not being recorded in the first image-pickup mode, the control unit controls such that the lens used in the first image-pickup mode can be switched from the lens in use to another lens, while when a moving image is being recorded in the first image-pickup mode, the lens used in the first image-pickup mode is not switched.
7. The image pickup device according to claim 1, wherein the accepting unit displays an item for accepting a switching operation of a lens used in image pickup together with a picked-up image picked up in the first image-pickup mode on a display unit of the image pickup device and accepts the switching operation in response to an operation to the item.
8. The image pickup device according to claim 1, wherein the accepting unit includes a first item which is superimposed and displayed on a picked-up image in the first image-pickup mode and switches a lens used in the first image-pickup mode and a second item which is superimposed and displayed on a picked-up image in the second image-pickup mode and switches a lens used in the second image-pickup mode.
9. The image pickup device according to claim 1, wherein the accepting unit includes a third item which is superimposed and displayed on a picked-up image in the first image-pickup mode and switches a lens used in each of the first image-pickup mode and the second image-pickup mode, respectively; and the control unit is configured to: switch a lens used in the first image-pickup mode to a selected lens in a case where an operation to the third item is an operation by a single-touch at one spot; and switch the lens used in the second image-pickup mode to the selected lens in a case where an operation to the third item is an operation by a multi-touch at two spots or more.
10. The image pickup device according to claim 1, wherein when a moving image is being recorded in the first image-pickup mode, the accepting unit does not include the lens in use in the first image-pickup mode in candidates for a lens which can be switched in the second image-pickup mode.
11. The image pickup device according to claim 1, wherein the accepting unit: accepts an operation of setting the first image-pickup mode to a priority image-pickup mode with priority over the second image-pickup mode; and does not include the lens in use in the first image-pickup mode set to the priority image-pickup mode in candidates for a lens which can be switched in the second image-pickup mode.
12. The image pickup device according to claim 11, wherein an operation of setting the priority image-pickup mode is an operation of touch-move of a picked-up image in the image-pickup mode

of a setting target to an area on which a picked-up image in the priority image-pickup mode is displayed.

13. The image pickup device according to claim 11, wherein an operation of setting the priority image-pickup mode is an operation of changing a direction of a display of the image pickup device, and an image-pickup mode set in advance in accordance with the direction of the display is set as the priority image-pickup mode.

14. The image pickup device according to claim 1, wherein the accepting unit includes a fourth item for photographing a still image which can be moved between on a picked-up image in the first image-pickup mode and on a picked-up image in the second image-pickup mode; and the control unit is configured to control to: photograph a still image by a lens in use in the first image-pickup mode in a case where the fourth item is on the picked-up image in the first image-pickup mode; and photograph a still image by a lens in use in the second image-pickup mode in a case where the fourth item is on the picked-up image in the second image-pickup mode.

15. An image pickup device capable of image pickup in a plurality of image-pickup modes, comprising at least one memory and at least one processor which function as: a display control unit configured to live-view display any one of picked-up images picked up in the same direction in parallel in the plurality of image-pickup modes; and an accepting unit configured to accept a switching operation of switching between live-view display of a first picked-up image in a first picked-up image and live-view display of a second picked-up image in a second picked-up image, wherein the display control unit live-view displays the first picked-up image in the first image-pickup mode and, when the switching operation is accepted while a moving image is being recorded in the first image-pickup mode, live-view displays the second picked-up image in the second image-pickup mode while a recording of the moving image in the first image-pickup mode is continued.

16. The image pickup device according to claim 15, wherein the image pickup device has a plurality of lenses with angles of view different from one another and picks up images by using different lenses for the first image-pickup mode and the second image-pickup mode.

17. The image pickup device according to claim 15, wherein the image pickup device has a single lens; and the second picked-up image is generated by being cut out from the first picked-up image.

18. The image pickup device according to claim 15, wherein the accepting unit includes a fifth item for switching the image-pickup mode to be a target of the live-view display; and the switching operation is an operation of touching the fifth item.

19. The image pickup device according to claim 15, wherein the switching operation is an operation of double-tap or touch-move on the first picked-up image which is live-view displayed; and the display control unit live-view displays an image of an area including a position or a subject which was double-tapped or touch-moved as the second picked-up image.

20. The image pickup device according to claim 15, wherein the accepting unit accepts a pinch-out operation or a pinch-in operation for the second picked-up image which is live-view displayed; and the display control unit enlarges or reduces the second picked-up image by a zoom magnification acquired on the basis of the pinch-out operation or the pinch-in operation.

21. The image pickup device according to claim 20, wherein the image pickup device has a plurality of lenses with angles of view different from one another; and the at least one memory and the at least one processor further function as a control unit configured to control such that: when the zoom magnification becomes a magnification closer to a telephoto side than a tele-end of a lens in use in the second image-pickup mode by the pinch-out operation, the lens in the second image-pickup mode is switched to a lens with a smaller angle of view; and when the zoom magnification becomes a magnification closer to a wide-angle side than a wide-end of a lens in use in the second image-pickup mode by the pinch-in operation, the lens in the second image-pickup mode is switched to a lens with a wider angle of view.

22. The image pickup device according to claim 21, wherein the control unit executes control such

that the lens in use in the second image-pickup mode is not switched to a lens in use in the first image-pickup mode.

23. The image pickup device according to claim 15, wherein when the second picked-up image is live-view displayed, the display control unit causes the first picked-up image being recorded as the moving image to be superimposed on the second picked-up image and live-view displayed.

24. The image pickup device according to claim 23, wherein in a case where a predetermined operation is accepted, the display control unit causes the first picked-up image to be superimposed on the second picked-up image and live-view displayed.

25. The image pickup device according to claim 24, wherein the predetermined operation is a panning operation, a tilt operation, a pinch-out operation, a pinch-in operation, or a flick operation.

26. An image pickup device having a plurality of lenses with angles of view different from one another and capable of image pickup in parallel in a first image-pickup mode and a second image-pickup mode, comprising at least one memory and at least one processor which function as: an accepting unit configured to accept a switching operation of switching a lens to be used for image pickup of a picked-up image which is picked up in the first image-pickup mode and displayed on a first image area, or a lens to be used for image pickup of a picked-up image which is picked up in the second image-pickup mode and displayed on a second image area; and a control unit configured to control such that the lens to be used for the image pickup is switched in response to an acceptance of the switching operation of the lens to be used for the image pickup of the picked-up image which is displayed on the first image area or the image pickup of the picked-up image which is displayed on the second image area, wherein the control unit controls such that lenses to be used in the first image-pickup mode and the second image-pickup mode are switched such that different lenses are used in the first image-pickup mode and the second image-pickup mode; the accepting unit includes a third item which is superimposed and displayed on a picked-up image in the first image-pickup mode and switches a lens used in each of the first image-pickup mode and the second image-pickup mode, respectively; and the control unit is configured to: switch a lens used in the first image-pickup mode to a selected lens in a case where an operation to the third item is an operation by a single-touch at one spot; and switch the lens used in the second image-pickup mode to the selected lens in a case where an operation to the third item is an operation by a multi-touch at two spots or more.

27. A control method of an image pickup device having a plurality of lenses with angles of view different from one another, comprising the steps of: accepting a switching operation of switching a lens to be used for image pickup of a picked-up image which is picked up in the first image-pickup mode and displayed on a first image area, or a lens to be used for image pickup of a picked-up image which is picked up in the second image-pickup mode and displayed on a second image area, when an image is picked up in a first image-pickup mode and a second image-pickup mode in parallel; and controlling such that the lens to be used for the image pickup is switched in response to an acceptance of the switching operation of the lens to be used for the image pickup of the picked-up image which is displayed on the first image area or the image pickup of the picked-up image which is displayed on the second image area, wherein in the controlling step, control is executed such that lenses to be used in the first image-pickup mode and the second image-pickup mode are switched such that different lenses are used in the first image-pickup mode and the second image-pickup mode, and in the accepting step, a first item which switches a lens used in the first image-pickup mode is superimposed and displayed on a picked-up image displayed on the first image area, and a second item which switches a lens used in the second image-pickup mode is superimposed and displayed on a picked-up image displayed on the second image area.
