

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250252725
Kind Code	A1
Publication Date	August 07, 2025
Inventor(s)	Simpson; Ryan J.

SYSTEM AND METHOD FOR IMAGE COMPRESSION

Abstract

This application relates to a method and a system for compressing a captured image of an item such as a mailpiece or parcel. The system may include a memory configured to store images of a plurality of items captured while the items are being transported and a processor in data communication with the memory. The processor may be configured to receive or retrieve one or more of the captured images, perform a wavelet scattering transform on the one or more captured images, perform deep learning on the wavelet scattering transformed images to classify the wavelet scattering transformed images and compress the classified wavelet scattering transformed images. Various embodiments can significantly improve a compression efficiency, a communication efficiency of compressed data and save a memory space so that the functionality of computing devices is significantly improved.

Inventors:	Simpson; Ryan J. (Vienna, VA)
Applicant:	United States Postal Service (Washington, DC)
Family ID:	77463081
Appl. No.:	19/087255
Filed:	March 21, 2025

Related U.S. Application Data

parent US continuation 18534459 20231208 parent-grant-document US 12260631 child US 19087255
parent US continuation 17186479 20210226 parent-grant-document US 11842531 child US 18534459
us-provisional-application US 62983382 20200228

Publication Classification

Int. Cl.: G06V10/82 (20220101); **G06N3/08** (20230101); **G06N3/084** (20230101); **G06T9/00** (20060101); **G06V30/19** (20220101); **G06V30/413** (20220101)

U.S. Cl.:

CPC G06V10/82 (20220101); **G06N3/08** (20130101); **G06N3/084** (20130101); **G06T9/002** (20130101); **G06V30/19173** (20220101); **G06V30/413** (20220101);

Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS [0001] Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57. This application is a continuation of U.S. application Ser. No. 18/534,459, filed on Dec. 8, 2023, which is a continuation of U.S. application Ser. No. 17/186,479, filed on Feb. 26, 2021, now issued as U.S. Pat. No. 11,842,531, which in turn claims priority to and the benefit of Provisional Application No. 62/983,382 filed on Feb. 28, 2020 in the U.S. Patent and Trademark Office, the entire contents of which are incorporated herein by reference.

BACKGROUND

Technical Field

[0002] The described technology generally relates to image processing, and in particular to systems and methods for compressing images.

Description of the Related Technology

[0003] Handling items through processing systems and distribution networks typically includes capturing one or more images of the item as it is being processed and moves through a distribution network. For example, items, such as articles of mail (e.g., letters, flats, parcels, and the like), warehouse inventories, containers, or packages are sorted. Sorting items or articles can be done using imaging technologies to image destinations on the items.

SUMMARY

[0004] The embodiments disclosed herein each have several aspects no single one of which is solely responsible for the disclosure's desirable attributes. Without limiting the scope of this disclosure, its more prominent features will now be briefly discussed. After considering this discussion, and particularly after reading the section entitled “Detailed Description,” one will understand how the features of the embodiments described herein provide advantages over existing systems, devices, and methods for image compression through deep learning and wavelet scattering transform.

[0005] One aspect is a system for compressing a captured image of an item, the system comprising: a reader configured to capture an image of an item having a label thereon, the captured image including at least a portion of the label; a memory configured to store the captured image of the item; and a processor in data communication with the memory and configured to: receive or retrieve the captured image; perform a wavelet scattering transform the captured image; perform deep learning on the wavelet scattering transformed images to classify the wavelet scattering transformed image; and compress the classified wavelet scattering transformed image.

[0006] In the above system, in performing the wavelet scattering transform, the processor is configured to: perform one or more of wavelet transforms or a series of wavelet transforms on the captured image; perform a nonlinearity operation on the wavelet transformed image; and perform an averaging operation on the wavelet transformed images to produce a mean value of the wavelet transformed image on which the nonlinearity operation has been performed.

[0007] The above system further comprises: a model database (DB) configured to store one or more previously trained models relating to the captured image; a training data DB configured to store a plurality of sets of training data used to train one or more of the pre-trained models; and a test data DB configured to store a plurality of sets of test data used to test an identified and trained model, wherein the processor is configured to communicate data with the model DB, the training data DB and the test data DB to perform the deep learning.

[0008] In the above system, the processor is configured to: identify a relevant model, among the plurality of pre-trained models stored in the model DB, based on the wavelet scattering transformed image; train the identified model based on training data sets stored in the training data DB and associated with the wavelet scattering transformed image; test the trained model using one or more test data sets stored in the test data DB until a performance of the trained model satisfies a predetermined criteria; and classify the wavelet scattering transformed image using the trained model that satisfies the predetermined criteria.

[0009] In the above system, the captured image comprises a grayscale image. In the above system, the grayscale image comprises an image of the entirety of the item. In the above system, the grayscale image comprises an image of the label, the label comprising one or more data elements, and wherein the label is provided on an exterior surface of the item. In the above system, one of the one or more data elements comprises a return address region, a mailing address region, a barcode, a postage region, or a specialty item region. In the above system, the captured image comprises a summed grayscale image where grayscale values of the grayscale image have been summed or a mean grayscale image where grayscale values of the summed grayscale image have been averaged.

[0010] In the above system, the processor is configured to perform a wavelet scattering transform on the summed grayscale image and the mean grayscale image. In the above system, in compressing the wavelet scattering transformed image, the processor is further configured to: quantize values representing the wavelet scattering transformed image; compare the quantized values to a threshold, and discard values falling outside the threshold; and encode the remaining non-discarded quantized values to remove redundant information. In the above system, in encoding the remaining non-discarded quantized values, the processor is configured to use one of the following: entropy encoding, run-length encoding or Huffman coding.

[0011] In the above system, the processor is configured to receive the captured image from the reader. In the above system, the processor is configured to retrieve the captured image from the memory. In the above system, the captured images comprise binary data, and wherein the processor is configured to perform a wavelet scattering transform on the binary data. In the above system, the classified wavelet scattering transformed images comprise a plurality of features distinguishable from each other, and wherein the processor is configured to compress at least part of the features of the classified wavelet scattering transformed image.

[0012] Another aspect is a method of compressing a captured image of an item, comprising: capturing, at an optical sensor, a plurality of items that are being transported; receiving or retrieving, at a processor, one or more of the captured images; performing, at the processor, a wavelet scattering transform on the one or more captured images; performing, at the processor, deep learning on the wavelet scattering transformed images to classify the wavelet scattering transformed images; and compressing, at the processor, the classified wavelet scattering transformed images.

[0013] In the above method, performing the wavelet scattering transform comprises: performing, at the processor, one or more of wavelet transforms or a series of wavelet transforms on the one or more captured images; performing, at the processor, a nonlinearity operation on the wavelet transformed images; and performing, at the processor, an averaging operation on the wavelet transformed images to produce a mean value of the wavelet transformed images on which the nonlinearity operation has been performed. The above method further comprises: storing, at a model database (DB), one or more previously trained models relating to the one or more captured

images; storing, at a training data DB, a plurality of sets of training data used to train one or more of the pre-trained models; and storing, at a test data DB, a plurality of sets of test data used to test an identified and trained model, wherein performing the deep learning comprises communicating data between the processor and the model DB, the training data DB and the test data DB.

[0014] In the above method, performing the deep learning comprises: identifying, at the processor, a relevant model, among the plurality of pre-trained models stored in the model DB, based on the wavelet scattering transformed images; training, at the processor, the identified model based on training data sets stored in the training data DB and associated with the wavelet scattering transformed images; testing, at the processor, the trained model using one or more test data sets stored in the test data DB until a performance of the trained model satisfies a predetermined criteria; and classifying, at the processor, the wavelet scattering transformed images using the trained model that satisfies the predetermined criteria.

[0015] In the above method, the one or more captured images comprise a grayscale image. In the above method, the grayscale image comprises an image of the entirety of the item. In the above method, the grayscale image comprises an image of one or more of elements provided on an exterior surface of the item. In the above method, the elements comprise a return address region, a mailing address region, a barcode, a postage region and a specialty item region. In the above method, the captured images comprise a summed grayscale image where grayscale values of the grayscale image have been summed or a mean grayscale image where grayscale values of the summed grayscale image have been averaged.

[0016] In the above method, the compressing comprises: quantizing values representing the wavelet scattering transformed images; comparing the quantized values to a threshold, and discarding values falling outside the threshold; and encoding the remaining non-discarded quantized values to remove redundant information. In the above method, the encoding is performed using one of the following: entropy encoding, run-length encoding or Huffman coding. In the above method, the compressing comprises compressing wavelet coefficients of the wavelet scattering transformed images. In the above method, the classified wavelet scattering transformed images comprise a plurality of features distinguishable from each other, and wherein the compressing is performed on at least part of the features of the classified wavelet scattering transformed images.

[0017] Another aspect is a system for decompressing compressed data of an item, the system comprising: a memory configured to store compressed data of captured images of a plurality of items; and a processor in data communication with the memory and configured to: receive or retrieve the compressed data; decode and de-quantize the compressed data to generate a first version of compressed images; identify classified wavelet scattered images from the first version of decompressed images; perform deep learning on the identified wavelet scattered images to declassify the classified wavelet scattered images; perform an inverse wavelet scattering transform on the declassified wavelet scattered images on which the deep learning has been performed; and generate a second version of decompressed images from the inverse wavelet scattering transformed images.

[0018] In the above system, in performing the inverse wavelet scattering transform, the processor is configured to: perform a de-averaging operation on the declassified wavelet scattered images on which the deep learning has been performed to generate de-averaged wavelet scattered images; perform a linearity operation on the de-averaged wavelet scattered images; and perform one or more of inverse wavelet transforms or a series of inverse wavelet transforms on the de-averaged wavelet scattered images on which the linearity operation has been performed.

[0019] Another aspect is a method of decompressing compressed data of an item, the method comprising: receiving or retrieving, at a processor, compressed data of a plurality of images of items captured while the items are being transported; decoding and de-quantizing, at the processor, the compressed data to generate a first version of compressed images; identifying, at the processor,

classified wavelet scattered images from the first version of decompressed images; performing, at the processor, deep learning on the identified wavelet scattered images to declassify the classified wavelet scattered images; performing, at the processor, an inverse wavelet scattering transform on the declassified wavelet scattered images on which the deep learning has been performed; and generating, at the processor, a second version of decompressed images from the inverse wavelet scattering transformed images.

[0020] In the above method, performing the inverse wavelet scattering transform comprises: performing, at the processor, a de-averaging operation on the declassified wavelet scattered images on which the deep learning has been performed to generate de-averaged wavelet scattered images; performing, at the processor, a linearity operation on the de-averaged wavelet scattered images; and performing, at the processor, one or more of inverse wavelet transforms or a series of inverse wavelet transforms on the de-averaged wavelet scattered images on which the linearity operation has been performed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The foregoing and other features of the disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several embodiments in accordance with the disclosure and are not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through use of the accompanying drawings.

[0022] FIG. 1 illustrates an example of sorting/sequencing equipment that may be used in an item processing facility.

[0023] FIG. 2 illustrates an example image of an item that may be processed by the item processing equipment shown in FIG. 1.

[0024] FIG. 3 illustrates an example image of another item that may be processed by the item processing facility of FIG. 1.

[0025] FIG. 4 illustrates an example image compression system according to some embodiments.

[0026] FIG. 5 illustrates another image compression system according to some embodiments.

[0027] FIG. 6A illustrates an example grayscale image of a barcode according to some embodiments.

[0028] FIG. 6B illustrates an example summed grayscale image of the barcode according to some embodiments.

[0029] FIG. 6C illustrates an example mean grayscale image of the barcode according to some embodiments.

[0030] FIG. 7 is an example process of a method for compressing captured images according to some embodiments.

[0031] FIG. 8 is an example process of the wavelet scattering transform shown in FIG. 7 according to some embodiments.

[0032] FIG. 9 is a conceptual diagram showing a wavelet transform operation according to some embodiments.

[0033] FIG. 10 is an example process of a method for performing the deep learning operation of FIG. 7.

[0034] FIG. 11 is a node diagram illustrating an example neural network for performing the deep learning operation of FIG. 10.

[0035] FIG. 12 is a block diagram of a system for compressing a captured image of an item and decompressing the compressed data according to some embodiments.

[0036] FIG. 13 is an example process of a method for decompressing compressed data according to

some embodiments.

[0037] FIG. 14 is an example process of the inverse wavelet scattering transform shown in FIG. 13 according to some embodiments.

[0038] FIG. 15 is a block diagram of an example first or second controller illustrated in FIG. 12 according to some embodiments.

DETAILED DESCRIPTION

[0039] Provided herein are various embodiments of systems and methods for image processing including, for example, a system and method for compressing a captured image using deep learning and wavelet scattering transform on the capture image. various embodiments can significantly improve a compression efficiency, for example, where a smaller size of wavelet coefficients of the wavelet scattering transformed images are compressed, a communication efficiency of compressed data and save a memory space so that the functionality of computing devices is significantly improved.

[0040] In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. Thus, in some embodiments, part numbers may be used for similar components in multiple figures, or part numbers may vary depending from figure to figure. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the Figures, can be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and made part of this disclosure.

[0041] Reference in the specification to “one embodiment,” “an embodiment,” or “in some embodiments” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. Moreover, the appearance of these or similar phrases throughout the specification do not necessarily all refer to the same embodiment, nor are separate or alternative embodiments necessarily mutually exclusive. Various features are described herein which may be exhibited by some embodiments and not by others. Similarly, various requirements are described which may be requirements for some embodiments but may not be requirements for other embodiments.

[0042] As used here, the term “item” or “items” may refer to flats, letters, parcels, residual mail, and the like. Although the present disclosure describes systems and devices for image processing related to articles of mail, such as letters and flats, it will be apparent to one of skill in the art that the disclosure presented herein is not limited thereto. For example, the described technology may have application in a variety of manufacturing, assembly, distribution, or sorting applications which include processing images including personal or sensitive information at high rates of speed and volume.

[0043] As used here, the term “compress” or “compression” generally refers to generating a data file that takes a smaller quantity of memory than an original, uncompressed data file. Compressing image files retains at least a portion of the visual information of the original image data. As such, with an appropriate viewing application, a user may open a compressed file to view the image data. The resource may include one or more of: memory, network bandwidth, network packets, memory blocks, processor cycles, time to write to memory (e.g., disk), time to read from memory, or the like. Compression may include generating a compressed file from an uncompressed file by reducing the number of bits needed to represent the same information. In some embodiments, compression may include losing some clarity from the original image, such as image resolution or color range, to achieve the resource savings. Such compressions may be referred to as lossy compression. Compression with no clarity loss may be referred to as lossless compression. As used here, the term “decompress” or “decompression” generally refers to reversing the compression

process to reconstruct a file to present the original file information. As discussed, the reconstruction may not be an identical reconstruction of the original file as some compression schemes are lossy. [0044] Items are sorted and the information (e.g., intended destinations, senders, addresses, types of items, barcode, etc.) about them are obtained and used in processing the items. A processing facility can use automated processing equipment to sort items. An item processing facility may receive a very high volume of items, such as letters, flats, parcels, or other objects which must be sorted and/or sequenced for delivery. Sorting and/or sequencing may be accomplished using item processing equipment which can scan, read, image, or otherwise capture, read, and/or interpret an origination point, a sender, an item type, a destination end point and other information from the items being processed. In some embodiments, the intended destination end point may be encoded in a computer readable code, such as a bar code printed on or affixed to an exterior surface of the item. In some embodiments, the destination end point may be read by taking an image of the item and performing an optical character recognition (OCR) process on the image, and determining the delivery end point from the OCR'd address.

[0045] FIG. 1 illustrates an example of item processing equipment **100** that may be used in item processing facilities. Although one type of item processing equipment is depicted in FIG. 1, the current disclosure is not limited thereto. The systems and methods described here can be applicable to the illustrated type and other types of item processing equipment without departing from the scope of the current disclosure. The item processing equipment **100** includes an intake system **110**. The intake system **110** may be a counter, conveyor, or other receiving structure where a stack of items **115**, such as letters, are brought to be fed into the item processing equipment **100**. The intake system **110** may provide a surface or surfaces on which to place the stack of items **115** to stage the items for processing. The item processing equipment **100** has a scanning portion **120** that includes a scanner (e.g., **420** in FIG. 4 or **540/550** in FIG. 5) which scans or reads a computer readable code or performs OCR of an image of part or all of an item **115** in order to identify various characteristics of the item(s) **115**, such as class of service, addressee, and/or delivery end point. The item processing equipment **100** includes a processor (not shown) configured to control the operation of the sorter/sequence **100**, including controlling the movement of items through the item processing equipment **100** via conveyor belts, pinch belts, and/or motors, controlling the scanning portion **120** to facilitate the intake, sorting, and sequencing the items **115**. The processor is in communication with a memory (not shown) where information from the scanner is stored for further use. The memory can be part of the item processing equipment **100**, or may be remote to the item processing equipment **100**. The memory may be on a network with which the processor can communicate, and the memory may be shared by different components within a processing facility. The memory is configured to store the identity of each article processed, including information scanned, read, or interpreted from the letter, such as delivery end point, sender, class of service, postage, serial number, and the like. The memory is also configured to store the sequence of items in the item stream as they are scanned.

[0046] The item processing equipment **100** further includes a sorting portion **130**. The sorting portion **130** may be a large storage and conveyor cabinet as shown, which has inside various components (not shown), for directing items **115** along particular pathways as the items **115** are sorted. The sorting portion **130** may be located adjacent to or otherwise near the intake system **110**. In some embodiments, the items **115** may be moved or transported from the intake system **110** to the sorting portion **130** by an automated system including series of pinch belts, vacuum belts, or other conveying mechanisms. As the items are moved or transported from the intake system **110** to the sorting portion **130**, the items are read or scanned, and destinations identified for each individual item **115**. The processor then operates a system of motors, conveyors, and pinch belts to direct the item to the output portion **140**.

[0047] The output portion **140** may be a structural system having a plurality of stackers, receptacles, pockets, output areas, or bins **45** arrayed, in some embodiments, in vertically disposed

rows. Each bin **45** is configured to receive one or more items **115** from the sorting portion **130**.

Each bin **45** can be assigned to a particular delivery route or to one or more stop groups.

[0048] FIG. **2** illustrates an example image of an item that may be processed by the item processing equipment **100** shown in FIG. **1**. The image **200** may include a background region **210** and image data showing an item **220**. It will be appreciated that in some embodiments, the image **200** may show only a portion of the item **220**, such as a portion of one side of a parcel or a letter. The image **200** may include corners **202a-202d**. The item **220** may include a return address region (or sender region) **208**, a mailing address region (or recipient region) **206**, a barcode **204**, or postage region **230**.

[0049] FIG. **3** illustrates another example image of another item that may be processed by the item processing equipment **100** shown in FIG. **1**. The item **310** shown in FIG. **3** is an example of a pre-printed U.S. POSTAL SERVICE® PRIORITY MAIL® envelope. The image **300** may include a background region **305** upon which the item **310** is imaged. The background region **305** may show processing equipment upon which the item **310** is placed.

[0050] The image **300** may depict identifying marks such as graphics **340a**, **340b**, or **340c**. The graphics **340a-340c** may appear at predetermined locations on the envelope and thus can be used as features for identifying the item **310** or orientation thereof. The image **300** may depict construction artifacts for the envelope such as a first seam **330** or a second seam **335**. The location or orientation of the seams **330** and **335** within the image, within the portion of the image showing the envelope, relative to each other, or relative to another feature identified in the image data **300** may be used to identify the envelope or orientation thereof.

[0051] The image **300** may show a printed label **320**. The printed label **320** may include sorting, processing, and routing information (e.g., recipient mailing address, sender address, class of service, tracking number, postage payment, etc.) in a region of interest. In such instances, the location of the printed label **320** may be identified based on the identified features. In some embodiments, the printed label **320** may serve as a feature. The fields and lines of the printed label **320** can be used alternatively or in addition to other indicia. For example, the pattern of boxes and lines on the labels may be standardized, so those lines can be used to identify where the regions of interest are, and for orientation purposes. Consider a label having a specific pattern of horizontal lines from top to bottom in the label. If that pattern is detected in the image as vertical lines, or if the pattern is inverse, then the image may be identified as oriented sideways or upside down from a desired orientation.

[0052] Some embodiments provide an improved data compression system and method by compressing a scanned or captured image of an item using wavelet scattering transform and deep learning, machine learning, and/or the like. In this way, it is possible to significantly improve a compression efficiency, a communication efficiency of compressed data and save a memory space. The image processing and compression systems and methods of the present disclosure can have applicability in a variety of applications other than item processing. For example, the systems and methods described herein can be used in video applications, such as video compression, video streaming, and the like.

[0053] FIG. **4** illustrates an example image compression system **40** according to some embodiments. The image compression system **40** may be part of the item processing equipment **100** of FIG. **1** or can be separately provided, for example, to be disposed adjacent thereto. The image compression system **40** may include an item processing equipment **410**, an optical scanner or a reader **420**, a model DB **475**, a training data DB **485**, a test data DB **495**, a first controller **480** and a memory **490**. The image compression system **40** shown in FIG. **4** is merely an example image compression system, and certain elements may be modified or removed, and/or other elements or equipment may be added. Although only one optical scanner is shown in FIG. **4**, two or more optical scanners can be provided depending on the embodiment.

[0054] The item processing equipment **410** may include a conveyor belt or other component (not

shown) that moves items from one location to another. The item processing equipment **410** may automatically process a group **460** of items by conveying each of them past the optical scanner **420** capturing an image of an item **440** that is being conveyed. The optical scanner **420** may capture an entirety or a portion of one side of the item **440** facing the scanner **420**. The optical scanner **420** may capture information relevant to processing and/or delivery of the item **440**, such as names and addresses of senders and recipients, postages and barcodes, etc. In some embodiments, the barcodes may include an intelligent mail® package barcode (IMpb).

[0055] The captured image may include, for example, at least part of the images **200** and **300** shown in FIGS. 2 and 3. The optical scanner **420** may continuously and separately capture images of items being transported in front of the scanner **420**. In some embodiments, the captured images or digital data thereof may be stored in the memory **490**. In other embodiments, the captured images or digital data thereof may be stored in a memory of the scanner **420** or a memory of the first controller **480**. In other embodiments, the captured images or digital data thereof may be stored in a network memory such as a cloud or other device separately located from the elements **420**, **475**, **480**, **485**, **490** and **495**. The captured images or digital data thereof may also be transmitted to a decompression/receiving side **1220** (see FIG. 12) via a communication network (wired or wireless). In some embodiments, the digital data may be an image that was converted to binary data where for example, “0” represents a white pixel and “1” represents a black pixel, or vice versa.

[0056] The optical scanner **420** may be connected to the first controller **480** either by wire or wirelessly. In some embodiments, the optical scanner **420** may transmit a captured image of the item **440** and/or a label thereon, or at least one element on the item or on the label (hereinafter to be interchangeably used with “data element”). In the current disclosure, information, codes, words, etc. can be on a label, or can be on the item itself. The terms label and data element can be used to describe the information on an item or associated with an item even if a typical label is not present on the item. The label may include one or more data elements. The data elements may include, but are not limited to, an address section, a sender section and a recipient section, a barcode section, a postage section, and a special item section, etc.

[0057] The first controller **480** may communicate data with the model DB **475**, the training data DB **485**, the test data DB **495** and the memory **490**. The first controller **480** may receive or retrieve one or more of the captured images, perform a wavelet scattering transform on the captured images, perform deep learning on the wavelet scattering transformed images to classify the captured images and compress the classified wavelet scattered images (hereinafter to be interchangeably used with “wavelet scattering transformed images”).

[0058] The model DB **475** may store one or more previously trained deep learning AI, or machine learning models (or pre-trained models) relating to captured or retrieved images of items or data elements, similar images thereto, or images of similar items. In some embodiments, the pre-trained models may be used to identify features from captured images of items, such as labels and/or data elements within the captured image. For example, the pre-trained models may be programmed to identify types of items such as letters, flats, parcels, or other types of items based on features of the captured images. In some embodiments, one or more of the stored models may perform at least one of the following: identifying a relative location of a label or a data element within an image, identifying an item, identifying an element of the item within the image of the item, recognition of image patterns of an item, item shapes, empty spaces, or colors, etc.

[0059] The pre-trained models may also be used to identify types of data elements of the items. For example, the pre-trained models may be programmed to identify types of data elements such as barcodes, address sections, postage sections, or special mail sections (such as priority mail or express mail sections), etc. In some embodiments, the pre-trained models may determine shapes and/or relative positions of the labels and/or the data elements. The pre-trained models may also use image processing algorithms such as classification, edge detection, pattern recognition and/or

image segmentation. Edge detection can be used to find the presence and location of edges constituted by sharp changes in color and/or intensity of an image. For example, in the images **200** and **300** shown in FIG. **2** and FIG. **3**, edges between white images and non-white images or edges between different data elements can be determined. The captured or retrieved images may be color images or grayscale (black and white) images.

[0060] The pre-trained models stored in the model DB **475** may be used to process wavelet scattered images of the captured or retrieved images to identify or classify features of the captured or retrieved images (to be described in more detail). For example, the identified/classified features may include edges of captured image portions, such as edges between barcodes and blank or empty areas, or edges between numbers or shapes and blank areas. The identified/classified features may also be associated with a size, a contrast, a brightness, a grayscale value or a shape of an item, a label, or a data element, etc.

[0061] The training data DB **485** may store a plurality of sets of training data used to train one or more of the pre-trained models. The training data may include previously captured or retrieved images of items or data elements that are generally different from those images used to create the pre-trained models.

[0062] The test data DB **495** may store a plurality of sets of test data used to test an identified and trained model. The test data set may include previously captured or retrieved images of items or data elements that are generally different from those images used to train the identified models and those used to create the pre-trained models.

[0063] FIG. **5** illustrates an example image compression system **50** according to some embodiments. The image compression system **50** may include a conveyor **510**, an upper optical scanner **540** and a front optical scanner **550**. For the purpose of convenience, the first controller **480** in data communication with the scanners **540** and **550**, the memory **490** and the DBs **475**, **485** and **495** are not shown in FIG. **5**. The conveyor **510** may transport items **520** and **530** via a conveyor belt **515**. For the purpose of convenience, only two items **520** and **530** are shown in FIG. **5**, however, the scanners **540** and **550** may continuously scan many more items (not shown) that are being transported on the conveyor belt **515**. The upper scanner **540** may be spaced apart and positioned above the conveyor **510** and the items **520** and **530** so as to scan top surfaces of the items **520** and **530** such as the top surface **522** of the item **520**. The front optical scanner **550** may be positioned in front of the conveyor **510** and the items **520** and **530** so as to scan front surfaces of the items **520** and **530** such as the front surface **524** of the item **520** being transported on the conveyor belt **515**. In some embodiments, the system **50** can include only one camera or scanner, for example, only the upper optical scanner **540** or only the front optical scanner **550**. In some embodiments, the optical scanner can be in another location, as desired.

[0064] FIG. **6A** illustrates an example grayscale image **62** of a barcode according to some embodiments. FIG. **6B** shows an example of a summed grayscale image **64**. FIG. **6C** shows an example of the mean grayscale image **66**. The grayscale images are exemplary only. The images of computer readable codes, such as barcodes, described herein in can be in color or in black and white without departing from the scope of the current disclosure. The captured grayscale image **62** of FIG. **6A** may be processed by the first controller **480** or by another component of the system **40** to generate the summed grayscale image **64** shown in FIG. **6B**. The first controller **480** or another component of the system **40** can generate, from the summed grayscale image **64**, the mean (averaged) grayscale image **66** shown in FIG. **6C**. The first controller **480** or the scanner **420** may generate the summed grayscale image **64** and the mean grayscale image **66** based on the captured grayscale image **62**. The first controller **480** or the scanner **420** may store the generated summed grayscale image **64** and mean grayscale image **66** in the memory **490**. In some embodiments, the grayscale image **64** may be formed by summing grayscale values of the grayscale image **62**. In some embodiments, the summed grayscale image **64** can be formed by selecting a row of pixels, or a representative set of pixels across or extending the length of the grayscale image **64**. The intensity

values of the grayscale image **64** can be graphed or plotted to obtain the summed grayscale image **64**. The summed grayscale image **64** can have peaks or maxima where the intensity of the grayscale image **64** is highest, for example, where the pixels are white (for example corresponding to a white bar or a space between bars) and can have troughs or minima where the pixels are darkest (for example, corresponding to a black bar). In some embodiments, the pixels in a column of the image can be averaged or can be summed, and the resulting averages or sums can be plotted or graphed or determined to generate the summed grayscale image **64**.

[0065] The mean grayscale image **66** can be generated by taking the mean or average values of the pixels in a row or column in the grayscale image **62**, or in the summed grayscale image **64**. In some embodiments, the mean grayscale image **66** can be generated by determining the mean distance of a brightness value or intensity value of a pixel from a baseline point, from a value of an adjacent pixel, and the like.

[0066] FIG. **7** is an example process **70** of a method for compressing captured images of items or data elements according to some embodiments. Although the process **70** is described herein with reference to a particular order, in various embodiments, states herein may be performed in a different order, or omitted, and additional states may be added. This may apply to the processes **1000** and **1300** shown in FIGS. **10** and **13**. The process **70** may be implemented by a computing device such as the first controller **480**. For the purpose of the convenience, the description will be made based on the first controller **480** performing the process **70**.

[0067] In state **710**, the first controller **480** may receive, from one or more of the optical scanners **420**, **540** and **550** or retrieve from the memory **490**, a captured image of an item. The captured image of the item may include portions of the item (e.g., corners, sides, top or bottom surfaces, etc.) and/or one or more data elements provided on a surface of the item (e.g., sender section, recipient section, barcode section, postage section, special item section, etc.) described above.

[0068] In some embodiments, the captured image may include a grayscale image such as the grayscale barcode image **62** shown in FIG. **6A**. In some embodiments, the captured image may be converted into the summed grayscale image **64** shown in FIG. **6B** and/or the mean grayscale image **66** shown in FIG. **6C**. In these embodiments, the first controller **480** may retrieve the summed grayscale image **64** and the mean grayscale image **66** from the memory **490**. In other embodiments, the grayscale image **62** may be converted into digital data such as binary data. In these embodiments, the first controller **480** may convert the captured grayscale image **62** into the binary data, and then store the binary data in the memory **490**. In other embodiments, the captured image may include a color image (e.g., RGB color images). The RGB color images may be converted into other color format such as YIQ or YUV images. For the purpose of convenience, the description will be provided mainly for grayscale images.

[0069] In state **720**, the first controller **480** may perform a wavelet scattering transform on the received or retrieved image. In some embodiments, as described below, in performing the wavelet scattering transform on the captured image, the first controller **480** may identify features of the captured image distinguishable from each other. The wavelet scattering transform may be used to map input image or data into some alternative representation which discards irrelevant information while retaining discriminative properties of each class. Furthermore, the wavelet scattering transform may construct low-variance representations of images which are insensitive to translations and small deformations. Because translations and small deformations in the image may not affect a class membership, coefficients of a wavelet scattering transform may provide features to build robust classification models. For example, by extracting or identifying features from an input image, the wavelet scattering transform may allow for the images in the same class to be moved closer to each other in the scattering transform representation, while images belonging to different classes may be moved farther apart.

[0070] Wavelet image transforms as described herein can be processed in machine learning or deep learning networks to identify edges, identify regions of interest, read barcodes, etc. from the

transformed images. The images described above are transformed through wavelet processing of the summed grayscale image **64** and/or the mean grayscale image **66**. The plots of wavelet scattered images can be passed through the image processing networks described herein to identify features, read computer readable codes, etc.

[0071] In some embodiments, the input signals of images can be received and multiplied by 255 and then multiplied by 3 to get a three dimensional color image prior to passing the images to the learning networks described herein. In some embodiments, the input signals can be converted to binary, grayscale images, etc., as described herein.

[0072] In some embodiments, the wavelet compression mechanism can be JPEG2000 or similar compression format. The JPEG2000 output, based on the input described herein can result in wavelength data which is input into the deep learning or artificial intelligence network for recognition or classification.

[0073] In some embodiments, classification of images, reading barcodes, etc. as described herein can be performed on the compressed wavelet scatter by inputting the wavelet scatter for the image into the deep learning network as described herein. This can be advantageous because classification of images can be done on the compressed image data. This can reduce computation time and processing power compressing and decompressing images. The images do not need to be decompressed, pre-processed, and the like prior to classification of the images or reading portions of the images in the deep learning network. The deep learning network can use the run length encoding of the wavelet compression to generate a string, sequence, plot, or array of distances of different pixel values and the changes in pixel values in order to learn how to classify, or to classify or identify patterns, codes, etc., within the source images.

[0074] In some embodiments, wavelet scattered images may show certain features of an item in a distribution network, or features of a label or a data element. The features may include edges between two different elements or pixels (e.g., black and white pixels), differences in contrast, brightness, grayscale, or pixel density, etc. In some embodiments, the wavelet scattering transform may be performed by cascading an input image through a series of wavelet transforms, nonlinearities, and averaging shown in FIG. **8**. The operation of the wavelet scattering transform **720** will be described in more detail with reference to FIG. **8**.

[0075] FIG. **8** is an example process **720** of the wavelet scattering transform shown in FIG. **7** according to some embodiments. The first controller **480** may produce low-variance representations or features of an input image by performing a wavelet transform **722**, nonlinearity **724**, and averaging **726**. FIG. **8** is merely an example process of the wavelet scattering transform, and certain states elements may be removed, other states added, two or more states combined or one state can be separated into multiple states depending on the specification and requirements. The process **720** for the wavelet scattering transform may be implemented by a computing device such as the first controller **480**. For the purpose of the convenience, the description will be made based on the first controller **480** performing the wavelet scattering transform process **720**.

[0076] Referring to FIG. **8**, in state **722**, the first controller **480** may perform one or more of wavelet transforms or a series of wavelet transforms on the received or retrieved images of items or data elements. A wavelet transform segments an input image into smaller images, for example, as shown in FIG. **9**. The first controller **480** may repeatedly use wavelet filters such as high pass filters and low pass filters on segmented images. When the first controller **480** performs a wavelet transform on the input image, the controller **480** may generate as many wavelet coefficients as there are pixels in the image (i.e., this is pre-compression transform). The wavelet transform operation **722** of FIG. **8** will be described in more detail with reference to FIG. **9**.

[0077] FIG. **9** is a conceptual diagram showing a wavelet transform operation according to some embodiments. Wavelet transforms may linearize small deformations such as dilations by separating the variations across different scales to produce data representations that minimize differences within a class while preserving discriminability across classes. Referring to FIG. **9**, a captured

image **760** may be wavelet transformed (**722**) to generate a plurality of sets of a smaller wavelet transformed image **780**. The transformed image **780** can be converted back into the original image **760** by performing an inverse wavelet transform operation **770**, for example, as part of a decompression procedure (to be described in more detail with respect to FIGS. **13** and **14**). FIG. **9** shows a three-level wavelet transform where the wavelet transformed image **780** includes ten smaller images **780a-780j**. Each of the images **780a-780j** can be generated by using one or more filters (e.g., low pass filter and/or high pass filter). More or less wavelet images may be generated depending on the decomposition level.

[0078] Referring back to FIG. **8**, in state **724**, the first controller **480** may perform a nonlinearity operation on the wavelet transformed image. In some embodiments, the first controller **480** may perform a nonlinearity operation **724** based on lookup tables and approximate mathematical functions by mapping input values to output values. In state **726**, the first controller **480** may perform an averaging operation to produce a mean value of the image on which the nonlinearity operation has been performed.

[0079] Referring back to FIG. **7**, in state **730**, the first controller **480** may perform deep learning on the wavelet scattering transformed image. The deep learning algorithm may classify the wavelet scattering transformed image based on the features identified by the wavelet scattering transform. In some embodiments, the first controller **480** may classify the wavelet scattering transformed image into two or more of wavelet scattering transformed images based on the distinguishable features identified in state **720**. The deep learning operation **730** will be described in more detail by referring to FIGS. **10** and **11**.

[0080] FIG. **10** is an example process **1000** of the deep learning operation **730** shown in FIG. **7** according to some embodiments. FIG. **10** is merely an example process of the deep learning operation **730**, and certain states or elements may be removed, other states added, two or more states combined or one state can be separated into multiple states depending on the specification and requirements. For example, the states **1040-1080** may be omitted, and the identified relevant model may be used to classify the wavelet scattered image. In some embodiments, the same model may be used for images of different types of items (e.g., letters, parcels, flats, etc.). In other embodiments, different models may be used for images of different types of items.

[0081] FIG. **11** is a node diagram **80** illustrating an example deep learning neural network **810** that performs the deep learning operation of FIGS. **7** and **10**. The process **1000** may be implemented by a computing device such as the first controller **480**. The node diagram **80** may be implemented by a computing device such as the first controller **480**. For the purpose of the convenience, the description will be made based on the first controller **480** performing the process **1000** of FIG. **10** and the node diagram **80** of FIG. **11**.

[0082] Referring back to FIG. **10**, in state **1010**, the first controller **480** may receive the wavelet scattered image or data. As described above, the wavelet scattering transform may be performed on an analog image such as a grayscale image or digital data such as binary data. The first controller **480** may receive the wavelet scattered image when the wavelet scattering transform is performed on an analog image. The first controller **480** may receive the wavelet scattering transformed data when the wavelet scattering transform is performed on digital data. For the purpose of the convenience, the description will be made based on the wavelet scattering transformed image.

[0083] In state **1020**, the first controller **480** may access the model DB **475** shown in FIG. **4**. As described above, the model DB **475** may store a plurality of pre-trained models that can classify the wavelet scattered images of items or data elements generated by the wavelet scattering transform.

[0084] In state **1030**, the first controller **480** may identify a relevant model (i.e. . . . , a pre-trained model), among the plurality of pre-trained models stored in the model DB **475**, based on the received wavelet scattered image. In some embodiments, the first controller **480** may extract one or more features from the wavelet scattered image in order to identify the relevant model. Extracting the features may include identifying a specific shape of the images of items or data elements. In

these embodiments, the identification may be based at least in part on the extracted features.

[0085] In some embodiments, in performing the state **1030**, the first controller **480** may perform an image analysis such as feature detection. Feature detection may include processing an image to identify specific characteristics shown (e.g., features). For example, referring to FIG. **2**, the corners **202a-202d** of the image **200** may be detected based on a detected contrast between the image data showing the item **220** and the background region **210**. In some embodiments, this may be referred to as edge detection. Once the corners or other features are detected, the distance between the detected features may be calculated. Using the ratio of differences between distances, for example, the short side of a letter may be distinguished from the long side of the letter. This can then be used to orient the image, such as where the long side is shown perpendicular to the bottom of the image **200**. Angles formed between detected features may be used in addition or as an alternative identification means. For example, an angle between a corner (e.g., the corner **202a**) and a corner of the image **200** may be compared. This can provide an indication of whether the image data showing the item **220** is rotated and, if so, by how much. Feature detection may also identify regions of content within the image **200** such as the return address region (or sender region) **208**, the mailing address region (or recipient region) **206**, the barcode **204**, or postage region **230**. The location of these regions relative to each other, the corners, or within the image **200** itself may be used to identify characteristics of the item shown in the image **200**. The extracted information may be compared to the information associated with pre-trained models included in the model DB **475**. The comparison may include determining whether a value associated with the wavelet scattered image corresponds with a value for a pre-trained model. As used herein, the term “correspond” encompasses a range of relative relationships between two or more elements. Correspond may refer to equality (e.g., complete match). Correspond may also refer to partial-equality (e.g., partial match, fuzzy match, soundex). Correspond may further refer to a value which falls within a range of values.

[0086] In some embodiments, instead of identifying the relevant model from the model DB **475**, the first controller **480** may generate a new model using the identified relevant model. For the purpose of the convenience, the description will be made based on the identified model instead of a new model.

[0087] In some embodiments, the first controller **480** may use a classification model in performing one or more of the states **1030-1060** of FIG. **10**. Generally, a classification model is a supervised learning approach in which a computer program learns from data input given to it and then uses this learning to classify new observation. This data set may simply be bi-class (like identifying whether an email is spam or non-spam) or it may be multi-class too. Some examples of classification problems may include speech recognition, handwriting recognition, biometric identification, document classification, etc. Types of classification algorithms may include, but are not limited to, linear classifiers, logistic regression, Naive Bayes classifier, nearest neighbor, support vector machines, decision trees, boosted trees, random forest and neural networks. For example, a classification model may be trained using distances between a region and the corners of the item. The distances may be calculated from the center of the region to the respective corner. The distances may be collected as a vector of values and provided to the classification model. Using the vector, the classification model may provide a classification for the region (e.g., return address, mailing address, postage, barcode, unknown). The classification model may also provide a confidence indicating a confidence that the resulting classification is the “correct” classification. The analysis may also include character recognition. The character recognition may identify specific characters shown in the image **200** such as the ZIP code, street address, type of mailer used for the item (e.g., pre-paid envelope or box), or similar identifying marks that can be identified in the image **200** shown in FIG. **2**.

[0088] Referring back to FIG. **10**, in state **1040**, the first controller **480** may train the identified model. Training the identified model may be based on training data that is stored in the training

data DB **485** and is associated with the wavelet scattered image. In some embodiments, in training the identified model, parameters (e.g., wavelet coefficients) of the model can be modified until the model produces (or “converges” on) the correct or desired output. For instance, a correct output of an image recognition model may include generating an output that identifies the subject included in the image. This allows the model to evolve by adjusting weight values to affect the output for one or more hidden nodes (see **820-850** shown in FIG. **11**). The changing of the weight values may be performed through a variety of methods such as random weight updates or backward propagation sometimes referred to as “back propagation.” Back propagation includes comparing the expected model output with the obtained model output and then traversing the model to determine the difference between the expected node output that produces the expected model output and the actual node output. An amount of change for one or more of the weight values may be identified using this difference such that the model output more closely matches the expected output. The training operation **1040** will be described in more detail with reference to FIG. **11**.

[0089] Referring to FIG. **11**, in some embodiments, the first controller **480** may use the node diagram **80** for a deep learning neural network model **810** shown in FIG. **11** in training the identified model. Referring to FIG. **11**, the neural network model **810** includes a plurality of hidden nodes: two nodes **11** (**822**) and **12** (**824**) at an input layer **820**, three nodes **H11** (**832**), **H12** (**834**) and **H13** (**836**) at a first middle layer **830**, three nodes **Hn1** (**842**), **Hn2** (**844**) and **Hn3** (**846**) at an nth middle layer **840**, and two nodes **852** (**O1**) and **854** (**O2**) at an output layer **850**. The neural network model **810** may be trained on input data such as a first input **860** and a second input **862** and provide output data such as a first output **870** and a second output **872**. In some embodiments, one or more of the inputs **860** and **862** may be a wavelet scattered image, and one or more of the outputs **870** and **872** may be a classified wavelet scattered image including one or more features of items or data elements identified such that the identified features are distinguishable from other portions of the image. In some embodiments, certain features may be grouped together to be distinguished from other groups of features.

[0090] Although FIG. **11** shows only two inputs and two outputs, depending on the embodiment, more than or less than two inputs can be used, and/or more than or less than two outputs can be used. In some embodiments, each layer may process over, for example, 100, 1,000, 10,000, 100,000, 1,000,000 or greater parameter values. Furthermore, the model **810** shown in FIG. **11** includes n middle layers. However, depending on the embodiment, only one middle layer or more than two layers (e.g., 4, 5, 7, 12, 30 or more layers) can be used. To further emphasize the complexity of the models, the number of nodes at each layer is shown as being two or three in FIG. **11**, but can be increased to factors of ten or one hundred in some embodiments. The lines connecting each node are each associated with a weight.

[0091] Referring back to FIG. **10**, in state **1050**, the first controller **480** may determine whether the training process is complete. The determination may be based on the accuracy of the outputs generated by the identified model for a set of inputs. The accuracy of the outputs may be compared to an accuracy threshold or other target accuracy metric. In some embodiments, the completion may be based on resources spent training such as processor time, processor cycles, memory utilization, or other detectable characteristic of the system.

[0092] If it is determined in state **1050** that the training process is not complete, the states **1040** and **1050** may repeat, for example, until the training process is complete. If it is determined in state **1050** that the training process is complete, the first controller **480** may test the trained model (state **1060**). In some embodiments, the testing may be performed using one or more test data sets stored in the test data DB **495**. The test data sets may be different from the training data sets stored in the training data DB **485**.

[0093] In state **1070**, the first controller **480** may determine whether the performance of the tested model is good or sufficient. The determination of the performance may be based on the accuracy of the outputs generated by the identified model for a set of inputs as described above. If it is

determined in state **1070** that the performance is not good or not sufficient, the states **1030-1070** may repeat, for example, until the performance is good or sufficient. If it is determined in state **1070** that the performance is good or sufficient, the first controller **480** may use the tested model to classify the wavelet scattered image (state **1080**).

[0094] Referring back to FIG. 7, in state **740**, the first controller **480** may compress the wavelet scattered images classified by the deep learning. As described above, the classified wavelet scattered image may include a plurality of features distinctively grouped from each other. In some embodiments, the compression may be performed selectively on certain groups of features of the wavelet scattered image which include more interesting or relevant information than the other features depending on the embodiment.

[0095] When the wavelet scattered image has not been binarized (i.e. analog image), the compression may include, for example, quantization, thresholding and encoding to generate compressed digital data. In performing the quantization and thresholding operations, the first controller **480** may quantize values representing the transformed images, and compare the quantized values to thresholds, and discard values falling outside the threshold. If the wavelet scattered data (binary data) is used, quantization and thresholding are not required, and the digital wavelet scattered data may be merely encoded. In performing the encoding operation, the first controller **480** may encode the remaining quantized values to remove redundant information, creating a compressed image file. In some embodiments, the first controller **480** may compress wavelet coefficients. The operation of compressing the wavelet coefficients may be relatively efficient, as the information is statistically concentrated in just a few coefficients. Thereafter, the first controller **480** may quantize the compressed coefficients. The compressed coefficients may be entropy encoded and/or run length encoded, for example, using Huffman coding. In state **750**, the first controller **480** may store in the memory **490** or database **1230** (see FIG. 12), output or transmit the compressed data.

[0096] FIG. 12 is a block diagram of a system **1200** for compressing images and decompressing the compressed data according to some embodiments. FIG. 12 is merely an example block diagram of the system **1200**, and certain elements may be removed, other elements added, two or more elements combined or one element can be separated into multiple elements depending on the specification and requirements.

[0097] The system **1200** may include the first controller **480**, the scanner **420**, a database **1230**, a second controller **1240** and a display **1250**. The first controller **480** and the scanner **420** may be located in a compression/transmission side **1210**. The second controller **1240** and the display **1250** may be located in a decompression/receiving side **1220**. In some embodiments, the database **1230** may be located between the compression/transmission side **1210** and the decompression/receiving side **1220**. In these embodiments, the database **1230** may belong to neither of the sides **1210** and **1220**. In other embodiments, the database **1230** may belong to either of the compression/transmission side **1210** and the decompression/receiving side **1220**.

[0098] In some embodiments, the compressed data may be stored locally in the compression/transmission side **1210** or stored in the database **1230**. In other embodiments, the compressed data may be transmitted to the decompression/receiving side **1220** either directly or through one or more of intermediate elements (not shown) between the compression/transmission side **1210** and the decompression/receiving side **1220**.

[0099] The compression/transmission side **1210** may store the compressed data (and encrypted data, if necessary) in the database **1230** and/or transmit the compressed/encrypted data to the decompression/receiving side **1220**. The second controller **1240** may then generate the raw image by converting the compressed/encrypted sequences included in the compressed image file to the original pixel information included in the raw image. The raw image may then be provided for further processing such as dynamic configuration of processing equipment based on the item shown in the image, tracking an item as it is routed to a final destination, or the like. The

reconstructed image can be displayed on the display **1250**. The reconstructed image can also be stored in the database **1230**. The reconstructed image can also be stored in a memory of the second controller **1240**, a separate memory (not shown) in data communication with the second controller **1240**, or a network memory such as a cloud (not shown).

[0100] FIG. **13** is an example process **1300** of a method for decompressing compressed captured data. The process **1300** is generally an inverse procedure of the compression process **70** shown in FIG. **7**. The process **1300** may be implemented by a computing device such as the second controller **1240** shown in FIG. **12**. For the purpose of the convenience, the description will be made based on the second controller **1240** performing the process **1300**.

[0101] In state **1310**, the second controller **1240** may receive or retrieve compressed data. The second controller **1240** may receive the compressed data from the compression/transmission side **1210** shown in FIG. **12**, or retrieve the compressed data from the database **1230** shown in FIG. **12** or other memory (not shown). The compressed data may include a classified wavelet scattered image including classified or distinguishable features of groups of the captured image described with respect to FIGS. **7-11**.

[0102] In state **1320**, the second controller **1240** may decode and de-quantize the compressed data to generate a first version of a decompressed image containing the classified wavelet scattered image. The first version of the decompressed image may be different from a second version of the decompressed image (or the original decompressed image) described with respect to state **1360** in that the former includes a classified wavelet scattered image whereas the classification has been removed in the latter. In state **1330**, the second controller **1240** may identify the classified wavelet image included in the first version of the decompressed image.

[0103] In state **1340**, the second controller **1240** may perform a deep learning operation to declassify the classified wavelet scattered image. The second controller **1240** may use the same deep learning algorithm described with respect to FIGS. **10** and **11**, except that the deep learning network **810** is trained to output the original wavelet scattered image where the classification has been removed.

[0104] In state **1350**, the second controller **1240** may perform an inverse wavelet scattering transform to generate the second version of the decompressed image. The second controller **1240** may use the same wavelet scattering transform of FIG. **8** in a reversed way, as shown in FIG. **14**, including a de-averaging operation **766**, a linearity operation **768** and an inverse wavelet transform operation **770**. The inverse wavelet scattering transform operation **1350** will be described in more detail with reference to FIG. **14**.

[0105] Referring to FIG. **14**, the second controller **1240** may perform the de-averaging operation **766** which is an inverse or opposite operation of the averaging operation **726** of FIG. **8**. For example, the second controller **1240** may perform a de-averaging operation on the declassified wavelet scattered image on which the deep learning operation has been performed to generate de-averaged wavelet scattered images (i.e., wavelet scattered image before the averaging operation (see **726** of FIG. **8**) has been performed).

[0106] The second controller **1240** may perform the linearity operation **768** which is an inverse or opposite operation of the nonlinearity operation **724** of FIG. **8**. For example, the second controller **1240** may perform a linearity operation on the de-averaged wavelet scattered images. The second controller **1240** may perform the inverse wavelet transform operation **770**, which is an opposite operation of the wavelet transform operation **722** of FIG. **8**. For example, the second controller **1240** may perform one or more of inverse wavelet transforms or a series of inverse wavelet transforms on the output of the linearity block **768**.

[0107] Referring back to FIG. **13**, in state **1360**, the second controller **1240** may store or output the second version of the decompressed image (i.e., the original decompressed image), for example, as shown in FIG. **9** (see the original image **760**). For example, the second controller **1240** may store the decompressed image in one or more of the database **1230** shown in FIG. **12**, a memory thereof

(not shown), a separate memory or a network memory as described above. The second controller **1240** may also display the decompressed (original) image on the display **1250** shown in FIG. **12**. Although not shown in FIG. **13**, before storing or outputting the original decompressed image, the second controller **1240** may perform an image post-processing operation such as sharpening, smoothing, and/or brightening to enhance the image quality. The second controller **1240** may use various filters to perform the image post-processing operation.

[0108] In some embodiments, the images of items, or the files or data structures indicative of compressed files can have supplemental information stored therein, such as digital watermark or other similar data, metadata, etc., can be included with the compressed images. The watermark can be an indication of the classification of the image which can be generated and stored in the image by the deep learning network or other computer component, and which can be stored with the data indicative of the compressed image. The identity of an image can be determined subsequent to the initial analysis by reading the watermark without needing to run the deep learning process again.

[0109] In some embodiments, images or items which are imaged can include personally identifiable information (PII). In order to protect images with PII or to track or provide accountability for images, the watermark can be an identifier corresponding to an operator, a piece of equipment, etc., which processed the image, looked at the image, or interacted with the image or the compressed file in any way. The watermark, for example, can store a face ID, a badge, or other image information, or a string of alphanumeric characters, that are embedded into or appended to the image and/or compressed image data. The watermark can be encrypted such that it can only be decrypted using the correct decryption keys and algorithms.

[0110] The watermark would not be visible to the human eye if the image were decompressed and displayed, but by running the correct algorithm on the image, the embedded image, the watermark, etc. could be revealed. For example, the watermark can be a pattern of minute variations in colors, pixel values, etc., which are known, but which would not be identifiable to a human viewing the image. The pattern can be recognized using the correct algorithm, and the patterns can correspond to users, operators, machines, etc. If an image is found in a location where it should be, or someplace that it should not be, e.g., on a public computer system, the watermark can be used to identify an operator or machine which processed the image. This can be used to track the source of the image and ensure accountability for the PII in the image.

[0111] FIG. **15** is a block diagram of an embodiment of a computing device **900** for compressing images or decompressing compressed data according to some embodiments. FIG. **15** is merely an example block diagram of the computing device **900**, and certain elements may be removed, other elements added, two or more elements combined or one element can be separated into multiple elements depending on the specification and requirements.

[0112] The computing device **900** can be a server or other computing device, and can include a processing unit or processor **902**, an image feature processor **930**, a network interface **904**, a computer readable medium drive **906**, an input/output device interface **908**, and a memory **910**. The computing device **900** may implement the features of one or more of the optical scanners **420/540/550**, the first controller **480**, or the second controller **1240**.

[0113] The network interface **904** can provide connectivity to one or more networks or computing systems. The network interface **904** can receive information and instructions from other computing systems or services via the network interface **904**. The network interface **904** can also store data directly to memory **910**. The processing unit **902** can communicate to and from memory **910** and output information to an optional display **918** via the input/output device interface **908**. The input/output device interface **908** can also accept input from the optional input device **920**, such as a keyboard, mouse, digital pen, microphone, mass storage device, etc.

[0114] The memory **910** may contain computer program instructions that the processing unit **902** executes in order to implement one or more embodiments. The memory **910** generally includes RAM, ROM, and/or other persistent, non-transitory computer readable media. The memory **910**

can store an operating system **912** that provides computer program instructions for use by the processing unit **902** or other elements included in the computing device in the general administration and operation of the computing device **900**. The memory **910** can further include computer program instructions and other information for implementing aspects of the present disclosure.

[0115] For example, in one embodiment, the memory **910** includes an image feature configuration **914**. The image feature configuration **914** may include one or more desired orientations for displaying different types of items, regular expressions for sets of characters including the routing information (e.g., ZIP code), area(s) of pre-printed packaging material that may include address information or other routing information, or other information supporting the image based routing of items described herein. The image feature configuration **914** may store specific values for a given configuration. The image feature configuration **914** may, in some embodiments, store information for obtaining values for a given configuration. For example, an address information extraction service implementing the regular expressions for identifying the address information or identify destination location information extracted from an image may be specified as a network location (e.g., URL) in conjunction with username and password information to access the service. In such embodiments, a message including the extracted text (or portion thereof) may be provided to the service. A response message may include the extracted address or destination location information, if available.

[0116] The memory **910** may also include or communicate with one or more auxiliary data stores, such as data store **922**. The data store **922** may electronically store data regarding mail pieces, image files, or finalization results therefore.

[0117] The elements included in the computing device **900** may be coupled by a bus **990**. The bus **990** may be a data bus, communication bus, or other bus mechanism to enable the various components of the computing device **900** to exchange information.

[0118] In some embodiments, the computing device **900** may include additional or fewer components than are shown in FIG. 15. For example, a computing device **900** may include more than one processing unit **902** and computer readable medium drive **906**. In another example, the computing device **900** may not be coupled to a display **918** or an input device **920**. In some embodiments, two or more computing devices **900** may together form a computer system for executing features of the present disclosure.

[0119] In some embodiments, a non-transitory computer readable medium having stored thereon instructions which when executed by at least one computing device performs all or a portion of the methods described.

[0120] Depending on the embodiment, certain acts, events, or functions of any of the processes or algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (e.g., not all described operations or events are necessary for the practice of the algorithm). Moreover, in certain embodiments, operations or events can be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially.

[0121] The various illustrative logical blocks, modules, routines, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, or as a combination of electronic hardware and executable software. To clearly illustrate this interchangeability, various illustrative components, blocks, modules, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as specialized hardware, or as specific software instructions executable by one or more hardware devices, depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

[0122] Moreover, the various illustrative logical blocks and modules described in connection with the embodiments disclosed herein can be implemented or performed by a machine, such as a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. An image processing system can be or include a microprocessor, but in the alternative, the image processing system can be or include a controller, microcontroller, or state machine, combinations of the same, or the like configured to generate and analyze indicator feedback. An image processing system can include electrical circuitry configured to process computer-executable instructions. Although described herein primarily with respect to digital technology, an image processing system may also include primarily analog components. For example, some or all of the image file analysis and rotation notation features described herein may be implemented in analog circuitry or mixed analog and digital circuitry. A computing environment can include a specialized computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

[0123] The elements of a method, process, routine, or algorithm described in connection with the embodiments disclosed herein can be embodied directly in specifically tailored hardware, in a specialized software module executed by an image processing system, or in a combination of the two. A software module can reside in random access memory (RAM) memory, flash memory, read only memory (ROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), registers, hard disk, a removable disk, a compact disc read-only memory (CD-ROM), or other form of a non-transitory computer-readable storage medium. An exemplary storage medium can be coupled to the image processing system such that the image processing system can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the image processing system. The image processing system and the storage medium can reside in an application specific integrated circuit (ASIC). The ASIC can reside in an access device or other monitoring device. In the alternative, the image processing system and the storage medium can reside as discrete components in an access device or other item processing device. In some embodiments, the method may be a computer-implemented method performed under the control of a computing device, such as an access device or other item processing device, executing specific computer-executable instructions.

[0124] Conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without other input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list.

[0125] Disjunctive language such as the phrase “at least one of X, Y, Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to present that an item, term, etc., may be either X, Y, or Z, or any combination thereof (e.g., X, Y, and/or Z). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each is present.

[0126] Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are intended to include one or more recited devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A working in conjunction with a second processor configured to carry out recitations B and C.

[0127] As used herein, the terms “determine” or “determining” encompass a wide variety of actions. For example, “determining” may include calculating, computing, processing, deriving, looking up (e.g., looking up in a table, a database or another data structure), ascertaining and the like. Also, “determining” may include receiving (e.g., receiving information), accessing (e.g., accessing data in a memory) and the like. Also, “determining” may include resolving, selecting, choosing, establishing, and the like.

[0128] As used herein, the term “selectively” or “selective” may encompass a wide variety of actions. For example, a “selective” process may include determining one option from multiple options. A “selective” process may include one or more of: dynamically determined inputs, preconfigured inputs, or user-initiated inputs for making the determination. In some embodiments, an n-input switch may be included to provide selective functionality where n is the number of inputs used to make the selection.

[0129] As used herein, the terms “provide” or “providing” encompass a wide variety of actions. For example, “providing” may include storing a value in a location for subsequent retrieval, transmitting a value directly to the recipient, transmitting or storing a reference to a value, and the like. “Providing” may also include encoding, decoding, encrypting, decrypting, validating, verifying, and the like.

[0130] As used herein, the term “message” encompasses a wide variety of formats for communicating (e.g., transmitting or receiving) information. A message may include a machine readable aggregation of information such as an XML document, fixed field message, comma separated message, or the like. A message may, in some embodiments, include a signal utilized to transmit one or more representations of the information. While recited in the singular, it will be understood that a message may be composed, transmitted, stored, received, etc. in multiple parts.

[0131] All references cited herein are incorporated herein by reference in their entirety. To the extent publications and patents or patent applications incorporated by reference contradict the disclosure contained in the specification, the specification is intended to supersede and/or take precedence over any such contradictory material.

[0132] The term “comprising” as used herein is synonymous with “including,” “containing,” or “characterized by,” and is inclusive or open-ended and does not exclude additional, unrecited elements or method steps.

[0133] The above description discloses several methods and materials of the present invention. This invention is susceptible to modifications in the methods and materials, as well as alterations in the fabrication methods and equipment. Such modifications will become apparent to those skilled in the art from a consideration of this disclosure or practice of the invention disclosed herein. Consequently, it is not intended that this invention be limited to the specific embodiments disclosed herein, but that it cover all modifications and alternatives coming within the true scope and spirit of the invention as embodied in the attached claims.

Claims

1. A system for compressing a captured image of an item, the system comprising: a reader configured to capture an image of an item having a label thereon; and one or more processors in data communication with the reader, the one or more processors configured to: receive the captured

image; transform the captured image into one or more transformed images using a transformation protocol; perform a nonlinearity operation on the one or more transformed images; perform an averaging operation on the one or more transformed images to produce a mean value of the one or more transformed images on which the nonlinearity operation has been performed; classify the one or more transformed captured images; and compress the one or more classified transformed captured images.

2. The system of claim 1, wherein the one or more processors are further configured to: identify features of the captured image distinguishable from each other; and classify the one or more transformed captured image into two or more transformed images based on the identified features.

3. The system of claim 1, wherein the captured image comprises an image of a label provided on an exterior surface of the item, the label comprising at least one of: a return address region; a mailing address region; a barcode; a postage region; or a specialty item region.

4. The system of claim 1, wherein the captured image comprises a grayscale image, and wherein the one or more processors are further configured to: sum grayscale values of the grayscale image to produce a summed grayscale image; and average grayscale values of the summed grayscale image to produce a mean grayscale image.

5. The system of claim 4, wherein the one or more processors are configured to transform the summed grayscale image and the mean grayscale image using the transformation protocol.

6. The system of claim 1, wherein the captured image comprises binary data, and wherein the one or more processors is configured transform the binary data using the transformation protocol.

7. The system of claim 1, wherein the classified transformed captured image comprises a plurality of features distinguishable from each other, and wherein the one or more processors are configured to compress at least part of the features of the classified transformed captured image.

8. A system for compressing a captured image of an item, the system comprising: a reader configured to capture an image of an item having a label thereon; a memory configured to store the captured image of the item; and one or more processors in data communication with the memory and the reader, the one or more processors configured to: receive the captured image; transform the captured image using a transformation protocol; classify the transformed captured image; and compress the classified transformed captured image, wherein to compress the classified transformed image, the one or more processors are configured to: quantize values representing the classified transformed captured image; compare the quantized values to a threshold, and discard values falling outside the threshold; and encode remaining non-discarded quantized values to remove redundant information.

9. The system of claim 8, wherein the one or more processors are further configured to: identify features of the captured image distinguishable from each other; and classify, using the machine learning model, the transformed captured image into two or more transformed images based on the identified features.

10. The system of claim 8, wherein the captured image comprises an image of a label provided on an exterior surface of the item, the label comprising at least one of: a return address region; a mailing address region; a barcode; a postage region; or a specialty item region.

11. The system of claim 8, wherein, in encoding the remaining non-discarded quantized values, the one or more processors are configured to perform at least one of: entropy encoding, run-length encoding, or Huffman coding.

12. The system of claim 8, wherein the captured image comprises binary data, and wherein the one or more processors is configured transform the binary data using the transformation protocol.

13. The system of claim 8, wherein the classified transformed captured image comprises a plurality of features distinguishable from each other, and wherein the one or more processors are configured to compress at least part of the features of the classified transformed captured image.

14. A method of image compression, the method comprising: transforming an image using a transformation protocol; classifying the transformed image; and compressing the classified

transformed captured image, wherein compressing the classified transformed captured image comprises: quantizing values representing the classified transformed captured image; comparing the quantized values to a threshold, and discard values falling outside the threshold; and encoding remaining non-discarded quantized values to remove redundant information.

15. The method of claim 14, further comprising: identifying features of the image which are distinguishable from each other; and classifying, the transformed captured image into two or more transformed images based on the identified features.

16. The method of claim 14, wherein the image is an image of a label on an exterior surface of a distribution item, the label comprising at least one of: a return address region; a mailing address region; a barcode; a postage region; or a specialty item region.

17. The method of claim 14, wherein the captured image comprises a grayscale image, and wherein the method further comprises: summing grayscale values of the grayscale image to produce a summed grayscale image; and averaging grayscale values of the summed grayscale image to produce a mean grayscale image.

18. The method of claim 17, further comprising transforming the summed grayscale image and the mean grayscale image using the transformation protocol.

19. The method of claim 14, wherein the captured image comprises binary data, and wherein the method further comprises transforming the binary data using the transformation protocol.

20. The method of claim 14, wherein the classified transformed captured image comprises a plurality of features distinguishable from each other, and wherein the method further comprises compressing at least part of the features of the classified transformed captured image.
