

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250253719

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Patel; Parin et al.

Wireless Power System with Communications

Abstract

A wireless power system may include an accessory configured to transfer or relay wireless power to a portable electronic device. The portable electronic device may include wireless charging circuitry and sensors configured to detect compatible accessories currently coupled with the portable electronic device. The portable electronic device performs wireless charging or related functions in accordance with the coupled accessories.

Inventors: Patel; Parin (Monte Sereno, CA), Kumar; Daniel P. (Fremont, CA), Chang; Andrew C. (Sunnyvale, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 77665654

Appl. No.: 19/186187

Filed: April 22, 2025

Related U.S. Application Data

parent US continuation 17487975 20210928 parent-grant-document US 12308671 child US 19186187

parent US continuation 17409378 20210823 parent-grant-document US 12308670 child US 17487975

parent US division 17028404 20200922 parent-grant-document US 11121590 child US 17409378
us-provisional-application US 63075035 20200904

Publication Classification

Int. Cl.: H02J50/90 (20160101); G06K7/10 (20060101); G06K19/07 (20060101); H01Q7/00 (20060101); H02J7/00 (20060101); H02J7/02 (20160101); H02J50/12 (20160101);

U.S. Cl.:

CPC **H02J50/90** (20160201); **G06K7/10297** (20130101); **G06K19/0723** (20130101); **H01Q7/00** (20130101); **H02J7/00045** (20200101); **H02J7/0047** (20130101); **H02J7/02** (20130101); **H02J50/12** (20160201); **H02J50/60** (20160201); **H02J50/80** (20160201); **H04B5/79** (20240101); **H04W12/06** (20130101)

Background/Summary

[0001] This application is a continuation of application Ser. No. 17/487,975, filed Sep. 28, 2021, which is a continuation of application Ser. No. 17/409,378, filed Aug. 23, 2021, which is a division of application Ser. No. 17/028,404, filed Sep. 22, 2020, now U.S. Pat. No. 11,121,590, which claims the benefit of provisional patent application No. 63/075,035, filed Sep. 4, 2020, which are hereby incorporated by reference herein in their entireties.

FIELD

[0002] This relates generally to power systems, and, more particularly, to wireless power systems for charging battery-powered electronic devices.

BACKGROUND

[0003] In a wireless charging system, a wireless power transmitting device such as a charging mat wirelessly transmits power to a wireless power receiving device such as a battery-powered, portable electronic device. The wireless power transmitting device has a coil that produces electromagnetic flux. The wireless power receiving device has a coil and rectifier circuitry that uses electromagnetic flux produced by the transmitter to generate direct-current power that can be used to power electrical loads in the battery-powered portable electronic device.

SUMMARY

[0004] A wireless charging system includes an electronic device operable with an accessory. In accordance with some embodiments, the electronic device can include a wireless charging coil, near-field communications circuitry having a near-field communications antenna around the wireless charging coil, a magnetic alignment structure configured to align the near-field communications antenna with a corresponding near-field communications antenna in the accessory when the magnetic alignment structure is magnetically coupled to the accessory, a magnetic sensor configured to detect when the magnetic alignment structure is magnetically coupled to the accessory, and an output device. The near-field communications circuitry can be configured to retrieve information from the accessory in response to detecting that the magnetic alignment structure is magnetically coupled to the accessory. The output device can be configured to present an output associated with the accessory using the retrieved information.

[0005] The near-field communications antenna can run along an inner or outer peripheral edge of the wireless charging coil. The magnetic alignment structures can run along an inner or outer peripheral edge of the near-field communications antenna. The output device can be a display configured to present a wireless charging mat icon, a wireless charging puck icon, a removable case icon, a battery case icon, a dock icon, a physical characteristic such as a color of the accessory, a functionality associated with the accessory, and ownership information associated with the accessory. The output device can also provide audio, haptic, or other visual feedback when the device attaches to the accessory. Near-field communications can be performed while wireless power handshake operations are paused or while wireless power transfer operations are halted.

[0006] In accordance with some embodiments, a method of operating an electronic device with an

accessory is provided. Such method can include using a magnet to magnetically attract a corresponding magnet in the accessory, using a magnetic sensor to detect when the magnet is magnetically attracting the corresponding magnet in the accessory, using near-field communications circuitry to receive information from the accessory in response to detecting that the magnet is magnetically attracting the corresponding magnet in the accessory, and using a display to display an output associated with the accessory based on the retrieved information. The method can further include using a wireless charging coil to receive wireless power signals from the accessory and charging a battery with the wireless power signals. The method can further include performing near-field communication authentication operations while wireless power handshake operations are temporarily paused or while active wireless power transfer is temporarily halted.

[0007] In accordance with some embodiments, an electronic device operable in a wireless power system to receive wireless power signals from a power transmitting device is provided. The electronic device can include a wireless power receiving coil configured to receive the wireless power signals, a near-field communications reader with a near-field communications antenna that runs along a peripheral edge of the wireless power receiving coil, a magnet at least partially surrounding the near-field communications antenna, where the magnet is configured to magnetically coupled to a corresponding magnet in the power transmitting device to align the wireless power receiving coil with a wireless power transmitting coil in the power transmitting device, and a magnetic sensor configured to detect when the magnet is magnetically coupled to an external accessory separate from the power transmitting device and when the magnet is magnetically coupled to both the external accessory and the power transmitting device. The magnetic sensor can differentiate between when the magnet is only magnetically coupled to the external accessory and when the magnet is magnetically coupled to both the external accessory and the power transmitting device. The power transmitting device can include a first near-field communications tag configured to transmit information about the power transmitting device to the near-field communications reader. The external accessory comprises a second near-field communications tag configured to transmit information about the external accessory to the near-field communications reader. The near-field communications reader can perform anti-collision operations when multiple tags are detected. When collisions are detected, the near-field communications reader may communicate with only one of the tags while the other tag is halted, before halting the tag that was just read and then reading the tag that was first halted.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a block diagram of an illustrative wireless power system in accordance with some embodiments.

[0009] FIG. 2 is a circuit schematic of illustrative wireless power transmitting and receiving circuitry in accordance with some embodiments.

[0010] FIG. 3 is a cross-sectional side view of an illustrative wireless charging system in accordance with some embodiments.

[0011] FIG. 4 is a cross-sectional side view of an illustrative wireless charging system in accordance with some embodiments.

[0012] FIG. 5 is a diagram of an accessory configured to mate with a portable electronic device in accordance with some embodiments.

[0013] FIG. 6 is a top view of a portable electronic device in accordance with some embodiments.

[0014] FIG. 7 is a flow chart of illustrative steps for using near-field communications circuitry to communicate between a portable electronic device and one or more accessories in accordance with

some embodiments.

[0015] FIG. **8** is a timing diagram illustrating how a magnetometer can be used to detect the presence of one or more accessories in accordance with an embodiment.

[0016] FIG. **9** is a flow chart for performing near-field communications in accordance with some embodiments.

[0017] FIG. **10** is a flow chart for performing near-field communications in accordance with some embodiments.

DETAILED DESCRIPTION

[0018] A wireless power system may include one or more electronic devices that transmit wireless power, one or more electronic devices that receive wireless power, and one or more electronic devices that both transmit and receive wireless power. The wireless power transmitting device may be a wireless charging mat or wireless charging puck, as examples. The wireless power receiving device may be a portable device such as a wristwatch, cellular telephone, tablet computer, laptop computer, or other electronic equipment, as examples. The wireless power transmitting and receiving device may be an electronic device case (e.g., a removable case for a cellular telephone) or other type of electronic device. The wireless power transmitting device may wirelessly transmit power to a wireless power receiving device. The wireless power receiving device uses power from the wireless power transmitting device for powering the device and for charging an internal battery.

[0019] Wireless power is transmitted from the wireless power transmitting device to the wireless power receiving device using one or more wireless power transmitting coils. The wireless power receiving device has one or more wireless power receiving coils coupled to rectifier circuitry that converts received wireless power signals into direct-current power.

[0020] An illustrative wireless power system (wireless charging system or wireless power transfer system) is shown in FIG. **1**. Devices in wireless power system **8** may include wireless power transmitting devices such as wireless power transmitting device **12**. Devices in wireless power system **8** may include wireless power receiving devices such as wireless power receiving device **24**. Devices in wireless power system **8** may include electronic devices capable of both transmitting and receiving wireless power such as wireless power transmitting and receiving device **18**.

[0021] Exemplary wireless power transmitting device **12** includes control circuitry **16**. Exemplary wireless power receiving device **24** includes control circuitry **30**. Exemplary wireless power transmitting and receiving device **18** includes control circuitry **78**. These control circuitries may include processing circuitry associated with microprocessors, power management units, baseband processors, digital signal processors, microcontrollers, and/or application-specific integrated circuits with processing circuits. These processing circuitry implements desired control and communications features in devices **12**, **18**, and **24**. For example, the processing circuitry may be used in selecting coils, determining power transmission levels, processing sensor data and other data to detect foreign objects and perform other tasks, processing user input, handling negotiations/handshakes between devices **12**, **18**, and **24**, sending and receiving in-band and out-of-band data, making measurements, and otherwise controlling the operation of respective wireless transmitters and receivers in system **8**.

[0022] Control circuitry in system **8** may be configured to perform operations in system **8** using hardware (e.g., dedicated hardware or circuitry), firmware and/or software. Software code for performing operations in system **8** is stored on non-transitory computer readable storage media (e.g., tangible computer readable storage media) in control circuitry **8**. The software code may sometimes be referred to as software, data, program instructions, instructions, or code. The non-transitory computer readable storage media may include non-volatile memory such as non-volatile random-access memory (NV RAM), one or more hard drives (e.g., magnetic drives or solid state drives), one or more removable flash drives or other removable media, or the like. Software stored on the non-transitory computer readable storage media may be executed on the processing circuitry of control circuitry **16**, **30**, and/or **78**. The processing circuitry may include application-specific

integrated circuits with processing circuitry, one or more microprocessors, a central processing unit (CPU) or other processing circuitry.

[0023] Power transmitting device **12** may be a stand-alone power adapter (e.g., a wireless charging mat or charging puck that includes power adapter circuitry), may be a wireless charging mat or puck that is coupled to a power adapter or other equipment by a cable, may be a portable device, may be equipment that has been incorporated into furniture, a vehicle, or other system, may be a removable battery case, or may be other wireless power transfer equipment. Illustrative configurations in which wireless power transmitting device **12** is a wireless charging mat or puck are sometimes described herein as an example.

[0024] Power receiving device **24** may be a portable electronic device such as a wristwatch, a cellular telephone, a laptop computer, a tablet computer, an accessory such as an earbud or an electronic pencil (e.g., a stylus), a head-mounted display, or other electronic equipment. Power transmitting device **12** may be coupled to a wall outlet (e.g., an alternating current power source), may have a battery **32** for supplying power, and/or may have another source of power. Power transmitting device **12** may have an alternating-current (AC) to direct-current (DC) power converter such as AC-DC power converter **14** for converting AC power from a wall outlet or other power source into DC power. DC power may be used to power control circuitry **16**. During operation, a controller in control circuitry **16** uses power transmitting circuitry **52** to transmit wireless power to power receiving circuitry **54** of device **24**.

[0025] Power transmitting circuitry **52** may have switching circuitry (e.g., inverter circuitry **61** formed from transistors) that is turned on and off based on control signals provided by control circuitry **16** to create A C current signals through one or more wireless power transmitting coils such as wireless power transmitting coil(s) **36**. These coil drive signals cause coil(s) **36** to transmit wireless power. Coils **36** may be arranged in a planar coil array or may be arranged to form a cluster of coils. In some embodiments, device **12** (e.g., a charging mat, puck, etc.) may have only a single coil. In other embodiments, a wireless charging device may have multiple coils.

[0026] As the AC currents pass through one or more coils **36**, alternating-current electromagnetic (e.g., magnetic) fields (wireless power signals **44**) are produced that are received by one or more corresponding receiver coils such as coil(s) **48** in power receiving device **24**. Rectifier circuitry such as rectifier circuitry **50** converts received A C signals (received alternating-current signals associated with electromagnetic signals **44**) from one or more coils **48** into DC voltage signals for powering device **24**. The DC voltage produced by rectifier circuitry **50** (sometime referred to as rectifier output voltage V_{rect}) can be used in charging a battery such as battery **58** and can be used in powering other components in device **24**.

[0027] Device **12**, device **18**, and/or device **24** may communicate wirelessly using in-band or out-of-band communications. Device **12** may, for example, have wireless transceiver circuitry **40** that wirelessly transmits out-of-band signals (e.g., to device **18** or device **24**) using an antenna. Wireless transceiver circuitry **40** may be used to wirelessly receive out-of-band signals from device **18** or **24** using the antenna. Device **24** may have wireless transceiver circuitry **46** that transmits out-of-band signals. Receiver circuitry in wireless transceiver **46** may use an antenna to receive out-of-band signals. Device **18** may have wireless transceiver circuitry **80** that transmits out-of-band signals. Receiver circuitry in wireless transceiver **80** may use an antenna to receive out-of-band signals.

[0028] In illustrative embodiments, device **12** includes near-field communications (NFC) circuitry **53** for transmitting information to corresponding NFC circuitry **55** in device **24**. Device **18** may also include NFC circuitry **85** for receiving information from device **12** and/or transmitting information to device **24**. Data conveyed using these NFC components may also be considered out-of-band signals and may be radiated using a separate NFC antenna within each device. Each NFC circuitry may include circuitry that operates as an NFC reader (sometimes referred to as a proximity coupling device or PCD) and/or as an NFC tag (sometimes referred to as a proximity inductive coupling card or PICC). An NFC tag may be active or passive. An active NFC tag can

actively transmit a signal to the NFC reader, whereas a passive NFC tag modulates the carrier waveform transmitted by the NFC reader. Exemplary NFC communications operate at 13.56 M Hz. In some embodiments, NFC communications may employ millimeter/centimeter wave technologies at 10 GHz or above (to about 300 GHz).

[0029] Wireless transceiver circuitry **40**, **46**, and **80** may also be used for in-band transmissions between devices **12**, **24**, and **18** using coils **36**, **48**, and **90**. Frequency-shift keying (FSK) and/or amplitude-shift keying (ASK) may be used to convey in-band data between devices **12**, **18**, and **24**. Power may be conveyed wirelessly during these FSK and ASK transmissions. It is desirable for power transmitting device **12**, power transmitting and receiving device **18**, and power receiving device **24** to be able to communicate information such as received power, battery states of charge, and so forth, to control wireless power transfer. Control circuitry **16** has external object measurement circuitry **41** that may be used to detect external objects on the charging surface of the housing of device **12** (e.g., on the top of a charging mat or, if desired, to detect objects adjacent to the coupling surface of a charging puck). The housing of device **12** may have polymer walls, walls of other dielectric, and/or other housing wall structures that enclose coil(s) **36** and other circuitry of device **12**. The charging surface may be formed by a planer outer surface of the upper housing wall of device **12** or may have other shapes (e.g., concave or convex shapes, etc.). In arrangements in which device **12** forms a charging puck, the charging puck may have a surface shape that mates with the shape of device **24**. A puck or other device **12** may, if desired, have magnets that removably attach device **12** to device **24**, so that coil **48** aligns with coil **36** during wireless charging).

[0030] Circuitry **41** can detect foreign objects such as coils, paper clips, and other metallic objects and can detect the presence of wireless power receiving devices **24** (e.g., circuitry **41** can detect the presence of one or more coils **48** and/or magnetic core material associated with coils **48**). During object detection and characterization operations, external object (foreign object) measurement circuitry **41** can be used to make measurements on coil(s) **36** such as Q-factor measurements, resonant frequency measurements, and/or inductance measurements that can indicate whether coil **48** is present and/or whether foreign objects such as coins or paperclips are present. Measurement circuitry can also be used to make sensor measurements using a capacitive sensor, can be used to make temperature measurements, and/or can otherwise be used in gathering information indicative of whether a foreign object or other external object (e.g., device **18** or **24**) is present on device **12**.

[0031] Power transmitting and receiving device **18** may be a battery case or a battery pack that is coupled to a power adapter or other equipment by a cable, may be equipment that has been incorporated into furniture, a vehicle, or other system, may be a removable battery case, may be a portable electronic device such as a wrist watch, a cellular telephone, a laptop computer, a tablet computer, an accessory such as an earbud, or other electronic equipment. Power transmitting and receiving device **18** is capable of both transmitting and receiving wireless power. Power transmitting and receiving device **18** therefore may include power transmitting components, similar to power transmitting device **12**. Power transmitting and receiving device **18** may also include power receiving components, similar to power receiving device **24**.

[0032] Power transmitting and receiving device **18** may have an alternating-current (AC) to direct-current (DC) power converter such as AC-DC power converter **96** for converting A C power from a wall outlet or other power source into DC power. DC power may be used to power control circuitry **78**. Control circuitry **78** includes wireless transceiver circuitry **80** for in-band communications (using coils **90**) and out-of-band communications (using an antenna). Control circuitry **78** may also optionally include measurement circuitry **82** (e.g., measurement circuitry of the type described in connection with measurement circuitry **41**).

[0033] Wireless power circuitry **84** in device **18** may include both an inverter **86** and a rectifier **88**. Inverter circuitry **86** (e.g., formed from transistors) may be turned on and off based on control signals provided by control circuitry **78** to create A C current signals through one or more coils

such as coil(s) **90**. These coil drive signals cause coil(s) **90** to transmit wireless power. Coils **90** may be arranged in a planar coil array or may be arranged to form a cluster of coils. In some arrangements, device **18** may have only a single coil. In other arrangements, device **18** may have multiple coils (e.g., two or more coils, 5-10 coils, at least 10 coils, 10-30 coils, fewer than 35 coils, fewer than 25 coils, or other suitable number of coils).

[0034] As the AC currents pass through one or more coils **90**, alternating-current electromagnetic (e.g., magnetic) fields (wireless power signals **44**) are produced that are received by one or more corresponding receiver coils such as coil(s) **48** in power receiving device **24**. In other words, one or more of coils **90** may be inductively coupled to one or more of coils **48**.

[0035] Power transmitting and receiving device **18** may also receive wireless power (e.g., from power transmitting device **12**). Coil(s) **90** may receive alternating-current electromagnetic fields from transmitting coils **36**, resulting in corresponding alternating-current currents in coil(s) **90**. Rectifier circuitry such as rectifier circuitry **88**, which contains rectifying components such as synchronous rectification metal-oxide-semiconductor transistors arranged in a bridge network, converts received AC signals (received alternating-current signals associated with electromagnetic signals **44**) from one or more coils **90** into DC voltage signals for powering device **18**. The DC voltage produced by rectifier circuitry **88** can be used in charging a battery such as battery **94** and can be used in powering other components in device **18**.

[0036] In some applications, power transmitting and receiving device **18** only transmits wireless power (e.g., using inverter **86** and coil(s) **90**). In some applications, power transmitting and receiving device **18** only receives wireless power (e.g., using rectifier **88** and coil(s) **90**). In some applications, power transmitting and receiving device **18** simultaneously receives and transmits wireless power. When simultaneously receiving and transmitting wireless power, device **18** may optionally perform both the power transmitting and power receiving operations associated with inverter **86** and rectifier **88** (e.g., device **18** uses the rectifier to charge the battery and operate the device and independently uses the inverter to transmit a desired amount of power). Alternatively, device **18** may relay or pass through received wireless power signals without rectifying the power. Device **18** may include only one coil that is used for both wireless power transmission and wireless power reception. Alternatively, device **18** may have at least one dedicated wireless power transmitting coil and at least one dedicated wireless power receiving coil. Device **18** may have multiple coils that are all used for both wireless power transmission and wireless power reception. Different coils in device **18** may optionally be shorted together in different modes of operation.

[0037] FIG. 2 is a circuit diagram of illustrative wireless charging circuitry useful in implementing system **8**. Wireless charging circuitry of a power transmitting device **12** and a power receiving device **24** is shown. However, it should be understood that device **18** may have the corresponding components for both power transmission and power reception and may be used in place of either device **12** and/or device **24** if desired. As shown in FIG. 2, circuitry **52** may include inverter circuitry such as one or more inverters **61** or other drive circuitry that produces wireless power signals that are transmitted through an output circuit that includes one or more coils **36** and capacitors such as capacitor **71**. In some embodiments, device **12** may include multiple individually controlled inverters **61**, each of which supplies drive signals to a respective coil **36**. In other embodiments, an inverter **61** is shared between multiple coils **36** using switching circuitry.

[0038] During operation, control signals for inverter(s) **61** are provided by control circuitry **16** at control input **74**. A single inverter **61** and single coil **36** is shown in the example of FIG. 2, but multiple inverters **61** and multiple coils **36** may be used, if desired. In a multiple coil configuration, switching circuitry (e.g., multiplexer circuitry) can be used to couple a single inverter **61** to multiple coils **36** and/or each coil **36** may be coupled to a respective inverter **61**. During wireless power transmission operations, transistors in one or more selected inverters **61** are driven by AC control signals from control circuitry **16**. The relative phase between the inverters can be adjusted dynamically. For example, a pair of inverters **61** may produce output signals in phase or out of

phase (e.g., 180 degrees out of phase).

[0039] The application of drive signals using inverter(s) **61** (e.g., transistors or other switches in circuitry **52**) causes the output circuits formed from selected coils **36** and capacitors **71** to produce alternating-current electromagnetic fields (signals **44**) that are received by wireless power receiving circuitry **54** using a wireless power receiving circuit formed from one or more coils **48** and one or more capacitors **72** in device **24**.

[0040] If desired, the relative phase between driven coils **36** (e.g., the phase of one of coils **36** that is being driven relative to another adjacent one of coils **36** that is being driven) may be adjusted by control circuitry **16** to help enhance wireless power transfer between device **12** and device **24**.

Rectifier circuitry **50** is coupled to one or more coils **48** (e.g., a pair of coils) and converts received power from A C to DC and supplies a corresponding direct current output voltage V_{rect} across rectifier output terminals **76** for powering load circuitry in device **24** (e.g., for charging battery **58**, for powering a display and/or other input-output devices **56**, and/or for powering other components). A single coil **48** or multiple coils **48** may be included in device **24**. In an illustrative configuration, device **24** may be a wristwatch or other portable device with at least two coils **48**. These two (or more) coils **48** may be used together when receiving wireless power. Other configurations may be used, if desired.

[0041] As previously mentioned, in-band transmissions using coils **36** and **48** may be used to convey (e.g., transmit and receive) information between devices **12** and **24**. With one illustrative configuration, frequency-shift keying (FSK) is used to transmit in-band data from device **12** to device **24** and amplitude-shift keying (ASK) is used to transmit in-band data from device **24** to device **12**. In other words, a device transmitting wireless power may use FSK to transmit in-band data to a device receiving wireless power (regardless of whether either device is a dedicated power transmitting/receiving device **12/24** or a power receiving and transmitting device **18**). A device receiving wireless power may use ASK to transmit in-band data to a device transmitting wireless power (regardless of whether either device is a dedicated power transmitting/receiving device **12/24** or a power receiving and transmitting device **18**).

[0042] Power may be conveyed wirelessly from device **12** to device **24** during these FSK and ASK transmissions. While power transmitting circuitry **52** is driving AC signals into one or more of coils **36** to produce signals **44** at the power transmission frequency, wireless transceiver circuitry **40** may use FSK modulation to modulate the power transmission frequency of the driving AC signals and thereby modulate the frequency of signals **44**. In device **24**, coil **48** is used to receive signals **44**. Power receiving circuitry **54** uses the received signals on coil **48** and rectifier **50** to produce DC power. At the same time, wireless transceiver circuitry **46** monitors the frequency of the AC signal passing through coil(s) **48** and uses FSK demodulation to extract the transmitted in-band data from signals **44**. This approach allows FSK data (e.g., FSK data packets) to be transmitted in-band from device **12** to device **24** with coils **36** and **48** while power is simultaneously being wirelessly conveyed from device **12** to device **24** using coils **36** and **48**.

[0043] In-band communications between device **24** and device **12** may use ASK modulation and demodulation techniques. Wireless transceiver circuitry **46** transmits in-band data to device **12** by using a switch (e.g., one or more transistors in transceiver **46** that are coupled coil **48**) to modulate the impedance of power receiving circuitry **54** (e.g., coil **48**). This, in turn, modulates the amplitude of signal **44** and the amplitude of the AC signal passing through coil(s) **36**. Wireless transceiver circuitry **40** monitors the amplitude of the A C signal passing through coil(s) **36** and, using ASK demodulation, extracts the transmitted in-band data from these signals that was transmitted by wireless transceiver circuitry **46**. The use of ASK communications allows ASK data bits (e.g., ASK data packets) to be transmitted in-band from device **24** to device **12** with coils **48** and **36** while power is simultaneously being wirelessly conveyed from device **12** to device **24** using coils **36** and **48**.

[0044] The example of FSK modulation being used to convey in-band data from power

transmitting device **12** to power receiving device **24** and ASK modulation being used to convey in-band data from power receiving device **24** to power transmitting device **12** is merely illustrative. In general, any desired communication techniques may be used to convey information from power transmitting device **12** to power receiving device **24** and from power receiving device **24** to power transmitting device **12**. In general, wireless power may simultaneously be conveyed between devices during in-band communications (using ASK or FSK).

[0045] The power transmission frequency used for transmission of wireless power may be, for example, a predetermined frequency of about 125 kHz, at least 80 kHz, at least 100 kHz, between 100 kHz and 205 kHz, less than 500 kHz, less than 300 kHz, or other suitable wireless power frequency. In some configurations, the power transmission frequency may be negotiated in communications between devices **12** and **24**. In other configurations, the power transmission frequency may be fixed.

[0046] It has been described that power may be simultaneously conveyed between devices while using in-band communication for data transmission between the devices. In other words, in some examples in-band communications may rely on modulation of the power transmission signal (e.g., modulating the power transmission frequency or modulating amplitude of a signal at the power transmission frequency). However, other communication techniques may be used that do not rely on modulation of the power transmission signals. For example, signals (sometimes referred to as in-band signals) may be conveyed between coils in the system at a frequency that is different than the power transmission frequency. Signals (at the same frequency or a different frequency than the power transmission frequency) that are conveyed using the coils (e.g., coils **36**, **48**, and **90** in FIG. **1**) may be considered in-band signals.

[0047] FIG. **3** is a cross-sectional side view of a portable electronic device **100** (e.g., a wrist watch, a cellular telephone, a laptop computer, a tablet computer, or other electronic equipment) on the surface of wireless charging mat (or puck) **102**. Device **100** may be a wireless power receiving device (e.g., device **24** in FIG. **1**) or may be a wireless power transmitting and receiving device (e.g., device **18** in FIG. **1**). Device **102** may be a wireless power transmitting device (e.g., device **12** in FIG. **1**).

[0048] As shown in FIG. **3**, device **102** may include a wireless charging coil **120** (e.g., a wireless power transmitting coil), an NFC antenna structure **122**, and magnetic alignment structure **124**. Wireless charging coil **120** may be wound from a single-strand conductor, a multiple strand conductor having multiple wires connected in parallel, braided wire, Litz wire, a conductive ink or conductive trace such as multilayer tracks on a printed circuit board, or other conductive elements suitable for forming coils. Coil **120** may represent a single coil or multiple coils (e.g., a planar coil array, a cluster of coils, or any suitable number of overlapping and/or non-overlapping coil structures). NFC antenna **122** may be formed around wireless charging coil **120** (e.g., NFC antenna **122** may be routed along the inner or outer periphery of coil **120** and may at least partially or completely surround coil **120**). In one suitable arrangement, wireless charging coil **120** and NFC antenna **122** may form concentric loop structures. Magnetic alignment structure **124** may be formed around NFC antenna **122** (e.g., alignment structure **124** may be formed along the periphery of antenna **122** and may at least partially or completely surround antenna **122**). In some configurations, NFC antenna **122** and magnetic alignment structure **124** may form concentric loops.

[0049] Device **100** may include a wireless charging coil **110** (e.g., a wireless power receiving coil), an NFC antenna structure **112**, magnetic alignment structure **114**, and a magnetic sensor such as a magnetometer **116**. Wireless power receiving coil **110** may be configured to received wireless power signals from wireless power transmitting coil **120**. For instance, wireless power transmitting coil **120** may be driven using inverter **61** in device **12** of FIG. **2**, whereas wireless power receiving coil **110** may be used to drive rectifier **50** in device **24** of FIG. **2**. Wireless charging coil **110** may be wound from a single-strand conductor, a multiple strand conductor having multiple wires

connected in parallel, braided wire, Litz wire, a conductive ink or conductive trace such as multilayer tracks on a printed circuit board, or other conductive elements suitable for forming coils. [0050] NFC antenna **112** may be formed around wireless charging coil **110** (e.g., NFC antenna **112** may be routed along the periphery of coil **110** and may at least partially or completely surround coil **110**). In one suitable arrangement, wireless charging coil **110** and NFC antenna **112** may form concentric loop structures. NFC antenna structure **112** in device **100** should have the same or similar structure and footprint as NFC antenna structure **122** of device **102** to ensure optimal coupling between the two antenna structures.

[0051] Magnetic alignment structure **114** may be formed around NFC antenna **112** (e.g., alignment structure **114** may be formed along the periphery of antenna **112** and may at least partially or completely surround antenna **112**). In some configurations, NFC antenna **112** and magnetic alignment structure **114** may form concentric loops. Magnetic alignment structure **114** in device **100** may magnetically couple with a corresponding magnetic alignment structure **124** in device **102** (e.g., magnets **114** may magnetically attract magnets **124** and vice versa). When magnetic alignment structure **114** in device **100** is coupled to magnetic alignment structure **124** in device **102**, the power transmitting coil **120** may be aligned with the power receiving coil **110** (e.g., so that coils **110** and **120** are in proper spatial alignment for optimal wireless power transfer). The magnetic alignment structures thus promote proper alignment of the wireless power receiving coil with respect to the wireless power transmitting coil. Magnetic alignment structures **114** and **124** may be permanent magnets (e.g., formed from hard magnetic materials that retain their magnetism over time).

[0052] In accordance with an embodiment, devices **100** and **102** may communicate prior to wireless power transfer operations. These communications include communications to establish wireless power delivery. In some embodiments, these communications include negotiations that support features such as issuing a charging notification, chime, alert, or otherwise conveying the nature of the device **102**, such that the user is informed as to the operation of their device. As an example, device **100** may receive information indicating that it has been placed on a wireless charging mat. In response, device **100** may present a wireless charging mat icon on its display to indicate that its battery is now charging from a wireless charging mat.

[0053] Communications may also include NFC-based communications. The NFC reader in device **100** may be triggered or activated using a magnetic sensor such as magnetometer **116**.

Magnetometer **116** is, for example, a Hall effect sensor, a rotating coil magnetometer, a magneto-resistive sensor, a fluxgate sensor, a microelectromechanical systems magnetic field sensor, or other types of magnetic sensors. In some embodiments, magnetometer **116** is multiple-axis magnetic sensor configured to decipher the polarity of attachment. When multi-axis magnetic sensor **116** detects that accessory **104** is coupled in a first, correct, orientation with device **100**, further processing such as NFC communications are triggered. When multi-axis magnetic sensor **116** detects a magnetic reading that is unrecognized or indicates that an accessory has been coupled in a second, incorrect orientation (e.g., upside down), device **100** forgoes operations such as indicating the attachment via user notification. Magnetic sensor **116** may monitor or measure the magnetic field at magnetic alignment structure **114**. When device **100** is not attached to device **102**, magnetic sensor **116** may measure a first amount of magnetism that is below a threshold level. When device **100** is attached to device **102** (e.g., when structures **114** and **124** are aligned), magnetic sensor **116** may detect a second amount of magnetism that exceeds the threshold level. When the output of sensor **116** exceeds the threshold, magnetic sensor **116** may send a wake-up signal to the NFC reader in device **100**. Operated in this way, magnetometer **116** may be used to trigger or initiate the NFC communications between devices **100** and **102**.

[0054] In some embodiments device **100** presents an indication regarding the attachment of an accessory. For example, when a wireless power transmitter is inductively coupled with device **100**, device **100** chimes audibly, and displays a battery charging icon and chimes. In some embodiments,

device **100** presents an indication regarding an attribute of an attached accessory. For example, when device **100** is coupled with a purple colored protective cover, device **100** presents an indication that it is coupled with a purple cover. In some embodiments, device **100** presents an indication regarding a functionality of an attached accessory. For example, when device **100** is coupled with a battery-powered protective cover, device **100** presents an indication that it is coupled with a purple cover, that the cover has a battery that is charged, and/or that it is receiving power from the battery-powered case. In some embodiments, device **100** presents an indication regarding an identity of an attached accessory. For example, when device **100** is coupled with a dock, device **100** presents an indication that is coupled with an unknown device and seeks permission to proceed further. Responsive to user permission to proceed, device **100** may indicate that the dock is named “Kitchen” and is associated with a number of food recipes that may be presented via device **100**.

[0055] FIG. 4 illustrates another suitable configuration in which portable electronic device **100** is inserted within battery case **104**. Device **102** may be a wireless power transmitting device such as a wireless charging mat or puck with a charging surface. Device **104** has a housing such as housing **138** with a recess R and/or other structures configured to receive device **100**. In this way, a user may removably attach device **100** to device **104** so that devices **100** and **104** may be used together as a portable unit. When it is desired to receive wireless power from device **102**, devices **104** and **100** may be placed together on the charging surface of device **102**. Device **104** optionally includes NFC antenna **132** and magnetic alignment structure **134**. NFC antenna **132** allows device **104** to communicate with devices **100** and/or **102**. Magnetic alignment structure **143** promotes spatial alignment and inductive coupling of device **104** with devices **100** and/or **102**.

[0056] In some embodiments, devices **100** and **104** communicate using NFC antennas **112** and **132** respectively. In some examples, NFC communication occurs during wireless power handshake operations, by temporarily halting the power handshake/negotiation process to perform the NFC communications. In some examples, NFC communication occurs during wireless power transfer operations, by temporality halting the active wireless power transfer to perform the NFC communications. The NFC reader in device **100** may be triggered or activated using magnetic sensor **116**, which monitors or measures the magnetic field at magnetic alignment structure **114**. When device **100** is not attached to device **104**, magnetic sensor **116** may detect a first amount of magnetism that is below a given threshold. When device **100** is attached to device **104** (e.g., when structures **114** and **134** are aligned), magnetic sensor **116** may measure a second amount of magnetism that exceeds the given threshold. When the output of sensor **116** exceeds the given threshold, magnetic sensor **116** may signal the NFC reader in device **100**. Operated in this way, magnetometer **116** may be used to trigger or initiate the NFC communications between devices **100** and **104**.

[0057] In the example of FIG. 4 in which portable electronic device **100** is attached to two different accessory devices, the audio, haptic, and/or visual affordance output by device **100** may be triggered upon attachment of each accessory or both accessories at the same time. For instance, device **100** may first be installed within device **104**. When device **100** is placed within recess R in housing **138** of device **104**, magnetic alignment structures **114** and **134** may spatially align devices **100** and **104** so that transmitting coil **130** is aligned with receiving coil **110**. When magnetic alignment structures **114** and **134** are aligned, magnetic sensor **116** may detect the presence of device **104** and will activate NFC antenna **112** of the reader in device **100** to generate a magnetic field. The magnetic field generated by antenna **112** may induce a corresponding current to flow through antenna **132** of the NFC tag in device **104**, thereby activating the NFC tag.

[0058] FIG. 5 is a side view of another accessory such as device **108** that may be attached to device **100**. Device **108** may be a stand or dock for holding or otherwise supporting device **100** in an upright or semi-upright position. In some embodiments device **108** does not include a wireless charging coil. If desired, however, device **108** may be provided with one or more wireless charging

coils. Device **106** includes NFC antenna **152** and magnetic alignment structure **154**. Magnetic alignment structure **154** may be formed around NFC antenna **152** (e.g., magnetic alignment structure **154** may be routed along the periphery of antenna **152** and may at least partially or completely surround antenna **152**). In one suitable arrangement, NFC antenna **152** and magnetic alignment structure **154** may form concentric loop structures. NFC antenna structure **152** in device **108** should have the same or similar structure and footprint as NFC antenna structure **112** of device **100** to ensure optimal coupling between the two antenna structures. NFC antenna **152** may be part of an NFC tag within device **108**, which may be used to transmit device-specific information to NFC antenna **112** within device **100**.

[0059] Magnetic alignment structure **154** in device **108** may magnetically couple with a corresponding magnetic alignment structure **114** in device **100** (e.g., magnets **114** may magnetically attract magnets **154** and vice versa). When magnetic alignment structure **154** in device **108** is coupled to magnetic alignment structure **114** in device **100**, NFC tag antenna **152** may be aligned with the corresponding NFC reader antenna **112** in device **100** to carry out NFC communication.

[0060] In accordance with an embodiment, device **108** may be configured to transmit information to device **100** using NFC upon attaching to device **100** but prior to wireless power transfer operations so that device **100** may issue a notification, chime, alert, or otherwise display some confirmatory information about the coupling of device **108** to the user. As an example, device **100** may receive information from device **108** indicating that it has been inserted into a docking accessory. In response, device **100** may present a dock icon on its display to indicate that it is now attached to a dock accessory. In another example, device **100** may receive information from device **108** indicating that it has been attached to a dock named “kitchen”. Device may present a kitchen icon on its display and/or may provide a default user interface screen that is associated with the dock.

[0061] FIG. **6** is a top view of a wireless charging coil, NFC antenna, and magnetic alignment structures in an illustrative portable electronic device **100**. As shown, device **100** includes one or more coils **110**. Coil(s) **110** may be wrapped around or overlapping with a magnetic core. Coil **110** may be ring-shaped (sometimes referred to as an annular coil or circular coil), may have a central opening **164** with one or more magnetic cores optionally formed in the central opening. A ring-shaped NFC antenna **112** may laterally surround coil **110**. Antenna structure **112** may sometimes be described as annular or circular. A ring-shaped magnetic alignment structure **114** may laterally surround NFC antenna **112**. Magnetic alignment structure **114** may sometimes be described as annular or circular. In FIG. **7**, coil **110**, antenna **112**, and magnetic alignment structure **114** are concentric (e.g., each structure **110**, **112**, and **114** may have a center coinciding at point C). Antenna **112** runs along a peripheral edge of wireless charging coil **110**. Magnetic alignment structure **114** runs along a peripheral edge of NFC antenna **112**. Concentric point C may bisect the horizontal width dimension across the housing of device **100** (as shown by bisecting line **160**) and may also bisect the vertical length dimension across the housing of device **100** (as shown by bisecting line **162**).

[0062] If desired, device **100** may include two or more wireless charging coils, NFC antenna **112** may be formed from two or more discrete antenna members arranged in a circular (annular) pattern, and magnetic alignment structure **114** may be formed from two or more discrete magnetic alignment members arranged in a circular (annular) pattern. Each of the discrete NFC antenna members and/or magnetic alignment members may have an arcuate arrangement. In other suitable embodiments, structures **110**, **112**, and **114** may be oval, triangular, rectangular, pentagonal, hexagonal, octagonal, or have another polygonal footprint.

[0063] Magnetic sensor **116** may be placed in close proximity to magnetic alignment structure **114** to effectively measure the magnetism of alignment structure **114**. For example, magnetic sensor **116** and alignment structure **114** may be separated by a distance less than 1 cm, less than 0.5 cm, less than 1 mm, less than 0.5 mm, less than 0.1 mm, between 0.1 mm and 1 cm, between 0.1 mm

and 1 mm, between 0.1 cm and 1 cm, between 0.1 cm and 0.5 cm, between 0.1 mm and 0.5 mm, or by other suitable distance.

[0064] Various arrangements of wireless charging coil (such as coil **110**) NFC antenna (such as antenna **112**), magnet (such as magnet **114**) are possible consistent with the techniques described herein. In some embodiments, NFC antenna **112** is disposed along an outer periphery of magnet **114**, and wireless charging coil **110** is disposed along the inner periphery of magnet **114**. The positions of NFC antenna **112** and wireless charging coil **110** can be reversed. In some embodiments, both wireless charging coil **110** and NFC antenna **112** reside inside the inner periphery of magnet **114**. The positions of wireless charging coil **110** and NFC antenna **112** can be reversed. In some embodiments, both wireless charging coil **110** and NFC antenna **112** reside outside the outer periphery of magnet **114**. The positions of wireless charging coil **110** and NFC antenna **112** can be reversed. These examples are illustrative.

[0065] FIG. 7 is a flow chart of exemplary processes involved in attaching a portable electronic device to one or more accessory devices in accordance with embodiments described herein. At block **200**, a device such as portable electronic device **100** (FIG. 1) is attached to an accessory device (e.g., power transmitting device **12** of FIG. 1, power transmitting and receiving device **18** of FIG. 1, device **102** of FIG. 3, device **104** of FIG. 4, device **108** of FIG. 5,) via magnetic alignment structures (e.g., structures **114** and **124** of FIG. 3, structures **114** and **134** of FIG. 4).

[0066] At block **202**, magnetic sensor **116** of portable electronic device **100** detects the presence of the accessory device that has just been attached to device **100**. In response to magnetic sensor **116** detecting appropriate attachment of an accessory device, at block **204** (FIG. 8), NFC components in device **100** and the attached accessory communicate with one another. In some embodiments, NFC communications include verifying the authenticity of the attached devices. In some embodiments, NFC communications include encryption. In some embodiments, NFC communications include transfer of information regarding device **100** and/or the accessory. In some examples, device **100** obtains information indicative of the type of accessory that has been attached, such as whether the accessory is a dock. In some examples, device **100** obtains information indicating functionalities provided by the attached accessory, such as whether the accessory provides power.

[0067] At block **206**, device **100** presents information about the attached accessory on its display using the information received during block **204**. For example, device **100** may display a wireless charging puck graphic or a phone case graphic, responsive to determining that a wireless charging puck or a phone case, respectively, has been attached to device **100**. Device **100** may also display a charging icon if device **100** is receiving power, such as wireless power signals, from the attached accessory. A functionality of device **100** may be made available or made unavailable based on the information received from the attached accessory. That is, certain applications may be enabled when device **100** is attached to a certain type of accessory. Also, certain applications may be disabled when device **100** is attached to a certain type of accessory. Device **100** may also alter its menu of available functions, such as the widget and application icons, based on information received from an attached accessory.

[0068] As indicated by branch **208**, device **100** may repeat blocks **202-206** as additional devices are attached. For example, device **100** may attach to wireless charging puck through an intervening protective case.

[0069] When device **100** is detached from an accessory, magnetic sensor **116** may sense the removal of the accessory at block **210**, and present information about the detachment in block **212**. The presentation of information includes one or more of an audio, haptic, and visual indications. When device **100** is detached from an accessory, device **100** may also note the location of detachment, and later present lost-and-found information. For example, the detaching of device **100** from a car mount provides a meaningful parking location for the car, and the parking location could be presented in a map of the local area.

[0070] FIG. 8 is a timing diagram illustrating how magnetic sensor **116** of device **100** (FIG. 1) may

detect attachment and detachment of accessories to device **100**, such as during blocks **202** and **210** of FIG. **7**, respectively. Sensor **116** may be configured to gather measurements at a predetermined time interval. For example, sensor **116** may gather one or more readings once per second (with a frequency of 1 Hz), twice per second (with a frequency of 2 Hz), three times per second (with a frequency of 3 Hz), more than three times per second (with a frequency greater than 3 Hz), 3-10 times per second, less than once per second, at most once every two seconds, at most once every three seconds, or at other suitable periodicity.

[0071] FIG. **8** illustrates exemplary measurements **312** at times **t1**, **t2**, and **t3**, provided by sensor **116**. These magnetic measurements lay within a first range of values **302**. Magnetic sensor outputs within range **302** may be indicative that no external accessory or magnetic component is presently attached to device **100**. At time **t4**, a first accessory (e.g., a battery case) may be installed on device **100**. During the attachment of device **100** and the battery case, the magnetic alignment structure within the battery case may be magnetically coupled to and aligned with magnetic alignment structure **114** of device **100**. Sensor **116** may detect the approach and proximity of the battery case and output second magnetic measurements **314** lying within a second range of values **304**. Magnetic sensor readings falling within range **304** may be indicative that one external accessory is presently attached to device **100**. Ranges **302** and **304** may be separated by a trigger gap **308** to ensure that there is adequate margin to help differentiate between the first scenario where no accessory is present and the second scenario where one accessory is attached.

[0072] At time **t9**, device **100** and the battery case, as one movable unit, may be placed on a second accessory (e.g., a wireless charging mat or puck). When the battery case is placed on the charging surface of the second accessory, the magnetic alignment structure within the battery case may be magnetically coupled to and aligned with the magnetic alignment structure of the second accessory and with magnetic alignment structure **114** of device **100**. As a result, sensor **116** within device **100** may output second magnetic measurements **316** lying within a third range of values **306**. Magnetic sensor readings falling within range **306** may be indicative that two external accessories are presently attached to device **100** (i.e., device **100** is presently stacked with at least two external accessories). Ranges **306** and **304** may be separated by a trigger gap **310** to ensure that there is adequate margin to help differentiate between the second scenario where one accessory is attached to device **100** and a third scenario where device **100** is attached or coupled to at least two accessories. In this illustrative example of FIG. **9**, magnetic sensor **116** distinguishes between the attachment of zero, one, or multiple external accessories.

[0073] The near-field communications reader in device **100** may perform anti-collision operations when multiple external accessories are detected. For example, a first near-field communications tag in a first accessory and a second near-field communications tag in a second accessory may both want to transmit information to the reader of device **100**. When detecting such potential collision, the near-field communications reader of device **100** may communicate with only one of the tags while communications with the other tag is halted. After communications with the first tag is complete, the reader can then proceed to communicate with the second tag.

[0074] Other sensing techniques are possible. In some examples, multiple magnetic sensors may be used. In some examples, NFC communication can be used to detect the presence of multiple attached accessories once a magnetic sensor has indicated the presence of at least one attached accessory. In some embodiments, device **100** uses NFC to detect when one or more accessories have been attached, instead of magnetic sensor **116**. An NFC reader may periodically transmit NFC pings to detect whether an accessory has been coupled to the housing of device **100**.

[0075] Turning to FIGS. **9** and **10**, exemplary techniques for communicating using NFC and wireless charging signals are described. Careful sequencing in the use of NFC and wireless charging signal can improve and mitigate interferences between the wireless operations. FIG. **9** is a flow chart of illustrative processes for performing NFC communications by pausing wireless power handshake operations in accordance with some embodiments.

[0076] At block **400**, portable electronic device **100** is attached to an accessory such as wireless power transmitting device **12** of FIG. **1**. At block **402**, the accessory detects the presence of portable electronic device **100**. At block **404**, power transmitting accessory **12** begins wireless power handshake operations with portable electronic device **100**. These handshaking operations may include authentication, negotiation of supported communication protocols and power transfer levels, and so forth. At block **406**, power transmitting accessory **12** pauses the wireless power handshake operations so that NFC communications can be performed between NFC components in devices **12** and **100**. In some embodiments these NFC communications include those described with reference to block **204** of FIG. **7**. At block **408**, after the NFC communications, power transmitting accessory **12** resumes the wireless power handshake operations. At block **410**, after the needed handshake and power negotiation operations are performed, wireless power transmitting accessory **12** begins active wireless power transfer by sending wireless power signals at appropriate (e.g., negotiated) levels to portable electronic device **100**. During active wireless power transfer in block **410**, devices **12** and **100** may further communication with one another, such as via in-band communication, to convey control and/or feedback signals to sustain wireless power transfer.

[0077] The example of FIG. **9** in which device **100** is attached to a power transmitting accessory is merely illustrative. As another example, device **100** can also be attached to an accessory such as power transmitting and receiving device **18** of FIG. **1**. In such scenarios, device **100** can communicate with the accessory via near-field communications and determine whether to then either transmit wireless power to the accessory or receive wireless power from the accessory.

[0078] FIG. **10** is a flow chart of illustrative processes for performing near-field communications by pausing active, on-going wireless power transmission in accordance with some embodiments. In some embodiments, the NFC communications operations during block **204** of FIG. **8** is performed after wireless power transmitting device **12** and portable electronic device **100** have negotiated for and begun wireless power transfer.

[0079] At block **500**, portable electronic device **100** is attached to an accessory such as wireless power transmitting device **12** of FIG. **1**. At block **502**, wireless power transmitting accessory **12** detects the presence of portable electronic device **100**. At block **504**, wireless power transmitting accessory **12** begins wireless power handshake operations with portable electronic device **100**. These handshaking operations may include authentication, to negotiation of supported communication protocols and power transfer levels, so forth. At block **506**, after the handshake and power negotiation operations are performed, wireless power transmitting accessory **12** begins active wireless power transfer at appropriate (e.g., negotiated) levels. During operations of block **506**, the power transmitting accessory may transmit wireless power signals to device **100** via the wireless power charging coils and may optionally perform in-band communications to convey control and data signals between the two devices.

[0080] At block **508**, wireless power transmitting accessory **12** pauses the active wireless power transfer operations (e.g., by temporarily halting the wireless power transmission and operating the accessory in a wireless-power-transfer-halted mode). During the wireless-power-transfer-halted mode, near-field communications can be performed between the NFC circuitry in devices **12** and **100**. In some embodiments these NFC communications include those described with reference to block **204** of FIG. **8**. At block **510**, after the needed NFC communications are performed, wireless power transmitting device **12** resumes active wireless power transfer operations.

[0081] Although the methods of operations are described in a specific order, it should be understood that other operations may be performed in between described operations, described operations may be adjusted so that they occur at slightly different times or described operations may be distributed in a system which allows occurrence of the processing operations at various intervals associated with the processing, as long as the processing of the overlay operations are performed in a desired way.

[0082] The foregoing describes exemplary embodiments of wireless power transfer systems

utilizing NFC communications. This information can be beneficially used to control efficient wireless charging operations and to appraise users of characteristics of accessories that are inductively coupled with their device. It is contemplated that some implementers of the present technology may consider the passage of identifiers, such as serial numbers, UIDs, manufacturer IDs, MAC addresses, or the like, to aide in the identification and handling of devices in a wireless charging system.

[0083] Entities implementing the present technology should take care to ensure that, to the extent any sensitive information is used in particular implementations, that well-established privacy policies and/or privacy practices are complied with. In particular, such entities would be expected to implement and consistently apply privacy practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining the privacy of users.

Implementers should inform users where personally identifiable information is expected to be transmitted in a wireless power transfer system, and allow users to “opt in” or “opt out” of participation. For instance, such information may be presented to the user when they place a device onto a wireless power transmitter.

[0084] It is the intent of the present disclosure that personal information data, if any, should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, data de-identification can be used to protect a user's privacy. For example, a device identifier may be masked to convey the characteristics of the device without uniquely identifying the device. De-identification may be facilitated, when appropriate, by removing identifiers, controlling the amount or specificity of data stored, controlling how data is stored, and/or other methods such as differential privacy. For example, a dock that has been paired with a user device may identify itself using minimally required information, such as a byte value of 0x00000001. While devices that have been explicitly paired by the user may understand that 0x00000001 refers to a Kitchen dock, the bit value of 0x00000001 itself does not inherently convey this level of information. Robust encryption may also be utilized to reduce the likelihood that communication between inductively coupled devices are spoofed or intercepted. NFC authentication can provide additional protection by preventing certain information from being exchanged with an unauthorized NFC device.

[0085] Entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of any personal information data should comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations.

[0086] The foregoing is merely illustrative and various modifications can be made to the described embodiments. The foregoing embodiments may be implemented individually or in any combination.

Claims

- 1.** An electronic device operable with an accessory, the electronic device comprising: near-field communications circuitry having a near-field communications antenna; a magnetic alignment structure configured to align the near-field communications antenna with a corresponding near-field communications antenna in the accessory when the magnetic alignment structure is magnetically coupled to the accessory; a magnetic sensor configured to detect when the magnetic alignment structure is magnetically coupled to the accessory, wherein the near-field communications circuitry is configured to receive information from the accessory in response to detecting that the magnetic alignment structure is magnetically coupled to the accessory; and an output device configured to present an output associated with the accessory using the received information.
- 2.** The electronic device of claim 1, wherein the magnetic alignment structure runs along a peripheral edge of the near-field communications antenna.
- 3.** The electronic device of claim 1, wherein the output device comprises a display configured to present, using the received information, the output associated with the accessory.
- 4.** The electronic device of claim 3, wherein the output associated with the accessory comprises a physical characteristic associated with the accessory.
- 5.** The electronic device of claim 4, wherein the physical characteristic comprises a color of the accessory.
- 6.** The electronic device of claim 3, wherein the output associated with the accessory comprises a functionality associated with the accessory and wherein the functionality comprises an operating mode that varies depending on a location of the accessory.
- 7.** The electronic device of claim 3, wherein the output associated with the accessory comprises ownership information associated with the accessory.
- 8.** The electronic device of claim 1, further comprising: a wireless charging coil, wherein the near-field communications antenna runs along a peripheral edge of the wireless charging coil.
- 9.** The electronic device of claim 1, wherein the output comprises an icon associated with the accessory and wherein the icon comprises an icon selected from a group consisting of: a wireless charging mat icon, a wireless charging puck icon, a removable case icon, a battery case icon, and a dock icon.
- 10.** An electronic device comprising: a magnetic structure configured to magnetically couple to a corresponding magnet in a first external device; and a magnetometer configured to distinguish between: (1) a first condition in which the electronic device is magnetically coupled to a second external device using the magnetic structure without being magnetically coupled to the first external device; and (2) a second condition in which the electronic device is magnetically coupled to both the first and second external devices using the magnetic structure.
- 11.** The electronic device of claim 10, further comprising: an output device configured to: present a visual output associated with the second external device in response to detecting the first condition in which the electronic device is magnetically coupled to the second external device using the magnetic structure without being magnetically coupled to the first external device; and present a visual output associated with the first external device in response to detecting the second condition in which the electronic device is magnetically coupled to both the first and second external devices using the magnetic structure.
- 12.** The electronic device of claim 10, wherein the second external device comprises a protective case.
- 13.** The electronic device of claim 10, further comprising: a near-field communications antenna configured to receive information from the second external device in response to detecting the first condition in which the electronic device is magnetically coupled to the second external device

using the magnetic structure without being magnetically coupled to the first external device.

14. The electronic device of claim 13, wherein the near-field communications antenna is further configured to receive information from the first external device in response to detecting the second condition in which the electronic device is magnetically coupled to both the first and second external devices using the magnetic structure.

15. An electronic device operable with an external accessory, comprising: a magnetic structure configured to magnetically couple with a corresponding magnetic structure in the external accessory; a magnetometer configured to detect detachment of the external accessory from the electronic device; and a display configured to present information about the detected detachment of the external accessory from the electronic device.

16. The electronic device of claim 15, further comprising: a near-field communications antenna configured to receive information from the external accessory in response to detecting that the magnetic structure is magnetically coupled to the external accessory.

17. The electronic device of claim 15, wherein the display is configured to present a location of the detected detachment of the external accessory from the electronic device.

18. The electronic device of claim 15, further comprising: a wireless charging coil, wherein the magnetic structure at least partially surrounds the wireless charging coil.

19. The electronic device of claim 15, wherein the display is configured to present a color of the external accessory.

20. The electronic device of claim 15, wherein the display is configured to present a device type of the external accessory.
