

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388922
Kind Code	B1
Date of Patent	August 12, 2025
Inventor(s)	Tian; Wen

Bracket

Abstract

A bracket includes a base. The base includes a base body, a suction cup, and a connecting rod. The suction cup is provided at a bottom portion of the base body. The connecting rod is provided on the base body and connected to the suction cup. The connecting rod is movable between a first position and a second position along its axial direction. When the connecting rod is moved from the second position to the first position along its axial direction, the connecting rod is configured for driving the suction cup to rise to form a vacuum negative pressure cavity. When the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod is configured for driving the suction cup to descend to release vacuum negative pressure in the vacuum negative pressure cavity.

Inventors: Tian; Wen (Guangdong, CN)

Applicant: Shenzhen Zhenwei Xin Technology Co., Ltd. (Shenzhen, CN)

Family ID: 1000008392965

Assignee: SHENZHEN ZHENWEI XIN TECHNOLOGY CO., LTD. (Shenzhen, CN)

Appl. No.: 19/012274

Filed: January 07, 2025

Foreign Application Priority Data

CN	202422135379.9	Sep. 01, 2024
CN	202422140116.7	Sep. 01, 2024
CN	202422152901.4	Sep. 01, 2024

Publication Classification

Int. Cl.: H04M1/04 (20060101); F16B47/00 (20060101); F16M13/02 (20060101)

U.S. Cl.:

CPC **H04M1/04** (20130101); **F16B47/006** (20130101); **F16M13/022** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10641314	12/2019	Fan	N/A	F16B 47/006
2011/0210225	12/2010	Chen	248/363	F16B 47/006

Primary Examiner: Bataille; Frantz

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The application claims priority of Chinese patent application CN2024221529014, filed on Sep. 1, 2024, which is incorporated herein by reference in its entirety. The application also claims priority of Chinese patent application CN2024221401167, filed on Sep. 1, 2024, which is incorporated herein by reference in its entirety. The application also claims priority of Chinese patent application CN2024221353799, filed on Sep. 1, 2024, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present invention relates to the field of brackets, particularly to a bracket.

BACKGROUND ART

(3) At present, brackets are mainly used as a fixed accessory for mobile phones, camera devices, or other intelligent devices, and are widely used in daily life. The existing brackets are mainly fixed by adhering suction cups provided with adhesive to objects.

(4) The Chinese invention patent with application No. 202320683949.0 discloses a technical solution in which a bracket uses a suction cup for suction and a protruding piece for taking is provided on a side end of the suction cup. In this technical solution, although the suction cup can be used for suction and the bracket can be disassembled by pulling the protruding piece to remove the suction cup, due to the protruding piece being arranged on an edge of the suction cup, there is a problem that accidental touching of the protruding piece in the process of use may cause failure of suction of the suction cup.

(5) Therefore, it is urgent to research and develop a bracket to solve the problem of failure of suction of the bracket due to accidental touching.

SUMMARY

(6) In order to overcome the shortcomings of the prior art, a bracket is provided in the present invention. A base of the bracket can improve the suction stability of the bracket base.

(7) The technical solution adopted by the present invention to solve its technical problem is as follows.

(8) A bracket is provided in the present invention, including a base. The base includes: a base body;

a suction cup provided at a bottom portion of the base body; and a connecting rod provided on the base body and connected to the suction cup.

(9) The connecting rod is movable between a first position and a second position along its axial direction.

(10) When the connecting rod is moved from the second position to the first position along its axial direction, the connecting rod is configured for driving the suction cup to rise to form a vacuum negative pressure cavity. When the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod is configured for driving the suction cup to descend to release vacuum negative pressure in the vacuum negative pressure cavity.

(11) As an improvement of the present invention, the connecting rod is connected with a pin shaft. The base body is equipped with climbing tracks. The pin shaft cooperates with the climbing track to drive the connecting rod to move between the first position and the second position. A relative climbing motion of the pin shaft along the climbing track drives the connecting rod to move from the second position to the first position, and a relative descending motion of the pin shaft along the climbing track drives the connecting rod to move from the first position to the second position.

(12) As an improvement of the present invention, the base body is provided with a rotating member. The rotating member is rotatable relative to the base body. The climbing track is formed on the rotating member. An end portion of the pin shaft extends into the climbing track and performs the relative climbing motion or the relative descending motion relative to the climbing track with the rotation of the rotating member.

(13) The climbing track includes a first position limiting point and a second position limiting point. The first position limiting point is higher than the second position limiting point.

(14) A total number of the climbing tracks is two. The two climbing tracks are opposite to each other and are arranged at positions of a top portion of the rotating member.

(15) As an improvement of the present invention, the rotating member rotates relatively in a third position and a fourth position of the base body.

(16) The rotating member rotates relative to the base from the third position to the fourth position, driving the pin shaft to perform the relative climbing motion from the second position limiting point of the climbing track to the first position limiting point, thereby driving the connecting rod to move from the second position to the first position.

(17) The rotating member rotates relative to the base body from the fourth position back to the third position, driving the pin shaft to perform the relative descending motion from the first position limiting point of the climbing track back to the second position limiting point, thereby driving the connecting rod to move from the first position to the second position.

(18) As an improvement of the present invention, the base body is covered with a first cover body. The rotating member, the connecting rod, and the pin shaft are positioned inside the first cover body. A swing groove is defined in the first cover body.

(19) The rotating member is connected with a swing rod. An end portion of the swing rod passes through the swing groove and extends out of the first cover body.

(20) As an improvement of the present invention, a top surface of the base body is provided with a first position limiting rod. A first arc-shaped position limiting groove is defined in the rotating member. The first position limiting rod passes through the first arc-shaped position limiting groove and cooperates with two ends of the first arc-shaped position limiting groove for position limiting.

(21) As an improvement of the present invention, a restoration spring is sleeved on the connecting rod. One end of the restoration spring abuts against the suction cup, and an opposite end of the restoration spring abuts against the rotating member.

(22) As an improvement of the present invention, the base body is provided with a second cover body. The rotating member, the connecting rod, and the pin shaft are positioned inside the second cover body. A connecting sleeve is provided in the second cover body.

(23) Connecting convex blocks are provided on an outer wall of the rotating member, and

connecting grooves engaged with the connecting convex blocks are defined in an inner wall of the connecting sleeve.

(24) As an improvement of the present invention, at least one second position limiting rod is provided on a top surface of the base body. The second cover body is provided with a second arc-shaped position limiting groove corresponding to the second position limiting rod. The second position limiting rod passes through the second arc-shaped position limiting groove and cooperates with two ends of the second arc-shaped position limiting groove for position limiting.

(25) As an improvement of the present invention, a protrusion is provided at a bottom portion of the suction cup. The protrusion extends towards one side away from the base body. When the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod and the suction cup are driven to descend, the protrusion abuts against a suction surface of the suction cup, and the vacuum negative pressure in the vacuum negative pressure cavity between the suction cup and the suction surface is released, thus forming a disengaged state.

(26) As an improvement of the present invention, a height of the protrusion is higher than a height of the suction surface of the suction cup. A bottom portion of the base body is provided with a rim. The rim corresponds to an outer peripheral edge of the suction cup.

(27) As an improvement of the present invention, the connecting rod is moved from a second position back to a first position along its axial direction, driving the connecting rod to lift and pull the suction cup connected to the connecting rod to deform upward. A first gap is defined between the protrusion and the suction surface of the suction cup. The rim presses against the outer peripheral edge of the suction cup. The suction cup and the suction surface form a vacuum negative pressure cavity, thus forming a suction state.

(28) In the suction state, the rim is pressed against the outer peripheral edge of the suction cup.

(29) In the disengaged state, a second gap is defined between the rim and the suction cup, or the rim is in contact with the outer peripheral edge of the suction cup.

(30) As an improvement of the present invention, the protrusion is provided at a central position of the suction cup. A bottom portion of the connecting rod is provided with a protruding column. The protruding column is positioned inside the suction cup, and the protruding column is at least partially positioned below the suction cup.

(31) As an improvement of the present invention, the connecting rod and the suction cup are integrally formed. The suction cup is made of plastic or silicone material. An area of the protrusion accounts for 2%-65% of an area of the suction cup.

(32) As an improvement of the present invention, a step is provided on the connecting rod. A plurality of holes extending along an axial direction is defined in the step. A flexible body is accommodated in the hole. The suction cup cooperates to receive the step. The flexible body inside the hole is integrally connected to the suction cup.

(33) When the connecting rod moves along its axial direction, the suction cup is pulled up to be deformed or lowered to be restored driven by the flexible body in the hole and the step.

(34) As an improvement of the present invention, the step is provided with a plurality of layers, and the holes are defined in at least one layer of the step. The suction cup is provided with a suction cup groove body. Both a bottom portion of the connecting rod and the step are accommodated in the suction cup groove body.

(35) As an improvement of the present invention, the suction cup is integrally formed with both the connecting rod and the flexible body by second stage injection molding.

(36) As an improvement of the present invention, the bracket further includes a support rod and a support main body. The support main body is used for supporting a mobile phone. One end of the support rod is rotatably connected to the base, and an opposite end of the support rod is rotatably connected to the support main body.

(37) As an improvement of the present invention, the support rod includes a first telescopic rod and a second telescopic rod. The first telescopic rod is sleeved on the second telescopic rod, and the

second telescopic rod is telescopic within the first telescopic rod. A magnetic attraction member is provided inside the support main body. The magnetic attraction member is used for adhering an electronic device to the support main body.

(38) As an improvement of the present invention, an accommodating groove is defined in a bottom portion of the support main body. When the first telescopic rod is completely retracted relative to the second telescopic rod, the supporting rod is capable of being accommodated in the accommodating groove, and the support main body is capable of rotating to completely cover a top surface of the base.

(39) Beneficial effects of the present invention are as follows. The bracket is provided in the present invention, including a base. The base includes the base body, the suction cup, and the connecting rod. The suction cup is provided at the bottom portion of the base body. The connecting rod is provided on the base body and connected to the suction cup. The connecting rod is movable between the first position and the second position along its axial direction. When the connecting rod is moved from the second position to the first position along its axial direction, the connecting rod drives the suction cup to rise to form the vacuum negative pressure cavity. When the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod drives the suction cup to descend to release the vacuum negative pressure in the vacuum negative pressure cavity. The present invention can improve the convenience of disassembly and assembly of the base of the bracket, and enhance the suction stability of the base of the bracket.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Implementations of the present disclosure will now be described, by way of embodiment, with reference to the attached figures. It should be understood, the drawings are shown for illustrative purpose only, for ordinary person skilled in the art, other drawings obtained from these drawings without paying creative labor by an ordinary person skilled in the art should be within scope of the present disclosure.

(2) FIG. 1 is a schematic diagram of a structure of a base of the present invention.

(3) FIG. 2 is an exploded view of a base of the present invention.

(4) FIG. 3 is a schematic diagram of a structure of a rotating member of the present invention.

(5) FIG. 4 is a sectional view of the present invention taken along a connecting rod.

(6) FIG. 5 is a schematic diagram of a structure of another base of the present invention.

(7) FIG. 6 is an exploded view of another base of the present invention.

(8) FIG. 7 is a schematic diagram of a structure of another rotating member of the present invention.

(9) FIG. 8 is a schematic diagram of a structure of a second cover body of the present invention.

(10) FIG. 9 is a sectional view of the present invention taken along another connecting rod.

(11) FIG. 10 is a schematic diagram of an overall structure of an open state of a bracket according to the present invention.

(12) FIG. 11 is a schematic diagram of an overall structure of a closed state of a bracket according to the present invention.

(13) FIG. 12 is a schematic diagram of a partial structure of a base of the present invention.

(14) FIG. 13 is an exploded view of a partial structure of a base of the present invention.

(15) FIG. 14 is a schematic structural diagram of a suction cup structure of the present invention.

(16) FIG. 15 is a cross-sectional view of a suction cup structure of the present invention.

(17) FIG. 16 is an exploded view of a suction cup structure of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(18) It will be appreciated that for simplicity and clarity of illustration, where appropriate, reference numerals have been repeated among the different figures to indicate corresponding or analogous elements. In addition, numerous specific details are set forth in order to provide a thorough understanding of the exemplary embodiments described herein. However, it will be understood by those of ordinary skill in the art that the exemplary embodiments described herein may be practiced without these specific details. In other instances, methods, procedures, and components have not been described in detail so as not to obscure the related relevant feature being described. Also, the description is not to be considered as limiting the scope of the exemplary embodiments described herein. The drawings are not necessarily to scale and the proportions of certain parts may be exaggerated to better illustrate details and features of the present disclosure.

(19) The term “comprising” when utilized, means “including, but not necessarily limited to”; it specifically indicates open-ended inclusion or membership in the so-described combination, group, series, and the like. The disclosure is illustrated by way of example and not by way of limitation in the figures of the accompanying drawings in which like references indicate similar elements. It should be noted that references to “an” or “one” embodiment in this disclosure are not necessarily to the same embodiment, and such references can mean “at least one”. In addition, the terms “first” and “second” are used for descriptive purposes only and cannot be understood as indicating or implying relative importance or implying the number of indicated technical features. Thus, the features defined as “first” and “second” may explicitly or implicitly include one or more of the features. In the description of embodiments of the application, “a plurality of” means two or more, unless otherwise specifically defined.

Embodiment One

(20) As shown in FIGS. 1-4, a bracket provided in this embodiment includes a base **10**. The base **10** includes a base body **100**. A first cover body **500** is provided on the base body **100**. The first cover body **500** is fixedly connected to the base body **100**. A cavity is formed between the first cover body **500** and the base body **100**. An installation groove **130** is defined in a top portion of the base body **100**. A hollow rotating member **300** is provided on the installation groove **130**. The rotating member **300** is rotatable relative to the base body **100**. At least one climbing track **310** is formed on a top portion of the rotating member **300**. This embodiment is preferably provided with two climbing tracks **310** arranged opposite to each other.

(21) The base body **100** is provided with a connecting rod **400**. The connecting rod **400** runs through the base body **100**. A bottom portion of the connecting rod **400** is connected to a suction cup **200**, and a top portion of the connecting rod **400** is configured for running through the rotating member **300**.

(22) A pin shaft **410** is provided on the connecting rod **400**. The pin shaft **410** cooperates with the climbing track **310** to drive the connecting rod **400** to move between a first position and a second position. A relative climbing motion of the pin shaft **410** along the climbing track **310** drives the connecting rod **400** to move from the second position to the first position, and a relative descending motion of the pin shaft **410** along the climbing track **310** drives the connecting rod **400** to move from the first position to the second position.

(23) The pin shaft **410** can be arranged to be integrally formed with the connecting rod **400**. Alternatively, a penetrating hole **103** can be defined in the connecting rod **400**, and the pin shaft **410** can be in interference fit inside the penetrating hole **103**.

(24) A groove body is defined in the rotating member **300**. A bottom groove wall of the groove body is curved to form the climbing track **310**. An end portion of the pin shaft **410** extends into the climbing track **310** and performs the relative climbing motion or the relative descending motion relative to the climbing track **310** with rotation of the rotating member **300**.

(25) The climbing track **310** is provided with a first position limiting point **311** and a second position limiting point **312**. A height of the first position limiting point **311** is higher than a height of the second position limiting point **312**. The pin shaft **410** is moved within the climbing track **310**

to cooperate with the first position limiting point **311** or the second position limiting point **312** for position limiting.

(26) The rotating member **300** rotates relatively in a third position and a fourth position of the base body **100**.

(27) The rotating member **300** rotates relative to the base **10** from the third position to the fourth position, driving the pin shaft **410** to perform the relative climbing motion from the second position limiting point **312** of the climbing track **310** to the first position limiting point **311**, thereby driving the connecting rod **400** to move from the second position to the first position.

(28) The rotating member **300** rotates relative to the base body **100** from the fourth position back to the third position, driving the pin shaft **410** to perform the relative descending motion from the first position limiting point **311** of the climbing track **310** back to the second position limiting point **312**, thereby driving the connecting rod **400** to move from the first position to the second position.

(29) A swing groove **510** in communication with an internal cavity is defined in the first cover body **500**. A swing rod **320** is provided on an outer wall of the rotating member **300**. An end portion of the swing rod **320** passes through the swing groove **510** and extends out of the first cover body **500**. In actual use, rotating the swing rod **320** can drive the rotating member **300** to rotate on the base body **100**, and a rotation angle is limited by an angle between the swing rod **320** and two end groove walls of the swing groove **510**.

(30) Moreover, at least one rubber ring **350** is provided at a bottom portion of the rotating member **300**. When the rotating member **300** is installed in the installation groove **130**, the rubber ring **350** abuts against both the installation groove **130** and the rotating member **300** to increase a friction force during the rotation of the rotating member **300**.

(31) A restoration spring **700** is sleeved on an outer wall of the connecting rod **400**. One end of the restoration spring **700** abuts against the suction cup **200**, and an opposite end of the restoration spring **700** abuts against the rotating member **300**, so as to assist in restoring the connecting rod **400** and the suction cup **200**.

(32) Specifically, the rotating member **300** is driven by the swing rod **320** to rotate, and the pin shaft **410** performs the relative climbing motion along the climbing track **310** to enter the first position limiting point **311** with a higher height from the second position limiting point **312** with a lower height. After the suction cup **200** is lifted to form a vacuum negative pressure cavity to adhere to an object, the connecting rod **400** drives the suction cup **200** to lift to compress the restoration spring **700**. When the suction cup **200** needs to release vacuum negative pressure in the vacuum negative pressure cavity to be separated from the object, the rotating member **300** is driven by the restoration of the swing rod **320** to rotate reversely to be restored, and an elastic force of the restoration spring **700** assists the suction cup **200** and the connecting rod **400** in being restored.

(33) A top portion of the base body **100** is provided with a first position limiting rod **110**. A first arc-shaped position limiting groove **330** is defined in the rotating member **300**. The first position limiting rod **110** passes through the first arc-shaped position limiting groove **330** and cooperates with two end groove walls of the first arc-shaped position limiting groove **330** for position limiting.

(34) The suction cup **200** in this embodiment is preferably any one of a TPE suction cup **200**, a silicone suction cup **200**, or a PVC suction cup **200**.

(35) A top portion of the first cover body **500** is hinged with a connecting rod structure, which is used for connecting with a bracket for fixing a mobile phone, another intelligent device, or a photographing device.

(36) Usage steps of the base **10** of the bracket in this embodiment are as follows: 1. When the base **10** of the bracket needs to be adhered to an object: attaching the suction cup **200** onto the object that needs to be adhered; and swinging the swing rod **320** within a range of the swing groove **510** until the pin shaft **410** disengages from the second position limiting point **312** and then enters the first position limiting point **311**.

(37) During this process, due to the rotation of the rotating member **300** on the base body **100**,

while a position of the connecting rod **400** and a position of the pin shaft **410** on the connecting rod **400** remain unchanged, the pin shaft **410** performs the relative climbing motion along the climbing track **310**, driving the connecting rod **400** to drive the suction cup **200** to lift and deform, and at the same time compressing the restoration spring **700**, thereby forming a vacuum negative pressure cavity between the suction cup **200** and the object to achieve suction on the object. 2. When the base **10** of the bracket needs to detach from the adhered object: swinging the swing rod **320** reversely until the pin shaft **410** disengages from the first position limiting point **311** and then enters the second position limiting point **312**.

(38) During this process, the rotating member **300** performs the relative descending motion along the climbing track **310** to achieve restoration, and cooperates with the elastic force of the restoration spring **700** to drive the connecting rod **400** and the suction cup **200** to be restored, releasing the vacuum negative pressure in the vacuum negative pressure cavity, causing the suction of the suction cup **200** to fail and achieving detachment from the object.

Embodiment Two

(39) As shown in FIGS. 1-4 and FIGS. 10-11, based on the embodiment one, the bracket further includes a support rod **20** and a support main body **30**. The support main body **30** is used for supporting a mobile phone. One end of the support rod **20** is rotatably connected to the base **10**, and an opposite end of the support rod **20** is rotatably connected to the support main body **30**.

(40) Furthermore, the support rod **20** includes a first telescopic rod **21** and a second telescopic rod **22**. The first telescopic rod **21** is sleeved on the second telescopic rod **22**, and the second telescopic rod **22** is telescopic within the first telescopic rod **21**. A magnetic attraction member is provided inside the support main body **30**. The magnetic attraction member is used for adhering an electronic device to the support main body **30**.

(41) Furthermore, an accommodating groove **31** is defined in a bottom portion of the support main body **30**. When the first telescopic rod **21** is completely retracted relative to the second telescopic rod **22**, the supporting rod **20** is capable of being accommodated in the accommodating groove **31**, and the support main body **30** is capable of rotating to completely cover a top surface of the base **10**.

(42) Through the above structure, a user can place a mobile phone on the support main body **30** in a magnetic attraction manner. When the bracket is not used, the support rod can be retracted and folded into the accommodating groove **31** of the support main body **30**, which is simple and clever, reduces storage area, and is easy to carry.

Embodiment Three

(43) As shown in FIGS. 5-9, in this embodiment, the base body **100** is covered with a second cover body **600**. The second cover body **600** is rotatable relative to the base body **100**. The second cover body **600** is provided with a connecting sleeve **610**. The connecting sleeve **610** is sleeved on the rotating member **300**. An inner wall of the connecting sleeve **610** is provided with connecting grooves **611**. An outer wall of the rotating member **300** is provided with connecting convex blocks **340**. When the connecting sleeve **610** is sleeved on the rotating member **300**, the connecting convex block **340** is inserted into the connecting groove **611**, so that when the second cover body **600** rotates relative to the base body **100**, the second cover body **600** drives the rotating member **300** to rotate, which can better prevent a disengagement structure of the suction cup **200** from being touched by mistake.

(44) Correspondingly, at least one second position limiting rod **120** is provided on a top surface of the base body **100**. The second cover body **600** is provided with a second arc-shaped position limiting groove **620** on a side portion of the connecting sleeve **610**. The second arc-shaped position limiting groove **620** corresponds to the second position limiting rod **120**. The second position limiting rod **120** passes through the second arc-shaped position limiting groove **620** and cooperates with two end groove walls of the second arc-shaped position limiting groove **620** for position limiting.

(45) A top portion of the second cover body **600** is hinged with a connecting rod structure, which is used for connecting with a bracket for fixing a mobile phone, another intelligent device, or a photographing device.

(46) Other structures of this embodiment are identical with embodiment one, and will not be repeated here.

(47) Usage steps of the base **10** of the bracket in this embodiment are as follows: 1. When the base **10** of the bracket needs to be adhered to an object: attaching the suction cup **200** onto the object that needs to be adhered; and rotating the second cover body **600** to drive the rotating member **300** to rotate until the pin shaft **410** disengages from the second position limiting point **312** and then enters the first position limiting point **311**.

(48) During this process, the pin shaft **410** performs a relative climbing motion along the climbing track **310**, driving the connecting rod **400** to drive the suction cup **200** to lift and deform, and at the same time compressing the restoration spring **700**, forming a vacuum negative pressure cavity between the suction cup **200** and the object to achieve suction on the object. 2. When the base **10** of the bracket needs to detach from the adhered object: rotating the second cover body **600** reversely until the pin shaft **410** disengages from the first position limiting point **311** and then enters the second position limiting point **312**.

(49) In this process, the rotating member **300** rotates relative to the base body **100** to achieve restoration, and cooperates with an elastic force of the restoration spring **700** to drive the connecting rod **400** and the suction cup **200** to be restored, releasing the vacuum negative pressure in the vacuum negative pressure cavity, causing the suction of the suction cup **200** to fail and achieving detachment from the object.

Embodiment Four

(50) As shown in FIGS. 1-4 and FIGS. 12-13, a base **10** of a bracket is provided in this embodiment. The base **10** includes a base body **100**. A suction cup **200** is provided at a bottom portion of the base body **100**. The suction cup **200** is made of plastic or silicone material. This embodiment preferably uses one of TPE suction cup **200**, PVC suction cup **200**, or silicone suction cup **200**. A connecting rod **400** is also provided on the base body **100**. The connecting rod **400** runs through the base body **100**. A bottom portion of the connecting rod **400** is connected to the suction cup **200**.

(51) Moreover, the connecting rod **400** is movable along its own axial direction on the base body **100**, driving the suction cup **200** to lift or descend.

(52) A protrusion **301** is provided at a central position of the suction cup **200**. A bottom portion of the protrusion **301** is positioned below a bottom portion of the suction cup **200**. It can be understood that in a natural state, a height of the protrusion **301** is higher than a height of a suction surface of the suction cup **200**.

(53) Moreover, an area of the protrusion **301** accounts for 2%-65% of an area of the suction cup **200**.

(54) Optionally, the connecting rod **400** and suction cup **200** are integrally formed. Alternatively, the connecting rod **400** and the suction cup **200** is integrally formed by second stage injection molding (an injection molding process), so that the bottom portion of the connecting rod **400** is wrapped by the suction cup **200**.

(55) A bottom portion of the connecting rod **400** is provided with a protruding column **201**. The protruding column **201** is positioned inside the suction cup **200**, so that both one part of the connecting rod **400** and the protruding column **201** are accommodated inside the suction cup **200**. At least one part of the protruding column **201** is positioned below the suction cup **200**, thus forming the protrusion **301**.

(56) A bottom portion of the base body **100** is provided with a rim **101**. The rim **101** corresponds to an outer peripheral edge of the suction cup **200**.

(57) In practical use, the suction cup **200** cooperates with the base body **100** to form a disengaged

state or a suction state, and the connecting rod **400** is moved along its axial direction to form a first position and a second position.

(58) The connecting rod **400** is moved from the first position to the second position along its axial direction, driving the connecting rod **400** to descend. The protrusion **301** abuts against the suction surface of the suction cup **200**, and the vacuum negative pressure in the vacuum negative pressure cavity between the suction cup **200** and the suction surface is released, thus forming the disengaged state.

(59) The connecting rod **400** is moved from the second position back to the first position along its axial direction, driving the connecting rod **400** to lift and pull the suction cup **200** connected to the connecting rod **400** to deform upward. A first gap is defined between the protrusion **301** and the suction surface of the suction cup **200**. The rim **101** on the base body **100** presses against the peripheral edge of the suction cup **200**, and the suction cup **200** forms the vacuum negative pressure cavity with the suction surface, thus forming the suction state.

(60) A restoration spring **700** is sleeved on the connecting rod **400**. One end of the restoration spring **700** abuts against the suction cup **200**, and on opposite end of the restoration spring **700** abuts against the base body **100**. After the connecting rod **400** is lifted along its axial direction, the suction cup **200** and the base body **100** cooperate to compress the restoration spring **700**, so that when the connecting rod **400** descends to be restored, an elastic restoration force of the restoration spring **700** can assist in the restoration of the connecting rod **400**, improving the convenience of the restoration.

Embodiment Five

(61) As shown in FIGS. 1-4 and FIGS. 12-13, based on the embodiment four, this embodiment also includes a rotatable rotating member **300** at a top portion of the base body **100**. The rotating member **300** has a hollow structure, and two climbing tracks **310** opposite to each other are arranged at a top portion of the rotating member **300**. Each of the climbing tracks **310** is provided with a first position limiting point **311** and a second position limiting point **312**. The first position limiting point **311** and the second position limiting point **312** have different heights. A top portion of the connecting rod **400** is equipped with a pin shaft **410**. The pin shaft **410** is mounted on the rotating member **300**, and two ends of the pin shaft **410** extend into the climbing tracks **310** respectively corresponding to the two ends of the pin shaft **410**.

(62) A first cover body **500** is provided on the base body **100**. The first cover body **500** covers the rotating member **300**, the connecting rod **400**, and the pin shaft **410** inside. A swing groove **510** penetrating through the first cover body **500** is defined in the first cover body **500**. A swing rod **320** is provided on an outer wall of the rotating member **300**. The swing rod **320** passes through the swing groove **510** and extends out of the first cover body **500**.

(63) In actual use, a user rotates the swing rod **320** to make the rotating member **300** rotate, and the pin shaft **410** moves from a positioning part with a lower height to a positioning part with a higher height, so that the connecting rod **400** is driven to lift along its axial direction, the suction cup **200** is pulled up and deformed upward, and the rim **101** is pressed against an outer peripheral edge of the suction cup **200**, thus forming a vacuum negative pressure cavity between the suction cup **200** and a suction surface to complete the suction.

(64) On the contrary, by rotating the swing rod **320** reversely, the rotating member **300** is restored, and the pin shaft **410** moves from the positioning part with a higher height to the positioning part with a lower height, driving the connecting rod **400** to descend to be restored along its axial direction. The suction cup **200** and the protrusion **301** are restored with the assistance of the restoration spring **700**. The protrusion **301** abuts against the suction surface, and the rim **101** no longer presses against the outer peripheral edge of the suction cup **200**, releasing the vacuum negative pressure inside the vacuum negative pressure cavity between the suction cup **200** and the suction surface, thereby completing the detachment of the suction cup **200** from the suction surface.

Embodiment Six

(65) As shown in FIGS. 1-4 and FIGS. 14-16, a suction cup structure includes a connecting rod **400** and a suction cup **200**. The suction cup **200** is arranged on a bottom portion of the connecting rod **400** and is connected to the connecting rod **400**. A step **102** is provided on the connecting rod **400**. The step **102** is provided with a plurality of layers, and a plurality of holes **103** are defined in at least one layer of the step **102**. A flexible body is provided inside the hole **103**, and the flexible body is connected to the suction cup **200**. The holes **103** in this embodiment are preferably arranged in an annular array along an axis of the connecting rod **400**.

(66) A suction cup groove body **202** is provided inside the suction cup **200**. The suction cup groove body **202** is used for accommodating the bottom portion of the connecting rod **400** and the step **102**.

(67) The suction cup **200** is integrally formed and connected with both the connecting rod **400** and the flexible body by second stage injection molding. Mainly, the connecting rod **400** is first placed into an injection mold of the suction cup **200**, and while the suction cup **200** is formed by injection molding, the suction cup groove body **202** is formed in the suction cup **200** to accommodate and wrap the bottom portion of the connecting rod **400** and the step **102**. Moreover, the hole **103** on the step **102** is injected with the flexible body to connect the step **102** and the suction cup **200** together, improving the stability of the connection between the connecting rod **400** and the suction cup **200**.

(68) In practical use, the connecting rod **400** of this embodiment is capable of moving up and down along its own axial direction. During the process of moving up and down, the step **102** on the connecting rod **400** and the flexible body in the hole **103** in the step **102** cooperate to drive the suction cup **200** to be pulled up and deformed to form a vacuum negative pressure cavity, or to be lowered and restored to release vacuum negative pressure in the vacuum negative pressure cavity, thereby achieving suction connection or detachment between the suction cup **200** and a suction surface.

Embodiment Seven

(69) As shown in FIGS. 1-9 and FIGS. 14-16, a base **10** of a bracket is provided in this embodiment, including a base body **100**. A bottom portion of the base body **100** is provided with the suction cup **200** and the connecting rod **400** of embodiment six. The connecting rod **400** runs through the base body **100**, and a top portion of the connecting rod **400** extends above the base body **100**.

(70) A groove is defined in a top portion of the base body **100**. A rotating member **300** is provided inside the groove. The rotating member **300** rotates along a circumferential direction of the connecting rod **400**, and the rotating member **300** is hollow. The connecting rod **400** runs through the rotating member **300**. Two climbing tracks **310** are provided on the rotating member **300**. Each of the climbing tracks **310** is provided with a first position limiting point **311** and a second position limiting point **312**. A height of the first position limiting point **311** is different from a height of the second position limiting point **312**.

(71) A pin shaft **410** is provided on the connecting rod **400**. The pin shaft **410** is mounted on the rotating member **300**. The pin shaft **410** has two opposite ends. Each end of the pin shaft **410** extends into a corresponding climbing track **310**.

(72) A restoration spring **700** is sleeved on the connecting rod **400**. One end of the restoration spring **700** abuts against the suction cup **200**, and an opposite end of the restoration spring **700** abuts against the base body **100**.

(73) Optionally, a swing rod **320** is provided on an outer wall of the rotating member **300**. A first cover body **500** is provided on the base body **100**. The first cover body **500** is fixedly connected to the base body **100**, and a swing groove **510** is defined in the first cover body **500**. An end portion of the swing rod **320** passes through the swing groove **510** and extends out of the first cover body **500**.

(74) When in use, the swinging rod **320** is rotated within the swinging groove **510** to drive the rotating member **300** to rotate, causing the pin shaft **410** to switch between the first position limiting point **311** and the second position limiting point **312**, thereby driving the suction cup

structure in the embodiment to ascend and descend, achieving suction connection or detachment between the suction cup **200** and a suction surface.

(75) Optionally, connecting convex blocks **340** are provided on an outer wall of the rotating member **300**. A second cover body **600** is provided on the base body **100**. The second cover body **600** rotates relative to the base body **100**. Connecting grooves **611** are defined in the second cover body **600**. The connecting convex blocks **340** are engaged with the connecting grooves **611**.

(76) When in use, the second cover body **600** is rotated to drive the rotating member **300** to rotate, causing the pin shaft **410** to switch between the first position limiting point **311** and the second position limiting point **312**, thereby driving the suction cup structure in the embodiment to ascend and descend, achieving suction connection or detachment between the suction cup **200** and the suction surface.

(77) The above description only describes embodiments of the present disclosure, and is not intended to limit the present disclosure; various modifications and changes can be made to the present disclosure. Any modifications, equivalent substitutions, and improvements made within the spirit and scope of the present disclosure are intended to be included within the scope of the present disclosure.

Claims

1. A bracket, comprising: a base, wherein the base comprises: a base body; a suction cup provided at a bottom portion of the base body; and a connecting rod provided on the base body and connected to the suction cup; wherein the connecting rod is movable between a first position and a second position along its axial direction; when the connecting rod is moved from the second position to the first position along its axial direction, the connecting rod is configured for driving the suction cup to rise to form a vacuum negative pressure cavity; and when the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod is configured for driving the suction cup to descend to release vacuum negative pressure in the vacuum negative pressure cavity; wherein the base body is provided with a rotating member, the rotating member is rotatable relative to the base body; the base body is covered with a first cover body; and a swing groove is horizontally defined in the first cover body; the swing groove is parallel to a bottom surface of the suction cup; the rotating member is connected with a swing rod; an end portion of the swing rod passes through the swing groove and extends out of the first cover body; wherein a rotation angle of the rotating member is limited by two end groove walls of the swing groove.

2. The bracket according to claim 1, wherein the connecting rod is connected with a pin shaft; the base body is equipped with climbing tracks; the pin shaft cooperates with the climbing track to drive the connecting rod to move between the first position and the second position; a relative climbing motion of the pin shaft along the climbing track drives the connecting rod to move from the second position to the first position; and a relative descending motion of the pin shaft along the climbing track drives the connecting rod to move from the first position to the second position.

3. The bracket according to claim 2, wherein the climbing track is formed on the rotating member; an end portion of the pin shaft extends into the climbing track and performs the relative climbing motion or the relative descending motion relative to the climbing track with the rotation of the rotating member; the climbing track comprises a first position limiting point and a second position limiting point; and the first position limiting point is higher than the second position limiting point; a total number of the climbing tracks is two; the two climbing tracks are opposite to each other and are arranged at positions of a top portion of the rotating member.

4. The bracket according to claim 3, wherein the rotating member rotates relatively in a third position and a fourth position of the base body; the rotating member rotates relative to the base from the third position to the fourth position, driving the pin shaft to perform the relative climbing

motion from the second position limiting point of the climbing track to the first position limiting point, thereby driving the connecting rod to move from the second position to the first position; the rotating member rotates relative to the base body from the fourth position back to the third position, driving the pin shaft to perform the relative descending motion from the first position limiting point of the climbing track back to the second position limiting point, thereby driving the connecting rod to move from the first position to the second position.

5. The bracket according to claim 3, wherein the rotating member, the connecting rod, and the pin shaft are positioned inside the first cover body.

6. The bracket according to claim 3, wherein a top surface of the base body is provided with a first position limiting rod; a first arc-shaped position limiting groove is defined in the rotating member; and the first position limiting rod passes through the first arc-shaped position limiting groove and cooperates with two ends of the first arc-shaped position limiting groove for position limiting.

7. The bracket according to claim 3, wherein a restoration spring is sleeved on the connecting rod; one end of the restoration spring abuts against the suction cup; and an opposite end of the restoration spring abuts against the rotating member.

8. The bracket according to claim 3, wherein the base body is provided with a second cover body; the rotating member, the connecting rod, and the pin shaft are positioned inside the second cover body; and a connecting sleeve is provided in the second cover body; connecting convex blocks are provided on an outer wall of the rotating member; and connecting grooves engaged with the connecting convex blocks are defined in an inner wall of the connecting sleeve.

9. The bracket according to claim 8, wherein at least one second position limiting rod is provided on a top surface of the base body; the second cover body is provided with a second arc-shaped position limiting groove corresponding to the second position limiting rod; and the second position limiting rod passes through the second arc-shaped position limiting groove and cooperates with two ends of the second arc-shaped position limiting groove for position limiting.

10. The bracket according to claim 1, wherein a protrusion is provided at a bottom portion of the suction cup; the protrusion extends towards one side away from the base body; when the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod and the suction cup are driven to descend, the protrusion abuts against a suction surface of the suction cup, and the vacuum negative pressure in the vacuum negative pressure cavity between the suction cup and the suction surface is released, thus forming a disengaged state.

11. The bracket according to claim 10, wherein a height of the protrusion is higher than a height of the suction surface of the suction cup; a bottom portion of the base body is provided with a rim; and the rim corresponds to an outer peripheral edge of the suction cup.

12. The bracket according to claim 11, wherein the connecting rod is moved from a second position back to a first position along its axial direction, driving the connecting rod to lift and pull the suction cup connected to the connecting rod to deform upward; a first gap is defined between the protrusion and the suction surface of the suction cup; the rim presses against the outer peripheral edge of the suction cup; and the suction cup and the suction surface form a vacuum negative pressure cavity, thus forming a suction state; in the suction state, the rim is pressed against the outer peripheral edge of the suction cup; in the disengaged state, a second gap is defined between the rim and the suction cup, or the rim is in contact with the outer peripheral edge of the suction cup.

13. The bracket according to claim 10, wherein the protrusion is provided at a central position of the suction cup; a bottom portion of the connecting rod is provided with a protruding column; the protruding column is positioned inside the suction cup; and the protruding column is at least partially positioned below the suction cup.

14. The bracket according to claim 10, wherein the connecting rod and the suction cup are integrally formed; the suction cup is made of plastic or silicone material; and an area of the protrusion accounts for 2%-65% of an area of the suction cup.

15. The bracket according to claim 1, wherein a step is provided on the connecting rod; a plurality

of holes extending along an axial direction is defined in the step; a flexible body is accommodated in the hole; the suction cup cooperates to receive the step; and the flexible body inside the hole is integrally connected to the suction cup; when the connecting rod moves along its axial direction, the suction cup is pulled up to be deformed or lowered to be restored driven by the flexible body in the hole and the step.

16. The bracket according to claim 1, further comprising a support rod and a support main body, wherein the support main body is used for supporting a mobile phone; one end of the support rod is rotatably connected to the base; and an opposite end of the support rod is rotatably connected to the support main body.

17. The bracket according to claim 16, wherein the support rod comprises a first telescopic rod and a second telescopic rod; the first telescopic rod is sleeved on the second telescopic rod; the second telescopic rod is telescopic within the first telescopic rod; a magnetic attraction member is provided inside the support main body; and the magnetic attraction member is used for adhering an electronic device to the support main body.

18. The bracket according to claim 17, wherein an accommodating groove is defined in a bottom portion of the support main body; when the first telescopic rod is completely retracted relative to the second telescopic rod, the supporting rod is capable of being accommodated in the accommodating groove, and the support main body is capable of rotating to completely cover a top surface of the base.

19. A bracket, comprising: a base, wherein the base comprises: a base body; a suction cup provided at a bottom portion of the base body; and a connecting rod provided on the base body and connected to the suction cup; wherein the connecting rod is movable between a first position and a second position along its axial direction; when the connecting rod is moved from the second position to the first position along its axial direction, the connecting rod is configured for driving the suction cup to rise to form a vacuum negative pressure cavity; and when the connecting rod is moved from the first position to the second position along its axial direction, the connecting rod is configured for driving the suction cup to descend to release vacuum negative pressure in the vacuum negative pressure cavity; wherein the bracket further comprises a support rod and a support main body; the support rod comprises a first telescopic rod and a second telescopic rod; the first telescopic rod is sleeved on the second telescopic rod; the second telescopic rod is telescopic within the first telescopic rod; a magnetic attraction member is provided inside the support main body; and the magnetic attraction member is used for adhering an electronic device to the support main body.

20. The bracket according to claim 1, wherein the swing rod is perpendicular to the connecting rod.
