

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385436
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Davis; Todd A. et al.

Gas turbine engine front center body architecture

Abstract

A gas turbine engine includes a fan that has fan blades wherein the fan delivers airflow to a bypass duct. A gearbox is defined along an engine axis. A low spool is arranged aft of the gearbox and coupled to drive the gearbox. A front center body assembly is defined around the engine axis. A flexible support supports the gearbox relative to the front center body assembly. A bearing package is mounted to the front center body assembly and the low spool. A front wall is mounted to the front center body assembly. The front wall is removable from the front center body assembly to access at least one of the gearbox or the bearing package. The low spool includes a low pressure compressor hub that provides an engagement feature for engaging the bearing package.

Inventors:	Davis; Todd A. (Tolland, CT), Cigal; Brian P. (Windsor, CT)
Applicant:	RAYTHEON TECHNOLOGIES CORPORATION (Farmington, CT)
Family ID:	1000008748972
Assignee:	RTX CORPORATION (Farmington, CT)
Appl. No.:	18/142131
Filed:	May 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230272745 A1	Aug. 31, 2023

Related U.S. Application Data

continuation parent-doc US 16836001 20200331 US 11713713 child-doc US 18142131
continuation parent-doc US 13860774 20130411 US 10605167 20200331 child-doc US 16836001
continuation parent-doc US 13732647 20130102 US 8911204 20141216 child-doc US 13860774
continuation parent-doc US 13282919 20111027 US 8366385 20130205 child-doc US 13732647
continuation-in-part parent-doc US 13275286 20111017 ABANDONED child-doc US 13282919

Publication Classification

Int. Cl.: **F02C7/06** (20060101); **F01D15/12** (20060101); **F01D25/16** (20060101); **F01D25/28** (20060101); **F02C7/20** (20060101); **F02C7/36** (20060101); **F02K3/06** (20060101)

U.S. Cl.:

CPC **F02C7/06** (20130101); **F01D15/12** (20130101); **F01D25/162** (20130101); **F01D25/285** (20130101); **F02C7/20** (20130101); **F02C7/36** (20130101); **F02K3/06** (20130101); F05D2230/60 (20130101); F05D2230/70 (20130101); F05D2230/72 (20130101); F05D2230/80 (20130101); Y02T50/60 (20130101); Y10T29/49245 (20150115)

Field of Classification Search

CPC: F02C (7/06); F02C (7/20); F02C (7/36); F02K (3/06); Y10T (29/49245); F05D (2230/60); F05D (2230/72); F05D (2230/70); F05D (2230/80); F01D (5/12); F01D (25/16); F01D (25/162); F01D (25/285); B23P (6/002); B23P (6/005)

USPC: 415/189-190; 415/209.2-2; 415/214.1; 415/229-230; 415/122.1; 415/124.1; 416/174; 416/244A; 416/245R; 416/170R; 60/798; 29/889.1; 29/402.03; 29/426.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3909085	12/1974	Wilkinson	384/517	F16C 25/083
5622438	12/1996	Walsh	384/624	F01D 25/162
11713713	12/2022	Davis	29/888.025	F02C 7/36
2007/0084185	12/2006	Moniz	60/226.1	F02K 3/072
2008/0006018	12/2007	Sheridan	60/39.1	F02C 7/36
2009/0081039	12/2008	McCune	415/214.1	F02C 7/36
2010/0105516	12/2009	Sheridan	475/346	F16H 1/2827

Primary Examiner: Verdier; Christopher

Attorney, Agent or Firm: Carlson, Gaskey & Olds, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present disclosure is a continuation of U.S. patent application Ser. No. 16/836,001, filed Mar. 31, 2020, which is a continuation of U.S. patent application Ser. No. 13/860,774, filed Apr. 11, 2013, now granted U.S. Pat. No. 10,605,167 granted Mar. 31, 2020, which claims benefit of U.S. Provisional Application No. 61/789,224 filed Mar. 15, 2013 and is also a continuation of application Ser. No. 13/732,647, filed Jan. 2, 2013, now granted U.S. Pat. No. 8,911,204 granted Dec. 16, 2014, which is a

continuation of U.S. patent application Ser. No. 13/282,919, filed on Oct. 27, 2011, now granted U.S. Pat. No. 8,366,385 granted Feb. 5, 2013, which is a continuation-in-part application of U.S. patent application Ser. No. 13/087,579, filed 15 Apr. 2011, now abandoned, and of U.S. patent application Ser. No. 13/275,286, filed 17 Oct. 2011, now abandoned.

BACKGROUND

(1) The present disclosure relates to a gas turbine engine, and in particular, to a case structure therefor.

(2) Gas turbine engines typically include one or more rotor shafts that transfer power and rotary motion from a turbine section to a compressor section and fan section. The rotor shafts are supported within an engine static structure which is typically constructed of modules with individual case sections which are joined together at bolted flanges. The flanges form a joint capable of withstanding the variety of loads transmitted through the engine static structure. An ongoing issue for gas turbine engines is the ease and speed at which they can be serviced.

SUMMARY

(3) In one exemplary embodiment, a method for servicing a gas turbine engine includes disassembling a bearing compartment, providing access from a forward side of the gas turbine engine to a gearbox contained within said bearing compartment. The gas turbine engine provides a core flow path that extends from the forward side aftward in a core flow direction. The method includes servicing a component located within the bearing compartment.

(4) In a further embodiment of any of the above, disassembling the bearing compartment includes disassembling a front wall from a front center body support.

(5) In a further embodiment of any of the above, the method includes providing access from the forward side to a flex support mounted within the front center body support. The flex support is mounted to the gearbox.

(6) In a further embodiment of any of the above, the method includes disassembling a bearing package from the front center body support.

(7) In a further embodiment of any of the above, the method includes disassembling the front wall from an output shaft driven by the gearbox.

(8) In a further embodiment of any of the above, the step of disassembling includes removing as a module the gearbox by displacing the gearbox forward and away from said bearing compartment and a low spool.

(9) In a further embodiment of any of the above, the component servicing step includes servicing one of the gearbox, a bearing package and a seal package.

(10) In another exemplary embodiment, a method for servicing a gas turbine engine includes providing access from a forward side of a front center body assembly to a gearbox driven by a low spool, and servicing a component located within a bearing compartment aft of the front center body assembly.

(11) In a further embodiment of any of the above, the method includes disassembling a fan mounted to the gearbox.

(12) In a further embodiment of any of the above, the method includes removing first fasteners located within the forward side of the front center body assembly to disassemble a front wall from a front center body support of the front center body assembly.

(13) In a further embodiment of any of the above, the disassembling step includes removing a fan hub from an output shaft coupled to the gearbox. The fasteners removing step is performed subsequent to the fan hub removing step.

(14) In a further embodiment of any of the above, the forward side faces a fan.

(15) In a further embodiment of any of the above, the access providing step includes removing as a module the gearbox by displacing the gearbox forward and away from said bearing compartment and said low spool thereby exposing the component. The component servicing step includes

servicing one of a bearing package and a seal package.

(16) In another exemplary embodiment, a gas turbine engine includes a gearbox defined along an engine axis. A low spool is arranged aft of the gearbox and is operable to drive said gearbox. A front center body support is defined around the engine axis. A bearing package is mounted to the front center body support and the low spool. A seal package is located aft of the bearing package. A front wall is mounted to the front center body support. The front wall is removable from the front center body support to access at least one of the gearbox, the bearing package and the seal package.

(17) In a further embodiment of any of the above, the front center body support is defined about an engine longitudinal axis.

(18) In a further embodiment of any of the above, the seal package is mounted to the front center body support.

(19) In a further embodiment of any of the above, the front center body support includes a flange which abuts a flange of the front wall.

(20) In a further embodiment of any of the above, the gas turbine engine includes fasteners, which attach the flange of the front wall to the flange of the front center body support.

(21) In a further embodiment of any of the above, the fasteners are accessible from a forward side of the gas turbine engine.

(22) In a further embodiment of any of the above, the front wall supports a bearing structure to support an output shaft driven by the gearbox. The output shaft is operable to drive a fan.

(23) In a further embodiment of any of the above, the gearbox drives a fan section at a speed different than a speed of the low speed spool.

(24) In a further embodiment of any of the above, the front center body support provides a unitary component with a front center body section having a vane arranged in an annular core path and that at least partially defines a core flow path.

(25) In a further embodiment of any of the above, the front center body support and the front center body section are integral with one another.

(26) In a further embodiment of any of the above, the front center body support and the front center body section are welded to one another.

(27) In a further embodiment of any of the above, the gas turbine engine includes a coupling shaft interconnecting and splined to each of the gearbox and the coupling shaft section.

(28) In a further embodiment of any of the above, the low spool includes a low pressure compressor hub providing a spline engageable with the bearing package. The seal package is mounted to the low pressure compressor hub.

(29) In one exemplary embodiment, a gas turbine engine is configured to include a propulsor section having a fan drive geared architecture. The engine includes a gas generator section that includes a compressor section having a first rotor rotationally mounted to a first spool. Further included is a bearing package rotationally supporting the first spool. The bearing package supports the first spool during at least one of (1) a period prior to installation of the fan drive geared architecture into the engine and (2) a period after removal of the fan drive geared architecture from the engine.

(30) In a further embodiment of any of the above, the first spool is a low spool of the engine.

(31) In a further embodiment of any of the above, the fan drive geared architecture drives a fan section at a speed different than a speed of the low spool.

(32) In a further embodiment of any of the above, a front center body support is defined around an engine longitudinal axis.

(33) In a further embodiment of any of the above, the bearing package is mounted to the front center body support and the low spool.

(34) In a further embodiment of any of the above, an engine static structure is included.

(35) In a further embodiment of any of the above, the bearing package is adapted for rotationally supporting the first spool against the static structure.

- (36) Another exemplary embodiment includes a method of supporting a first rotor of a gas turbine engine. The engine is configured to include a propulsor section having a fan drive geared architecture. The engine further includes a gas generator section that includes a compressor section having a first rotor rotationally mounted to a first spool, an engine static structure, and a bearing package adapted for rotationally supporting the first spool against the engine static structure. The method includes supporting the first rotor with the bearing package during at least one of (1) a period prior to installation of the fan drive geared architecture into the engine and (2) a period after removal of the fan drive geared architecture from the engine.
- (37) In a further embodiment of any of the above, the compressor section includes a low pressure compressor.
- (38) In a further embodiment of any of the above, the bearing package supports the first rotor during each of (1) before the fan drive geared architecture into the engine and (2) after the fan drive geared architecture is removed from the engine.
- (39) In a further embodiment of any of the above, the fan drive geared architecture includes a gearbox.
- (40) In a further embodiment of any of the above, the bearing package supports a low rotor of the engine.
- (41) In a further embodiment of any of the above, the geared architecture is serviced while removed from the engine.
- (42) Another exemplary embodiment of a method of partially disassembling a gas turbine engine. The engine includes a propulsor section having a fan drive geared architecture, a gas generator section that includes a compressor section having a first rotor rotationally mounted to a first spool, an engine static structure, and a bearing package adapted for rotationally supporting the first spool relative to the static structure. The method includes removing the propulsor section without otherwise supporting the first rotor, whereby the bearing package disposed within the engine supports the first rotor.
- (43) In a further embodiment of any of the above, the compressor section includes a low pressure compressor.
- (44) In a further embodiment of any of the above, the bearing package is provided in a bearing compartment of the engine.
- (45) In a further embodiment of any of the above, the geared architecture includes a gearbox.
- (46) In a further embodiment of any of the above, the first rotor is the low rotor of the engine.
- (47) In a further embodiment of any of the above, the geared architecture is serviced while removed from the engine.
- (48) In a further embodiment of any of the above, the bearing package is adapted for rotationally supporting the first spool against the static structure.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Various features will become apparent to those skilled in the art from the following detailed description of the disclosed non-limiting embodiment. The drawings that accompany the detailed description can be briefly described as follows:
- (2) FIG. 1 is a schematic cross-section of an embodiment of a gas turbine engine;
- (3) FIG. 2 is an enlarged cross-section of a portion of the gas turbine engine which illustrates a front center body assembly;
- (4) FIG. 3 is an enlarged cross-section of the geared architecture of the gas turbine engine;
- (5) FIG. 4 is an exploded perspective view of a front center body assembly;
- (6) FIG. 5 is an enlarged perspective partial cross-section of a front center body support of the front

- center body assembly;
- (7) FIG. 6 is an enlarged sectional view of the front center body support;
- (8) FIG. 7 is an exploded view of the front center body support; and
- (9) FIG. 8 is a schematic view of a forward gearbox removal from the gas turbine engine.

DETAILED DESCRIPTION

(10) FIG. 1 schematically illustrates a gas turbine engine 20. The gas turbine engine 20 is disclosed herein as a two-spool turboprop that generally incorporates a propulsor section that includes a fan section 22, and a gas generator section that includes a compressor section 24, a combustor section 26 and a turbine section 28. Alternative engines might include an augmentor section (not shown) among other systems or features. The fan section 22 drives air along a bypass flowpath while the compressor section 24 drives air along a core flowpath for compression and communication into the combustor section 26 then expansion through the turbine section 28. Although depicted as a turbo gas turbine engine in the disclosed non-limiting embodiment, it should be understood that the concepts described herein are not limited to use with turboprops as the teachings may be applied to other types of turbine engines.

(11) The engine 20 generally includes a low spool 30 and a high spool 32 mounted for rotation about an engine central longitudinal axis A relative to an engine static structure 36 via several bearing supports 38. The low spool 30 generally includes an inner shaft 40 that interconnects a fan 42, a low pressure compressor 44 and a low pressure turbine 46. The inner shaft 40 drives the fan 42 through a geared architecture 48 to drive the fan 42 at a lower speed than the low spool 30. For purposes of relating to the disclosed embodiments, the geared architecture is considered part of the propulsor section. The high spool 32 includes an outer shaft 50 that interconnects a high pressure compressor 52 and high pressure turbine 54. A combustor 56 is arranged between the high pressure compressor 52 and the high pressure turbine 54. The inner shaft 40 and the outer shaft 50 are concentric and rotate about the engine central longitudinal axis A which is collinear with their longitudinal axes.

(12) Core airflow is compressed by the low pressure compressor 44 then the high pressure compressor 52, mixed with the fuel and burned in the combustor 56, then expanded over the high pressure turbine 54 and low pressure turbine 46. The turbines 54, 46 rotationally drive the respective low spool 30 and high spool 32 in response to the expansion.

(13) The main engine shafts 40, 50 are supported at a plurality of points by the bearing system 38 within the static structure 36. In one non-limiting embodiment, bearing system 38 includes a #2 bearing support 38A located within the compressor section 24.

(14) With reference to FIG. 2, the engine static structure 36 proximate the compressor section 24 includes a front center body assembly 60 adjacent a #2 bearing support 38A. The front center body assembly 60 generally includes a front center body support 62. The #2 bearing support 38A generally includes a seal package 64, a bearing package 66, a flex support 68 and a centering spring 70.

(15) With reference to FIG. 3, the flex support 68 provides a flexible attachment of the geared architecture 48 within the front center body support 62 (also illustrated in FIG. 4). The flex support 68 reacts the torsional loads from the geared architecture 48 and facilitates vibration absorption as well as other support functions. The centering spring 70 is a generally cylindrical cage-like structural component with a multiple of beams which extend between flange end structures (also illustrated in FIG. 4). The centering spring 70 resiliently positions the bearing package 66 with respect to the low spool 30. In one embodiment, the beams are double-tapered beams arrayed circumferentially to control a radial spring rate that may be selected based on a plurality of considerations including, but not limited to, bearing loading, bearing life, rotor dynamics, and rotor deflection considerations.

(16) The front center body support 62 includes a front center body section 72 and a bearing section 74 defined about axis A with a frusto-conical interface section 76 therebetween (FIG. 5). The front

center body section **72** at least partially defines the core flowpath into the low pressure compressor **44**. The front center body section **72** includes an annular core passage with a multiple of front center body vanes **72A**, **72B**. The bearing section **74** is defined radially inward of the front center body section **72**. The bearing section **74** locates the bearing package **66** and the seal package **64** with respect to the low spool **30**. The frustro-conical interface section **76** combines the front center body section **72** and the bearing section **74** to form a unified load path, substantially free of kinks typical of a conventional flange joint, from the bearing package **66** to the outer periphery of the engine static structure **36**. The frustro-conical interface section **76** may include a weld **W** (FIG. 5) or, alternatively, be an integral section such that the front center body support **62** is a unitary component.

(17) The integral, flange-less arrangement of the frustro-conical interface section **76** facilitates a light weight, reduced part count architecture with an increased ability to tune the overall stiffness and achieve rotor dynamic requirements. Such an architecture also further integrates functions such as oil and air delivery within the bearing compartment which surrounds bearing package **66**.

(18) With reference to FIG. 6, the front center body support **62** includes mount features to receive the flex support **68**. In one disclosed non-limiting embodiment, the mount features of the front center body support **62** includes an internal spline **78** and a radial inward directed fastener flange **80** on the front center body section **72**. The flex support **68** includes a corresponding outer spline **82** and radially outwardly directed fastener flange **84**. The flex support **68** is received into the front center body support **62** at a splined interface **86** formed by splines **78**, **82** and retained therein such that fastener flange **84** abuts fastener flange **80**. A set of fasteners **88** such as bolts are threaded into the fastener flanges **80**, **84** to mount the flex support **68** within the front center body support **62**.

(19) With reference to FIG. 7, the fasteners **88** are directed forward to provide access from a forward section of the front center body assembly **60** opposite the bearing package **66** of the number two bearing system **38A**. The fasteners **88** are thereby readily removed to access a gearbox **90** of the geared architecture **48**.

(20) A front wall **102** aft of the fan **42** is mounted to a forward section of the front center body support **62** to provide access to the geared architecture **48** from the front of the engine **20**. The front wall **102** includes a flange **103** mountable to the front center body support **62** at the flange **60** by a multiple of fasteners **105**, which fasteners **105** may in one non-limiting embodiment be bolts. The front wall **102** and the front center body support **62** define a bearing compartment **100** (also shown in FIG. 2) which mounts to the bearing package **66**. The front wall **102** is removable such that the gearbox **90** may be accessed as a module. The gearbox **90** may thereby be accessed to facilitate rapid on-wing service.

(21) It should be appreciated that various bearing structures **104** (illustrated schematically and in FIG. 2) and seals **106** (illustrated schematically and in FIG. 2) may be supported by the front wall **102** to contain oil and support rotation of an output shaft **108**. The output shaft **108** connects with the geared architecture **48** to drive the fan **42**. Fan blades **42B** extend from a fan hub **110** which are mounted to the output shaft **108** for rotation therewith. It should be appreciated that the bearing structures **104** and seals **106** may, in the disclosed non-limiting embodiment may be disassembled with the front wall **102** as a unit after removal of the fan hub **110**.

(22) The gearbox **90** is driven by the low spool **30** (FIG. 1) through a coupling shaft **112**. The coupling shaft **112** transfers torque through the bearing package **66** to the gearbox **90** as well as facilitates the segregation of vibrations and other transients. The coupling shaft **112** generally includes a forward coupling shaft section **114** and an aft coupling shaft section **116** which extends from the bearing package **66**. The forward coupling shaft section **114** includes an interface spline **118** which mates with an aft spline **120** of the aft coupling shaft section **116**. An interface spline **122** of the aft coupling shaft section **116** connects the coupling shaft **112** to the low spool **30** through, in this non limiting embodiment, splined engagement with a spline **124** on a low pressure compressor hub **126** of the low pressure compressor **44**. In the implementation of FIGS. 3 and 7,

the low pressure (e.g., first) compressor **44** includes the compressor hub **126** and a disk **127** extending from the compressor hub **126** to support a plurality of compressor blades **45**. The bearing package **66** engages the compressor hub **126** at a position forward of the disk **127** relative to the engine longitudinal axis A (see also FIG. 3).

(23) To remove the gearbox **90**, the fan hub **110** is disassembled from the output shaft **108**. The multiple of fasteners **105** are then removed such that the front wall **102** is disconnected from the front center body support **62**. The multiple of fasteners **88** are then removed from the front of the engine **20**. The geared architecture **48** is then slid forward out of the front center body support **62** such that the interface spline **118** is slid off the aft spline **120** and the outer spline **82** is slid off the internal spline **78**. The geared architecture **48** is thereby removable from the engine **20** as a module (FIG. 8; illustrated schematically). It should be appreciated that other componentry may need to be disassembled to remove the geared architecture **48** from the engine **20**, however, such disassembly is relatively minor and need not be discussed in detail. It should be further appreciated that other components such as the bearing package **66** and seal **64** are also now readily accessible from the front of the engine **20**.

(24) Removal of the gearbox **90** from the front of the engine **20** as disclosed saves significant time and expense. The geared architecture **48**, is removable from the engine **20** as a module and does not need to be further disassembled. Moreover, although the geared architecture **48** must be removed from the engine to gain access to the bearing package **66** and the seal **64**, the geared architecture **48** does not need to be removed from the engine **20** to gain access to the engine core itself. Further, as one would appreciate from the above, in an example where a portion of the geared architecture **48** itself requires service, the bearing package **66** can remain in place to support the low spool **30**, and in turn a low rotor, of the gas turbine engine **20** while the geared architecture **48** is removed for service.

(25) It should be understood that like reference numerals identify corresponding or similar elements throughout the several drawings. It should also be understood that although a particular component arrangement is disclosed in the illustrated embodiment, other arrangements will benefit herefrom.

(26) Although particular step sequences are shown, described, and claimed, it should be understood that steps may be performed in any order, separated or combined unless otherwise indicated and will still benefit from the present invention.

(27) Although the different examples have the specific components shown in the illustrations, embodiments of this disclosure are not limited to those particular combinations. It is possible to use some of the components or features from one of the examples in combination with features or components from another one of the examples.

(28) One of ordinary skill in this art would understand that the above-described embodiments are exemplary and non-limiting. That is, modifications of this disclosure would come within the scope of the claims. Accordingly, the following claims should be studied to determine their true scope and content.

Claims

1. A gas turbine engine comprising: a propulsor including a plurality of blades; a geared architecture including a gearbox; a first spool including a first shaft interconnecting a first turbine and a first compressor, and the first compressor includes a compressor hub and a disk extending from the compressor hub to support a plurality of compressor blades; a front center body assembly defined around an engine longitudinal axis, wherein the front center body assembly defines a portion of a core flow path through the gas turbine engine that is upstream of an inlet to the first compressor; a flex support that supports the gearbox relative to the front center body assembly; a bearing support including a bearing package mounted to the front center body assembly and the

first spool, wherein the bearing package engages the compressor hub at a position forward of the disk relative to the engine longitudinal axis; a front wall mounted to the front center body assembly; and wherein the front wall is removable from the front center body assembly to access at least one of the gearbox or the bearing package.

2. The gas turbine engine as recited in claim 1, wherein the flex support establishes a flexible attachment of the geared architecture within a front center body support of the front center body assembly, and the flex support is configured to react torsional loads from the geared architecture.
3. The gas turbine engine as recited in claim 2, wherein the gearbox is axially aligned with the front center body support relative to the engine longitudinal axis.
4. The gas turbine engine as recited in claim 2, wherein the geared architecture is removeable from the gas turbine engine as a module.
5. The gas turbine engine as recited in claim 2, wherein the bearing package is axially aft of the flex support relative to the engine longitudinal axis.
6. The gas turbine engine as recited in claim 4, wherein the front wall supports a front bearing structure positioned along a periphery of an output shaft, and the output shaft interconnects the geared architecture and the propulsor.
7. The gas turbine engine as recited in claim 4, wherein: the front wall and the front center body support establish a bearing compartment; the front center body support includes a front center body section, a bearing section and an interface section that interconnects the front center body section and the bearing section; and the front center body section includes an annular flow path that establishes the portion of the core flow path, and an array of vanes are circumferentially distributed in the annular flow path.
8. The gas turbine engine as recited in claim 7, wherein the interface section has a frustro-conical geometry that flairs radially outwardly from the bearing section towards the front center body section.
9. The gas turbine engine as recited in claim 7, further comprising: a centering spring that resiliently positions the bearing package with respect to the first spool.
10. The gas turbine engine as recited in claim 7, wherein: the geared architecture is removable from the gas turbine engine in response to sliding the geared architecture in a forward direction out of the front center body support relative to the engine longitudinal axis.
11. The gas turbine engine as recited in claim 10, wherein the bearing package engages the compressor hub to establish a first splined interface.
12. The gas turbine engine as recited in claim 10, wherein the flex support disengages the front center body support in response to sliding the geared architecture in the forward direction.
13. The gas turbine engine as recited in claim 12, wherein the flex support engages the front center body support to establish a second splined interface.
14. The gas turbine engine as recited in claim 10, wherein the bearing support includes a seal package positioned aft of the bearing package relative to the engine longitudinal axis, and the seal package is mounted to the bearing section of the front center body assembly.
15. The gas turbine engine as recited in claim 10, further comprising: a centering spring that resiliently positions the bearing package with respect to the first spool; and wherein the centering spring includes an array of beams circumferentially distributed about the engine longitudinal axis.
16. The gas turbine engine as recited in claim 10, further comprising: a coupling shaft interconnecting the gearbox and the bearing package; and wherein the first spool drives the gearbox through the coupling shaft, and the coupling shaft facilitates segregation of vibrations.
17. The gas turbine engine as recited in claim 16, wherein: the coupling shaft engages the bearing package to establish a third splined interface.
18. The gas turbine engine as recited in claim 10, wherein the front center body support includes a first flange that abuts a flange of the front wall, and a plurality of fasteners attach the first flange of the front wall to the flange of the front center body support.

19. The gas turbine engine as recited in claim 18, wherein the fasteners are accessible from a forward side of the gas turbine engine relative to the engine longitudinal axis.

20. The gas turbine engine as recited in claim 18, wherein the flex support includes a flange that abuts a second flange of the front center body support, and a plurality of fasteners attach the flange of the flex support to the second flange of the front center body support.

21. The gas turbine engine as recited in claim 10, wherein the propulsor is a fan, and an outer housing surrounds the fan to establish a bypass duct.
