

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383953
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lee; Chanul et al.

Casting mold device

Abstract

A casting mold device includes a lower die and an upper die capable of being attached to or detached from the lower die and is configured to produce a cylinder head having spark plug mounting portions. In particular, the casting mold device includes: i) a plurality of core pin assemblies mounted in the upper die to form the spark plug mounting portions and having cooling air flow paths formed therein, ii) a cooling unit installed on the upper die and including cooling air inlet portions and cooling air outlet portions respectively connected to the cooling air flow paths of the core pin assemblies, and iii) a sealing unit coupled to the cooling unit and the upper die to seal portions between the core pin assemblies and the cooling unit.

Inventors: Lee; Chanul (Ulsan, KR), Kim; Si Young (Ulsan, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Family ID: 1000008749972

Assignee: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Appl. No.: 18/747052

Filed: June 18, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250091123 A1	Mar. 20, 2025

Foreign Application Priority Data

KR	10-2023-0123694	Sep. 18, 2023
----	-----------------	---------------

Publication Classification

Int. Cl.: B22D17/22 (20060101); B22D17/24 (20060101)

U.S. Cl.:

CPC B22D17/2218 (20130101); B22D17/2227 (20130101); B22D17/24 (20130101);

Field of Classification Search

CPC: B22D (17/2218); B22D (17/2227); B22D (17/24); B22D (25/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0250186	12/2008	Kwak	164/253	B22D 25/06

Primary Examiner: Kerns; Kevin P

Assistant Examiner: Ha; Steven S

Attorney, Agent or Firm: Lempia Summerfield Katz LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to and the benefit of Korean Patent Application No. 10-2023-0123694, filed in the Korean Intellectual Property Office on Sep. 18, 2023, the entire contents of which are incorporated herein by reference.

BACKGROUND

- (a) Field
- (2) Embodiments of the present disclosure relate to a casting mold device, and more particularly, to a casting mold device capable of producing an engine component for a vehicle.
- (b) Description of the Related Art
- (3) In general, a casting process method refers to a manufacturing process for producing a product with a predetermined shape by injecting molten metal into a casting mold and changing a phase of the molten metal into a solid state (e.g., solidifying the molten metal). For example, components for a vehicle engine, such as a cylinder head, may be manufactured by a high-pressure or low-pressure casting process using molten aluminum.
- (4) Examples of the casting process may include a low-pressure casting process that pushes molten metal upward to a portion between an upper die and a lower die along a stalk by using low-pressure compressed air from a heat retention furnace disposed below a casting mold and then solidifies the molten metal.
- (5) The casting mold device, which produces a cylinder head by using the low-pressure casting process, is equipped with a core pin provided in the upper die to form a spark plug mounting hole in the cylinder head. The core pin is mounted in an upper forming part of the upper die.
- (6) In addition, the casting mold device is equipped with a cooling unit configured to cool the core pin by allowing a cooling medium to flow around the core pin during a casting process.
- (7) In this case, the cooling unit may cool the core pin using the cooling medium as a coolant and

allow the coolant to flow around the core pin.

(8) However, in case that the coolant is used, the core pin may be overcooled, which may degrade quality of a cylinder head product. In addition, the coolant may leak from the core pin, which may cause a safety accident during the casting process.

(9) Therefore, a cooling unit, which uses cooling air as the cooling medium and allows the cooling air to flow around the core pin, is applied.

(10) However, in order to simplify the structure, the casting mold device, which adopts the air-cooled cooling unit, does not have a separate discharge structure configured to discharge cooling air, and the casting mold device discharges the cooling air through a gap between the cooling unit and the core pin.

(11) Therefore, because the cooling air is discharged through the gap between the cooling unit and the core pin, exhaust noise may occur. This exhaust noise may degrade a working environment of an operator, such as causing hearing impairment of the operator.

(12) Furthermore, the core pin, to which the air-cooled cooling unit is applied, is configured as an integrated type. Because the core pin is in contact with molten metal over a long period of time, the core pin is damaged even though the core pin is cooled, and for this reason, an excessive amount of costs may be required to replace the core pin.

(13) The above information disclosed in this background section is provided only to enhance understanding of the background of the present disclosure and therefore it may contain information that does not form the prior art that is already known to a person of ordinary skill in the art.

SUMMARY

(14) The present disclosure provides a casting mold device capable of minimizing exhaust noise of cooling air generated when a core pin is cooled by cooling air.

(15) An embodiment of the disclosed present disclosure provides a casting mold device configured to produce a cylinder head having spark plug mounting portions. The casting mold device includes: a lower die and an upper die capable of being attached to or detached from the lower die. The casting mold device further includes: i) a plurality of core pin assemblies mounted in the upper die to form the spark plug mounting portions and having cooling air flow paths formed therein, ii) a cooling unit installed on the upper die and including cooling air inlet portions and cooling air outlet portions respectively connected to the cooling air flow paths of the core pin assemblies, and iii) a sealing unit coupled to the cooling unit and the upper die to seal portions between the core pin assemblies and the cooling unit.

(16) In another embodiment, the cooling unit may include a cooling air discharge module connected to the cooling air outlet portions.

(17) In an embodiment of the present disclosure, the sealing unit may include: a sealing plate disposed between the core pin assemblies and the cooling unit; and a plurality of sealing fastening members configured to fasten the cooling unit and the sealing plate and fasten the sealing plate and the upper die.

(18) Another embodiment of the disclosed present disclosure provides a casting mold device that includes a lower die and an upper die capable of being attached to or detached from the lower die. The casting mold device further includes: a plurality of core pin assemblies mounted in the upper die and including a plurality of separating pins capable of being coupled to or separated from one another. In particular, the plurality of core pin assemblies includes cooling air flow paths formed in the separating pins coupled to one another. The casting mold device further includes: a cooling unit installed on the upper die and connected to the cooling air flow paths so as to inject and discharge cooling air; and a sealing unit coupled to the cooling unit and the upper die to seal portions between the core pin assemblies and the cooling unit.

(19) In another embodiment of the present disclosure, the core pin assemblies may be respectively mounted in pin insertion holes formed in the upper die in an upward/downward direction to form spark plug mounting portions of a cylinder head.

- (20) In other embodiment of the present disclosure, the separating pins may each include: a cylindrical plug casing fitted with a pin insertion hole formed in the upper die in an upward/downward direction. In particular, the cylindrical plug casing is opened at upper and lower ends thereof. The separating pins may each include: a plug pin fitted with the plug casing, coupled to a lower portion of the cylindrical plug casing, opened at an upper end thereof, and closed at a lower end thereof; and a plug bushing fitted with the plug casing so as to be positioned above the plug pin, coupled to an upper portion of the cylindrical plug casing, and having a cylindrical shape opened at upper and lower ends thereof.
- (21) In an embodiment of the present disclosure, the cylindrical plug casing may include a casing outer flange formed on an outer periphery of an upper end thereof, and a casing inner flange formed on an inner periphery of a lower end thereof.
- (22) In an embodiment of the present disclosure, the plug bushing may include a bushing outer flange formed on an outer periphery of an upper end thereof.
- (23) In an embodiment of the present disclosure, the casing outer flange and the bushing outer flange may be fastened by a plurality of bolts.
- (24) In an embodiment of the present disclosure, the casing inner flange may be coupled to a pin outer flange formed at an upper end of the plug pin by means of a locking projection.
- (25) In another embodiment of the present disclosure, the cooling unit may include: a plurality of head blocks disposed at positions corresponding to the core pin assemblies and respectively having cooling air inlet portions and cooling air outlet portions; cooling pipes connected to the cooling air inlet portions of the head blocks and disposed in the cooling air flow paths; and a cooling air discharge module connected to the cooling air outlet portions of the head blocks.
- (26) In an embodiment of the present disclosure, the cooling unit may include cooling air inlet pipes each connected to one side of each of the cooling air inlet portions of the head blocks.
- (27) In an embodiment of the present disclosure, the cooling pipes may each be connected to the other side of each of the cooling air inlet portions by tapping.
- (28) In an embodiment of the present disclosure, the cooling air discharge module may include: a connection pipe connected to the cooling air outlet portions of the head blocks; an air discharge housing connected to the connection pipe; and an air discharge pipe connected to the air discharge housing.
- (29) In an embodiment of the present disclosure, the air discharge pipe may extend toward one side edge of an upper holder coupled to the upper die.
- (30) In an embodiment of the present disclosure, the cooling air flow paths may include a flow path groove formed in the plug pin, and a hollow portion of the plug bushing connected to the flow path groove.
- (31) In an embodiment of the present disclosure, the cooling unit may include: a plurality of head blocks disposed at positions respectively corresponding to the core pin assemblies and respectively having cooling air inlet portions and cooling air outlet portions; and cooling pipes connected to the cooling air inlet portions of the head blocks and disposed in the plug bushing and the plug pin.
- (32) In an embodiment of the present disclosure, at least one cooling air flow path of the cooling air flow paths may include a cooling air discharge flow path formed between an outer periphery of the cooling pipe, an inner periphery of the plug bushing, and an inner periphery of the plug pin. The cooling air discharge flow path is connected to the cooling pipe and the cooling air outlet portion.
- (33) In an embodiment of the present disclosure, the sealing unit may include: a sealing plate disposed between the core pin assemblies and the head block; and a plurality of sealing fastening members configured to fasten the head blocks and the sealing plate and fasten the sealing plate and the upper die.
- (34) In an embodiment of the present disclosure, the sealing fastening members may respectively include sealing fastening bolts.
- (35) According to the casting mold device according to the embodiment of the present disclosure, it

is possible to minimize exhaust noise of the cooling air used to cool the core pin assemblies, thereby improving the working environment of the operator while preventing hearing impairment of the operator.

(36) Other effects, which may be obtained or expected by the embodiments of the present disclosure, should be directly or implicitly disclosed in the detailed description on the embodiments of the present disclosure. In other words, various effects expected according to the embodiments of the present disclosure are disclosed in the detailed description below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Because the drawings are provided for reference to describe embodiments of the present disclosure, the technical spirit of the present disclosure should not be construed as being limited to the accompanying drawings.
- (2) FIG. 1 is a block configuration view schematically illustrating a casting mold device according to an embodiment of the present disclosure.
- (3) FIG. 2 is a view schematically illustrating an example of a cylinder head produced by the casting mold device according to the embodiment of the present disclosure.
- (4) FIG. 3 is a perspective view illustrating the casting mold device according to an embodiment of the present disclosure.
- (5) FIG. 4 is a top plan view illustrating the casting mold device according to the embodiment of the present disclosure.
- (6) FIG. 5 is an exploded perspective view illustrating the casting mold device according to the embodiment of the present disclosure.
- (7) FIG. 6 is a cross-sectional view illustrating the casting mold device according to the embodiment of the present disclosure.
- (8) FIG. 7 is a perspective view and a cross-sectional view illustrating a core pin assembly applied to the casting mold device according to an embodiment of the present disclosure.
- (9) FIG. 8 is an exploded perspective view illustrating the core pin assembly applied to the casting mold device according to an embodiment of the present disclosure.
- (10) FIG. 9 is a perspective view illustrating a cooling unit applied to the casting mold device according to an embodiment of the present disclosure.
- (11) FIG. 10 is a cross-sectional view illustrating the cooling unit applied to the casting mold device according to the embodiment of the present disclosure.
- (12) FIGS. 11 and 12 are views illustrating a sealing unit applied to the casting mold device according to the embodiment of the present disclosure.
- (13) FIG. 13 is a view illustrating an operation of the casting mold device according to an embodiment of the present disclosure.
- (14) It should be understood that the accompanying drawings are not necessarily to scale, but provide a somewhat simplified representation of various features that exemplify the basic principles of the present disclosure. For example, specific design features of the present disclosure, including particular dimensions, directions, positions, and shapes, should be partially determined by the particularly intended application and use environment.

DETAILED DESCRIPTION

- (15) Hereinafter, embodiments of the present disclosure are described in detail with reference to the accompanying drawings so that those with ordinary skill in the art to which the present disclosure pertains may easily carry out the embodiments. However, the present disclosure may be implemented in various different ways and is not limited to the embodiments described herein.
- (16) A part irrelevant to the description has been omitted to clearly describe the present disclosure,

and the same or similar constituent elements are designated by the same reference numerals throughout the specification.

(17) The size and thickness of each component illustrated in the drawings are arbitrarily shown for ease of description, but the present disclosure is not necessarily limited thereto. In order to clearly describe several portions and regions, thicknesses thereof are enlarged.

(18) In addition, the term “unit,” “part,” “member”, or the like, which is described in the specification, means a unit of a comprehensive configuration that performs at least one function or operation.

(19) When a component, device, element, or the like of the present disclosure is described as having a purpose or performing an operation, function, or the like, the component, device, or element should be considered herein as being “configured to” meet that purpose or to perform that operation or function.

(20) The terms used in the present specification are for explaining the exemplary embodiments, not for limiting the present disclosure. The singular expressions used herein are intended to include the plural expressions unless the context clearly dictates otherwise.

(21) It is to be understood that the term “comprise (include)” and/or “comprising (including)” used in the present specification means that the features, the integers, the steps, the operations, the constituent elements, and/or component are present, but the presence or addition of one or more of other features, integers, steps, operations, constituent elements, components, and/or groups thereof is not excluded.

(22) The term ‘coupled’ used in the present specification indicates a physical relationship between two components that are connected directly to each other or connected indirectly through one or more intermediate components.

(23) Hereinafter, embodiments of the present disclosure are described in detail with reference to the accompanying drawings.

(24) FIG. 1 is a block configuration view schematically illustrating a casting mold device according to an embodiment of the present disclosure.

(25) With reference to FIG. 1, a casting mold device **100** according to an embodiment of the present disclosure may be applied to a process of manufacturing a casting product with a desired shape by injecting molten metal, which is made of aluminum, magnesium, or an alloy thereof, into a die.

(26) According to an embodiment of the present disclosure, the casting mold device **100** may be applied to a process of manufacturing components for a vehicle engine by using a casting process.

(27) Furthermore, the casting mold device **100** according to the embodiment of the present disclosure may be applied to a process of manufacturing a cylinder head for a vehicle engine by using a low-pressure casting process.

(28) In this case, as illustrated in FIG. 2, a cylinder head **1**, which is produced by the casting mold device **100**, includes spark plug mounting portions **3** provided in the form of holes in which a plurality of spark plugs (not illustrated) is mounted.

(29) Therefore, the casting mold device **100** according to the embodiment of the present disclosure is configured to produce the cylinder head **1** having the spark plug mounting portions **3**.

(30) In the present specification, reference directions for explaining the following components may be set as a forward/rearward direction, a leftward/rightward direction, and an upward/downward direction.

(31) Further, in the present specification, the terms ‘upper end portion,’ ‘upper portion,’ ‘upper end’ or ‘upper surface’ of a component means an end portion, a portion, an end, or a surface of the component which is disposed at a relative upper side, and the terms ‘lower end portion,’ ‘lower portion,’ ‘lower end,’ or ‘lower surface’ of a component means an end portion, a portion, an end, or a surface of the component which is disposed at a relatively lower side.

(32) In addition, in the present specification, an end (e.g., one end or the other end) of a component

means an end of the component in any one direction, and an end portion (e.g., one end portion or the other end portion) of a component means a predetermined portion of the component that includes the end of the component.

(33) With reference to FIGS. **1** and **2**, the casting mold device **100** according to the embodiment of the present disclosure basically includes a lower die **10** and an upper die **20**.

(34) The lower die **10** is disposed on a floor of a process workplace and mounted on a lower holder **11**. The lower die **10** includes a molten metal injection part **13** and a lower forming part **15**.

(35) The molten metal injection part **13** is provided below the lower forming part **15**. The molten metal injection part **13** is connected to a heat retention furnace **17** disposed below the lower holder **11**.

(36) The heat retention furnace **17** may accommodate molten metal **5**, push the molten metal **5** upward by using low-pressure compressed air, and inject the molten metal **5** into the molten metal injection part **13**. A method of injecting the molten metal **5** into the molten metal injection part **13** with low pressure may be defined as a low-pressure casting process.

(37) The lower forming part **15** is provided at an upper side of the lower die and has a shape corresponding to a lower shape of the cylinder head **1**. The lower forming part **15** may be connected to the molten metal injection part **13**.

(38) Further, the upper die **20** is installed at a position corresponding to the lower die **10** and configured to be movable in the upward/downward direction. The upper die **20** is mounted on an upper holder **21** and configured to be attached to or detached from the lower die **10**.

(39) The upper die **20** may be reciprocated in the upward/downward direction by a drive device, such as a drive slider, known to those having ordinary skill in the art.

(40) The upper die **20** includes an upper forming part **25**. The upper forming part **25** is provided at a lower side of the upper die **20** and has a shape corresponding to an upper shape of the cylinder head **1**.

(41) Therefore, according to the casting mold device **100** according to the embodiment of the present disclosure, when the lower die **10** and the upper die are attached to each other, the lower forming part **15** and the upper forming part **25** may define a cavity **7** with a preset shape and volume.

(42) Therefore, in the casting mold device **100** according to the embodiment of the present disclosure, when the molten metal **5** is injected into the cavity **7** through the molten metal injection part **13**, the cylinder head **1** with a preset shape may be produced by the lower forming part **15** and the upper forming part **25**.

(43) According to the embodiment of the present disclosure, the casting mold device **100** includes a pin-type core structure configured to form the spark plug mounting portions **3** in the form of holes in the cylinder head **1**. In another embodiment, the casting mold device **100** includes a cooling structure configured to cool the pin-type core structure.

(44) In this case, the cooling structure is configured to cool the pin-type core structure by using cooling air. The cooling structure may cool the pin-type core structure by allowing the cooling air to flow to the pin-type core structure.

(45) The casting mold device **100** according to the embodiment of the present disclosure minimizes exhaust noise of the cooling air generated when the pin-type core structure is cooled by the cooling air.

(46) FIG. **3** is a perspective view illustrating the casting mold device according to the embodiment of the present disclosure, FIG. **4** is a top plan view illustrating the casting mold device according to the embodiment of the present disclosure, and FIG. **5** is an exploded perspective view illustrating the casting mold device according to the embodiment of the present disclosure.

(47) With reference to FIGS. **1-5**, the casting mold device **100** according to the embodiment of the present disclosure includes a plurality of core pin assemblies **30**, a cooling unit **60**, and a sealing unit **90**.

(48) In the embodiment of the present disclosure, the core pin assemblies are configured to form the spark plug mounting portions **3** in the cylinder head **1**. The core pin assemblies **30** are mounted in the upper die **20**.

(49) The core pin assemblies **30** are disposed in the upper die **20** and spaced apart from one another at preset intervals in the forward/rearward direction. The core pin assemblies **30** may be respectively mounted in pin insertion holes **27** formed in the upper die **20** in the upward/downward direction. In this case, the pin insertion hole **27** penetrates the upper forming part **25** in the upward/downward direction from above the upper die **20**.

(50) FIG. **6** is a cross-sectional view illustrating the casting mold device according to the embodiment of the present disclosure, FIG. **7** is a perspective view and a cross-sectional view illustrating the core pin assembly applied to the casting mold device according to the embodiment of the present disclosure, and FIG. **8** is an exploded perspective view illustrating the core pin assembly applied to the casting mold device according to the embodiment of the present disclosure.

(51) With reference to FIGS. **5-8**, the core pin assemblies **30** according to the embodiment of the present disclosure include a plurality of separating pins **30a** capable of being coupled to and separated from one another.

(52) The separating pins **30a** each include a plug casing **31**, a plug pin **41**, and a plug bushing **51**.

(53) In the embodiment of the present disclosure, the plug casing **31** is fitted with the pin insertion hole **27** of the upper die **20** in the upward/downward direction. The plug casing **31** may have a cylindrical shape having a hollow portion **32** opened at upper and lower ends thereof.

(54) The plug casing **31** may include a casing outer flange **33** and a casing inner flange **35**.

(55) The casing outer flange **33** is formed on an outer periphery of an upper end of the plug casing **31**. The casing outer flange **33** may support an upper surface of the upper die **20**. The casing inner flange **35** is formed on an inner periphery of a lower end of the plug casing **31**.

(56) In an embodiment of the present disclosure, the plug pin **41** is fitted with the hollow portion **32** of the plug casing **31** in the upward/downward direction and coupled to a lower portion of the plug casing **31**. Further, the plug pin **41** protrudes downward from the pin insertion hole **27**.

(57) The plug pin **41** includes a flow path groove **42** opened at an upper end thereof and closed at a lower end thereof. In another embodiment, the plug pin **41** includes a pin outer flange **45** formed on an outer periphery of an upper end of the plug pin **41**.

(58) In this case, the pin outer flange **45** of the plug pin **41** may be coupled to the casing inner flange **35** of the plug casing **31** by a locking projection.

(59) Therefore, the plug pin **41** is coupled to the casing inner flange **35** by means of the pin outer flange **45** in the hollow portion **32** of the plug casing **31**, such that the plug pin **41** may protrude downward from the pin insertion hole **27** in a state in which the plug pin **41** is coupled to the lower end of the plug casing **31**.

(60) In an embodiment of the present disclosure, the plug bushing **51** may be provided in the hollow portion **32** of the plug casing **31** and positioned above the plug pin **41**.

(61) The plug bushing **51** is fitted with the hollow portion **32** of the plug casing **31** in the upward/downward direction and coupled to the upper end of the plug casing **31**. The plug bushing **51** may have a cylindrical shape having a hollow portion **52** opened at upper and lower ends thereof. In this case, a lower end of the plug bushing **51** is in contact with the upper end of the plug pin **41**.

(62) The plug bushing **51** includes a bushing outer flange **53** formed on an outer periphery of the upper end of the plug bushing **51**. The bushing outer flange **53** may support an upper surface of the casing outer flange **33** of the plug casing **31**.

(63) The bushing outer flange **53** and the casing outer flange **33** are fastened in the upward/downward direction by a plurality of bolts **55**. Further, the plug pin **41** may be coupled to the casing inner flange **35** of the plug casing **31** by means of the pin outer flange **45** and a locking projection and fixed by the plug bushing **51**.

(64) Therefore, the plug casing **31**, the plug pin **41**, and the plug bushing **51** may be mounted in the pin insertion hole **27** of the upper die **20** in the state in which the plug casing **31**, the plug pin **41**, and the plug bushing **51** are coupled to one another. Further, the plug casing **31**, the plug pin **41**, and the plug bushing **51**, which are coupled to one another, may be separated from one another, in a state in which the plug casing **31**, the plug pin **41**, and the plug bushing **51** are withdrawn from the pin insertion hole **27**.

(65) Furthermore, the core pin assemblies **30**, in which the plug casing **31**, the plug pin **41**, and the plug bushing **51** are coupled to one another, each include therein a cooling air flow path **57** formed in the upward/downward direction.

(66) The cooling air flow path **57** may be defined by the flow path groove **42** of the plug pin **41** and the hollow portion **52** of the plug bushing **51** that are connected in the upward/downward direction in the hollow portion **32** of the plug casing **31**.

(67) With reference to FIGS. **3-6**, in the embodiment of the present disclosure, the cooling unit **60** is configured to cool the core pin assemblies **30** by using the cooling air by allowing the cooling air through the cooling air flow paths **57** of the core pin assemblies **30**.

(68) The cooling unit **60** is installed on the upper die **20**, connected to the cooling air flow paths **57** of the core pin assemblies **30**, and configured to inject and discharge the cooling air.

(69) FIG. **9** is a perspective view illustrating the cooling unit applied to the casting mold device according to the embodiment of the present disclosure, and FIG. **10** is a cross-sectional view illustrating the cooling unit applied to the casting mold device according to the embodiment of the present disclosure.

(70) With reference to FIGS. **9** and **10**, the cooling unit **60** according to the embodiment of the present disclosure includes a plurality of head blocks **61**, cooling pipes **71**, and a cooling air discharge module **81**.

(71) In an embodiment of the present disclosure, the head blocks **61** are each provided in the form of a block and disposed at positions on the upper die respectively corresponding to the core pin assemblies **30**.

(72) The head blocks **61** each include a path connection portion **63**, a cooling air inlet portion **65**, and a cooling air outlet portion **67**.

(73) The path connection portions **63** are connected to the cooling air flow paths **57** of the core pin assemblies **30**. The path connection portion **63** is formed in a groove shape in a lower portion of each of the head blocks **61**. Further, the path connection portion **63** is connected to the cooling air inlet portion **65** and the cooling air outlet portion **67** to be described below.

(74) The cooling air inlet portion **65** is configured to introduce the cooling air into the cooling air flow path **57**. The cooling air inlet portion **65** is provided in the form of a hole formed through an upper portion of each of the head blocks **61** in the upward/downward direction, and the cooling air inlet portion **65** is connected to the path connection portion **63**.

(75) Furthermore, a cooling air inlet pipe **69** is connected to one side (upper portion based on the drawings) of the cooling air inlet portion **65**. The cooling air inlet pipe **69** may be connected to a cooling air supply part (not illustrated).

(76) Further, the cooling air outlet portion **67** is configured to discharge the cooling air to the outside from the cooling air flow path **57**. The cooling air outlet portion **67** is provided in the form of a hole formed through an approximately middle portion of each of the head blocks **61** in the leftward/rightward direction, and the cooling air outlet portion **67** is connected to the path connection portion **63**.

(77) In this case, a groove cross-sectional area of the path connection portion **63** is larger than a hole cross-sectional area of each of the cooling air inlet portion **65** and the cooling air outlet portion **67**.

(78) In an embodiment of the present disclosure, the cooling pipes **71** are connected to the cooling air inlet portions **65** of the head blocks **61** and disposed in the cooling air flow paths **57** of the core

pin assemblies **30**.

(79) The cooling pipe **71** is configured to inject the cooling air, which is introduced through the cooling air inlet pipe **69**, into the cooling air flow path **57**. Therefore, the cooling pipe **71** is disposed in the flow path groove **42** of the plug pin **41** and the hollow portion **52** of the plug bushing **51**.

(80) The cooling pipe **71** is coupled to the other side (lower portion based on the drawings) of the cooling air inlet portion **65** through the path connection portion **63**. Furthermore, the cooling pipe **71** is coupled to the other side of the cooling air inlet portion **65** by tapping. To this end, the cooling pipe **71** has a coupling end (upper end based on the drawings), and a tapping screw thread **73** is formed at the other side of the cooling air inlet portion **65**.

(81) In this case, the cooling air flow path **57** of each of the core pin assemblies **30**, in which the cooling pipe **71** is disposed, includes a cooling air discharge flow path **59**.

(82) The cooling air discharge flow path **59** is formed between an outer periphery of the cooling pipe **71**, an inner periphery of the plug bushing **51**, and an inner periphery of the plug pin **41**. The inner periphery of the plug bushing **51** may be defined as an inner peripheral surface of the hollow portion **52**, and the inner periphery of the plug pin **41** may be defined as an inner peripheral surface of the flow path groove **42**.

(83) The cooling air discharge flow path **59** may be connected to the cooling pipe **71**, the path connection portion **63**, and the cooling air outlet portion **67**.

(84) Further, in the embodiment of the present disclosure, the cooling air discharge module **81** may be configured to discharge the cooling air, which flows along the cooling air discharge flow path **59**, to the outside through the cooling air outlet portion **67**.

(85) The cooling air discharge module **81** is connected to the cooling air outlet portions **67** of the head blocks **61**. The cooling air discharge module **81** includes a connection pipe **83**, an air discharge housing **85**, and an air discharge pipe **87**.

(86) The connection pipe **83** is connected to the cooling air outlet portions **67** of the head blocks **61**. The air discharge housing **85** is configured to capture the cooling air discharged through the connection pipe **83**. The air discharge housing **85** is connected to the connection pipe **83**. The air discharge pipe **87** is connected to the air discharge housing **85**.

(87) In this case, as illustrated in FIG. 4, the air discharge pipe **87** may extend toward one side edge of the upper holder **21** coupled to the upper die **20**. As an example, the air discharge pipe **87** may extend toward one side edge of the upper holder **21** farthest from the operator.

(88) With reference to FIGS. 3-6 and 10, in the embodiment of the present disclosure, the sealing unit **90** is configured to fix the cooling unit **60**, which is connected to the core pin assemblies **30**, to the upper die **20** and to seal portions between the core pin assemblies **30** and the cooling unit **60**.

(89) The sealing unit **90** is coupled to the cooling unit **60** and the upper die **20**.

(90) FIGS. 11 and 12 are views illustrating the sealing unit applied to the casting mold device according to the embodiment of the present disclosure.

(91) With reference to FIGS. 11 and 12, the sealing unit **90** according to the embodiment of the present disclosure includes a sealing plate **91** and a plurality of sealing fastening members **93**.

(92) The sealing plate **91** is disposed between upper portions of the core pin assemblies **30** and the head blocks **61** of the cooling unit **60**.

(93) In this case, lower portions of the head blocks **61** may be supported by an upper surface of the sealing plate **91**. Further, as illustrated in FIG. 10, a lower surface of the sealing plate **91** may support the bushing outer flange **53** of the plug bushing **51** fastened to the casing outer flange **33** of the plug casing **31** by means of the plurality of bolts **55**.

(94) The plurality of sealing fastening members **93** is configured to fasten the head blocks **61** and the sealing plate **91** and fasten the sealing plate **91** and an upper portion of the upper die **20**.

(95) In an embodiment, the sealing fastening members **93** may each include a sealing fastening bolt **95**.

(96) Hereinafter, a process of assembling the casting mold device **100** according to the embodiment of the present disclosure configured as described above and an operation of the casting mold device **100** are described in detail with reference to FIGS. **1-13** attached hereto.

(97) FIG. **13** is a view illustrating an operation of the casting mold device according to another embodiment of the present disclosure.

(98) With reference to FIGS. **1-12**, the plurality of core pin assemblies **30**, which each includes the plug casing **31**, the plug pin **41**, and the plug bushing **51**, is provided.

(99) In the state in which the plug casing **31**, the plug pin **41**, and the plug bushing **51** of each of the core pin assemblies **30** are separated from one another, the plug casing **31**, the plug pin **41**, and the plug bushing **51** are coupled to one another.

(100) The structure for coupling the plug casing **31**, the plug pin **41**, and the plug bushing **51** is described below. The plug pin **41** is fitted with the hollow portion **32** of the plug casing **31**.

(101) In this case, the plug pin **41** protrudes from the hollow portion **32** of the plug casing **31**, and the plug pin **41** is coupled to the casing inner flange **35** of the plug casing **31** by means of the pin outer flange **45** and the locking projection.

(102) Next, the plug bushing **51** is fitted with the hollow portion **32** of the plug casing **31**. The plug bushing **51** is disposed in the hollow portion **32** of the plug casing **31** and positioned above the plug pin **41**. Further, the bushing outer flange **53** of the plug bushing **51** supports the upper surface of the casing outer flange **33** of the plug casing **31**.

(103) In this state, the bushing outer flange **53** and the casing outer flange **33** are fastened by the plurality of bolts **55**. Then, the plug pin **41** may be fixed by the plug bushing **51** in the state in which the plug pin **41** is coupled to the casing inner flange **35** by means of the pin outer flange **45** and the locking projection.

(104) As described above, the cooling air flow path **57** is formed in the core pin assembly **30** in which the plug casing **31**, the plug pin **41**, and the plug bushing **51** are coupled to one another.

(105) Next, the core pin assemblies **30** are fitted with the pin insertion holes **27** of the upper die **20** in the upward/downward direction. In this case, the casing outer flange **33** of the plug casing **31** supports the upper surface of the upper die **20**. Further, the plug pins **41** of the core pin assemblies **30** protrude downward from the pin insertion holes **27**.

(106) Meanwhile, in the embodiment of the present disclosure, the cooling unit **60**, which includes the plurality of head blocks **61**, the cooling pipes **71**, and the cooling air discharge module **81**, is provided.

(107) In an embodiment, the cooling unit **60** may be provided as a modularized component in which the plurality of head blocks **61**, the cooling pipes **71**, and the cooling air discharge module **81** are connected to one another. In the cooling unit **60**, the cooling air discharge module **81** includes the connection pipe **83**, the air discharge housing **85**, and the air discharge pipe **87**.

(108) The cooling pipes **71** are connected to the cooling air inlet portions **65** of the head blocks **61**. In addition, the cooling air inlet pipe **69** is connected to the cooling air inlet portion **65**.

(109) Further, the connection pipe **83** of the cooling air discharge module **81** is connected to the cooling air outlet portions **67** of the head blocks **61**, and the air discharge housing **85** is connected to the connection pipe **83**. The air discharge pipe **87** is connected to the air discharge housing **85**.

(110) In an embodiment of the present disclosure, the sealing unit **90**, which includes the sealing plate **91** and the plurality of sealing fastening members **93**, is provided. The plurality of sealing fastening members **93** may include the sealing fastening bolts **95**.

(111) As described above, the sealing plate **91** is disposed on the upper portions of the core pin assemblies **30** in the state in which the core pin assemblies **30** are fitted with the pin insertion holes **27** of the upper die **20**.

(112) In this case, the lower surface of the sealing plate **91** supports the bushing outer flange **53** of the plug bushing **51** fastened to the casing outer flange **33** of the plug casing **31** by means of the plurality of bolts **55**.

(113) The cooling pipe **71** of the cooling unit **60** penetrates a hole formed in the sealing plate **91** and is fitted with the cooling air flow path **57** of each of the core pin assemblies **30**. In this case, the cooling pipe **71** is disposed in the flow path groove **42** of the plug pin **41** and the hollow portion **52** of the plug bushing **51** of each of the core pin assemblies **30**.

(114) The upper surface of the sealing plate **91** supports the lower portions of the head blocks **61**. In this state, the path connection portion **63** of each of the head blocks **61** is connected to the cooling air flow path **57**.

(115) The head blocks **61** and the sealing plate **91** are fastened by the sealing fastening bolts **95**. Further, the sealing plate **91** and the upper portion of the upper die **20** are fastened by the sealing fastening bolts **95**.

(116) The cooling unit **60** may be connected to the core pin assemblies **30** and fixed to the upper die **20**. Further, the portions between the core pin assemblies **30** and the cooling unit **60** may be sealed by the sealing plate **91**.

(117) Because the cooling unit **60** is coupled to the core pin assemblies **30** as described above, the cooling air discharge flow paths **59** are formed in the cooling air flow paths **57** of the core pin assemblies **30** in which the cooling pipes **71** are disposed.

(118) The cooling air discharge flow path **59** is formed between the outer periphery of the cooling pipe **71**, the inner periphery of the plug bushing **51**, and the inner periphery of the plug pin **41**. Further, the cooling air discharge flow path **59** is connected to the cooling pipe **71**, the path connection portion **63**, and the cooling air outlet portion **67**.

(119) Hereinafter, an operation of the casting mold device **100**, in which the core pin assemblies **30** are mounted in the upper die **20** as described above, is described with reference to FIG. **13**. First, the upper die **20** is moved upward by the drive device, such that the upper die **20** is in a state of being detached from the lower die **10**.

(120) In this state, when the upper die **20** is moved downward by the drive device and attached to the lower die **10**, the cavity **7** with a preset shape and volume is formed between the lower forming part **15** of the lower die **10** and the upper forming part **25** of the upper die **20**.

(121) Next, the molten metal **5** accommodated in the heat retention furnace **17** is pushed upward along a preset route by low-pressure compressed air from below the lower die **10**. Then, the molten metal **5** is injected into the cavity **7** through the molten metal injection part **13** of the lower die **10**.

(122) Therefore, the casting mold device **100** according to the embodiment of the present disclosure may produce the cylinder head **1** with a preset shape by solidifying the molten metal **5** injected into the cavity **7**.

(123) In this case, the core pin assemblies **30** may form the spark plug mounting portions **3** in the form of holes in the cylinder head **1** in the state in which the core pin assemblies **30** are disposed in the upper forming part **25** of the upper die **20**.

(124) As described above, in the embodiment of the present disclosure, during the process of producing the cylinder head **1**, the cooling air is supplied to the cooling air inlet pipes **69** and introduced into the cooling air inlet portions **65** of the head blocks **61**.

(125) The cooling air is introduced into the cooling air flow paths **57** of the core pin assemblies **30** through the cooling pipes **71**. In this case, the cooling air introduced into the cooling air flow path **57** flows along the cooling air discharge flow path **59** in the flow path groove **42** of the plug pin **41**.

(126) The cooling air, which flows along the cooling air discharge flow paths **59** as described above, passes through the path connection portions **63** of the head blocks **61** and is discharged through the cooling air outlet portions **67**.

(127) In this case, because the portions between the core pin assemblies and the cooling unit **60** are sealed by the sealing unit **90**, the cooling air introduced into the cooling air flow paths **57** may be discharged through the cooling air outlet portions **67** without leaking between the core pin assemblies **30** and the cooling unit **60**.

(128) Therefore, the casting mold device **100** according to the embodiment of the present

disclosure may cool the core pin assemblies **30** while allowing the cooling air to flow to the cooling air flow paths **57** of the core pin assemblies **30**.

(129) Meanwhile, the cooling air, which is discharged through the cooling air outlet portions **67** of the head blocks **61**, is captured in the air discharge housing **85** through the connection pipe **83**. The cooling air, which is captured in the air discharge housing **85** as described above, is discharged to the outside through the air discharge pipe **87**.

(130) In this case, the air discharge pipe **87** discharges the cooling air at one side edge of the upper holder **21** farthest from the operator.

(131) The casting mold device **100** according to the embodiment of the present disclosure described above applies the separate cooling air discharge structure, which discharges the cooling air to the outside, to the cooling unit **60** configured to cool the core pin assemblies **30** by using the cooling air.

(132) Further, the casting mold device **100** according to the embodiment of the present disclosure adopts the sealing structure configured to seal the cooling air that may leak between the core pin assemblies **30** and the cooling unit **60**.

(133) Therefore, the casting mold device **100** according to the embodiment of the present disclosure may minimize exhaust noise of the cooling air caused when the core pin assemblies **30** are cooled by the cooling air.

(134) In particular, the casting mold device **100** according to the embodiment of the present disclosure may discharge the cooling air through the cooling air discharge module **81** at one side edge of the upper holder **21** farthest from the operator.

(135) Therefore, the casting mold device **100** according to the embodiment of the present disclosure may improve the working environment of the operator while preventing hearing impairment of the operator caused by exhaust noise of the cooling air.

(136) Furthermore, according to the casting mold device **100** according to the embodiment of the present disclosure, the plug casing **31**, the plug pin **41**, and the plug bushing **51** of each of the core pin assemblies **30** are structured to be separated from or coupled to one another.

(137) Therefore, according to the casting mold device **100** according to the embodiment of the present disclosure, when the core pin assemblies **30** are damaged because the core pin assemblies **30** are in contact with the high-temperature molten metal **5** over a long period of time, only some damaged parts may be replaced, which may reduce costs required to replace the core pin assemblies **30**.

(138) While the embodiments of the present disclosure have been described above, the present disclosure is not limited thereto, and various modifications can be made and carried out within the scope of the claims, the detailed description of the present disclosure, and the accompanying drawings, and also fall within the scope of the present disclosure.

(139) TABLE-US-00001 <Description of symbols> 1: Cylinder head 3: Spark plug mounting portion 5: Molten metal 7: Cavity 10: Lower die 11: Lower holder 13: Molten metal injection part 15: Lower forming part 17: Heat retention furnace 20: Upper die 21: Upper holder 25: Upper forming part 27: Pin insertion hole 30: Core pin assembly 30a: Separating pins 31: Plug casing 32, 52: Hollow portion 33: Casing outer flange 35: Casing inner flange 41: Plug pin 42: Flow path groove 45: Pin outer flange 51: Plug bushing 53: Bushing outer flange 55: Bolt 57: Cooling air flow path 59: Cooling air discharge flow path 60: Cooling unit 61: Head block 63: Path connection portion 65: Cooling air inlet portion 67: Cooling air outlet portion 69: Cooling air inlet pipe 71: Cooling pipe 73: Tapping screw thread 81: Cooling air discharge module 83: Connection pipe 85: Air discharge housing 87: Air discharge pipe 90: Sealing unit 91: Sealing plate 93: Sealing fastening member 95: Sealing fastening bolt 100: Casting mold device

Claims

1. A casting mold device comprising: a lower die; an upper die configured to attach to or detach from the lower die; a plurality of core pin assemblies mounted in the upper die and including a plurality of separating pins capable configured to couple to or separate from one another, wherein the plurality of core pin assemblies includes cooling air flow paths formed in the plurality of separating pins coupled to one another; a cooling unit installed on the upper die and connected to the cooling air flow paths so as to inject and discharge cooling air; and a sealing unit coupled to the cooling unit and the upper die to seal portions between the core pin assemblies and the cooling unit, wherein the plurality of separating pins each comprise: a cylindrical plug casing fitted with a pin insertion hole formed in the upper die in an upward/downward direction, the cylindrical plug casing being opened at upper and lower ends thereof; a plug pin fitted with the cylindrical plug casing, coupled to a lower portion of the cylindrical plug casing, opened at an upper end thereof, and closed at a lower end thereof; and a plug bushing fitted with the cylindrical plug casing so as to be positioned above the plug pin, coupled to an upper portion of the cylindrical plug casing, and having a cylindrical shape opened at upper and lower ends thereof.
2. The casting mold device of claim 1, wherein the core pin assemblies are respectively mounted in the pin insertion holes formed in the upper die in the upward/downward direction to form spark plug mounting portions of a cylinder head.
3. The casting mold device of claim 1, wherein the cooling unit comprises: a plurality of head blocks disposed at positions corresponding to the core pin assemblies and respectively having cooling air inlet portions and cooling air outlet portions; cooling pipes connected to the cooling air inlet portions of the plurality of head blocks and disposed in the cooling air flow paths; and a cooling air discharge module connected to the cooling air outlet portions of the plurality of head blocks.
4. The casting mold device of claim 3, wherein the cooling unit comprises cooling air inlet pipes each connected to one side of each of the cooling air inlet portions of the plurality of head blocks, and the cooling pipes are each connected to another side of each of the cooling air inlet portions by tapping.
5. The casting mold device of claim 3, wherein the cooling air discharge module comprises: a connection pipe connected to the cooling air outlet portions of the plurality of head blocks; an air discharge housing connected to the connection pipe; and an air discharge pipe connected to the air discharge housing.
6. The casting mold device of claim 5, wherein the air discharge pipe extends toward one side edge of an upper holder coupled to the upper die.
7. The casting mold device of claim 3, wherein the sealing unit comprises: a sealing plate disposed between the core pin assemblies and the plurality of head blocks; and a plurality of sealing fastening members configured to fasten the plurality of head blocks and the sealing plate and fasten the sealing plate and the upper die.
8. The casting mold device of claim 7, wherein the sealing fastening members respectively include sealing fastening bolts.
9. The casting mold device of claim 1, wherein: the cylindrical plug casing comprises a casing outer flange formed on an outer periphery of an upper end thereof, and a casing inner flange formed on an inner periphery of a lower end thereof, and the plug bushing comprises a bushing outer flange formed on an outer periphery of an upper end thereof.
10. The casting mold device of claim 9, wherein the casing outer flange and the bushing outer flange are fastened by a plurality of bolts.
11. The casting mold device of claim 9, wherein the casing inner flange is coupled to a pin outer flange formed at an upper end of the plug pin by a locking projection.
12. The casting mold device of claim 1, wherein the cooling air flow paths comprise a flow path groove formed in the plug pin, and a hollow portion of the plug bushing connected to the flow path

groove.

13. The casting mold device of claim 1, wherein the cooling unit comprises: a plurality of head blocks disposed at positions respectively corresponding to the core pin assemblies and respectively having cooling air inlet portions and cooling air outlet portions; and cooling pipes connected to the cooling air inlet portions of the plurality of head blocks and disposed in the plug bushing and the plug pin.

14. The casting mold device of claim 13, wherein the cooling air flow paths comprise: a cooling air discharge flow path formed between an outer periphery of a cooling pipe of the cooling pipes, an inner periphery of the plug bushing, and an inner periphery of the plug pin, wherein the cooling air discharge flow path is connected to the cooling pipe and a cooling air outlet portion of the cooling air outlet portions.
