

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250252687

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Cansizoglu; Omer et al.

---

### RECORDING AUGMENTED REALITY CONTENT ON AN EYEWEAR DEVICE

---

#### Abstract

The subject technology sends captured image data and metadata to a first set of computing processes for processing. The subject technology receives, asynchronously from a second set of computing processes, second metadata. The subject technology detects a signal indicating a command to stop image data capturing. The subject technology, in response to the detected signal, generating a composite AR content item based on the metadata and the captured image data. The subject technology provides the composite AR content item for rendering for display on an eyewear device.

---

**Inventors:** Cansizoglu; Omer (Mercer Island, WA), Doshi; Chintan (Marina Del Rey, CA), Li; Yuechuan (Rancho Palo Verdes, CA), Minakov; Stanislav (Playa Vista, CA), Poliakov; Fedir (Playa Vista, CA), Wilder; Justin (Santa Monica, CA)

**Applicant:** Snap Inc. (Santa Monica, CA)

**Family ID:** 80168228

**Appl. No.:** 19/188289

**Filed:** April 24, 2025

#### Related U.S. Application Data

parent US continuation 17646431 20211229 parent-grant-document US 12307605 child US 19188289

us-provisional-application US 63132963 20201231

---

#### Publication Classification

**Int. Cl.:** G06T19/00 (20110101); G02B27/01 (20060101); G06V20/20 (20220101)

## U.S. Cl.:

CPC      **G06T19/006** (20130101); **G02B27/017** (20130101); **G06V20/20** (20220101);  
G02B2027/0178 (20130101)

---

## Background/Summary

CLAIM OF PRIORITY [0001] This application is a continuation of U.S. patent application Ser. No. 17/646,431, filed Dec. 29, 2021, which application claims the benefit of priority of U.S. Provisional Patent Application No. 63/132,963, filed Dec. 31, 2020, which are hereby incorporated by reference herein in their entireties for all purposes.

### BACKGROUND

[0002] With the increased use of digital images, affordability of portable computing devices, availability of increased capacity of digital storage media, and increased bandwidth and accessibility of network connections, digital images have become a part of the daily life for an increasing number of people.

[0003] Some electronics-enabled eyewear devices, such as so-called smart glasses, allow users to interact with virtual content while a user is engaged in some activity. Users wear the eyewear devices and can view a real-world environment through the eyewear devices while interacting with virtual content that is displayed by the eyewear devices.

---

## Description

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0004] To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

[0005] FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some example embodiments.

[0006] FIG. 2 is a diagrammatic representation of a messaging client application, in accordance with some example embodiments.

[0007] FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some example embodiments.

[0008] FIG. 4 is a diagrammatic representation of a message, in accordance with some example embodiments.

[0009] FIG. 5 shows a front perspective view of an eyewear device in the form of a pair of smart glasses that include a eyewear system according to one example embodiment.

[0010] FIG. 6 is a schematic diagram illustrating a structure of the message annotations, as described in FIG. 4, including additional information corresponding to a given message, according to some embodiments.

[0011] FIG. 7 is a block diagram illustrating various modules of an eyewear system, according to certain example embodiments.

[0012] FIG. 8 is a flowchart illustrating a method, according to certain example embodiments.

[0013] FIG. 9 is a block diagram illustrating various modules of an AR content editing system that implements an AR graphics pipeline, according to certain example embodiments.

[0014] FIG. 10 is a schematic diagram of an example of a graphical processing pipeline, namely a post-processing pipeline implemented for components (e.g., a GPU) of a client device or eyewear device, according to some example embodiments.

[0015] FIG. 11 is a schematic diagram of an example of a stacking of augmented reality content

layers as implemented via a graphical processing pipeline, namely the post-processing pipeline(s) described in FIG. 10, according to some example embodiments.

[0016] FIG. 12 is a flowchart illustrating a method, according to certain example embodiments.

[0017] FIG. 13 illustrates examples of recording and rendering AR content in an eyewear device, according to certain example embodiments.

[0018] FIG. 14 is block diagram showing a software architecture within which the present disclosure may be implemented, in accordance with some example embodiments.

[0019] FIG. 15 is a diagrammatic representation of a machine, in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed, in accordance with some example embodiments.

## DETAILED DESCRIPTION

[0020] Users with a range of interests from various locations can capture digital images of various subjects and make captured images available to others via networks, such as the Internet. To enhance users' experiences with digital images and provide various features, enabling computing devices to perform image processing operations on various objects and/or features captured in a wide range of changing conditions (e.g., changes in image scales, noises, lighting, movement, or geometric distortion) can be challenging and computationally intensive.

[0021] Augmented reality technology aims to bridge a gap between virtual environments and a real world environment by providing an enhanced real world environment that is augmented with electronic information. As a result, the electronic information appears to be part of the real world environment as perceived by a user. In an example, augmented reality technology further provides a user interface to interact with the electronic information that is overlaid in the enhanced real world environment.

[0022] A augmented reality (AR) system enables real and virtual environments to be combined in varying degrees to facilitate interactions from a user in a real time manner. Such an AR system, as described herein, therefore can include various possible combinations of real and virtual environments, including augmented reality that primarily includes real elements and is closer to a real environment than a virtual environment (e.g., without real elements). In this manner, a real environment can be connected with a virtual environment by the AR system. A user immersed in an AR environment can navigate through such an environment and the AR system can track the user's viewpoint to provide a visualization based on how the user is situated in the environment. Augmented reality (AR) experiences can be provided in a messaging client application (or the messaging system) as described in embodiments herein.

[0023] Embodiments of the subject technology described herein enable various operations involving AR content for capturing and editing such content with a given electronic device, such as a wearable headset device (e.g., a given eyewear device) and a mobile computing device.

[0024] As referred to herein, a post-capture stage refers to a period where AR content has been captured by a given device (e.g., using a capture sensor such as a camera) and has been stored in a given storage device and/or persistent memory device. Further such AR content may have undergone transcoding and/or compression to transform the AR content into a suitable format for storage. A user of a messaging client application, as described further herein, can retrieve the stored AR content at a later time period for applying a set of post-processing image and AR processing operations described further herein, which advantageously utilizes the novel graphical processing pipelines, systems, methods, techniques, and user interfaces as described in more detail herein.

[0025] Messaging systems are frequently utilized and are increasingly leveraged by users of mobile computing devices, in various settings, to provide different types of functionality in a convenient manner. As described herein, the subject messaging system comprises practical applications that provide improvements in capturing image data and rendering AR content (e.g., images, videos, and the like) based on the captured image data by at least providing technical improvements with capturing image data using power and resource constrained electronic devices, and performing

post-processing operations on the AR content using such devices. Such improvements in capturing image data are enabled by techniques provided by the subject technology, which reduce latency and increase efficiency in processing captured image data thereby also reducing power consumption in the capturing devices. Such post-processing operations are enabled by at least an extensible graphical rendering pipeline software architecture (as described further herein) which supports layering of post-processing operations to provide composite AR content. Via such an extensible architecture, processing and computing improvements can be achieved over existing graphical rendering pipelines. The extensible architecture can further reduce latency in rendering of the post-processing operations compared with image processing operations that are performed in conjunction with image and/or video capture operations (e.g., via a camera of a given electronic computing device).

[0026] As discussed further herein, the subject infrastructure supports the creation and sharing of interactive media, referred to herein as messages including 3D content or AR effects, throughout various components of a messaging system. In example embodiments described herein, messages can enter the system from a live camera or via from storage (e.g., where messages including 3D content and/or AR effects are stored in memory or a database). The subject system supports motion sensor input, and loading of external effects and asset data.

[0027] As referred to herein, the phrase “augmented reality experience,” “augmented reality content item,” “augmented reality content generator” includes or refers to various image processing operations corresponding to an image modification, filter, AR content generators, media overlay, transformation, and the like, and additionally can include playback of audio or music content during presentation of AR content or media content, as described further herein.

[0028] FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple instances of a client device **102**, each of which hosts a number of applications including a messaging client application **104**. Each messaging client application **104** is communicatively coupled to other instances of the messaging client application **104** and a messaging server system **108** via a network **106** (e.g., the Internet).

[0029] A messaging client application **104** is able to communicate and exchange data with another messaging client application **104** and with the messaging server system **108** via the network **106**. The data exchanged between messaging client application **104**, and between a messaging client application **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

[0030] The messaging system **100** includes an eyewear device **150**, which hosts an eyewear system **160**, among other applications. The eyewear device **150** is communicatively coupled to the client device **102** via the network **106** (which may include via a dedicated short-range communication path, such as a Bluetooth™ or Wi-Fi direct connection).

[0031] The eyewear device **150** may be a head mounted portable system, worn by a user, that includes a display system capable of presenting a visualization of an augmented reality environment to the user (e.g., head mounted display device). The eyewear device **150** may be powered with a battery of some kind. In an example, the display system controlled by the eyewear system **160** of the eyewear device **150** provides a stereoscopic presentation of the augmented reality environment, enabling a three-dimensional visual display of a rendering of a particular scene, to the user. Further, the eyewear device **150** may include various sensors including, but not limited to, cameras, image sensors, touch sensors, microphones, inertial measurement units (IM U), heart rate, temperature, among other types of sensors. Moreover, the eyewear device **150** may include hardware elements that can receive user input such as hardware buttons or switches. User input detected by such sensors and/or hardware elements correspond to various input modalities to initiate a particular operation(s). For example, such input modalities may include, but not limited to, facial tracking, eye tracking (e.g., gaze direction), hand tracking, gesture tracking, biometric

readings (e.g., heart rate, pulse, pupil dilation, breath, temperature, electroencephalogram, olfactory), recognizing speech or audio (e.g., particular hotwords), and activating buttons or switches, etc.

[0032] The eyewear device **150** may be communicatively coupled to a base device such as the client device **102**. Such a base device may, in general, include more computing resources and/or available power in comparison with the eyewear device **150**. In an example, the eyewear device **150** may operate in various modes. For instance, the eyewear device **150** can operate in a standalone mode independent of any base device.

[0033] The eyewear device **150** may also operate in a wireless tethered mode (e.g., connected via a wireless connection with a base device such as client device **102**), working in conjunction with a given base device. When the eyewear device **150** operates in the wireless tethered mode, at least a portion of processing user inputs and/or rendering the augmented reality environment may be offloaded to the base device thereby reducing processing burdens on the eyewear device **150**. For instance, in an implementation, the eyewear device **150** works in conjunction with the client device **102** to generate an augmented reality environment including physical and/or virtual objects that enables different forms of interaction (e.g., visual, auditory, and/or physical or tactile interaction) between the user and the generated augmented reality environment in a real-time manner. In an example, the eyewear device **150** provides a rendering of a scene corresponding to the augmented reality environment that can be perceived by the user and interacted with in a real-time manner. Additionally, as part of presenting the rendered scene, the eyewear device **150** may provide sound, haptic, or tactile feedback to the user. The content of a given rendered scene may be dependent on available processing capability, network availability and capacity, available battery power, and current system workload.

[0034] In an implementation, the eyewear system **160** generates a message including a recording of a real environment and generates an augmented reality environment including two-dimensional (2D) video for sharing and playback. In another implementation, the eyewear system **160** generates a message, and subsequently generates a three-dimensional (3D) representation merging information from all sensors and/or combining recording with other users' messages (e.g., different point of views (POVs)). It is further appreciated that the client device **102** can also generate such augmented reality environments either working in conjunction with the eyewear device **150** or independently of the eyewear device **150**.

[0035] The eyewear system **160** automatically or selectively moves augmented reality or virtual reality content from one virtual position to another as the user moves around the eyewear device **150**. For example, the user or wearer of the eyewear device **150** may initially be looking at a first portion of a real-world environment (e.g., a first room in a house). The user may provide input (e.g., using a client device **102** or a voice activated or touch activated interface of the eyewear device **150**) to launch or access virtual content that includes one or more objects.

[0036] The messaging server system **108** provides server-side functionality via the network **106** to a particular messaging client application **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client application **104** or by the messaging server system **108**, the location of certain functionality either within the messaging client application **104** or the messaging server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108**, but to later migrate this technology and functionality to the messaging client application **104** where a client device **102** has a sufficient processing capacity.

[0037] The messaging server system **108** supports various services and operations that are provided to the messaging client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client application **104**. This data may include, message content, client device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event

information, as examples. Data exchanges within the messaging system **100** are invoked and controlled through functions available via user interfaces (UIs) of the messaging client application **104**.

[0038] Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the application server **112**.

[0039] The Application Program Interface (API) server **110** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client application **104** in order to invoke functionality of the application server **112**. The Application Program Interface (API) server **110** exposes various functions supported by the application server **112**, including account registration, login functionality, the sending of messages, via the application server **112**, from a particular messaging client application **104** to another messaging client application **104**, the sending of media files (e.g., images or video) from a messaging client application **104** to the messaging server application **114**, and for possible access by another messaging client application **104**, the setting of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, and opening an application event (e.g., relating to the messaging client application **104**).

[0040] The application server **112** hosts a number of applications and subsystems, including a messaging server application **114**, an image processing system **116** and a social network system **122**. The messaging server application **114** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available, by the messaging server application **114**, to the messaging client application **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server application **114**, in view of the hardware requirements for such processing.

[0041] The application server **112** also includes an image processing system **116** that is dedicated to performing various image processing operations, typically with respect to images or video received within the payload of a message at the messaging server application **114**.

[0042] The social network system **122** supports various social networking functions services, and makes these functions and services available to the messaging server application **114**. To this end, the social network system **122** maintains and accesses an entity graph **304** (as shown in FIG. 3) within the database **120**. Examples of functions and services supported by the social network system **122** include the identification of other users of the messaging system **100** with which a particular user has relationships or is 'following', and also the identification of other entities and interests of a particular user.

[0043] The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the messaging server application **114**.

[0044] FIG. 2 is block diagram illustrating further details regarding the messaging system **100**, according to example embodiments. Specifically, the messaging system **100** is shown to comprise the messaging client application **104** and the application server **112**, which in turn embody a number of some subsystems, namely an ephemeral timer system **202**, a collection management

system **204** and an annotation system **206**.

[0045] The ephemeral timer system **202** is responsible for enforcing the temporary access to content permitted by the messaging client application **104** and the messaging server application **114**. To this end, the ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, or collection of messages (e.g., a story), selectively display and enable access to messages and associated content via the messaging client application **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

[0046] The collection management system **204** is responsible for managing collections of media (e.g., collections of text, image video and audio data). In some examples, a collection of content (e.g., messages, including images, video, text and audio) may be organized into an ‘event gallery’ or an ‘event story.’ Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a ‘story’ for the duration of that music concert. The collection management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client application **104**.

[0047] The collection management system **204** furthermore includes a curation interface **208** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **208** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **204** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain embodiments, compensation may be paid to a user for inclusion of user-generated content into a collection. In such cases, the curation interface **208** operates to automatically make payments to such users for the use of their content.

[0048] The annotation system **206** provides various functions that enable a user to annotate or otherwise modify or edit media content associated with a message. For example, the annotation system **206** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The annotation system **206** operatively supplies a media overlay or supplementation (e.g., an image filter) to the messaging client application **104** based on a geolocation of the client device **102**. In another example, the annotation system **206** operatively supplies a media overlay to the messaging client application **104** based on other information, such as social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay may include text that can be overlaid on top of a photograph taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the annotation system **206** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **120** and accessed through the database server **118**.

[0049] In one example embodiment, the annotation system **206** provides a user-based publication platform that enables users to select a geolocation on a map, and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The annotation system **206** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

[0050] In another example embodiment, the annotation system **206** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the annotation system **206** associates the media overlay of a highest bidding merchant with a corresponding geolocation for a predefined amount of time.

[0051] FIG. **3** is a schematic diagram illustrating data structures **300** which may be stored in the database **120** of the messaging server system **108**, according to certain example embodiments. While the content of the database **120** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

[0052] The database **120** includes message data stored within a message table **314**. The entity table **302** stores entity data, including an entity graph **304**. Entities for which records are maintained within the entity table **302** may include individuals, corporate entities, organizations, objects, places, events, etc. Regardless of type, any entity regarding which the messaging server system **108** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown).

[0053] The entity graph **304** furthermore stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

[0054] The database **120** also stores annotation data, in the example form of filters, in an annotation table **312**. Filters for which data is stored within the annotation table **312** are associated with and applied to videos (for which data is stored in a video table **310**) and/or images (for which data is stored in an image table **308**). Filters, in one example, are overlays that are displayed as overlaid on an image or video during presentation to a recipient user. Filters may be of various types, including user-selected filters from a gallery of filters presented to a sending user by the messaging client application **104** when the sending user is composing a message. Other types of filters include geolocation filters (also known as geo-filters) which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the messaging client application **104**, based on geolocation information determined by a GPS unit of the client device **102**. Another type of filter is a data filter, which may be selectively presented to a sending user by the messaging client application **104**, based on other inputs or information gathered by the client device **102** during the message creation process. Example of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device **102**, or the current time.

[0055] Other annotation data that may be stored within the image table **308** are augmented reality content generators (e.g., corresponding to applying AR content generators, augmented reality experiences, or augmented reality content items). An augmented reality content generator may be a real-time special effect and sound that may be added to an image or a video.

[0056] As described above, augmented reality content generators, augmented reality content items, overlays, image transformations, AR images and similar terms refer to modifications that may be made to videos or images. This includes real-time modification which modifies an image as it is captured using a device sensor and then displayed on a screen of the device with the modifications. This also includes modifications to stored content, such as video clips in a gallery that may be modified. For example, in a device with access to multiple augmented reality content generators, a user can use a single video clip with multiple augmented reality content generators to see how the different augmented reality content generators will modify the stored clip. For example, multiple augmented reality content generators that apply different pseudorandom movement models can be applied to the same content by selecting different augmented reality content generators for the content. Similarly, real-time video capture may be used with an illustrated modification to show



how video images currently being captured by sensors of a device would modify the captured data. Such data may simply be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the modifications (or both). In some systems, a preview feature can show how different augmented reality content generators will look within different windows in a display at the same time. This can, for example, enable multiple windows with different pseudorandom animations to be viewed on a display at the same time.

[0057] Data and various systems using augmented reality content generators or other such transform systems to modify content using this data can thus involve detection of objects (e.g., faces, hands, bodies, cats, dogs, surfaces, objects, etc.), tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various embodiments, different methods for achieving such transformations may be used. For example, some embodiments may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other embodiments, tracking of points on an object may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further embodiments, neural network analysis of video frames may be used to place images, models, or textures in content (e.g., images or frames of video). Augmented reality content generators thus refer both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

[0058] Real-time video processing can be performed with any kind of video data (e.g., video streams, video files, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using a computer animation model, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

[0059] In some embodiments, when a particular modification is selected along with content to be transformed, elements to be transformed are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream. Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of object's elements characteristic points for each of element of an object are calculated (e.g., using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A first set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method, a background of the modified object can be changed or distorted as well by tracking and modifying the background.

[0060] In one or more embodiments, transformations changing some areas of an object using its elements can be performed by calculating of characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus

transforming the frames of the video stream. Depending on the specific request for modification properties of the mentioned areas can be transformed in different ways. Such modifications may involve changing color of areas; removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various embodiments, any combination of such modifications or other similar modifications may be used. For certain models to be animated, some characteristic points can be selected as control points to be used in determining the entire state-space of options for the model animation.

[0061] In some embodiments of a computer animation model to transform image data using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g., Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

[0062] In other embodiments, other methods and algorithms suitable for face detection can be used. For example, in some embodiments, features are located using a landmark which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left eye pupil may be used. In an initial landmark is not identifiable (e.g., if a person has an eyepatch), secondary landmarks may be used. Such landmark identification procedures may be used for any such objects. In some embodiments, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

[0063] In some embodiments, a search for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector is started. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable and the shape model pools the results of the weak template matchers to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

[0064] Embodiments of a transformation system can capture an image or video stream on a client device (e.g., the client device **102**) and perform complex image manipulations locally on the client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on the client device **102**.

[0065] In some example embodiments, a computer animation model to transform image data can be used by a system where a user may capture an image or video stream of the user (e.g., a selfie) using a client device **102** having a neural network operating as part of a messaging client application **104** operating on the client device **102**. The transform system operating within the messaging client application **104** determines the presence of a face within the image or video stream and provides modification icons associated with a computer animation model to transform image data, or the computer animation model can be present as associated with an interface described herein. The modification icons include changes which may be the basis for modifying the user's face within the image or video stream as part of the modification operation. Once a modification icon is selected, the transform system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). In some embodiments, a modified image or video stream may be presented in a graphical user interface

displayed on the mobile client device as soon as the image or video stream is captured and a specified modification is selected. The transform system may implement a complex convolutional neural network on a portion of the image or video stream to generate and apply the selected modification. That is, the user may capture the image or video stream and be presented with a modified result in real time or near real time once a modification icon has been selected. Further, the modification may be persistent while the video stream is being captured and the selected modification icon remains toggled. Machine taught neural networks may be used to enable such modifications.

[0066] In some embodiments, the graphical user interface, presenting the modification performed by the transform system, may supply the user with additional interaction options. Such options may be based on the interface used to initiate the content capture and selection of a particular computer animation model (e.g., initiation from a content creator user interface). In various embodiments, a modification may be persistent after an initial selection of a modification icon. The user may toggle the modification on or off by tapping or otherwise selecting the face being modified by the transformation system and store it for later viewing or browse to other areas of the imaging application. Where multiple faces are modified by the transformation system, the user may toggle the modification on or off globally by tapping or selecting a single face modified and displayed within a graphical user interface. In some embodiments, individual faces, among a group of multiple faces, may be individually modified or such modifications may be individually toggled by tapping or selecting the individual face or a series of individual faces displayed within the graphical user interface.

[0067] In some example embodiments, a graphical processing pipeline architecture is provided that enables different augmented reality experiences (e.g., AR content generators) to be applied in corresponding different layers. Such a graphical processing pipeline provides an extensible rendering engine for providing multiple augmented reality experiences that are included in a composite media (e.g., image or video) or composite AR content for rendering by the messaging client application **104** (or the messaging system **100**).

[0068] As mentioned above, the video table **310** stores video data which, in one embodiment, is associated with messages for which records are maintained within the message table **314**. Similarly, the image table **308** stores image data associated with messages for which message data is stored in the entity table **302**. The entity table **302** may associate various annotations from the annotation table **312** with various images and videos stored in the image table **308** and the video table **310**.

[0069] A story table **306** stores data regarding collections of messages and associated image, video, or audio data, which are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **302**). A user may create a ‘personal story’ in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the messaging client application **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

[0070] A collection may also constitute a ‘live story,’ which is a collection of content from multiple users that is created manually, automatically, or using a combination of manual and automatic techniques. For example, a ‘live story’ may constitute a curated stream of user-submitted content from various locations and events. Users whose client devices have location services enabled and are at a common location event at a particular time may, for example, be presented with an option, via a user interface of the messaging client application **104**, to contribute content to a particular live story. The live story may be identified to the user by the messaging client application **104**, based on his or her location. The end result is a ‘live story’ told from a community perspective.

[0071] A further type of content collection is known as a ‘location story,’ which enables a user whose client device **102** is located within a specific geographic location (e.g., on a college or university campus) to contribute to a particular collection. In some embodiments, a contribution to

a location story may require a second degree of authentication to verify that the end user belongs to a specific organization or other entity (e.g., is a student on the university campus).

[0072] FIG. 4 is a schematic diagram illustrating a structure of a message **400**, according to some embodiments, generated by a messaging client application **104** or the eyewear system **160** for communication to a further messaging client application **104** or the messaging server application **114**. The content of a particular message **400** is used to populate the message table **314** stored within the database **120**, accessible by the messaging server application **114**. Similarly, the content of a message **400** is stored in memory as ‘in-transit’ or ‘in-flight’ data of the client device **102** or the application server **112**. The message **400** is shown to include the following components:

[0073] A message identifier **402**: a unique identifier that identifies the message **400**.

[0074] A message text payload **404**: text, to be generated by a user via a user interface of the client device **102** and that is included in the message **400**.

[0075] A message image payload **406**: image data, captured by a camera component of a client device **102** or retrieved from a memory component of a client device **102**, and that is included in the message **400**.

[0076] A message video payload **408**: video data, captured by a camera component or retrieved from a memory component of the client device **102** and that is included in the message **400**.

[0077] A message audio payload **410**: audio data, captured by a microphone or retrieved from a memory component of the client device **102**, and that is included in the message **400**.

[0078] A message annotations **412**: annotation data (e.g., filters, stickers or other enhancements) that represents annotations to be applied to message image payload **406**, message video payload **408**, or message audio payload **410** of the message **400**.

[0079] A message duration parameter **414**: parameter value indicating, in seconds, the amount of time for which content of the message (e.g., the message image payload **406**, message video payload **408**, message audio payload **410**) is to be presented or made accessible to a user via the messaging client application **104**.

[0080] A message geolocation parameter **416**: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter **416** values may be included in the payload, each of these parameter values being associated with respect to content items included in the content (e.g., a specific image into within the message image payload **406**, or a specific video in the message video payload **408**).

[0081] A message story identifier **418**: identifier values identifying one or more content collections (e.g., ‘stories’) with which a particular content item in the message image payload **406** of the message **400** is associated. For example, multiple images within the message image payload **406** may each be associated with multiple content collections using identifier values.

[0082] A message tag **420**: each message **400** may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload **406** depicts an animal (e.g., a lion), a tag value may be included within the message tag **420** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition.

[0083] A message sender identifier **422**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** on which the message **400** was generated and from which the message **400** was sent

[0084] A message receiver identifier **424**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** to which the message **400** is addressed.

[0085] The contents (e.g., values) of the various components of message **400** may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload **406** may be a pointer to (or address of) a location within an image table

**308.** Similarly, values within the message video payload **408** may point to data stored within a video table **310**, values stored within the message annotations **412** may point to data stored in an annotation table **312**, values stored within the message story identifier **418** may point to data stored in a story table **306**, and values stored within the message sender identifier **422** and the message receiver identifier **424** may point to user records stored within an entity table **302**.

[0086] FIG. 5 shows a front perspective view of an eyewear device **150** in the form of a pair of smart glasses that include a eyewear system **160** according to one example embodiment. The eyewear device **150** includes a body **503** comprising a front piece or frame **506** and a pair of temples **509** connected to the frame **506** for supporting the frame **506** in position on a user's face when the eyewear device **150** is worn. The frame **506** can be made from any suitable material such as plastics or metal, including any suitable shape memory alloy.

[0087] The eyewear device **150** includes a pair of optical elements in the form of a pair of lenses **512** held by corresponding optical element holders in the form of a pair of rims **515** forming part of the frame **506**. The rims **515** are connected by a bridge **518**. In other embodiments, one or both of the optical elements can be a display, a display assembly, or a lens and display combination.

[0088] The frame **506** includes a pair of end pieces **521** defining lateral end portions of the frame **506**. In this example, a variety of electronics components are housed in one or both of the end pieces **521**. The temples **509** are coupled to the respective end pieces **521**. In this example, the temples **509** are coupled to the frame **506** by respective hinges so as to be hingedly movable between a wearable mode and a collapsed mode in which the temples **509** are pivoted towards the frame **506** to lie substantially flat against it. In other embodiments, the temples **509** can be coupled to the frame **506** by any suitable means, or can be rigidly or fixedly secured to the frame **506** so as to be integral therewith.

[0089] Each of the temples **509** that includes a front portion of that is coupled to the frame **506** and any suitable rear portion for coupling to the ear of the user, such as the curves or cute piece illustrated in the example embodiment of FIG. 5. In some embodiments, the frame **506** is formed of a single piece of material, so as to have a unitary or monolithic construction. In some embodiments, the whole of the body **503** (including both the frame **506** and the temples **509**) can be of the unitary or monolithic construction.

[0090] The eyewear device **150** has onboard electronics components including a computing device, such as a computer **524**, or low power processor, which can in different embodiments be of any suitable type so as to be carried by the body **503**. In some embodiments, the computer **524** is at least partially housed in one or both of the temples **509**. In the present embodiment, various components of the computer **524** are housed in the lateral end pieces **521** of the frame **506**. The computer **524** includes one or more processors with memory (e.g., a volatile storage device, such as random access memory or registers), a storage device (e.g., a non-volatile storage device), wireless communication circuitry (e.g., BLE communication devices and/or WiFi direct devices), and a power source. The computer **524** comprises low-power circuitry, high-speed circuitry, and, in some embodiments, a display processor. Various embodiments may include these elements in different configurations or integrated together in different ways.

[0091] The computer **524** additionally includes a battery **527** or other suitable portable power supply. In one embodiment, the battery **527** is disposed in one of the temples **509**. In the eyewear device **150** shown in FIG. 5, the battery **527** is shown as being disposed in one of the end pieces **521**, being electrically coupled to the remainder of the computer **524** housed in the corresponding end piece **521**.

[0092] The eyewear device **150** is camera-enabled, in this example comprising a camera **530** mounted in one of the end pieces **521** and facing forwards so as to be aligned more or less with the direction of view of a wearer of the eyewear device **150**. The camera **530** is configured to capture digital images (also referred to herein as digital photographs or pictures) as well as digital video content. Operation of the camera **530** is controlled by a camera controller provided by the computer

**524**, image data representative of images or video captured by the camera **530** being temporarily stored on a memory forming part of the computer **524**. In some embodiments, the eyewear device **150** can have a pair of cameras **530**, e.g. housed by the respective end pieces **521**.

[0093] As will be described in greater detail below, the onboard computer **524** and the lenses **512** are configured together to provide a eyewear system **160** that automatically and selectively re-centers virtual content to bring the virtual content to within view of the lenses **512** by moving the virtual content from a first virtual location to a second virtual location. Specifically, the lenses **512** can display virtual content or one or more virtual objects. This makes it appear to the user that the virtual content is integrated within a real-world environment that the user views through the lenses **512**. In some embodiments, the virtual content is received from the client device **102**. In some embodiments, the virtual content is received directly from the application server **112**.

[0094] The eyewear device **150** includes an accelerometer and a touch interface and a voice command system. Based on input received by the eyewear device **150** from the accelerometer and a touch interface and the voice command system, the eyewear device **150** can control user interaction with the virtual content. In one example, the user interaction can control playback of content that is presented on the lenses **512**. In another example, the user interaction can navigate through a playlist or music or video library. In another example, the user interaction can navigate through a conversation the user is involved in, such as by scrolling through various three-dimensional or two-dimensional conversation elements (e.g., chat bubbles) and selecting individual conversation elements to respond to generate messages to transmit to participants of the conversation.

[0095] The eyewear system **160** (which can be implemented by the computer **524**) assigns virtual content to virtual locations. The eyewear system **160** monitors the current virtual location that is within view of a real-world environment. The eyewear system **160** retrieves virtual content for display that is within a specified range of the current virtual location that is within view. As the eyewear device **150** is moved around to be directed to a new portion of the real-world environment, associated with a different set of virtual locations, the eyewear system **160** excludes any virtual content that is not within range of the different set of virtual locations. For example, as the eyewear device **150** is moved around to be directed to a new portion of the real-world environment that does not overlap with the previously displayed portion of the real-world environment, the eyewear system **160** excludes any virtual content that is not within range of the different set of virtual locations.

[0096] The eyewear system **160** can receive a request to bring virtual content into a current view. In response, the eyewear system **160** updates the virtual location assigned and associated with the virtual content to be the virtual location that is associated with the current view of the real-world environment. As a result, the virtual content is now moved from being out of view to be included in the current view to allow the user to interact with the virtual content. In some cases, the user can only interact with virtual content that is within view of the lenses **512**. If the user moves around to face another direction resulting in the virtual content going out of view, the user input no longer can control or interact with the previously displayed virtual content until the virtual content is brought back into view.

[0097] The eyewear device **150** further includes one or more communication devices, such as Bluetooth low energy (BLE) communication interface. Such BLE communication interface enables the eyewear device **150** to communicate wirelessly with the client device **102**. Other forms of wireless communication can also be employed instead of, or in addition to, the BLE communication interface, such as a WiFi direct interface. The BLE communication interface implements a standard number of BLE communication protocols.

[0098] A first of the communications protocols implemented by the BLE interface of the eyewear device **150** enables an unencrypted link to be established between the eyewear device **150** and the client device **102**. In this first protocol, the link-layer communication (the physical interface or medium) between the eyewear device **150** and the client device **102** includes unencrypted data. In

this first protocol, the application layer (the communication layer operating on the physically exchanged data) encrypts and decrypts data that is physically exchanged in unencrypted form over the link layer of the BLE communication interface. In this way, data exchanged over the physical layer can freely be read by an eavesdropping device, but the eavesdropping device will not be able to decipher the data that is exchanged without performing a decryption operation in the application layer.

[0099] A second of the communications protocols implemented by the BLE interface of the eyewear device **150** enables an encrypted link to be established between the eyewear device **150** and the client device **102**. In this second protocol, the link-layer communication (the physical interface) between the eyewear device **150** and the client device **102** receives data from the application layer and adds a first type of encryption to the data before exchanging the data over the physical medium. In this second protocol, the application layer (the communication layer operating on the physically exchanged data) may or may not use a second type of encryption to encrypt and decrypt data that is physically exchanged in encrypted form, using the first type of encryption, over the link layer of the BLE communication interface. Namely, data can be first encrypted by the application layer and then be further encrypted by the physical layer before being exchanged over the physical medium. Following the exchange over the physical medium, the data is then decrypted by the physical layer and then decrypted again (e.g., using a different type of encryption) by the application layer. In this way, data exchanged over the physical layer cannot be read by an eavesdropping device as the data is encrypted in the physical medium.

[0100] In some embodiments, the client device **102** communicates with the eyewear device **150** using the first protocol to exchange images or videos or virtual content between the messaging client **104** and the eyewear device **150**.

[0101] As described above, media overlays, such as AR content generators, overlays, image transformations, AR images and similar terms refer to modifications that may be made to videos or images. This includes real-time modification which modifies an image as it is captured using a device sensor and then displayed on a screen of the device with the modifications. This also includes modifications to stored content, such as video clips in a gallery that may be modified. For example, in a device with access to multiple media overlays (e.g., AR content generators), a user can use a single video clip with multiple AR content generators to see how the different AR content generators will modify the stored clip. For example, multiple AR content generators that apply different pseudorandom movement models can be applied to the same content by selecting different AR content generators for the content. Similarly, real-time video capture may be used with an illustrated modification to show how video images currently being captured by sensors of a device would modify the captured data. Such data may simply be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the modifications (or both). In some systems, a preview feature can show how different AR content generators will look within different windows in a display at the same time. This can, for example, enable multiple windows with different pseudorandom animations to be viewed on a display at the same time.

[0102] Data and various systems to use AR content generators or other such transform systems to modify content using this data can thus involve detection of objects (e.g. faces, hands, bodies, cats, dogs, surfaces, objects, etc.), tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various embodiments, different methods for achieving such transformations may be used. For example, some embodiments may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other embodiments, tracking of points on an object may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further embodiments, neural network analysis of video frames may be used

to place images, models, or textures in content (e.g. images or frames of video). Lens data thus refers both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

[0103] Real time video processing can be performed with any kind of video data, (e.g. video streams, video files, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using a computer animation model, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

[0104] In some embodiments, when a particular modification is selected along with content to be transformed, elements to be transformed are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream.

Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of object's elements characteristic points for each of element of an object are calculated (e.g. using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A first set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method a background of the modified object can be changed or distorted as well by tracking and modifying the background.

[0105] In one or more embodiments, transformations changing some areas of an object using its elements can be performed by calculating of characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus transforming the frames of the video stream. Depending on the specific request for modification properties of the mentioned areas can be transformed in different ways. Such modifications may involve: changing color of areas; removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various embodiments, any combination of such modifications or other similar modifications may be used. For certain models to be animated, some characteristic points can be selected as control points to be used in determining the entire state-space of options for the model animation.

[0106] In some embodiments of a computer animation model to transform image data using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g. Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

[0107] In other embodiments, other methods and algorithms suitable for face detection can be used. For example, in some embodiments, features are located using a landmark which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left eye pupil may be used. In an initial landmark is not identifiable (e.g. if a person has an eyepatch), secondary landmarks may be used. Such landmark identification



procedures may be used for any such objects. In some embodiments, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

[0108] In some embodiments, a search for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector is started. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable and the shape model pools the results of the weak template matchers to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

[0109] Embodiments of a transformation system can capture an image or video stream on a client device and perform complex image manipulations locally on a client device such as client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on a client device.

[0110] In some example embodiments, a computer animation model to transform image data can be used by a system where a user may capture an image or video stream of the user (e.g., a selfie) using a client device **102** having a neural network operating as part of a messaging client application **104** operating on the client device **102**. The transform system operating within the messaging client application **104** determines the presence of a face within the image or video stream and provides modification icons associated with a computer animation model to transform image data, or the computer animation model can be present as associated with an interface described herein. The modification icons include changes which may be the basis for modifying the user's face within the image or video stream as part of the modification operation. Once a modification icon is selected, the transform system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). In some embodiments, a modified image or video stream may be presented in a graphical user interface displayed on the mobile client device as soon as the image or video stream is captured and a specified modification is selected. The transform system may implement a complex convolutional neural network on a portion of the image or video stream to generate and apply the selected modification. That is, the user may capture the image or video stream and be presented with a modified result in real time or near real time once a modification icon has been selected. Further, the modification may be persistent while the video stream is being captured and the selected modification icon remains toggled. Machine taught neural networks may be used to enable such modifications.

[0111] In some embodiments, the graphical user interface, presenting the modification performed by the transform system, may supply the user with additional interaction options. Such options may be based on the interface used to initiate the content capture and selection of a particular computer animation model (e.g. initiation from a content creator user interface). In various embodiments, a modification may be persistent after an initial selection of a modification icon. The user may toggle the modification on or off by tapping or otherwise selecting the face being modified by the transformation system. and store it for later viewing or browse to other areas of the imaging application. Where multiple faces are modified by the transformation system, the user may toggle the modification on or off globally by tapping or selecting a single face modified and displayed

within a graphical user interface. In some embodiments, individual faces, among a group of multiple faces, may be individually modified or such modifications may be individually toggled by tapping or selecting the individual face or a series of individual faces displayed within the graphical user interface.

[0112] In some example embodiments, a graphical processing pipeline architecture is provided that enables different media overlays to be applied in corresponding different layers. Such a graphical processing pipeline provides an extensible rendering engine for providing multiple augmented reality content generators that are included in a composite media (e.g., image or video) or composite AR content for rendering by the messaging client application **104** (or the messaging system **100**).

[0113] As discussed herein, the subject infrastructure supports the creation and sharing of interactive messages with interactive effects throughout various components of the messaging system **100**. In an example, to provide such interactive effects, a given interactive message may include image data along with 2D data, or 3D data. The infrastructure as described herein enables other forms of 3D and interactive media (e.g., 2D media content) to be provided across the subject system, which allows for such interactive media to be shared across the messaging system **100** and alongside photo and video messages. In example embodiments described herein, messages can enter the system from a live camera or via from storage (e.g., where messages with 2D or 3D content or augmented reality (AR) effects (e.g., 3D effects, or other interactive effects are stored in memory or a database). In an example of an interactive message with 3D data, the subject system supports motion sensor input and manages the sending and storage of 3D data, and loading of external effects and asset data.

[0114] As mentioned above, an interactive message includes an image in combination with a 2D effect, or a 3D effect and depth data. In an example embodiment, a message is rendered using the subject system to visualize the spatial detail/geometry of what the camera sees, in addition to a traditional image texture. When a viewer interacts with this message by moving a client device, the movement triggers corresponding changes in the perspective the image and geometry are rendered at to the viewer.

[0115] In an embodiment, the subject system provides AR effects (which may include 3D effects using 3D data, or interactive 2D effects that do not use 3D data) that work in conjunction with other components of the system to provide particles, shaders, 2D assets and 3D geometry that can inhabit different 3D-planes within messages. The AR effects as described herein, in an example, are rendered in a real-time manner for the user.

[0116] As mentioned herein, a gyro-based interaction refers to a type of interaction in which a given client device's rotation is used as an input to change an aspect of the effect (e.g., rotating phone along x-axis in order to change the color of a light in the scene).

[0117] As mentioned herein, an augmented reality content generator refers to a real-time special effect and/or sound that may be added to a message and modifies image and/or 3D data with an AR effects and/or other 3D content such as 3D animated graphical elements, 3D objects (e.g., non-animated), and the like.

[0118] The following discussion relates to example data that is stored in connection with such a message in accordance to some embodiments.

[0119] FIG. **6** is a schematic diagram illustrating a structure of the message annotations **412**, as described above in FIG. **4**, including additional information corresponding to a given message, according to some embodiments, generated by the messaging client application **104** or the eyewear system **160**.

[0120] In an embodiment, the content of a particular message **400**, as shown in FIG. **3**, including the additional data shown in FIG. **6** is used to populate the message table **314** stored within the database **120** for a given message, which is then accessible by the messaging client application **104**. As illustrated in FIG. **6**, message annotations **412** includes the following components

corresponding to various data: [0121] augmented reality (AR) content identifier **652**: identifier of an AR content generator utilized in the message [0122] message identifier **654**: identifier of the message [0123] asset identifiers **656**: a set of identifiers for assets in the message. For example, respective asset identifiers can be included for assets that are determined by the particular AR content generator. In an embodiment, such assets are created by the AR content generator on the sender side client device, uploaded to the messaging server application **114**, and utilized on the receiver side client device in order to recreate the message. Examples of typical assets include: [0124]  custom-character The original still RGB image(s) captured by the camera [0125]  custom-character The post-processed image(s) with AR content generator effects applied to the original image [0126] augmented reality (AR) content metadata **658**: additional metadata associated with the AR content generator corresponding to the AR identifier **652**, such as: [0127] AR content generator category: corresponding to a type or classification for a particular AR content generator [0128] AR content generator carousel index [0129] carousel group: This can be populated and utilized when eligible post-capture AR content generators are inserted into a carousel interface. In an implementation, a new value “AR\_DEFAULT\_GROUP” (e.g., a default group assigned to an AR content generator can be added to the list of valid group names. [0130] capture metadata **660** corresponding to additional metadata, such as: [0131] camera image metadata [0132] camera intrinsic data [0133] focal length [0134] principal point [0135] other camera information (e.g., camera position) [0136] sensor information [0137] gyroscopic sensor data [0138] position sensor data [0139] accelerometer sensor data [0140] other sensor data [0141] location sensor data [0142] FIG. 7 is a block diagram illustrating various modules of an eyewear system **160**, according to certain example embodiments. The eyewear system **160** is shown as including an AR content recording system **700**. As further shown, the AR content recording system **700** includes a camera module **702**, a capture module **704**, an image data processing module **706**, a rendering module **708**, and a content recording module **710**. The various modules of the AR content recording system **700** are configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of these modules may be implemented using one or more computer processors **720** (e.g., by configuring such one or more computer processors to perform functions described for that module) and hence may include one or more of the computer processors **720** (e.g., a set of processors provided by the eyewear device **150**).

[0143] Any one or more of the modules described may be implemented using hardware alone (e.g., one or more of the computer processors **720** of a machine (e.g., machine **1500**) or a combination of hardware and software. For example, any described module of the eyewear system **160** may physically include an arrangement of one or more of the computer processors **720** (e.g., a subset of or among the one or more computer processors of the machine (e.g., machine **1500**) configured to perform the operations described herein for that module. As another example, any module of the AR content recording system **700** may include software, hardware, or both, that configure an arrangement of one or more computer processors **720** (e.g., among the one or more computer processors of the machine (e.g., machine **1500**) to perform the operations described herein for that module. Accordingly, different modules of the AR content recording system **700** may include and configure different arrangements of such computer processors **720** or a single arrangement of such computer processors **720** at different points in time. Moreover, any two or more modules of the eyewear system **160** may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

[0144] The camera module **702** performs camera related operations, including functionality for operations involving one or more cameras of the eyewear device **150**. In an example, camera module **702** can access camera functionality across different processes that are executing on the eyewear device **150**, determining surfaces for face or surface tracking, responding to various

requests (e.g., involving image data of a particular resolution or format) for camera data or image data (e.g., frames) from such processes, providing metadata to such processes that are consuming the requested camera data or image data. As mentioned herein, a “process” or “computing process” can refer to an instance of a computer program that is being executed by one or more threads of a given processor(s).

[0145] As mentioned herein, surface tracking refers to operations for tracking one or more representations of surfaces corresponding to planes (e.g., a given horizontal plane, a floor, a table) in the input frame. In an example, surface tracking is accomplished using hit testing and/or ray casting techniques. Hit testing, in an example, determines whether a selected point (e.g., pixel or set of pixels) in the input frame intersects with a surface or plane of a representation of a physical object in the input frame. Ray casting, in an example, utilizes a Cartesian based coordinate system (e.g., x and y coordinates) and projects a ray (e.g., vector) into the camera's view of the world, as captured in the input frame, to detect planes that the ray intersects.

[0146] In an example, the camera module **702** receives the input frame (or alternatively a duplicate of the input frame in an embodiment). The camera module **702** can include various tracking functionality based on a type of object to track. In an example, the camera module **702** includes tracking capabilities for surface tracking, face tracking, object tracking, and the like. In an implementation, the camera module **702** may only execute one of each of a plurality of tracking processes at a time for facilitating the management of computing resources at the client device **102** or eyewear device **150**. In addition, the camera module **702** may perform one or more object recognition operations on the input frame.

[0147] As referred to herein, tracking refers to operations for determining spatial properties (e.g., position and/or orientation) of a given object (or portion thereof) during the post-processing stage. In an implementation, during tracking, the object's position and orientation are measured in a continuous manner. Different objects may be tracked, such as a user's head, eyes, or limbs, surfaces, or other objects. Tracking involves dynamic sensing and measuring to enable virtual objects and/or effects to be rendered with respect to physical objects in a three-dimensional space corresponding to a scene (e.g., the input frame). Thus, the camera module **702** determines metrics corresponding to at least the relative position and orientation of one or more physical objects in the input frame and includes these metrics in tracking data which is provided to the rendering module **708**. In an example, the camera module **702** updates (e.g., track over time) such metrics from frame to subsequent frame.

[0148] In an implementation, the camera module **702** provides, as output, tracking data (e.g., metadata) corresponding to the aforementioned metrics (e.g., position and orientation). In some instances, the camera module **702** includes logic for shape recognition, edge detection, or any other suitable object detection mechanism. The object of interest may also be determined by the camera module **702** to be an example of a predetermined object type, matching shapes, edges, or landmarks within a range to an object type of a set of predetermined object types.

[0149] In an implementation, the camera module **702** can utilize techniques which combines information from the device's motion sensors (e.g., accelerometer and gyroscope sensors, and the like) with an analysis of the scene provided in the input frame. For example, the camera module **702** detects features in the input frame, and as a result, tracks differences in respective positions of such features across several input frames using information derived at least in part on data from the motion sensors of the device.

[0150] As mentioned herein, face tracking refers to operations for tracking representations of facial features, such as portions of a user's face, in the input frame. In some embodiments, the camera module **702** includes facial tracking logic to identify all or a portion of a face within the one or more images and track landmarks of the face across the set of images of the video stream. As mentioned herein, object tracking refers to tracking a representation of a physical object in the input frame.

[0151] In an embodiment, the camera module **702** acts as an intermediary between other components of the AR content recording system **700** and the capture module **704**. As mentioned above, the camera module **702** can receive requests for captured image data from the image data processing module **706**. The camera module **702** can also receive requests for the captured image data from the content recording module **710**. The camera module **702** can forward such requests to the capture module **704** for processing.

[0152] The capture module **704** captures images (which may also include depth data) captured by one or more cameras of eyewear device **150** (e.g., in response to the aforementioned requests from other components). For example, an image is a photograph captured by an optical sensor (e.g., camera) of the eyewear device **150**. An image includes one or more real-world features, such as a user's face or real-world object(s) detected in the image. In some embodiments, an image includes metadata describing the image. Each captured image can be included in a data structure mentioned herein as a "frame", which can include the raw image data along with metadata and other information. In an embodiment, capture module **704** can send captured image data and metadata as (captured) frames to one or more components of the AR content recording system **700**. The sending of the captured frames can occur asynchronously, which may cause synchronization issues as one component might receive and process a given frame slightly before or after another component receives and processes the same frame. In applications for rendering AR effects and AR environments, such synchronization issues can result in a perceived lag from the viewpoint of the user (e.g., a glitch or perception of non-responsiveness), which reduces and detracts from the immersive experience of the AR environments. As discussed further below, embodiments of the subject technology therefore enables generating time information for each captured frame (e.g., timestamps) to facilitate synchronization of operations and improve rendering of AR effects and AR environments which is presented to the viewing user of the eyewear device **150**.

[0153] The image data processing module **706** generates tracking data and other metadata for captured image data, including metadata associated with operations for generating AR content and AR effects applied to the captured image data. The image data processing module **706** performs operations on the received image data. For example, various image processing operations are performed by the image data processing module **706**. The image data processing module **706** performs various operations based on algorithms or techniques that correspond to animations and/or providing visual and/or auditory effects to the received image data. In an embodiment, a given augmented reality content generator can utilize the image data processing module **706** to perform operations as part of generating AR content and AR effects which is then provided to a rendering process to render such AR content and AR effects (e.g., including 2D effects or 3D effects) and the like.

[0154] The rendering module **708** performs rendering of AR content for display by the eyewear system **160** based on data provided by at least one of the aforementioned modules. In an example, the rendering module **708** utilizes a graphical processing pipeline to perform graphical operations to render the AR content for display. The rendering module **708** implements, in an example, an extensible rendering engine which supports multiple image processing operations corresponding to respective augmented reality content generators. In an example, the rendering module **708** can receive a composite AR content item for rendering on a display provided by eyewear device **150**.

[0155] In some implementations, the rendering module **708** provide a graphics system that renders two-dimensional (2D) objects or objects from a three-dimensional (3D) world (real or imaginary) onto a 2D display screen. Such a graphics system (e.g., one included on the eyewear device **150**) includes a graphics processing unit (GPU) in some implementations for performing image processing operations and rendering graphical elements for display.

[0156] In an implementation, the GPU includes a logical graphical processing pipeline, which can receive a representation of a 2D or 3D scene and provide an output of a bitmap that represents a 2D image for display. Existing application programming interfaces (APIs) have implemented graphical

pipeline models. Examples of such APIs include the Open Graphics Library (OpenGL) API and the METAL API. The graphical processing pipeline includes a number of stages to convert a group of vertices, textures, buffers, and state information into an image frame on the screen. In an implementation, one of the stages of the graphical processing pipeline is a shader, which may be utilized as part of a particular augmented reality content generator that is applied to an input frame (e.g., image or video). A shader can be implemented as code running on a specialized processing unit, also referred to as a shader unit or shader processor, usually executing several computing threads, programmed to generate appropriate levels of color and/or special effects to fragments being rendered. For example, a vertex shader processes attributes (position, texture coordinates, color, etc.) of a vertex, and a pixel shader processes attributes (texture values, color, z-depth and alpha value) of a pixel. In some instances, a pixel shader is referred to as a fragment shader.

[0157] It is to be appreciated that other types of shader processes may be provided. In an example, a particular sampling rate is utilized, within the graphical processing pipeline, for rendering an entire frame, and/or pixel shading is performed at a particular per-pixel rate. In this manner, a given electronic device (e.g., the eyewear device **150**) operates the graphical processing pipeline to convert information corresponding to objects into a bitmap that can be displayed by the electronic device.

[0158] The content recording module **710** sends a request(s) to the camera module **702** to initiate recording of image data by one or more cameras provided by the eyewear device **150**. In an embodiment, the camera module **702** acts as intermediary between other components in the AR content recording system. For example, the camera module can receive a request from the content recording module **710** to initiate recording, and forward the request to the capture module **704** for processing. The capture module **704**, upon receiving the request from the camera module **702**, performs operations to initiate image data capture by the camera(s) provided by the eyewear device **150**. Captured image data, including timestamp information for each frame from the captured image data, can then be sent to the content recording module **710** for processing. In an example, the content recording module **710** can perform operations to process captured image data for rendering by the rendering module **708**.

[0159] In an embodiment, components of the AR content recording system **700** can communicate using an inter-process communication (IPC) protocol. In an embodiment, components of the AR content recording system **700** can communicate through an API provided by the AR content recording system **700**.

[0160] In an embodiment, the camera module **702** receives a signal or command (or a request) to stop recording of image data (e.g., sent from the content recording module **710**). In response, the camera module **702** sends a request to the capture module **704** to stop capturing image data. The capture module **704**, in response to the request to stop recording, complies with the request and ceases further operations to capture image data using one or more cameras of the eyewear device **150**. The camera module **702**, after receiving the signal or command to stop recording, can also asynchronously send a signal to the image data processing module **706** that recording of image data (e.g., capture of image data by the capture module **704**) has (requested to be) stopped. The image data processing module **706**, after receiving the signal, performs operations to complete or finish image processing operations, including performing operations to generate metadata related to AR content items and AR effects. Such metadata can then be sent to the capture module **704**, which then generates a composite AR content item, including the metadata. The composite AR content item can be received by the rendering module **708** and rendered for display on a display device provided by the eyewear device **150**.

[0161] FIG. **8** is a flowchart illustrating a method **800**, according to certain example embodiments. The method **800** may be embodied in computer-readable instructions for execution by one or more computer processors such that the operations of the method **800** may be performed in part or in whole by the eyewear device **150**, particularly with respect to respective components of the AR

content recording system **700** described above in FIG. 7; accordingly, the method **800** is described below by way of example with reference thereto. However, it shall be appreciated that at least some of the operations of the method **800** may be deployed on various other hardware configurations and the method **800** is not intended to be limited to the AR content recording system **700**.

[0162] At operation **802**, the camera module **702** sends captured image data and metadata (e.g., timing information in the form of timestamps) to a first set of computing processes for processing. In an example, captured image data and metadata can be sent to the image data processing module **706** and the content recording module **710**.

[0163] At operation **804**, second metadata is received asynchronously from a second set of computing processes. In an example, the second metadata includes particular metadata from the image data processing module **706** that is received by the content recording module **710**.

[0164] At operation **806**, the image data processing module **706** detects a signal indicating a command to stop image data capturing. In an example, the image data processing module **706** sends metadata to the capture module **704** to generate a composite AR content item based on the metadata.

[0165] At operation **808**, in response to the detected signal, the capture module **704** generates composite AR content item based on the metadata and captured image data.

[0166] At operation **810**, the capture module **704** provides the composite AR content item to the rendering module for rendering for display on an eyewear device.

[0167] In embodiments, the first set of computing processes comprises an image data processing module and a content recording module, the second set of computing processes includes the image data processing module, and the metadata comprises a first set of timestamps corresponding to a first set of frames from the captured image data, and generating the composite AR content item occurs without transcoding the captured image data to a different image data format from a raw image format of the captured image data, the different image data format having a reduced image size or reduced image quality from the raw image format.

[0168] In embodiments, prior to sending captured image data and metadata to the first set of computing processes for processing, the following occurs: sending, by the image data processing module **706**, a request to a camera module **702** to initiate capturing of image data, sending, by the camera module **702**, a second request to a capture module **704** to capture image data, receiving, by the camera module **702**, the captured image data and the metadata from the capture module **704**, wherein the metadata comprises at least timestamp information for each frame from the captured image data, and sending, by the camera module **702**, the captured image data and the metadata to the image data processing module **706** and the content recording module **710**.

[0169] In embodiments, the following occurs: generating, by the image data processing module **706** for the each frame from the captured image data, tracking data and augmented reality content data corresponding to a particular augmented reality content generator, the second metadata comprising the tracking data and the augmented reality content data, sending, the tracking data, the augmented reality content data, and timestamp information including at least a timestamp associated with the tracking data and the augmented reality content data of each frame to the content recording module **710**.

[0170] In embodiments, the augmented reality content data includes an augmented reality identifier, an augmented reality content generator category, an augmented reality content generator carousel index, and a carousel group.

[0171] In embodiments, the tracking data comprises a set of coordinates for a set of objects or a set of surface planes in the each frame, the set of coordinates corresponding to a subset of coordinates from a field of view from a eyewear device.

[0172] In embodiments, the following occurs: encoding, by the content recording module **710**, each frame from the captured image data to a second image data format different from a raw image format of the captured image data, each of the encoded frames including an associated timestamp

indicating when the encoded frames were captured.

[0173] In embodiments, the following occurs: receiving, by the content recording module **710**, a first event indicating recording has stopped, determining, by the content recording module **710**, that the tracking data, the augmented reality content data, and the timestamp information has not been received, receiving, by the content recording module **710**, second captured frames, discarding, by the content recording module **710**, the second captured frames in response to the first event, receiving, by the content recording module **710**, the tracking data, the augmented reality content data, and the timestamp information, and generating, by the content recording module **710**, the composite A R content item, the generating including: combining, based on matching timestamp information, a set of encoded frames with the tracking data and the augmented reality content data into a set of composite A R content frames, each composite AR content frame including a corresponding encoded frame, corresponding tracking data, corresponding augmented reality content data, and corresponding timestamp information.

[0174] In embodiments, providing the composite AR content item for rendering for display on the eyewear device comprises: for each composite AR content frame from the set of composite AR content frames: rendering, by a rendering module **708**, AR content based on the corresponding tracking data and corresponding augmented reality content data, the rendering causing the AR content to be displayed within the corresponding encoded frame, and predicting, by the rendering module **708**, a future frame to be rendered, the future frame not yet received by the rendering module **708** and having a particular timestamp at a future time from each timestamp from the set of composite AR content frames, and rendering, by the rendering module **708**, the future frame for display on the eyewear device.

[0175] In embodiments, the following occurs: predicting, by the rendering module **708**, a predicted position to render AR content based at least in part on the tracking data from the set of composite AR content frames, the tracking data indicating a likelihood of the predicted position.

[0176] FIG. **9** is a block diagram illustrating various modules of an AR content editing system **900** that implements an AR graphics pipeline, according to certain example embodiments. The AR content editing system **900** is shown as including a camera and AR effects module **902**, a render pipeline module **904**, and a rendering module **906**. The various modules of the AR content editing system **900** are configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of these modules may be implemented using one or more computer processors **920** (e.g., by configuring such one or more computer processors to perform functions described for that module) and hence may include one or more of the computer processors **920** (e.g., a set of processors provided by the client device **102**). In another embodiment, the computer processors **920** refers to a set of processors provided by a server or server system, such as the messaging server system **108**.

[0177] Any one or more of the modules described may be implemented using hardware alone (e.g., one or more of the computer processors **920** of a machine (e.g., machine **1500**) or a combination of hardware and software. For example, any described module of the AR content editing system **900** may physically include an arrangement of one or more of the computer processors **920** (e.g., a subset of or among the one or more computer processors of the machine (e.g., machine **1500**) configured to perform the operations described herein for that module. As another example, any module of the AR content editing system **900** may include software, hardware, or both, that configure an arrangement of one or more computer processors **920** (e.g., among the one or more computer processors of the machine (e.g., machine **1500**) to perform the operations described herein for that module. Accordingly, different modules of the AR content editing system **900** may include and configure different arrangements of such computer processors **920** or a single arrangement of such computer processors **920** at different points in time. Moreover, any two or more modules of the AR content editing system **900** may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules.



Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

[0178] For the purpose of clarity in explaining the technical concepts below, the following discussion relates to a single input frame. However, it is understood that for media content (e.g., image data, and the like) including multiple frames (e.g., a video), the following discussion would also be applicable.

[0179] The render pipeline module **904** receives an input frame captured by a client device **102** or by eyewear device **150**, such as included in a captured image or video. For example, the input frame can be an image captured by an optical sensor (e.g., camera) of the client device **102** or eyewear device **150** during capture of an image or video. An image, in an example, includes one or more real-world features, such as a physical object(s) detected in the image. In an embodiment, such an input frame has been saved to persistent storage and subsequently retrieved to be sent to the render pipeline module **904** for processing.

[0180] The render pipeline module **904** modifies virtual AR content (e.g., changing its size, scale, direction/orientation, color, shape) such as performing an operation that affects the visual appearance and/or position of a virtual object(s) that may be anchored to a representation of a physical object in the scene of the input frame.

[0181] The render pipeline module **904** receives AR content metadata from camera and AR effects module **902** and an input frame. In an example, such AR content metadata includes information regarding a set of AR content items that are to be applied, by the render pipeline module **904**, as effects to the input frame.

[0182] The render pipeline module **904**, in an embodiment, utilizes machine learning techniques for applying image processing to facial features in the input frame, using the AR content metadata. One example of a machine learning model is a machine learning model (e.g., one or more neural networks) that has been trained to generate an “average face” by marking of the borders of facial features based on training data (e.g., several thousands of images). In this example, the machine learning model generates an “average face” that can be utilized to align with a face detected (e.g., object of interest) in the input frame for use in performing image processing to modify the input frame to generate an output frame. Additionally, the render pipeline module **904** may perform the one or more modifications to the portions of the above-mentioned object of interest to generate the modified input frame (e.g., the output frame).

[0183] As discussed further herein, the render pipeline module **904** can perform different image processing operations in multiple render passes thereby generating an output frame after each render pass, which in turn is received by a subsequent render pass to perform a subsequent image processing operation and generating a second output frame.

[0184] In one embodiment, the rendering module **906** generates a composite AR content item. The composite AR content item includes the (final) output frame, the AR content metadata and/or other metadata, and in some instances, the original input frame. Further, it is to be understood that by including the original input frame, example embodiments enable providing non-destructive editing for the message whereby a different image processing operation can be applied to the original input frame, which replaces previous image processing operation performed on the output frame.

[0185] Further, the rendering module **906** performs rendering of content for display by the messaging client application **104** using the AR content metadata. The rendering may be performed in conjunction with graphical processing pipelines and/or AR content stacking (e.g., the application of multiple AR contents to media content) described further herein. In an embodiment, the rendering module **906** utilizes multiple render pipelines. In an embodiment, the rendering module can utilize a “ping-pong” render pass technique to optimize memory utilization while rendering.

[0186] In some implementations, the rendering module **906** provide a graphics system that renders two-dimensional (2D) objects or objects from a three-dimensional (3D) world (real or imaginary)

onto a 2D display screen. Such a graphics system (e.g., one included on the client device **102**) includes a graphics processing unit (GPU) in some implementations for performing image processing operations and rendering graphical elements for display.

[0187] In an implementation, the GPU includes a logical graphical processing pipeline, which can receive a representation of a 2D or 3D scene and provide an output of a bitmap that represents a 2D image for display. Existing application programming interfaces (APIs) have implemented graphical pipeline models. Examples of such APIs include the Open Graphics Library (OpenGL) API and the METAL API. The graphical processing pipeline includes a number of stages to convert a group of vertices, textures, buffers, and state information into an image frame on the screen. In an implementation, one of the stages of the graphical processing pipeline is a shader, which may be utilized as part of a particular augmented reality content generator that is applied to an input frame (e.g., image or video). A shader can be implemented as code running on a specialized processing unit, also referred to as a shader unit or shader processor, usually executing several computing threads, programmed to generate appropriate levels of color and/or special effects to fragments being rendered. For example, a vertex shader processes attributes (position, texture coordinates, color, etc.) of a vertex, and a pixel shader processes attributes (texture values, color, z-depth and alpha value) of a pixel. In some instances, a pixel shader is referred to as a fragment shader.

[0188] It is to be appreciated that other types of shader processes may be provided. In an example, a particular sampling rate is utilized, within the graphical processing pipeline, for rendering an entire frame, and/or pixel shading is performed at a particular per-pixel rate. In this manner, a given electronic device (e.g., the client device **102**) operates the graphical processing pipeline to convert information corresponding to objects into a bitmap that can be displayed by the electronic device.

[0189] Although the above discussion with respect to FIG. **9** refers to an input frame, it is appreciated that the aforementioned components of the AR content processing system can perform similar operations on a set of images (e.g., video) corresponding to respective frames of such video content.

[0190] FIG. **10** is a schematic diagram of an example of a graphical processing pipeline, namely a post-processing pipeline **1000** implemented for components (e.g., a GPU) of the client device **102** (or eyewear device **150**), according to some example embodiments. More specifically, the example of FIG. **10** illustrates a graphical processing pipeline where graphical operations performed on a given input frame are cumulative such that the input frame is processed in accordance with a first selected AR content item and the output of the processing is then provided as input for processing in accordance with a second selected AR content item, and so on throughout the remaining stages of the graphical processing pipeline.

[0191] In an embodiment, the post-processing pipeline **1000** illustrated in FIG. **10** implements an extensible rendering engine which supports multiple image processing operations corresponding to respective AR content items. Such an extensible rendering engine enables a reduction in the consumption of memory resources of a given electronic device (e.g., the client device **102** or eyewear device **150**) as a single rendering engine can be loaded into memory for execution rather than having multiple different rendering engines in memory, each occupying distinct memory spaces, as in some existing implementations.

[0192] In one example, the client device **102** (or eyewear device **150**) is configured to implement one or more of the stages of the post-processing pipeline **1000**, which are shown as various AR content render passes **1010-1030** each corresponding to a respective AR content item. In an example, each AR content render pass **1010-1030** is configurable, for instance, to perform one or more shader and/or image processing operations corresponding to a particular AR content item.

[0193] As shown in AR content render pass **1010**, the post-processing pipeline **1000** receives an original frame **1012** and performs post-processing operations **1014** such as transformations, color effects, shader effects (e.g., distortions), face effects, and the like, based on a first selected AR content item, and outputs a processed frame **1016**.

[0194] As shown in AR content render pass **1020**, the post-processing pipeline **1000** receives the processed frame **1016** and performs second post-processing operations **1022** based on a second selected AR content item. A second processed frame **1024** is provided as output to a subsequent AR content render pass corresponding to AR content render pass **1030**.

[0195] Further, as shown in AR content render pass **1030**, the post-processing pipeline **1000** receives the second processed frame **1024** and performs third post processing operations **1032** based on a third selected AR content item. In another example, the AR content render pass **1030** is instead an output layer which generates pipeline output data (e.g., the second processed frame **1024**) for rendering whereby the third post processing operations **1032** correspond to operations for the pipeline output data.

[0196] FIG. **11** is a schematic diagram of an example of a stacking of AR content layers as implemented via a graphical processing pipeline, namely the post-processing pipeline(s) described above in FIG. **10**, according to some example embodiments.

[0197] As illustrated in the example of FIG. **11**, the stacking of AR content layers can be implemented and executed on computer processors **1110**, such as when provided by a given electronic device (e.g., the client device **102** or eyewear device **150**). A first AR content layer corresponding to an AR content layer **1101** is applied to media content (e.g., AR content, image data, and the like) by the computer processors **1110**. A second AR content layer corresponding to an AR content layer **1102** is applied to media content (e.g., AR content, image data, and the like) by the computer processors **1110**. A third AR content layer corresponding to an AR content layer **1103** is applied to media content (e.g., AR content, image data, and the like) by the computer processors **1110**. Further, a fourth AR content layer corresponding to an AR content layer **1104** is applied to media content (e.g., AR content, image data, and the like) by the computer processors **1110**. In this manner, various AR contents can be stacked (e.g., layered) and applied to media content (e.g., AR content, image data, and the like) for inclusion in a composite AR content item in an example.

[0198] Although four various layers are described as examples in FIG. **11**, it is appreciated that fewer or more layers can be provided without departing from the scope of the subject technology.

[0199] FIG. **12** is a flowchart illustrating a method **1200**, according to certain example embodiments. The method **1200** may be embodied in computer-readable instructions for execution by one or more computer processors such that the operations of the method **1200** may be performed in part or in whole by the messaging client application **104**, particularly with respect to respective components of the AR content editing system **900** described above in FIG. **9**; accordingly, the method **1200** is described below by way of example with reference thereto. However, it shall be appreciated that at least some of the operations of the method **1200** may be deployed on various other hardware configurations and the method **1200** is not intended to be limited to the AR content editing system **900**.

[0200] At operation **1202**, the render pipeline module **904** receives first image data from a storage device. The first image data may be an image such as a photograph or frame of a video captured by the electronic device at a previous time. For example, the first image data is captured by the client device **102** (or eyewear device **150**) at a previous time, stored to the storage device, and later retrieved by the render pipeline module **904**.

[0201] At operation **1204**, the render pipeline module **904** receives first metadata corresponding to a first image processing operation (e.g., AR content item) and a second image processing operation. Such metadata may be stored with and/or generated by the camera and AR effects module **902** (or stored in the database **120**) in order to enable post-processing of AR content. For example, metadata or information corresponding to a AR content item to be applied to AR content (e.g., the first image data) is provided (e.g., either by the client device **102** and/or the messaging server system **108**) during post-processing to enable performing the first and second image processing operations.

[0202] At operation **1206**, the render pipeline module **904** generates, in a first render pass, second

image data based at least in part on the first metadata and the first image processing operation performed on the received first image data. For example, the client device **102** applies an image processing operation corresponding to a selected AR content item to AR content (e.g., to enable a rendering of the applied AR content item on the display screen of the client device **102**).

[0203] In a further example, the camera and AR effects module **902** receives sensor data including an orientation of the client device **102** corresponding to the first image data, the sensor data including metadata associated with the first image data, where generating second image data is further based on the sensor data, the received sensor data indicating an orientation of the client device **102**. For example, using a particular tracking engine with the sensor data, the camera and AR effects module **902** detects the device orientation from the sensor data and then generates corresponding metadata. The render pipeline module **904** can utilize such metadata to generate second image data in a format to fit the device orientation and/or to appropriately provide augmentation of the first image data to thereby generate the second image data. The rendering module **906** can store the second image data separately from the first image data in an embodiment.

[0204] In another example, the first image data includes a representation of an environment. The camera and AR effects module **902** performs a tracking process based on the first image data. The tracking process can be tracking a surface recognized in the representation of the environment, tracking a face recognized in the representation of the environment, tracking an object using a machine learning model, and so forth. In one example embodiment, only one tracking process is performed at a time by the camera and AR effects module **902**.

[0205] At operation **1208**, the render pipeline module **904** generates, in a second render pass, third image data based on the first metadata and the second image processing operation performed on the second image data.

[0206] At operation **1210**, the camera and AR effects module **902** generates second metadata comprising information related to the first and second image processing operations (e.g., respective AR content items). For example, the second metadata comprises a first identifier associated with the first image data, second identifier associated with the second image data, third identifier associated with the third image data, and/or other metadata. Further, the second metadata, in some embodiments, can include the following information to indicate that the image processing occurred during a post-processing stage: gesture information (e.g., swipe direction), gesture sequence count (e.g., number in a sequence or series of swipes), tap count (e.g., number of tap/touch inputs received), AR content item name, AR content item type (e.g., classification indicator), AR content item index, number of AR content items, AR content item score (e.g., relevance indicator), AR content item group, and the like.

[0207] At operation **1212**, the rendering module **906** generates a composite AR content item comprising the second metadata, the third image data, and the first image data.

[0208] In embodiments, the render pipeline module **904** performs the following: providing a multi-layer image processing pipeline, the multi-layer image processing pipeline comprising a feature layer, a render pipeline layer, and a render pass layer, and generating, using the feature layer, cascaded render passes, the cascaded render passes comprising a sequence of respective render passes in which an order of the respective render passes is fixed based at least in part on metadata corresponding to a set of augmented reality content generators to apply for each of the respective render passes, each of the set of augmented reality content generators corresponding to a respective image processing effect or operation related to an augmented reality object or augmented reality content.

[0209] In embodiments, the render pipeline module **904** performs the following: receiving, by the render pipeline layer, the first image data, the first image data comprising a first pixel buffer, a second pixel buffer, and a bitmap, the first pixel buffer including a first set of pixels in a first color space, the first color space comprising a BT.709 color space, the second pixel buffer including a second set of pixels in a second color space, the second color space comprising a BT.601 color

space, and the bitmap comprising a third set of pixels in a third color space, the third color space comprising an RGB color space.

[0210] In embodiments, the render pipeline module **904** performs the following: performing, by the render pipeline layer, a color conversion process based on the first pixel buffer and the second pixel buffer, the color conversion process converting the first set of pixels in the first color space to a first color converted set of pixels in the RGB color space and the second set of pixels in the second color space to a second color converted set of pixels in the RGB color space, and generating a set of textures, based on the first color converted set of pixels and the second color converted set of pixels, for the cascaded render passes, and generating rendering information corresponding the cascaded render passes, each of the cascaded render passes comprising a respective set of image processing operations to render at least one texture from the set of textures, the cascaded render passes comprising multiple render passes that are ordered starting from a first render pass up to a last render pass.

[0211] In embodiments, the render pipeline module **904** performs the following: determining a render destination for the set of textures, the render destination comprising a framebuffer of a rendering pipeline, the framebuffer comprising a portion of memory provided by an eyewear device that stores a final image data for display by a display of the eyewear device.

[0212] In embodiments, the rendering module **906** performs the following: performing, by a render engine of the render pass layer, each render pass from the cascaded render passes for display by a display of an eyewear device, the performing comprising: rendering, using a first render pipeline, the last render pass from the cascaded render passes, the last render pass corresponding to a particular set of augmented reality content generators to apply based on the respective set of image processing operations to render at least one texture from the set of textures, rendering, using a second render pipeline, a second render pass from the cascaded render passes, the second render pass corresponding to a second particular set of augmented reality content generators to apply based on the respective set of image processing operations to render at least one different texture from the set of textures, and rendering, using a third render pipeline, the first render pass from the cascaded render passes, the first render pass corresponding to a third particular set of augmented reality content generators to apply based on the respective set of image processing operations to render at least one second different texture from the set of textures.

[0213] In embodiments, the rendering module **906** performs the following: where performing, by the render engine of the render pass layer, each render pass from the cascaded render passes is based on a ping-pong render pass process, the ping-pong render pass process comprises sending output image data of the first render pipeline as input image data to the second render pipeline, and sending output image data of the second render pipeline as input image data to the first render pipeline.

[0214] In embodiments, the rendering module **906** performs the following: sending output image data from the third render pipeline to a render destination comprising memory provided by an eyewear device.

[0215] In embodiments, the rendering module **906** performs the following: providing a final output image from the render engine of the render pass layer after performing each of the cascaded render passes.

[0216] In embodiments, the rendering module **906** performs the following: providing the composite AR content item for display by a display of an eyewear device.

[0217] FIG. **13** illustrates examples of recording and rendering AR content in an eyewear device, according to certain example embodiments.

[0218] As illustrated, a field of view **1302** from one of the lenses of an eyewear device (e.g., lenses **512**) that includes A R content (e.g., corresponding to a dancing avocado avatar or figure) that is currently being recorded by the eyewear device, which can be implemented based at least on the discussion in FIG. **8** above. It is appreciated, that different A R content generators can be selected

for inclusion in the recording.

[0219] Upon stopping the recording of AR content, a field of view **1304** from one of the lenses of the eyewear device shows a preview of the recorded AR content (e.g., short video clip of the recorded AR content, thumbnail image, and the like) which is shown in a portion of the field of view **1304**. Below the preview of the recorded AR content, includes selectable graphical items for saving the recorded AR content, sending the recorded AR content to one or more different recipients (e.g., other users in the social network, or contacts), and for editing the recorded AR content.

[0220] FIG. **14** is a block diagram illustrating an example software architecture **1406**, which may be used in conjunction with various hardware architectures herein described. FIG. **14** is a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture **1406** may execute on hardware such as machine **1500** of FIG. **15** that includes, among other things, processors **1404**, memory **1414**, and (input/output) I/O components **1418**. A representative hardware layer **1452** is illustrated and can represent, for example, the machine **1500** of FIG. **15**. The representative hardware layer **1452** includes a processing unit **1454** having associated executable instructions **1404**. Executable instructions **1404** represent the executable instructions of the software architecture **1406**, including implementation of the methods, components, and so forth described herein. The hardware layer **1452** also includes memory and/or storage modules memory/storage **1456**, which also have executable instructions **1404**. The hardware layer **1452** may also comprise other hardware **1458**.

[0221] In the example architecture of FIG. **14**, the software architecture **1406** may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture **1406** may include layers such as an operating system **1402**, libraries **1420**, frameworks/middleware **1418**, applications **1416**, and a presentation layer **1414**. Operationally, the applications **1416** and/or other components within the layers may invoke API calls **1408** through the software stack and receive a response as in messages **1412** to the API calls **1408**. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide a frameworks/middleware **1418**, while others may provide such a layer. Other software architectures may include additional or different layers.

[0222] The operating system **1402** may manage hardware resources and provide common services. The operating system **1402** may include, for example, a kernel **1422**, services **1424**, and drivers **1426**. The kernel **1422** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **1422** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **1424** may provide other common services for the other software layers. The drivers **1426** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1426** include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration.

[0223] The libraries **1420** provide a common infrastructure that is used by the applications **1416** and/or other components and/or layers. The libraries **1420** provide functionality that allows other software components to perform tasks in an easier fashion than to interface directly with the underlying operating system **1402** functionality (e.g., kernel **1422**, services **1424** and/or drivers **1426**). The libraries **1420** may include system libraries **1444** (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and the like. In addition, the libraries **1420** may include API libraries **1446** such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as MPREG4, H.264, MP3, AAC, AMR, JPG, PNG), graphics libraries (e.g., an

OpenGL framework that may be used to render 2D and 3D in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **1420** may also include a wide variety of other libraries **1448** to provide many other APIs to the applications **1416** and other software components/modules.

[0224] The frameworks/middleware **1418** (also sometimes referred to as middleware) provide a higher-level common infrastructure that may be used by the applications **1416** and/or other software components/modules. For example, the frameworks/middleware **1418** may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware **1418** may provide a broad spectrum of other APIs that may be used by the applications **1416** and/or other software components/modules, some of which may be specific to a particular operating system **1402** or platform.

[0225] The applications **1416** include built-in applications **1438** and/or third-party applications **1440**. Examples of representative built-in applications **1438** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, and/or a game application. Third-party applications **1440** may include an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform, and may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. The third-party applications **1440** may invoke the API calls **1408** provided by the mobile operating system (such as operating system **1402**) to facilitate functionality described herein.

[0226] The applications **1416** may use built in operating system functions (e.g., kernel **1422**, services **1424** and/or drivers **1426**), libraries **1420**, and frameworks/middleware **1418** to create user interfaces to interact with users of the system. Alternatively, or additionally, in some systems interactions with a user may occur through a presentation layer, such as presentation layer **1414**. In these systems, the application/component ‘logic’ can be separated from the aspects of the application/component that interact with a user.

[0227] FIG. **15** is a block diagram illustrating components of a machine **1500**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **15** shows a diagrammatic representation of the machine **1500** in the example form of a computer system, within which instructions **1510** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1500** to perform any one or more of the methodologies discussed herein may be executed. As such, the instructions **1510** may be used to implement modules or components described herein. The instructions **1510** transform the general, non-programmed machine **1500** into a particular machine **1500** programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **1500** operates as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1500** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1500** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1510**, sequentially or otherwise, that specify actions to be taken by machine **1500**. Further, while only a single machine **1500** is illustrated, the term ‘machine’ shall also be taken to include a collection of machines that individually or jointly execute the

instructions **1510** to perform any one or more of the methodologies discussed herein.

[0228] The machine **1500** may include processors **1504**, including processor **1508** to processor **1512**, memory/storage **1506**, and I/O components **1518**, which may be configured to communicate with each other such as via a bus **1502**. The memory/storage **1506** may include a memory **1514**, such as a main memory, or other memory storage, and a storage unit **1516**, both accessible to the processors **1504** such as via the bus **1502**. The storage unit **1516** and memory **1514** store the instructions **1510** embodying any one or more of the methodologies or functions described herein. The instructions **1510** may also reside, completely or partially, within the memory **1514**, within the storage unit **1516**, within at least one of the processors **1504** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1500**. Accordingly, the memory **1514**, the storage unit **1516**, and the memory of processors **1504** are examples of machine-readable media.

[0229] The I/O components **1518** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1518** that are included in a particular machine **1500** will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1518** may include many other components that are not shown in FIG. 15. The I/O components **1518** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **1518** may include output components **1526** and input components **1528**. The output components **1526** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **1528** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

[0230] In further example embodiments, the I/O components **1518** may include biometric components **1530**, motion components **1534**, environmental components **1536**, or position components **1538** among a wide array of other components. For example, the biometric components **1530** may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **1534** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environmental components **1536** may include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometer that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **1538** may include location sensor components



(e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

[0231] Communication may be implemented using a wide variety of technologies. The I/O components **1518** may include communication components **1540** operable to couple the machine **1500** to a network **1532** or devices **1520** via coupling **1524** and coupling **1522**, respectively. For example, the communication components **1540** may include a network interface component or other suitable device to interface with the network **1532**. In further examples, communication components **1540** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1520** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

[0232] Moreover, the communication components **1540** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1540** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1540**, such as, location via Internet Protocol (IP) geo-location, location via Wi-Fi® signal triangulation, location via detecting a NFC beacon signal that may indicate a particular location, and so forth.

[0233] The following discussion relates to various terms or phrases that are mentioned throughout the subject disclosure.

[0234] ‘Signal Medium’ refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term ‘signal medium’ shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term ‘modulated data signal’ means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms ‘transmission medium’ and ‘signal medium’ mean the same thing and may be used interchangeably in this disclosure.

[0235] ‘Communication Network’ refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EV DO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-

setting organizations, other long-range protocols, or other data transfer technology.

[0236] 'Processor' refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., 'commands', 'op codes', 'machine code', etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as 'cores') that may execute instructions contemporaneously.

[0237] 'Machine-Storage Medium' refers to a single or multiple storage devices and/or media (e.g., a centralized or distributed database, and/or associated caches and servers) that store executable instructions, routines and/or data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and/or device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms 'machine-storage medium,' 'device-storage medium,' 'computer-storage medium' mean the same thing and may be used interchangeably in this disclosure. The terms 'machine-storage media,' 'computer-storage media,' and 'device-storage media' specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term 'signal medium.'

[0238] 'Component' refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A 'hardware component' is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by

software), may be driven by cost and time considerations. Accordingly, the phrase ‘hardware component’ (or ‘hardware-implemented component’) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, ‘processor-implemented component’ refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a ‘cloud computing’ environment or as a ‘software as a service’ (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

[0239] ‘Carrier Signal’ refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

[0240] 'Computer-Readable Medium' refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms 'machine-readable medium,' 'computer-readable medium' and 'device-readable medium' mean the same thing and may be used interchangeably in this disclosure.

[0241] 'Client Device' refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network. In the subject disclosure, a client device is also referred to as an 'electronic device.'

[0242] 'Ephemeral Message' refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

[0243] 'Signal Medium' refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term 'signal medium' shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term 'modulated data signal' means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms 'transmission medium' and 'signal medium' mean the same thing and may be used interchangeably in this disclosure.

[0244] 'Communication Network' refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

[0245] 'Processor' refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., 'commands', 'op codes', 'machine code', etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as 'cores') that may execute instructions contemporaneously.

[0246] ‘Machine-Storage Medium’ refers to a single or multiple storage devices and/or media (e.g., a centralized or distributed database, and/or associated caches and servers) that store executable instructions, routines and/or data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and/or device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms ‘machine-storage medium,’ ‘device-storage medium,’ ‘computer-storage medium’ mean the same thing and may be used interchangeably in this disclosure. The terms ‘machine-storage media,’ ‘computer-storage media,’ and ‘device-storage media’ specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term ‘signal medium.’

[0247] ‘Component’ refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A ‘hardware component’ is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase ‘hardware component’ (or ‘hardware-implemented component’) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a

particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, ‘processor-implemented component’ refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a ‘cloud computing’ environment or as a ‘software as a service’ (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

[0248] ‘Carrier Signal’ refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

[0249] ‘Computer-Readable Medium’ refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms ‘machine-readable medium,’ ‘computer-readable medium’ and ‘device-readable medium’ mean the same thing and may be used interchangeably in this disclosure.

[0250] ‘Client Device’ refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

[0251] ‘Ephemeral Message’ refers to a message that is accessible for a time-limited duration. An

ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

## Claims

1. A method, comprising: sending captured image data and metadata to a first set of computing processes for processing, the first set of computing processes comprising a content recording module; receiving, asynchronously from a second set of computing processes, second metadata; detecting a signal indicating a command to stop image data capturing; in response to the detected signal, generating a composite augmented reality (AR) content item based on the metadata and the captured image data, wherein generating the composite AR content item occurs without modifying a raw image format of the captured image data that results in a reduced image quality from the raw image format, wherein generating the composite AR content item comprises: encoding, by the content recording module, each frame from the captured image data to a second image data format different from the raw image format of the captured image data, each of the encoded frames including an associated timestamp indicating when the encoded frames were captured; providing the composite AR content item for rendering for display on an eyewear device, wherein the first set of computing processes further comprises an image data processing module, the second set of computing processes includes the image data processing module, and the metadata comprises a first set of timestamps corresponding to a first set of frames from the captured image data; generating, by the image data processing module for each frame from the captured image data, tracking data and augmented reality content data corresponding to a particular augmented reality content generator, the second metadata comprising the tracking data and the augmented reality content data; sending, the tracking data, the augmented reality content data, and timestamp information including at least a timestamp associated with the tracking data and the augmented reality content data of each frame to the content recording module; receiving, by the content recording module, second captured frames; receiving, by the content recording module, the tracking data, the augmented reality content data, and the timestamp information, wherein generating, by the content recording module, the composite AR content item, the generating further comprises: combining, based on matching timestamp information, a set of encoded frames with the tracking data and the augmented reality content data into a set of composite AR content frames, each composite AR content frame including a corresponding encoded frame, corresponding tracking data, corresponding augmented reality content data, and corresponding timestamp information, rendering, by a rendering module, AR content based on the corresponding tracking data and corresponding augmented reality content data, the rendering causing the AR content to be displayed within the corresponding encoded frame, and predicting, by the rendering module, a predicted position to render AR content based at least in part on the tracking data from the set of composite AR content frames, the tracking data indicating a likelihood of the predicted position.
2. The method of claim 1, further comprising: prior to sending captured image data and metadata to the first set of computing processes for processing: sending, by the image data processing module, a request to a camera module to initiate capturing of image data; and sending, by the camera module, a second request to a capture module to capture image data.
3. The method of claim 2, further comprising: receiving, by the camera module, the captured image data and the metadata from the capture module, wherein the metadata comprises at least timestamp information for each frame from the captured image data.
4. The method of claim 3, further comprising: sending, by the camera module, the captured image data and the metadata to the image data processing module and the content recording module.
5. The method of claim 1, wherein the augmented reality content data includes an augmented

reality identifier, an augmented reality content generator category, an augmented reality content generator carousel index, and a carousel group.

**6.** The method of claim 1, wherein the tracking data comprises a set of coordinates for a set of objects or a set of surface planes in the each frame, the set of coordinates corresponding to a subset of coordinates from a field of view from an eyewear device.

**7.** The method of claim 1, further comprising: predicting, by the rendering module, a predicted position to render AR content based at least in part on the tracking data from the set of composite AR content frames.

**8.** The method of claim 1, wherein the tracking data indicates a likelihood of the predicted position.

**9.** A system comprising: a processor; and a memory including instructions that, when executed by the processor, cause the processor to perform operations comprising: sending captured image data and metadata to a first set of computing processes for processing, the first set of computing processes comprising a content recording module; receiving, asynchronously from a second set of computing processes, second metadata; detecting a signal indicating a command to stop image data capturing; in response to the detected signal, generating a composite augmented reality (AR) content item based on the metadata and the captured image data, wherein generating the composite AR content item occurs without modifying a raw image format of the captured image data that results in a reduced image quality from the raw image format, wherein generating the composite AR content item comprises: encoding, by the content recording module, each frame from the captured image data to a second image data format different from the raw image format of the captured image data, each of the encoded frames including an associated timestamp indicating when the encoded frames were captured; providing the composite AR content item for rendering for display on an eyewear device, wherein the first set of computing processes further comprises an image data processing module, the second set of computing processes includes the image data processing module, and the metadata comprises a first set of timestamps corresponding to a first set of frames from the captured image data; generating, by the image data processing module for each frame from the captured image data, tracking data and augmented reality content data corresponding to a particular augmented reality content generator, the second metadata comprising the tracking data and the augmented reality content data; sending, the tracking data, the augmented reality content data, and timestamp information including at least a timestamp associated with the tracking data and the augmented reality content data of each frame to the content recording module; receiving, by the content recording module, second captured frames; receiving, by the content recording module, the tracking data, the augmented reality content data, and the timestamp information, wherein generating, by the content recording module, the composite AR content item, the generating further comprises: combining, based on matching timestamp information, a set of encoded frames with the tracking data and the augmented reality content data into a set of composite AR content frames, each composite AR content frame including a corresponding encoded frame, corresponding tracking data, corresponding augmented reality content data, and corresponding timestamp information, rendering, by a rendering module, AR content based on the corresponding tracking data and corresponding augmented reality content data, the rendering causing the AR content to be displayed within the corresponding encoded frame, and predicting, by the rendering module, a predicted position to render AR content based at least in part on the tracking data from the set of composite AR content frames, the tracking data indicating a likelihood of the predicted position.

**10.** The system of claim 9, wherein the operations further comprise: prior to sending captured image data and metadata to the first set of computing processes for processing: sending, by the image data processing module, a request to a camera module to initiate capturing of image data; and sending, by the camera module, a second request to a capture module to capture image data.

**11.** The system of claim 10, wherein the operations further comprise: receiving, by the camera module, the captured image data and the metadata from the capture module, wherein the metadata



comprises at least timestamp information for each frame from the captured image data.

**12.** The system of claim 11, wherein the operations further comprise: sending, by the camera module, the captured image data and the metadata to the image data processing module and the content recording module.

**13.** The system of claim 9, wherein the augmented reality content data includes an augmented reality identifier, an augmented reality content generator category, an augmented reality content generator carousel index, and a carousel group.

**14.** The system of claim 9, wherein the tracking data comprises a set of coordinates for a set of objects or a set of surface planes in the each frame, the set of coordinates corresponding to a subset of coordinates from a field of view from an eyewear device.

**15.** The system of claim 9, wherein the operations further comprise: predicting, by the rendering module, a predicted position to render AR content based at least in part on the tracking data from the set of composite AR content frames.

**16.** The system of claim 9, wherein the tracking data indicates a likelihood of the predicted position.

**17.** A non-transitory computer-readable medium comprising instructions, which when executed by a computing device, cause the computing device to perform operations comprising: sending captured image data and metadata to a first set of computing processes for processing, the first set of computing processes comprising a content recording module; receiving, asynchronously from a second set of computing processes, second metadata; detecting a signal indicating a command to stop image data capturing; in response to the detected signal, generating a composite augmented reality (AR) content item based on the metadata and the captured image data, wherein generating the composite AR content item occurs without modifying a raw image format of the captured image data that results in a reduced image quality from the raw image format, wherein generating the composite AR content item comprises: encoding, by the content recording module, each frame from the captured image data to a second image data format different from the raw image format of the captured image data, each of the encoded frames including an associated timestamp indicating when the encoded frames were captured; providing the composite AR content item for rendering for display on an eyewear device, wherein the first set of computing processes further comprises an image data processing module, the second set of computing processes includes the image data processing module, and the metadata comprises a first set of timestamps corresponding to a first set of frames from the captured image data; generating, by the image data processing module for each frame from the captured image data, tracking data and augmented reality content data corresponding to a particular augmented reality content generator, the second metadata comprising the tracking data and the augmented reality content data; sending, the tracking data, the augmented reality content data, and timestamp information including at least a timestamp associated with the tracking data and the augmented reality content data of each frame to the content recording module; receiving, by the content recording module, second captured frames; receiving, by the content recording module, the tracking data, the augmented reality content data, and the timestamp information, wherein generating, by the content recording module, the composite AR content item, the generating further comprises: combining, based on matching timestamp information, a set of encoded frames with the tracking data and the augmented reality content data into a set of composite AR content frames, each composite AR content frame including a corresponding encoded frame, corresponding tracking data, corresponding augmented reality content data, and corresponding timestamp information, rendering, by a rendering module, AR content based on the corresponding tracking data and corresponding augmented reality content data, the rendering causing the AR content to be displayed within the corresponding encoded frame, and predicting, by the rendering module, a predicted position to render AR content based at least in part on the tracking data from the set of composite AR content frames, the tracking data indicating a likelihood of the predicted position.

- 18.** The non-transitory computer-readable medium of claim 17, wherein the operations further comprise: prior to sending captured image data and metadata to the first set of computing processes for processing: sending, by the image data processing module, a request to a camera module to initiate capturing of image data; and sending, by the camera module, a second request to a capture module to capture image data.
- 19.** The non-transitory computer-readable medium of claim 18, wherein the operations further comprise: receiving, by the camera module, the captured image data and the metadata from the capture module, wherein the metadata comprises at least timestamp information for each frame from the captured image data.
- 20.** The non-transitory computer-readable medium of claim 19, wherein the operations further comprise: sending, by the camera module, the captured image data and the metadata to the image data processing module and the content recording module.
-