

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250251606

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Komanduri; Ravi Kumar et al.

TIME-MULTIPLEXED DISPLAY OF VIRTUAL CONTENT AT VARIOUS DEPTHS

Abstract

Techniques for operating an optical system are disclosed. World light may be linearly polarized along a first axis. When the optical system is operating in accordance with a first state, a polarization of the world light may be rotated by 90 degrees, the world light may be linearly polarized along a second axis perpendicular to the first axis, and zero net optical power may be applied to the world light. When the optical system is operating in accordance with a second state, virtual image light may be projected onto an eyepiece of the optical system, the world light and the virtual image light may be linearly polarized along the second axis, a polarization of the virtual image light may be rotated by 90 degrees, and non-zero net optical power may be applied to the virtual image light.

Inventors: Komanduri; Ravi Kumar (Austin, TX), Edwin; Lionel Ernest (Hollywood,, FL), Oh; Chulwoo (Sammamish, WA)

Applicant: Magic Leap, Inc. (Plantation, FL)

Family ID: 71521779

Assignee: Magic Leap, Inc. (Plantation, FL)

Appl. No.: 19/190186

Filed: April 25, 2025

Related U.S. Application Data

parent US continuation 18661157 20240510 parent-grant-document US 12313852 child US 19190186

parent US continuation PCT/US2020/013130 20200110 PENDING child US 17370882

parent US division 17370882 20210708 parent-grant-document US 12013537 child US 18661157

us-provisional-application US 62791441 20190111

Publication Classification

Int. Cl.: **G02B27/01** (20060101); **G02B5/30** (20060101); **G02B27/42** (20060101); **G06T19/00** (20110101); **H04N13/279** (20180101); **H04N13/344** (20180101)

U.S. Cl.:

CPC **G02B27/0172** (20130101); **G02B5/3083** (20130101); **G02B27/4261** (20130101); **G02B27/4272** (20130101); **G06T19/006** (20130101); **H04N13/279** (20180501); **H04N13/344** (20180501); **G02B2027/0118** (20130101); **G02B2027/0127** (20130101); **G02B2027/0138** (20130101); **G02B2027/014** (20130101)

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/661,157, filed May 10, 2024, entitled “TIME-MULTIPLEXED DISPLAY OF VIRTUAL CONTENT AT VARIOUS DEPTHS,” which is a divisional of U.S. patent application Ser. No. 17/370,882, filed Jul. 8, 2021, U.S. Pat. No. 12,013,537, issued Jun. 18, 2024, entitled “TIME-MULTIPLEXED DISPLAY OF VIRTUAL CONTENT AT VARIOUS DEPTHS,” which is a continuation of International Patent Application No. PCT/US2020/013130 filed Jan. 10, 2020, entitled “TIME-MULTIPLEXED DISPLAY OF VIRTUAL CONTENT AT VARIOUS DEPTHS,” which claims the benefit of and priority to U.S. Provisional Patent Application No. 62/791,441, filed Jan. 11, 2019, entitled “TIME-MULTIPLEXED DISPLAY OF VIRTUAL CONTENT AT VARIOUS DEPTHS,” the entire disclosures of which are hereby incorporated by reference, for all purposes, as if fully set forth herein.

BACKGROUND OF THE INVENTION

[0002] Modern computing and display technologies have facilitated the development of systems for so called “virtual reality” or “augmented reality” experiences, wherein digitally reproduced images or portions thereof are presented to a user in a manner wherein they seem to be, or may be perceived as, real. A virtual reality, or “VR,” scenario typically involves presentation of digital or virtual image information without transparency to other actual real-world visual input; an augmented reality, or “AR,” scenario typically involves presentation of digital or virtual image information as an augmentation to visualization of the actual world around the user.

[0003] Despite the progress made in these display technologies, there is a need in the art for improved methods, systems, and devices related to augmented reality systems, particularly, display systems.

SUMMARY OF THE INVENTION

[0004] The present disclosure relates generally to techniques for improving the performance and user experience of optical systems. More particularly, embodiments of the present disclosure provide systems and methods for operating an augmented reality (AR) device comprising adaptive lens assemblies and/or shutter elements for displaying virtual content at various depths. Although the present disclosure is described in reference to an AR device, the disclosure is applicable to a variety of applications in computer vision and image display systems. A summary of the present disclosure is provided below in reference to a series of examples.

[0005] Example 1 is a method of operating an optical system, the method comprising: receiving, at the optical system, light associated with a world object; linearly polarizing, by a world-side polarizer of the optical system, the light associated with the world object along a first axis; when

the optical system is operating in accordance with a first state: rotating, by a world-side switchable waveplate of the optical system, a polarization of the light associated with the world object by 90 degrees; linearly polarizing, by a user-side polarizer of the optical system, the light associated with the world object along a second axis perpendicular to the first axis; applying zero net optical power, by a lens assembly of the optical system, to the light associated with the world object; when the optical system is operating in accordance with a second state: projecting, by a projector of the optical system, light associated with a virtual image onto an eyepiece of the optical system; outcoupling, by the eyepiece, the light associated with the virtual image toward the user-side polarizer; linearly polarizing, by the user-side polarizer, the light associated with the world object and the light associated with the virtual image along the second axis; rotating, by a user-side switchable waveplate, a polarization of the light associated with the virtual image by 90 degrees; and applying non-zero net optical power, by the lens assembly, to the light associated with the virtual image; wherein the optical system is operating in accordance with the first state when the world-side switchable waveplate is electrically activated and the user-side switchable waveplate is not electrically activated; wherein the optical system is operating in accordance with the second state when the user-side switchable waveplate is electrically activated and the world-side switchable waveplate is not electrically activated; wherein the world-side polarizer is coupled to the world-side switchable waveplate; wherein the world-side switchable waveplate is coupled to the eyepiece at a world side of the eyepiece; wherein the user-side polarizer is coupled to the eyepiece at a user side of the eyepiece; wherein the lens assembly is coupled to the user-side polarizer; wherein the user-side switchable waveplate is positioned between two layers of the lens assembly.

[0006] Example 2 is an optical system comprising: a world-side polarizer configured to linearly polarize light associated with a world object along a first axis; a world-side switchable waveplate coupled to the world-side polarizer and configured to rotate a polarization of the light associated with the world object by 90 degrees when the optical system is operating in accordance with a first state; an eyepiece coupled to the world-side switchable waveplate; a projector configured to project light associated with a virtual image onto an eyepiece when the optical system is operating in accordance with a second state; a user-side polarizer coupled to the eyepiece and configured to: linearly polarize the light associated with the world object along a second axis perpendicular to the first axis when the optical system is operating in accordance with the first state; and linearly polarize the light associated with the world object and the light associated with the virtual image along the second axis when the optical system is operating in accordance with the second state; a lens assembly coupled to the user-side polarizer and configured to: apply zero net optical power to the light associated with the world object when the optical system is operating in accordance with the first state; and apply non-zero net optical power to the light associated with the virtual image when the optical system is operating in accordance with the second state; and a user-side switchable waveplate positioned between two layers of the lens assembly and configured to rotate a polarization of the light associated with the virtual image by 90 degrees when the optical system is operating in accordance with the second state.

[0007] Example 3 is a method of operating an optical system, the method comprising: receiving, at the optical system, light associated with a world object; linearly polarizing, by one or more world-side shutter elements of the optical system, the light associated with the world object along a first axis; when the optical system is operating in accordance with a first state: rotating, by the one or more world-side shutter elements, a polarization of the light associated with the world object by 90 degrees; linearly polarizing, by one or more user-side shutter elements of the optical system, the light associated with the world object along a second axis perpendicular to the first axis; when the optical system is operating in accordance with a second state: projecting, by a projector of the optical system, light associated with a virtual image onto an eyepiece of the optical system; linearly polarizing, by the one or more user-side shutter elements, the light associated with the world object

and the light associated with the virtual image along the second axis; and rotating, by the one or more user-side shutter elements, a polarization of the light associated with the virtual image by 90 degrees.

[0008] Example 4 is the method of example(s) 3, further comprising: applying zero net optical power, by a lens assembly of the optical system, to the light associated with the world object when the optical system is operating in accordance with the first state.

[0009] Example 5 is the method of example(s) 3, further comprising: applying non-zero net optical power, by a lens assembly of the optical system, to the light associated with the virtual image when the optical system is operating in accordance with the second state.

[0010] Example 6 is the method of example(s) 3, further comprising: outcoupling, by the eyepiece, the light associated with the virtual image toward the one or more user-side shutter elements when the optical system is operating in accordance with the second state.

[0011] Example 7 is the method of example(s) 3, wherein the one or more world-side shutter elements includes: a world-side polarizer; and a world-side switchable waveplate.

[0012] Example 8 is the method of example(s) 7, wherein the one or more user-side shutter elements includes: a user-side polarizer; and a user-side switchable waveplate.

[0013] Example 9 is the method of example(s) 8, wherein the optical system includes a lens assembly.

[0014] Example 10 is the method of example(s) 9, wherein the optical system is operating in accordance with the first state when the world-side switchable waveplate is electrically activated and the user-side switchable waveplate is not electrically activated.

[0015] Example 11 is the method of example(s) 9, wherein the optical system is operating in accordance with the second state when the user-side switchable waveplate is electrically activated and the world-side switchable waveplate is not electrically activated.

[0016] Example 12 is the method of example(s) 9, wherein the world-side polarizer is coupled to the world-side switchable waveplate.

[0017] Example 13 is the method of example(s) 9, wherein the world-side switchable waveplate is coupled to the eyepiece at a world side of the eyepiece.

[0018] Example 14 is the method of example(s) 9, wherein the user-side polarizer is coupled to the eyepiece at a user side of the eyepiece.

[0019] Example 15 is the method of example(s) 9, wherein the lens assembly is coupled to the user-side polarizer.

[0020] Example 16 is the method of example(s) 9, wherein the user-side switchable waveplate is positioned between two layers of the lens assembly.

[0021] Example 17 is an optical system comprising: one or more world-side shutter elements configured to: linearly polarize light associated with a world object along a first axis; and rotate a polarization of the light associated with the world object by 90 degrees when the optical system is operating in accordance with a first state; an eyepiece coupled to the one or more world-side shutter elements; a projector configured to project light associated with a virtual image onto the eyepiece when the optical system is operating in accordance with a second state; and one or more user-side shutter elements coupled to the eyepiece and configured to: linearly polarize the light associated with the world object along a second axis perpendicular to the first axis when the optical system is operating in accordance with the first state; linearly polarize the light associated with the world object and the light associated with the virtual image along the second axis when the optical system is operating in accordance with the second state; and rotate a polarization of the light associated with the virtual image by 90 degrees when the optical system is operating in accordance with the second state.

[0022] Example 18 is the optical system of example(s) 17, further comprising: a lens assembly coupled to the one or more user-side shutter elements.

[0023] Example 19 is the optical system of example(s) 18, wherein the lens assembly is configured

to apply zero net optical power to the light associated with the world object when the optical system is operating in accordance with the first state.

[0024] Example 20 is the optical system of example(s) 18, wherein the lens assembly is configured to apply non-zero net optical power to the light associated with the virtual image when the optical system is operating in accordance with the second state.

[0025] Example 21 is the optical system of example(s) 17, wherein the eyepiece is configured to outcouple the light associated with the virtual image toward the one or more user-side shutter elements when the optical system is operating in accordance with the second state.

[0026] Example 22 is the optical system of example(s) 17, wherein the one or more world-side shutter elements includes: a world-side polarizer; and a world-side switchable waveplate.

[0027] Example 23 is the optical system of example(s) 22, wherein the one or more user-side shutter elements includes: a user-side polarizer; and a user-side switchable waveplate.

[0028] Example 24 is the optical system of example(s) 23, wherein the optical system is operating in accordance with the first state when the world-side switchable waveplate is electrically activated and the user-side switchable waveplate is not electrically activated.

[0029] Example 25 is the optical system of example(s) 23, wherein the optical system is operating in accordance with the second state when the user-side switchable waveplate is electrically activated and the world-side switchable waveplate is not electrically activated.

[0030] Example 26 is the optical system of example(s) 23, wherein the world-side polarizer is coupled to the world-side switchable waveplate.

[0031] Example 27 is the optical system of example(s) 23, wherein the world-side switchable waveplate is coupled to the eyepiece at a world side of the eyepiece.

[0032] Example 28 is the optical system of example(s) 23, wherein the user-side polarizer is coupled to the eyepiece at a user side of the eyepiece.

[0033] Example 29 is the optical system of example(s) 23, wherein the lens assembly is coupled to the user-side polarizer.

[0034] Example 30 is the optical system of example(s) 23, wherein the user-side switchable waveplate is positioned between two layers of the lens assembly.

[0035] Example 31 is a display device comprising: a waveguide assembly configured to guide light in a lateral direction parallel to an output surface of the waveguide assembly, the waveguide assembly further configured to outcouple the guided light through the output surface; and an adaptive lens assembly disposed on a first side of the waveguide assembly, the adaptive lens assembly disposed to receive outcoupled light from the waveguide assembly and to be selectively switched between a plurality of states having different optical powers, wherein the adaptive lens assembly comprises a lens stack configured to exert polarization-dependent optical power to linearly polarized light, the lens stack comprising a birefringent lens and an isotropic lens contacting each other, wherein contacting surfaces of the birefringent lens and the isotropic lens form a conformal interface.

[0036] Example 32 is the display device of example(s) 31, further comprising: a second adaptive lens assembly disposed on a second side of the waveguide assembly opposite the first side, the second adaptive lens assembly configured to be selectively switched between a plurality of states having different optical powers and comprising: a second lens stack configured to exert polarization-dependent optical power to linearly polarized light, wherein the second lens stack comprises a second birefringent lens and a second isotropic lens contacting each other to form a conformal interface therebetween.

[0037] Example 33 is the display device of example(s) 32, wherein each of the first and second adaptive lens assemblies further comprises a switchable half waveplate comprising twisted nematic (TN) liquid crystals (LCs) optically coupled to a respective one of the lens stack or the second lens stack, wherein the switchable half waveplate is configured to preserve a polarization of linear polarized light passing therethrough when deactivated and to alter the polarization of linear

polarized light passing therethrough when activated.

[0038] Example 34 is the display device of example(s) 33, further comprising on a second side opposite the first side of the waveguide assembly: a shutter configured to temporally alternately block and pass light incident thereon; and a linear polarizer.

[0039] Example 35 is the display device of example(s) 34, wherein the waveguide assembly comprises cholesteric liquid crystals and configured to outcouple circularly polarized light.

[0040] Example 36 is the display device of example(s) 35, wherein the waveguide assembly is interposed by a pair of quarter waveplates.

[0041] Example 37 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is controllable to allow a variable amount of ambient light from an environment of the user to pass therethrough toward the user; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is controllable to impart a variable amount of optical power to light passing therethrough toward the user; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between two or more states comprising: a first state in which the shutter assembly is configured to allow a first amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a first amount of optical power to light passing therethrough; and a second state in which the shutter assembly is configured to allow a second amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a second amount of optical power to light passing therethrough, wherein the second amount of ambient light is less than the first amount of ambient light and the second amount of optical power is greater than the first amount of optical power.

[0042] Example 38 is the optical system of example(s) 37, wherein the first amount of ambient light comprises a maximum amount of ambient light from the environment of the user to which the shutter assembly is configured to allow to pass therethrough toward the user and the first amount of optical power comprises a minimum amount of optical power to which the adaptive lens assembly is configured to impart to light passing therethrough.

[0043] Example 39 is the optical system of any of example(s) 37 or 38, wherein, in the second state, the control circuitry is configured to cause the projector to emit light representing virtual content that is to be perceived by the user as being positioned at a first depth in front of the user.

[0044] Example 40 is the optical system of example(s) 39, wherein the control circuitry is configured to determine the second amount of ambient light and the second amount of optical power based on the first depth in front of the user at which virtual content is to be perceived by the user.

[0045] Example 41 is the optical system of example(s) 39, wherein, in the first state, the control circuitry is configured to cause the projector to emit light representing virtual content that is to be perceived by the user as being positioned at a second depth in front of the user, the second depth being greater than the first depth.

[0046] Example 42 is the optical system of example(s) 41, wherein the second depth is substantially equivalent to optical infinity.

[0047] Example 43 is the optical system of example(s) 39, wherein, in the first state, the control circuitry is configured to cause the projector to not emit light.

[0048] Example 44 is the optical system of any of example(s) 37 or 38, wherein the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between the two or more states at a rate greater than or equal to a minimum

switching frequency.

[0049] Example 45 is the optical system of example(s) 44, wherein the minimum switching frequency is 120 Hz.

[0050] Example 46 is the optical system of example(s) 44, further comprising: an ambient light sensor configured to measure an intensity of ambient light from the environment of the user; wherein the control circuitry is communicatively coupled to the ambient light sensor and further configured to determine the rate at which to cause the shutter assembly and the adaptive lens assembly to synchronously switch between the two or more states based on data received from the ambient light sensor.

[0051] Example 47 is the optical system of example(s) 38, wherein the minimum amount of optical power to which the adaptive lens assembly is configured to impart to light passing therethrough is about zero.

[0052] Example 48 is the optical system of any of the above examples, wherein the second amount of ambient light comprises a minimum amount of ambient light from the environment of the user to which the shutter assembly is configured to allow to pass therethrough toward the user and the second amount of optical power comprises a maximum amount of optical power to which the adaptive lens assembly is configured to impart to light passing therethrough.

[0053] Example 49 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is controllable to allow a variable amount of ambient light from an environment of the user to pass therethrough toward the user; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is controllable to impart a variable amount of optical power to light passing therethrough toward the user; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to synchronously: cause the adaptive lens assembly to vary the amount of optical power imparted to light passing therethrough toward the user; and cause the shutter assembly to vary the amount of ambient light from the environment of the user allowed to pass therethrough toward the user inversely with the amount of optical power imparted by the adaptive lens assembly to light passing therethrough.

[0054] Example 50 is the optical system of any of the above examples, wherein the at least one waveguide is further configured to allow ambient light from the environment of the user to pass therethrough toward the user.

[0055] Example 51 is the optical system of any of the examples above, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the environment of the user.

[0056] Example 52 is the optical system of any of the examples above, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the user.

[0057] Example 53 is the optical system of any of the examples above, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the adaptive lens assembly.

[0058] Example 54 is the optical system of any of the above examples, wherein the at least one waveguide comprises a plurality of waveguides.

[0059] Example 55 is a non-transitory computer-readable medium storing instructions that, when executed by one or more processors, cause the one or more processors to at least in part perform the methods of any of the above examples.

[0060] Example 56 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light

therefrom toward a user, a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is selectively switchable between different states in which the shutter assembly is configured to allow different amounts of ambient light from an environment of the user to pass therethrough toward the user, respectively; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is selectively switchable between different states in which the adaptive lens is configured to impart different amounts of wavefront divergence to light passing therethrough toward the user, respectively; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly.

[0061] Example 57 is the optical system of example 56, wherein the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between two or more states at a particular rate, the two or more states comprising: a first state in which the shutter assembly is configured to allow a first amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a first amount of wavefront divergence to light passing therethrough; and a second state in which the shutter assembly is configured to allow a second amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a second amount of wavefront divergence to light passing therethrough, wherein the second amount of ambient light is different from the first amount of ambient light and the second amount of wavefront divergence is different from the first amount of wavefront divergence.

[0062] Example 58 is the optical system of example 57, wherein the particular rate at which to cause the shutter assembly and the adaptive lens assembly to synchronously switch between the two or more states comprises a rate greater than or equal to a minimum switching frequency.

[0063] Example 59 is the optical system of examples 57 or 58 further comprising an ambient light sensor configured to measure an intensity of ambient light from the environment of the user, wherein the control circuitry is communicatively coupled to the ambient light sensor and further configured to determine the particular rate at which to cause the shutter assembly and the adaptive lens assembly to synchronously switch between the two or more states based on data received from the ambient light sensor.

[0064] Example 60 is the optical system of examples 58 or 59, wherein the minimum switching frequency is 120 Hz.

[0065] Example 61 is the optical system of example 57, wherein the first amount of ambient light comprises a maximum amount of ambient light from the environment of the user to which the shutter assembly is configured to allow to pass therethrough toward the user and the first amount of wavefront divergence comprises a minimum amount of wavefront divergence to which the adaptive lens assembly is configured to impart to light passing therethrough.

[0066] Example 62 is the optical system of any of examples 57 or 61, wherein, in the second state, the control circuitry is configured to cause the projector to emit light representing virtual content that is to be perceived by the user as being positioned at a first depth in front of the user.

[0067] Example 63 is the optical system of example 62, wherein the control circuitry is configured to determine at least one of the second amount of ambient light and the second amount of wavefront divergence based on the first depth in front of the user at which virtual content is to be perceived by the user.

[0068] Example 64 is the optical system of example 62, wherein, in the first state, the control circuitry is configured to cause the projector to emit light representing virtual content that is to be perceived by the user as being positioned at a second depth in front of the user, the second depth being greater than the first depth.

[0069] Example 65 is the optical system of example 64, wherein the second depth is substantially equivalent to optical infinity.

[0070] Example 66 is the optical system of example 62, wherein, in the first state, the control

circuitry is configured to cause the projector to not emit light.

[0071] Example 67 is the optical system of example 61, wherein the minimum amount of wavefront divergence to which the adaptive lens assembly is configured to impart to light passing therethrough is about zero.

[0072] Example 68 is the optical system of claim 57, wherein the second amount of ambient light is less than the first amount of ambient light and the second amount of wavefront divergence is greater than the first amount of wavefront divergence.

[0073] Example 69 is the optical system of any of the above examples, wherein the second amount of ambient light comprises a minimum amount of ambient light from the environment of the user to which the shutter assembly is configured to allow to pass therethrough toward the user and the second amount of wavefront divergence comprises a maximum amount of wavefront divergence to which the adaptive lens assembly is configured to impart to light passing therethrough.

[0074] Example 70 is the optical system of example 56, wherein the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between different states in a manner yielding an inverse relationship between the amount of ambient light from the environment of the user allowed by the shutter assembly to pass therethrough toward the user and the amount of wavefront divergence imparted by the adaptive lens assembly to light passing therethrough toward the user.

[0075] Example 71 is the optical system of example 56, wherein the control circuitry is configured to alternate between at least two different modes of operation comprising: a first mode of operation in which the control circuitry is configured to control a state of the shutter assembly and a state of the adaptive lens assembly in an asynchronous manner; and a second mode of operation in which the control circuitry is configured to control the state of the shutter assembly and the state of the adaptive lens assembly in a synchronous manner.

[0076] Example 72 is the optical system of example 71, wherein, in the second mode of operation, the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between two or more states comprising: a first state in which the shutter assembly is configured to allow a first amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a first amount of wavefront divergence to light passing therethrough; and a second state in which the shutter assembly is configured to allow a second amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a second amount of wavefront divergence to light passing therethrough, wherein the second amount of ambient light is different from the first amount of ambient light and the second amount of wavefront divergence is different from the first amount of wavefront divergence.

[0077] Example 73 is the optical system of example 71 further comprising one or more cameras configured to capture images of one or both of the user's eyes, wherein the control circuitry is communicatively coupled to the one or more cameras and further configured to alternate between the at least two different modes of operation based at least in part on data received from the one or more cameras.

[0078] Example 74 is the optical system of example 73, wherein the control circuitry is further configured to: determine a depth at which the user's eyes are fixated based on data received from the one or more cameras; and alternate between the at least two different modes of operation based at least in part on the depth at which the user's eyes are determined to be fixated.

[0079] Example 75 is the optical system of example 71, wherein the control circuitry is further configured to cause the projector to emit light representing virtual content.

[0080] Example 76 is the optical system of example 75, wherein the control circuitry is further configured to: determine whether an accommodation-vergence mismatch for the virtual content exceeds a threshold; and alternate between the at least two different modes of operation in response to a determination that the accommodation-vergence mismatch for the virtual content exceeds the

threshold.

[0081] Example 77 is the optical system of example 75, wherein the control circuitry is further configured to alternate between the at least two different modes of operation based at least in part on a depth in front of the user at which the virtual content is to be perceived by the user.

[0082] Example 78 is the optical system of example 71, wherein, in the first mode of operation, the control circuitry is configured to cause the state of at least one of the shutter assembly and the adaptive lens assembly to remain substantially fixed.

[0083] Example 79 is the optical system of any of the above examples, wherein the at least one waveguide is further configured to allow ambient light from the environment of the user to pass therethrough toward the user.

[0084] Example 80 is the optical system of any of the above examples, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the environment of the user.

[0085] Example 81 is the optical system of any of the above examples, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the user.

[0086] Example 82 is the optical system of any of the above examples, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the adaptive lens assembly.

[0087] Example 83 is the optical system of any of the above examples, wherein the at least one waveguide comprises a plurality of waveguides.

[0088] Example 84 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is selectively switchable between different states in which the shutter assembly is configured to allow different amounts of ambient light from an environment of the user to pass therethrough toward the user, respectively; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is selectively switchable between different states in which the adaptive lens is configured to impart different amounts of wavefront divergence to light passing therethrough toward the user, respectively; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between two or more states at a particular rate, the two or more states comprising: a first state in which the shutter assembly is configured to allow a first amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a first amount of wavefront divergence to light passing therethrough; and a second state in which the shutter assembly is configured to allow a second amount of ambient light from the environment of the user to pass therethrough toward the user and the adaptive lens assembly is configured to impart a second amount of wavefront divergence to light passing therethrough, wherein the second amount of ambient light is different from the first amount of ambient light and the second amount of wavefront divergence is different from the first amount of wavefront divergence.

[0089] Example 85 is the optical system of example 84, wherein the second amount of ambient light is less than the first amount of ambient light and the second amount of wavefront divergence is greater than the first amount of wavefront divergence.

[0090] Example 86 is the optical system of example 84, wherein the particular rate at which to cause the shutter assembly and the adaptive lens assembly to synchronously switch between the two or more states comprises a rate greater than or equal to a minimum switching frequency.

[0091] Example 87 is the optical system of example 84, wherein in the second state, the control circuitry is configured to cause the projector to emit light representing virtual content that is to be

perceived by the user as being positioned at a first depth in front of the user; and wherein the control circuitry is configured to determine at least one of the second amount of ambient light and the second amount of wavefront divergence based on the first depth in front of the user at which virtual content is to be perceived by the user.

[0092] Example 88 is the optical system of example 84, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the user.

[0093] Example 89 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is controllable to allow a variable amount of ambient light from an environment of the user to pass therethrough toward the user; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is controllable to impart a variable amount of wavefront divergence to light passing therethrough toward the user; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to synchronously: cause the adaptive lens assembly to vary the amount of wavefront divergence imparted to light passing therethrough toward the user; and cause the shutter assembly to vary the amount of ambient light from the environment of the user allowed to pass therethrough toward the user inversely with the amount of wavefront divergence imparted by the adaptive lens assembly to light passing therethrough.

[0094] Example 90 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is selectively switchable between different states in which the shutter assembly is configured to allow different amounts of ambient light from an environment of the user to pass therethrough toward the user, respectively; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is selectively switchable between different states in which the adaptive lens is configured to impart different amounts of wavefront divergence to light passing therethrough toward the user, respectively; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to cause the shutter assembly and the adaptive lens assembly to synchronously switch between different states in a manner yielding an inverse relationship between the amount of ambient light from the environment of the user allowed by the shutter assembly to pass therethrough toward the user and the amount of wavefront divergence imparted by the adaptive lens assembly to light passing therethrough toward the user.

[0095] Example 91 is an optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is selectively switchable between different states in which the shutter assembly is configured to allow different amounts of ambient light from an environment of the user to pass therethrough toward the user, respectively; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is selectively switchable between different states in which the adaptive lens is configured to impart different amounts of wavefront divergence to light passing therethrough toward the user, respectively; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to alternate between at least two different modes of operation comprising: a first mode of operation in which the control circuitry is configured to control a state of the shutter assembly and a state of the

adaptive lens assembly in an asynchronous manner; and a second mode of operation in which the control circuitry is configured to control the state of the shutter assembly and the state of the adaptive lens assembly in a synchronous manner.

[0096] Example 92 is a non-transitory computer-readable medium storing instructions that, when executed by one or more processors, cause the one or more processors to perform one or more of the operations performed by the control circuitry of any of the above examples.

[0097] Numerous benefits are achieved by way of the present disclosure over conventional techniques. Various embodiments described herein provide a compact, time-multiplexed display that can apply optical power to virtual image light so as to provide virtual content at various depths while at the same time leaving world light undistorted. Various embodiments described herein also provide adaptive lens assemblies that include a polarization-selective lens stack. In certain implementations, the polarization-selective lens stack comprises a birefringent lens, e.g., a Fresnel birefringent lens, and an isotropic lens contacting each other. Such assemblies can be compact (e.g., can have reduced thickness) and/or lightweight. These assemblies may potentially also provide various advantageous optical functionalities such as high bandwidth, increased switching speeds, reduced chromatic aberrations, increased ease of alignment, and/or variable optical power. Some embodiments of the disclosure provide for replacing the conventional front adaptive lens assembly with a shutter assembly, yielding smaller/lighter form factors and increased power savings. In addition, various embodiments described herein can provide adaptive lens assemblies with relatively low amount of leakage light that can otherwise lead to “ghost” images. Other benefits of the present disclosure will be readily apparent to those skilled in the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0098] FIG. 1 illustrates an augmented reality (AR) scene as viewed through a wearable AR device according to an embodiment described herein.

[0099] FIG. 2 illustrates an example of a display system comprising a pair of adaptive lens assemblies.

[0100] FIG. 3A illustrates an example of the display system of FIG. 2 displaying virtual content to a user at a virtual depth plane using an adaptive lens.

[0101] FIG. 3B illustrates an example of the display system of FIG. 2 providing a view of real world content to a user through adaptive lenses.

[0102] FIGS. 4A-4C illustrate one or more general features of an AR device according to the present disclosure.

[0103] FIG. 5 illustrates a schematic view of a wearable AR device according to the present disclosure.

[0104] FIG. 6A illustrates a cross-sectional view of an example polarization-selective lens stack comprising a birefringent lens and an isotropic lens.

[0105] FIG. 6B illustrates the polarization-selective lens stack of FIG. 6A in operation, passing therethrough linearly polarized light having a first polarization.

[0106] FIG. 6C illustrates the polarization-selective lens stack of FIG. 6A in operation, passing therethrough linearly polarized light having a second polarization.

[0107] FIG. 7A illustrates the polarization-selective lens stack of FIG. 6A with annotated parameters.

[0108] FIG. 7B illustrates cross-sectional and top down views of an example of a polarization-selective lens stack comprising a birefringent Fresnel lens and an isotropic lens.

[0109] FIG. 8A illustrates a cross-sectional view of an example adaptive lens assembly comprising a polarization-selective lens stack coupled with a switchable waveplate comprising twisted nematic

liquid crystals.

[0110] FIG. 8B illustrates the switchable waveplate comprising twisted nematic liquid crystals of adaptive lens assembly illustrated in FIG. 8A.

[0111] FIG. 9A illustrates a cross-sectional view of an example adaptive lens assembly comprising a first polarization-selective lens stack coupled with a first switchable waveplate comprising twisted nematic liquid crystals and a second polarization-selective lens stack coupled with a second switchable waveplate comprising twisted nematic liquid crystals.

[0112] FIGS. 9B-9E illustrate the example adaptive lens assembly of FIG. 9A in operation under different configurations configured to exert different optical powers.

[0113] FIG. 10 illustrates a cross-sectional view of an example display device comprising a waveguide assembly interposed between a first adaptive lens assembly and a second adaptive assembly each having a polarization-selective lens stack.

[0114] FIG. 11A illustrates a cross-sectional view of an example display device comprising a waveguide assembly interposed between a shutter and a linear polarizer on a first side and an adaptive assembly having a polarization-selective lens stack on a second side.

[0115] FIG. 11B illustrates the waveguide assembly of the display device of FIG. 11A, comprising cholesteric liquid crystals and configured to outcouple circularly polarized light.

[0116] FIG. 11C illustrates the example display device of FIG. 11A in operation, under configuration for viewing world images.

[0117] FIG. 11D illustrates the example display device of FIG. 11A in operation, under configuration for viewing virtual images.

[0118] FIG. 12A illustrates an example of a display device having a single adaptive lens assembly on the user side of an eyepiece, according to some embodiments of the present disclosure.

[0119] FIG. 12B illustrates an example of a display device operating in accordance with a first state, according to some embodiments of the present disclosure.

[0120] FIG. 12C illustrates an example of a display device operating in accordance with a second state, according to some embodiments of the present disclosure.

[0121] FIG. 13 illustrates a method of operating an optical system, according to some embodiments of the present disclosure.

[0122] FIG. 14 illustrates a method of operating an optical system, according to some embodiments of the present disclosure.

[0123] FIG. 15 illustrates an example performance of a method of operating an optical system, according to some embodiments of the present disclosure.

[0124] FIG. 16A illustrates an example of a display device operating in accordance with a first state, according to some embodiments of the present disclosure.

[0125] FIG. 16B illustrates an example of a display device operating in accordance with a second state, according to some embodiments of the present disclosure.

[0126] FIG. 16C illustrates an example of a display device operating in accordance with a third state, according to some embodiments of the present disclosure.

[0127] FIG. 17 illustrates a simplified computer system according to an embodiment described herein.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

[0128] Optical see through (OST) augmented reality (AR) devices can improve the virtual content being presented to a user by applying optical power to the virtual image light (i.e., light associated with a virtual image) using one or more adaptive lens assemblies arranged within the optical stack. One issue with such configurations is that optical power is necessarily also applied to the world light (i.e., light associated with a world object) passing therein, causing distortion of the perceived world object and thereby diminishing the user experience. Some embodiments described herein overcome these and other issues by providing various shutter elements arranged within the optical stack that may be sequentially activated to produce the result of world light being passed through

the AR device without distortion and virtual image light being imparted optical power from the adaptive lens assembly as needed.

[0129] FIG. 1 illustrates an AR scene as viewed through a wearable AR device according to an embodiment described herein. An AR scene **100** is depicted wherein a user of an AR technology sees a real-world park-like setting **106** featuring people, trees, buildings in the background, and a concrete platform **120**. In addition to these items, the user of the AR technology also perceives that he “sees” a robot statue **110** standing upon the real-world platform **120**, and a cartoon-like avatar character **102** flying by, which seems to be a personification of a bumble bee, even though these elements (character **102** and statue **110**) do not exist in the real world. Due to the extreme complexity of the human visual perception and nervous system, it is challenging to produce a virtual reality (VR) or AR technology that facilitates a comfortable, natural-feeling, rich presentation of virtual image elements amongst other virtual or real-world imagery elements.

[0130] FIG. 2 illustrates an example of a display device **200**, e.g., a wearable display device, comprising one or more adaptive lens assemblies including a polarization-selective lens stack, e.g., a pair of adaptive lens assemblies **204**, **208** in an optical path **216** that are interposed by a waveguide assembly **212**. As described herein, waveguide assembly **212** may include a waveguide configured to propagate light (e.g., visible light) under total internal reflection and to outcouple the light in an optical axis extending from (e.g., in a direction normal to) a light output surface of the waveguide (e.g., a major surface of the waveguide). The light may be outcoupled by a diffraction grating in some embodiments. Each of adaptive lens assemblies **204**, **208** may be configured to at least partially transmit outcoupled light therethrough. In the illustrated embodiments, each of adaptive lens assemblies **204**, **208** may be configured to receive outcoupled light from waveguide assembly **212** and to converge or diverge the outcoupled light in the optical axis direction. Each of adaptive lens assemblies **204**, **208** comprises a polarization-selective lens stack comprising a birefringent lens and an isotropic lens contacting each other, wherein contacting surfaces of the birefringent lens and the isotropic lens form a conformal interface therebetween. Each of adaptive lens assemblies **204**, **208** is configured to be selectively switched between a plurality of states having different optical powers. That is, each of adaptive lens assemblies **204**, **208** is configured to be selectively switched between a plurality of states in which the respective adaptive lens assembly is configured to impart different amounts of wavefront divergence or convergence to light passing therethrough. Each of adaptive lens assemblies **204**, **208** can further be configured to alter a polarization state of the outcoupled light passing therethrough when activated (e.g., electrically activated).

[0131] As used herein, an adaptive lens assembly refers to a lens assembly having at least one optical property that may be adjusted, e.g., reversibly activated and deactivated, using an external stimulus. Example optical properties that may be reversibly activated and deactivated include, among other properties, optical power (focal length), phase, polarization, polarization-selectivity, transmissivity, reflectivity, birefringence and diffraction properties, among other properties. In various embodiments, adaptive lens assemblies are capable of electrically varying the optical power and the polarization state of light passing therethrough.

[0132] In the illustrated embodiment, each of the pair of adaptive lens assemblies **204**, **208** is configured to be selectively switched between at least two states, where, in a first state each is configured to pass the outcoupled light therethrough without altering a polarization state thereof, while in a second state each is configured to alter the polarization state of the outcoupled light passing therethrough. For example, in the second state, each of adaptive lens assemblies **204**, **208** reverses the handedness of circularly polarized light, while in the first state, each of adaptive lens assemblies **204**, **208** preserves the handedness of circularly polarized light.

[0133] Still referring to FIG. 2, display device **200** may further comprise waveguide assembly **212** interposed between the pair of adaptive lens assemblies **204**, **208**. Each of waveguide assemblies **204**, **208** may be configured to propagate light under total internal reflection in a lateral direction

parallel to a major surface of the waveguide. Each of waveguide assemblies **204**, **208** may further be configured to outcouple the light, e.g., in a direction normal to the major surface of the waveguide.

[0134] Still referring to FIG. 2, a first adaptive lens assembly **204** of the pair of adaptive lens assemblies is disposed on a first side of waveguide assembly **212**, e.g., the side of the world observed by a user, and a second adaptive lens assembly **208** of the pair of lens assemblies is disposed on a second side of the waveguide assembly **212**, e.g., the side of the eye of the user. As described infra, the pair of adaptive lens assemblies **204**, **208** as configured provides to a user virtual content from waveguide assembly **212** at a plurality of virtual depth planes, as well the view of the real world. In some embodiments, there is little or no distortion due to the presence of the pair of adaptive lens assemblies **204**, **208**. The virtual content and the view of the real world are provided to the user upon activation of the first and second adaptive lens assemblies **204**, **208**, as described infra with respect to FIGS. 3A and 3B.

[0135] FIGS. 3A and 3B illustrate examples of display devices **300A**, **300B**, each comprising adaptive lens assemblies in operation to output image information to a user. Display devices **300A**, **300B** may correspond to the same display device at different times and/or in different states. In some embodiments, display devices **300A**, **300B** in unpowered states are structurally identical. Display device **300A** is used herein to describe outputting virtual image to the user, while display device **300B** is used herein to describe transmitting a real world image through the display device **300B** to the user. Display devices **300A**, **300B** include a pair of adaptive lens assemblies **204**, **208** that are configured to be electrically activated by, e.g., application of a voltage or a current. In some embodiments, in a deactivated state, e.g., when no voltage or current is applied, each of first and second adaptive lens assemblies **204**, **208** has a low, e.g., about zero, optical power. In some embodiments, in an activated state, e.g., when a voltage or a current is applied, first adaptive lens assembly **204** on the side of the world may provide a first net optical power ($P_{\text{sub.net1}}$) having a first sign, e.g., a positive optical power. When in an activated state, second adaptive lens assembly **208** on the side of the user may provide a second net optical power ($P_{\text{sub.net2}}$) having a second sign, e.g., a negative optical power. However, embodiments are not so limited, and in other embodiments, first and second adaptive lens assemblies **200A**, **200B** may provide the optical powers in the deactivated state while providing substantially zero power when activated.

[0136] FIG. 3A illustrates an example of the display system of FIG. 2 displaying virtual content to a user at a virtual depth plane **304**, according to some embodiments. As described supra, waveguide assembly **212** interposed between the pair of adaptive lens assemblies **204**, **208** comprises a waveguide configured to receive light containing virtual image information and propagate the light under total internal reflection. Waveguide assembly **212** is further configured to outcouple the light through, e.g., a diffraction grating, towards the eye of the user. The outcoupled light passes through user-side adaptive lens assembly **208** prior to entering the eye of the user. When activated, user-side adaptive lens assembly **208** has a second net optical power, $P_{\text{sub.net2}}$, which may have a negative value, such that the user sees the virtual image at a virtual depth plane **304**.

[0137] In some embodiments, the second net optical power $P_{\text{sub.net2}}$ may be adjusted electrically to adjust the second net optical power ($P_{\text{sub.net2}}$) of user-side adaptive lens assembly **208**, thereby adjusting the distance to virtual depth plane **304**. For example, as a virtual object “moves” closer and further relative to the eye of the user within a virtual three dimensional space, the second net optical power $P_{\text{sub.net2}}$ of user-side adaptive lens assembly **208** may be correspondingly adjusted, such that virtual depth plane **304** adjusts to track the virtual object. Thus, the user may experience relatively little or no accommodation/vergence mismatch beyond an acceptable threshold. In some embodiments, the magnitude of the distance to virtual depth plane **304** may be adjusted in discrete steps, while in some other embodiments, the magnitude of the distance to virtual depth plane **304** may be adjusted continuously.

[0138] FIG. 3B illustrates an example of the display system of FIG. 2 providing a view of real

world content to a user, according to some embodiments. When user-side adaptive lens assembly **208** is activated to have the second net optical power ($P_{\text{sub.net2}}$) to display the virtual content at virtual depth plane **304**, light from the real world passing through user-side adaptive lens assembly **208** may also be converged or diverged according to $P_{\text{sub.net2}}$ of the activated user-side adaptive lens assembly **208**. Thus, objects in the real world may appear out of focus or distorted.

[0139] To mitigate such distortion, according to embodiments, when activated, adaptive lens assemblies **204**, **208** may be configured to have optical powers having opposite signs. In some embodiments, light passing through adaptive lens assemblies **204**, **208** converges or diverges according to a combined optical power having a magnitude that is about a difference between magnitudes of first and second net optical powers $P_{\text{sub.net1}}$, $P_{\text{sub.net2}}$, of world-side and user-side adaptive lens assemblies **204**, **208**, respectively. In some embodiments, waveguide assembly **212** may also have optical power and adaptive lens assembly **208** may be configured to account for the distortions caused by both lens assembly **204** and waveguide assembly **212**. For example, the optical power of adaptive lens assembly **208** may be opposite in sign to the sum of the optical powers of adaptive lens assembly **204** and waveguide assembly **212**.

[0140] In some embodiments, world-side adaptive lens assembly **204** is configured to have the first net optical power $P_{\text{sub.net1}}$ that has a magnitude that is close to or the same as the magnitude of the second net optical power $P_{\text{sub.net2}}$ of user-side adaptive lens assembly **208** while having an opposite sign. As a result, when both of adaptive lens assemblies **204**, **208** are activated simultaneously, objects in the real world appear relatively unaffected by the optical power of user-side adaptive lens assembly **208** provided for displaying the virtual content.

[0141] In some embodiments, first adaptive lens assembly **204** may be configured such that when activated, the first net optical power $P_{\text{sub.net1}}$ dynamically matches the second net optical power $P_{\text{sub.net2}}$ of user-side adaptive lens assembly **208**. For example, as the second net optical power $P_{\text{sub.net2}}$ of user-side adaptive lens assembly **208** is adjusted to track moving virtual objects within the virtual three dimensional space, the first net optical power $P_{\text{sub.net1}}$ of world-side adaptive lens assembly **204** may be dynamically adjusted, such that the magnitude of the combined optical power $P = P_{\text{sub.net1}} + P_{\text{sub.net2}}$ may be kept less than a predetermined value. Thus, according to embodiments, the objects in the real world may be prevented from being unacceptably out of focus by compensating the second net optical power ($P_{\text{sub.net2}}$) of user-side adaptive lens assembly **208**, which may have a negative value, with the first net optical power ($P_{\text{sub.net1}}$) of world-side adaptive lens assembly **204**, such that the combined optical power $P = P_{\text{sub.net1}} + P_{\text{sub.net2}}$ remains small. As described in further detail below, in some implementations, a wearable display device may include a waveguide assembly and a user-side adaptive lens assembly that are functionally equivalent or similar to waveguide assembly **212** and user-side adaptive lens assembly **208**, respectively, but may not include a world-side adaptive lens assembly similar to that of world-side adaptive lens assembly **204**. Instead, as described in further detail below, in these implementations, the display device may include one or more shutter elements, and may be configured to control such one or more shutter elements in synchronization with the user-side adaptive lens in a manner such that objects in the real world are not rendered unacceptably out of focus by the optical power imparted by the user-side adaptive lens.

[0142] FIG. 4A illustrates one or more general features of an AR device **400** according to the present disclosure. As shown in FIG. 4A, AR device **400** includes an eyepiece **402** and an adaptive lens assembly **405**, which may be functionally equivalent or similar to waveguide assembly **212** and user-side adaptive lens assembly **208**, respectively, as described above. During operation, a projector **414** of AR device **400** may project virtual image light **423** (i.e., light associated with a virtual image) onto eyepiece **402**, which may cause a light field (i.e., an angular representation of virtual content) to be projected onto the user's retina in a manner such that the user perceives the corresponding virtual content as being positioned at some location within the user's environment. For example, the user may perceive character **102** as being positioned at or near a first virtual depth

and statue **110** as being positioned at or near a second virtual depth. While AR device **400** may include only one adaptive lens assembly **405** (e.g., positioned on the user side of eyepiece **402** i.e., the side of eyepiece **402** closest to the eye of the user), such an adaptive lens assembly may be capable of imparting a plurality of different non-zero optical powers to light passing therethrough. That is, adaptive lens assembly **405** may be capable of imparting a plurality of different amounts of at least one of wavefront divergence and collimation to light passing therethrough.

[0143] AR device **400** may also include one or more shutter elements **403** coupled to the world side of eyepiece **402** (the side of eyepiece **402** furthest from the eye of the user and closest to world objects **430**) and/or to the user side of eyepiece **402**. By sequentially electrically activating different elements/layers of shutter elements **403** as described herein, world light **432** associated with world objects **430** may pass through AR device **400** with zero net optical power being applied by lens assembly **405** and virtual image light **423** may pass through with non-zero (e.g., negative) net optical power being applied by lens assembly **405**. Example dimming components, which may represent or be included in shutter elements **403** and other shutter assemblies described herein, are described in U.S. Patent Application Publication No. 2020/0074724, filed Aug. 30, 2019, and International Patent Application No. PCT/US2019/051188, filed on Sep. 13, 2019, all of which are incorporated by reference herein in their entirety.

[0144] In some embodiments, AR device **400** may include an ambient light sensor **434** configured to detect world light **432**. Ambient light sensor **434** may be positioned such that world light **432** detected by ambient light sensor **434** is similar to and/or representative of world light **432** that impinges on AR device **400** (e.g., shutter elements **403**, eyepiece **402** and/or lens assembly **405**). In some embodiments, ambient light sensor **434** may be configured to detect a plurality of spatially-resolved light values corresponding to different pixels of the field of view of AR device **400**. In some embodiments, or in the same embodiments, ambient light sensor **434** may be configured to detect a global light value corresponding to an average light intensity or a single light intensity of world light **432**. Detected ambient light may be used by AR device **400** to determine a shuttering frequency at which AR device **400** alternates between operating in accordance with a first state or a second state. In some instances, the shuttering frequency may exceed the flicker fusion threshold, such that the shuttering may not be readily perceivable to the user. For example, the shuttering frequency may be at least 120 Hz (e.g., 160 Hz or 200 Hz).

[0145] FIG. 4B illustrates A R device **400** operating in accordance with a first state, according to some embodiments of the present disclosure. While operating in accordance with the first state, projector **414** is turned off and one or more of shutter elements **403** are electrically activated such that world light **432** passes through AR device **400** with zero net optical power being applied by lens assembly **405**. As will be shown below, this is accomplished using a world-side polarizer of shutter elements **403** to linearly polarize world light **432** along a first axis, a world-side switchable waveplate of shutter elements **403** to rotate a polarization of world light **432** by 90 degrees, and a user-side polarizer of shutter elements **403** to linearly polarize world light **432** along a second axis perpendicular to the first axis.

[0146] In some embodiments, one or more components of shutter elements **403** are considered to be subcomponents of lens assembly **405** (i.e., are considered to be included in lens assembly **405**). For example, the user-side polarizer of shutter elements **403** may be considered to be a subcomponent of lens assembly **405**. In such embodiments, when AR device **400** is operating in accordance with the first state, lens assembly **405** is considered to be switched, activated, and/or controlled into a state in which it applies zero optical power to light passing therethrough.

[0147] FIG. 4C illustrates A R device **400** operating in accordance with a second state, according to some embodiments of the present disclosure. While operating in accordance with the second state, projector **414** is turned on and one or more of shutter elements **403** are electrically activated such that world light **432** is completely or at least partially reduced, blocked, or dimmed, and virtual image light **423** passes through AR device **400** with non-zero net optical power being applied by

lens assembly **405**. As will be shown below, this is accomplished using a world-side polarizer of shutter elements **403** to linearly polarize world light **432** along a first axis, a user-side polarizer of shutter elements **403** to linearly polarize world light **432** and virtual image light **423** along a second axis perpendicular to the first axis, and a user-side switchable waveplate of shutter elements **403** to rotate a polarization of virtual image light **423** by 90 degrees.

[0148] Similar to that described in reference to FIG. 4B, in some embodiments, one or more components of shutter elements **403** are considered to be subcomponents of lens assembly **405** (i.e., are considered to be included in lens assembly **405**). For example, the user-side polarizer of shutter elements **403** may be considered to be a subcomponent of lens assembly **405**. In such embodiments, when AR device **400** is operating in accordance with the second state, lens assembly **405** is considered to be switched, activated, and/or controlled into a state in which it applies non-zero optical power to light passing therethrough. In some examples, (e.g., those described in reference to FIGS. 11C and 11D), a polarizing eyepiece may also be switched, activated, and/or controlled with each state such that the optical power applied to the light it outcouples may vary.

[0149] FIG. 5 illustrates a schematic view of a wearable AR device **500** according to the present disclosure. AR device **500** may include a left eyepiece **502A**, left shutter elements **503A**, and a left lens assembly **505A** arranged in a side-by-side configuration and a right eyepiece **502B**, right shutter elements **503B**, and a right lens assembly **505B** also arranged in a side-by-side configuration. In some embodiments, AR device **500** includes one or more sensors including, but not limited to: a left front-facing world camera **506A** attached directly to or near left eyepiece **502A**, a right front-facing world camera **506B** attached directly to or near right eyepiece **502B**, a left side-facing world camera **506C** attached directly to or near left eyepiece **502A**, a right side-facing world camera **506D** attached directly to or near right eyepiece **502B**, a left eye tracker positioned so as to observe a left eye of a user, a right eye tracker positioned so as to observe a right eye of a user, and an ambient light sensor **534**. In some embodiments, AR device **500** includes one or more image projection devices such as a left projector **514A** optically linked to left eyepiece **502A** and a right projector **514B** optically linked to right eyepiece **502B**.

[0150] Some or all of the components of AR device **500** may be head mounted such that projected images may be viewed by a user. In one particular implementation, all of the components of AR device **500** shown in FIG. 5 are mounted onto a single device (e.g., a single headset) wearable by a user. In another implementation, one or more components of a processing module **550** are physically separate from and communicatively coupled to the other components of AR device **500** by one or more wired and/or wireless connections. For example, processing module **550** may include a local module **552** on the head mounted portion of AR device **500** and a remote module **556** physically separate from and communicatively linked to local module **552**. Remote module **556** may be mounted in a variety of configurations, such as fixedly attached to a frame, fixedly attached to a helmet or hat worn by a user, embedded in headphones, or otherwise removably attached to a user (e.g., in a backpack-style configuration, in a belt-coupling style configuration, etc.).

[0151] Processing module **550** may include a processor and an associated digital memory, such as non-volatile memory (e.g., flash memory), both of which may be utilized to assist in the processing, caching, and storage of data. The data may include data captured from sensors (which may be, e.g., operatively coupled to AR device **500**) or otherwise attached to a user, such as cameras **506**, ambient light sensor **534**, eye trackers, microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, and/or gyros. For example, processing module **550** may receive image(s) **520** from cameras **506**. Specifically, processing module **550** may receive left front image(s) **520A** from left front-facing world camera **506A**, right front image(s) **520B** from right front-facing world camera **506B**, left side image(s) **520C** from left side-facing world camera **506C**, and right side image(s) **520D** from right side-facing world camera **506D**. In some embodiments, image(s) **520** may include a single image, a pair of images, a video comprising

a stream of images, a video comprising a stream of paired images, and the like. Image(s) 520 may be periodically generated and sent to processing module 550 while AR device 500 is powered on, or may be generated in response to an instruction sent by processing module 550 to one or more of the cameras. As another example, processing module 550 may receive ambient light information from ambient light sensor 534. As another example, processing module 550 may receive gaze information from the eye trackers. As another example, processing module 550 may receive image information (e.g., image brightness values) from one or both of projectors 514.

[0152] Eyepieces 502A, 502B may comprise transparent or semi-transparent waveguides configured to direct and outcouple light from projectors 514A, 514B, respectively. Specifically, processing module 550 may cause left projector 514A to output left virtual image light 522A onto left eyepiece 502A, and may cause right projector 514B to output right virtual image light 522B onto right eyepiece 502B. In some embodiments, each of eyepieces 502 may comprise a plurality of waveguides corresponding to different colors and/or different depth planes. In some embodiments, shutter elements 503 may be coupled to and/or integrated with eyepieces 502. For example, shutter elements 503 may be incorporated into a multi-layer eyepiece and may form one or more layers that make up one of eyepieces 502. In some embodiments, processing module may electrically activate shutter elements 503A, 503B using left shutter control signals 519A and right shutter control signals 519B, respectively. For example, processing module 550 may apply different voltages to shutter control signals 519 to cause AR device 500 to alternate between presenting world light and virtual image light to a user.

[0153] Cameras 506A, 506B may be positioned to capture images that substantially overlap with the field of view of a user's left and right eyes, respectively. Accordingly, placement of cameras 506 may be near a user's eyes but not so near as to obscure the user's field of view. Alternatively or additionally, cameras 506A, 506B may be positioned so as to align with the incoupling locations of virtual image light 522A, 522B, respectively. Cameras 506C, 506D may be positioned to capture images to the side of a user, e.g., in a user's peripheral vision or outside the user's peripheral vision. Image(s) 520C, 520D captured using cameras 506C, 506D need not necessarily overlap with image(s) 520A, 520B captured using cameras 506A, 506B.

Polarization-Selective Lens Stack Comprising Birefringent Lens and Isotropic Lens for Adaptive Lens Assemblies

[0154] Various embodiments described herein provide adaptive lens assemblies that include a polarization-selective lens stack. In certain implementations, the polarization-selective lens stack comprises a birefringent lens, e.g., a Fresnel birefringent lens, and an isotropic lens contacting each other. Such assemblies can be compact (e.g., can have reduced thickness) and/or lightweight. These assemblies may potentially also provide various advantageous optical functionalities such as high bandwidth, increased switching speeds, reduced chromatic aberrations, increased ease of alignment, and/or variable optical power. In addition, various embodiments described herein can provide adaptive lens assemblies with relatively low amount of leakage light that can otherwise lead to "ghost" images. According to various embodiments, adaptive assemblies comprise a polarization-selective lens stack comprising a birefringent lens and an isotropic lens, as described herein.

[0155] Referring to FIG. 6A, to provide images at a plurality of depth planes with high efficiency over a wide range of the visible spectrum, adaptive lens assemblies according to various embodiments include a polarization-selective lens stack 600 configured to exert polarization-dependent optical power to linearly polarized light. Polarization-selective lens stack 600 may comprise a birefringent lens 604 having an optic axis 602 extending in a lateral direction, e.g., x-direction or y-direction, perpendicular to the direction of light propagation, e.g., the z-direction. Birefringent lens 604 has a birefringence Δn . Birefringence Δn corresponds to a difference between an extraordinary refractive index $n_{\text{sub.e}}$ and an ordinary refractive index $n_{\text{sub.o}}$ of birefringent lens 604. Birefringent lens 604 can have a radius of curvature $R_{\text{sub.1}}$ such

that it is configured to exert a first optical power $p_{\text{sub}.1}$ to light passing therethrough and having a polarization direction parallel to the optic axis, and to exert a second optical power $p_{\text{sub}.2}$ to light passing therethrough and having a polarization direction perpendicular to the optic axis.

[0156] Polarization-selective lens stack **600** may additionally include an isotropic lens **608** having a refractive index $n_{\text{sub}.c}$, which has a second radius of curvature $R_{\text{sub}.2}$ such that it is configured to exert to light passing therethrough a third optical power $p_{\text{sub}.3}$ opposite in sign as the first optical power $p_{\text{sub}.1}$ and the second optical power $p_{\text{sub}.2}$.

[0157] In the illustrated embodiment, without limitation, the extraordinary refractive index $n_{\text{sub}.e}$ of isotropic lens **608** has substantially the same value as the ordinary refractive index $n_{\text{sub}.0}$ of birefringent lens **604**. However, it will be appreciated that the extraordinary refractive index $n_{\text{sub}.e}$ can be different from the ordinary refractive index $n_{\text{sub}.0}$ in some other embodiments.

[0158] In the illustrated embodiment, without limitation, the first radius of curvature $R_{\text{sub}.1}$ and the second radius of curvature $R_{\text{sub}.2}$ are substantially the same in magnitude R while having opposite signs. Furthermore, because $R_{\text{sub}.1}$ and $R_{\text{sub}.2}$ are substantially the same in magnitude, birefringent lens **604** and isotropic lens **608** make continuous contact along the interface having the radius of curvature R . That is, the contacting surfaces of birefringent lens **604** and isotropic lens **608** form a conformal interface therebetween.

[0159] With reference to FIG. 6B, polarization-selective lens stack **600** is illustrated in operation when an incident light **612**, e.g., linearly polarized light, has a direction of polarization that is parallel to the direction of optic axis **602**. Under this condition, because light passing through birefringent lens **604** experiences a refractive index corresponding to extraordinary refractive index $n_{\text{sub}.e}$ and light passing through isotropic lens **608** experiences a refractive index corresponding to ordinary refractive index $n_{\text{sub}.0}$, lens stack **600** exerts an optical power to the light that can be expressed as:

$$[00001] \varphi_1 = \frac{n_e - n_o}{R} = \frac{\Delta n}{R}$$

where R represents the magnitude of radii of birefringent lens **604** and isotropic lens **608**.

[0160] With reference to FIG. 6C, polarization-selective lens stack **600** is illustrated in operation when an incident light **616**, e.g., linearly polarized light, has a direction of polarization that is perpendicular to the direction of optical axis **602**. Under this condition, because light passing through birefringent lens **604** experiences a refractive index corresponding to ordinary refractive index $n_{\text{sub}.0}$, which is the same as the refractive index experienced by light passing through isotropic lens **608**, lens stack **600** exerts an optical power to the light that can be expressed as:

$$[00002] \varphi_1 = \frac{n_e - n_o}{R} \cong \frac{\Delta n}{R}$$

where R represents the magnitude radii of birefringent lens **604** and isotropic lens **608**.

[0161] Still referring to FIGS. 6A-6C, in some embodiments, isotropic lens **608** may be formed of an isotropic material, e.g., glass, acrylic, etc. On the other hand, birefringent lens **604** may be formed of or comprises a birefringent material, e.g., liquid crystals according to various embodiments. For example, birefringent lens **604** may comprise a transparent substrate e.g., a glass substrate, having formed thereon liquid crystal (LC) molecules that are elongated along a lateral direction (e.g., x-direction or y-direction) perpendicular to the light propagation direction (e.g., z-direction).

[0162] However, embodiments are not so limited and in other embodiments, birefringent lens **604** may be formed of or comprises a suitable birefringent material other than LCs. For example, birefringent lens **604** may comprise, e.g., BaB₂O₄, Be₃Al₂(SiO₃)₆, CaCO₃, LiNbO₃, TiO₂, SiC, tourmaline and ZrSiO₄ to name a few.

Polarization-Selective Lens Stack Comprising a Birefringent Fresnel Lens and Isotropic Lens for Adaptive Lens Assemblies

[0163] As described above with respect to FIGS. 6A-6C, a lens stack comprising a birefringent lens, e.g., LC-based birefringent lens, and an isotropic lens can provide polarization-selective

lensing effect. In the following, a polarization-selective lens stack comprising a liquid crystal-based birefringent lens configured as a Fresnel lens is described.

[0164] A Fresnel lens can for example comprise a thin-plate type of lens, which comprises fractional prismatic structures formed by breaking a conventional curved (e.g., spherical) lens into a set of sections, e.g., concentric annular sections, known as Fresnel zones. The Fresnel zones replace the continuous curvature of a continuous refractive lens with a set of surfaces of the same shape having discontinuities between them. A substantial reduction in thickness can be achieved by employing such fractional sections and lenses with a relatively large aperture can be manufactured using a smaller volume of material.

[0165] FIG. 7A illustrates a cross-sectional side view of lens stack **600** described above with respect to FIGS. 6A-6C, annotated with relevant optical dimensions including the distance R to a given location on birefringent lens **604** from the focal point, the radial distance A to the given location from a central axis (e.g., optical axis) of lens stack **600**, the angle θ defined by the distances R and A, and the thickness d of the curved portion of birefringent lens **604**. As described above, in various implementations, because birefringent lens **604** and isotropic lens **608** have substantially the same radius of curvature, birefringent lens **604** and isotropic lens **608** make continuous contact along the interface formed therebetween having the radius of curvature R.

[0166] FIG. 7B illustrates a cross-sectional side view **700A** (top) and a top down view **700B** (bottom) of a lens stack **700** comprising a birefringent Fresnel lens **704** and a counterpart lens, e.g., an isotropic Fresnel lens **708**. By employing the Fresnel lens **704**, the groove thickness d' of the curved portion of birefringent lens **704** can be substantially reduced. Despite the substantially reduced thickness d', lens stack **700** has a corresponding curvature such as effective radius of curvature R corresponding to the actual radius of curvature R of the conventional lens illustrated with respect to FIG. 7A. Accordingly, while not illustrated, lens stack **700A** additionally has a radial distance A.sub.k of a given Fresnel zone or a groove **706** from a central axis of lens stack **700** and the angle θ defined by the distances R and A.sub.k. In some implementations such as shown in FIG. 7B, despite the grooves separating the Fresnel zones, birefringent Fresnel lens **704** and isotropic lens **708** make continuous contact throughout the interface formed therebetween having the effective radius of curvature R. In some embodiments, successive Fresnel zones in the radially outward direction can have different radial distances A.sub.k and different distances between adjacent grooves **706**. For example, in the illustrated embodiment, the distances between adjacent Fresnel zones become smaller in the radially outward direction of birefringent Fresnel lens **704**. However, embodiments are not so limited and in other embodiments, the radial distances A.sub.k of successive Fresnel zones can increase linearly with constant distances between adjacent Fresnel zones while having different groove thicknesses within each zone to provide similar or same optical effects as the illustrated embodiment.

[0167] Referring to FIG. 7B (bottom), the illustrated birefringent Fresnel lens **704** comprises a plurality of concentric Fresnel zones according to some embodiments. The birefringent Fresnel lens **704** has a plurality of grooves **716** forming boundaries of Fresnel zones **712** at distances from the central axis represented by radii A.sub.k. According to various embodiments, the groove thickness d' of the birefringent lens **704** is designed such that the path length is a multiple of the design wavelength λ . This arrangement can create a 2 nm phase jump between the zones that leads to the same wavefront. The value of d' can be chosen (e.g., optimized) to balance fabrication tolerances and to reduce or minimize aberrations that can arise from sharp edges of grooves **716**. In one example, the radius R, of the k.sup.th Fresnel zone can be calculated by setting the thickness of the curved region to be kd', by the following equation:

$$[00003] A_k = \sqrt{\frac{2\Delta n f k m \lambda}{n_o}} - \left(\frac{k m \lambda}{n_o}\right)^2$$

where k represents the number of the Fresnel zone counting from the center of the lens, and where the groove thickness d' is constant across the surface of the illustrated birefringent Fresnel lens **704**.

[0168] In some embodiments, birefringent Fresnel lens **704** includes LCs. The LC molecules may be laterally aligned, or have elongation directions extending, substantially in a lateral direction **720** indicated by the arrow (e.g., y direction). In addition, the alignment directions of the LC molecules may be substantially homogenous throughout the thickness of birefringent Fresnel lens **704** without undergoing rotation. That is, the local director n of the LC molecules may be substantially constant laterally across the area and vertically across the thickness (e.g., in z direction) of the birefringent Fresnel lens **704**. The illustrated alignment may be suitable, e.g., for providing polarization selectivity for linearly polarized light. In these embodiments, linearly polarized light having polarization direction that is parallel to the direction of LC alignment (e.g., y direction) may experience one of $n_{\text{sub.e}}$ or $n_{\text{sub.o}}$, while linearly polarized light having polarization direction that is perpendicular to the direction of LC alignment (e.g., x direction) may experience the other of $n_{\text{sub.e}}$ or $n_{\text{sub.o}}$. As a result, lens stack **700** exerts an optical power of $\Delta n/R$ for light having one linear polarization while exerting a substantially zero optical power for light having the other linear polarization, as described above.

[0169] In various embodiments herein and throughout the specification, the birefringent Fresnel lens **704** can have an average, a local, a mean, a median, a maximum or a minimum birefringence Δn of 0.05-0.10, 0.15-0.20, 0.20-0.25, 0.25-0.30, 0.30-0.35, 0.35-0.40, 0.40-0.45, 0.45-0.50, 0.50-0.55, 0.55-0.60, 0.60-0.65, 0.65-0.70, or any value within any range defined by any of these values, for instance 0.05-0.40. In addition, birefringent Fresnel lens **704** can have a within-layer birefringence (Δn) range of 0.01-0.05, 0.05-0.10, 0.15-0.20, 0.20-0.25, 0.25-0.30, 0.30-0.35, 0.35-0.40, or any value within any range defined by any of these values.

[0170] In various embodiments herein and throughout the specification, birefringent Fresnel lens **704** has a thickness of about 0.1 μm -200 μm , 0.1-5 μm , 5-50 μm , 50-100 μm , 100-150 μm , 150-200 μm , or a value within any range defined by these values, for instance 5-200 μm .

Adaptive Lens Assemblies Comprising Polarization-Selective Lens Stack Coupled with Switchable Waveplate

[0171] To provide images at a plurality of depth planes with high efficiency over a wide range of the visible spectrum, adaptive lens assemblies according to various embodiments include a polarization-selective lens stack (e.g., **600** in FIGS. 6A-6C, **700** in FIG. 7B) comprising a birefringent lens and an isotropic lens. According to various embodiments, adaptive lens assemblies can be selectively switched between a plurality of states with different optical powers. In the following, adaptive lens assemblies are disclosed, in which the selective switching is performed by activating or deactivating a switchable waveplate coupled to a polarization-selective lens included in the adaptive lens assembly according to embodiments.

[0172] Referring to FIG. 8A, in some embodiments, an adaptive lens assembly **800A** is configured to be activated or deactivated by employing a switchable waveplate **804** comprising LCs in the same optical path as polarization-selective lens stack **700** described above comprising birefringent Fresnel lens **704** and isotropic lens **708**. Fresnel lens **704** may be formed using LCs or other birefringent materials. Adaptive lens assembly **800A** may be selectively switched between different states by electrically activating and deactivating switchable waveplate **804** (or otherwise changing the states of the waveplate, e.g., by applying different voltages). One example of the switchable waveplate **804** is illustrated with respect to FIG. 8B.

[0173] Referring to FIG. 8B, in some embodiments, switchable waveplate **802** may be a half waveplate or a polarization rotator comprising a layer **802** of unpolymerized twisted nematic (TN) liquid crystals (LCs), or reactive mesogens (RM) comprising TN LC molecules, which is configured to be switched upon application of an electric field across a thickness of layer **802** of TN LCs. Layer **802** of TN LCs is disposed between a pair of transparent substrates **812**. Each of transparent substrates **812** has formed on the inner surface a conducting transparent electrode **816**, **820**. In some embodiments, transparent electrodes **816**, **820** may serve as substrates, and one or both of substrates **812** may be omitted.

[0174] The surfaces of transparent electrodes **816**, **820** and/or substrates **812** may be configured such that the TN LC molecules in contact with or immediately adjacent to upper electrode **816** tend to orient with their long axes extending in a first lateral direction, while the TN LC molecules in contact with or immediately adjacent to lower electrode **820** tend to orient with their long axes extending in a second lateral direction, which may cross, e.g., to form an angle of about 90 degrees relative to, the first lateral direction. Accordingly, the TN LC molecules between electrodes **816**, **820** undergo a twist.

[0175] Still referring to FIG. **8B** (left), in operation, in the absence of an electric field (deactivated state) across TN LC layer **802**, the nematic director of the TN LC molecules undergoes a smooth 90 degree twist across the thickness of TN LC layer **802**. As illustrated, incident light **808** polarized in a first direction (same direction as the LC molecules closest to lower electrodes **812**) is incident on the TN LC layer **802**. The twisted arrangement of the TN LC molecules within TN LC layer **802** serves as an optical wave guide and rotates the plane of polarization by a quarter turn (90 degrees) prior to the light reaching upper electrodes **816**. In this state, TN LC layer **802** serves to shift the polarization direction of linearly polarized light passing therethrough from one linear polarization direction to another. Thus, transmitted light **806A** is polarized in a second direction (same direction as the LC molecules closest to upper electrodes **816**) opposite the first direction.

[0176] On the other hand, when a voltage exceeding a threshold voltage ($V > V_{th}$) of TN LC switchable waveplate **804** is applied to across electrodes **816**, **820** (right, activated state), the TN LC molecules within TN LC layer **802** tend to align with the resulting electric field and the optical wave guiding property of TN LC layer **802** described above with respect to the deactivated state is lost. In this state, TN LC layer **802** serves to preserve the polarization direction of light passing therethrough. Thus, incident light **808** and transmitted light **806B** are polarized in the same first direction (same direction as the LC molecules closest to lower electrodes **820**). When the electric field is turned off, the TN LC molecules relax back to their twisted state and the TN LC molecules of TN LC layer **802** in the activated state returns to the configuration of TN LC molecules of TN LC layer **802** in the deactivated state (left).

[0177] Still referring to FIG. **8A**, in operation, as described above, polarization-selective lens stack **700** exerts a lens power to incident light **820** passing therethrough depending on the polarization direction of incident light **820**. After having or not having exerted optical power thereto, depending on the relative polarization direction of the incident light, the light is incident on switchable waveplate **804**. As described above, the LCs of switchable waveplate **804** are configured such that, when activated, e.g., electrically activated, the polarization of a linearly polarized light passing therethrough is preserved, while when deactivated, e.g., electrically deactivated, the polarization of the linearly polarized light passing therethrough is altered, e.g., flipped or rotated. That is, a linearly vertical polarized (LVP) light beam is converted to a linearly horizontal polarized (LHP) light beam and vice versa, or the polarization is preserved, depending on whether switchable waveplate **804** is activated or deactivated.

[0178] In operation, the LCs of birefringent Fresnel lens **704** are configured such that, when the polarization direction of linearly polarized incident light **820** is parallel to the optic axis of birefringent Fresnel lens **704**, polarization-selective lens stack **700** exerts an optical power thereto, as described above with respect to FIG. **6B**, while when the polarization direction of linearly polarized incident light **820** is perpendicular to the optic axis, polarization-selective lens stack **700** exerts substantially zero optical power thereto, as described above with respect to FIG. **6C**. After passing through birefringent lens stack **700**, when activated, e.g., electrically activated, the polarization of a linearly polarized light passing through the switchable waveplate **804** is preserved, while when deactivated, e.g., electrically deactivated, the polarization of the linearly polarized light passing through switchable waveplate **804** is flipped or rotated, due to rearrangement of liquid crystal molecules.

[0179] With respect to FIGS. **8A-8B**, adaptive lens assemblies comprising a passive polarization-

selective lens stack coupled with a waveplate (FIG. 8A) for switchably exerting lens power have been described. The inventors have recognized that, by arranging a plurality of such elements, adaptive lens assemblies having a plurality of different lens powers can be formed. Thus, in the following, embodiments of adaptive waveplate lens assemblies comprising a plurality of passive polarization-selective lens stacks coupled with waveplates are disclosed. Such adaptive lens assemblies may be integrated with a waveguide either on the user side or the world side, to form display devices described with respect to, e.g., FIGS. 3A and 3B.

[0180] FIG. 9A illustrates an example of an adaptive lens assembly **900** comprising a plurality of passive polarization-selective lens stacks and a plurality of waveplates that are alternatingly arranged to exert a plurality, e.g., at least four, possible optical powers to light passing therethrough. Adaptive lens assembly **900** comprises, in the order of light passing therethrough, a first switchable waveplate (HWP1) **804-1**, e.g., a half waveplate, a first polarization-selective lens stack (L1) **700-1**, a second switchable waveplate (HWP2) **804-2**, e.g., a half waveplate, and a second polarization-selective lens stack (L2) **700-2**. Each of HWP1 **804-1** and HWP2 **804-2** is configured in a manner similar to that described above with respect to FIGS. 8A and 8B. In addition, each of L1 **700-1** and L2 **700-2** is configured in a similar manner to that described above with respect to FIGS. 6A-6C, 7A-7B and 8A-8B. However, first and second polarization-selective lens stacks **700-1**, **700-2** have different optic axes, different curvature (e.g., effective radii of curvature) and/or different birefringence. That is, L1 **700-1** has a first optic axis (extending in a vertical or y direction) and is configured to exert a first optical power $\phi_{\text{sub.1}}$ of $\Delta n_{\text{sub.1}}/R_{\text{sub.1}}$ or substantially zero to light incident thereon having a polarization direction parallel or perpendicular to the optic axis, respectively, while the **700-2** has a second optic axis (extending in a horizontal or x-axis) and is configured to exert a second optical power $\phi_{\text{sub.2}}$ of $\Delta n_{\text{sub.2}}/R_{\text{sub.2}}$ or substantially zero to light incident thereon having a polarization direction parallel or perpendicular to the optic axis, respectively.

[0181] FIGS. 9B-9E illustrate the adaptive lens assembly **900** in operation, for incident light **820** having a polarization parallel to the optic axis of L1 **700-1**, at four different states corresponding to HWP1 **804-1**/HWP **804-2** being deactivated (OFF)/deactivated (OFF) (FIG. 9B), activated (ON)/activated (ON) (FIG. 9C), OFF/ON (FIG. 9D), and ON/OFF (FIG. 9E). As described above, each of HWP1 **804-1** and HWP2 **804-2** can be turned OFF and ON, or deactivated and activated, by removing and applying a voltage across the TN LC layer. Each of HWP1 **804-1** and HWP2 **804-2** is configured to alter a polarization state, e.g., rotate or invert a polarization state, of light passing therethrough when electrically deactivated (OFF), while being configured to substantially pass light without altering the polarization state of light passing therethrough when activated (ON). The electrical signal, e.g., a current signal or a voltage signal, for switching each of HWP1 **804-1** and HWP2 **804-2** may be provided by a switching circuit (not shown) electrically connected thereto. For illustrative purposes, in the following, both HWP1 **804-1** and HWP2 **804-2** are TN LC cells having optic axes along the y and x directions at their two substrates respectively, similar to FIG. 8B. In the illustrated embodiment, the incident light **820** has a polarization parallel to y direction, i.e., a linear vertical polarization (LVP). However, it will be appreciated that the polarization axis of incident light **820** can be polarized in a different direction, a linear horizontal polarization (LHP), to achieve the different optical power states.

[0182] Referring to FIG. 9B, each of HWP1 **804-1** and HWP2 **804-2** are in the OFF state and configured to rotate the polarization of linearly polarized light having one of LVP and LHP into linearly polarized having the other of LVP and LHP. Thus, incident light **820** having LHP, upon passing through HWP1 **804-1**, is converted to light **824** incident on L1 **700-1** having LHP, which exerts substantially zero optical power ($\phi_{\text{sub.1}}=0$) due to the relative orthogonal orientations between the polarization of light **824** and the optic axis of the L1 **700-1**. Thereafter, light **828** having LHP incident on HWP2 **804-2** is converted to light **832** having LVP. L2 **700-2** exerts substantially zero optical power ($\phi_{\text{sub.2}}=0$) due to the relative orthogonal orientations between the

polarization of L2 700-2 and the optic axis of L2 700-2. In sum, adaptive lens assembly 900 exerts a net power $\phi_{\text{sub.1}} + \phi_{\text{sub.2}}$ equal to about zero to the incident light 820 having LVP and does not alter its polarization, thereby outputting light 836 having LVP.

[0183] Referring to FIG. 9C, each of HWP1 804-1 and HWP2 804-2 are in the ON state and configured to preserve the polarization of linearly polarized light passing therethrough. Thus, the polarization of incident light 820 having LVP, upon passing through HWP1 804-1, is preserved into light 824 incident on L1 700-1, which exerts an optical power ($\phi_{\text{sub.1}}$) due to the relative parallel orientations between the polarization of light 824 and the optical axis of L1 700-1. Thereafter, the polarization of light 828 having LVP incident on HWP2 802-2 is preserved into light 832. L2 700-2 exerts substantially zero optical power ($\phi_{\text{sub.2}}=0$) due to the relative orthogonal orientations between the polarization of light 832 and the optic axis of L2 700-2. In sum, adaptive lens assembly 900 exerts a net power $\phi_{\text{sub.1}} + \phi_{\text{sub.2}}$ equal to about $\phi_{\text{sub.1}}$ to incident light 820 having LVP and outputs light 836 having LVP.

[0184] Referring to FIG. 9D, HWP1 804-1 is in the OFF state and configured to rotate the polarization of linearly polarized light having one of LVP and LHP into linearly polarized having the other of LVP and LHP, while HWP2 804-2 is in the ON state and configured to preserve the polarization of linearly polarized light. Thus, incident light 820 having LVP, upon passing through HWP1 804-1, is converted to light 824 incident on L1 700-1 having LHP, which exerts substantially zero optical power ($\phi_{\text{sub.1}}=0$) due to the relative orthogonal orientations between the polarization of light 824 and the optic axis of L1 700-1. Thereafter, the polarization of light 828 having LHP passing through HWP2 802-2 is preserved into light 832. The light 832 incident on L2 700-2 has LHP, which exerts an optical power ($\phi_{\text{sub.2}}$) due to the relative parallel orientations between the polarization of light 832 and the optic axis of L2 700-2. In sum, adaptive lens assembly 900 exerts a net power $\phi_{\text{sub.1}} + \phi_{\text{sub.2}}$ equal to about $\phi_{\text{sub.2}}$ to incident light 820 having LVP and outputs light 836 having LHP.

[0185] Referring to FIG. 9E, HWP1 804-1 is in the ON state and configured to preserve the polarization of linearly polarized light, while HWP2 804-2 is in the OFF state and is configured to rotate the polarization of linearly polarized light having one of LVP and LHP into linearly polarized having the other of LVP and LHP. Thus, the polarization of incident light 820 having LVP, upon passing through HWP1 804-1, is preserved into light 824 incident on L1 700-1 having LVP, which exerts an optical power ($\phi_{\text{sub.1}}$) due to the relative parallel orientations between the polarization of light 824 and the optic axis of L1 700-1. Thereafter, light 828 having LVP passing through HWP2 804-2 is converted into light 832 having LHP. L2 700-2 exerts an optical power ($\phi_{\text{sub.2}}$) due to the relative parallel orientations between the polarization of light 832 and the optic axis of L2 700-2. In sum, adaptive lens assembly 900 exerts a net power $\phi_{\text{sub.1}} + \phi_{\text{sub.2}}$ to incident light 820 having LVP and outputs light 836 having LHP.

[0186] Thus, as illustrated by FIGS. 9A-9E, for light with linear polarization, four possible net powers (0, $\phi_{\text{sub.1}}$, $\phi_{\text{sub.2}}$, and $\phi_{\text{sub.1}} + \phi_{\text{sub.2}}$) can be exerted on the light passing through the adaptive lens assembly 900. By way of a numerical example, for $\phi_{\text{sub.1}}=0.75$ D and $\phi_{\text{sub.2}}=1.5$ D for the design wavelength, net optical powers of 0, 0.75 D, 1.5 D, and 2.25 D can be obtained using adaptive lens assembly 900.

[0187] Still referring to FIGS. 9A-9E in conjunction with FIGS. 3A and 3B, in the illustrated embodiment, incident light 820 may represent a light beam incident on either world-side adaptive lens assembly 204 or user-side adaptive lens assembly 208. By placing adaptive lens assembly 900 on either or both sides, display systems described above, e.g., with respect to FIGS. 3A and 3B, can be implemented, according to various embodiments as described herein.

Display Devices Including Adaptive Lens Assemblies Having Polarization-Selective Lens Stack Coupled to Nonpolarizing Waveguide Assembly

[0188] In the following example implementations, an adaptive lens assembly comprising a plurality of switchable polarization-selective lens stacks (e.g., adaptive lens assembly 900, FIGS. 9A-9E)

has been integrated into a display device, such as for example, a display device such as described supra with respect to FIGS. 2, 3A, and 3B.

[0189] FIG. 10 illustrates an example display device **1000** including a waveguide assembly **1012** interposed between a first or front adaptive lens assembly (FLA) **1004** and a second or back adaptive lens assembly (BLA) **1008**. Display device **1000** can be similar to display devices **300A**, **300B** described above with respect to FIGS. 3A and 3B. In the illustrated embodiment, BLA **1008** is configured similarly to adaptive lens assembly **900** described above with respect to FIGS. 9A-9E, and includes a first switchable waveplate (HWP1) **804-1**, a first polarization-selective lens stack (L1) **700-1**, a second switchable waveplate (HWP2) **804-2** and a second polarization-selective lens stack (L2) **700-2**. First and second polarization-selective lens stacks **700-1**, **700-2** have different, e.g., orthogonal optic axes, curvature (e.g., effective radii of curvature) and/or different birefringence, such that L1 **700-1** is configured to exert a first optical power $\phi_{\text{sub.1}}$ of $n_{\text{sub.1}}/R_{\text{sub.1}}$ or substantially zero for light incident thereon having a polarization direction parallel or perpendicular to the optic axis, respectively, while L2 **700-2** is configured to exert a second optical power $\phi_{\text{sub.2}}$ of $n_{\text{sub.2}}/R_{\text{sub.2}}$ or substantially zero for light incident thereon having a polarization direction parallel or perpendicular to the optic axis, respectively.

[0190] FLA **1004** includes a third switchable waveplate (HWP3) **804-3**, a third polarization-selective lens stack (L3) **700-3**, a fourth switchable waveplate (HWP4) **804-4** and a fourth polarization-selective lens stack (L4) **700-4**. Third and fourth polarization-selective lens stacks **700-3**, **700-4** have different, e.g., orthogonal optical axes, effective radii of curvature and/or different birefringence, such that L3 **700-3** is configured to exert a third optical power $\phi_{\text{sub.3}}$ of $n_{\text{sub.3}}/R_{\text{sub.3}}$ or substantially zero to light incident thereon having a polarization direction parallel or perpendicular to the optic axis, respectively, while the L4 **700-4** is configured to exert a fourth optical power $\phi_{\text{sub.4}}$ of $n_{\text{sub.4}}/R_{\text{sub.4}}$ or substantially zero to light incident thereon having a polarization direction parallel or perpendicular to the optic axis, respectively.

[0191] In various embodiments, the effective radii of curvature of L1 **700-1** and L2 **700-2** are such that the $\phi_{\text{sub.1}}$ and $\phi_{\text{sub.2}}$ have a first sign, e.g., positive sign, while the effective radii of curvature of L3 **700-3** and L4 **700-4** are such that the $\phi_{\text{sub.3}}$ and $\phi_{\text{sub.4}}$ have a second sign opposite the first sign, e.g., negative sign. That is, when the three possible non-zero net powers ($\phi_{\text{sub.1}}$, $\phi_{\text{sub.2}}$, and $\phi_{\text{sub.1}}+\phi_{\text{sub.2}}$) of FLA **1004** may have one of converging or diverging effects (e.g., converging), the three possible non-zero net powers ($\phi_{\text{sub.3}}$, $\phi_{\text{sub.4}}$, and $\phi_{\text{sub.3}}+\phi_{\text{sub.4}}$) of BLA **1008** may have the other of converging or diverging effects (e.g., diverging). In the illustrated embodiment, FLA **1004** and BLA **1008** are configured to be substantially the same, except for the curvatures of the interface between the birefringent and isotropic lenses (e.g., one is concave and other is convex or vice versa, etc.). In particular, FLA **1004** and BLA **1008** form mirror images about waveguide assembly **1012**. Thus, as configured, L1 **804-1** and L3 **804-3** have optical powers $\phi_{\text{sub.1}}$ and $\phi_{\text{sub.3}}$, respectively, that are substantially the same in magnitude but opposite in sign, and L2 **804-2** and L4 **804-4** have optical powers $\phi_{\text{sub.2}}$ and $\phi_{\text{sub.4}}$, respectively, that are substantially the same in magnitude but opposite in sign. That is, $\phi_{\text{sub.1}}$ is approximately equal to $-\phi_{\text{sub.3}}$, and $\phi_{\text{sub.2}}$ is approximately equal to $-\phi_{\text{sub.4}}$.

[0192] Still referring to FIG. 10, in the illustrated embodiment, waveguide assembly **1012** is configured to outcouple unpolarized light that has been totally internally reflected. In this configuration, display device **1000** additionally includes a linear polarizer **1005** between waveguide assembly **1012** and BLA **1008** configured to reduce or eliminate, e.g., reflect or absorb, light having polarization state that does not lead to lens action by BLA **1008**. For example, in arrangements where light **1009** outcoupled from waveguide assembly **1012**, or light **1020** transmitted through FLA **1004** unaffected is not linearly polarized, e.g., not LVP, linear polarizer **1005** serves to linearly polarize the transmitted light to feed incident light **820** into BLA **1008**.

[0193] As configured, BLA **1008** serves to provide variable optical powers ($\phi_{\text{sub.1}}$, $\phi_{\text{sub.2}}$, and $\phi_{\text{sub.1}}+\phi_{\text{sub.2}}$) to form images at a plurality of depth planes for the virtual images exiting

waveguide assembly **1012** towards the eye of the user. While BLA **1008** provides virtual images by focusing images from waveguide assembly **1012** at a plurality of depth planes, the world image can be distorted by BLA **1008**. FLA **1004** serves to compensate the distortion of the world image caused by BLA **1008** by providing variable optical powers ($\phi_{\text{sub.3}} = -\phi_{\text{sub.1}}$, $\phi_{\text{sub.4}} = -\phi_{\text{sub.2}}$, and $\phi_{\text{sub.3}} + \phi_{\text{sub.4}} = -(\phi_{\text{sub.1}} + \phi_{\text{sub.2}})$), such that the world image is presented to the eye of the user without substantial distortion.

[0194] In various embodiments, e.g., when deactivated, each of FLA **1004** and BLA **1008** may provide a net optical power (positive or negative) in the range between about ± 5.0 diopters and 0 diopters, ± 4.0 diopters and 0 diopters, ± 3.0 diopters and 0 diopters, ± 2.0 diopters and 0 diopters, ± 1.0 diopters and 0 diopters, including any range defined by any of these values, for instance ± 1.5 diopters. In some embodiments, FLA **1004** between waveguide assembly **1012** and the world may have a positive optical power, whereas BLA **1008** between waveguide assembly **1012** and the user may have a negative optical power, such that the optical powers of FLA **1004** and BLA **1008** compensate each other in viewing the world.

[0195] As described supra, as the images of virtual objects produced by light outcoupled by waveguide assembly **1012** move in 3D, the net optical power of BLA **1008** on the user side is adjusted to adapt to the changing depth of the virtual depth plane. Simultaneously, according to embodiments, the net optical power of FLA **1004** is correspondingly adjusted using a switching circuit, such that the view of the real world does not undesirably become defocused or distorted. To address this and other needs, in some embodiments, display device **1000** comprises a controller (not shown) configured such that, when the net optical power of one of FLA **1004** and BLA **1008** is electrically adjusted, the net optical power of the other of FLA **1004** and BLA **1008** is correspondingly adjusted such that the combined net optical powers remain about constant, e.g., about zero. The controller circuitry and the switchable waveplates are configured such that the time to switch HWP1 **804-1**, HWP2 **804-2**, HWP3 **804-3** and HWP4 **804-4**, to adjust the virtual depth planes using user-side adaptive lens assembly **1008** and to compensate the real world view using user-side adaptive lens assembly **1004**, is less than about 100 milliseconds, less than about 50 milliseconds, less than about less than about 10 milliseconds, less than about 5 milliseconds, less than about 1 millisecond, or a value within a range defined by any of these values.

Display Devices Including Adaptive Lens Assemblies Having Polarization-Selective Lens Stack Coupled to Polarizing Waveguide Assembly

[0196] FIG. **11A** illustrates an example display device **1100** according to some embodiments. Similar to the display device described above with respect to FIG. **10**, display device **1100** includes a second adaptive lens assembly (BLA) **1008** that includes a first switchable waveplate (HWP1) **804-1**, a first polarization-selective lens stack (L1) **700-1**, a second switchable waveplate (HWP2) **804-2** and a second polarization-selective lens stack (L2) **700-2**. However, unlike the display device described above with respect to FIG. **10**, display device **1100** includes a polarizing waveguide assembly **1112** that outcouples polarized light **1108**, e.g., circularly polarized light, into the BLA **1008**. Accordingly, BLA **1008** additionally includes a first quarter waveplate (QWP1) **1104**, e.g., an achromatic quarter waveplate, configured to convert RHCP light **1108-R** and LHCP light **1108-L**, outcoupled from the polarizing waveguide assembly **1112** into linear polarized light **820** incident on BLA **1008**. Thus, BLA **1008** operates in a similar manner as described above with respect to FIG. **10**.

[0197] However, unlike display device **1000** of FIG. **10**, display device **1100** does not have a FLA **1004** configured to compensate or cancel undesirable optical power exerted by BLA **1008** to world-side light **1020** when BLA **1008** exerts optical power to light from polarizing waveguide assembly **1112** containing virtual image information. Instead, display device **1100** is configured to alternately display world image and virtual image. This is achieved by replacing FLA **1004** (FIG. **10**) with a combination of a shutter **1120**, a linear polarizer **1116** and a second quarter waveplate (QWP2) **1114**, e.g., an achromatic quarter waveplate. In the following, polarizing waveguide

assembly **1112** is described with respect to FIG. **11B**, followed by the operational principles of display device **1100** with respect to FIGS. **11C** and **11D**.

[0198] FIG. **11B** illustrates an example of polarizing waveguide assembly **1112**, according to embodiments. In some embodiments, polarizing waveguide assembly **1112** is configured to output circularly polarized light, e.g., right-handed (RHCP) or left-handed (LHCP) circular polarized light. In various embodiments, polarizing waveguide assembly **1112** may comprise cholesteric liquid crystal (CLC) layers and/or CLC gratings (CLCGs), which in turn comprise liquid crystals arranged to have a plurality of chiral structures. Each of the chiral structures comprises a plurality of liquid crystal molecules that extend in a layer depth direction by at least a helical pitch and are successively rotated in a rotation direction. The CLC layers or CLCGs can advantageously be configured to substantially Bragg-reflect elliptically or circularly polarized light having a handedness of polarization that is matched to the rotation direction of the liquid crystal molecules, while being configured to substantially transmit elliptically or circularly polarized light having a handedness of polarization that is opposite to the rotation direction of the liquid crystal molecules. Based on these properties of the CLC layers and CLCGs, various embodiments of display devices disclosed herein have a polarizing waveguide assembly **1112** comprising one or more CLC layers or CLCGs. Polarizing waveguide assembly **1112** may include a CLCG **1150** configured as an outcoupling optical element, such as an exit pupil expander (EPE), according to embodiments. Polarizing waveguide assembly **1112** comprises a waveguide **1104** coupled to a CLCG **1150** and configured to propagate light by total internal reflection (TIR).

[0199] Still referring to FIG. **11B**, the liquid crystal molecules of the illustrated CLCG **1150** are successively rotated in a rotation direction, and arrangements of the liquid crystal molecules of the chiral structures vary periodically in a lateral direction (x,y directions) perpendicular to the layer depth direction (z direction). Because of the rotational arrangement of the liquid crystal molecules, when light **2604** is an elliptically/circularly polarized light having a polarization handedness, e.g., one of left-handedness or right-handedness, which matches the direction of rotation of the liquid crystal molecules of the chiral structures, light **2604** is Bragg-reflected by CLCG **1150**. That is, the rotational arrangement of the liquid crystal molecules in CLCG **1150** is such that, CLCG **1150** selectively Bragg reflects light having one handedness while non-Bragg reflecting or transmitting light having the opposite handedness. In addition, because Bragg reflection occurs under the diffraction condition, the Bragg reflected light **1108** is unidirectional (e.g., most of the light is directed toward one direction at outcoupling, such as the direction indicated by the arrows **1108** in FIG. **11B**). The outcoupled light can preserve a uniform polarization state, which corresponds to the chirality of the CLC material. Thus, when configured as an optical outcoupling element, CLCG **1150** serves as a polarizer and a unidirectional reflector, which allows for efficient integration with other optical components within display device **1100**.

[0200] As described above, display device **1100** is configured to alternately display world image (FIG. **11C**) and virtual image (FIG. **11D**). Referring to FIG. **11C**, when displaying the world image, display device **1100** has a configuration **1100C** in which both shutter **1120** and waveguide assembly **1112** are in the OFF state. In addition, both of HWP-1 **820-1** and HWP-2 **820-2** are in the ON state and OFF state, respectively. As configured, BLA **1008** is configured analogously to state **900B** described above with respect to FIG. **9B**. Under this configuration, light **1020** from the world, which is unpolarized, is transmitted through the shutter **1120** essentially unaffected and is linearly polarized, e.g., horizontally linearly polarized (LHP) into light **1124** by linear polarizer **1116**. Light **1124** is converted to circularly polarized light **1108-L**, e.g., LHCP light, which is incident on the polarizing waveguide assembly **1112**. Light **1108-L** passes through polarizing waveguide assembly **1112** in the OFF state essentially unaffected, and is converted by QWP1 **1104** into linearly polarized light **820-2** that is linearly polarized, e.g., LHP. BLA **1008** is configured to exert substantially zero optical power, analogously to the state described above with respect to FIG. **9B**, thereby passing light **820-2** essentially unaffected to be seen by the eye.

[0201] Referring to FIG. 11D, when displaying the virtual image, the display device has a configuration **1100D** in which both shutter **1120** and waveguide assembly **1112** are in the ON state. Thus, any light **1020** from the world side is blocked, e.g., reflected. Thus, display device configuration **1100D** is configured to display substantially only the virtual content outcoupled from polarizing waveguide assembly **1112** described above with respect to FIG. 11B. Light **1108-R** having a circular polarization, e.g., RHCP, is incident on QWP2 **1104**, and BLA **1008** is configured analogously to one of states **900C-900E** described above with respect to FIGS. 9C-9E. Under this configuration, circularly polarized light **1108-R** is transformed by QWP2 **1104** into linearly polarized light **820-1** having a polarization direction, e.g., vertical polarization direction (LVP). BLA **1008** then exerts an optical power according to one of states **900C-900E** described above with respect to FIGS. 9C-9E.

[0202] As described, display device **1100** is configured to sequentially display world images and virtual images. To display both the world images and the virtual images to a user as if they were simultaneously presented, configurations **1100C** (FIG. 11C) and **1100D** (FIG. 11D) are time multiplexed with respect to each other at a suitable frequency such that human eyes perceive them as being essentially simultaneous. For example, shutter **1120** and HWP-1 **820-1** and HWP-2 **820-2** are alternated at a frequency at-least twice as fast as the video refresh rate to minimize any switching artifacts. Advantageously, display device **1100** can reduce the overall number of optical elements by replacing FLA **1008** in display device **1000**. To compensate for reduction in intensity of the virtual image due to the multiplexing and polarization, the intensity of outcoupled light **1108-R** can be accordingly adjusted according to embodiments.

Display Devices Including World-Side and/or User-Side Shutter Elements and User-Side Lens Assembly

[0203] FIG. 12A illustrates an example of a display device **1200** having a single adaptive lens assembly **1208** on the user side of an eyepiece **1212** (the side of eyepiece **1212** closest to the eye of the user), according to some embodiments of the present disclosure. Lens assembly **1208** may include a variable focal element (VFE) assembly and may be configured to apply positive, negative, or zero optical power to the light passing through it. Display device **1200** may include one or more world-side shutter elements **1204** coupled to the world side of eyepiece **1212** (the side of eyepiece **1212** furthest from the eye of the user and closest to world objects), and one or more user-side shutter elements **1202** coupled to the user side of eyepiece **1212**. By sequentially electrically activating world-side shutter elements **1204** and user-side shutter elements **1202** as described herein, world light **432** may pass through display device **1200** with zero net optical power being applied by lens assembly **1208** and virtual image light **423** may pass through with non-zero (e.g., negative) net optical power being applied by lens assembly **1208**.

[0204] In the illustrated embodiment, world-side shutter elements **1204** include a world-side polarizer **1216** and a world-side switchable waveplate **1220**. World-side polarizer **1216** may be positioned closer to world objects **430** such that world light **432** passes first through world-side polarizer **1216** prior to passing through world-side switchable waveplate **1220**. Upon passing through world-side polarizer **1216**, world light **432** is linearly polarized along a first axis. Accordingly, world-side polarizer **1216** may comprise a linear polarizer. After passing through world-side polarizer **1216**, world light **432** passes through world-side switchable waveplate **1220**. When electrically activated, world-side switchable waveplate **1220** rotates a polarization of world light **432** by 90 degrees such that, for example, LVP light is converted to LHP light or LHP light is converted to LVP light. When not electrically activated, world-side switchable waveplate **1220** leaves world light **432** substantially unaltered.

[0205] In the illustrated embodiment, user-side shutter elements **1202** include a user-side polarizer **1214** and a user-side switchable waveplate **1218**. User-side polarizer **1214** may be positioned closer to eyepiece **1212** and world objects **430** such that virtual image light **423** and world light **432** passes first through user-side polarizer **1214** prior to passing through user-side switchable

waveplate **1218**. Upon passing through user-side polarizer **1214**, virtual image light **423** and world light **432** are linearly polarized along a second axis perpendicular to the first axis. Accordingly, user-side polarizer **1214** may comprise a linear polarizer that is perpendicular to world-side polarizer. After passing through user-side polarizer **1214**, virtual image light **423** and world light **432** pass through a first layer of lens assembly **1208**. As described herein, the first layer of lens assembly **1208** may apply optical power to the light passing therethrough. After passing through the first layer of lens assembly **1208**, virtual image light **423** and world light **432** pass through user-side switchable waveplate **1214**. When electrically activated, user-side switchable waveplate **1214** rotates a polarization of virtual image light **423** and world light **432** by 90 degrees such that, for example, LVP light is converted to LHP light or LHP light is converted to LVP light. When not electrically activated, user-side switchable waveplate **1214** leaves virtual image light **423** and world light **432** substantially unaltered.

[0206] After passing through user-side switchable waveplate **1218**, virtual image light **423** and world light **432** pass through a second layer of lens assembly **1208**. As described herein, the second layer of lens assembly **1208** may apply optical power to the light passing therethrough so as to cancel or add to the optical power applied to the light when passing through the first layer. For example, the first and second layers of lens assembly **1208** may be configured such that, when user-side switchable waveplate **1218** is electrically activated, light passing through both layers is applied a non-zero net optical power and, when user-side switchable waveplate **1218** is not electrically activated, light passing through both layers is applied a zero net optical power, i.e., is applied no net power. Accordingly, the first and second layers of lens assembly **1208** may be configured so as to apply a positive optical power to light having a first linear polarization and a negative optical power (with equal magnitude) to light having a second linear polarization orthogonal to the first linear polarization.

[0207] In some embodiments, the first and second layers of lens assembly **1208** are diffractive waveplate lenses. In some embodiments, lens assembly **1208** may take the form of a different type of VFE, such as an LC Fresnel lens, a deformable lens, or the like. In some embodiments, one or more components of user-side shutter elements **1202** are considered to be subcomponents of lens assembly **1208** (i.e., are considered to be included in lens assembly **1208**). In one example, user-side polarizer **1214** is considered to be a subcomponent of lens assembly **1208**. In another example, user-side switchable waveplate **1218** is considered to be a subcomponent of lens assembly **1208**. In another example, both user-side polarizer **1214** and user-side switchable waveplate **1218** are considered to be subcomponents of lens assembly **1208**. Example VFEs and other adaptive lens components, which may represent or be implemented as part of the one or more of the lens assemblies described herein, are described in U.S. Patent Application No. 15/902,927 filed on Feb. 22, 2018, published on Aug. 23, 2018 as U.S. Publication No. 2018/0239177, U.S. patent application Ser. No. 15/902,814 filed on Feb. 22, 2018, published on Aug. 23, 2018 as U.S. Publication No. 2018/0239147, U.S. patent application Ser. No. 15/933,297 filed on Mar. 22, 2018, published on Sep. 27, 2018 as U.S. Publication No. 2018/0275394, and U.S. patent application Ser. No. 16/006,080 filed on Jun. 12, 2018, published on

[0208] Dec. 13, 2018 as U.S. Publication No. 2018/0356639, all of which are expressly incorporated herein by reference in their entirety. Additional examples of such components are provided in U.S. Provisional Patent Application No. 62/639,882, filed Mar. 7, 2018 (Attorney Docket No. MLEAP.180PR) and U.S. patent application Ser. No. 16/158,041 filed on Oct. 11, 2018 (Attorney Docket No. MLEAP.183A), both of which are also expressly incorporated herein by reference in their entirety.

[0209] FIG. **12B** illustrates an example of display device **1200** operating in accordance with a first state, according to some embodiments of the present disclosure. While operating in accordance with the first state, projector and injection optics **1222** are turned off, world-side switchable waveplate **1220** is electrically activated, and user-side switchable waveplate **1218** is not electrically

activated. World light **432** is first linearly polarized along a first axis by world-side polarizer **1216**. Thereafter, a polarization of world light **432** is rotated by 90 degrees by world-side switchable waveplate **1220**. Thereafter, world light **432** is linearly polarized along a second axis perpendicular to the first axis by user-side polarizer **1214**. Thereafter, a first layer of lens assembly **1208** applies a first optical power to world light **432**. Thereafter, world light **432** passes through user-side switchable waveplate **1218** substantially unaltered. Thereafter, a second layer of lens assembly **1208** applies a second optical power to world light **432** equal in magnitude but opposite in sign to the first optical power, thereby canceling the first optical power. Thereafter, world light **432** reaches the eye of the user.

[0210] FIG. **12C** illustrates an example of display device **1200** operating in accordance with a second state, according to some embodiments of the present disclosure. While operating in accordance with the second state, projector and injection optics **1222** are turned on, world-side switchable waveplate **1220** is not electrically activated, and user-side switchable waveplate **1218** is electrically activated. World light **432** impinging on world-side polarizer **1216** is linearly polarized along a first axis by world-side polarizer **1216**. Thereafter, world light **432** passes through world-side switchable waveplate **1220** substantially unaltered. Thereafter, world light **432** is linearly polarized along a second axis perpendicular to the first axis by user-side polarizer **1214**, causing world light **432** to be completely or at least partially reduced, blocked, or dimmed. Concurrently, virtual image light **423** is projected onto one or more waveguides of eyepiece **1212** by projector and injection optics **1222**. Thereafter, virtual image light **423** is outcoupled by eyepiece **1212**. Thereafter, virtual image light **423** is linearly polarized along the second axis by user-side polarizer **1214**. Thereafter, a first layer of lens assembly **1208** applies a first optical power to virtual image light **423**. Thereafter, a polarization of virtual image light **423** is rotated by 90 degrees by user-side switchable waveplate **1218**. Thereafter, a second layer of lens assembly **1208** applies a second optical power to virtual image light **423** equal in magnitude and having the same sign as the first optical power, thereby doubling the applied optical power. Thereafter, virtual image light **423** reaches the eye of the user.

[0211] FIG. **13** illustrates a method **1300** of operating an optical system, according to some embodiments of the present disclosure. One or more steps of method **1300** may be performed in a different order than the illustrated embodiment, and one or more steps of method **1300** may be omitted during performance of method **1300**. In some embodiments, one or more steps of method **1300** can be implemented as a computer-readable medium or computer program product comprising instructions which, when the program is executed by one or more computers, cause the one or more computers to at least in part carry out some or all of the steps of method **1300**. Such computer program products can be transmitted, over a wired or wireless network, in a data carrier signal carrying the computer program product.

[0212] At step **1302**, light associated with a world object is received at the optical system. At step **1304**, the light associated with the world object is linearly polarized along a first axis. At step **1306**, it is determined whether the optical system is operating in accordance with a first state or a second state. When the optical system is operating in accordance with the first state, method **1300** proceeds to step **1308**. When the optical system is operating in accordance with the second state, method **1300** proceeds to step **1314**. At step **1308**, a polarization of the light associated with the world object is rotated by 90 degrees. At step **1310**, the light associated with the world object is linearly polarized along a second axis perpendicular to the first axis. At step **1312**, zero net optical power is applied to the light associated with the world object. Thereafter, the light associated with the world object reaches the eye of the user.

[0213] At step **1314**, light associated with a virtual image is projected onto an eyepiece of the optical system. At step **1316**, the light associated with the virtual image is outcoupled by the eyepiece. At step **1318**, the light associated with the world object and the light associated with the virtual image are linearly polarized along the second axis. At step **1320**, a polarization of the light

associated with the virtual image is rotated by 90 degrees. At step **1322**, non-zero net optical power is applied to the light associated with the virtual image. Thereafter, the light associated with the virtual image reaches the eye of the user.

[0214] FIG. **14** illustrates a method **1400** of operating an optical system, according to some embodiments of the present disclosure. One or more steps of method **1400** may be performed in a different order than the illustrated embodiment, and one or more steps of method **1400** may be omitted during performance of method **1400**. One or more steps of method **1400** may be combined with one or more steps of method **1300**. At step **1402**, ambient light is detected by an ambient light sensor. At step **1404**, a shuttering frequency is determined based on the detected ambient light. At step **1406**, the optical system is caused to switch between operation in accordance with a first state and operation in accordance with a second state based on the shuttering frequency.

[0215] FIG. **15** illustrates an example performance of method **1400**, according to some embodiments of the present disclosure. The upper plot of FIG. **15** shows detected ambient light intensity as a function of time (as detected by, e.g., ambient light sensors **434**, **534**). The lower plot of FIG. **15** shows state switching between a first state and a second state as a function of time, with time being aligned with the upper plot. At time $T_{sub.1}$, a user of the optical system is in a shaded outdoor area and the detected ambient light has a medium intensity. Based on the detected ambient light at time $T_{sub.1}$, a first shuttering frequency is determined. Determining the shuttering frequency may include determining a first period $P_{sub.1}$, the duration that the optical system is operating in accordance with the first state prior to switching to the second state, and a second period $P_{sub.2}$, the duration that the optical system is operating in accordance with the second state prior to switching to the first state. Alternatively or additionally, determining the shuttering frequency may include determining the ratio $P_{sub.1}/P_{sub.2}$, among other possibilities. Between times $T_{sub.1}$ and $T_{sub.2}$, the optical system is caused to switch between the first and second states based on the first shuttering frequency.

[0216] At time $T_{sub.2}$, the user of the optical system relocates to a low-light indoor area and the detected ambient light has a low intensity. Based on the detected ambient light at time $T_{sub.2}$, a second shuttering frequency is determined having a higher ratio $P_{sub.1}/P_{sub.2}$ than the first shuttering frequency. In other words, to improve user experience and not overly dim the world light in low-light conditions, the shuttering frequency may be adjusted so as to increase the amount of time that world light is allowed to pass through the optical system. Between times $T_{sub.2}$ and $T_{sub.3}$, the optical system is caused to switch between the first and second states based on the second shuttering frequency.

[0217] At time $T_{sub.3}$, the user of the optical system relocates to an outdoor area with direct sunlight and the detected ambient light has a high intensity. Based on the detected ambient light at time $T_{sub.3}$, a third shuttering frequency is determined having a lower ratio $P_{sub.1}/P_{sub.2}$ than both the first and second shuttering frequencies. In other words, to improve user experience and reduce the world light in high-light conditions, the shuttering frequency may be adjusted so as to decrease the amount of time that world light is allowed to pass through the optical system. After time $T_{sub.3}$, the optical system is caused to switch between the first and second states based on the third shuttering frequency.

[0218] FIG. **16A** illustrates an example of a display device **1600** operating in accordance with a first state, according to some embodiments of the present disclosure. Display device **1600** may include one or more components that are functionally equivalent or similar to one or more of those described above with reference to FIGS. **4A-4C**, **5**, **11A-11D**, and/or **12A-12C**. For example, display device **1600** may have a single adaptive lens assembly **1605** on the user side of an eyepiece **1602** (the side of eyepiece **1602** closest to the eye of the user). Lens assembly **1605** may include a VFE assembly and may be configured to apply positive, negative, or zero optical power to the light passing through it. Display device **1600** may include a shutter element **1603** coupled to the world side of eyepiece **1602** (the side of eyepiece **1602** furthest from the eye of the user and closest to

world objects). While operating in accordance with the first state, a controller **1620** causes a projector **1614** to be turned off, lens assembly **1605** to be inactive, and shutter element **1603** to be open. When shutter element **1603** is open (i.e., electrically activated), world light **432** passing therethrough is substantially unaltered. When lens assembly **1605** is inactive, lens assembly **1605** imparts zero net optical power to light (e.g., world light **432**) passing therethrough. Accordingly, while operating in accordance with the first state, world light **432** may be presented to the user substantially unaltered. As described in further detail below, in some examples, display device **1600** may hold/maintain the first state for an extended period of time (e.g., indefinitely or until display device **1600** is required to present virtual content to the user).

[0219] FIG. **16B** illustrates an example of display device **1600** operating in accordance with a second state, according to some embodiments of the present disclosure. While operating in accordance with the second state, controller **1620** causes projector **1614** to be turned on, lens assembly **1605** to be active, and shutter element **1603** to be closed. When shutter element **1603** is closed (i.e., not electrically activated), world light **432** passing therethrough is substantially blocked. When projector **1614** is turned on, virtual image light **423** is projected onto eyepiece **1602** and is thereafter outcoupled by eyepiece **1602** toward the eye of the user. When lens assembly **1605** is active, lens assembly **1605** imparts nonzero net optical power to light (e.g., virtual image light **423**) passing therethrough. Accordingly, while operating in accordance with the second state, display device **1600** may present virtual content to the user that is perceived by the user as being positioned at one or more of various possible depths. As described in further detail below, in some examples, display device **1600** may hold/maintain the second state for an extended period of time (e.g., indefinitely or until display device **1600** is required to provide the user with a view of the environment). In some embodiments, display device **1600** may synchronously control the shutter element **1603** and the lens assembly **1605** so as to rapidly alternate between the first and second states at a particular rate or frequency.

[0220] FIG. **16C** illustrates an example of display device **1600** operating in accordance with a third state, according to some embodiments of the present disclosure. While operating in accordance with the third state, controller **1620** causes projector **1614** to be turned on, lens assembly **1605** to be inactive, and shutter element **1603** to be open. When shutter element **1603** is open (i.e., electrically activated), world light **432** passing therethrough is substantially unaltered. When projector **1614** is turned on, virtual image light **423** is projected onto eyepiece **1602** and is thereafter outcoupled by eyepiece **1602** toward the eye of the user. When lens assembly **1605** is inactive, lens assembly **1605** imparts zero net optical power to light (e.g., world light **432** and/or virtual image light **423**) passing therethrough. Accordingly, while operating in accordance with the third state, display device **1600** may present virtual content to the user that is perceived by the user as being positioned at optical infinity.

[0221] As such, in the third state, display device **1600** need not activate lens assembly **1605** while injecting light representing virtual content at optical infinity into eyepiece **1602**, and may therefore allow light from the real world to pass through toward the user without any issues. As described in further detail below, in some examples, display device **1600** may hold/maintain the third state for an extended period of time (e.g., indefinitely or until display device **1600** is required to present virtual content at less than optical infinity). In some embodiments, display device **1600** may synchronously control the shutter element **1603** and the lens assembly **1605** to rapidly alternate between the second and third states so as to rapidly present some virtual content at less than optical infinity and other virtual content at optical infinity. Similar to that described in reference to FIGS. **14** and **15**, a shuttering frequency of switching between the first state, the second state, and/or the third state may be determined based on detected ambient light and/or the desired brightness of the virtual content.

[0222] As mentioned above, in some embodiments, display device **1600** may not synchronously control the shutter element **1603** and the lens assembly **1605** so as to rapidly alternate between two

or more states, but instead may selectively hold/maintain a single state (e.g., one of the first state, second state, and third state) or otherwise control the shutter element **1603** and the lens assembly **1605** independently for an extended period of time. In at least some of these embodiments, display device **1600** may be configured to alternate between at least two different modes of operation including (i) a first mode of operation in which display device **1600** is configured to control a state of the shutter element **1603** and a state of the lens assembly **1605** independently or in an otherwise asynchronous manner, and (ii) a second mode of operation in which display device **1600** is configured to control the state of the shutter element **1603** and a state of the lens assembly **1605** in a synchronous manner. For example, in the first mode of operation, display device **1600** may hold/maintain a single state (e.g., one of the first state, second state, and third state) or otherwise control the shutter element **1603** and the lens assembly **1605** independently, and in the second mode of operation, display device **1600** may cause the shutter element **1603** and the lens assembly **1605** to synchronously switch between two or more states (e.g., two or more of the first state, second state, and third state).

[0223] In some examples, in the first mode of operation, display device **1600** may hold/maintain a state similar or equivalent to the second state for an extended period of time (e.g., indefinitely or until display device **1600** is required to provide the user with a view of the environment). In at least some such examples, the first mode of operation may correspond to a VR mode in which controller **1620** causes projector **1614** to be turned on, lens assembly **1605** to be optionally active, and shutter element **1603** to be closed or otherwise held in a relatively dim state. Optionally, in the first mode of operation, controller **1620** may cause lens assembly **1605** to switch states as needed to impart the appropriate amount of optical power to light from the projector. In the aforementioned examples, controller **1620** may cause display device **1600** to switch into and/or out of the first mode of operation based on any of a variety of factors, including user input (e.g., as indicated by data received from one or more sensors, user interfaces, input devices, etc.), an application that is running on display device **1600**, user preferences, sensor data, and the like. For instance, controller **1620** may switch into the first mode of operation so as to initiate a VR experience in which the user is provided with little to no see-through visibility of the environment in front of them responsive to launching or terminating execution of a specific application on display device **1600**, receiving indication that the user wishes to enter such a mode or exit another mode based on input received through a handheld controller and/or graphical user interface, and/or an occurrence of one or more other events. Similarly, controller **1620** may switch out of the first mode of operation so as to terminate a VR experience or transition to an AR or mixed reality (MR) experience in which the user is provided with increased see-through visibility of the environment in front of them responsive to launching or terminating execution of a specific application on display device **1600**, receiving indication that the user wishes to exit a VR mode or enter another mode (e.g., an AR or MR mode) based on input received through a handheld controller and/or graphical user interface, and/or an occurrence of one or more other events. Other configurations are possible.

[0224] In other examples, in the first mode of operation, display device **1600** may hold/maintain a state similar or equivalent to the third state for an extended period of time (e.g., indefinitely or until display device **1600** is required to present virtual content at less than optical infinity). In at least some such examples, the first mode of operation may correspond to a mode in which controller **1620** causes projector **1614** to be turned on, lens assembly **1605** to be held in a fixed state, and shutter element **1603** to be held open. Optionally, in the first mode of operation, controller **1620** may cause shutter element **1603** to switch between open and closed states. In the aforementioned examples, controller **1620** may cause display device **1600** to switch into and/or out of the first mode of operation based on any of a variety of factors, including a depth at which the user's eyes are determined to be fixated, a depth in front of the user at which virtual content is to be perceived by the user, an accommodation-vergence mismatch for the virtual content, and the like. In some embodiments, controller **1620** may utilize data from one or more inward-facing cameras (e.g.,

images of one or both of the user's eyes) to determine the depth at which the user's eyes are fixated, evaluate the determined depth against a set of criteria, and switch into and/or out of the first mode of operation based on the results of the evaluation.

[0225] For instance, in these embodiments, controller **1620** may determine whether an accommodation-vergence mismatch for the virtual content exceeds one or more predetermined thresholds based at least in part on the depth at which the user's eyes are determined to be fixated, and may switch into and/or out of the first mode of operation in response to a determination that the accommodation-vergence mismatch for the virtual content exceeds one or more predetermined thresholds. Example systems and techniques for adjusting the wavefront divergence of light representing virtual content for enhanced user perception, comfort, and/or experience, which may represent or be implemented as part of one or more of the systems and techniques described herein, are described in U.S. patent application Ser. No. 15/430,277 filed on Feb. 10, 2017, published on Aug. 17, 2017 as U.S. Publication No. 2017/0237974, U.S. patent application Ser. No. 15/469,369 filed on Mar. 24, 2017, published on Sep. 28, 2019 as U.S. Publication No. 2017/0276948, U.S. patent application Ser. No. 16/250,931 filed on Jan. 17, 2019, published on Aug. 8, 2019 as U.S. Publication No. 2019/0243448, U.S. patent application Ser. No. 16/353,989 filed on Mar. 14, 2019, published on Oct. 10, 2019 as U.S. Publication No. 2019/0311527, and U.S. patent application Ser. No. 16/389,529 filed on Apr. 19, 2019, published on Oct. 24, 2019 as U.S. Publication No. 2019/0324276, all of which are expressly incorporated herein by reference in their entirety. In some embodiments, one or more of such systems and techniques described in one or more of the aforementioned patent applications may represent or be implemented as part of one or more of systems and techniques for switching into and/or out of the first mode of operation. Other configurations are possible.

[0226] In the second mode of operation, controller **1620** of display device **1600** may cause the shutter element **1603** and the lens assembly **1605** to synchronously switch between different states in a manner yielding an inverse relationship between the amount of ambient light from the environment of the user allowed by shutter assembly **1603** to pass therethrough toward the user and the amount of wavefront divergence imparted by lens assembly **1605** to light passing therethrough toward the user. For example, in the second mode of operation, controller **1620** of display device **1600** may cause the shutter element **1603** and the lens assembly **1605** to synchronously switch between two states that are similar or equivalent to the first and second states as described above in reference to FIGS. **16A** and **16B**, respectively, or may cause the shutter element **1603** and the lens assembly **1605** to synchronously switch between two states that are similar or equivalent to the second and third states as described above in reference to FIGS. **16B** and **16C**, respectively.

[0227] FIG. **17** illustrates a simplified computer system **1700** according to an embodiment described herein. Computer system **1700** as illustrated in FIG. **17** may be incorporated into devices described herein. FIG. **17** provides a schematic illustration of one embodiment of computer system **1700** that can perform some or all of the steps of the methods provided by various embodiments. It should be noted that FIG. **17** is meant only to provide a generalized illustration of various components, any or all of which may be utilized as appropriate. FIG. **17**, therefore, broadly illustrates how individual system elements may be implemented in a relatively separated or relatively more integrated manner.

[0228] Computer system **1700** is shown comprising hardware elements that can be electrically coupled via a bus **1705**, or may otherwise be in communication, as appropriate. The hardware elements may include one or more processors **1710**, including without limitation one or more general-purpose processors and/or one or more special-purpose processors such as digital signal processing chips, graphics acceleration processors, and/or the like; one or more input devices **1715**, which can include without limitation a mouse, a keyboard, a camera, and/or the like; and one or more output devices **1720**, which can include without limitation a display device, a printer, and/or the like.

[0229] Computer system **1700** may further include and/or be in communication with one or more non-transitory storage devices **1725**, which can comprise, without limitation, local and/or network accessible storage, and/or can include, without limitation, a disk drive, a drive array, an optical storage device, a solid-state storage device, such as a random access memory (“RAM”), and/or a read-only memory (“ROM”), which can be programmable, flash-updateable, and/or the like. Such storage devices may be configured to implement any appropriate data stores, including without limitation, various file systems, database structures, and/or the like.

[0230] Computer system **1700** might also include a communications subsystem **1719**, which can include without limitation a modem, a network card (wireless or wired), an infrared communication device, a wireless communication device, and/or a chipset such as a Bluetooth™ device, an 802.11 device, a WiFi device, a WiMax device, cellular communication facilities, etc., and/or the like. The communications subsystem **1719** may include one or more input and/or output communication interfaces to permit data to be exchanged with a network such as the network described below to name one example, other computer systems, television, and/or any other devices described herein. Depending on the desired functionality and/or other implementation concerns, a portable electronic device or similar device may communicate image and/or other information via the communications subsystem **1719**. In other embodiments, a portable electronic device, e.g. the first electronic device, may be incorporated into computer system **1700**, e.g., an electronic device as an input device **1715**. In some embodiments, computer system **1700** will further comprise a working memory **1735**, which can include a RAM or ROM device, as described above.

[0231] Computer system **1700** also can include software elements, shown as being currently located within the working memory **1735**, including an operating system **1740**, device drivers, executable libraries, and/or other code, such as one or more application programs **1745**, which may comprise computer programs provided by various embodiments, and/or may be designed to implement methods, and/or systems, provided by other embodiments, as described herein. Merely by way of example, one or more procedures described with respect to the methods discussed above, might be implemented as code and/or instructions executable by a computer and/or a processor within a computer; in an aspect, then, such code and/or instructions can be used to and/or adapt a general purpose computer or other device to perform one or more operations in accordance with the described methods.

[0232] A set of these instructions and/or code may be stored on a non-transitory computer-readable storage medium, such as the storage device(s) **1725** described above. In some cases, the storage medium might be incorporated within a computer system, such as computer system **1700**. In other embodiments, the storage medium might be separate from a computer system e.g., a removable medium, such as a compact disc, and/or provided in an installation package, such that the storage medium can be used to program, configure, and/or adapt a general purpose computer with the instructions/code stored thereon. These instructions might take the form of executable code, which is executable by computer system **1700** and/or might take the form of source and/or installable code, which, upon compilation and/or installation on computer system **1700** e.g., using any of a variety of generally available compilers, installation programs, compression/decompression utilities, etc., then takes the form of executable code.

[0233] It will be apparent to those skilled in the art that substantial variations may be made in accordance with specific requirements. For example, customized hardware might also be used, and/or particular elements might be implemented in hardware, software including portable software, such as applets, etc., or both. Further, connection to other computing devices such as network input/output devices may be employed.

[0234] As mentioned above, in one aspect, some embodiments may employ a computer system such as computer system **1700** to perform methods in accordance with various embodiments of the technology. According to a set of embodiments, some or all of the procedures of such methods are performed by computer system **1700** in response to processor **1710** executing one or more

sequences of one or more instructions, which might be incorporated into the operating system **1740** and/or other code, such as an application program **1745**, contained in the working memory **1735**. Such instructions may be read into the working memory **1735** from another computer-readable medium, such as one or more of the storage device(s) **1725**. Merely by way of example, execution of the sequences of instructions contained in the working memory **1735** might cause the processor(s) **1710** to perform one or more procedures of the methods described herein. Additionally or alternatively, portions of the methods described herein may be executed through specialized hardware.

[0235] The terms “machine-readable medium” and “computer-readable medium,” as used herein, refer to any medium that participates in providing data that causes a machine to operate in a specific fashion. In an embodiment implemented using computer system **1700**, various computer-readable media might be involved in providing instructions/code to processor(s) **1710** for execution and/or might be used to store and/or carry such instructions/code. In many implementations, a computer-readable medium is a physical and/or tangible storage medium. Such a medium may take the form of a non-volatile media or volatile media. Non-volatile media include, for example, optical and/or magnetic disks, such as the storage device(s) **1725**. Volatile media include, without limitation, dynamic memory, such as the working memory **1735**.

[0236] Common forms of physical and/or tangible computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, punchcards, papertape, any other physical medium with patterns of holes, a RAM, a PROM, EPROM, a FLASH-EPROM, any other memory chip or cartridge, or any other medium from which a computer can read instructions and/or code.

[0237] Various forms of computer-readable media may be involved in carrying one or more sequences of one or more instructions to the processor(s) **1710** for execution. Merely by way of example, the instructions may initially be carried on a magnetic disk and/or optical disc of a remote computer. A remote computer might load the instructions into its dynamic memory and send the instructions as signals over a transmission medium to be received and/or executed by computer system **1700**.

[0238] The communications subsystem **1719** and/or components thereof generally will receive signals, and the bus **1705** then might carry the signals and/or the data, instructions, etc. carried by the signals to the working memory **1735**, from which the processor(s) **1710** retrieves and executes the instructions. The instructions received by the working memory **1735** may optionally be stored on a non-transitory storage device **1725** either before or after execution by the processor(s) **1710**.

[0239] The methods, systems, and devices discussed above are examples. Various configurations may omit, substitute, or add various procedures or components as appropriate. For instance, in alternative configurations, the methods may be performed in an order different from that described, and/or various stages may be added, omitted, and/or combined. Also, features described with respect to certain configurations may be combined in various other configurations. Different aspects and elements of the configurations may be combined in a similar manner. Also, technology evolves and, thus, many of the elements are examples and do not limit the scope of the disclosure or claims.

[0240] Specific details are given in the description to provide a thorough understanding of exemplary configurations including implementations. However, configurations may be practiced without these specific details. For example, well-known circuits, processes, algorithms, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the configurations. This description provides example configurations only, and does not limit the scope, applicability, or configurations of the claims. Rather, the preceding description of the configurations will provide those skilled in the art with an enabling description for implementing described techniques. Various changes may be made in the function and arrangement of elements without departing from the spirit or scope of the disclosure.

[0241] Also, configurations may be described as a process which is depicted as a schematic flowchart or block diagram. Although each may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figure. Furthermore, examples of the methods may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks may be stored in a non-transitory computer-readable medium such as a storage medium. Processors may perform the described tasks.

[0242] Having described several example configurations, various modifications, alternative constructions, and equivalents may be used without departing from the spirit of the disclosure. For example, the above elements may be components of a larger system, wherein other rules may take precedence over or otherwise modify the application of the technology. Also, a number of steps may be undertaken before, during, or after the above elements are considered. Accordingly, the above description does not bind the scope of the claims.

[0243] As used herein and in the appended claims, the singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise. Thus, for example, reference to “a user” includes a plurality of such users, and reference to “the processor” includes reference to one or more processors and equivalents thereof known to those skilled in the art, and so forth.

[0244] Also, the words “comprise”, “comprising”, “contains”, “containing”, “include”, “including”, and “includes”, when used in this specification and in the following claims, are intended to specify the presence of stated features, integers, components, or steps, but they do not preclude the presence or addition of one or more other features, integers, components, steps, acts, or groups.

[0245] It is also understood that the examples and embodiments described herein are for illustrative purposes only and that various modifications or changes in light thereof will be suggested to persons skilled in the art and are to be included within the spirit and purview of this application and scope of the appended claims.

Claims

1. An optical system comprising: a projector configured to emit light; at least one waveguide optically coupled to the projector and configured to receive and redirect light therefrom toward a user; a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide, wherein the shutter assembly is controllable to allow a variable amount of ambient light from an environment of the user to pass therethrough toward the user; an adaptive lens assembly positioned between the at least one waveguide and the user, wherein the adaptive lens assembly is controllable to impart a variable amount of optical power to light passing therethrough toward the user; and control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly, wherein the control circuitry is configured to synchronously: cause the adaptive lens assembly to vary an amount of optical power imparted to light passing therethrough toward the user; and cause the shutter assembly to vary the amount of ambient light from the environment of the user allowed to pass therethrough toward the user inversely with the amount of optical power imparted by the adaptive lens assembly to light passing therethrough.
2. The optical system of claim 1, wherein the at least one waveguide is further configured to allow ambient light from the environment of the user to pass therethrough toward the user.
3. The optical system of claim 1, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the environment of the user.
4. The optical system of claim 1, wherein the at least one component of the shutter assembly

comprises at least one component positioned between the at least one waveguide and the user.

5. The optical system of claim 1, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the adaptive lens assembly.

6. The optical system of claim 1, wherein the at least one waveguide comprises a plurality of waveguides.

7. A method of operating an optical system, the method comprising: emitting light by a projector; receiving and redirecting, by at least one waveguide optically coupled to the projector, light from the projector toward a user; controlling a shutter assembly comprising at least one component positioned adjacent to the at least one waveguide to allow a variable amount of ambient light from an environment of the user to pass therethrough toward the user; controlling an adaptive lens assembly positioned between the at least one waveguide and the user to impart a variable amount of optical power to light passing therethrough toward the user; and using control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly to synchronously: cause the adaptive lens assembly to vary an amount of optical power imparted to light passing therethrough toward the user; and cause the shutter assembly to vary the amount of ambient light from the environment of the user allowed to pass therethrough toward the user inversely with the amount of optical power imparted by the adaptive lens assembly to light passing therethrough.

8. The method of claim 7, wherein the at least one waveguide is further configured to allow ambient light from the environment of the user to pass therethrough toward the user.

9. The method of claim 7, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the environment of the user.

10. The method of claim 7, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the user.

11. The method of claim 7, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the adaptive lens assembly.

12. The method of claim 7, wherein the at least one waveguide comprises a plurality of waveguides.

13. A non-transitory computer-readable medium comprising instructions that, when executed by one or more processors, cause the one or more processors to perform operations comprising: causing a projector to emit light, wherein at least one waveguide optically coupled to the projector is configured to receive and redirect the light from the projector toward a user; controlling a shutter assembly comprising at least one component positioned adjacent to at least one waveguide to allow a variable amount of ambient light from an environment of the user to pass therethrough toward the user; controlling an adaptive lens assembly positioned between the at least one waveguide and the user to impart a variable amount of optical power to light passing therethrough toward the user; and using control circuitry communicatively coupled to the projector, the shutter assembly, and the adaptive lens assembly to synchronously: cause the adaptive lens assembly to vary an amount of optical power imparted to light passing therethrough toward the user; and cause the shutter assembly to vary the amount of ambient light from the environment of the user allowed to pass therethrough toward the user inversely with the amount of optical power imparted by the adaptive lens assembly to light passing therethrough.

14. The non-transitory computer-readable medium of claim 13, wherein the at least one waveguide is further configured to allow ambient light from the environment of the user to pass therethrough toward the user.

15. The non-transitory computer-readable medium of claim 13, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one

waveguide and the environment of the user.

16. The non-transitory computer-readable medium of claim 13, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the user.

17. The non-transitory computer-readable medium of claim 13, wherein the at least one component of the shutter assembly comprises at least one component positioned between the at least one waveguide and the adaptive lens assembly.

18. The non-transitory computer-readable medium of claim 13, wherein the at least one waveguide comprises a plurality of waveguides.
