

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250251414

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Wiederin; Daniel R et al.

---

### AUTOSAMPLER SAMPLE AND SAMPLE RACK IDENTIFICATION

---

#### Abstract

A sample identification system for an automated sampling device is described. A system embodiment includes, but is not limited to, a sample holder having a plurality of apertures configured to receive a plurality of sample vessels therein, the sample holder having one or more corresponding sample holder identifiers positioned proximate to the sample holder; and an identifier capture device configured to detect the one or more sample holder identifiers positioned proximate to the sample holder and generate a data signal in response thereto, the data signal corresponding to at least an orientation of the sample holder relative to a surface on which the sample holder is positioned.

---

**Inventors:** Wiederin; Daniel R (Omaha, NE), Hahn; Kevin (Urbandale, IA), Doolan; Connor (Kansas City, MO), Hauke; Karl (Warranwood Victoria, AU), Ji; Guangwei (Omaha, NE), Yost; Tyler (Omaha, NE)

**Applicant:** Elemental Scientific, Inc. (Omaha, NE)

**Family ID:** 57944035

**Appl. No.:** 19/175791

**Filed:** April 10, 2025

#### Related U.S. Application Data

parent US continuation 18307135 20230426 parent-grant-document US 12298322 child US 19175791

parent US continuation 17512991 20211028 parent-grant-document US 11668724 child US 18307135

parent US continuation 16775061 20200128 parent-grant-document US 11175297 child US 17512991

parent US continuation 15229767 20160805 parent-grant-document US 10545160 child US 16775061

## Publication Classification

**Int. Cl.:** **G01N35/00** (20060101); **B01L3/00** (20060101); **B01L9/02** (20060101); **B01L9/06** (20060101); **G01N35/04** (20060101); **G01N35/10** (20060101)

**U.S. Cl.:**

**CPC** **G01N35/00732** (20130101); **B01L3/545** (20130101); **B01L9/06** (20130101); **G01N35/109** (20130101); **B01L9/02** (20130101); **B01L2200/025** (20130101); **G01N2035/00673** (20130101); **G01N2035/00752** (20130101); **G01N2035/00801** (20130101); **G01N2035/0091** (20130101); **G01N2035/0418** (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application claims the benefit under 35 U.S.C. § 119 (e) of U.S. Provisional Application Ser. No. 62/201,725, filed Aug. 6, 2015, and titled “AUTOSAMPLER SAMPLE RACK IDENTIFICATION,” and of U.S. Provisional Application Ser. No. 62/201,722, filed Aug. 6, 2015, and titled “AUTOMATIC DETECTION OF EXPIRED STANDARD SOLUTIONS,” each of which is herein incorporated by reference in its entirety.

### BACKGROUND

[0002] In many laboratory settings, it is often necessary to analyze a large number of chemical or biochemical samples at one time. In order to stream-line such processes, the manipulation of samples has been mechanized. Such mechanized sampling is commonly referred to as autosampling and is performed using an automated sampling device or autosampler.

### SUMMARY

[0003] A sample identification system for an automated sampling device is described. A system embodiment includes, but is not limited to, a sample holder having a plurality of apertures configured to receive a plurality of sample vessels therein, the sample holder having one or more corresponding sample holder identifiers positioned proximate to the sample holder; and an identifier capture device configured to detect the one or more sample holder identifiers positioned proximate to the sample holder and generate a data signal in response thereto, the data signal corresponding to at least an orientation of the sample holder relative to a surface on which the sample holder is positioned.

[0004] A method embodiment includes, but is not limited to, detecting a sample holder identifier positioned on a sample holder, the sample holder having a plurality of apertures configured to receive a plurality of sample vessels therein; and determining an orientation of the sample holder based upon the sample holder identifier detected, the orientation of the sample holder being relative to a surface on which the sample holder is positioned.

[0005] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

---

## Description

### FIGURES

[0006] The Detailed Description is described with reference to the accompanying figures. The use of the same reference numbers in different instances in the description and the figures may indicate similar or identical items.

[0007] FIG. 1 is an isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure.

[0008] FIG. 2A is a partial isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where a center slot in the support surface is present allowing the sample arm assembly to be connected with the drive assembly.

[0009] FIG. 2B is a partial isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where a raised slot on the support surface is present to attach the sample arm assembly to the drive assembly.

[0010] FIG. 3 is an exploded view of the automated sampling or dispensing device shown in FIG. 1, further illustrating components of the device.

[0011] FIG. 4A is an isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure where multiple sampling arm assemblies and drive assemblies are mounted to the top of the support surface of the automated sampling or dispensing device.

[0012] FIG. 4B is a plan view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where multiple sample arm assemblies and rinse stations are present on one support surface.

[0013] FIG. 5 is an isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where the support surface of the automatic sampling or dispensing device is provided with more than one plane.

[0014] FIG. 6 is an isometric view of the automated sampling or dispensing device shown in FIG. 1, further illustrating the drive assembly.

[0015] FIG. 7 is a partial isometric view of the drive assembly shown in FIG. 6, further illustrating components of the drive assembly.

[0016] FIG. 8 is a partial isometric view illustrating a sample arm assembly for an automated sampling or dispensing device in accordance with example implementations of the present disclosure.

[0017] FIG. 9A is a plan view illustrating a support surface for use with an automated sampling or dispensing device, where the support surface includes a slot and has a footprint in accordance with example implementations of the present disclosure.

[0018] FIG. 9B is a plan view illustrating a support surface for use with an automated sampling or dispensing device, in accordance with example implementations of the present disclosure.

[0019] FIG. 10 is an isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where the device includes a shroud.

[0020] FIG. 11 is an isometric view illustrating an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where the device is contained within a hood.

[0021] FIG. 12 is an isometric view illustrating an automated sampling or dispensing enclosure in accordance with example implementations of the present disclosure, where the enclosure includes two flexible sheets.

[0022] FIG. 13 is a partial front view of the automated sampling or dispensing device enclosure as

illustrated in FIG. 12, where one of the flexible sheets of the enclosure is retracted.

[0023] FIG. 14 is a front view of the automated sampling or dispensing device enclosure as illustrated in FIG. 12, where the mechanism of fastening a flexible side shut is demonstrated.

[0024] FIG. 15 is a front view of the automated sampling or dispensing device enclosure as illustrated in FIG. 12, where the flexible sheets have been removed.

[0025] FIG. 16 is an isometric view illustrating an enclosure for a bench top automated sampling or dispensing device in accordance with example implementations of the present disclosure, where the enclosure includes flexible sheets which are in a closed position.

[0026] FIG. 17 is a front view of the enclosure for the bench top automated sampling or dispensing device as illustrated in FIG. 16, where the flexible sheets are in an open position.

[0027] FIG. 18 is an isometric view illustrating an enclosure for an automated sampling or dispensing device in accordance with example implementations of the present disclosure, where the enclosure includes a single flexible front sheet.

[0028] FIG. 19 is an isometric view of the enclosure for the automated sampling or dispensing device as illustrated in FIG. 18, where the front sheet is retracted allowing access to the device.

[0029] FIG. 20 is a partially exploded isometric view of an automated sampling or dispensing device having a sample identification system in accordance with example implementations of the present disclosure.

[0030] FIG. 21A is an isometric view of the automated sampling or dispensing device of FIG. 20.

[0031] FIG. 21B is an isometric view of an automated sampling or dispensing device having a sample identification system in accordance with example implementations of the present disclosure.

[0032] FIG. 21C is an isometric view of the automated sampling or dispensing device of FIG. 20 shown in an operating position.

[0033] FIG. 22 is a partial side view of an identifier arm assembly in position beneath a sample holder having sample vessels with sample identifiers.

[0034] FIG. 23A is an isometric view of a sample holder including a substantially transparent bottom.

[0035] FIG. 23B is an isometric view of a sample holder including a first set of apertures configured to hold sample vessels and a second set of apertures on a bottom portion of the sample holder.

[0036] FIG. 24 is a partial side view of an identifier capture device and a sample probe, where the identifier capture device is aligned with the sample probe.

[0037] FIG. 25 is an isometric view of an identifier arm assembly having an identifier capture device.

[0038] FIG. 26A is a side view of an identifier arm assembly relative to an identifier capture device for a system, such as the system shown in FIG. 20, where the identifier arm assembly is positioned substantially perpendicular to the alignment axis, and where the identifier capture device is positioned at an angle from perpendicular to the alignment axis.

[0039] FIG. 26B is a side view of an identifier arm assembly relative to an identifier capture device for a system, such as the system shown in FIG. 20, where the identifier capture device is positioned substantially perpendicular to the alignment axis, and where the identifier arm assembly is positioned at an angle from perpendicular to the alignment axis.

[0040] FIG. 27 is a bottom perspective view of a sample holder including sample holder identifiers in accordance with example implementations of the present disclosure.

[0041] FIG. 28A is an isometric view of an automated sampling or dispensing device having sample vessels positioned in slots, numbers one to four, distal to a z-axis support.

[0042] FIG. 28B is a diagrammatic top view showing the automated sampling or dispensing device detecting sample vessels positioned in slots, numbers one to four, distal to a center slot through which a z-axis support can pass.

[0043] FIG. **29A** is an isometric view of an automated sampling or dispensing device with sample vessels positioned in slots, numbers one to four, adjacent to a z-axis support.

[0044] FIG. **29B** is a diagrammatic top view showing the automated sampling or dispensing device detecting sample vessels positioned in slots, numbers one to four, adjacent to a center slot through which a z-axis support can pass.

[0045] FIG. **30A** is an isometric view of an automated sampling or dispensing device having a plurality of scientific standard solution vessels positioned in slots accessible by a probe of the automated sampling or dispensing device in accordance with an example implementation of the present disclosure.

[0046] FIG. **30B** is a diagrammatic bottom view of a scientific standard solution vessel having a standard identifier associated therewith in accordance with an example implementation of the present disclosure.

[0047] FIG. **30C** is a diagrammatic top view showing the automated sampling or dispensing device detecting scientific standard solution vessels positioned in slots, numbers one to three, in accordance with an example implementation of the present disclosure.

[0048] FIG. **30D** is a table showing information associated with scientific standard solutions, where a standard identifier associated with one of the scientific standard solutions corresponds to an expired scientific standard solution.

[0049] FIG. **31** is an isometric view of an automated sampling or dispensing device including an enclosed sample holder and a heating element in accordance with example implementations of the present disclosure.

[0050] FIG. **32** is an isometric view of an automated sampling or dispensing device including an enclosed sample holder and a sampling base in accordance with example implementations of the present disclosure.

[0051] FIG. **33** is an isometric view of a sampling base of an enclosed sample holder, where the sampling base includes one or more protrusions for mating with a support surface.

[0052] FIG. **34** is an isometric view illustrating a support surface for use with an automated sampling or dispensing device, where the support surface includes recesses for mating with a sampling base in accordance with example implementations of the present disclosure

## DETAILED DESCRIPTION

### Overview

[0053] Often in laboratory settings, large numbers of samples are analyzed. Autosamplers are frequently used to test the composition of these samples. Using an autosampler allows more samples to be prepared and tested. During the sample preparation process, multiple samples may be prepared and placed in individual sample vessels at one time or over a period of time, which can lead to errors associated with sample identification. For example, laboratory personnel can place samples prepared for testing in sample vessels without labeling the vessels or identifying the sample vessels in some manner. This lack of labeling or identification may lead to errors (e.g., misplacement of samples, misidentification of samples, etc.) when arranging the samples for testing via autosampler or when entering the sample information into a computer system connected to an autosampler. For example, the sample rack itself could be placed in an orientation relative to the autosampler that would result in skewed data analysis even if the sample vessels were properly arranged within the sample rack.

[0054] Accordingly, a sample identification system for an automated sampling device is disclosed that includes a sample holder having one or more corresponding sample holder identifiers positioned proximate to the sample holder. The system also includes an identifier capture device configured to detect the one or more sample holder identifiers positioned proximate to the sample holder and generate a data signal in response thereto, the data signal corresponding to at least an orientation of the sample holder.

### Example Implementations

[0055] FIG. 1 illustrates automated sampling device **100** in accordance with an example implementation of the present disclosure. Automated sampling device **100** includes table top **102** and sample arm assembly **104**. Further, sample holders **106** holding multiple sample vessels **108** are present on table top **102** in preparation for sample assaying. It should be understood that automated sampling device **100** may assay from one to many hundreds of samples (e.g., greater than **1200** samples in the example implementation illustrated) in a given time depending upon test requirements. Verification of a sample identify of a sample to be analyzed is described with reference to FIGS. **20** through **29B**.

[0056] In the implementation illustrated, sample arm assembly **104** includes a z-axis support **110** and a sample probe support arm **112** that supports a sample probe **114**. As illustrated, the z-axis is aligned with gravity or a vertical axis. In use, sample probe **114** is mounted to sample probe support arm **112**, which is moved through space in three dimensions, or about an axis having y-motion that is a substantially rotary motion and along an axis having x-motion which is at least substantially horizontal linear motion or translation, and along a z-axis that is at least substantially vertical, for linear motion or translation. In an implementation, the length of a sample probe support arm (the length of an arm extending from the y-rotary axis) is no more than one-half the length of a linear translation of the center slot (i.e., is no more than half of the length of x-axis linear motion). In an implementation, the length of the sample probe support arm is approximately equal to one-half the length of a linear translation of the center slot. Such configuration allows nearly one hundred percent of the footprint of the table to be accessed by the sample probe. Footprint is defined as being substantially equivalent to an area encompassed by the area of the table top. In an additional implementation, the y-rotary axis of an automated sampling device allows for access to sample vessels on either side of the x-axis motion of linear travel (i.e., on either side of the center slot).

[0057] In an implementation, the components of sample arm assembly **104** are formed of carbon composite materials. Further, all exposed surfaces of the sample arm assembly **104** are made from inert or fluoropolymer-covered materials (i.e., Teflon®). It should be understood, however, that the sample arm assembly may be made with various materials, including aluminum, steel, plastic, and so forth.

[0058] In addition, sample arm assembly **104** is designed to attach to various surface supports including a table top. Such assembly may be attached to either side of the center slot. In an implementation, table top **102** may be mounted onto legs with casters **118**, rollers and so forth. Such configuration increases the mobility of the automated sampling device, thereby facilitating preparation of samples at a location separate from the analytical instruments. Further, this configuration provides storage room underneath the table top which may be absent with bench-top automated sampling devices. The height of the table is adjustable to compensate for the effects of gravity on liquid flow rates when self-aspirating sampling devices are used. The ability to adjust table top height also allows the automated sampling device to accommodate various sized sample vessels.

[0059] FIGS. **2A** and **2B** are additional illustrations of automated sampling or dispensing devices in which the sample arm assembly is attached to the drive assembly via a center slot or a raised slot, respectively. In FIG. **2A**, automated sampling device **100** is comprised of sample arm assembly **104** extending through center slot **120** and table top **102** including a plurality of recesses **124** and the channel **126**. The sample arm assembly **104** is attached to the drive assembly (not shown) via center slot **120**. In an implementation, the plurality of recesses is coupled with sensors for detecting the location of sample holders. The sample holder location information may then be transferred to a controller of a drive assembly controlling the sample arm assembly providing the alignment system. The previous configuration allows the sample arm assembly to detect the location of sample vessels on the table top at a given time. Channel **126** runs along the edge of table top **102** to collect possible sample spillage.

[0060] In addition to FIG. 2A, FIG. 2B demonstrates an automated sampling or dispensing device including a sample arm assembly **104** attached to the drive assembly **128** via a raised slot **129**. In one implementation, a magnet **131** is attached to the end of the sample probe support arm **112** which allows detection of a three-dimensional position in space where the magnet **131** is embedded into the sample probe support arm **112** and is detected by a sensing means such as a Hall Effect sensor.

[0061] Referring now to FIG. 3, an exploded view of the components comprising the automated sampling device **100** is provided. The automated sampling device **100** is comprised of a table top **102** with center slot **120**, drive assembly **128**, sample arm assembly **104**, housing **130**, and controller **132**. Sample arm assembly **104** includes z-axis support **110** attached to drive assembly **128**, sample probe support arm **112** attached to z-axis support **110**, and sample probe **114** attached to sample probe support arm **112**. Sample arm assembly **104** is controlled by drive assembly **128** and controller **132**. In an implementation, drive assembly **128** causes sample arm assembly **104** to move along center slot **120**, in translation along an axis coaxial to z-axis support **110**, and radially about the z-axis for inserting sample probe **114** into a sample vessel. Further, sample arm assembly **104** is no more than one-half the length of a linear translation of the length of center slot **120**. As previously mentioned, such configuration allows nearly one hundred percent of the footprint to be accessed by sample probe **114**. In addition, automated sampling device **100** is capable of assaying hundreds of samples at a given time without operator assistance, thereby allowing the operator to perform other tasks. Moreover, it is possible to configure the automated sampling device to assay samples overnight, allowing work productivity to be increased.

[0062] To accommodate gross differences in sample vessel height, sample probe support arm **112** may be moved up or down z-axis support **110** as desired prior to sample assaying. Once the desired position is reached, sample probe support arm **112** is secured into a fixed position on z-axis support **110** and sample vessels containing samples may be loaded onto the table top. This feature allows the automated sampling device to be used on various sizes of sample vessels while still not having mechanical moving parts above stationary samples. Additionally, housing **130** encloses drive assembly **128** to protect the assembly from debris, dust, contaminants, and so forth. Housing **130** may be made of various materials, e.g., blow molded polyethylene, and so forth.

[0063] FIGS. 4A and 4B illustrate an automated sampling device **200** in accordance with another example implementation of the present disclosure, where multiple sampling arm assemblies (i.e., sample arm assembly **206**, **208**, and **210**) are mounted to the table top of the automated sampling device. Automated sampling device **200** includes multiple automated sampling devices attached to a table top at one time. A rail **202** is attached to the edge of table top **204** to enable the attachment of additional sample arm assemblies (i.e., sample arm assembly **206** and **212**). Utilization of additional sample arm assemblies allows multiple sample zones to be configured (i.e., a prep zone, an assaying zone, and so forth).

[0064] In additional implementations, various types of multiple rinse or eluent stations may be included in the automated sampling device. For instance, multiple rinse stations (i.e., **214** and **216**) of the overflow type designed to reduce the chance of carry-over contamination may be present. Further, overflow rinse stations may contain a series of different chemical rinses to reduce contamination between sample analyses (e.g., surfactant, nitric acid, hydrofluoric acid, and/or deionized water). For multiple eluent stations, the automated sampling device may contain such stations for step elution from a chromatographic column.

[0065] Referring now to FIG. 5, an automated sampling device in accordance with another example implementation of the present disclosure is described, where a table top having more than one plane is provided. Automated sampling device **300** includes table top **302** which has more than one plane, plane one **304** and plane two **306**. Such configuration allows table top **302** to accommodate various sizes of vessels. For instance, the height of vessels in plane two **306** may be taller than vessels in plane one **304** of table top **302**.

[0066] FIGS. **6** and **7** further illustrate a drive assembly of automated sampling device **100** attached to a table top bottom. FIG. **6** provides an overview of a drive assembly in accordance with the present disclosure, depicting a linear drive **134** running parallel to center slot **120** and connected to sled **128**. FIG. **7** is an enlarged view of the drive assembly illustrated in FIG. **6**. Drive assembly **100** is comprised of motor one **138**, motor two **140**, motor three **142**, sled **136**, linear drive **134**, and controller **132**. Motor one **138** controls translation of a sample arm assembly's movements along the center slot **120** and is attached to table top bottom **144** and linear drive **134**. Various stepper motors may be used to control translation of the sample arm assembly's movements along center slot **120**. Moreover, it will be appreciated that various linear drives may be used including a worm drive. Motor two **140** controls angular rotation of a sample arm assembly and is connected to sled **136**. In an implementation, motor two **140** is a radial motor. Motor three **142** controls vertical movement of a sample arm assembly and is attached to sled **136**. Various stepper motors may be used for controlling vertical movement of the sample arm assembly. In an additional implementation, motor three **142** comprises a slip-clutch system. Further, in accordance with the present disclosure, the drive assembly may be hard-wired or, in another implementation, controlled via wireless communication. Thus, wireless communications may be used to connect controller **132** with the desired analytical instrument (not shown). Utilization of wireless communications allows sample assaying to occur without requiring physical connection with a controller computer increasing mobility of the automated sampling device.

[0067] FIG. **8** provides a detailed depiction of a sample arm assembly of an automated sampling device in accordance with the first example implementation of the present disclosure. As previously described, the sample arm assembly includes z-axis support **110** attached to a drive assembly (see FIGS. **6** and **7**), sample probe support arm **112** attached to z-axis support **110**, and sample probe **114** attached to sample probe support arm **112**. In an implementation, the sample arm assembly is attached to the drive assembly via the z-axis support extending through a center slot in the table top; in such implementation, the drive assembly is attached to a table top bottom. However, it should be understood that the drive assembly may be disposed in a variety of locations including on top of the table top without departing from the scope of the present disclosure.

[0068] In an additional implementation in accordance with the present disclosure, sample tubing **146** is present to allow sample removal or reagent delivery as desired. Further, a slip bearing is built into sample probe **114** to prevent winding of sample tubing **146**. It is contemplated that the sample may be delivered to various types of scientific instrumentation (e.g., an inductively couple plasma system, a mass spectrometer, and so forth) or a number of other types of vessels (e.g., a waste collecting bucket following a wash step). It is further contemplated that the sample tubing may be flexible (as shown) or rigid, e.g., comprised of plastic, metal, and so forth. In another implementation, the automated sampling device may be equipped with one or more independent components for the purpose of sample preparation, sample dilution, addition of standards to samples or sample acidification.

[0069] Referring to FIGS. **9A** and **9B**, tables for use with an automated sampling device are described in accordance with example implementations of the present disclosure. First, the table **102** includes a slot of length  $L$  providing for translation of the sample arm assembly along the length of the table. Further, the table **102** has a footprint for maximizing the usable area of the table **102**. As illustrated in FIG. **9A**, the table **102** has a width  $L$  substantially equal to the length of the slot  $L$ . Moreover, the table **102** is twice as long as the slot, having a length of  $2L$ . Further, the arm length of a sample probe assembly (as shown in FIGS. **1**, **2**, and **3**) is half the length of the slot, having length  $L/2$ . This configuration allows for approximately one hundred percent of the footprint of the table to be accessed. In contrast, FIG. **9B** illustrates an additional implementation in accordance with the present disclosure whereby the table is the shape of a semi-circle and a non-centered slot system is employed.

[0070] Referring to FIG. **10**, automated sampling or dispensing device **500** includes a shroud **502**.



In an example implementation, the shroud **502** substantially encloses the drive assembly **128** (FIG. **3**) for protecting the drive assembly from dust and debris, and/or preventing dust and debris from the drive assembly from contaminating samples during assaying.

[0071] FIG. **11** illustrates automated sampling device **600** completely enclosed within a hood **602**. Use of the hood allows the operations inside the hood to be isolated from the outside environment. The area within the hood may be ventilated to prevent the entry of contaminants such as bacteria or air-borne substances. In one specific implementation, the air drawn into the enclosure is passed through a high efficiency particulate air (HEPA) filter. Further, processing of samples which contain hazardous chemicals within a hood allows such samples to be processed without further exposing the user to such chemicals during processing.

[0072] Referring generally to FIGS. **12** through **19**, various implementations of an enclosure for an automated sampling/dispensing device are provided. In general, the enclosure includes at least one support member. The support member is generally perpendicular to a support surface on which the automated sampling/dispensing device is mounted. Further, a lid is mechanically coupled to the at least one support member for covering the support surface on which the automated sampling/dispensing device is mounted. Additionally, at least one flexible sheet is operationally coupled to at least one of the lid or the at least one support member. The at least one support member may provide support to both the lid as well as the at least one flexible sheet. The at least one support member, lid, and at least one flexible sheet enclose the automated sampling device while allowing access to the device by retracting the at least one flexible sheet.

[0073] The presently described example enclosures may minimize user exposure to the enclosed samples by allowing the containment of potentially hazardous chemicals within such enclosure. Further, the use of at least one flexible panel allows the enclosure to be shipped efficiently, as the enclosure may be disassembled into smaller pieces and thus be shipped in a smaller box when compared to enclosures with non-flexible panels/doors. Moreover, the use of the at least one flexible panel allows the enclosure to be shaped to accommodate varying shaped automated sampling and or dispensing devices and assemblies.

[0074] Referring to FIG. **12**, an enclosure **700** for an automated sampling/dispensing device is provided in which the enclosure **700** surrounds an automated sampling/dispensing device mounted to a circular support surface **702**. In an example implementation, the enclosure **700** includes a lid **704** for covering the support surface **702** on which the automated sampling/dispensing device is mounted. In such implementation, the lid **704** is generally equivalent in shape and size to that of the support surface **702** allowing the entire support surface **702** to be enclosed and available for use by a user. Further, an aperture for allowing the automated sampling/dispensing device to be connected with devices external to the enclosure may be defined within the lid. As illustrated in FIG. **12**, an aperture defined within the lid **704** of the enclosure **700** allows a supply tube to the automated sampling/dispensing device to be connected with external laboratory analysis equipment. In another implementation, the enclosure **700** is designed to be airtight, allowing the enclosure **700** to contain potentially hazardous chemicals without requiring unnecessary exposure to laboratory personnel during sample preparation or analysis.

[0075] As illustrated in FIG. **12**, the enclosure **700** includes a first support member **706** and a second support member **708**. The first and second support members **706** and **708** are generally perpendicular to a support surface **702** on which the automated sampling/dispensing device is mounted. For example, as illustrated in FIG. **12**, the first support member **706** and the second support member **708** are centered generally one hundred and eighty degrees ( $180^\circ$ ) opposite from one another. Moreover, such support members may be mechanically coupled to the lid **704** of the enclosure **700** as well as to the support surface **702**. For instance, fasteners such as screws, bolts, nuts, and so forth may be used to fasten the support members to the lid and support surface. In an implementation, all fasteners are either metal-free or coated with an inert plastic coating to prevent interaction of such fasteners with chemical reagents or other substances being used with the

automated sampling/dispensing device. In an additional implementation, an aperture may be formed within one or both of the support members to allow tubes, cords, and so forth to be connected to the automated sampling dispensing device contained within the enclosure as well as to external devices (e.g., laboratory analysis equipment), power sources, and so forth. It is contemplated that the lid **704** as well as the first support member **706** and the second support member **708** may be formed of inert, light-weight material including Plexiglas® (generically known as Lucite or polymethyl methacrylate.)

[0076] In additional implementations, as illustrated in FIG. **12**, a first flexible sheet **710** and a second flexible sheet **712** are operationally coupled to at least one of the lid **708** or the first support member **706** or the second support member **708**. In an implementation, the first flexible sheet **710** includes a first end and a second end. The first end of the first flexible sheet **710** includes a finished edge while the second end of the first flexible sheet **710** is fixedly coupled to the second support member **708**. For example, the first end of the flexible sheet **710** is finished with a hardened-plastic cover which extends substantially along the length of the first end of the first flexible sheet **710**. In addition, at least one guide member is attached to the first end of the first flexible sheet **710** to allow position of the first flexible sheet to be varied.

[0077] As illustrated in FIGS. **13** and **14**, the first end of the first flexible sheet **710** includes a first guide member **714** and a second guide member **716** to allow a user to slide the first flexible sheet **710** along an edge of the support surface **702**. In an implementation, the first guide member **714** and the second guide member **716** are press-fit latches allowing a user to secure the flexible sheet at multiple positions along the edge or side of the support surface. For example, a user may release the flexible sheet by applying pressure to the press-fit latches. As illustrated in FIG. **14**, a flexible sheet may be moved from a first position to a second position by guiding the first guide member **714** along the edge of the lid **704** while the second guide member is detached from the support surface **710**. It is contemplated that additional mechanisms may be employed to guide and secure the flexible sheet at various positions, including fasteners such as clips, pressure-sensitive screws, and so forth. It is further contemplated that a channel may be formed within the support surface to provide an area in which a guide member may slide and be secured.

[0078] In the present implementation, the second flexible side **712** includes a first end and a second end. The first end of the second flexible sheet **712** includes a finished edge while the second end of the second flexible sheet **712** is fixedly coupled to the second support member **708**. For example, the first end of the second flexible sheet **712** is finished with a hardened-plastic (e.g., Plexiglas®) cover which extends substantially along the length of the first end of the second flexible sheet **712**. In addition, at least one guide member is attached to the first end of the second flexible sheet **712** to allow position of the first flexible sheet to be varied. For instance, the first end of the second flexible sheet **712** may include a first guide member **714** and a second guide member **716** to allow a user to slide the second flexible sheet **712** along an edge or side of the support surface **702**. In an implementation, the first guide member **714** and the second guide member **716** are press-fit latches allowing a user to secure the flexible sheet at multiple positions along the edge or side of the support surface. It is contemplated that additional mechanisms may be employed to guide and secure the flexible sheet at various positions, including fasteners such as clips, pressure-sensitive screws, and so forth.

[0079] Referring to FIG. **15**, the first and second flexible sheets have been removed to allow access to the support surface **702**. In an implementation, the first and second flexible sheets are detachable. The detachable features of such sheets allow a user to load or remove samples efficiently from the support surface **702** so that a user does not have to reposition the sheets in order to gain access to a support surface area. It is contemplated that one or both sheets may be removed depending upon the needs of the user.

[0080] Referring to FIGS. **16** and **17**, an additional example enclosure for enclosing an automated sampling/dispensing device is provided in which the automated sampling/dispensing device is a

bench-top automated sampling dispensing device. As illustrated in FIGS. **16** and **17**, an enclosure **800** for a bench-top automated sampling dispensing device is configured in a similar manner as the enclosure **700** for a table-top automated sampling/dispensing device. The enclosure **800** includes a first support member **802** and a second support member **804** for supporting a lid **806**. In an example implementation, the lid **806** covers a support surface **808** secured to a base **810** of the bench-top automated sampling/dispensing device. In such implementation, the lid **806** is generally equivalent in shape and size to that of the support surface **808**, allowing the entire support surface **808** to be enclosed and available for use by a user. Further, the first **802** and second **804** support members are generally perpendicular to the support surface **808**.

[0081] As illustrated in FIGS. **16** and **17**, the first support member **802** and the second support member **804** are centered generally one hundred and eighty degrees ( $180^\circ$ ) opposite from one another. For example, the first support member **802** is positioned on the front side of the automated sampling/dispensing device (the front side defined as the side including a user power control panel) while the second support member **804** is positioned generally opposite the first support member **802** (e.g., to the rear side of the automated sampling/dispensing device). Moreover, such support members may be mechanically coupled to the lid **806** of the enclosure **800** as well as to the support surface **808**. For instance, fasteners such as screws, bolts, nuts, and so forth may be used to fasten the support members to the lid and support surface. In an implementation, all fasteners are either metal-free or coated with an inert plastic coating to prevent interaction of such fasteners with chemical reagents or other substances being used with the automated sampling/dispensing device.

[0082] It is contemplated that the lid **806** as well as the first support member **802** and the second support member **804** may be formed of inert, light-weight material including Plexiglas®. It is further contemplated that the enclosure **800** may include an aperture within the lid or at least one of the support members allowing for the automated sampling/dispensing device to be connected with devices external to the enclosure. For example, an aperture may be defined within the lid for allowing a supply tube to the automated sampling/dispensing device to be connected with external laboratory analysis equipment. In another implementation, the enclosure **800** is designed to be airtight allowing the enclosure to contain potentially harmful chemicals without requiring unnecessary exposure to laboratory personnel during sample preparation or analysis.

[0083] In additional example implementations, as illustrated in FIG. **17**, a first flexible sheet **812** and a second flexible sheet **814** are coupled to at least one of the lid **806** or the first support member **802** or the second support member **804**. In an implementation, each flexible sheet includes a first and second end. The first end of each flexible sheet includes a finished edge while the second end of each flexible sheet is fixedly coupled to the second support member **804**. For example, the first end of the flexible sheet **812** is finished with a hardened-plastic cover (e.g., Plexiglas®) which extends substantially along the length of the first end of the first flexible sheet **812**.

[0084] In further example implementations, at least one guide member is attached to the first end of each flexible sheet to allow the position of each flexible sheet to be varied. As illustrated in FIG. **17**, the first end of each flexible sheet includes a first guide member **816** and a second guide member **818** to allow a user to slide each sheet along an edge of the lid **806** or support surface **808**. In an implementation, the first guide member **816** and the second guide member **818** are press-fit latches allowing a user to secure the flexible sheet at multiple positions along the edge or side of the lid or support surface. For example, a user may release the flexible sheet by applying pressure to the press-fit latches. As illustrated in FIG. **17**, a flexible sheet may be moved from a first position to a second position by guiding the first guide member **816** along the edge of the lid **806** while the second guide member **818** is detached from the support surface **808**. It is contemplated that additional mechanisms may be employed to guide and secure the flexible sheet at various positions, including fasteners such as clips, pressure-sensitive screws, and so forth. It is further contemplated that a channel may be formed within the support surface to provide an area in which a guide

member may slide and be secured.

[0085] It is contemplated that the first and second flexible sheets may be detachable. The detachable features of such sheets allow a user to load or remove samples efficiently from the support surface **808** so that a user does not have to reposition the sheets in order to gain access to a support surface area. It is contemplated that one or both sheets may be removed depending upon the needs of the user.

[0086] Referring to FIGS. **18** and **19**, a further example enclosure **900** for enclosing an automated sampling/dispensing device is provided in which the enclosure **900** includes a single flexible sheet or panel **902**. As illustrated in FIGS. **18** and **19**, the enclosure **900** includes a plurality of support walls and a single flexible sheet **902** for enclosing the automated sampling/dispensing device mounted on a support surface **904**. For example, the enclosure **900** may include three support walls and the single flexible sheet **902**. In such example, a first side support wall and a second side support wall provide support to a rear support wall in which the rear support wall is secured to an edge of the first side support wall and an edge of the second side support wall. The rear support wall is generally opposite to that of the front of the enclosure (e.g., where the front of the enclosure includes the flexible sheet and is used to gain access to the automated sampling/dispensing device). The first and second side support walls are configured to allow the flexible sheet to be rolled along an outer edge of the first side support wall and an outer edge of the second side support wall. It is contemplated that an aperture may be defined within at least one of the plurality of walls for allowing the enclosed apparatus to be connected with external devices or power sources.

[0087] With continued reference to FIGS. **18** and **19**, the single flexible sheet **902** includes a first and second edge. The first end of the flexible sheet **902** includes a finished edge while the second end of the flexible sheet **902** is fixedly coupled to the rear support wall. For example, the first end of the flexible sheet **902** is finished with a hardened-plastic cover which extends substantially along the length of the first end of the flexible sheet **902**. To gain access to the interior of the enclosure **900**, the single flexible sheet **902** may be retracted with a first end of the first edge of the single flexible sheet **902** being secured to the outer edge of the first side support wall and a second end of the first edge being secured to the outer edge of the second side support wall. It is contemplated that various mechanisms may be employed to secure the first edge of the flexible sheet **902** to the side support edges including press fit latches, clips, screws, and so forth. In addition, the enclosure **900** may be mounted to an automated sampling/dispensing device for laboratory analysis equipment in which the enclosure may be positioned to enclose such device by securing the enclosure to a support area supporting the device. Moreover, the single flexible sheet may be detachable allowing a user access to the entire support surface area as well as to the over-head support surface area.

[0088] Although the presently described enclosure focuses upon the use of such enclosure with an automated sampling/dispensing device, it is contemplated that such enclosure may be employed with a variety of laboratory equipment in accordance with the present disclosure. It is further contemplated that example enclosures may be ventilated to prevent the entry of contaminants such as bacteria or air-borne substances into the external environment. For instance, the air drawn into the enclosure can be passed through a HEPA filter.

[0089] Referring now to FIG. **20**, a sample identification system **1000** for an automated sampling or dispensing device is shown in accordance with an example implementation of the pressure disclosure. The sample identification system **1000** is configured to verify a sample identity before, during, and/or after sampling and/or dispensing by the automated sampling or dispensing device occurs. As illustrated, the sample identification system **1000** includes a sample identifier **1002** and an identifier capture device **1004**. The sample identifier **1002** is configured to provide indicia of the sample, such as a sample positioned in a particular location with respect to the autosampler table top (e.g., table top **102**). The sample identifier **1002** may be configured for placement on the autosampler table top, on a sample holder (e.g., sample holder **106**), on a sample vessel (e.g.,

sample vessel **108**), or another location for reading by the identifier capture device **1004**. In an implementation, the sample identifier **1002** is located on a base or bottom of a sample vessel (e.g., sample vessel **108**), such as on the bottom of a test tube, such that the identifier capture device **1004** can access the sample identifier **1002** for processing/imaging of the sample identifier **1002** from a position beneath the sample vessel. In an implementation, the sample identifier **1002** includes a barcode configured for recognition by an optical reader (e.g., a barcode reader), where the barcode is configured to represent a particular sample according to one or more identifiers, including but not limited to, a position within a test rack, a position with respect to a table top, a particular identification number corresponding to a predetermined sampling order of sample vessels, and so forth. The barcode can include a data matrix two-dimensional (2D) barcode, such as a 12×12 matrix, a 13×13 matrix, a 14×14 matrix, or any other suitable matrix. While square matrices are provided as example data matrix barcodes, it is contemplated that rectangular matrices also may be utilized. The sample identifier **1002** can include other identification indicia including, but not limited to: characters and/or patterns configured for recognition by an optical camera or sensor; raised surfaces for recognition by touch sensors, optical sensors, and the like; illumination sources configured to generate a particular color (or wavelength), pattern of light, etc.; other identification indicia configured for recognition by the identifier capture device **1004**; and so forth. [0090] In an example implementation, the sample identification system **1000** includes an identifier arm assembly **1006** (which may be separate from or include the sample arm assembly **104**) supported by a z-axis support (which may be separate from or include the z-axis support **110**). In an implementation, the identifier arm assembly **1006** is configured to move vertically with respect to the z-axis support (shown as **110** in FIG. 20). As illustrated in FIG. 1, the z-axis is aligned with gravity or a vertical axis. The identifier arm assembly **1006** may include the identifier capture device **1004** mounted thereto, such that the identifier capture device **1004** can move to capture/image the sample identifier **1002** of various samples supported by the autosampler table top **102**, a sample holder (e.g., sample holder **106**), or other support surface. In use, identifier arm assembly **1006** is configured to be moved through space in three dimensions, or about an axis having y-motion that is a substantially rotary motion and along an axis having x-motion which is an at least substantially horizontal linear motion or translation, and along a z-axis that is an at least substantially vertical, linear motion or translation. As such, the identifier arm assembly **1006** may be configured for movement through an R-theta range of motion, an x-y range of motion, and the like, such as between a rest position and an operating position configured to image sample vessels including sample identifiers **1002**. In an implementation, the identifier arm assembly **1006** is configured to move independently from the sample arm assembly **104**.

[0091] In an implementation, as shown in FIG. 20, the autosampler includes a raised surface **1008** configured to be supported by the autosampler table top **102**. The raised surface **1008** can support sample holders and sample vessels for access by the sample probe **114**. The raised surface **1008** may be positioned with respect to the table top **102** such that the raised surface **1008** and the table top **102** define a gap **1010** into which the identifier arm assembly **1006** and identifier capture device **1004** can enter for access to the underside of the sample vessels (e.g., sample vessels **108**) and associated sample identifiers **1002**. For instance, in implementations, the raised surface **1008** defines gaps **1012** in the surface over which the sample vessels **108** having sample identifiers **1002** positioned on a bottom surface are situated. In this manner, the sample identifiers **1002** at the base or bottom of the sample vessels **108** are accessible to the identifier capture device **1004** when positioned beneath the raised surface **1008** in the gap **1010** (such as shown in FIG. 22). The raised surface **1008** can also define a center slot **1014** to correspond to at least a portion of the center slot **120** of the table top **102** to permit motion of the sample arm assembly **104** across the raised surface **1008** and the corresponding portion of the table top **102** (such as shown in FIGS. 21A through 21C).

[0092] In example implementations, the autosampler includes sample holders (e.g., sample racks

**106**) configured to permit the identifier capture device **1004** to read the sample identifier **1002**. For example, a base of the sample holders **106** may be constructed from a substantially clear, light transmissive, or transparent material. In other embodiments, the sample holder **106** may be constructed with an open bottom. Use of a light transmissive or transparent material may protect the identifier capture device **1004** from inadvertent contact with sample fluids within the sample vessels **108**. In an implementation, the sample holders are formed of, or are coupled with, a material configured to reduce or eliminate glare associated with light when utilizing the identifier capture device **1004**. Alternatively or additionally, the identifier capture device **1004** can include a protective coating or covering to protect the identifier capture device **1004** from inadvertent contact with the sample fluids. Such coating or covering of may be configured to reduce or eliminate glare associated with light when utilizing the identifier capture device **1004**. In an implementation (such as shown in FIG. 23A), the sample holder **106** includes a substantially transparent bottom **1120**, through which the image capture device **1004** can recognize the sample identifier **1002** on a base of a sample vessel **108** supported by the sample holder **106**. In an implementation (such as shown in FIGS. 22 and 23B), the sample holder **106** defines a first set of apertures **1016**, through which the sample vessels **108** may pass, and a second set of apertures **1018** which prohibit at least a portion of the sample vessels **108** from completely passing through. For instance, the first set of apertures **1016** can have a larger cross-sectional area (e.g., larger diameter with larger circular cross-sectional area) than the second set of apertures **1018**, where the second set of apertures **1018** have a cross-sectional area that is smaller than a cross-sectional area of the sample vessels **108** (e.g., the diameter of the second set of apertures **1018** is less than the diameter of a portion of the sample vessels **1018**). Such a configuration of apertures may provide an exposed bottom portion of the sample vessel **108** such that the sample identifier **1002** is unobstructed with respect to the identifier capture device **1004**. In an example implementation, the sample holder **106** includes a raised base, such that the sample vessels **108** within the holder **106** are positioned over the autosampler table top **102** with a gap between the base of the sample holder **106** and the autosampler table top **102**. Such a configuration may permit the identifier capture device **1004** access beneath the sample holder to read the sample identifier **1002**. It is contemplated that the size, shape, and materials comprising the sample holder **106** may vary depending on the type, size, and shape of the identifier capture device **1004** used in the sample identification system **1000**, and the type of samples to be analyzed (e.g., corrosive, inert, and so forth).

[0093] The autosampler may be configured to align the identifier capture device **1004** with the sample probe **114**. For example, as shown in FIG. 24, the identifier capture device **1004** includes an alignment light source **1022** configured to project light (e.g., a light beam) toward the sample probe **114**. In an implementation, the raised surface **1008** defines an aperture **1024** through which the alignment light source **1022** can project the light toward the sample probe **114**. Where the positioning of the sample probe **114** with respect to the identifier capture device **1004** is not aligned, one or more of the sample arm assembly **104** and the identifier arm assembly **1006** can be repositioned until the alignment is satisfactory. The repositioning can be accomplished through an automatic, motorized movement of the sample arm assembly **104** and the identifier arm assembly **1006** (e.g., through control of drive assembly **100**) or through manual means. For example, one or more of the sample arm assembly **104** and the identifier arm assembly **1006** can be secured with a set screw, with press fit, with a friction clamp, and so forth. The alignment may assist in accuracy of the correspondence between the imaged sample identifier **1002** by the identifier capture device **1004** and the actual sample drawn by the sample probe **114** from the sample vessel **108**.

[0094] The identifier capture device **1004** is configured to capture, image, or otherwise recognize the sample identifier **1002**. Accordingly, in an implementation such as shown in FIG. 25, the identifier capture device **1004** includes an imaging device **1026**, a light source **1028** (e.g., a flash source), and the alignment light source **1022**. The imaging device **1026** can capture video images

of the sample identifiers **1002** and surrounding areas, such that the imaging device **1026** can be associated with a display for displaying the captured images, such as on a live or continuous basis. In an implementation, the imaging device is configured to provide still images of a target. The light source **1028** may be configured to illuminate the bottom of the sample vessels **108** such that the sample identifier **1002** has increased visibility to the imaging device **1026** in order to image the sample identifier **1002**. In an implementation, the identifier capture device **1004** is aided by an external light source **1030** to provide illumination in addition to or instead of the light source **1028**. For example, the external light source **1030** can be mounted on the identifier arm assembly **1006**.

[0095] In implementations, the identifier capture device **1004** is angled relative to the identifier arm assembly **1006**, such that the imaging device **1026** views the sample identifier **1002** on the base of the sample vessel **108** at an angle from the horizontal or with respect to the orientation of the autosampler table top. For example, as shown in FIG. 26A, the identifier capture device **1004** and the identifier arm assembly **1006** are oriented at an angle of alpha ( $\alpha$ ) (e.g., 15 degrees) relative to each other, where a top surface of the identifier arm assembly **1006** is substantially perpendicular to the alignment axis (e.g., substantially parallel to the surface of table top). In FIG. 26B, the identifier capture device **1004** and the identifier arm assembly **1006** are oriented at an angle of alpha ( $\alpha$ ) (e.g., 15 degrees) relative to each other, where a top surface of the identifier capture device **1004** is substantially perpendicular to the alignment axis (e.g., substantially parallel to the surface of table top). Various configurations of the angle are contemplated, where the angle utilized may depend on the particular imaging device **1026** utilized in the identifier capture device **1004**.

[0096] The sample identification system **1000** is configured to verify data associated with the sample identifier **1002**, and correspondingly, the sample uniquely associated with the sample identifier **1002**, before, during, or after sampling of the sample by the autosampler sampling probe (e.g., sample probe **114**). The sample identification system **1000** may collect and process data associated with the sample identifier **1002**, where the data can include, but is not limited to, the location of a sample (e.g., a location on the autosampler table top **102**, a location within a sample rack **106**, a particular sample vessel **108**, and so forth), a timestamp of when a sample is taken (e.g., by the sample probe **114**), presence or absence of a sample, type or extent of analysis to be performed on a sample, dilution factor, and the like. In an implementation, the sample identifier **1002** is read by the identifier capture device **1004** for conversion to a serial number, where data associated with the serial number is associated with the particular sample vessel that includes the sample identifier **1002**. In this manner, the sample identifier **1002** can associate data including, but not limited to, the location of a sample, timestamp of when a sample is taken, presence or absence of a sample, type or extent of analysis to be performed on a sample, dilution factor, and the like with a particular sample in the vessel, where the data can be stored in a memory device of a data system to be correlated with the serial number stored by the sample identifier **1002**. In an implementation, the sample identification system **1000** can be configured for dilution factor control of a sample. For example, the data associated with a particular sample identifier **1002** can include a dilution factor for offline or online dilution of a sample. In an implementation, the sample identification system **1000** is configured to populate data of prepared samples, such as by filling in standards data into data tables automatically, based on the sample identifier **1002** and the results of a sample analysis by an analyzer (e.g., mass spectrometer, gas chromatograph, liquid chromatograph, and the like) of the particular sample.

[0097] The sample identifier **1002** can be associated with and/or comprise information including, but not necessarily limited to: a sample vial identification number, a destination vial identification number, a dilution factor (DF), a final volume, a sample volume, a diluent volume, a diluent location, and so forth. For example, a first barcode is placed on a sample vial and associated with a desired dilution factor and a desired final volume. A destination vial includes a second barcode associated with the first barcode. The system **1000** uses information obtained from the first barcode to dilute a portion of a sample contained in the sample vial. For instance, the system **1000** identifies

the destination vial using the second barcode and deposits a portion of the sample into the destination vial. The system **1000** also deposits an amount of diluent sufficient to provide the DF and final volume specified by the first barcode.

[0098] In another embodiment, the first barcode is representative of a sample vial identification number, and the sample identification number is associated with a desired dilution factor and a desired final volume. In some embodiments, a user interface (e.g., a graphical user interface) included with an information handling system device operatively coupled with the sample identification system **1000** via a communications interface is used to associate the first barcode with the desired dilution factor and the desired final volume. For instance, the desired dilution factor and the desired final volume can be stored in an electronic database with the first barcode. A destination vial includes a second barcode associated with the first barcode (e.g., via the electronic database). The system **1000** uses information associated with the first barcode in the electronic database to dilute a portion of the sample contained in the sample vial. For instance, the system **1000** identifies the destination vial using the association with the second barcode and deposits a portion of the sample into the destination vial. The system **1000** also deposits an amount of diluent sufficient to provide the DF and final volume specified in the electronic database.

[0099] However, these off-line embodiments are provided by way of example only and are not meant to limit the present disclosure. In other embodiments, dilution of a sample can be performed on-line. For example, the system **1000** uses information obtained from a barcode to dilute a portion of a sample contained in the sample vial by mixing the sample portion with an amount of diluent sufficient to provide a desired DF and a desired final volume as specified by a first barcode, associated with the first barcode in an electronic database, and so forth.

[0100] The data collected by the sample identification system **1000** may be transferred to another system for identity verification. In an example implementation, the data collected by the sample identification system **1000** is transferred to a laboratory information management system (LIMS) and/or a laboratory instrument to verify the identity of a measured sample. The identifier capture device **1004** may be configured for wired or wireless data transfer between the sample identification system **1000** and the LIMS, laboratory instrument, or other device. In an example embodiment, the identifier capture device **1004** is configured for fiber optic data transfer. The identifier capture device **1004** may be configured for control by the sample identification system **1000** via wired or wireless control mechanisms.

[0101] A sample identification system **1000**, including some or all of its components, can operate under computer control. For example, a processor can be included with or in a sample identification system **1000** to control the components and functions of systems **1000** described herein using software, firmware, hardware (e.g., fixed logic circuitry), manual processing, or a combination thereof. The terms “controller,” “functionality,” “service,” and “logic” as used herein generally represent software, firmware, hardware, or a combination of software, firmware, or hardware in conjunction with controlling the systems **1000**. In the case of a software implementation, the module, functionality, or logic represents program code that performs specified tasks when executed on a processor (e.g., central processing unit (CPU) or CPUs). The program code can be stored in one or more computer-readable memory devices (e.g., internal memory and/or one or more tangible media), and so on. The structures, functions, approaches, and techniques described herein can be implemented on a variety of commercial computing platforms having a variety of processors.

[0102] A processor provides processing functionality for the system **1000** and can include any number of processors, micro-controllers, or other processing systems, and resident or external memory for storing data and other information accessed or generated by the system **1000**. The processor can execute one or more software programs that implement techniques described herein. The processor is not limited by the materials from which it is formed or the processing mechanisms employed therein and, as such, can be implemented via semiconductor(s) and/or transistors (e.g.,



using electronic integrated circuit (IC) components), and so forth.

[0103] The system **1000** also includes a memory. The memory is an example of tangible, computer-readable storage medium that provides storage functionality to store various data associated with operation of the system **1000**, such as software programs and/or code segments, or other data to instruct the processor, and possibly other components of the system **1000**, to perform the functionality described herein. Thus, the memory can store data, such as a program of instructions for operating the system **1000** (including its components), and so forth. It is noted that while a single memory is described, a wide variety of types and combinations of memory (e.g., tangible, non-transitory memory) can be employed. The memory can be integral with the processor, can comprise stand-alone memory, or can be a combination of both. The memory can include, but is not necessarily limited to: removable and non-removable memory components, such as random-access memory (RAM), read-only memory (ROM), flash memory (e.g., a secure digital (SD) memory card, a mini-SD memory card, and/or a micro-SD memory card), magnetic memory, optical memory, universal serial bus (USB) memory devices, hard disk memory, external memory, and so forth. In implementations, the system **1000** and/or the memory can include removable integrated circuit card (ICC) memory, such as memory provided by a subscriber identity module (SIM) card, a universal subscriber identity module (USIM) card, a universal integrated circuit card (UICC), and so on.

[0104] The system **1000** includes a communications interface. The communications interface is operatively configured to communicate with components of the system **1000**. For example, the communications interface can be configured to transmit data for storage in the system **1000**, retrieve data from storage in the system **1000**, and so forth. The communications interface is also communicatively coupled with the processor to facilitate data transfer between components of the system **1000** and the processor (e.g., for communicating inputs to the processor received from a device communicatively coupled with the system **1000** and/or communicating output to a device communicatively coupled with the system **1000**). It is noted that while the communications interface is described as a component of a system **1000**, one or more components of the communications interface can be implemented as external components communicatively coupled to the system **1000** via a wired and/or wireless connection. The system **1000** can also comprise and/or connect to one or more input/output (I/O) devices (e.g., via the communications interface) including, but not necessarily limited to: a display, a mouse, and so on.

[0105] The communications interface and/or the processor can be configured to communicate with a variety of different networks including, but not necessarily limited to: a wide-area cellular telephone network, such as a 3G cellular network, a 4G cellular network, or a global system for mobile communications (GSM) network; a wireless computer communications network, such as a WiFi network (e.g., a wireless local area network (WLAN) operated using IEEE 802.11 network standards); an internet; the Internet; a wide area network (WAN); a local area network (LAN); a personal area network (PAN) (e.g., a wireless personal area network (WPAN) operated using IEEE 802.15 network standards); a public telephone network; an extranet; an intranet; and so on. However, this list is provided by way of example only and is not meant to limit the present disclosure. Further, the communications interface can be configured to communicate with a single network or multiple networks across different access points.

[0106] In an implementation, as shown in FIG. 27, the sample holder **106** includes a sample holder identifier **402** positioned on a bottom portion **404** of the sample holder **106**. The bottom portion **404** can correspond to a side of the sample holder **106** that is opposite or distal a side of the sample holder **106** that receives the sample vessels **108** via the first set of apertures **1016** (e.g., for holding the sample vessels upright for access by the sample probe **114**). For example, the bottom portion **104** can define the second set of apertures **1018**, the bottom portion can include the transparent bottom **1120**, or so forth. The sample holder identifier **402** is identifiable by an identifier capture device, such as the identifier capture device **1004** of the sample identification system **1000**. The

sample holder identifier **402** provides a unique identification of the sample holder **106**, where such unique identification can correspond to identification information including, but not limited to, sample identities, analysis methods associated with samples held in sample vessels **108** in the sample holder **106**, elements/species associated with samples held in sample vessels **108** in the sample holder **106**, dilution factors associated with samples held in sample vessels **108** in the sample holder **106**, weights associated with samples held in sample vessels **108** in the sample holder **106**, final volumes associated with samples held in sample vessels **108** in the sample holder **106**, and the like. Such corresponding identification information can be stored in a memory device accessible by one or more components of the automated sampling device or associated scientific instrumentation coupled thereto. For example, the sample holder identifier **402** may include one or more of a barcode or a QR code associated with the unique identification of the sample holder **106**. In an implementation, the sample holder identifier **402** includes a data matrix two-dimensional barcode in a square matrix form (e.g., a 12×12 matrix, a 13×13 matrix, a 14×14 matrix, a 144×144 matrix etc.). While square matrices are provided as example data matrix barcodes, it is contemplated that rectangular matrices (e.g., a 8×18 matrix, a 16×48 matrix, etc.), or any other suitable matrix also may be utilized. The sample holder identifier **402** can include other identification indicia including, but not limited to: characters and/or patterns configured for recognition by an optical camera or sensor; raised surfaces for recognition by touch sensors, optical sensors, and the like; illumination sources configured to generate a particular color (or wavelength), pattern of light, etc.; other identification indicia configured for recognition by the identifier capture device **1004**; and so forth.

[0107] While the sample holder identifier **402** is shown in FIG. 27 on the bottom portion **404** of the sample holder **106**, other configurations of the sample holder identifier **402** with respect to the sample holder **106** can be utilized, including, but not limited to, the sample holder identifier **402** being located on a top portion, a side portion, a support post portion, or the like, such that an identifier capture device can recognize the sample holder identifier **402**. For example, in an implementation, the sample holder identifier **402** is positioned on a top portion of the sample holder **106** (e.g., proximate the first set of apertures **1016**), for access by an identifier capture device associated with the sample arm assembly **104**, the z-axis support **110**, the sample probe **114**, or other perspective above the table top **102**.

[0108] In an implementation, the sample holder identifier **402** includes more than one sample holder identifier (e.g., FIG. 27 shows two sample holder identifiers, labeled **402a** and **402b**), where each sample holder identifier corresponds to a different orientation of the sample holder **106**. For example, sample holder identifier **402a** can include identification information that corresponds to a top, front, or side orientation of the sample holder **106**, whereas sample holder identifier **402b** can include identification information that corresponds to a bottom, back, or different side orientation of the sample holder **106**. As used herein, the orientation of the sample holder **106** can refer to a placement orientation used to align the sample holder **106** on a surface of an autosampler or sample identification device for processing of samples (e.g., on raised surface **1008**, on table top **102**, etc.). For example, the placement orientation can identify an orientation and/or position of the sample holder **106** relative to the center slot **1014**, the sample arm assembly **104**, the z-axis support **110**, the sample probe **114**, or other component or portion of the automated sampling device **100**.

[0109] In an implementation, as depicted in FIGS. 28A and 28B, sample vessels **108** are positioned in slots **406** (or apertures), numbers one to four, distal to a z-axis support **110** of an automated sampling or dispensing device, where the slots correspond to positions in the sample holder **106** configured to hold sample vessels **108**. The sample holder **106** can include labels to identify the particular slots **406** to a user, such as to provide an order in which to place the sample vessels within the slots **406**. For example, the sample holder **106** can include labels to identify the slots **406** with the numbers corresponding to those diagrammatically shown in FIG. 28B. In an implementation, the sample holder identifier **402b** is positioned on the same side of the sample

holder **106** as the slot **406** labeled with position one, such that when the sample holder **106** is placed in the reverse or flipped orientation, each of the sample holder identifier **402b** and the side of the sample holder **106** having the slot **406** labeled with position one will be adjacent the center slot **120** (e.g., as shown in FIG. **29A**). For example, the sample holder identifier **402a** can be positioned on the opposite side of the sample holder **106** (e.g., on the bottom portion of the sample holder **106**) as the slot **406** labeled with position one (e.g., the first designation in a series, such as the numbering series of slots **406**), such that when the sample holder **106** is placed in the standard orientation, the sample holder identifier **402a** will be adjacent the center slot **120**, and the side of the sample holder **106** having the slot **406** labeled with position one will be distal the center slot **120** (e.g., as shown in FIG. **28A**). The sample holder **106** can include a sample holder identifier **402** configured to provide dynamic data associated with the sample holder **106** including, but not limited to, a unique rack identification (ID), a position of the sample holder **106**, an orientation of the sample holder **106** (e.g., a standard orientation, a reverse or flipped orientation, etc.), an alignment of the sample holder **106**, and the like. For example, the sample holder identifier **402** can correspond to the dynamic data stored in memory, whereby a data controller, system processor, or the like can assign and/or update the dynamic data, such as responsive to user input, responsive to automatic implementation by the system **100**, or the like. In an implementation, the system **1000** determines an orientation a sample holder **106** (e.g., standard orientation shown in FIGS. **28A**, **28B**; reverse or flipped orientation shown in FIGS. **29A**, **29B**) by positioning the identifier capture device **1004** in a sample holder read position (shown as **408** in FIGS. **27** and **28A**) that corresponds to a position underneath the sample holder identifier **402** when the sample holder **106** is placed on the table top **102**, the raised surface **1008**, or otherwise positioned for allowing access to the sample vessels **108** by the sample probe **114**. Generally, the sample holder reader position corresponds to the positioning of the identifier capture device **1004** to read the sample holder identifier **402**. The system **1000** can include a plurality of sample holder read positions when multiple sample holders **106** are present on the on the table top **102**, the raised surface **1008**, etc. In an implementation, a user can input information associated with the placement of the sample holders **106**, including location and number of the individual sample holders **106**, whereby the system **1000** can automatically scan only the relevant sample holder read positions to identify the orientation of the sample holders **106** present (e.g., by ignoring sample holder read positions at locations where no sample holder **106** is present).

[0110] The sample holder identifier **402** can then inform the system **1000** about whether the sample holder **106** is in a standard orientation or a reverse or flipped orientation. The system **1000** can manipulate the operational positioning of the sample probe **114** based on the detected orientation of the sample holder **106**. For example, when the sample holder **106** is determined to be in the standard orientation (e.g., the identifier capture device **1004** detects the sample holder identifier **402A** in the sample holder read position), the system **1000** can operate according to a standard orientation protocol. The standard orientation protocol can involve, for example, initially positioning the sample probe **114** to measure the sample vessel **108** in position one of slots **406**, shown in FIG. **28B**, where position one is distal to the center slot **120**, and proceeding to position the sample probe **114** to sequentially measure the remaining sample vessels **108** based on slot number (e.g., continuing to slots two, three, and four). When the sample holder **106** is determined to be in the reverse or flipped orientation (e.g., the identifier capture device **1004** detects the sample holder identifier **402B** in the sample holder read position), the system **1000** can operate according to a reverse orientation protocol. The reverse orientation protocol can involve, for example, initially positioning the sample probe **114** to measure the sample vessel **108** in position one of slots **406**, shown in FIG. **29B**, where position one is adjacent to the center slot **120**, and proceeding to position the sample probe **114** to sequentially measure the remaining sample vessels **108** based on slot number (e.g., continuing to slots two, three, and four). In implementations, the system **1000** can provide an alert (e.g., via a display device) based upon detection of the particular orientation of

the sample holder **106**. For example, when a reverse orientation of the sample holder **106** is detected, the system **1000** can display an alert to an operation, notifying that the sample holder **106** is in the reverse orientation. The system **1000** can receive user input to continue operation with the sample holder **106** in the reverse orientation (e.g., by implementing the reverse orientation protocol), or alternatively, can receive user input to delay operation, such as to permit repositioning of the sample holder **106** and/or sample vessels **108**. When user input is received to delay operation, the system **1000** may scan any sample holder identifiers **402** at the sample holder read position and/or may scan the sample identifiers **1002** of any sample vessels **108** present in the sample holder upon resuming operation, such as to determine whether the user placed the sample holder **106** in the standard orientation, in the reverse orientation, changed the order of sample vessels **108** within the sample holder **106**, change the number of sample vessels **108** within the sample holder **106**, or the like.

[0111] In implementations, the sample vessel positions shown in FIG. **28A** correspond with a graphical representation of the sample vessels positions within the sample holder **106** shown on a communications interface operably coupled to the automated sampling or dispensing device **100**, as shown in FIG. **28B**. The communications interface can also show the presence (shown as **410**) or absence (shown as **412**) of the sample vessel **108** within a particular sample slot **406**, whereby detection of the sample vessel **108** within a particular slot **406** is automatically shown as the presence **410** of the sample vessels **108** via the communications interface. For example, the automated sampling or dispensing device (e.g., via identifier capture device **1004**) can detect sample vessels **108** positioned in the slots **406** via the sample identifiers **1002**, where the communications interface can provide a graphical representation (e.g., as shown in FIG. **28B**) of the presence of the sample vessels **108** relative to the orientation of the sample holder **106** (e.g., via detection of the sample holder identifier **402** information), such that the sample vessels **108** are shown distal the center slot **120** in the proper order/configuration. The presence of the particular sample vessels **108** in the slots **406** and the orientation of the sample holder **106** provide the system **1000** with the information as to which slots **406** the sample probe **114** should position above during its operation protocol. The communications interface can generate a sample list based on sample identifiers **1002** associated with the sample vessels **108** positioned in the sample holder **106** and based on the sample holder identifier **402** positioned on the sample holder **106**. Such sample list can be generated after scanning the sample identifiers **1002** and the sample holder identifier **402**, and can be populated with data associated with the analysis of the samples once completed, or on an individual sample vessel basis.

[0112] In an implementation, as depicted in FIG. **29A**, an automated sampling or dispensing device is shown with sample vessels **108** positioned in slots **406**, numbers one to four, adjacent to a z-axis support **110**. For instance, the sample rack is in the reverse or flipped orientation, where the samples vessels **108** are positioned in a reverse or flipped orientation as compared to the positioning in FIGS. **28A** and **28B**. By including one or more sample holder identifier **402**, the automated sampling or dispensing device can detect the reverse or flipped orientation of the samples and maintain an accurate accounting for the samples and the analyses of the samples. For example, the communications interface can provide a graphical representation (e.g., as shown in FIG. **29B**) of the presence of the sample vessels **108** in the slots, relative to the sample holder identifier **402** information, such that the sample vessels **108** are shown adjacent the center slot **120** in the proper order/configuration.

[0113] While sample holder identifiers **402** and sample identifiers **1002** have been described herein, it is noted that other aspects or components of the automated sampling or dispensing device can include labels configured for detection by identifier capture device **1004**. For example, diluents, diluent holders, standards, standard holders, eluents, eluent holders, buffers, buffer holders, waste vessels, and the like can include identifiers (e.g., data matrix two-dimensional barcode) for tracking of the positioning of the respective items.

[0114] In an implementation, as shown in FIG. 30A, a plurality of scientific standard solution vessels **1032** are positioned relative to an automated sampling or dispensing device (e.g., sample identification system **1000**), where the scientific standard solution vessels **1032** and any scientific standard solutions contained therein are accessible by a sample probe (e.g., sample probe **114**). The scientific standard solution vessels **1032** each include one or more standard identifiers **1034** positioned on the scientific standard solution vessels **1032**. For example, the standard identifiers can be positioned on a portion (e.g., bottom portion, top portion, side portion, etc.) of the scientific standard solution vessels **1032** for access by the identifier capture device **1004**. FIG. 30B shows the standard identifier **1034** positioned on a bottom portion of a scientific standard solution vessel **1032**. The standard identifier **1034** can include, but is not limited to, one or more of a barcode or a QR code. In an implementation, the standard identifier **1034** includes a data matrix two-dimensional barcode in a square matrix form (e.g., a 12×12 matrix, a 13×13 matrix, a 14×14 matrix, a 144×144 matrix etc.). While square matrices are provided as example data matrix barcodes, it is contemplated that rectangular matrices (e.g., a 8×18 matrix, a 16×48 matrix, etc.), or any other suitable matrix also may be utilized. The standard identifier **1034** can include other identification indicia including, but not limited to: characters and/or patterns configured for recognition by an optical camera or sensor; raised surfaces for recognition by touch sensors, optical sensors, and the like; illumination sources configured to generate a particular color (or wavelength), pattern of light, etc.; other identification indicia configured for recognition by the identifier capture device **1004**; and so forth. The standard identifier **1034** is identifiable by an identifier capture device, such as the identifier capture device **1004** of the sample identification system **1000**. The standard identifier **1034** can provide a unique identification of the scientific standard solution vessel **1032** and/or the scientific standard solution contained therein, where such unique identification can correspond to identification information including, but not limited to, standard identity, expiration status associated with the standard, analysis methods associated with the standard, matrices associated with the standard, elements/species associated with the standard, concentrations of the standard, and the like. Such corresponding identification information can be stored in a memory device accessible by one or more components of the automated sampling device or associated scientific instrumentation coupled thereto. In an implementation, the standard identifier **1034** is associated with an expiration status associated with a scientific standard solution located in the scientific standard solution vessel **1032** on which the standard identifier **1034** is positioned. The expiration status can include, but is not limited to, an expiration date, an indication that the scientific standard solution is expired, an indication that the scientific standard solution is about to expire (the current date is within a threshold time period (e.g., one day, one week, one month, etc.) of the expiration date), an initial preparation date, and so forth.

[0115] In an implementation, when the standard identifier **1034** is scanned and/or observed by the identifier capture device **1004**, the identifier capture device **1004** can generate one or more data signals associated with the standard identifier **1034** that is associated with the expiration status of the scientific standard solution contained in the particular scientific standard solution vessel **1032**. For example, the system **1000** can initiate a standard identifier protocol whereby the identifier capture device **1004** passes underneath the scientific standard solution vessels **1032** in a sequential manner (e.g., beginning at position **1** shown in FIG. 30C, continuing on to position **2**, then continuing onto position **3**, then continuing onto position **4**, then, continuing onto position **5**, etc.) to detect the presence (shown as **1036** in FIG. 30C) or absence (shown as **1038** in FIG. 30C) of a scientific standard solution vessel **1032** in a particular standard position. For instance, when the identifier capture device **1004** recognizes the standard identifiers **1034** associated with the scientific standard solution vessels **1032**, the location of the scientific standard solution vessels **1032** can be shown via a communications interface, as depicted in FIG. 30C. Further, data associated with the scientific standard solutions contained in the scientific standard solution vessels **1032**, provided by the standard identifiers **1034**, can be displayed via the communications interface, such as shown in

FIG. 30D (e.g., in tabular form). The communications interface can provide an expiration status of the individual scientific standard solutions, which can be displayed relative to the positions of the scientific standard solution vessels **1032**. For example, FIG. 30D includes an expiration date or an expiration status **1040** of each of the three scientific standard solutions identified by the identifier capture device **1004**, where the communications interface provides an indication that the scientific standard solution associated with position or vial **3** has expired (e.g., such as by comparing an expiry date with a current date). In an implementation, the system **1000** can provide an alert (e.g., via a display device) based upon detection of an expired scientific standard solution present in a scientific standard solution vessels **1032** via the standard identifier **1034** (e.g., the expiration status is indicative of an expired scientific standard solution). The system **1000** can automatically stop operation of the sample probe **114** upon detection of the expired scientific standard solution to prevent addition of the expired scientific standard solution to any of the sample vessels **108**. The system **1000** can receive user input to delay operation, such as to permit placement of a new scientific standard solution vessel **1032** in the position occupied by the expired scientific standard solution. When user input is received to delay operation, the system **1000** may scan the standard identifiers **1034** of any scientific standard solution vessels **1032** present upon resuming operation, such as to determine whether the user changed the order of scientific standard solution vessels **1032**, change the number of scientific standard solution vessels **1032**, introduced new scientific standard solution vessel(s) **1032** having new standard identifier(s) **1034**, or the like.

[0116] In an implementation, as depicted in FIGS. 31 through 34, the autosampler/dispensing device includes an enclosed sample holder **1102**. For example, the enclosed sample holder **1102** can have solid side portions, forming a block. The enclosed sample holder **1102** may be constructed from a heat resistive and/or heat retentive material including, but not necessarily limited to: aluminum, tungsten, nickel, titanium, graphite, heat resistant plastic, and so forth. The enclosed sample holder **1102** can be configured to heat the samples by dispersing heat throughout the sample vessels **108**. For example, the enclosed sample holder **1102** can be removably coupled to a heating element **1104** (such as shown in FIG. 31). In some implementations, the heating element **1104** comprises a relatively flat platform configured to receive the enclosed sample holder **1102** (e.g. a bottom portion of the enclosed sample holder **1102** rests on the platform). However other types of heating elements may be utilized. Heating the samples vessels **108** can reduce the viscosity of the samples (e.g., to improve the accuracy of the automated sampling or dispensing device, to facilitate transfer of a viscous sample through an analytical instrument and/or sample preparation system, or so forth). Alternatively, the enclosed sample holder **1102** can be utilized to reduce exposure of high sensitivity samples (e.g., light-sensitive samples). In some implementations, the enclosed sample holder **1102** defines a first set of apertures **1016**, through which the sample vessels **108** may pass, and a second set of apertures **1018** which prohibit at least a portion of the sample vessels **108** from completely passing through, as described above. In an implementation (such as shown in FIGS. 31 through 33), the enclosed sample holder **1102** includes a sampling base **1106**. The sampling base **1106** can be removably coupled to the enclosed sample holder **1102** so that the bottom portion of the enclosed sample holder **1102** sits within the sampling base **1106**. For example, the sampling base can include one or more rim portions **1108** configured to retain the enclosed sample holder **1102**. In some implementations, the sampling base **1106** can include a third set of apertures **1110** that correspond to the second set of apertures **1018** (e.g., the diameter of the third set of apertures **1110** is approximately equal to the diameter of the second set of apertures **1018**). Such a configuration of apertures may provide an exposed bottom portion of the sample vessel **108** such that a sample identifier **1002** positioned on the base of the sample vessel **108** is unobstructed with respect to an identifier capture device **1004**. Alternatively, a bottom portion of the enclosed sample holder **1102** and/or the sampling base **1106** may be constructed from a substantially clear, light transmissive, or transparent material to expose the bottom portion of the sample vessels **108**. It is contemplated that the size, shape, and materials comprising the enclosed sample holder **1102** and/or

the sampling base **1106** may vary depending on the type, size, and shape of the identifier capture device **1004** used in the automated sampling/dispensing device, and the type of samples to be analyzed (e.g., corrosive, inert, and so forth).

[0117] In example implementations, the support surface (e.g., table top **102**) of the automated sampling/dispensing device can be configured to mate with the sample holder **1102** (such as shown in FIGS. **33** and **34**). For example, the sampling base **1106** can include one or more protrusions **1112** (e.g., feet). The table top **102** can be keyed with corresponding recesses **1114** configured to mate with the protrusions **1112**. Alternatively, the protrusions **1112** can be located on the bottom portion of the enclosed sample holder **1102**. By configuring the table top **102** to mate with the sampling base **1106** and/or the enclosed sample holder **1102**, the sampling base **1106** and/or sample holder **1102** is properly oriented for detection by the sample arm assembly **104** and/or the identifier capture device **1004**). For example, the front portion or top portion of the sample holder **1102** is directionally oriented with respect to the sample arm assembly **104** and/or the identifier capture device **1004**.

[0118] In some implementations, the enclosed sample holder **1102** can include a sample holder identifier **402** configured to provide dynamic data associated with the enclosed sample holder **1102** including, but not limited to, a unique rack identification (ID), a position of the enclosed sample holder **1102**, an orientation of the enclosed sample holder **1102** (e.g., a standard orientation, a reverse or flipped orientation, etc.), an alignment of the enclosed sample holder **1102**, and the like, as described above. In some implementations, the sample holder identifier **402** can be located on the sampling base **1106**. Alternatively, the sample holder identifier **402** can be located on a top portion, a bottom portion, a side portion, a support post portion, or the like, of the enclosed sample holder **1102**, such that the identifier capture device **1004** can recognize the sample holder identifier **402**. For example, the sampling base **1106** can include an aperture configured to expose a sample holder identifier **402** located on a bottom portion of the enclosed sample holder **1102**. In some implementations, the enclosed sample holder **1102** can be directionally keyed to fit within the sampling base **1106** in a particular orientation. By keying the enclosed sample holder **1102**, the automated sampling or dispensing device can detect the orientation of the enclosed sample holder **1102** and/or the proper order/configuration of sample vessels **108** from sample holder identifiers **402** located on the sampling base **1106**. For example, a sample holder identifier **402a** including identification information that corresponds to a front orientation of the enclosed sample holder **1102** will correspond to the orientation of both the enclosed sample holder **1102** and the sampling base **1106**.

[0119] In some implementations, the identifier capture device **1004** can be positioned beneath the table top **102**, as described above. For example, the autosampler can include a raised surface **1008** configured to be supported by the autosampler table top **102** (such as shown in FIGS. **21A** through **21C**). For instance, in implementations, the raised surface **1008** defines gaps **1012** in the surface over which the enclosed sample holders **1102** and/or sample vessels **108** having sample holder identifiers **402** and sample identifiers **1002**, respectively, positioned on a bottom surface are situated. In this manner, the sample holder identifiers **402** and/or sample identifiers **1002** at the base or bottom of the sample vessels **108** are accessible to the identifier capture device **1004** when positioned beneath the raised surface **1008** in the gap **1010** (such as shown in FIG. **22**).

Alternatively, the table top **102**, or a portion thereof, may be constructed from a substantially clear, light transmissive, or transparent material to expose the bottom portion of the sample vessels **108** and/or a bottom portion of the enclosed sample holder **1102**. In other implementations, the identifier capture device **1004** can be positioned above the table top **102** (e.g., mounted to the sample arm assembly **104**). Alternatively, the enclosed sample holders **1102** can be detected by sensors coupled to the table top **102**.

[0120] Although particular embodiments of this invention have been illustrated, it is apparent that various modifications and embodiments of the invention may be made by those skilled in the art

without departing from the scope and spirit of the foregoing disclosure. Accordingly, the scope of the invention should be limited only by the claims appended hereto.

[0121] While the subject matter has been described in language specific to structural features and/or process operations, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

## Claims

**1.-20.** (canceled)

**21.** A sample identification system for an automated sampling or dispensing device, comprising: a sample holder having a plurality of apertures configured to receive a plurality of sample vessels therein, the sample holder having one or more corresponding sample holder identifiers positioned proximate to the sample holder; a surface structure supporting at least a portion of the sample holder, the surface structure defining a slot extending a length across the surface structure; a sample arm assembly including a support extending through the slot, the support coupled with a drive assembly configured to provide translation of the support along the length of the slot, the sample arm assembly further including a sample probe coupled to the support with at least a portion of the sample holder positioned between the sample probe and the surface structure; and an identifier capture device configured to detect the one or more sample holder identifiers positioned proximate to the sample holder and generate a data signal in response thereto, the data signal corresponding to at least an orientation of the sample holder relative to the surface structure on which the sample holder is positioned.

**22.** The sample identification system as recited in claim 21, wherein the one or more sample holder identifiers include at least one of a barcode or a QR code.

**23.** The sample identification system as recited in claim 21, wherein the one or more sample holder identifiers include at least two sample holder identifiers, each of which correspond to a different orientation of the sample holder.

**24.** The sample identification system as recited in claim 23, wherein the at least two sample holder identifiers include a first sample holder identifier corresponding to a standard orientation of the sample holder and a second sample holder identifier corresponding to a reverse orientation of the sample holder.

**25.** The sample identification system as recited in claim 24, wherein the sample holder includes a distinct label for each of the plurality of apertures, wherein the first sample holder identifier is positioned on an opposite side of the sample holder as compared to an aperture of the plurality of apertures having a first designation in a series as the distinct label.

**26.** The sample identification system as recited in claim 24, wherein the sample holder includes a distinct label for each of the plurality of apertures, wherein the first sample holder identifier is positioned on a same side of the sample holder as compared to an aperture of the plurality of apertures having a first designation in a series as the distinct label.

**27.** The sample identification system as recited in claim 21, wherein the sample holder includes at least one sample holder identifier positioned on a bottom surface of the sample holder, the bottom surface being opposite of a surface in which the plurality of sample vessels is received into the plurality of apertures.

**28.** The sample identification system as recited in claim 21, wherein the sample holder includes a distinct label for each of the plurality of apertures.

**29.** The sample identification system as recited in claim 21, wherein the data signal further corresponds to information regarding position of a sample vessel relative to an aperture of the plurality of apertures.

**30.** The sample identification system as recited in claim 21, wherein the sample holder comprises



an enclosed sample holder.

**31.** The sample identification system as recited in claim 30, further including a heating element removably coupled to the enclosed sample holder, the heating element configured to disperse heat to the enclosed sample holder.

**32.** The sample identification system as recited in claim 31, wherein the enclosed sample holder includes a removable sampling base configured to removably mate with the surface structure.

**33.** The sample identification system as recited in claim 32, wherein the removable sampling base includes one or more corresponding sample holder identifiers positioned on a portion of the sampling base.

**34.** A sample identification system for an automated sampling or dispensing device, comprising: a sample holder having a plurality of apertures configured to receive a plurality of sample vessels therein, the sample holder having one or more corresponding sample holder identifiers positioned proximate to the sample holder; a surface structure supporting at least a portion of the sample holder, the surface structure defining a slot extending a length across the surface structure; a sample arm assembly including a support extending through the slot, the support coupled with a drive assembly configured to provide translation of the support along the length of the slot, the sample arm assembly further including a sample probe coupled to the support with at least a portion of the sample holder positioned between the sample probe and the surface structure, the sample probe configured to couple with a tube to receive a fluid from a sample vessel of the plurality of sample vessels through the sample probe and into the tube; and an identifier capture device coupled with the support and configured to detect the one or more sample holder identifiers positioned proximate to the sample holder and generate a data signal in response thereto, the data signal corresponding to at least an orientation of the sample holder relative to the surface structure on which the sample holder is positioned.

**35.** The sample identification system as recited in claim 34, wherein the one or more sample holder identifiers include at least one of a barcode or a QR code.

**36.** The sample identification system as recited in claim 34, wherein the one or more sample holder identifiers include at least two sample holder identifiers, each of which correspond to a different orientation of the sample holder.

**37.** The sample identification system as recited in claim 36, wherein the at least two sample holder identifiers include a first sample holder identifier corresponding to a standard orientation of the sample holder and a second sample holder identifier corresponding to a reverse orientation of the sample holder.

**38.** The sample identification system as recited in claim 37, wherein the sample holder includes a distinct label for each of the plurality of apertures, wherein the first sample holder identifier is positioned on an opposite side of the sample holder as compared to an aperture of the plurality of apertures having a first designation in a series as the distinct label.

**39.** The sample identification system as recited in claim 37, wherein the sample holder includes a distinct label for each of the plurality of apertures, wherein the first sample holder identifier is positioned on a same side of the sample holder as compared to an aperture of the plurality of apertures having a first designation in a series as the distinct label.

**40.** The sample identification system as recited in claim 34, wherein the sample holder includes at least one sample holder identifier positioned on a bottom surface of the sample holder, the bottom surface being opposite of a surface in which the plurality of sample vessels is received into the plurality of apertures.

---