US Patent & Trademark Office Patent Public Search | Text View

United States Patent

Kind Code

Date of Patent

Inventor(s)

12389477

B2

August 12, 2025

Rahman; Muhammad Tawhidur

Staggered IMS bearer activation and radio bearer activation in 5G non-standalone networks

Abstract

Devices, systems, and methods relate to performing Internet Protocol (IP) Media Subsystem (IMS) bearer activation and radio bearer activation at different times. In some embodiments, a radio bearer is activated after the IMS bearer is activated. The radio bearer that is activated after the IMS bearer is activated may utilize a different Radio Access Technology (RAT) than an initial radio bearer. In certain instances, a device initiates activation of the radio bearer upon receiving confirmation that the IMS bearer is activated, or initiates activation of the radio bearer a predetermined period of time after initiating activation of the IMS bearer. In various embodiments, staggered IMS bearer activation and radio bearer activation can prevent collisions at components of an Evolved Packet Core (EPC).

Inventors: Rahman; Muhammad Tawhidur (Bellevue, WA)

Applicant: T-Mobile USA, Inc. (Bellevue, WA)

Family ID: 1000008751367

Assignee: T-Mobile USA, Inc. (Bellevue, WA)

Appl. No.: 17/961212

Filed: October 06, 2022

Prior Publication Data

Document IdentifierUS 20230031195 A1

Publication Date
Feb. 02, 2023

Related U.S. Application Data

continuation parent-doc US 16231320 20181221 US 11483886 child-doc US 17961212

Publication Classification

Int. Cl.: H04W76/15 (20180101); H04L65/1016 (20220101); H04L65/1069 (20220101); H04W8/02 (20090101); H04W60/00 (20090101); H04W74/0816 (20240101); H04W76/12 (20180101); H04W88/06 (20090101)

U.S. Cl.:

CPC **H04W76/15** (20180201); **H04L65/1016** (20130101); **H04L65/1069** (20130101); **H04W8/02** (20130101); **H04W60/005** (20130101); **H04W74/0816** (20130101); **H04W88/06** (20130101); H04W76/12 (20180201)

Field of Classification Search

CPC: H04W (76/15); H04W (8/02); H04W (60/005); H04W (74/0816); H04W (88/06); H04W

(76/12); H04W (60/00); H04L (65/1016); H04L (65/1069); H04L (65/1033); H04L

(65/80)

References Cited

| TIC | PATENT DOCUMENT | TC. |
|-----|-----------------|-----|
| | | - |

| Patent No. | Issued Date | Patentee Name | U.S. Cl. | CPC |
|--------------|--------------------|----------------------|----------|-----------------|
| 9462525 | 12/2015 | Malhotra | N/A | H04W 76/15 |
| 9906992 | 12/2017 | Youtz et al. | N/A | N/A |
| 10334485 | 12/2018 | Chandramouli et al. | N/A | N/A |
| 10541768 | 12/2019 | Su et al. | N/A | N/A |
| 2013/0301611 | 12/2012 | Baghel | 370/329 | H04L 63/123 |
| 2014/0079022 | 12/2013 | Wang et al. | N/A | N/A |
| 2015/0264687 | 12/2014 | Singh | 370/280 | H04W 72/0453 |
| 2015/0296559 | 12/2014 | Liu et al. | N/A | N/A |
| 2017/0208488 | 12/2016 | Hwang et al. | N/A | N/A |
| 2017/0215105 | 12/2016 | Tan Bergström | N/A | H04W 24/02 |
| 2017/0325142 | 12/2016 | Lam | N/A | H04L 65/1104 |
| 2017/0374695 | 12/2016 | Lau | N/A | H04L 65/1069 |
| 2018/0109972 | 12/2017 | Kim et al. | N/A | N/A |
| 2018/0227960 | 12/2017 | Belghoul | N/A | H04L 1/1854 |
| 2018/0343697 | 12/2017 | Hsu | N/A | H04W 76/16 |
| 2019/0029058 | 12/2018 | Russell | N/A | H04W 4/90 |
| 2019/0141521 | 12/2018 | Abe et al. | N/A | N/A |
| 2019/0166647 | 12/2018 | Velev | N/A | H04L 5/0098 |
| 2020/0205212 | 12/2019 | Rahman | N/A | N/A |
| | | | | |

FOREIGN PATENT DOCUMENTS

Patent No. Application Country CPC

| 20150138367 | 12/2014 | KR | N/A |
|--------------|---------|----|-----|
| WO2016122589 | 12/2015 | WO | N/A |

OTHER PUBLICATIONS

Cisco, "5G Non Standalone Solution Guide, StarOS Release 21.5", published Apr. 6, 2018, 66 pages. cited by applicant

Huawei et al, "Handover of deactivated PDU session to 4G", S2-1810484, #GPP TSD-SA WG2 Meeting #129, Dongguan, PR Chine, Oct. 9, 2018, pp. 1-6. cited by applicant

Office Action for U.S. Appl. No. 16/231,320, malled on Aug. 11, 2020, Rahman, "Staggered IMS Bearer Activation and Radio Bearer Activation in 5G Non-Standalone Networks", 19 Pages. cited by applicant

Non Final Office Action dated Feb. 5, 2020 for U.S. Appl. No. 16/231,320 "Staggered IMS Bearer Activation and Radio Bearer Activation in 5G Non-Standalone Networks" Rahman, 11 pages. cited by applicant

Office Action for U.S. Appl. No. 16/231,320, mailed on May 26, 2021,Rahman, "Staggered IMS Bearer Activation and Radio Bearer Activation in 5G Non-Standalone Networks", 12 pages. cited by applicant

Office Action for U.S. Appl. No. 16/231,320, mailed on Sep. 14, 2021, Rahman, "Staggered IMS Bearer Activation and Radio Bearer Activation in 5G Non-Standalone Networks", 14 pages. cited by applicant

PCT Search Report and Written Opinion mailed on Apr. 27, 2020 for PCT Application No. PCT/US2019/065215, 9 pages. cited by applicant

Rao, et. al., "Protocol Signaling Procedures in LTE", Continuous Computing, Radisys, Sep. 2011, pp. 1-15. cited by applicant

Primary Examiner: Latorre; Ivan O

Attorney, Agent or Firm: Lee & Hayes, P.C.

Background/Summary

RELATED APPLICATION (1) This application is a continuation of and claims priority to U.S. patent application Ser. No. 16/231,320, filed Dec. 21, 2018, titled "Staggered IMS Bearer Activation and Radio Bearer Activation in 5G Non-Standalone Networks," the entirety of which is incorporated herein by reference.

BACKGROUND

- (1) Modern terrestrial telecommunication systems include heterogeneous mixtures of second, third, and fourth generation (2G, 3G, and 4G) cellular-wireless access technologies, which can be cross-compatible and can operate collectively to provide data communication services. Global Systems for Mobile (GSM) is an example of 2G telecommunications technologies; Universal Mobile Telecommunications System (UMTS) is an example of 3G telecommunications technologies; and Long Term Evolution (LTE), including LTE Advanced, and Evolved High-Speed Packet Access (HSPA+) are examples of 4G telecommunications technologies. Moving forward, future telecommunications systems may include fifth generation (5G) cellular-wireless access technologies to provide improved bandwidth and decreased response times to a multitude of devices that may be connected to a network.
- (2) 5G technologies can be deployed using Standalone (SA) networks and/or Non-Standalone

(NSA) networks. NSA networks, for example, can deliver services using 5G-specific radio resources while utilizing at least some 4G infrastructure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The detailed description is set forth with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical items or features.
- (2) FIG. **1** is a diagram illustrating a Non-Standalone (NSA) network according to an embodiment of the present disclosure.
- (3) FIGS. **2**A and **2**B illustrate example signaling between elements of the system illustrated in FIG. **1**.
- (4) FIG. **3** is a diagram of a device that may correspond to a User Equipment (UE) in some embodiments.
- (5) FIG. **4** is a diagram of a first base station and a second base station according to an embodiment.
- (6) FIG. **5** illustrates an example process for performing staggered Internet Protocol (IP) Media Subsystem (IMS) bearer activation and radio bearer activation, in accordance with various embodiments of the present disclosure.
- (7) FIG. **6** illustrates an example process for performing staggered IMS bearer activation and radio bearer activation by waiting a predetermined period of time, in accordance with embodiments of the present disclosure.
- (8) FIG. **7** illustrates an example process for performing staggered IMS bearer activation and radio bearer activation by initiating radio bearer activation upon receiving an indication that default bearer activation is complete, in accordance with some embodiments of the present disclosure (9) FIG. **8** illustrates an example process for performing staggered IMS bearer activation and radio bearer activation by waiting to transmit an indication of a particular Radio Access Technology (RAT) capability until receiving a confirmation that bearer activation is complete, in accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION

- (10) The systems, devices, and techniques described herein relate to Non-Standalone (NSA) fifth generation (5G) networks that perform default Internet Protocol (IP) Multimedia Subsystem (IMS) Evolved Packet System (EPS) bearer activation and 5G radio bearer activation at different times.
- (11) 5G technologies can provide better throughput, lower latency, and new forms of wireless communication. In order to achieve these advantages, many 5G technologies must be implemented using higher frequency radio resources than previous technologies (e.g., fourth generation (4G) technologies). Accordingly, a significant amount of new hardware may need to be deployed in order to make 5G coverage as available as previous radio technologies.
- (12) Such deployment of hardware requires significant cost, and other resources, such as space. In order to spread out the cost of deploying 5G technology over time, and to reduce the overall costs associated with setting 5G networks, intermediary deployments of 5G have been proposed. These intermediate deployments include NSA deployments, in which 5G networks utilize existing 4G architecture. One such NSA deployment is referred to by 3GPP as "Option 3X."
- (13) One example of an Option 3X network includes a master base station and a slave base station that are independently connected to an Evolved Packet Core (EPC). The master base station can relay data between a device and the EPC using a 4G Radio Access Technology (RAT) but may be incapable of directly transmitting or directly receiving data wirelessly using a 5G New Radio (NR)

RAT. For example, the master base station may not have been designed to use the 5G NR RAT and may lack transceivers capable of transmitting or receiving wireless data in a 5G-specific frequency range (e.g., 24 GHz-52 GHz). However, the master base station can control the slave base station to relay data between the device and the EPC using the 5G NR RAT. In particular, the master base station can cause the EPC to transfer a radio bearer from the master base station to the slave base station, or to add a radio bearer including the slave base station, so that the slave base station can relay data between the device and a network (e.g., a Wide Area Network (WAN) and/or an Internet Protocol (IP) Media Subsystem (IMS) network) using a pre-established tunnel through the EPC. As a result, 5G-capable devices in the example Option 3X network can receive services using the 5G NR RAT.

- (14) One problem with Option 3X networks, as well as other NSA networks, is that in the processes of activating the IMS bearer and the radio bearer including the slave base station, a component of the EPC (e.g., a Mobile Management Entity (MME), a Serving Gateway (SGW), and/or a Packet Data Network (PDN) Gateway (PGW)) can receive different messages concerning the same end user device at substantially the same time. This can cause whet is referred to as a "collision." For example, the component can receive a first packet, corresponding to IMS bearer activation for a device, at substantially the same time as a second packet, corresponding to a process of transferring the bearer context for the device to a different radio technology, and the component may not be able to distinguish between the two packets. When packets collide at a component of the EPC, the component may ignore one of the packets.
- (15) If the component of the EPC disregards the second packet corresponding to the radio bearer activation process, for example, 5G-capable device may be prevented or delayed from receiving 5G radio services. Users, who may have paid a premium to obtain 5G-capable devices, may be particularly dissatisfied with only being able to access 4G services when 5G services should be available. The problem of devices not being able to access available services (e.g., available 5G services) that they are capable of receiving (e.g., via a 5G NR RAT) is known to those skilled in the art as "leakage," and should be avoided where possible.
- (16) Embodiments of the present disclosure address these problems by performing IMS bearer activation and 5G NR RAT radio bearer activation at different times. In some embodiments, the master base station waits to initiate 5GNR RAT radio bearer activation until it determines that IMS bearer activation is complete. In some examples, the device itself refrains from informing the master base station that the device is 5G-capable until after IMS bearer activation is complete, in order to ensure that the master base station waits to initiate the 5G NR RAT radio bearer activation until IMS bearer activation is complete. By staggering, in time, the IMS bearer activation and the radio bearer activation processes, signaling collisions in the EPC can be prevented.
- (17) Various embodiments improve the technical field of wireless communication by preventing signaling collisions at components of an EPC in NSA 5G networks. Embodiments also improve the technical field of wireless communication by ensuring that 5G-capable devices receive 5G services in NSA 5G networks. These and other improvements to the functioning of a computer and network are discussed herein.
- (18) The systems, devices, and techniques described herein can be implemented in a number of ways. In general, the techniques discussed herein may be implemented in any dual connectivity or multi connectivity environment and are not limited to second generation (2G), third generation (3G), 4G, and/or 5G environments. Example implementations are provided below with reference to the following figures.
- (19) FIG. **1** is a diagram illustrating a Non-Standalone (NSA) network **100** according to an embodiment of the present disclosure. The network **100** includes a User Equipment (UE) **102**, which can be connected to an eNodeB **104** and/or an gNodeB **106**. The eNodeB **104** and the gNodeB **106** can independently provide services between the UE **102** and a Wide Area Network (WAN) **120** or an Internet Protocol (IP) Media Subsystem (IMS) network **122** via an Evolved

Packet Core (EPC) 110.

- (20) The terms "user equipment (UE)," "user device," "wireless communication device," "wireless device," "communication device," "mobile device," and "client device," can be used interchangeably to describe any UE that is capable of transmitting/receiving data wirelessly using any suitable wireless communications/data technology, protocol, or standard, such as Global System for Mobile Communications (GSM), Time Division Multiple Access (TDMA), Universal Mobile Telecommunications System (UMTS), Evolution-Data Optimized (EVDO), Long Term Evolution (LTE), Advanced LTE (LTE+), New Radio (NR), Generic Access Network (GAN), Unlicensed Mobile Access (UMA), Code Division Multiple Access (CDMA), Orthogonal Frequency Division Multiple Access (OFDM), General Packet Radio Service (GPRS), Enhanced Data GSM Environment (EDGE), Advanced Mobile Phone System (AMPS), High Speed Packet Access (HSPA), evolved HSPA (HSPA+), Voice over IP (VoIP), VoLTE, Institute of Electrical and Electronics Engineers' (IEEE) 702.1x protocols, WiMAX, Wi-Fi, Data Over Cable Service Interface Specification (DOCSIS), Digital Subscriber Line (DSL), CBRS, and/or any future IPbased network technology or evolution of an existing IP-based network technology. Examples of UEs can include, but are not limited to, smart phones, mobile phones, cell phones, tablet computers, portable computers, laptop computers, Personal Digital Assistants (PDAs), electronic book devices, or any other portable electronic devices that can generate, request, receive, transmit, or exchange voice, video, and/or digital data over a network. Additional examples of UEs include, but are not limited to, smart devices such as televisions, refrigerators, washing machines, dryers, smart mirrors, coffee machines, lights, lamps, temperature sensors, leak sensors, water sensors, electricity meters, parking sensors, music players, headphones, or any other electronic appliances that can generate, request, receive, transmit, or exchange voice, video, and/or digital data over a network.
- (21) The term "eNodeB," and its equivalents, may refer to a base station configured to transmit and receive wireless data over 4G-specific frequency bands. An eNodeB may be configured to transmit and receive data using a 4G Radio Access Technology (RAT). That is, an eNodeB may be configured to transmit and receive data wirelessly over one or more channels in a 4G-specific range of electromagnetic frequencies.
- (22) The term "4G-specific," and its equivalents, may refer to a technology that is utilized in the fourth generation of broadband cellular network technology, such as in the Long Term Evolution (LTE) standard. For example, a "4G-specific frequency band" may be an LTE band. In some instances, a 4G-specific technology can be utilized in another generation of broadband cellular network technology, such as 5G technology.
- (23) The term "gNodeB," and its equivalents, may refer to a base station configured to transmit and receive wireless data over 5G New Radio (NR)-specific frequency bands. In some instances, one or more slave gNodeBs can be controlled by a master eNodeB. A gNodeB may be configured to utilize a 5G NR RAT. That is, an eNodeB may be configured to transmit and receive data wirelessly over one or more channels in a 4G-specific range of electromagnetic frequencies.
- (24) The term "5G-specific," and its equivalents, may refer to a technology that is utilized in the fifth generation of broadband cellular network technology, such as in the NR standard, but is not utilized in the fourth generation of broadband cellular network technology, such as in the LTE standard. For example, a "5G-specific frequency band" may be GHz frequency band that is not utilized in the LTE standard.
- (25) The terms "base station," "Access Point (AP)," or their equivalents, can refer to one or more devices that can provide wireless services to one or more UEs in a coverage area. For example, a base station can be implemented as a variety of technologies to provide wired and/or wireless access to the network, as discussed herein. In some instances, a base station can include a 3GPP RAN, such a GSM/EDGE RAN (GERAN), a Universal Terrestrial RAN (UTRAN), an evolved UTRAN (E-UTRAN), an eNodeB, a gNodeB, or alternatively, a "non-3GPP" RAN, such as a Wi-

- Fi RAN, or another type of wireless local area network (WLAN) that is based on the IEEE 702.11 standards. Further, a base station can include any number and type of transceivers and/or base stations representing any number and type of macrocells, microcells, picocells, or femtocells, for example, with any type or amount of overlapping coverage or mutually exclusive coverage. (26) The term "Wide Area Network (WAN)," and its equivalents, can refer to a telecommunications and/or computer network that extends over a relatively large geographical distance. The Internet is an example of a WAN.
- (27) The term "Internet Protocol (IP) Media Subsystem (IMS)," and its equivalents, can refer to an architectural framework over which voice or other multimedia services can be provided to UEs, such as mobile phones. An IMS network can include multiple functions, such as Call Session Control Functions (CSCFs), that are used to process signaling packets in the IMS network. For example, an IMS network can include a Proxy CSCF (P-CSCF), which can be a destination for data packets (e.g., Session Initiation Protocol (SIP) packets) sent by a UE seeking services from the IMS network. In examples, the CSCFs may further include an Interrogating-CSCF (I-CSCF), a Serving-CSCF (S-CSCF). In various embodiments, the IMS network may further include any of a Home Subscriber Server (HSS), a Subscription Locator Function (SLF), a Media Resource Function (MRF), a Break Out Gateway Control Function (BGCF), In some implementations, an IMS network supports services Public Switched Telephony Network (PSTN) Gateway(s), Application Server(s), IP Multimedia Serving Switch Function (IM-SSF), and Service Layer Interfaces. The IMS network may provide particular services, such as Voice over Internet Protocol (VoIP) services. When services to and from an IMS are also traverse an EPC, VoIP services can include Voice over LTE (VoLTE) services. In various implementations, an IMS network is managed by a carrier organization.
- (28) The terms "Evolved Packet Core (EPC)," and its equivalents, can refer to a core network of the LTE standard. An EPC may have an all-IP architecture, with separation of control plane and user plane traffic. The EPC can include a Mobility Management Entity (MME), a Serving Gateway (SGW), a Packet Data Network (PDN) Gateway (PGW), a Home Subscriber Server (HSS), an Access Network Discovery and Selection Function (ANDSF), and an Evolved Packet Data Gateway (ePDG). An EPC may relay data exchanged between an access point (e.g., a base station, an eNodeB, a gNodeB, etc.) and a WAN.
- (29) The EPC **110** of FIG. **1** includes an MME **112**, an SGW **114**, and a PGW **116**. The SGW **114** and the PGW **116** can be collectively referred to as a System Architecture Evolution (SAE) Gateway. (SAEGW) **118**. Although not illustrated, the EPC **110** can further include other elements, such as a Home Subscriber Server (HSS).
- (30) The MME **112** functions as a control node for the EPC **110**. For example, the MME **112** may facilitate idle mode, bearer activation and deactivation, SGW selection, user authentication, and the like. In practice, an EPC may have multiple MMEs. The MME **112** may be responsible for signaling various elements of the EPC for mobility, security, and/or E-UTRAN access. In various embodiments, the MME **112** is responsible for selecting the SGW **114** among multiple candidate SGWs.
- (31) The SGW **520** functions as a communication gateway of the EPC **110**. The SGW **520** is a data plane interface with LTE and NR base stations, such as eNodeB **104** and gNodeB **106**, respectively. An EPC may have multiple SGWs. The SGW **114** may be responsible for transporting Internet Protocol (IP) data traffic between the UE **102** and an external network, e.g., WAN **120** and/or IMS network **122**. In particular, the SGW **114** can carry data traffic between the PGW **116** and a base station, such as the eNodeB **104**, the gNodeB **106**, or both.
- (32) The PGW **116** may also transport the IP data traffic between the UE **102** and the WAN **120**. The PGW **116** may carry data traffic between the SGW **114** and the WAN **120**.
- (33) In various embodiments of the present disclosure, the UE **102** can access services from the WAN **120** by undergoing an initial attachment procedure. Initially, the UE **102** can transmit an

attach request to the eNodeB **104**. In turn, the eNodeB **104** can initiate the activation of a PDN bearer traversing the EPC **110** between the UE **102** and the WAN **120**. For example, the PDN bearer may include an EPS bearer. The UE **102** and the eNodeB **104** may wirelessly communicate with each other using a first RAT, such as a 4G LTE RAT. The eNodeB **104** may therefore be part of a first radio bearer that is utilized by the EPS bearer to carry data to and from the UE **102**. (34) The term "bearer," "tunnel," and their equivalents can refer to a path over which data is transmitted. A bearer can include one or more nodes.

- (35) A "PDN bearer," an "Internet bearer," an "EPS Internet bearer," and their equivalents, can refer to a data pathway that connects a UE and a PDN. A UE can connect to a PDN or WAN, such as the Internet, via the PDN bearer. In some instances, a PDN bearer can include an EPS bearer. (36) An "EPS bearer" can refer to a specific path through an EPC over which data can be transferred to and from a device. For example, an EPS bearer may include the SGW **114** and a PGW **116**, which routes IP-related data traffic between the WAN **120** or the IMS network **122** and the UE **102**. In some examples, the EPS bearer may further include, or at least utilize, one or more radio bearers including Radio Access Networks (RANs) that connect the UE **102** to the EPC **110**, e.g., a base station such as eNodeB **104**, gNodeB **106**, or both.
- (37) A "radio bearer" can refer to a path including a wireless link over which data can be transferred to and from a device. A radio bearer may include a base station, such as any of an eNodeB, a gNodeB, and the like.
- (38) With reference to FIG. **1**, the eNodeB **104** can initiate the creation of the PDN bearer and the EPS bearer for the UE **102** by forwarding the attach request to the MME **112**. The MME **112**, in turn, can initiate a process of selecting the SGW **114** and the PGW **116** for the EPS bearer. (39) Initially, the EPS bearer can include the SGW **114** and the PGW **116** selected by the MME **112**. The EPS bearer can utilize, or can be associated with, a radio bearer including the eNodeB **104**. In some cases, the eNodeB **104** can utilize the EPS bearer to transmit data between the UE **102** and the WAN **120** via the PDN bearer, which includes the EPS bearer. Downlink services can be transmitted over the PDN bearer from the WAN **120**, to the PGW **116**, to the SGW **114**, to the eNodeB **104**, and then to the UE **102**. Uplink services can be transmitted over the PDN bearer from the UE **102**, to the eNodeB **104**, to the SGW **114**, to the PGW **116**, and then to the WAN **120**. The PDN bearer can enable the UE **102** to access the Internet, for example.
- (40) Next, or simultaneously during the creation of the PDN bearer, an IMS bearer can be generated. As used herein, the term "IMS bearer," and its equivalents, can refer to a pathway over which data can traverse between an IMS network and a UE. In some instances, an IMS bearer includes an EPS bearer.
- (41) Once the UE **102** is connected to the WAN **120** and the EPS bearer has been established, the UE **102** can transmit a request to connect to the IMS network **122** to the MME **112** via the eNodeB **104**. In some instances, the request specifies an Access Point Name (APN) associated with the IMS network **122**. In response, the MME **112** can set up an IMS bearer between the UE **102** and the IMS network **122** using the existing EPS bearer. For example, the MME **112** can initiate the creation of the IMS bearer by communicating with the SGW **114**, the PGW **116**, or both. In response, the SGW **114**, the PGW **116**, or both, can transmit a response to the MME **112** that informs the MME **112** of the IMS bearer. The MME **112** can then inform the UE **102** of the activated IMS bearer.
- (42) Once the IMS bearer has been activated for the UE **102**, the UE **102** may be able to exchange services with the IMS network **122**. In some instances, the activated IMS bearer allows the UE to receive voice services, such as Voice over LTE (VoLTE) services. The IMS bearer may include components of the original EPS bearer, which is included in the PDN bearer, but may connect to the IMS network **122** rather than (or in addition to) the WAN **120**.
- (43) In some embodiments, the eNodeB **104** can learn that the UE **102** is 5G-capable from the

attach request, or from some other message transmitted from the UE **102**. The eNodeB **104** may be incapable of transmitting or receiving data using a 5G New Radio (NR) RAT. However, the gNodeB **106**, which is controlled by the eNodeB **104**, may be capable of transmitting and receiving data using the 5G NR RAT. In order to ensure that the UE **102** is provided 5G services, the eNodeB **104** may initiate activation of a second radio bearer including the gNodeB **106** and may initiate introducing the second radio bearer to the EPS bearer for the UE **102**. The second radio bearer may be a 5G NR RAT radio bearer. In some cases, the EPS bearer may retain the first radio bearer that includes the eNodeB **104**. That is, the EPS bearer may utilize both the first radio bearer (including the eNodeB **104**) and the second radio bearer (including the gNodeB **106**). In certain implementations, the first radio bearer may be excluded from the EPS bearer after the second radio bearer is activated, such that the EPS bearer is transferred from the first radio bearer to the second radio bearer.

- (44) The processes activating the IMS bearer and activating the second radio bearer may include transmitting and receiving various messages indicating the UE **102** between the MME **112**, the SGW **114**, and/or the PGW **116**. If more than one of these messages is received by the same component of the EPC **110** (e.g., the MME **112**, the SGW **114**, or the PGW **116**), a collision may occur.
- (45) In various embodiments, the eNodeB **104** waits to initiate activation of the second radio bearer including the gNodeB **106** until after the IMS bearer is created. The creation of the IMS bearer and the activation of the second radio bearer can be performed at different times, thereby preventing collisions in the EPC **110**.
- (46) In some embodiments, the eNodeB may know that the UE **102** is 5G-capable before the IMS bearer is created. For example, the attach request transmitted from the UE **102** and received by the eNodeB **104** may inform the eNodeB **104** that the UE **102** is 5G-capable. In some instances, the eNodeB **104** may wait a predetermined period of time after initiating the creation of the PDN bearer or the IMS bearer before initiating the creation of the second radio bearer. The eNodeB **104** may, in certain instances, run a timer after forwarding the attach request to the MME **112**. In some instances, the eNodeB **104** may initiate the activation of the second radio bearer in response to receiving an indication that the IMS bearer has been activated or created. This indication can comprise a message transmitted to the eNodeB **104** from the MME **112**, the SGW **114**, or the UE **102**.
- (47) In some embodiments, the UE **102** may inform the eNodeB **104** that the UE **102** is 5G-capable after the IMS bearer is created. The UE **102** may download instructions to wait to inform the eNodeB **104** that the UE **102** is 5G-capable from an update, which can be provided by a carrier network, for example. In some instances, the UE **102** may wait a predetermined period of time after transmitting the attach request to the eNodeB **104** before transmitting an indication that the UE **102** is 5G-capable to the eNodeB **104**. In some instances, the UE **102** may transmit an indication that the UE **102** is 5G-capable to the eNodeB **104** in response to receiving an indication that the IMS bearer has been activated. Accordingly, in some embodiments, the UE **102** can control the timing of the IMS bearer activation and the second radio bearer activation.
- (48) Once the second radio bearer including the gNodeB **106** has been activated for the UE **102**, the EPS bearer can utilize the gNodeB **106** to transmit data to and from the UE **102**. The EPS bearer may retain the SGW **114** and the PGW **116** selected during the initial EPS bearer creation process during the PDN bearer activation. As a result of the second radio bearer activation, downlink services can be provided along the PDN bearer from the WAN **120**, to the PGW **116**, to the SGW **114**, to the gNodeB **106**, and to the UE **102**, and uplink services can be provided along the PDN bearer from the UE **102**, to the gNodeB **106**, to the SGW **114**, to the PGW **116**, and to the WAN **120**. Similarly, as a result of the second radio bearer activation, downlink services can be provided along the IMS bearer from the IMS network **122**, to the PGW **116**, to the SGW **114**, to the gNodeB **106**, and to the UE **102**, and uplink services can be provided along the IMS bearer from the UE

102, to the gNodeB **106**, to the SGW **114**, to the PGW **116**, and to the IMS network **122**. Accordingly, in various embodiments, activating the second radio bearer can enable the UE **102** to receive services from the WAN **120** (e.g., Internet browsing services) and/or from the IMS network **122** (e.g., VoLTE services) via the 5G NR RAT utilized by the gNodeB **106**.

- (49) In some instances, the environment **100** can further include one or more communication servers to facilitate communications by and between the various devices in the environment 100. The WAN **120**, for example, can include the one or more servers. That is, environment **100** can include any computing devices implementing various aspects of one or more of second, third, fourth generation, and fifth generation (2G, 3G, 4G, and 5G) cellular-wireless access technologies, which may be cross-compatible and may operate collectively to provide data communication services. Global Systems for Mobile (GSM) is an example of 2G telecommunications technologies; Universal Mobile Telecommunications System (UMTS) is an example of 3G telecommunications technologies; and Long Term Evolution (LTE), including LTE Advanced, and Evolved High-Speed Packet Access (HSPA+) are examples of 4G telecommunications technologies. Thus, the environment 100 may implement GSM, UMTS, and/or LTE/LTE Advanced telecommunications technologies. The environment **100** may include, but is not limited to, a combination of: base transceiver stations BTSs (e.g., NodeBs, Enhanced-NodeBs), Radio Network Controllers (RNCs), serving GPRS support nodes (SGSNs), gateway GPRS support nodes (GGSNs), proxies, a mobile switching center (MSC), MME(s), SGW(s), PGW(s), an evolved packet data gateway (e-PDG), an Internet Protocol (IP) Multimedia Subsystem (IMS), or any other data traffic control entity configured to communicate and/or route data packets between the UE 102, and one or more endpoints of the network (e.g., servers, websites, etc.), such as endpoints in WAN 120 or the IMS network **122**.
- (50) While FIG. **1** illustrates the example environment **100**, it is understood in the context of this document, that the techniques discussed herein may also be implemented in other networking technologies, such as nodes that are part of a wide area network (WAN), metropolitan area network (MAN), local area network (LAN), neighborhood area network (NAN), personal area network (PAN), or the like.
- (51) FIGS. **2**A and **2**B illustrate example signaling **200**A and **200**B between elements of the system **100** illustrated in FIG. **1**. In particular, FIG. **2** illustrates signaling between the User Equipment (UE) **102**, the eNodeB **104**, the gNodeB **106**, the Mobility Management Entity (MME) **112**, and the System Architecture Evolution (SAE) Gateway (SAEGW) **118**, according to some embodiments. (52) FIG. **2**A illustrates signaling **200**A for establishing a Packet Data Network (PDN) bearer and an (IP) Media Subsystem (IMS) bearer, according to embodiments.
- (53) Initially, the PDN bearer is activated. In various embodiments, the UE 102 may transmit an attach request 202 to the eNodeB 104. The UE 102 may transmit the attach request 202 to the eNodeB 104 upon entering or being activated in a coverage area associated with eNodeB 104. In some embodiments, the UE 102 transmits the attach request 202 in response to receiving a broadcast message from the eNodeB 104, e.g., a System Information Broadcast. In certain instances, the attach request 202 indicates to the eNodeB 104 that the UE 102 is capable of using a particular Radio Access Technology (RAT), e.g., a 5G New Radio (NR) RAT. In other instances, the attach request 202 omits an indication that the UE 102 is capable of using the particular RAT. The eNodeB 104 may be part of a first radio bearer for data transmitted to and from the UE 102. (54) In response to receiving the attach request 202 from the UE 102, the eNodeB 104 may initiate the creation of an initial Evolved Packet System (EPS) bearer for the UE 102 by transmitting an initial bearer request 204 to the MME 112. The initial EPS bearer may include, or at least utilize, a radio bearer that includes the eNodeB 104. In some instances, the initial bearer request 204 includes the attach request 202. For example, the initial bearer request 204 may include an S1-MME control message.
- (55) The MME 112, in turn, may transmit an establish bearer request 206 to the SAEGW 118. The

- establish bearer request **206** may include multiple messages transmitted from the MME **112** to the SAEGW **118**. For example, the establish bearer request **206** can include a create session request. In some embodiments, the establish bearer request **206** informs the SAEGW **118** about the UE **102** and the eNodeB **104**. For example, the establish bearer request **206** may include an identity of the UE **102** and an identity of the eNodeB **104**. In some instances, a PGW within the SAEGW **118** creates a new entry in an EPS bearer context table corresponding to a SGW within the SAEGW **118**.
- (56) In response, the SAEGW **118** may transmit an establish bearer response **208** to the MME **112**. The establish bearer response **208** may confirm, to the MME **112**, that a tunnel including the SAEGW **118** has been established through the Evolved Packet Core (EPC). That is, the establish bearer response **208** may indicate that an EPS bearer has been established. The establish bearer response **208** may further indicate that a PDN bearer has been established between a Wide Area Network (WAN) and the UE **102**. That is, the establish bearer response **208** may confirm that the SAEGW **118** will automatically forward data destined for the UE **102** to the eNodeB **104**, and that the SAEGW **118** will forward data from the UE **102** via the eNodeB **104** to the WAN.
- (57) The MME **112** may transmit bearer information **210** to the eNodeB **104**. The bearer information may notify the eNodeB **104** of the identity of the SAEGW **118**. In some embodiments, the bearer information **210** includes a create session response. The bearer information **210** may indicate to the eNodeB **104** that an initial PDN bearer has been created, for example.
- (58) The eNodeB **104** may transmit an initial bearer confirmation **212** to the UE **102**. The initial bearer confirmation **212** may inform the UE **102** that the PDN bearer, which includes the EPS bearer that contains the SAEGW **118**, has been established for the UE **102**. In some embodiments, the initial bearer confirmation **212** includes a Radio Resource Control (RRC) connection reconfiguration message, an RRC direct transfer message, or both.
- (59) The UE **102** may transmit an attachment complete message **214** to the eNodeB **104**. In some embodiments, the attachment complete message **214** includes an RRC connection reconfiguration complete message, a direct transfer message, or both. The eNodeB **104** may forward the attach complete message **214** to the MME **112**.
- (60) The UE **102** may transmit and/or receive first data **216** to and from the WAN via the established PDN bearer, which includes the EPS bearer utilizing the gNodeB **104** and including the SAEGW **118**. The first data **216** may include uplink data, downlink data, or both. In some embodiments, the first data **216** may include a message transmitted from the UE **102** to the eNodeB **104** that indicates the UE **102** is capable of receiving and/or transmitting data over the particular RAT, e.g., the 5G NR RAT.
- (61) Once the UE **102** can receive and transmit the first data **216**, the UE **102** has an initial connection with the WAN. In some instances, this is known as an initial PDN connection. In some examples, this initial connection connects the UE **102** to the Internet.
- (62) Next, an IMS bearer for the UE **102** can be established. That is, a connection between the UE **102** and an IMS network may be established. The UE **102** may transmit an IMS connection request **218** to the eNodeB **104**. The eNodeB may forward the IMS connection request **218** to the MME **112**. In some instances, the IMS connection request **218** includes information identifying the IMS network, which can be prestored at the UE **102**. For example, the IMS connection request **218** may include an Access Point Name (APN) associated with the IMS network.
- (63) In response to receiving the IMS connection request **218**, the MME **112** may transmit a create session request **220** to the SAEGW **118**. The create session request **220** may instruct the SAEGW **118** to establish a connection with the IMS network.
- (64) The SAEGW **118** may transmit a create session response **222** to the MME **112**. In some instances, the create session response **222** includes information that can enable the UE **102** to connect to the IMS network. For example, the create session response **222** may include a Proxy-Call Session Control Function (P-CSCF) IP address associated with the IMS network.

- (65) The MME **112** may transmit an activate IMS bearer message **224** to the UE **102** via the eNodeB **104**. The activate IMS bearer message **224** may include information that can enable the UE **102** to connect to the IMS network. In some instances, the IMS bearer message **224** may include information enabling the UE **102** to access voice services via the IMS network. The activate IMS bearer message **224** can include the P-CSCF IP address associated with the IMS network.
- (66) The established IMS bearer for the UE **102** may include the same components of the EPC used in the EPS bearer of the PDN bearer. That is, the IMS bearer may initially utilize the same eNodeB **104** and include the same SAEGW **118** as the PDN bearer.
- (67) The eNodeB **104** and/or the UE **102** may identify that the initial IMS bearer has been established when the activate IMS bearer message **224** is received from the MME **112**. Upon identifying that the IMS bearer has been established, the UE **102** and or the eNodeB **104** can initiate activation of a second radio bearer including the gNodeB **106**. In some cases, the EPS bearer may utilize the gNodeB **106**, rather than the eNodeB **104**, to transfer data over wireless resources between the EPC and the UE **102**.
- (68) FIG. **2B** illustrates signaling **200**B for activating a second radio bearer according to various embodiments. Signaling **200**B may occur after signaling **200**A. Alternatively, signaling **200**B can occur between the creation of the initial PDN bearer and the creation of the IMS bearer, e.g., before the IMS connection request **218** is transmitted by the UE **102**.
- (69) In some instances, the UE **102** may transmit capability information **226** to the eNodeB **104**. The capability information **226** may inform the eNodeB that the UE **102** is capable of exchanging data over a 5G New Radio (NR) Radio Access Technology (RAT). In some embodiments, the capability information **226** is omitted, and the eNodeB **104** may learn about the capabilities of the UE **102** through other means. For example, the initial attach request **202** may inform the eNodeB **104** that the UE **102** is 5G-capable.
- (70) The eNodeB **104** may transmit a second radio bearer activation request **228** to the MME **112**. The second radio bearer activation request **228** may be a request to activate a second radio bearer including the gNodeB **106**. That is, the second radio bearer activation request **228** may be a request to activate the second radio bearer, which can be utilized by the EPS bearer, such that wireless data is transmitted to and from the UE **102** by the gNodeB **106**, rather than (or in addition to) the eNodeB **104**.
- (71) In some embodiments, the eNodeB **104** transmits the second radio bearer activation request **228** to the MME **112** in response to receiving the indication that the IMS bearer activation has been at least partially completed. In some instances, the eNodeB **104** transmits the second radio bearer activation request **218** in response to receiving the capability information **226** from the UE **102**. The second radio bearer activation request **228** may include an identification of the gNodeB **106**. The second radio bearer activation request **228** may include an Evolved Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access Node (E-UTRAN) Radio Access Bearer (E-RAB) modification indication, for example.
- (72) The MME **112** may transmit a modify bearer request **230** to the SAEGW **118**. The modify bearer request **230** may identify the existing EPS bearer to the SAEGW **118** (e.g., by identifying an identity of the UE **102** and/or the eNodeB **104**) and may also identify the gNodeB **106**. As a result of receiving the modify bearer request **230**, the SAEGW **118** may alter and/or replace a record of the existing EPS bearer, in order to identify that data destined for the UE **102** should be transmitted to the gNodeB **106**, rather than the eNodeB **104**.
- (73) The SAEGW **118** may transmit a modify bearer response **232** to the MME **112**. The modify bearer response **232** may confirm that the SAEGW's **118** record of the EPS bearer between the UE **102** and the SAEGW **118** utilizes the gNodeB **106** in addition to the eNodeB **104** and/or rather than the eNodeB **104**.
- (74) The MME **112** may confirm to the eNodeB **104** that the second bearer activation is complete

- by transmitting a second radio bearer activation confirmation message **234** to the eNodeB **104**. (75) Second data **236** may be transmitted through the modified EPS bearer. The second data **236** may be transmitted between the SAWGW **118** and the gNodeB **106**, and between the gNodeB **106** and the UE **102**. The second data **236** may be transmitted to and from the WAN along the PDN bearer, to and from the IMS network along the IMS bearer, or both. In some embodiments, the second data **236** includes an initial message indicating that the second radio bearer has been activated, wherein the message is transmitted from the SAEGW **118** to UE **102** via the eNodeB **104**. Accordingly, the UE **102** may know to transmit wireless uplink data to the gNodeB **106**, at least in certain cases.
- (76) As a result of the signaling **200**A and **200**B illustrated in FIGS. **2**A and **2**B, the UE **102** may access services via the particular RAT (e.g., the 5G NR RAT) utilized by the gNodeB **106**. In addition, collisions at the MME **112**, the SGW **114**, and the PGW **116** can be avoided by staggering the activation of the IMS bearer and activation of the second radio bearer. For example, the activation of the IMS bearer and the activation of the second radio bearer can be decoupled in the time domain.
- (77) FIG. **3** is a diagram of a device **300** that may correspond to a User Equipment (UE), e.g., UE **102**, in some embodiments. Device **300** includes a memory **304**, processor(s) **306**, removable storage **308**, non-removable storage **310**, input device(s) **312**, output device(s) **314**, and transceiver(s) **316**.
- (78) The memory **304** may include an attachment request component **318**, an Internet Protocol (IP) Media Subsystem (IMS) connection request component **320**, and a capability component **322**. The attachment request component **318** may include instructions that, when executed by processor(s) **306**, cause the processor(s) **306** to generate an attachment request and cause the transceiver(s) **316** to transmit the attachment request component **318** may instruct the transceiver(s) **316** to transmit the attachment request to a first base station, e.g., an eNodeB. (79) The IMS connection request component **320** may include instructions that, when executed by the processor(s) **306**, cause the processor(s) **306** to generate an IMS connection request, and cause the transceiver(s) **316** to transmit the IMS connection request. The IMS connection request may identify a particular IMS network.
- (80) The capability component **322** may include instructions that, when executed by processor(s) **306**, cause the processor(s) **306** to generate a capability indication and cause the transceiver(s) **316** to transmit the capability indication. The capability indication may be an indication that the transceiver(s) **316** are capable of transmitting and receiving data wirelessly using a particular Radio Access Technology (RAT), such as a 5G New Radio (NR) RAT. For example, the capability indication may be an indication that the device **300** is 5G-capable.
- (81) FIG. **4** is a diagram of a first base station **400** and a second base station **420** according to an embodiment. The first base station **400** may be an eNodeB, e.g., eNodeB **104**. The second base station **420** may be a gNodeB, e.g., gNodeB **106**. Each one of the first base station **400** and the second base station **420** can include multiple devices.
- (82) The first base station **400** may include a memory **402**, processor(s) **404**, removable storage **406**, non-removable storage **408**, input device(s) **410**, output device(s) **412**, and transceiver(s) **414**. (83) The memory **402** may include an IMS bearer activator component **416** and a radio bearer activation component **418**. The IMS bearer activator component **416** may include instructions that, when executed by processor(s) **404**, cause the processor(s) **404** to generate and/or forward a bearer request and cause the transceiver(s) **414** to transmit the bearer request to a component in an Evolved Packet Core (EPC), e.g., a Mobility Management Entity (MME). The bearer request may be received, by the transceiver(s) **414**, from a UE, and may include an attachment request or an Internet Protocol (IP) Media Subsystem (IMS) connection request. The radio bearer activation component **418** may include instructions that, when executed by processor(s) **404**, cause the processor(s) **404** generate a second radio bearer activation request and cause the transceiver(s) to

- transmit the second radio bearer activation request to a component in the EPC, e.g., the MME. (84) In various embodiments, the transceiver(s) **414** may be capable of transmitting and receiving data wirelessly over frequency bands associated with a first RAT, e.g., a 4G RAT. However, the transceiver(s) **414** may be incapable of transmitting and receiving data over frequency bands associated with a second RAT, e.g., a 5G New Radio (NR) RAT.
- (85) The second base station **420** may include a memory **422**, processor(s) **424**, removable storage **426**, non-removable storage **428**, input device(s) **430**, output device(s) **432**, and transceiver(s) **434**.
- (86) The memory **422** may include a particular RAT component **336** including instructions that, when executed by processor(s) **424**, cause the processor(s) **424** to convert data to and from a format suitable for transmission over the second RAT, and cause the transceiver(s) **434** to transmit data over the second RAT. In various embodiments, the transceiver(s) **434** may be capable of transmitting and receiving data wirelessly over frequency bands associated with the second RAT, which may be the 5G NR RAT.
- (87) The first base station **410** may be configured to control the second base station **420**, such that the first base station **410** and the second base station **420** have a master-slave relationship. In some embodiments, a communication link may connect the transceiver(s) **414** of the first base station **400** to the transceiver(s) of the second base station **434**.
- (88) In some embodiments, each one of memory **304**, memory **402**, and memory **422**, is volatile (such as RAM), non-volatile (such as ROM, flash memory, etc.) or some combination of the two. Further, each of the device **300**, the first base station **400**, and the second base station **420** may also include additional data storage devices (removable and/or non-removable) such as, for example, magnetic disks, optical disks, or tape. Such additional storage is illustrated by, for example, removable storage **308**, removable storage **406**, removable storage **426**, non-removable storage **310**, non-removable storage **408**, and non-removable storage **428**. Tangible computer-readable media can include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, or other data. The memory 304, memory 402, memory 422, removable storage **308**, removable storage **406**, removable storage **426**, non-removable storage 310, non-removable storage 408, and non-removable storage 428 can all be examples of computerreadable storage media. Computer-readable storage media include, but are not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile discs (DVD), content-addressable memory (CAM), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information. Any such tangible computer-readable media can be part of any of the device **300**, the first base station **400**, and/or the second base station **420**.
- (89) In some embodiments, each one of processor(s) **306**, processor(s) **404**, and processor(s) **424** includes a central processing unit (CPU), a graphics processing unit (GPU), or both CPU and GPU, or other processing unit or component known in the art.
- (90) In some embodiments, each one of input device(s) **312**, input device(s) **410**, and input device(s) **430** can include any of a keypad, a cursor control, a touch-sensitive display, voice input device, etc., and each one of output device(s) **314**, output device(s) **412**, and output device(s) **434** can include any of a display, speakers, printers, etc. These devices are well known in the art and need not be discussed at length here.
- (91) In some embodiments, each one of transceiver(s) **316**, transceiver(s) **414**, and transceiver(s) **434** can include a network interface card (NIC), a network adapter, a LAN adapter, or a physical, virtual, or logical address to connect to various networks, devices, or components. To increase throughput when exchanging wireless data, each one of transceiver(s) **316**, transceiver(s) **414**, and transceiver(s) **434** can utilize multiple-input/multiple-output (MIMO) technology. Each one of transceiver(s) **316**, transceiver(s) **414**, and transceiver(s) **434** can comprise any sort of wireless transceivers capable of engaging in wireless, radio frequency (RF) communication. Each one of

- transceiver(s) **316**, transceiver(s) **414**, and transceiver(s) **434** can also include other wireless modems, such as a modem for engaging in Wi-Fi, WiMAX, Bluetooth, infrared communication, and the like.
- (92) FIGS. 5 through 8 illustrate example processes in accordance with embodiments of the present disclosure. These processes are illustrated as logical flow graphs, each operation of which represents a sequence of operations that can be implemented in hardware, software, or a combination thereof. In the context of software, the operations represent computer-executable instructions stored on one or more computer-readable storage media that, when executed by one or more processors, perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures, and the like that perform particular functions or implement particular abstract data types. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described operations can be combined in any order and/or in parallel, and can be performed multiple times, to implement the processes.
- (93) FIG. **5** illustrates an example process **500** for performing staggered IMS bearer activation and second radio bearer activation, in accordance with various embodiments of the present disclosure. Process **500** may be performed by a first base station, e.g., first base station **400**.
- (94) At operation **502**, a request is received from a User Equipment (UE) via a first radio bearer. In some embodiments, the request is an attach request, e.g., attach request **202**. The attach request may be received over a wireless link, for example. The wireless link may be part of the first radio bearer, which may utilize a first Radio Access Technology (RAT), such as a 4G LTE RAT. The first radio bearer may include the first base station. The attach request may indicate that the UE is requesting to attach to a network. In some instances, the attach request includes an indication that the UE is capable of using a second RAT, such as a 5G NR RAT. In other instances, the attach request may omit the indication.
- (95) In some embodiments, the request is an Internet Protocol (IP) Media Subsystem (IMS) connection request, e.g., IMS connection request **218**. The request may indicate a particular IMS network.
- (96) At operation **504**, activation of an IMS bearer for the UE is initiated. Operation **504** can be performed in response to receiving the request at operation **502**. In some examples, the activation of the IMS bearer is initiated by transmitting a message to a Mobility Management Entity (MME). In some instances, the message is the IMS connection request **218**.
- (97) In various embodiments, an Evolved Packet System (EPS) bearer has already been created for the UE. For example, the EPS bearer may be part of an existing Packet Data Network (PDN) bearer by which the UE can receive services from the Internet, or some other WAN.
- (98) In response to initiating the IMS bearer, the MME and other components of an Evolved Packet Core (EPC) can establish the IMS bearer. In various embodiments, IMS bearer includes the existing EPS bearer. The EPS bearer includes a System Architecture Evolution Gateway (SAEGW), which may include a Serving Gateway (SGW) and a Packet Data Network (PDN) Gateway (PGW). The EPS bearer may further include, or at least utilize, the first radio bearer including the first base station.
- (99) At operation **506**, activation of a second radio bearer is initiated. The initial EPS bearer may include the SGW and the PGW in the EPC and may utilize the first radio bearer containing the first base station. In various embodiments, the first base station may be configured to use a first RAT (e.g., a 4G RAT). The first base station may learn that the UE is capable of using a second RAT (e.g., a 5G NR RAT), and the first base station may be incapable of using the second RAT. In some embodiments, the second RAT corresponds to wireless bands with higher frequencies than wireless bands corresponding to the first RAT.
- (100) The second radio bearer may include the second base station. Activating the second radio bearer may enable the UE to receive services from a WAN (over the PDN bearer) or the IMS

network (over the IMS bearer) via the second RAT.

(101) In some instances, operation **506** includes transmitting a message, e.g., second radio bearer activation request **228**, to the MME requesting the activation of the second radio bearer that includes the second base station. The message may include an identifier associated with the second base station. In response, the MME may transmit a message to one or more elements of the EPC to activate the second radio bearer between the UE and the EPC. For example, the MME may transmit a modify bearer request, e.g., modify bearer request **230**, to the SAEGW. The SAEGW may transmit a message, e.g., modify bearer response **232**, back to the MME indicating that the second radio bearer has been activated. In turn, the MME may inform the first base station that the second radio bearer has been activated by transmitting a message, e.g., confirmation **224**, to the first base station

(102) As a result of the activation of the second radio bearer, the second base station may be configured to transmit data wirelessly to the UE using the second RAT. In some cases, the first radio bearer may only be utilized by the EPS bearer when the second radio bearer is disconnected, or the UE is out of range of the second base station. Otherwise, the second base station may carry data, e.g., second data **236**, transmitted between the EPC and the UE using the second RAT. (103) In various embodiments, operation **506** can be performed at a time after operation **504**. In some embodiments, operation **506** is performed a predetermined period of time after operation **504**. The predetermined period of time may be, for example, derived from past measurements taken of initial IMS bearer setup procedures. In a specific example, the predetermined period of time could be 1 second.

(104) In some embodiments, operation **506** is performed in response to receiving an indication that the IMS bearer has been established. In certain embodiments, the indication can be part of a message confirming that the IMS bearer has been established. This message can be received from any of the MME, the UE, or the SGW. For example, the MME may transmit an activate IMS bearer message, e.g., activate IMS bearer message **224**, to the UE via the first base station, which may inform the first base station that the IMS bearer has been established.

(105) In some instances, operation **506** is performed in response to receiving an indication that the UE is capable of using the second RAT. For example, the UE may wait to indicate that the UE is second RAT-capable until receiving a message, e.g., IMS bearer message **224**, from the first base station confirming that the IMS bearer has been established. In some examples, the message can be in data, e.g., first data **216**, received from the first base station.

(106) In various embodiments, operation **506** is performed after the IMS bearer is initially established. Accordingly, collisions between messages received by elements of the EPC can be avoided.

(107) FIG. **6** illustrates an example process **600** for performing staggered IMS bearer activation and second radio bearer activation by waiting a predetermined period of time, in accordance with embodiments of the present disclosure. Process **600** may be performed by a first base station, e.g., first base station **400**. Process **600** may occur after an initial Packet Data Network (PDN) bearer is established between a User Equipment (UE) and a Wide Area Network (WAN). The PDN bearer may include an Evolved Packet System (EPS) bearer that traverses an Evolved Packet Core (EPC). (108) At operation **602**, an Internet Protocol (IP) Media Subsystem (IMS) connection request is received from the UE via a first radio bearer. The request may indicate a particular IMS network. In some embodiments, IMS connection request can be, e.g., IMS connection request **218**. The first radio bearer that may include a wireless link between the UE and the first base station. The first radio bearer may utilize a first Radio Access Technology (RAT), e.g., a 4G LTE RAT. (109) At operation **604**, the IMS connection request is transmitted to a Mobility Management Entity (MME). The IMS connection request may initiate the creation of an IMS bearer connecting the UE to an IMS network. In response to initiating the activation of the IMS bearer, the MME and

other components of the EPC can establish the IMS bearer. The IMS bearer may include the EPS

bearer included in the PDN bearer.

message **224**.

- (110) Operation **606** includes waiting a predetermined period of time. In some instances, the predetermined period of time is stored in a local memory. In certain embodiments, the predetermined period of time is prescribed according to an update received from a carrier network. The predetermined period of time may be an average time it has taken for an IMS bearer to be established, for example, based on historic trends. In a specific example, the predetermined period of time is about 1 second to 3 seconds. The predetermined period of time may elapse as the MME and other components of the EPC are establishing IMS bearer.
- (111) At operation **608**, a second radio bearer activation request may be transmitted to the MME. Operation **608** may occur after the predetermined period of time has passed. The bearer second radio bearer activation request may initiate activation of a second radio bearer including a second base station (e.g., a gNodeB). The second radio bearer may utilize a second RAT, e.g., a 5G NR RAT. In some instances, the bearer second radio bearer activation request includes second radio bearer activation request **228**, for example.
- (112) At operation **610**, a confirmation that the second radio bearer has been activated may be received from the MME. For example, in response to receiving an indication that the second radio bearer has been activated, e.g., modify bearer response **232**, from a System Architecture Evolution Gateway (SAEGW), the MME may transmit a confirmation message, e.g., second radio bearer activation confirmation message **234**, to the device(s) performing process **600**.
- (113) Once the second radio bearer has been activated, data, e.g., second data **236**, may be exchanged between the UE and the SAEGW via the second base station. In some embodiments, the second base station may be capable of transmitting and receiving data via a particular RAT (e.g., a 5G NR RAT) that the first base station may be incapable of utilizing. Once the second base station is included, or at least utilized, by the EPS bearer, the second base station may use the specific RAT to transmit data wirelessly to the UE and receive data wirelessly from the UE.
- (114) FIG. 7 illustrates an example process **700** for performing staggered IMS bearer activation and second radio bearer activation by initiating the second radio bearer activation upon receiving an indication that default bearer activation is complete, in accordance with some embodiments of the present disclosure. Process **700** may be performed by a first base station, e.g., first base station **400**. Process **700** may occur after an initial Packet Data Network (PDN) bearer is established between a User Equipment (UE) and a Wide Area Network (WAN). The PDN bearer may include an Evolved Packet System (EPS) bearer that traverses an Evolved Packet Core (EPC).
- (115) At operation **702**, an Internet Protocol (IP) Multimedia Subsystem (IMS) connection request is received from the UE via a first radio bearer. The request may indicate a particular IMS network. In some embodiments, IMS connection request can be, e.g., IMS connection request **218**. The IMS connection request may be received over a wireless link that is included in the first radio bearer. (116) At operation **704**, the IMS connection request is transmitted to a Mobility Management Entity (MME). The IMS connection request may initiate the activation of an IMS bearer through the EPC. In response to the IMS connection request, the MME and other components of the EPC can establish the IMS bearer. The IMS bearer may include the EPS bearer included in the PDN bearer. (117) At operation **706**, an indication that the IMS bearer activation is complete is received. In certain embodiments, the indication can be part of a message confirming that the IMS bearer has been established. This message can be received from the MME or the UE. For example, the MME may transmit a message including an activate IMS bearer message, e.g., activate IMS bearer
- (118) At operation **708**, a second radio bearer activation request may be transmitted to the MME. The second radio bearer activation request may initiate activation of a second radio bearer, which may include a second base station (e.g., a gNodeB). Operation **708** may be performed in response to receiving the indication that the IMS bearer activation is complete.
- (119) At operation **710**, a confirmation that the second radio bearer has been activated may be

received from the MME. For example, in response to receiving an indication that the second radio bearer has been activated, e.g., modify bearer response **232**, from a Systems Architecture Evolution Gateway (SAEGW), the MME may transmit a confirmation message, e.g., confirmation **224**, to the device(s) performing process **700**.

- (120) Once the second radio bearer has been activated, data, e.g., second data 226, may be exchanged between the UE and the WAN and/or the IMS network via the second base station. In some embodiments, the second base station may be capable of transmitting and receiving data via a specific RAT (e.g., a 5G NR RAT) that the first base station is incapable of utilizing. Once the second base station is included, or at least utilized, by the EPS bearer, the second base station may use the specific RAT to transmit data wirelessly to the UE and receive data wirelessly from the UE. (121) FIG. 8 illustrates an example process 800 for performing staggered IMS bearer activation and second radio bearer activation by waiting to transmit an indication of a particular Radio Access Technology (RAT) capability until receiving a confirmation that IMS bearer activation is complete. Process 800 may be performed by a User Equipment (UE), e.g., UE 102. In some instances, process 800 is performed after an initial Packet Data Network (PDN) bearer is established between the UE and a Wide Area Network (WAN). The PDN bearer may include an Evolved Packet System (EPS) bearer that traverses an Evolved Packet Core (EPC).
- (122) At operation **802**, an IMS connection request is transmitted to a first base station. The IMS connection request may specify a particular IMS network, e.g., by including an Access Point Name (APN) associated with the IMS network. The IMS connection request may be transmitted to the first base station over a first radio bearer utilizing a first RAT.
- (123) In some instances, the first base station is a base station that is capable of transmitting and receiving data wirelessly using the first RAT, but not a second RAT. However, the first base station may be configured to control a second base station that is capable of transmitting and receiving data wirelessly using the second RAT. For example, the first base station may be an eNodeB and the second base station may be a gNodeB.
- (124) In certain embodiments, upon receiving the IMS connection request, the first base station may initiate IMS bearer activation for the UE, e.g., initiate activation of an IMS bearer utilizing the EPS bearer. The first base station may transmit one or more messages (e.g., the IMS connection request **218**) to components of the EPC, in order to set up a bearer of data through the EPC between the UE and the IMS network.
- (125) At operation **804**, a confirmation that the IMS bearer activation is complete is received from the first base station. The confirmation may indicate that data can now be exchanged with the IMS network via the IMS bearer including the initial EPS bearer (e.g., utilizing the first base station and including a particular Serving Gateway (SGW) and a particular Packet Data Network (PDN) Gateway (PGW)). In some embodiments, the confirmation can include an activate IMS bearer message, e.g., activate IMS bearer message **224**.
- (126) At operation **806**, an indication of a particular RAT capability is transmitted to the first base station. Operation **806** may be performed in response to receiving the confirmation that the IMS bearer activation is complete. The indication can be in the form of capability information, e.g., capability information **226**. The indication may inform the base station that the UE is capable of transmitting and/or receiving data wirelessly using a 5G NR RAT.
- (127) The indication of the particular RAT capability may cause the first base station to initiate activation of the second radio bearer for the UE. In some embodiments, the first base station may be incapable of transmitting or receiving data wirelessly using the 5G NR RAT, but a second base station under control of the first station may be capable of transmitting and receiving data wirelessly using the 5G NR RAT. The first base station may initiate activation of the second radio bearer, which may include the second base station, by transmitting a message to the EPC, e.g., second radio bearer activation request **228**.
- (128) At operation **808**, data may be received from the second base station via the particular RAT.

In various embodiments, the data originates from the WAN and traverses the EPC through the SGW and the PGW in the initial EPS bearer for the UE. The data may be received wirelessly from the second base station via a wireless band that is 5G-specific. For example, the data may be received via a particular frequency band, which includes a higher frequency than the maximum frequency over which the first base station can communicate.

(129) Following process **800**, the UE may be capable of exchanging data with the WAN and the IMS network via an EPS bearer that includes the SGW and the PGW. The UE may further be capable of exchanging data with the WAN and the IMS network via a radio bearer that includes the second base station and that is connected to the EPS bearer.

Conclusion

(130) Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as exemplary forms of implementing the claims.

Claims

- 1. A method, comprising: causing, by a user equipment (UE), a first base station to initiate activation of Internet Protocol (IP) Media Subsystem (IMS) bearer by transmitting, to the first base station, an IMS connection request that includes an access point name (APN) associated with an IMS network; receiving, from the first base station, a confirmation message including i) an indication that the activation of the IMS bearer is complete and ii) an indication of a particular serving gateway (SGW) and a particular packet data network gateway (PGW) for utilizing the first base station, the IMS bearer comprising an Evolved Packet System (EPS) bearer that utilizes the first base station including a first radio bearer and the indication including both a Radio Resource Control (RRC) connection reconfiguration message and an RRC direct transfer message; in response to receiving the indication that the activation of the IMS bearer is complete, causing the first base station to initiate creation of a second radio bearer including a second base station by transmitting, to the first base station, an indication that the UE is 5G-capable; and receiving, from the second base station, data via a 5G New Radio (NR) Radio Access Technology (RAT), wherein the first base station and the second base station form a non-standalone (NSA) network and the first radio bearer remains active while the second radio bearer is active.
- 2. The method of claim 1, wherein the first base station is configured to use a first Radio Access Technology (RAT), the method further comprising: waiting, by the UE, for a predetermined period of time after receiving the indication that the activation of the IMS bearer is complete; and in response to receiving the indication that the activation of the IMS bearer is complete and after waiting for the predetermined period of time, causing the first base station to initiate activation of the second radio bearer including the second base station that is configured to use a second RAT corresponding to a higher frequency than the first RAT, the IMS bearer utilizing the second radio bearer
- 3. The method of claim 2, wherein the first RAT and the second RAT form the NSA network and the first radio bearer remains active while the second radio bearer is active.
- 4. The method of claim 1, wherein the first base station comprises a eNodeB and the second base station comprises a gNodeB.
- 5. The method of claim 1, wherein the EPS bearer includes the particular SGW and the particular PGW.
- 6. The method of claim 1, further comprising sending capability information to the first base station, the capability information including an indication that the UE is capable of transmitting and/or receiving data wirelessly using the 5G NR RAT.
- 7. The method of claim 1, wherein the data originates from a wide area network (WAN) and

traverses a Evolved Packet Core (EPC) through a SGW and a PGW in the EPS bearer for the UE.

- 8. The method of claim 1, wherein initiating the activation of the IMS bearer for the UE comprises forwarding the IMS connection request to a Mobility Management Entity (MME).
- 9. The method of claim 1, wherein the first base station utilizes a 4G RAT and the second base station utilizes the 5G NR RAT, and wherein the first base station is incapable of transmitting data to the UE using the 5G NR RAT.
- 10. The method of claim 1, wherein the indication that the activation of the IMS bearer is complete comprises an activate IMS bearer message.
- 11. A device, comprising: one or more processors; a memory; and one or more components stored in the memory and executable by the one or more processors to perform operations comprising: causing a first base station to initiate activation of Internet Protocol (IP) Media Subsystem (IMS) bearer by transmitting, to the first base station, an IMS connection request that includes an access point name (APN) associated with an IMS network; receiving, from the first base station, a confirmation message including i) an indication that the activation of the IMS bearer is complete and ii) an indication of a particular serving gateway (SGW) and a particular packet data network gateway (PGW) for utilizing the first base station, the IMS bearer comprising an Evolved Packet System (EPS) bearer that utilizes the first base station including a first radio bearer; in response to receiving the indication that the activation of the IMS bearer is complete, causing the first base station to initiate creation of a second radio bearer including a second base station by transmitting, to the first base station, an indication that the device is 5G-capable, the indication including both a Radio Resource Control (RRC) connection reconfiguration message and an RRC direct transfer message; and receiving, from the second base station, data via a 5G New Radio (NR) Radio Access Technology (RAT), wherein the first base station and the second base station form a non-standalone (NSA) network and the first radio bearer remains active while the second radio bearer is active. 12. The device of claim 11, wherein the first base station is configured to use a first Radio Access Technology (RAT), the operations further comprising: waiting, by the device, for a predetermined period of time after receiving the indication that the activation of the IMS bearer is complete; and in response to receiving the indication that the activation of the IMS bearer is complete and after waiting for the predetermined period of time, causing the first base station to initiate activation of the second radio bearer including the second base station that is configured to use a second RAT corresponding to a higher frequency than the first RAT, the IMS bearer utilizing the second radio bearer.
- 13. The device of claim 12, wherein the first RAT and the second RAT form the NSA network and the first radio bearer remains active while the second radio bearer is active.
- 14. The device of claim 11, wherein the first base station comprises a eNodeB and the second base station comprises a gNodeB.
- 15. The device of claim 11, wherein the data originates from a wide area network (WAN) and traverses a Evolved Packet Core (EPC) through a SGW and a PGW in the EPS bearer for the device.
- 16. A method, comprising: causing, by a user equipment (UE), a first base station to initiate activation of Internet Protocol (IP) Media Subsystem (IMS) bearer by transmitting, to the first base station, an IMS connection request; receiving, from the first base station, a confirmation message including i) an indication that the activation of the IMS bearer is complete and ii) an indication of a particular serving gateway (SGW) and a particular packet data network gateway (PGW) for utilizing the first base station, the IMS bearer comprising an Evolved Packet System (EPS) bearer that utilizes the first base station and the indication including both a Radio Resource Control (RRC) connection reconfiguration message and an RRC direct transfer message; waiting, by the UE, for a predetermined period of time after receiving the indication that the activation of the IMS bearer is complete; in response to receiving the indication that the activation of the IMS bearer is complete, causing the first base station to initiate creation of a second radio bearer including a second base

station by transmitting, to the first base station, an indication that the UE is 5G-capable; and receiving, from the second base station, data via a 5G New Radio (NR) Radio Access Technology (RAT), wherein the data is received via a particular frequency band that includes a higher frequency than a maximum frequency over which the first base station can communicate.

17. The method of claim 16, further comprising sending capability information to the first base station, the capability information including an indication that the UE is capable of transmitting and/or receiving data wirelessly using the 5G NR RAT.

18. The method of claim 16, wherein the data originates from a wide area network (WAN) and traverses a Evolved Packet Core (EPC) through a SGW and a PGW in the EPS bearer for the UE. 19. The method of claim 16, wherein initiating the activation of the IMS bearer for the UE comprises forwarding the IMS connection request to a Mobility Management Entity (MME). 20. The method of claim 16, wherein the first base station utilizes a 4G RAT and the second base station utilizes the 5G NR RAT, and wherein the first base station is incapable of transmitting data to the UE using the 5G NR RAT.