

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260730

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Gale; Maxwell et al.

AUTOMATICALLY NAVIGATING BETWEEN ROOMS WITHIN A VIRTUAL CONFERENCING SYSTEM

Abstract

Aspects of the present disclosure involve a system comprising a computer-readable storage medium storing a program and method for providing automatically navigating between rooms within a virtual space for virtual conferencing. The program and method provide for virtual conferencing between plural participants within a first room of plural rooms included within the virtual space; provide, for each of the plural participants, display of a participant video element which corresponds to the participant and which includes a user-selectable button for requesting that the participant follow another participant with respect to navigating between the plural rooms; receive a first indication of a user selection, by a first participant, of the user-selectable button corresponding to a second participant; receive a second indication that the second participant authorizes following the first participant when navigating between the plural rooms; and provide for the second participant to follow the first participant.

Inventors: Gale; Maxwell (New York, NY), Lin; Andrew Cheng-min (Long Island City, NY), Lin; Walton (Chatham, NY)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008563400

Appl. No.: 19/194429

Filed: April 30, 2025

Related U.S. Application Data

parent US continuation 17390546 20210730 parent-grant-document US 12316689 child US 19194429

us-provisional-application US 63168049 20210330

Publication Classification

Int. Cl.: H04L65/403 (20220101); G06F3/0482 (20130101); H04L65/1083 (20220101)

U.S. Cl.:

CPC H04L65/403 (20130101); G06F3/0482 (20130101); H04L65/1083 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This patent application is a continuation of U.S. patent application Ser. No. 17/390,546, filed Jul. 30, 2021, which application claims the benefit of U.S. Provisional Patent Application No. 63/168,049, filed Mar. 30, 2021, entitled “AUTOMATICALLY NAVIGATING BETWEEN ROOMS WITHIN A VIRTUAL CONFERENCING SYSTEM”, each of which are incorporated by reference herein in their entireties.

TECHNICAL FIELD

[0002] The present disclosure relates generally to virtual conferencing systems, including automatically navigating between rooms within a virtual conferencing system.

BACKGROUND

[0003] A virtual conferencing system provides for the reception and transmission of audio and video data between devices, for communication between device users in real-time.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0004] In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced. Some nonlimiting examples are illustrated in the figures of the accompanying drawings in which:

[0005] FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some examples.

[0006] FIG. 2 is a diagrammatic representation of a virtual conferencing system, in accordance with some examples, that has both client-side and server-side functionality.

[0007] FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some examples.

[0008] FIG. 4 illustrates a virtual space design interface with interface elements for designing a virtual space, in accordance with some example embodiments.

[0009] FIG. 5 illustrates a virtual space navigation interface with interface elements to navigate between the rooms of a virtual space and to participate in virtual conferencing with respect to the rooms, in accordance with some example embodiments.

[0010] FIG. 6 is an interaction diagram illustrating a process for automatically navigating between rooms of a virtual space, in accordance with some example embodiments.

[0011] FIGS. 7A-7E illustrate various interface elements relating to automatically navigating between rooms of a virtual space, in accordance with some example embodiments.

[0012] FIG. 8 is a flowchart illustrating a process for automatically navigating between rooms of a

virtual space, in accordance with some example embodiments.

[0013] FIG. **9** is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, in accordance with some examples.

[0014] FIG. **10** is a block diagram showing a software architecture within which examples may be implemented.

DETAILED DESCRIPTION

[0015] A virtual conferencing system provides for the reception and transmission of audio and video data between devices, for communication between device users in real-time. A virtual conferencing system allows a user to design or select a virtual space with multiple rooms for real-time communication. Participants may switch between the different rooms of the virtual space, for example, to engage in different conversations, events, seminars, and the like. In some cases, a first participant may wish for a second participant to automatically follow the first participant between rooms, for example, to facilitate exploring rooms within the virtual space together.

[0016] The disclosed embodiments provide for the second user to automatically follow the first participant between rooms. Each of the participants within a current room is represented by a respective participant video element corresponding to that participant. Each participant video element may include a video feed for that participant. From the perspective of the first participant, each other participant video element includes a user-selectable button to request that participant to follow the first participant.

[0017] The first participant may select the button for a second participant, causing the virtual conferencing system to prompt the second participant whether to authorize following the first participant. In response to receiving authorization from the second participant, the virtual conferencing system provides for the second participant to follow the first participant when navigating between rooms of the virtual space. Thus, the virtual conferencing system facilitates the exploration of rooms within the virtual space, by providing automatic navigation between the rooms.

[0018] FIG. **1** is a block diagram showing an example virtual conferencing system **100** for exchanging data over a network. The virtual conferencing system **100** includes multiple instances of a client device **102**, each of which hosts a number of applications, including a virtual conference client **104** and other application(s) **106**. Each virtual conference client **104** is communicatively coupled to other instances of the virtual conference client **104** (e.g., hosted on respective other client devices **102**), a virtual conference server system **108** and third-party servers **110** via a network **112** (e.g., the Internet). A virtual conference client **104** can also communicate with locally-hosted applications **106** using Applications Program Interfaces (APIs).

[0019] The virtual conferencing system **100** provides for the reception and transmission of audio, video, image, text and/or other signals by user devices (e.g., at different locations), for communication between users in real-time. In some cases, two users may utilize virtual conferencing to communicate with each other in one-to-one communication at their respective devices. In other cases, multiway virtual conferencing may be utilized by more than two users to participate in a real-time, group conversation. Thus, multiple client devices **102** may participate in virtual conferencing, for example, with the client devices **102** participating in a group conversation in which audio-video content streams and/or message content (e.g., text, images) are transmitted between the participant devices.

[0020] A virtual conference client **104** is able to communicate and exchange data with other virtual conference clients **104** and with the virtual conference server system **108** via the network **112**. The data exchanged between virtual conference clients **104**, and between a virtual conference client **104** and the virtual conference server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., video, audio, other multimedia data, text).

[0021] The virtual conference server system **108** provides server-side functionality via the network

112 to a particular virtual conference client **104**. For example, with respect to transmitting audio and/or video streams, the virtual conference client **104** (e.g., installed on a first client device **102**) may facilitate in transmitting streaming content to the virtual conference server system **108** for subsequent receipt by other participant devices (e.g., one or more second client devices **102**) running respective instances of the virtual conference client **104**.

[0022] The streaming content can correspond to audio and/or video content captured by sensors (e.g., microphones, video cameras) on the client devices **102**, for example, corresponding to real-time video and/or audio capture of the users (e.g., faces) and/or other sights and sounds captured by the respective device. The streaming content may be supplemented with other audio/visual data (e.g., animations, overlays, emoticons and the like) and/or message content (e.g., text, stickers, emojis, other image/video data), for example, in conjunction with extension applications and/or widgets associated with the virtual conference client **104**.

[0023] While certain functions of the virtual conferencing system **100** are described herein as being performed by either a virtual conference client **104** or by the virtual conference server system **108**, the location of certain functionality either within the virtual conference client **104** or the virtual conference server system **108** may be a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the virtual conference server system **108** but to later migrate this technology and functionality to the virtual conference client **104** where a client device **102** has sufficient processing capacity.

[0024] The virtual conference server system **108** supports various services and operations that are provided to the virtual conference client **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the virtual conference client **104**. This data may include the above-mentioned streaming content and/or message content, client device information, and social network information, as examples. Data exchanges within the virtual conferencing system **100** are invoked and controlled through functions available via user interfaces (UIs) of the virtual conference client **104**.

[0025] Turning now specifically to the virtual conference server system **108**, an Application Program Interface (API) server **114** is coupled to, and provides a programmatic interface to, application servers **118**. The application servers **118** are communicatively coupled to a database server **124**, which facilitates access to a database **126** that stores data associated with virtual conference content processed by the application servers **118**. Similarly, a web server **116** is coupled to the application servers **118**, and provides web-based interfaces to the application servers **118**. To this end, the web server **116** processes incoming network requests over the Hypertext Transfer Protocol (HTTP) and several other related protocols.

[0026] The Application Program Interface (API) server **114** receives and transmits virtual conference data (e.g., commands, audio/video payloads) between the client device **102** and the application servers **118**. Specifically, the Application Program Interface (API) server **114** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the virtual conference client **104** in order to invoke functionality of the application servers **118**. The Application Program Interface (API) server **114** exposes various functions supported by the application servers **118**, including account registration, login functionality, the streaming of audio and/or video content, and/or the sending and retrieval of message content, via the application servers **118**, from a particular virtual conference client **104** to another virtual conference client **104**, the retrieval of a list of contacts of a user of a client device **102**, the addition and deletion of users (e.g., contacts) to a user graph (e.g., a social graph), and opening an application event (e.g., relating to the virtual conference client **104**).

[0027] The application servers **118** host a number of server applications and subsystems, including for example a virtual conference server **120** and a social network server **122**. The virtual conference server **120** implements a number of virtual conference processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., streaming content)

included in audio-video feeds received from multiple instances of the virtual conference client **104**. Other processor and memory intensive processing of data may also be performed server-side by the virtual conference server **120**, in view of the hardware requirements for such processing.

[0028] The social network server **122** supports various social networking functions and services and makes these functions and services available to the virtual conference server **120**. To this end, the social network server **122** maintains and accesses a user graph **304** (as shown in FIG. 3) within the database **126**. Examples of functions and services supported by the social network server **122** include the identification of other users of the virtual conferencing system **100** with which a particular user has relationships (e.g., contacts such as friends, colleagues, teachers, students, and the like).

[0029] In one or more embodiments, a user interacting via the virtual conference client **104** running on a first client device **102** may select and invite participant(s) to a virtual conference. For example, the participants may be selected from contacts maintained by the social network server **122**. In another example, the participants may be selected from contacts included within a contact address book stored in association with the first client device **102** (e.g., in local memory or in a cloud-based user account). In another example, the participants may be selected by the user manually entering email addresses and/or phone numbers of the participants.

[0030] The user at the first client device **102** may initiate the virtual conference by selecting an appropriate user interface element provided by the virtual conference client **104**, thereby prompting the invited participants, at their respective devices (e.g., one or more second client devices **102**), to accept or decline participation in the virtual conference. When the participant(s) have accepted the invitation (e.g., via the prompt), the virtual conference server system **108** may perform an initialization procedure in which session information is published between the participant client devices **102**, including the user who provided the invite. Each of the participant client devices **102** may provide respective session information to the virtual conference server system **108**, which in turn publishes the session information to the other participant client devices **102**. The session information for each client device **102** may include content stream(s) and/or message content that is made available by the client device **102**, together with respective identifiers for the content stream(s) and/or message content.

[0031] As described below with respect to FIG. 2, the virtual conference may correspond to a virtual space which includes one or more rooms (e.g., virtual rooms). The virtual space and its corresponding rooms may have been created at least in part by the inviting user and/or by other users. In this manner, an end user may act as an administrator, who creates their own virtual spaces with rooms, and/or designs a virtual space based on preset available rooms.

[0032] FIG. 2 is a block diagram illustrating further details regarding the virtual conferencing system **100**, according to some examples. Specifically, the virtual conferencing system **100** is shown to comprise the virtual conference client **104** and the application servers **118**. The virtual conferencing system **100** embodies a number of subsystems, which are supported on the client-side by the virtual conference client **104** and on the server-side by the application servers **118**. These subsystems include, for example, a virtual space creation system **202** which implements a virtual space design interface **204**, and a virtual space participation system **206** which implements a virtual space navigation interface **208**.

[0033] The virtual space creation system **202** provides for a user to design one or more virtual space(s) in which participants may engage in virtual conferencing. In one or more embodiments, a virtual space corresponds to an environment with one or more rooms configured to accommodate virtual conferencing.

[0034] The virtual space may be created and/or selected (e.g., from among a set of predefined virtual spaces with rooms) by an end user who wishes to invite other users for virtual conferencing. In addition, the individual rooms of a virtual space may be newly-created and/or selected (e.g., from among a set of predefined rooms) by the end user. In one or more embodiments, the virtual

space creation system **202** includes a virtual space design interface **204**, which is usable by the end user to design a virtual space, including creating and/or selecting rooms for including in the virtual space.

[0035] As discussed below with respect to FIG. **4**, the virtual space design interface **204** enables an end user (e.g., acting as an administrator) to select and/or position multiple elements within in a room. Examples of elements include, but are not limited to, participant video elements (e.g., for displaying the respective video feeds of participants), chat interfaces (e.g., for participants to provide text-based messages, stickers and/or reactions within a room), breakout buttons (e.g., for shuffling from a first room to one or more second rooms), and/or other user-definable elements for performing certain actions (e.g., speaking into a virtual microphone, querying an administrator via a button, and the like).

[0036] The virtual space participation system **206** is configured to perform virtual conferencing among participants within a virtual space. The participants may include the end user (e.g., administrator) who created the virtual space, as well as those users who were invited to participate in virtual conferencing with respect to the virtual space created/selected by the end user. The virtual space participation system **206** includes a virtual space navigation interface **208** (e.g., discussed below with respect to FIG. **5**) that allows participants to navigate between the rooms of a virtual space, and to participate in virtual conferencing with respect to the rooms.

[0037] In one or more embodiments, the virtual space creation system **202** and the virtual space participation system **206** provide for an end user (e.g., an administrator) to create different types of environments (e.g., virtual spaces with rooms) for virtual conferencing, and for participants to engage in virtual conferencing within such environments. Examples of such virtual conferencing include, but are not limited to: business meetings, seminars, presentations, classroom lectures, teacher office hours, concerts, reunions, virtual dinners, escape rooms, and the like.

[0038] FIG. **3** is a schematic diagram illustrating data structures **300**, which may be stored in the database **126** of the virtual conference server system **108**, according to certain examples. While the content of the database **126** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object- oriented database).

[0039] The database **126** includes profile data **302**, a user graph **304** and a user table **306** relating to the users (participants) of the virtual conferencing system **100**. The user table **306** stores user data, and is linked (e.g., referentially) to the user graph **304** and the profile data **302**. Each user of the virtual conferencing system **100** is associated with a unique identifier (email address, telephone number, social network identifier, etc.).

[0040] The user graph **304** stores (e.g., in conjunction with the social network server **122**) information regarding relationships and associations between users. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example. As noted above, the user graph **304** may be maintained and accessed at least in part by the social network server **122**.

[0041] The profile data **302** stores multiple types of profile data about a particular user. The profile data **302** may be selectively used and presented to other users of the virtual conferencing system **100**, based on privacy settings specified by a particular user. The profile data **302** includes, for example, a user name, telephone number, email address, and/or settings (e.g., notification and privacy settings), as well as a user-selected avatar representation.

[0042] The database **126** further includes a virtual spaces table **308**. As noted above, a virtual space corresponds to an environment with one or more rooms configured to accommodate virtual conferencing. A virtual space may be newly-created by a user, or may be included within one or more sets of public virtual spaces made available (e.g., by other users, system administrators, and the like) for virtual conferencing. The virtual spaces table **308** stores information representing the one or more sets of public virtual spaces, as well as any private virtual space(s) created by a user (e.g., in a case where the particular user did not make such virtual space(s) public).

[0043] In one or more embodiments, the virtual spaces table **308** stores associations between its virtual spaces and users (e.g., within the user table **306**) who selected those virtual spaces. In this manner, it is possible for a particular user to have one or more virtual spaces associated therewith. Moreover, the database **126** includes a rooms table **310** which may be associated with the virtual spaces within the virtual spaces table **308**. As noted above, a room may be newly-created by a user, or may be included within one or more sets (e.g., galleries) of public rooms made available for user selection. The rooms table **310** stores information representing the one or more sets of rooms, as well as any private room(s) created by the user (e.g., in a case where the particular user did not make such room(s) public). The stored information is usable by the virtual conferencing system **100** to create the corresponding rooms for use in a virtual space. In one or more embodiments, the stored information may further include recordings (e.g., audio and/or video recordings) of a particular virtual conference, for subsequent playback by corresponding participants.

[0044] FIG. **4** illustrates a virtual space design interface **204** with interface elements for designing a virtual space, in accordance with some example embodiments. Designing the virtual space may include creation and/or selection of rooms for including in the virtual space. The virtual space design interface **204** includes a menu interface **402**, a room elements interface **404**, an element properties interface **406**, a controls interface **408**, a room list interface **410**, a room canvas interface **412**, and an administrator name **414**. It is noted that elements **402-414** correspond to an example of interface elements for the virtual space design interface **204**, and that additional, fewer and/or different interface elements may be used.

[0045] An administrator (e.g., corresponding to administrator name **414**) may use the various interface elements to design a virtual space. In one or more embodiments, the menu interface **402** includes user-selectable categories (e.g., menu headings) relating to a virtual space (e.g., “workspace”), rooms within the virtual space, and/or elements within a room. For example, the workspace category is user-selectable for presenting options (e.g., via a drop-down list) to manage settings for the virtual space, manage invites for the virtual space, manage versions of a virtual space, publish the virtual space (e.g., for future use by users), manage virtual space publications, and/or to start/manage recordings (e.g., audio and/or video recordings) with respect to the virtual space.

[0046] The room category of the menu interface **402** is user-selectable for presenting options (e.g., via a drop-down list) to manage settings for a room within the virtual space, set a room background, set an order for the rooms listed in the room list interface **410**, create a new room, import a room from a set of available rooms, remove a room, publish a room, manage room publications, and/or to start/manage recordings with respect to a room.

[0047] In addition, the element category is user-selectable for presenting options (e.g., via a drop-down list) to insert elements into a room, insert shapes into a room, foreground/background elements, arrange/position elements, and/or group elements. Examples of elements include, but are not limited to: an action button, analog clock, audience question board, backpack item, breakout button, chat, closed caption display, closed caption input, countdown, clock, digital clock, doorbell, double-sided image, feedback, image, multiuser video chat, music, participant audio mixer, participant count, participant video, picture strip, poll, random source, room preview, scheduled time, sound effect, stopwatch, take picture, text, timer, user search, video, waiting list, web media, website. Examples of shapes include, but are not limited to, a circle, rectangle and triangle.

[0048] The users category of the menu interface **402** is user-selectable for presenting options (e.g., via a drop-down list) to manage users/participants of the virtual space (e.g., adding tags for participants, so as to distinguish between roles such as an administrator or an attendee/participant). In addition, the edit category is user-selectable for performing edit operations (e.g., undo, redo, cut, copy, paste), and the help category is user-selectable for performing help operations (e.g., getting started, discord, live help, submitting feedback).

[0049] In one or more embodiments, the room elements interface **404** includes user-selectable

icons for inserting elements (e.g., corresponding to a subset of those available via the above-mentioned element category) into a current room. For example, the elements may be added and/or positioned within the current room by selecting the element and dragging the selected element onto the room canvas interface **412**, which represents the layout of the current room.

[0050] In one or more embodiments, the room elements interface **404** include icons including but not limited to: a text icon for adding text to a room; a participant video icon for adding a single participant video element (e.g., an interface element which is selectable by a single participant for displaying that participant's video feed) to a room; a multiuser video icon for adding a multiple participant video element (e.g., an interface element which is selectable by one or more participants for displaying the video feeds for those participants) to a room; a chat icon for adding a chat interface (e.g., for messaging using text, stickers, emojis, etc.) to a room; a video playback icon for adding a video playback element (e.g., screen) to a room for playback of a selected video; a background icon for selecting a background color/gradient, image or video to a room; an action icon for adding an action element (e.g., button) to a room for performing a user-defined action (e.g., speaking into a virtual microphone, querying an administrator via a button, and the like); and/or a breakout button for adding a breakout element (e.g., button) for shuffling selected participants between the current room and one or more other rooms.

[0051] In one or more embodiments, the element properties interface **406** include various fields for setting configuration properties for above-described room elements. For example, with respect to elements in general (e.g., text, single participant video element, multi participant video element, chat interface, video element, background image, action element, breakout button), the element properties interface **406** includes fields for setting the element title/name, opacity, gradient, style, layout, borders/corners, shadows, interaction (e.g., to what extent participant(s) may delete, modify, resize the element), filtering, full screen status, conditions, accessibility and actions for the element. For the single participant video element, the element properties interface **406** includes further fields for setting the manner in which users are placed into the single participant video element during virtual conferencing (e.g., automatically, manually by the participant and/or the administrator end user). In addition, for the chat interface, the element properties interface **406** includes further properties for setting who (e.g., administrator and/or participants) can provide chat input, and/or which types of input (e.g., text, stickers, emojis, etc.) are available. For the action element, the element properties interface **406** includes further properties for setting what type of action is to be performed in response to user selection of the action element (e.g., button). Moreover, for the breakout element, the element properties interface **406** includes further properties for selecting participants and/or breakout rooms.

[0052] In one or more embodiments, the element properties interface **406** includes fields for setting configuration properties for the room canvas interface **412**. For example, the element properties interface **406** includes fields selecting a number of fake participants (e.g., simulated video feeds) in order to visualize multiple users, selecting music (e.g., background music), and/or selecting which reaction buttons are available for participants to indicate real-time reactions with respect to virtual conferencing within a room.

[0053] In one or more embodiments, the controls interface **408** includes user-selectable icons corresponding to controls (e.g., administrative controls) for the virtual space. For example, the controls interface **408** include icons including but not limited to: a director mode icon for toggling between a director mode for designing a room and a user mode for viewing the room within the virtual space design interface **204** (e.g., with the director mode including the room elements interface **404** and the element properties interface **406** while the user mode does not); a view icon for viewing the room within the virtual space navigation interface **208**; a share screen icon (e.g., for collaborative design with other user(s) such as co-administrators); a microphone icon for enabling or disabling the microphone; a help icon (e.g., getting started, discord, live help, submitting feedback); an invite icon (e.g., for displaying an invite link for sending to participants to visit the

virtual space); a settings icon (e.g., for selecting the end user's video and audio devices for the virtual conferencing, and for selecting a user avatar); and/or an exit icon for exiting the virtual space design interface **204**.

[0054] In one or more embodiments, the room list interface **410** displays the list of rooms for the virtual space. Each listed room is user selectable to switch to edit (e.g., in director mode) and/or view (e.g., in user mode) the selected room. As noted above, the list of rooms may be modified (e.g., by adding, importing and/or removing rooms) via the options within the room category of the menu interface **402**.

[0055] FIG. 5 illustrates a virtual space navigation interface **208** with interface elements to navigate between the rooms of a virtual space and to participate in virtual conferencing with respect to the rooms, in accordance with some example embodiments. The virtual space navigation interface **208** includes a controls interface **502**, a room list interface **504**, a current room interface **506**, a participant video element **508** and a participant video element **510**. It is noted that elements **502-512** correspond to an example of interface elements for the virtual space navigation interface **208**, and that additional, fewer and/or different interface elements may be used.

[0056] In one or more embodiments, the controls interface **502** includes user-selectable icons corresponding to controls (e.g., administrative controls) for the virtual space. For example, the controls interface **408** include icons including but not limited to: an edit icon for redirecting to the virtual space design interface **204** to edit the current room; a volume icon for adjusting a volume level for the current room; a share screen icon (e.g., for allowing others to view the room without necessarily joining the room); a microphone icon for muting and unmuting the microphone; a help icon (e.g., getting started, discord, live help, submitting feedback); an invite icon (e.g., for displaying an invite link for participants to visit the virtual space); a settings icon (e.g., for selecting the end user's video and audio devices for the virtual conferencing, and for selecting a user avatar); and/or an exit icon for exiting the virtual space design interface **204**.

[0057] In one or more embodiments, the room list interface **504** displays the list of rooms for the virtual space. Each listed room is user selectable to switch to the selected room (e.g., for virtual conferencing). The selected room is presented as a current room within the current room interface **506**. In this manner, a participant may navigate among the multiple rooms available within the virtual space. Alternatively or in addition, navigation between rooms is possible via a virtual space map interface (not shown) which depicts a map view of the virtual space (e.g., a floor plan) and its corresponding rooms, with each room being user selectable to navigate thereto. Alternatively or in addition, navigation between rooms is further possible by positioning a navigation button (not shown) within a room, where user selection of the button results in navigating to another room (e.g., a predefined room). As noted above, the virtual space design interface **204** allows for the design of a virtual space and its corresponding rooms. As such, navigation between rooms is based at least in part on the design of the virtual space (e.g., a virtual space may include one or more of the above-mentioned room list interface **504**, the virtual space map/floor plan interface and/or the navigation button).

[0058] With respect to the current room interface **506**, each participant is represented as a respective participant video element. As noted above, a participant video element corresponds to an interface element (e.g., a box) which is selectable by a single participant for displaying that participant's video feed. The example of FIG. 5 includes a first participant associated with the participant video element **508** and a second participant associated with the participant video element **510**. In one or more embodiments, with respect to the perspective of the first participant, the participant video element **510** showing the feed of the second participant may include participant button(s) **512**. For example, the participant button(s) **512** are selectable by the first participant so as to perform a predefined action (e.g., initiate a side conversation, designate the second participant to follow the first participant when the first participant moves rooms) with respect to the second participant.

[0059] While the example of FIG. 5 illustrates two participants, it is possible for the current room interface **506** to accommodate additional participants for virtual conferencing. The additional participants may be positioned (e.g., automatically and/or manually by dragging) based on the positioning of participant video elements (e.g., boxes) as designed by the virtual space design interface **204**.

[0060] In one or more embodiments, the virtual space navigation interface **208** may vary based on whether a given participant is an administrator or another participant (e.g., an attendee). For example, some participant video elements may be designated (e.g., via the virtual space design interface **204**) for administrators, while other participant video elements are designated for other participants. The virtual conference server system **108** is configured to distinguish between these administrator or other participant roles, for example, based on the above-described tags assigned to participants via the users category of the menu interface **402** provided by the virtual space design interface **204**.

[0061] FIG. 6 is an interaction diagram illustrating a process for automatically navigating between rooms of a virtual space, in accordance with some example embodiments. For explanatory purposes, the process **600** is described herein with reference to a first client device **602**, a second client device **604**, and the virtual conference server system **108**. Each of the first client device **602** and the second client device **604** may correspond to a respective client device **102**. The process **600** is not limited to the first client device **602**, the second client device **604** and the virtual conference server system **108**. Moreover, one or more blocks (or operations) of the process **600** may be performed by one or more other components of the first client device **602**, the second client device **604** or the virtual conference server system **108**, and/or by other suitable devices. Further for explanatory purposes, the blocks (or operations) of the process **600** are described herein as occurring in serial, or linearly. However, multiple blocks (or operations) of the process **600** may occur in parallel or concurrently. In addition, the blocks (or operations) of the process **600** need not be performed in the order shown and/or one or more blocks (or operations) of the process **600** need not be performed and/or can be replaced by other operations. The process **600** may be terminated when its operations are completed. In addition, the process **600** may correspond to a method, a procedure, an algorithm, etc.

[0062] Each of the first client device **602** and the second client device **604** have instances of the virtual conference client **104** installed thereon. In the example of FIG. 6, the first client device **602** and the second client device **604** are associated with a respective first participant and a second participant of the virtual conference server system **108**. For example, the first participant may be associated with a first user account of the virtual conference server system **108**, and the second participant may be associated with a second user account of the virtual conference server system **108**.

[0063] As noted above, the first and second participants are identifiable by the virtual conference server system **108** based on unique identifiers (e.g., email addresses, telephone numbers) associated with respective user accounts for the first and second participants. In one or more embodiments, the virtual conference server system **108** implements and/or works in conjunction with a social network server **122** which is configured to identify contacts with which a particular user has relationships. For example, the first and second participants may be contacts with respect to the virtual conference server system **108**.

[0064] As described herein, the virtual conferencing system **100** provides for the first participant to request the second participant to follow the first participant, in cases where the first participant moves from a current room to another room within the virtual space. At operations **606-608**, the virtual conference server system **108** provides for real-time communication between the participant devices, which include the first client device **602**, the second client device **604**, and any other participating devices (not shown). For example, virtual conference server system **108** provides for receiving and transmitting of data between the participating devices, including one or more of

audio, video, image, text and/or other signals.

[0065] In one or more embodiments, each participant is represented by a respective participant video element (e.g., elements **508-510** in FIG. 5). As noted above, from the perspective of the first participant, the first client device **602** is configured to display a participant button for each of the other participants (e.g., each other participant has a respective participant video element with a participant button). The participant button is user-selectable to request the corresponding participant to follow the first participant when the first participant moves rooms within the virtual space. As discussed below with respect to FIGS. 7A-7E, the participant button for requesting such following is depicted as a walking person icon.

[0066] At block **610**, the first client device **602** receives user selection (e.g., by the first participant) of the participant button to request the second participant to begin following the first participant. The first client device **602** sends an indication of the user selection to the virtual conference server system **108** (operation **612**).

[0067] In response, the virtual conference server system **108** sends a request to the second client device **604**, prompting the second participant whether to authorize automatically following the first participant when navigating between rooms (operation **614**). In the example of FIG. 6, the second participant at the second client device **604** selects to authorize such following of the first participant (block **616**). The second client device **604** then sends an indication of user authorization by the second participant to the virtual conference server system **108** (operation **618**).

[0068] The virtual conference server system **108** stores an indication that the second participant is following the first participant with respect to navigating between rooms in the virtual space (block **620**). For example, the indication is stored in the database **126**, in conjunction with the user table **306** and the virtual spaces table **308**. The stored indication associates the second participant as following the first participant with respect to the current virtual space (e.g., based on respective identifiers for the first participant, the second participant, and/or the virtual space).

[0069] In addition, the virtual conference server system **108** sends, to the first client device **602**, an indication that the second participant is following the first participant (operation **622**). In one or more embodiments, the virtual conference server system **108** causes the first client device **602** to display a notification confirming that the second participant has agreed to, and will follow, the first participant when navigating between rooms of the virtual space.

[0070] In the example of FIG. 6, the first participant (e.g., at a subsequent time) provides user input at the first client device **602**, to move from the current room to another room in the virtual space (block **624**). As discussed above with respect to FIG. 5, such user input may correspond with the first participant selecting a new room within the room list interface **504**, selecting the new room within a virtual space map (e.g., floor plan) interface, and/or pressing a predefined navigation button within the current room. The first client device **602** sends, to the virtual conference server system **108**, a request to switch from the current room to the selected room (operation **626**).

[0071] In response, at operations **628-630**, the virtual conference server system **108** provides for the first and second participants to switch to the selected room. For example, the virtual conference server system **108** is configured to check the virtual spaces table **308** in conjunction with the user table **306**, to determine whether there is a stored indication associating the second participant as following the first participant with respect to the current virtual space. Based on determining that there is a stored indication, the virtual conference server system **108** causes the second participant to follow the first participant when switching from the current room to the selected room.

[0072] In one or more embodiments, the virtual conference server system **108** provides user-selectable interface elements (e.g., discussed below with respect to FIGS. 7C-7E) by which the first participant and/or the second participant can select to discontinue the following of the first participant by the second participant. The example of FIG. 6 depicts an optional block **632**, which is performed in response to receiving such user selection by the first or second participant. At block **632**, the virtual conference server system **108** removes the stored indication (e.g., within the

database **126**) that the second participant is following the first participant. After removing the stored indication, subsequent navigation of the first participant between rooms does not cause the second participant to automatically follow the first participant (e.g., although the second participant may still manually choose to switch rooms).

[0073] Although the example of FIG. **6** is described with respect to a first participant and a single second participant, the virtual conferencing system **100** is not limited to a single participant following the first participant. For example, the first participant may select the participant button requesting to be followed by multiple second participant(s), each of which may individually authorize or decline to follow the first participant. The virtual conference server system **108** is configured to store respective indications (e.g., in the database **126**) of which second user(s) authorized following the first participant, and to provide for causing those second participant(s) to follow the first participant when navigating between rooms.

[0074] Thus, the virtual conferencing system **100** as described herein facilitates the exploration of rooms within the virtual space, by providing automatic navigation between the rooms. Without such automatic navigation, second participant(s) may otherwise be required to detect when the first participant moves between rooms and/or to manually coordinate (e.g., via a separate communication) with the first participant, in cases where the first participant and second participant(s) wish to explore rooms together. The virtual conferencing system **100** reduces such additional efforts by the second participant(s), thereby saving time for the first and second participant(s), and reducing computational resources/processing power for the virtual conferencing system **100**.

[0075] FIGS. **7A-7E** illustrate various interface elements relating to automatically navigating between rooms of a virtual space, in accordance with some example embodiments. As noted above, a participant video element (e.g., participant video element **510**) may include one or more participant button(s) (e.g., participant button(s) **512**). FIG. **7A** depicts one example, in which a follow button **702** is depicted as a walking person icon.

[0076] As described above with respect to FIG. **6**, in response to user selection (e.g., by a first participant) of the follow button **702** (e.g., presented within the participant video element of a second participant), the virtual conference server system **108** requests the second participant to automatically follow the first participant when navigating between rooms of a virtual space. In the example of FIG. **7A**, the virtual conference server system **108** provides a notification **704** to the second client device **604** associated with of the second participant. The notification **704** prompts the second participant whether to authorize automatically following the first participant. For example, the notification **704** includes a button **706** to decline (e.g., “ignore”) the request and a button **708** to accept (e.g., “follow”) the request.

[0077] With respect to FIG. **7B**, the virtual conference server system **108** further provides a notification **710** to the first participant as described above with respect to FIG. **6**. The notification **710** indicates, to the first participant, that the second participant has started to follow the first participant (e.g., based on authorization by the second participant).

[0078] Regarding FIG. **7C**, the virtual conference server system **108** further updates a follower list **712** corresponding to the first participant. For example, the follower list **712** is displayed within the virtual space navigation interface **208** of the first user. In one or more embodiments, the follower list **712** for the first user indicates the name(s) of those participants which follow the first participant. For each listed name, the virtual conference server system **108** provides a button **714** which is selectable to discontinue having the corresponding participant follow the first participant. As noted above, selection of the button **714** causes the virtual conference server system **108** to remove the stored indication (e.g., within the database **126**) that the second participant is following the first participant.

[0079] With respect to FIG. **7D**, the virtual conference server system **108** provides a notification **718** to the second participant, confirming that the second participant authorized (and has begun)

following the first participant when navigating between rooms of the virtual space. The notification **718** includes a button **720** which is selectable to discontinue following the first participant. Selection of the button **720** causes the virtual conference server system **108** to remove the stored indication (e.g., within the database **126**) that the second participant is following the first participant.

[0080] Thus, either the first participant or the second participant is provided with an option to discontinue the following of the first participant by the second participant. With respect to FIG. 7E, in response to selecting this option, the virtual conference server system **108** provides a notification **716** to the first participant, confirming that the second participant has stopped following the first participant.

[0081] FIG. **8** is a flowchart illustrating a process for automatically navigating between rooms of a virtual space, in accordance with some example embodiments. For explanatory purposes, the process **800** is primarily described herein with reference to the first client device **602**, the second client device **604** and the virtual conference server system **108** of FIG. **1** and FIG. **2**. However, one or more blocks (or operations) of the process **800** may be performed by one or more other components, and/or by other suitable devices. Further for explanatory purposes, the blocks (or operations) of the process **800** are described herein as occurring in serial, or linearly. However, multiple blocks (or operations) of the process **800** may occur in parallel or concurrently. In addition, the blocks (or operations) of the process **800** need not be performed in the order shown and/or one or more blocks (or operations) of the process **800** need not be performed and/or can be replaced by other operations. The process **800** may be terminated when its operations are completed. In addition, the process **800** may correspond to a method, a procedure, an algorithm, etc.

[0082] The virtual conference server system **108** provides for virtual conferencing between plural participants within a first room of plural rooms, the plural rooms being included within a virtual space for virtual conferencing (block **802**).

[0083] The virtual conference server system **108** provides, for each of the plural participants in the first room, display of a participant video element which corresponds to the participant and which includes a user-selectable button, the user-selectable button for requesting that the participant follow another participant with respect to navigating between the plural rooms (block **804**). For each of the plural participants, the participant video element may include a video feed for the participant.

[0084] The virtual conference server system **108** receives a first indication of a user selection, by a first participant (e.g., associated with the first client device **602**) of the plural participants, of the user-selectable button corresponding to a second participant (e.g., associated with the second client device **604**) of the plural participants (block **806**).

[0085] The virtual conference server system **108** receives, in response to receiving the first indication, a second indication that the second participant authorizes following the first participant with respect to navigating between the plural rooms (block **808**). Prior to receiving the second indication, the virtual conference server system **108** may send a request to the second client device **604**, for the second participant to authorize following the first participant.

[0086] The virtual conference server system **108** provides, in response to receiving the second indication, for the second participant to follow the first participant when the first participant navigates between the plural rooms of the virtual space (block **810**).

[0087] The virtual conference server system **108** may receive a third indication for the second participant to discontinue following the first participant, and provide, in response to receiving the third indication, for the second participant to discontinue following the first participant. The third indication may be based on a request received from the first participant (e.g., via the first client device **602**). Alternatively or in addition, the third indication may be based on a request received from the second participant (e.g., via the second client device **604**).

[0088] The virtual conference server system **108** may receive a third indication of a user selection, by the first participant, of the user-selectable button corresponding to a third participant of the plural participants. The virtual conference server system **108** may receive, in response to receiving the third indication, a fourth indication that the third participant authorizes following the first participant with respect to navigating between the plural rooms, and provide, in response to receiving the third indication, for the third participant to follow the first participant, such that both the second participant and the third participant follow the first participant navigating between the plural rooms of the virtual space.

[0089] FIG. **9** is a diagrammatic representation of the machine **900** within which instructions **910** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **900** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **910** may cause the machine **900** to execute any one or more of the methods described herein. The instructions **910** transform the general, non-programmed machine **900** into a particular machine **900** programmed to carry out the described and illustrated functions in the manner described. The machine **900** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **900** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **900** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smartphone, a mobile device, a wearable device (e.g., a smartwatch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **910**, sequentially or otherwise, that specify actions to be taken by the machine **900**. Further, while only a single machine **900** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **910** to perform any one or more of the methodologies discussed herein. The machine **900**, for example, may comprise the client device **102** or any one of a number of server devices forming part of the virtual conference server system **108**. In some examples, the machine **900** may also comprise both client and server systems, with certain operations of a particular method or algorithm being performed on the server-side and with certain operations of the particular method or algorithm being performed on the client-side.

[0090] The machine **900** may include processors **904**, memory **906**, and input/output I/O components **902**, which may be configured to communicate with each other via a bus **940**. In an example, the processors **904** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) Processor, a Complex Instruction Set Computing (CISC) Processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **908** and a processor **912** that execute the instructions **910**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **9** shows multiple processors **904**, the machine **900** may include a single processor with a single-core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

[0091] The memory **906** includes a main memory **914**, a static memory **916**, and a storage unit **918**, both accessible to the processors **904** via the bus **940**. The main memory **906**, the static memory **916**, and storage unit **918** store the instructions **910** embodying any one or more of the methodologies or functions described herein. The instructions **910** may also reside, completely or partially, within the main memory **914**, within the static memory **916**, within machine-readable

medium **920** within the storage unit **918**, within at least one of the processors **904** (e.g., within the Processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **900**.

[0092] The I/O components **902** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **902** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **902** may include many other components that are not shown in FIG. **9**. In various examples, the I/O components **902** may include user output components **926** and user input components **928**. The user output components **926** may include visual components (e.g., a display such as a plasma display panel (PDP), a light-emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The user input components **928** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

[0093] In further examples, the I/O components **902** may include biometric components **930**, motion components **932**, environmental components **934**, or position components **936**, among a wide array of other components. For example, the biometric components **930** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye-tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **932** include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope).

[0094] The environmental components **934** include, for example, one or cameras (with still image/photograph and video capabilities), illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment.

[0095] With respect to cameras, the client device **102** may have a camera system comprising, for example, front cameras on a front surface of the client device **102** and rear cameras on a rear surface of the client device **102**. The front cameras may, for example, be used to capture still images and video of a user of the client device **102** (e.g., “selfies”), which may then be augmented with augmentation data (e.g., filters) described above. The rear cameras may, for example, be used to capture still images and videos in a more traditional camera mode, with these images similarly being augmented with augmentation data. In addition to front and rear cameras, the client device **102** may also include a 360° camera for capturing 360° photographs and videos.

[0096] Further, the camera system of a client device **102** may include dual rear cameras (e.g., a primary camera as well as a depth-sensing camera), or even triple, quad or penta rear camera

configurations on the front and rear sides of the client device **102**. These multiple cameras systems may include a wide camera, an ultra-wide camera, a telephoto camera, a macro camera and a depth sensor, for example.

[0097] The position components **936** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

[0098] Communication may be implemented using a wide variety of technologies. The I/O components **902** further include communication components **938** operable to couple the machine **900** to a network **922** or devices **924** via respective coupling or connections. For example, the communication components **938** may include a network interface Component or another suitable device to interface with the network **922**. In further examples, the communication components **938** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **924** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

[0099] Moreover, the communication components **938** may detect identifiers or include components operable to detect identifiers. For example, the communication components **938** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **938**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

[0100] The various memories (e.g., main memory **914**, static memory **916**, and memory of the processors **904**) and storage unit **918** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **910**), when executed by processors **904**, cause various operations to implement the disclosed examples.

[0101] The instructions **910** may be transmitted or received over the network **922**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **938**) and using any one of several well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **910** may be transmitted or received using a transmission medium via a coupling (e.g., a peer-to-peer coupling) to the devices **924**.

[0102] FIG. **10** is a block diagram **1000** illustrating a software architecture **1004**, which can be installed on any one or more of the devices described herein. The software architecture **1004** is supported by hardware such as a machine **1002** that includes processors **1020**, memory **1026**, and I/O components **1038**. In this example, the software architecture **1004** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1004** includes layers such as an operating system **1012**, libraries **1010**, frameworks **1008**, and applications **1006**. Operationally, the applications **1006** invoke API calls **1050** through the software stack and receive messages **1052** in response to the API calls **1050**.

[0103] The operating system **1012** manages hardware resources and provides common services. The operating system **1012** includes, for example, a kernel **1014**, services **1016**, and drivers **1022**. The kernel **1014** acts as an abstraction layer between the hardware and the other software layers.

For example, the kernel **1014** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services **1016** can provide other common services for the other software layers. The drivers **1022** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1022** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., USB drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

[0104] The libraries **1010** provide a common low-level infrastructure used by the applications **1006**. The libraries **1010** can include system libraries **1018** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1010** can include API libraries **1024** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1010** can also include a wide variety of other libraries **1028** to provide many other APIs to the applications **1006**.

[0105] The frameworks **1008** provide a common high-level infrastructure that is used by the applications **1006**. For example, the frameworks **1008** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1008** can provide a broad spectrum of other APIs that can be used by the applications **1006**, some of which may be specific to a particular operating system or platform.

[0106] In an example, the applications **1006** may include a home application **1036**, a contacts application **1030**, a browser application **1032**, a book reader application **1034**, a location application **1042**, a media application **1044**, a messaging application **1046**, a game application **1048**, and a broad assortment of other applications such as a third-party application **1040**. The applications **1006** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1006**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third-party application **1040** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party application **1040** can invoke the API calls **1050** provided by the operating system **1012** to facilitate functionality described herein.

Glossary

[0107] “Carrier signal” refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

[0108] “Client device” refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication

device that a user may use to access a network.

[0109] “Communication network” refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1xRTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

[0110] “Component” refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various examples, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering examples in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component

comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In examples in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some examples, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other examples, the processors or processor-implemented components may be distributed across a number of geographic locations.

[0111] “Computer-readable storage medium” refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure.

[0112] “Machine storage medium” refers to a single or multiple storage devices and media (e.g., a centralized or distributed database, and associated caches and servers) that store executable instructions, routines and data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks

such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium.”

[0113] “Non-transitory computer-readable storage medium” refers to a tangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine.

[0114] “Signal medium” refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term “signal medium” shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure.

Claims

1. A method, comprising: providing for virtual interaction between plural participants within a first room of plural rooms, the plural rooms being included within a virtual space for virtual interaction; providing, for each of the plural participants in the first room, display of a participant video element which corresponds to the participant and which includes a user-selectable button, the user-selectable button for requesting that the participant automatically follow another participant with respect to navigating between the plural rooms; receiving a first indication of a user selection, by a first participant of the plural participants, of the user-selectable button corresponding to a second participant of the plural participants; receiving, in response to receiving the first indication, a second indication that the second participant authorizes automatically following the first participant with respect to navigating between the plural rooms; in response to receiving the second indication, storing the second indication, and updating a follower list for the first participant to include the second participant, the follower list indicating names of the plural participants that automatically follow the first participant with respect to navigating between the plural rooms; providing, based on the stored second indication, for the second participant to automatically follow the first participant from the first room to the second room.
2. The method of claim 1, further comprising: sending, prior to receiving the second indication, a request to a device associated with the second participant, the request for the second participant to authorize automatically following the first participant.
3. The method of claim 1, further comprising: receiving a third indication for the second participant to discontinue automatically following the first participant; and providing, in response to receiving the third indication, for the second participant to discontinue automatically following the first participant.
4. The method of claim 3, wherein the third indication is based on a request received from the first participant.
5. The method of claim 3, wherein the third indication is based on a request received from the second participant.
6. The method of claim 1, further comprising: receiving a third indication of a user selection, by the first participant, of the user-selectable button corresponding to a third participant of the plural participants; receiving, in response to receiving the third indication, a third indication that the third participant authorizes automatically following the first participant with respect to navigating between the plural rooms; and providing, in response to receiving the third indication, for the third participant to automatically follow the first participant, such that both the second participant and

the third participant automatically follow the first participant navigating between the plural rooms of the virtual space.

7. The method of claim 1, wherein for each of the plural participants, the participant video element includes a video feed for the participant.

8. The method of claim 1, wherein each name in the follower list is presented with a respective button which is user-selectable by the first participant to discontinue automatically following the first participant.

9. A system comprising: at least one processor; and a memory storing instructions that, when executed by the at least one processor, configure the at least one processor to perform operations comprising: providing for virtual interaction between plural participants within a first room of plural rooms, the plural rooms being included within a virtual space for virtual interaction; providing, for each of the plural participants in the first room, display of a participant video element which corresponds to the participant and which includes a user-selectable button, the user-selectable button for requesting that the participant automatically follow another participant with respect to navigating between the plural rooms; receiving a first indication of a user selection, by a first participant of the plural participants, of the user-selectable button corresponding to a second participant of the plural participants; receiving, in response to receiving the first indication, a second indication that the second participant authorizes automatically following the first participant with respect to navigating between the plural rooms; in response to receiving the second indication, storing the second indication, and updating a follower list for the first participant to include the second participant, the follower list indicating names of the plural participants that automatically follow the first participant with respect to navigating between the plural rooms; providing, based on the stored second indication, for the second participant to automatically follow the first participant from the first room to the second room.

10. The system of claim 9, the operations further comprising: sending, prior to receiving the second indication, a request to a device associated with the second participant, the request for the second participant to authorize automatically following the first participant.

11. The system of claim 9, the operations further comprising: receiving a third indication for the second participant to discontinue automatically following the first participant; and providing, in response to receiving the third indication, for the second participant to discontinue automatically following the first participant.

12. The system of claim 11, wherein the third indication is based on a request received from the first participant.

13. The system of claim 11, wherein the third indication is based on a request received from the second participant.

14. The system of claim 9, the operations further comprising: receiving a third indication of a user selection, by the first participant, of the user-selectable button corresponding to a third participant of the plural participants; receiving, in response to receiving the third indication, a third indication that the third participant authorizes automatically following the first participant with respect to navigating between the plural rooms; and providing, in response to receiving the third indication, for the third participant to automatically follow the first participant, such that both the second participant and the third participant automatically follow the first participant navigating between the plural rooms of the virtual space.

15. The system of claim 9, wherein for each of the plural participants, the participant video element includes a video feed for the participant.

16. The system of claim 9, wherein each name in the follower list is presented with a respective button which is user-selectable by the first participant to discontinue automatically following the first participant.

17. A non-transitory computer-readable storage medium, the computer-readable storage medium including instructions that when executed by a computer, cause the computer to perform operations

comprising: providing for virtual interaction between plural participants within a first room of plural rooms, the plural rooms being included within a virtual space for virtual interaction; providing, for each of the plural participants in the first room, display of a participant video element which corresponds to the participant and which includes a user-selectable button, the user-selectable button for requesting that the participant automatically follow another participant with respect to navigating between the plural rooms; receiving a first indication of a user selection, by a first participant of the plural participants, of the user-selectable button corresponding to a second participant of the plural participants; receiving, in response to receiving the first indication, a second indication that the second participant authorizes automatically following the first participant with respect to navigating between the plural rooms; in response to receiving the second indication, storing the second indication, and updating a follower list for the first participant to include the second participant, the follower list indicating names of the plural participants that automatically follow the first participant with respect to navigating between the plural rooms; providing, based on the stored second indication, for the second participant to automatically follow the first participant from the first room to the second room.

18. The non-transitory computer-readable storage medium of claim 17, the operations further comprising: sending, prior to receiving the second indication, a request to a device associated with the second participant, the request for the second participant to authorize automatically following the first participant.

19. The non-transitory computer-readable storage medium of claim 17, the operations further comprising: receiving a third indication for the second participant to discontinue automatically following the first participant; and providing, in response to receiving the third indication, for the second participant to discontinue automatically following the first participant.

20. The non-transitory computer-readable storage medium of claim 19, wherein the third indication is based on a request received from the first participant.
