

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385525
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	M S; Anand et al.

Magnetic thrust bearing systems

Abstract

Magnetic thrust bearing systems are disclosed. Examples disclosed herein include a thrust bearing system comprising a thrust disc protruding radially outward from a shaft, the thrust disc including a first magnet, the first magnet including a first pole at a forward side of the thrust disc and a second pole at an aft side, a first thrust pad positioned on the forward side, the first thrust pad including a second magnet adjacent to a first surface of the first thrust pad, the first surface facing the thrust disc, the second magnet including a third pole, the third and first pole having the same polarity, and a second thrust pad including a third magnet adjacent to a second surface of the second thrust pad, the second surface facing the thrust disc, the third magnet including a fourth pole, the fourth and second pole having the same polarity.

Inventors: M S; Anand (Bengaluru, IN), Ganiger; Ravindra Shankar (Bengaluru, IN), Yamarthi; David Raju (Bengaluru, IN)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 1000008749296

Assignee: GENERAL ELECTRIC COMPANY (Evendale, OH)

Appl. No.: 18/331698

Filed: June 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240337290 A1	Oct. 10, 2024

Foreign Application Priority Data

IN	202311025954	Apr. 06, 2023
----	--------------	---------------

Publication Classification

Int. Cl.: F16C32/04 (20060101); H02K7/09 (20060101)

U.S. Cl.:

CPC F16C32/0474 (20130101); H02K7/09 (20130101); H02K2205/03 (20130101)

Field of Classification Search

CPC: F16C (32/0474); H02K (2205/03)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3347262	12/1966	Gibson	N/A	N/A
6213736	12/2000	Weisser	N/A	N/A
6811135	12/2003	Moreno et al.	N/A	N/A
6986647	12/2005	Jones et al.	N/A	N/A
7140393	12/2005	Sheydayi	N/A	N/A
7186093	12/2006	Goshi	N/A	N/A
7249939	12/2006	Yanagihara	N/A	N/A
11098817	12/2020	Eddleman et al.	N/A	N/A
11137144	12/2020	Wilson et al.	N/A	N/A
2018/0100543	12/2017	Hyatt	N/A	F16C 32/0427

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2037121	12/2008	EP	F03D 80/70
2282091	12/2016	EP	N/A
S59186520	12/1983	JP	N/A
2002130256	12/2001	JP	N/A
2007092646	12/2006	JP	N/A
2015035006	12/2014	WO	N/A

OTHER PUBLICATIONS

JP-2002130256-A_translate (Year: 2002). cited by examiner

JPS59186520U_translate (Year: 1984). cited by examiner

Xu et al., "Numerical and Experimental Study on Air Thrust Foil Bearing Performance with Improved Structural Model Based on Real-time Taper Inlet Height", Research Square, Jul. 8, 2020, 26 pages. cited by applicant

Bruckner et al., "Analytic Modeling of the Hydrodynamic, Thermal, and Structural Behavior of Foil Thrust Bearings", NASA, Jun. 2005, 19 pages. cited by applicant

European Patent Office, "Extended European Search Report," issued in connection with European Patent Application No. 24168135.2, dated Sep. 16, 2024, 11 pages. cited by applicant

Primary Examiner: Patel; Tulsidas C

Assistant Examiner: Qureshi; Mohammed Ahmed

Attorney, Agent or Firm: HANLEY, FLIGHT & ZIMMERMAN, LLC

Background/Summary

RELATED APPLICATIONS

(1) This patent claims the benefit of Indian Provisional Patent Application No. 202311025954, which was filed on Apr. 6, 2023. Indian Provisional Patent Application No. 202311025954 is hereby incorporated herein by reference in its entirety. Priority to India Provisional Patent Application No. 202311025954 is hereby claimed.

FIELD OF THE DISCLOSURE

(2) This disclosure relates generally to fluid pumps, and, more particularly, to magnetic thrust bearing systems for fluid pumps.

BACKGROUND

(3) Aircraft typically include various accessory systems supporting the operation of the aircraft and/or its gas turbine engine(s). For example, such accessory systems may include a lubrication system that lubricates components of the engine(s), an engine cooling system that provides cooling air to engine components, an environmental control system that provides cooled air to the cabin of the aircraft, and/or the like. As such, heat is added or removed from a fluid (e.g., oil, air, etc.) during operation of these accessory systems.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a side view of an example aircraft.
- (2) FIG. 2 is a schematic cross-sectional view of an example gas turbine engine of an aircraft.
- (3) FIG. 3 is a schematic diagram of an example thermal management system for transferring heat between fluids.
- (4) FIG. 4 is a schematic illustration of an example thermal transport bus pump.
- (5) FIG. 5 is a schematic illustration of an example thrust bearing system.
- (6) FIG. 6 is a schematic illustration of an example first dynamic thrust bearing system in accordance with the teachings disclosed herein.
- (7) FIG. 7 is a partial view of the example first dynamic thrust bearing system in accordance with the teachings disclosed herein.
- (8) FIG. 8 is another partial view of the example first dynamic thrust bearing system in accordance with the teachings disclosed herein.
- (9) FIGS. 9A and 9B are a detailed views of portions of an example thrust disc constructed in accordance with teachings disclosed.
- (10) FIG. 10 is a schematic illustration of an example second dynamic thrust bearing system in accordance with the teachings disclosed herein.
- (11) FIG. 11 is a schematic illustration of an example third dynamic thrust bearing system in accordance with the teachings disclosed herein.
- (12) The figures are not to scale. In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts.

DETAILED DESCRIPTION

(13) “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation.

(14) As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, or (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

(15) As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

(16) As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” object, as used herein, refers to one or more of that object. The terms “a” (or “an”), “one or more”, and “at least one” are used interchangeably herein. Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., the same entity or object. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

(17) As used herein, connection references (e.g., attached, coupled, connected, and joined) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other. As used herein, stating that any part is in “contact” with another part is defined to mean that there is no intermediate part between the two parts.

(18) Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.

(19) Approximating language, as used herein throughout the specification and claims, is applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about”, “approximately”, and “substantially”, are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an

instrument for measuring the value, or the precision of the methods or machines for constructing or manufacturing the components and/or systems. For example, the approximating language may refer to being within a ten percent margin.

(20) The terms “forward” and “aft” refer to relative positions within a gas turbine engine, pump, or vehicle, and refer to the normal operational attitude of the gas turbine engine, pump, or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust. Further, with regard to a pump, forward refers to a position closer to a pump inlet and aft refers to a position closer to an end of the pump opposite the inlet.

(21) The terms “upstream” and “downstream” refer to the relative direction with respect to a flow in a pathway. For example, with respect to a fluid flow, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(22) As used herein, in the context of describing the position and/or orientation of a first object relative to a second object, the term “substantially orthogonal” encompasses the term orthogonal and more broadly encompasses a meaning whereby the first object is positioned and/or oriented relative to the second object at an absolute angle of no more than five degrees (5°) from orthogonal. For example, a first axis that is substantially orthogonal to a second axis is positioned and/or oriented relative to the second axis at an absolute angle of no more than five degrees (5°) from orthogonal.

(23) As used herein, “radially” is used to express a point or points along a radial vector originating at a central axis of a rotating body and pointing perpendicularly outward from the central axis. In some examples, fluid is said to accelerate radially outward from an impeller, meaning that the fluid flows outward from a central axis (axis of rotation) of the impeller at a direction that is substantially orthogonal to the central axis.

(24) A centrifugal fluid pump moves fluid (e.g., fuel, water, oil, supercritical carbon dioxide (sCO₂), etc.) through systems (e.g., waste heat recovery (WHR) systems) by converting rotational kinetic energy of an impeller to hydrodynamic energy of the flowing fluid. In other words, the angular velocity of the impeller is directly proportional to the flow rate of the flowing fluid exiting the pump. The impeller is provided a change in rotational kinetic energy from an electric motor applying mechanical work to an impeller shaft coupled to the impeller and to a rotor of an electric motor. The rotor is provided a change in mechanical work over a period of time (e.g., mechanical power) from a stator in the electric motor applying electromagnetic forces to the rotor in the form of torque. When the motor supplies a constant amount of electrical energy to the stator, then the rotor supplies a constant amount of mechanical energy to the impeller.

(25) During operation of the pump, spinning of an impeller shaft and the associated impeller can cause the impeller shaft to radially vibrate within housing(s) of the pump. The pump housing(s) internally frame(s) radial bearings (e.g., hydrodynamic bearings, foil bearings, rolling-element bearings, etc.) to support radial loads (e.g., weight) of the impeller shaft and dampen the vibrations.

(26) Also during pump operations, the impeller shaft may experience axial loads that act generally parallel to the central axis of the pump and/or impeller shaft. Axial loads acting on the impeller can be unbalanced, meaning that a forward axial load (e.g., axial load acting toward a forward portion of the pump) and an aft axial load (e.g., axial load acting toward an aft portion of the pump) can be unequal and produce an axial thrust of the impeller shaft. A forward or an aft axial thrust can cause the impeller shaft to shift along the central axis and cause parts coupled to the impeller shaft (e.g., impeller, rotor shaft, motor armature, etc.) to contact the housing(s), the motor, and/or other internal parts of the pump. The pump housing(s) include axial bearings (e.g., hydrodynamic bearings, foil bearings, etc.) that support axial thrusts of the impeller shaft and reduce, inhibit, and/or dampen such movements.

(27) In some examples, the fluid (e.g., sCO₂, oil, liquid helium, etc.) that the pump pressurizes in the system can be used to lubricate the radial and/or axial bearings to reduce frictional forces

between rotating elements within those bearings. For example, the pump can include flowlines leading from a pump outlet to the axial bearings to provide and/or transmit pressurized fluid to a thrust bearing.

(28) As used herein, a “flowline” can refer to a path (e.g., a flowpath, flow direction, etc.) of the fluid and/or a structure (e.g., pipe, casing, etc.) used to enclose (e.g., direct, guide, etc.) the fluid.

(29) The pressurized fluid flows in between a thrust disc, a forward thrust pad, and an aft thrust pad of the thrust bearing apparatus, system, and/or assembly. The thrust disc is coupled to the impeller shaft and protrudes radially outward from the impeller shaft, and the thrust pads are coupled to the pump housing(s) and protrude radially inward toward the impeller shaft. Furthermore, the pump can include expeller vanes to drive the fluid from internal portions of the pump housing to the pump outlet. In some examples, expeller vanes protrude from an aft side of the impeller and function similarly to impeller vanes. That is, fluid approaches the expeller vanes along the central axis and accelerates radially outward from the expeller vanes. Thus, the flowlines and the expeller vanes can implement a lubricating circuit from the pump outlet to the axial bearing(s) and back to the expeller vanes to provide a continuous flow of the fluid to the axial load bearings.

(30) During operation of the pump, axial thrust of the impeller shaft can act in forward or aft directions based on interactions between the impeller vanes/expeller vanes and the fluid. The fluid enters through the pump inlet along a central/rotating/shaft axis toward the impeller, which includes the impeller vanes to accelerate the fluid radially outward into a pump outlet, chamber, flowline, casing, etc. Fluid pressure on a forward side, end, portion, face, etc., of the impeller can transfer aft axial loads to the impeller shaft in the aft direction.

(31) Similarly, the fluid in the pump housing flows forward along the axis of rotation of the impeller shaft and builds up pressure on an aft side, end, portion, face, etc. of the impeller (e.g., the expeller). Fluid pressure on an aft side of the impeller can transfer forward loads to the impeller shaft in the forward direction.

(32) When the forward and aft axial loads are of equal values and act in opposite directions, the pump is said to be “thrust balanced.” As used herein, “forward thrust” refers to unbalanced thrust of the impeller shaft acting in the forward direction due to the forward axial load exceeding the aft axial load. As used herein, “aft thrust” refers to unbalanced thrust of the impeller shaft acting in the aft direction due to the aft axial load exceeding the forward axial load.

(33) In some examples, when the pump operates at substantially low rotational speeds, angular velocities, operating speeds, etc. (e.g., 500, 1,000, 2,500 rpm, etc.), the fluid pressure at the pump inlet exceeds the fluid pressure within the pump housing(s). Thus, at substantially low operating speeds (“low speeds”), aft thrust of the impeller shaft is induced.

(34) In some examples, when the pump operates at substantially high rotational speeds, angular velocities, operating speeds, etc. (e.g., 5000, 10,000, 25,000 revolutions per minute (rpm), etc.), the fluid pressure within the pump housing(s) exceeds the fluid pressure at the pump inlet. Thus, at substantially high operating speeds (“high speeds”), forward thrust of the impeller shaft is induced.

(35) When forward thrust or aft thrust is applied to the impeller shaft, axial displacement (e.g., in forward or aft directions) of the impeller shaft from an initial position can occur by some amount (e.g., 0.001, 0.005, 0.010 inches (in), etc.) despite the axial support of the thrust bearing(s). At some operational speeds of the pump, the axial thrust acting on the impeller shaft can oscillate between forward and aft directions. At such speeds, the thrust can oscillate at frequencies that known thrust bearings are incapable of adaptively and/or dynamically supporting or cannot support quickly, efficiently, and/or adequately enough. Example thrust bearings that are unable to balance pressure may fail to keep appropriate spacing between thrust pads, spacers, thrust discs, etc. In such examples, damage to thrust pads, thrust discs, impeller shafts, or other pump components can result.

(36) In examples disclosed herein, dynamic thrust bearing systems can adjust fluid pressures on forward and/or aft sides of the thrust disc to counteract the forward and/or aft thrust and inhibit,

dampen, and/or restrict axial movement of the impeller shaft. In some examples, lubrication flowline(s) (e.g., primary flowline, secondary flowline(s), etc.) lead the fluid to the dynamic thrust bearing system (e.g., thrust pads and/or thrust disc) at an outer diameter of the dynamic thrust bearing system (e.g., traveling external to the pump housing(s)) and/or at points distal to a central axis of the dynamic thrust bearing system. In some examples, the lubrication flowline(s) direct the fluid to the dynamic thrust bearing system at an inner diameter of the dynamic thrust bearing system (e.g., internal to the pump housing(s)) and/or at points proximal to the central axis of the dynamic thrust bearing system. Rotation of the thrust disc in the dynamic thrust bearing system causes the fluid to pressurize between the thrust disc and the forward and aft thrust pads. In other words, the pressurized fluid, at least partially, bears the axial thrust of the impeller shaft.

(37) In some examples, first and second secondary flowlines of the secondary lubrication flowline terminate at the forward and aft thrust pads, respectively, where magnet and/or spring assemblies can permit, inhibit, and/or prohibit the fluid from entering the dynamic thrust bearing system. For example, when the pump operates at low speeds, when aft thrust of the impeller shaft occurs, and/or when the impeller shaft moves in the aft direction, the fluid pressure on the aft side of the thrust disc can increase, cause an aft magnet and/or spring assembly to interact (e.g., engage), permit the fluid to enter a bearing chamber on the aft side of the thrust disc, further increase the aft fluid pressure, and inhibit, counteract, and/or stabilize aft movement of the thrust disc and/or impeller shaft.

(38) In some other examples, the thrust pads and/or other parts of the dynamic thrust bearing system can divide the flow path of the primary flowline into separate internal channels of the thrust disc depending on a position of the impeller shaft and/or the thrust disc. For example, as the impeller shaft moves forward, forward internal passages become exposed, which direct the fluid to the forward side of the thrust disc, increase the forward fluid pressure, and inhibit, counteract, and/or stabilize forward movement of the thrust disc and/or impeller shaft.

(39) Example magnetic thrust bearing systems disclosed herein reduce the amount of axial movement that the impeller shaft experiences due to forward and aft thrusts. Example magnetic thrust bearing systems disclosed herein can also dampen or otherwise reduce the frequency of oscillations in the impeller shaft due to unbalanced and alternating axial thrusts. Thus, examples disclosed herein can reduce a frequency or magnitude at which the impeller shaft or parts coupled thereto physically contact other part(s) and/or housing(s) of the pump. For example, examples disclosed herein employ magnets to prevent contact between (e.g., repel) an example thrust disc and example thrust pads. Additionally, examples disclosed herein employ magnets. Furthermore, example systems disclosed herein can improve the operational efficiency of the pump (e.g., centrifugal sCO₂ pump) by minimizing or otherwise reducing frictional energy losses associated with axial impeller shaft movement. Furthermore, the example systems disclosed herein can increase the time between maintenance services to repair and/or replace component(s) of the thrust bearing(s), motor, pump, etc.

(40) For the figures disclosed herein, identical numerals indicate the same elements throughout the figures. Referring now to the drawings, FIG. 1 is a side view of an example aircraft 10. As shown in FIG. 1, the aircraft 10 includes a fuselage 12 and a pair of wings 14 (one is shown) extending outward from the fuselage 12. In the illustrated example, a gas turbine engine 100 is supported on each wing 14 to propel the aircraft through the air during flight. Additionally, the aircraft 10 includes a vertical stabilizer 16 and a pair of horizontal stabilizers 18 (one is shown). However, in some examples, the aircraft 10 includes engines of different types and/or in different positions than the illustrative example of FIG. 1.

(41) Furthermore, the aircraft 10 can include a thermal management system 200 for transferring heat between fluids supporting the operation of the aircraft 10. More specifically, the aircraft 10 can include one or more accessory systems configured to support the operation of the aircraft 10. For example, such accessory systems include a lubrication system that lubricates components of the

engines **100**, a cooling system that provides cooling air to components of the engines **100**, an environmental control system that provides cooled air to the cabin of the aircraft **10**, and/or the like. In such examples, the thermal management system **200** is configured to transfer heat from one or more fluids supporting the operation of the aircraft **10** (e.g., the oil of the lubrication system, the air of the cooling system and/or the environmental control system, and/or the like) to one or more other fluids supporting the operation of the aircraft **10** (e.g., the fuel supplied to the engines **100**). However, in some other examples, the thermal management system **200** is configured to transfer heat between another fluid or component supporting the operation of the aircraft **10**.

(42) Although examples disclosed herein are described with reference to the aircraft **10** of FIG. **1**, examples disclosed herein can be applicable to another type or configuration of aircraft that uses a thermal management system substantially similar to the thermal management system **200** of FIGS. **1-3**. Thus, the present subject matter can be readily adaptable to another aircraft and/or another heat transfer application associated with another type of vehicle.

(43) FIG. **2** is a schematic cross-sectional view of an example gas turbine engine **100**. In the illustrated example, the engine **100** is configured as a high-bypass turbofan engine. However, in some examples, the engine **100** is configured as a propfan engine, a turbojet engine, a turboprop engine, a turboshaft gas turbine engine, etc.

(44) In general, the engine **100** extends along an axial centerline **102** and includes a fan **104**, a low-pressure (LP) spool **106**, and a high pressure (HP) spool **108** at least partially encased by an annular nacelle **110**. More specifically, the fan **104** can include a fan rotor **112** and a plurality of fan blades **114** (one is shown) coupled to the fan rotor **112**. In this respect, the fan blades **114** are circumferentially spaced apart and extend radially outward from the fan rotor **112**. Moreover, the LP and HP spools **106**, **108** are positioned downstream from the fan **104** along the axial centerline **102**. As shown, the LP spool **106** is rotatably coupled to the fan rotor **112**, which permits the LP spool **106** to rotate the fan blades **114**. Additionally, a plurality of outlet guide vanes or struts **116** circumferentially spaced apart from each other and extend radially between an outer casing **118** surrounding the LP and HP spools **106**, **108** and the nacelle **110**. As such, the struts **116** support the nacelle **110** relative to the outer casing **118** such that the outer casing **118** and the nacelle **110** define a bypass airflow passage **120** positioned therebetween.

(45) The outer casing **118** generally surrounds or encases, in serial flow order, a compressor section **122**, a combustion section **124**, a turbine section **126**, and an exhaust section **128**.

(46) In some examples, the compressor section **122** includes a low-pressure (LP) compressor **130** of the LP spool **106** and a high-pressure (HP) compressor **132** of the HP spool **108** positioned downstream from the LP compressor **130** along the axial centerline **102**. Each compressor **130**, **132** can, in turn, include one or more rows of compressor stator vanes **134** interdigitated with one or more rows of compressor rotor blades **136**. As such, the compressors **130**, **132** define a compressed air flow path **133** extending therethrough.

(47) Moreover, in some examples, the turbine section **126** includes a high-pressure (HP) turbine **138** of the HP spool **108** and a low-pressure (LP) turbine **140** of the LP spool **106** positioned downstream from the HP turbine **138** along the axial centerline **102**. Each turbine **138**, **140** can, in turn, include one or more rows of turbine stator vanes **142** interdigitated with one or more rows of turbine rotor blades **144**.

(48) Additionally, the LP spool **106** includes the low-pressure (LP) shaft **146** and the HP spool **108** includes a high-pressure (HP) shaft **148** positioned concentrically around the LP shaft **146**. In such examples, the HP shaft **148** rotatably couples the turbine rotor blades **144** of the HP turbine **138** and the compressor rotor blades **136** of the HP compressor **132** such that rotation of the turbine rotor blades **144** of the HP turbine **138** rotatably drives the compressor rotor blades **136** of the HP compressor **132**. As shown, the LP shaft **146** is directly coupled to the turbine rotor blades **144** of the LP turbine **140** and the compressor rotor blades **136** of the LP compressor **130**. Furthermore, the LP shaft **146** is coupled to the fan **104** via a gearbox **150**. In this respect, the rotation of the

turbine rotor blades **144** of the LP turbine **140** rotatably drives the compressor rotor blades **136** of the LP compressor **130** and the fan blades **114**.

(49) In some examples, the engine **100** generates thrust to propel an aircraft. More specifically, during operation, air **152** enters an inlet portion **154** of the engine **100**. The fan **104** supplies a first portion **156** of the air **152** to the bypass airflow passage **120** and a second portion **158** of the air **152** to the compressor section **122**. The second portion **158** of the air **152** first flows through the LP compressor **130** in which the compressor rotor blades **136** therein progressively compress the second portion **158** of the air **152**. Next, the second portion **158** of the air **152** flows through the HP compressor **132** in which the compressor rotor blades **136** therein continue to progressively compress the second portion **158** of the air **152**. The compressed second portion **158** of the air **152** is subsequently delivered to the combustion section **124**. In the combustion section **124**, the second portion **158** of the air **152** mixes with fuel and burns to generate high-temperature and high-pressure combustion gases **160**. Thereafter, the combustion gases **160** flow through the HP turbine **138** which the turbine rotor blades **144** of the HP turbine **138** extract a first portion of kinetic and/or thermal energy therefrom. This energy extraction rotates the HP shaft **148**, which drives the HP compressor **132**. The combustion gases **160** then flow through the LP turbine **140** in which the turbine rotor blades **144** of the LP turbine **140** extract a second portion of kinetic and/or thermal energy therefrom. This energy extraction rotates the LP shaft **146**, which drives the LP compressor **130** and the fan **104** via the gearbox **150**. The combustion gases **160** then exit the engine **100** through the exhaust section **128**.

(50) As mentioned above, the aircraft **10** can include a thermal management system **200** for transferring heat between fluids supporting the operation of the aircraft **10**. In this respect, the thermal management system **200** can be positioned within the engine **100**. For example, as shown in FIG. 2, the thermal management system **200** is positioned within the outer casing **118** of the engine **100**. However, in some other examples, the thermal management system **200** is positioned at another location within the engine **100**.

(51) Furthermore, in some examples, the engine **100** defines a third-stream flow path **170**. In general, the third-stream flow path **170** extends from the compressed air flow path **133** defined by the compressor section **122** to the bypass airflow passage **120**. In this respect, the third-stream flow path **170** allows compressed a portion of the second portion **158** of the air **152** from the compressor section **122** to bypass the combustion section **124**. More specifically, in some examples, the third-stream flow path **170** defines a concentric or non-concentric passage relative to the compressed air flow path **133** downstream of one or more of the compressors **130**, **132** or the fan **104**. The third-stream flow path **170** can be configured to selectively remove the second portion **158** of the air **152** from the compressed air flow path **133** via one or more variable guide vanes, nozzles, or other actuatable flow control structures.

(52) In addition, as will be described below, in some examples, the thermal management system **200** transfers heat to the air flowing through the third-stream flow path **170**. However, a pressure and/or a flow rate of a fluid (e.g., a heat exchange fluid such as a supercritical fluid (e.g., supercritical carbon dioxide (sCO₂), etc.)) within the thermal management system **200** limits a rate at which thermal energy is transferred between the air and the heat exchange fluid.

Additionally, it is advantageous for the thermal management system **200** to produce the pressure and/or the flow rate with pumps that support axial thrusts of the shaft within the pump to improve the lifespan and/or efficiency of the pump(s) and the thermal management system **200**.

(53) Although examples disclosed herein are described with reference to the gas turbine engine **100** of FIG. 2, examples disclosed herein can be applicable to another type or configuration of engine that uses a thermal management system substantially similar to the thermal management system **200** of FIGS. 1-3. Thus, the present subject matter can be readily adaptable to another engine and/or another heat transfer application associated with another type of vehicle.

(54) FIG. 3 is a schematic view of an example implementation of the thermal management system

200 for transferring heat between fluids. In general, the thermal management system **200** is discussed in the context of the aircraft **10** and the gas turbine engine **100** described above and shown in FIGS. **1** and **2**. However, the thermal management system **200** can be implemented within another type of aircraft and/or another gas turbine engine of another configuration.

(55) As shown, the thermal management system **200** includes a thermal transport bus **202**.

Specifically, in some examples, the thermal transport bus **202** is configured as one or more fluid conduits through which a fluid (e.g., a heat exchange fluid) flows. As described below, the heat exchange fluid flows through various heat exchangers such that heat is added to and/or removed from the heat exchange fluid. In this respect, the heat exchange fluid can be a working fluid, such as supercritical carbon dioxide, oil, liquid helium, etc. Moreover, in such examples, the thermal management system **200** includes a pump **204** configured to pump the heat exchange fluid through the thermal transport bus **202**.

(56) Additionally, the thermal management system **200** includes one or more heat source heat exchangers **206** arranged along the thermal transport bus **202**. More specifically, the heat source heat exchanger(s) **206** is fluidly coupled to the thermal transport bus **202** such that the heat exchange fluid flows through the heat source heat exchanger(s) **206**. In this respect, the heat source heat exchanger(s) **206** is configured to transfer heat from fluids supporting the operation of the aircraft **10** to the heat exchange fluid, which cools the fluids supporting the operation of the aircraft **10**. Thus, the heat source heat exchanger(s) **206** adds heat to the heat exchange fluid. Although FIG. **3** illustrates two heat source heat exchangers **206**, the thermal management system **200** can include a single heat source heat exchanger **206** or three or more heat source heat exchangers **206**.

(57) The heat source heat exchanger(s) **206** can correspond to many configurations of heat exchanger(s) that cool a fluid supporting the operation of the aircraft **10**. In some examples, at least one of the heat exchangers **206** is a heat exchanger(s) of the lubrication system(s) of the engine(s) **100**. In such examples, the heat exchanger(s) **206** transfers heat from the oil lubricating the engine(s) **100** to the heat transfer fluid. In some other examples, at least one of the heat exchangers **206** is a heat exchanger(s) of the cooling system of the engine(s) **100**. In such examples, the heat exchanger(s) **206** transfers heat from the cooling air bled from the compressor section(s) **122** (or a compressor discharge plenum) of the engine(s) **100** to the heat transfer fluid. However, in some other examples, the heat source heat exchanger(s) **206** corresponds to other types of heat exchangers that cool a fluid supporting the operation of the aircraft **10**.

(58) Furthermore, the thermal management system **200** includes a plurality of heat sink heat exchangers **208** arranged along the thermal transport bus **202**. More specifically, the heat sink heat exchangers **208** are fluidly coupled to the thermal transport bus **202** such that the heat exchange fluid flows through the heat sink heat exchangers **208**. In this respect, the heat sink heat exchangers **208** are configured to transfer heat from the heat exchange fluid to other fluids supporting the operation of the aircraft **10**, which heats the other fluids supporting the operation of the aircraft **10**. Thus, the heat sink heat exchangers **208** remove heat from the heat exchange fluid. Although FIG. **3** illustrates two heat sink heat exchangers **208**, the thermal management system **200** can include three or more heat sink heat exchangers **208**.

(59) The heat sink heat exchangers **208** can correspond to many configurations exchangers that heat a fluid supporting the operation of the aircraft **10**. For example, at least of one of the heat exchangers **208** is a heat exchanger(s) of the fuel system(s) of the engine(s) **100**. In such examples, the fuel system heat exchanger(s) **208** transfers heat from the heat transfer fluid to the fuel supplied to the engine(s) **100**. In some other examples, at least one of the heat exchangers **208** is a heat exchanger(s) in contact with the first portion **156** of the air **152** flowing through the bypass airflow passage(s) **120** of the engine(s) **100**. In such examples, the heat exchanger(s) **208** transfers heat from the heat exchange fluid to the first portion **156** of the air **152** flowing through the bypass airflow passage(s) **120**.

(60) In some examples, one or more of the heat exchangers **208** are configured to transfer heat to

the air flowing through the third-stream flow path **170**. In such examples, the heat exchanger(s) **208** is in contact with the air flow through the third-stream flow path **170**. Thus, heat from the heat exchange fluid flowing through the thermal transport bus **202** can be transferred to the air flow through the third-stream flow path **170**. The use of the third-stream flow path **170** as a heat sink for the thermal management system **200** provides one or more technical advantages. For example, the third-stream flow path **170** provides greater cooling than other sources of bleed air because a larger volume of air flows through the third-stream flow path **170** than other bleed air flow paths. Moreover, the air flowing through third-stream flow path **170** is cooler than the air flowing through other bleed air flow paths and the compressor bleed air. Additionally, the air in the third-stream flow path **170** is pressurized, which allows the heat exchanger(s) **208** to be smaller than heat exchangers relying on other heat sinks within the engine **100**. Furthermore, in examples in which the engine **100** is unducted, using the third-stream flow path **170** as a heat sink does not increase drag on the engine **100** unlike the use of ambient air (e.g., a heat exchanger in contact with air flowing around the engine **100**). However, in some other examples, the heat sink heat exchangers **208** correspond to other types of heat exchangers that heat a fluid supporting the operation of the aircraft **10**.

(61) Moreover, in some examples, the thermal management system **200** includes one or more bypass conduits **210**. Specifically, as shown, each bypass conduit **210** is fluidly coupled to the thermal transport bus **202** such that the bypass conduit **210** allows at least a portion of the heat exchange fluid to bypass one of the heat exchangers **206**, **208**. In some examples, the heat exchange fluid bypasses one or more of the heat exchangers **206**, **208** to adjust the temperature of the heat exchange fluid within the thermal transport bus **202**. The flow of example heat exchange fluid through the bypass conduit(s) **210** is controlled to regulate the pressure of the heat exchange fluid within the thermal transport bus **202**. In the illustrated example of FIG. **3**, each heat exchanger **206**, **208** has a corresponding bypass conduit **210**. However, in some other examples, other numbers of heat exchangers **206**, **208** can have a corresponding bypass conduit **210** as long as there is at least one bypass conduit **210**.

(62) Additionally, in some examples, the thermal management system **200** includes one or more heat source valves **212** and one or more heat sink valves **214**. In general, each heat source valve **212** is configured to control the flow of the heat exchange fluid through a bypass conduit **210** that bypasses a heat source heat exchanger **206**. Similarly, each heat sink valve **214** is configured to control the flow of the heat exchange fluid through a bypass conduit **210** that bypasses a heat sink heat exchanger **208**. In this respect, each valve **212**, **214** is fluidly coupled to the thermal transport bus **202** and a corresponding bypass conduit **210**. As such, each valve **212**, **214** can be moved between fully and/or partially opened and/or closed positions to selectively occlude the flow of heat exchange through its corresponding bypass conduit **210**.

(63) The valves **212**, **214** are controlled based on the pressure of the heat exchange fluid within the thermal transport bus **202**. More specifically, as indicated above, in certain instances, the pressure of the heat exchange fluid flowing through the thermal transport bus **202** can fall outside of a desired pressure range. When the pressure of the heat exchange fluid is too high, the thermal management system **200** can incur accelerated wear. In this respect, when the pressure of the heat exchange fluid within the thermal transport bus **202** exceeds a maximum or otherwise increased pressure value, one or more heat source valves **212** open. In such examples, at least a portion of the heat exchange fluid flows through the bypass conduits **210** instead of the heat source heat exchanger(s) **206**. Thus, less heat is added to the heat exchange fluid by the heat source heat exchanger(s) **206**, which reduces the temperature and, thus, the pressure of the fluid. In some examples, the maximum pressure value is between 3800 and 4000 pounds per square inch or less. In some examples, the maximum pressure value is between 2700 and 2900 pounds per square inch, such as 2800 pounds per square inch. In some other examples, the maximum pressure value is between 1300 and 1500 pounds per square inch, such as 1400 pounds per square inch. Such

maximum pressure values generally prevent the thermal management system **200** from incurring accelerated wear.

(64) In some examples, the maximum pressure value is set prior to and/or during operation based on one or more parameters (e.g., materials utilized, pump **204** design, aircraft **10** design, gas turbine engine **100** design, heat exchange fluid, etc.) associated with the thermal management system **200**. The example maximum pressure value can be adjusted relative to the pressure capacities of the thermal transport bus **202**, the pump **204**, the heat exchangers **206**, **208**, the bypass conduit(s) **210**, and/or the valves **212**, **214**.

(65) Conversely, when the pressure of the heat exchange fluid is too low, the pump **204** can experience operability problems and increased wear. As such, when the pressure of the heat exchange fluid within the thermal transport bus falls below a minimum or otherwise reduced pressure value, one or more thermal sink valves **214** open. In such examples, at least a portion of the heat exchange fluid flows through the bypass conduits **210** instead of the heat sink heat exchangers **208**. Thus, less heat is removed from the heat exchange fluid by the heat sink heat exchangers **208**, which increases the temperature and, thus, the pressure of the fluid. In some examples, the minimum pressure value is 1070 pounds per square inch or more. In some examples, the minimum pressure value is between 1150 and 1350 pounds per square inch, such as 1250 pounds per square inch. In some other examples, the minimum pressure value is between 2400 and 2600 pounds per square inch, such as 2500 pounds per square inch. Such minimum pressure values are generally utilized when the heat exchange fluid is in a supercritical state (e.g., when the heat exchange fluid is carbon dioxide).

(66) As such, the thermal management system **200** can be configured to operate such that the pressure of the heat transport fluid is maintained with a range extending between the minimum and maximum pressure values. In some examples, the range extends from 1070 to 4000 pounds per square inch. Specifically, in one example, the range extends from 1250 to 1400 pounds per square inch. In some other examples, the range extends from 2500 to 2800 pounds per square inch.

(67) Accordingly, the operation of the pump **204** and the valves **212**, **214** allows the disclosed thermal management system **200** to maintain the pressure of the heat exchange fluid within the thermal transport bus **202** within a specified range of values as the thermal load placed on the thermal management system **200** varies.

(68) Furthermore, the example pump **204** drives the flow of the heat exchange fluid through the thermal management system **200**. In some examples, the thermal management system **200** includes one pump **204** or multiple pumps **204** depending on the desired flow rate, delta pressure across the pump **204**, and/or the kinetic energy loss of the heat exchange fluid in the thermal transport bus **202**. For example, the pump **204** can increase the output pressure head to accelerate the flow of the heat exchange fluid to a first flowrate. As the heat exchange fluid passes through the thermal transport bus **202**, the example kinetic energy of the heat exchange fluid dissipates due to friction, temperature variations, etc. Due to the kinetic energy losses, the heat exchange fluid decelerates to a second flow rate at some point upstream of the pump **204**. When the example second flow rate is below a desired operating flow rate of the heat exchange fluid, the pump **204** can either be of a different architecture that outputs a higher first flow rate, or one or more additional pumps **204** can be included in the thermal management system **200**.

(69) FIG. 4 is a schematic illustration of an example thermal transport bus pump **400** (e.g., a supercritical carbon dioxide (sCO₂) pump, the pump **204** of FIG. 3, etc.). In the illustrated example of FIG. 4, the thermal transport bus pump **400** drives a heat exchange fluid, such as supercritical carbon dioxide, through one or more fluid conduits (e.g., the thermal transport bus **202** of FIG. 3) **402**. Specifically, the heat exchange fluid flows through an inlet pipe **404** and encounters an impeller **406** (e.g., a compressor wheel) that rotates to drive the heat exchange fluid through a pump outlet **408** fluidly coupled to the fluid conduit(s) **402**. In turn, the fluid conduit(s) **402** can feed the heat exchange fluid to one or more heat exchangers (e.g., the heat exchanger **206**, **208** of

FIG. 3). Accordingly, the thermal transport bus pump **400** can pump the heat exchange fluid to manage a thermal energy of working fluids associated with the aircraft **10** of FIG. **1** and/or the gas turbine engine **100** of FIG. **2**.

(70) In the illustrated example of FIG. **4**, the thermal transport bus pump **400** includes a motor **410** positioned in a motor housing **412**. In FIG. **4**, the motor **410** is an induction motor operatively coupled to a variable frequency drive (VFD) and controlling circuitry (not shown), such as a full authority digital engine control (FADEC), that controls a rotational speed of the motor **410**. For example, the controlling circuitry can operate the motor **410** based on a pressure and/or a temperature of the heat exchange fluid in the fluid conduit(s) **402** and/or in the thermal transport bus pump **400**. In some examples, the controlling circuitry can operate the motor **410** based on a pressure and/or a temperature of the working fluids affected by the heat exchange fluid. Additionally or alternatively, the controlling circuitry can operate the motor **410** based on vibration measurements obtained by accelerometers operatively coupled to the thermal transport bus pump **400** and/or the fluid conduit(s) **402**.

(71) In FIG. **4**, the motor housing **412** is at least partially surrounded by a cooling jacket **414** to prevent the motor **410** from overheating. An aft end of the motor housing **412** is coupled to an aft bearing housing **416** via first bolts **418**. Furthermore, an end cap **420** is coupled to the aft bearing housing **416** via the first bolts **418**. A forward end of the motor housing **412** is coupled to a forward bearing housing **422** opposite the aft bearing housing **416** via second bolts **424**. Moreover, the forward bearing housing **422** is coupled to a backplate **426** and the pump outlet **408** on an opposite side of the backplate **426** via the second bolts **424**.

(72) In the illustrated example of FIG. **4**, the motor **410** includes a stator **428** to induce alternating electrical currents in field coils and emit alternating magnetic fields about a central axis of the motor **410**. The alternating magnetic fields interact with permanent magnets of a rotor **430** and, in turn, provide torque to the rotor **430**. The rotor **430** is fixedly coupled to an impeller shaft **432** ("shaft **432**"), and the shaft is fixedly coupled to the impeller **406**. As such, the motor **410** drives a rotation of the shaft **432** and, in turn, a rotation of the impeller **406**. An aft end of the shaft **432** is supported by a first radial foil bearing **434**, which is coupled to the aft bearing housing **416**. Similarly, a forward end of the shaft **432** is supported by a second radial bearing **436** coupled to the forward bearing housing **422**.

(73) The first radial foil bearing **434** and the second radial bearing **436** include spring-loaded foil journal linings that support radial loads of the shaft **432** during substantially low (e.g., startup) rotational speeds (e.g., 0-5,000 rotations per minute (rpm), etc.). When the motor **410** causes the shaft **432** to rotate at a substantially high (e.g., operational) rotational speed (e.g., 5000-20,000 rpm, etc.), a pressure of the working medium (e.g., air, oil, supercritical carbon dioxide (sCO₂), etc.) increases and pushes the foil lining radially outward. Thus, the pressurized working medium supports the radial loads of the shaft **432** when the shaft **432** is rotating at operational speeds (e.g., 3000 rpm, 10,000 rpm, 25,000 rpm, etc.).

(74) In the illustrated example of FIG. **4**, a thrust disc **438** of the shaft **432** is supported by a thrust bearing system **440**. For example, the thrust bearing system **440** can include foil bearings to support axial loads of the shaft **432** via interactions with the thrust disc **438**. In some examples, the thrust bearing system **440** is coupled to the aft bearing housing **416** and/or the end cap **420** via bolts.

(75) The example impeller **406** of the pump **400** includes expeller vanes **442** on an aft portion of the impeller **406**. At operational speeds of the motor **410**, the expeller vanes **442** cause the working fluid (e.g., sCO₂) to flow forward from the forward bearing housing **422**, motor housing **412**, etc. into the fluid conduit **402**.

(76) In the illustrated example of FIG. **4**, the example sCO₂ fluid flows into the pump **400** by way of the fluid conduit **402** as illustrated with an arrow indicating a flow direction **444**. At low speeds (e.g., startup speeds) of the motor **410**, the flow direction **444** of the example sCO₂ imparts an aft

thrust **446** on the impeller **406** and the shaft **432** as illustrated with an arrow indicating a direction of the aft thrust **446**. At high speeds (e.g., operational speeds) of the motor **410**, the expeller vanes **442** drive the heat exchange fluid inside the pump **400** forward toward the pump outlet **408**, and the fluid generates a forward thrust **448** on the impeller **406** and the shaft **432** as illustrated with an arrow indicating a direction of the forward thrust **448**. The thrust bearing system **440** is included in the pump **400** to support the aft and forward thrusts **446**, **448** of the shaft **432**.

(77) In some examples, the pump **400** includes an example outer flowline **450** that diverges from the pump outlet **408** to provide sCO₂ as a working medium to the thrust bearing system **440** and to support the thrust disc **438** when pressurized. Additionally or alternatively, the outer flowline **450** diverges from the fluid conduit **402** and/or the expeller vanes **442**. The example outer flowline **450** can circumvent one or more of the motor housing **412**, the aft bearing housing **416**, the forward bearing housing **422**, and/or the backplate **426** to access the thrust bearing system **440**.

(78) In some examples, the pump **400** includes an example inner flowline **452** that diverges from the expeller vanes **442** to provide sCO₂ as a working medium to the thrust bearing system **440** and to support the thrust disc **438** when pressurized. Additionally or alternatively, the inner flowline **452** diverges from the fluid conduit **402** and/or the pump outlet **408**. The example inner channel can pass through one or more of the motor housing **412**, the aft bearing housing **416**, the forward bearing housing **422**, and/or the backplate **426** to access the thrust bearing system **440**.

(79) The outer and inner flowlines **450**, **452** of FIG. 4 are illustrated as example configurations to reflect general locations of the flowlines and directions of the flow. Although both the outer and inner flowlines **450**, **452** are illustrated in FIG. 4, only one may be included in the pump **400** to achieve a same function. The pump **400** can be configured with the outer flowline **450** to reduce complication during fabrication and/or assembly and to reduce risk of internal leakages. The pump **400** can be configured with the inner flowline **452** to reduce an amount of space the pump **400** occupies.

(80) Also illustrated in FIG. 4 are first return flowline(s) **454** and second return flowline(s) **456** to generally depict exit points and flow directions of the working fluid from the thrust bearing system **440** to the expeller vanes **442**. Further details of the outer flowline **450**, the inner flowline **452**, the first return flowline **454**, and the second return flowline **456** are described below with reference to FIG. 5.

(81) In the illustrated example of FIG. 4, the thrust disc **438** and the thrust bearing system **440** are designed such that forward and aft bearing capacities are not dynamically adjusted to account for fluctuations between aft and forward thrusts **446**, **448**. In other words, there may be no dynamic subsystems in the thrust bearing system **440** to dynamically change axial support a forward or an aft side of the thrust disc **438** in response transition(s) from the aft thrust **446** to the forward thrust **448** and vice versa. Examples disclosed herein include apparatus and systems to dynamically support axial loads in forward and/or aft directions (e.g., aft and/or forward thrusts **446**, **448**) based on a fluid pressure changes on forward and aft sides of a thrust disc.

(82) FIG. 5 is a schematic illustration of a thrust bearing system **500** that can be used in the pump **400** illustrated in FIG. 4. The thrust bearing system **500** includes the thrust disc **438** fixedly coupled to the impeller shaft **432** and interposed between a forward thrust pad **502** and an aft thrust pad **504**. The thrust bearing system **500** includes a thrust bearing housing **506** to rigidly affix the forward and aft thrust pads **502**, **504** in place. The forward and aft thrust pads **502**, **504** are spaced at a distance by a spacer **508** to define a bearing chamber **510** where the fluid can collect and become pressurized by the rotating thrust disc **438**. The thrust bearing housing **506** includes an opening **512** (e.g., a hole, slot, port, etc.) to permit the fluid to enter the bearing chamber **510**, become pressurized on forward and aft sides of the thrust disc **438**, and bear axial loads of the shaft **432**. In some examples, the thrust bearing system **500** and example systems disclosed herein include a magnet and/or spring assembly in the bearing chamber **510** between the thrust disc **438** and the forward and aft thrust pads **502**, **504** to support axial loads of the shaft **432** during startup

operations of the pump **400** before the pressurized working fluid solely supports the thrust disc **438**.

(83) The illustration of FIG. 5 depicts a primary outer flowline **450A** to provide the working fluid (e.g., sCO₂) to the thrust disc **438** via the opening **512** (distal to a central axis **518** of the shaft **432**). The example thrust bearing system **500** also includes a secondary outer flowline **450B** to illustrate how the fluid is provided to the forward and/or aft thrust pads **502**, **504**. As mentioned previously, the outer flowlines **450A-B** can circumvent the exterior of the pump **400** around one or more of the motor housing **412**, the aft bearing housing **416**, the end cap **420**, and/or the forward bearing housing **422**. In some examples, the outer flowlines **450A-B** exit the pump **400** at the pump outlet **408** and re-enter at the aft bearing housing **416** and/or the end cap **420**. Although one primary outer flowline **450A** and one secondary outer flowline **450B** are illustrated in FIG. 5, the thrust bearing system **500** can include a plurality of (e.g., two, four, ten, etc.) primary and secondary outer flowlines **450A-B**. In general, the number of primary outer flowlines **450A** corresponds to the number of secondary flowlines **450B**. However, in some examples, the unequal numbers of primary and second flowlines **450A-B** are utilized.

(84) When the outer flowlines **450A-B** are included, the thrust bearing system **500** can also include the first return flowline(s) **454** to transmit the working fluid back to the expeller vanes **442**. The first return flowline(s) **454** exit the bearing chamber **510** proximal to the central axis **518** of the shaft **432**. Although two of the first return flowlines **454** are illustrated in FIG. 5, there can be a plurality (e.g., four, eight, 12, etc.) of first return flowlines **454** included in the thrust bearing system **500**. Generally, when the outer flowlines **450A-B** are utilized, the thrust bearing system **500** includes at least one of the first return flowline(s) **454** on the forward side of the thrust disc **438** and at least one of the first return flowline(s) **454** on the aft side of the thrust disc **438**. In some examples, the first return flowlines **454** illustrated in FIG. 5 originate as distinct flowlines that converge at some point downstream of the thrust bearing system **500** and upstream of the expeller vanes **442**. In some examples, the first return flowlines **454** remain distinct and separated between the thrust bearing system **500** and the expeller vanes **442**.

(85) The illustration of FIG. 5 also depicts a primary inner flowline **452A** to provide the fluid to the thrust disc **438** via gaps and/or openings proximal to the central axis **518** of the shaft **432**. Furthermore, the example thrust bearing system **500** also includes a secondary inner flowline **452B** to illustrate how the fluid is provided to the forward and/or aft thrust pads **502**, **504**. As mentioned previously, the inner flowlines **452A-B** can pass through the interior of the pump **400** through and/or between one or more of the motor **410**, the motor housing **412**, the aft bearing housing **416**, the end cap **420**, and/or the forward bearing housing **422**. Although one primary inner flowline **452A** and one secondary inner flowline **452B** are illustrated in FIG. 5, the thrust bearing system **500** can include a plurality of (e.g., two, four, ten, etc.) primary and secondary inner flowlines **452A-B**. In general, the number of primary inner flowlines **452A** corresponds to the number of secondary inner flowlines **452B**. However, in some examples, the unequal numbers of primary and secondary inner flowlines **452A-B** are utilized.

(86) When the inner flowlines **452A-B** are included, the thrust bearing system **500** can also include the second return flowline(s) **456** to transmit the working fluid back to the expeller vanes **442**. The second return flowline(s) **456** exit the bearing chamber **510** distal to the central axis **518** of the shaft **432** via the opening **512**. Although one of the second return flowline(s) **456** is illustrated in FIG. 5, there can be a plurality (e.g., two, four, 12, etc.) of second return flowlines **456** included in the thrust bearing system **500**. Generally, when the inner flowlines **452A-B** are utilized, the thrust bearing system **500** includes at least one of the second return flowline(s) **456** at respective openings **512** disposed on the spacer **508** circumferentially distributed about the central axis **518**.

(87) It should be appreciated that the secondary outer and inner flowlines **450B**, **452B** are included in FIG. 5 merely to illustrate possible configurations of examples disclosed herein and do not contribute to the functionality of the thrust bearing system **500**. Furthermore, as mentioned below,

the secondary inner or outer flowlines **450B**, **452B** are applicable to example dynamic thrust bearing systems illustrated in and described in reference to FIG. 5 but not to those illustrated in and described in reference to FIGS. 6-11.

(88) The example illustration of FIG. 5 includes a primary heat exchanger **514** and a secondary heat exchanger **516** to adjust mass flowrates in the primary and secondary outer flowlines **450A**, **450B**, respectively. In some examples, the primary and secondary heat exchangers **514**, **516** are included to adjust mass flowrates in the primary and secondary inner flowlines **452A**, **452B**. In some examples, only the second heat exchanger **516** is included without the primary heat exchanger **514** to adjust a mass flowrate of fluid to the forward and aft thrust pads **502**, **504**. The primary and secondary heat exchangers **514**, **516** can be heat source heat exchangers that transfer heat from another component of the example aircraft **10** or the thermal management system **200** to the fluid. In some examples, increasing the temperature of the flowing fluid (e.g., sCO₂) also increases the pressure of the fluid, and, in turn, increases the mass flowrate of the fluid. In some examples, the primary and secondary heat exchangers **514**, **516** can be heat sink heat exchanges that transfer heat from the fluid to another component of the example aircraft **10** or the thermal management system **200**.

(89) Although both the outer flowlines **450A-B** and the inner flowlines **452A-B** are illustrated in FIG. 5, the pump **400**, the thrust bearing system **500**, and/or example dynamic thrust bearing systems disclosed herein can function with either the outer flowlines **450A-B** or the inner flowlines **452A-B** without including the other. Both the outer flowlines **450A-B**, and inner flowlines **452A-B** are illustrated in FIG. 5 to show that outer or inner configurations are possible in examples disclosed herein. Although the example dynamic thrust bearing systems described below are illustrated and referenced as being used with the outer flowline **450A**, alternative examples of the dynamic thrust bearing systems can be used with one or more of the inner flowlines **452A-B** or the outer flow lines **450A-B**.

(90) As mentioned above, example thrust bearing systems mentioned in connection with FIGS. 6-11 facilitate (e.g., guide) the working fluid through flowlines **450B**, **452B**. FIG. 6 is a schematic illustration of an example first dynamic thrust bearing system **600** to direct the flow of the working fluid (e.g., sCO₂) to a forward side **602** or an aft side **604** of a thrust disc **606** based on a position of the thrust disc **606** and/or an example sleeve **608**. The example thrust disc **606** is coupled to the shaft **432**. The system **600** includes a forward thrust pad **610** and an aft thrust pad **612** to support axial thrust transferred from the shaft **432** via the thrust disc **606**. The example thrust disc **606** of the first system **600** includes a forward channel **614** and an aft channel **616** that can direct flow of the fluid to the forward side **602** and/or the aft side **604** in response to displacement of the shaft **432** and the thrust disc **606**. The forward channel **614** includes outlets for directing flow to the forward side **602** and the aft channel **616** includes outlets for directing flow to the aft side **604**. The example channels **614**, **616** are axially spaced in the thrust disc **606**.

(91) In the example of FIG. 6, the system **600** includes an example forward opening **618** and an example aft opening **620**. The example forward opening **618** permits fluid to enter a bearing chamber **622**, become pressurized on the forward side **602**, and at least partially bear axial loads of the shaft **432**. Further, the example aft opening **620** permits fluid to enter a bearing chamber **624**, become pressurized on the aft side **604**, and at least partially bear axial loads of the shaft **432**.

(92) The example sleeve **608** includes a forward sleeve portion **626** corresponding to the forward opening **618** and an aft sleeve portion **628** corresponding to the aft opening **620**. The example sleeve **608** includes a central sleeve portion **630** positioned between the forward sleeve portion **626** and the aft sleeve portion **628**. In this example, the sleeve **608** includes example apertures **629**, **631** to permit fluid flow therethrough, the apertures **629**, **631** extending through opposing surfaces of the sleeve **608**.

(93) The example system **600** includes an example spring **632** positioned between the forward sleeve portion **626** and the forward thrust pad **610** and an example spring **634** positioned between

the aft sleeve portion **628** and the aft thrust pad **612**. In FIG. **6**, the forward thrust pad **610** includes a cavity **636** positioned in a surface of the forward thrust pad **610** that faces the thrust disc **606**. Further, the aft thrust pad **612** includes a cavity **638** positioned in a surface of the aft thrust pad **612** that faces the thrust disc **606**. Accordingly, the spring **632** extends from an inner wall of the cavity **636** to the forward sleeve portion **626**. Further, the spring **634** extends from an inner wall of the cavity **638** to the aft sleeve portion **628**. The example springs **632**, **634** can generate spring forces on the sleeve **608** to counteract (e.g., react to) forces generated by the fluid pressure forward of the thrust disc **606**, fluid pressure aft of the thrust disc **606**, and/or axial displacement of the thrust disc **606**. In some examples, the stiffness (e.g., spring force) of the springs **632**, **634** is at least partially based on material(s) (e.g., low-alloy steel, cold formed steel, etc.) and/or a number of coils of the springs **632**, **634**.

(94) The example thrust disc **606** of the system **600** includes branches (e.g., walls, protrusions, sides of the thrust disc **606**, etc.) **640**, **642**, **644** that are positioned on a surface (e.g., a circumferential surface) of the thrust disc **606** and protrude radially outward relative to the central axis **518** of the shaft **432**. In some examples, walls **640**, **642**, **644** extend from a surface of the thrust disc **606** and are defined by the channels **614**, **616** extending through the thrust disc. The branch **640** is facing the forward thrust pad **610**, the branch **644** is facing the aft thrust pad **612**, and the branch **642** is positioned between the branch **640** and the branch **644**. The example branches **640**, **642**, **644** can direct (e.g., guide, obstruct, inhibit, etc.) flow received through the openings **618**, **620** to the forward side **602** or the aft side **604**. In some examples, at least one of the branches **640**, **642**, **644** can direct flow from the openings **618**, **620** through the channels **614**, **616** to the forward side **602** or the aft side **604**. For example, the forward channel **614** is positioned between the branches **640**, **642** to guide flow from the forward opening **618** and the aft channel **616** is positioned between the branches **642**, **644** to guide flow from the aft opening **620**. In some examples, the branches **640**, **642**, **644** are bodies (e.g., structures) added to a surface of the thrust disc **606**. In other examples, the branches **640**, **642**, **644** are walls of the thrust disc **606** defined by the channels **614**, **616**.

(95) The example system **600** includes example magnets **646**, **648**, **650**, **652** that repel (e.g., interact with) each other to balance pressure in the system **600**, maintain positioning of the thrust disc **606** and/or the sleeve **608**, and/or at least partially counteract axial thrust in the system **600**.

(96) For example, the magnets **648**, **650** can be embedded in and/or surrounding the branches **640**, **644** and/or the sides **602**, **604** of the thrust disc **606**. In some examples, the magnets **648**, **650** are shaped (e.g., arc shaped, ring shaped, etc.) to surround (e.g., encircle) the branches **640**, **644**. Further, the magnets **646**, **652** can be embedded in the sleeve **608**. In some examples, the magnets **646**, **652** are positioned adjacent to the thrust pads **610**, **612**.

(97) In the example of FIG. **6**, the north poles of the magnets **650**, **652** are facing each other and the south poles of the magnets **646**, **648** are facing each other. Accordingly, the magnet **648** can repel (e.g., interact with) the magnet **646** embedded in the forward sleeve portion **626**. Additionally, the magnet **650** can repel the magnet **652** embedded in the aft sleeve portion **628**.

(98) In some examples, the system **600** includes the magnets **646**, **648**, **652**. In such examples, the magnet **648** is associated with (e.g., encircles, surrounds, embedded in, etc.) at least one of the branches **640**, **642**, **644**. Further, the magnet **648** can repel at least one of the magnets **646**, **652**.

(99) In some examples, the repelling force of the magnets **646**, **648**, **650**, **652** can cause the thrust disc **606** to move. In some examples, the force interactions between the magnets **646**, **648**, **650**, **652** and the compressible springs **632**, **634** can prevent the thrust disc **606** from contacting the thrust pads **610**, **612**, described in detail below in connection with FIGS. **7-9**.

(100) In some examples, diameters of the magnets **646**, **648**, **650**, **652** can be 0.045 inches (in). In other examples, diameters of the magnets **646**, **648**, **650**, **652**, can be a percentage (e.g., 35%) of a thickness of the thrust disc **606**. Further, the example magnets **646**, **648**, **650**, **652** can include a thickness of 0.045 in, a width of 0.045 in, a circumferential width of 0.5 in, etc. In some examples,

each of the example magnets **646**, **648**, **650**, **652** can withstand a force of 70 pounds (lbs.) (e.g., 300 N, 35 kilo revolutions per minute (KRPM), etc.). Additionally or alternatively, repelling force(s) of the example magnets **646**, **648**, **650**, **652** may be determined based on known thrust variations (e.g., 10-50 lbs. in foil bearings).

(101) FIGS. **7**, **8**, **9A**, and **9B** are schematic views of the first system **600** including a first cross-sectional view **700**, a second cross-sectional view **800**, a third cross-sectional view **900**, and a side view **902**. The first cross-sectional view **700** illustrates a forward displacement of the thrust disc **606** and the sleeve **608** in the bearing chamber **622** due to the forward thrust **448** of the shaft **432**. When the thrust disc **606** is in a central position (shown in FIG. **6**), the branch **642** and/or the central sleeve portion **630** obstructs the fluid such that the fluid diverts to the forward side **602** and the aft side **604** of the thrust disc **606** (e.g., via the forward channel **614** and the aft channel **616**) substantially equally (e.g., within ± 1 kilogram per second (kg/s)). In other words, the openings **618**, **620**, the apertures **629**, **631**, and the channels **614**, **616** are aligned.

(102) As illustrated in FIG. **7**, when the sleeve **608** moves forward in the bearing chamber **622**, the aft sleeve portion **628** obstructs and/or inhibits flow through the aft opening **620**. Example arrows **702** illustrate the flow direction of the fluid when the thrust disc **606** and the sleeve **608** are in the forward position. As the fluid flows through the forward opening **618** into the forward channel **614**, the fluid flows to the forward side **602** of the thrust disc **606**, increases the fluid pressure in the bearing chamber **622** at the forward side **602**, and causes the thrust disc **606** to return to the central position of FIG. **6**. In particular, the fluid can flow aft of the branch **640** (via the channel **614**) and/or forward of the branch **640** (to the forward side **602**).

(103) Additionally or alternatively, when the sleeve **608** moves forward in the bearing chamber **622**, the spring **632** compresses and causes the sleeve **608** to return to the central position of FIG. **6**. In some examples, the spring **632** compresses when fluid flows to the forward side **602** of the thrust disc **606**. In some examples, the spring **634** tenses when the sleeve **608** and/or the thrust disc **606** is in the forward position. Accordingly, the spring **634** can tense and cause the sleeve **608** to return to the central position of FIG. **6**.

(104) Further, when the sleeve **608** and the thrust disc **606** move forward in the bearing chamber **622**, the magnets **646**, **648** move closer to one another. Accordingly, the magnetic repulsion of the magnets **646**, **648** increases as the distance between the magnets **646**, **648** (e.g., between like poles of the magnets **646**, **648**) decreases. Thus, the forward sleeve portion **626** and the thrust disc **606** can push away from each other due to the interaction between the magnetic fields of their respective embedded magnets **646**, **648**. In the example of FIG. **7**, the sleeve **608** and/or the thrust disc **606** can return to the central position of FIG. **6** due to at least one of the increase in fluid pressure at the forward side **602**, the compression of the spring **632**, the tension in the spring **634**, or the magnetic repulsion of the magnets **646**, **648**.

(105) The second cross-sectional view **800** illustrates an aft displacement of the thrust disc **606** and the sleeve **608** in the bearing chamber **624** due to the aft thrust **446** of the shaft **432**. As illustrated in FIG. **8**, when the sleeve **608** moves aft in the bearing chamber **624**, the forward sleeve portion **626** obstructs and/or inhibits flow through the forward opening **618**. Example arrows **802** illustrate the flow direction of the fluid when the thrust disc **606** and/or the sleeve **608** is in the aft position. As the fluid flows into the aft channel **616** (e.g., via the opening **620**), the fluid flows to the aft side **604** of the thrust disc **606**, increases the fluid pressure in the bearing chamber **624** at the aft side **604**, and causes the thrust disc **606** to return to the central position of FIG. **6**. In particular, the fluid can flow forward of the branch **644** (via the channel **616**) and/or aft of the branch **644** (to the aft side **604**).

(106) Additionally or alternatively, when the sleeve **608** moves aft in the bearing chamber **624**, the spring **634** compresses and causes the sleeve **608** to return to the central position of FIG. **6**. In some examples, the spring **634** compresses when fluid flows to the aft side **604** of the thrust disc **606**. In some examples, the spring **632** tenses when the sleeve **608** and/or the thrust disc **606** is in the aft

position. Accordingly, the spring **632** can tense and cause the sleeve **608** to return to the central position of FIG. **6**.

(107) Further, when the sleeve **608** and/or the thrust disc move aft in the bearing chamber **624**, the magnets **650**, **652** move closer to one another. Accordingly, the magnetic repulsion of the magnets **650**, **652** increases as the distance between the magnets **650**, **652** (e.g., between like poles of the magnets **650**, **652**) decreases. Thus, the aft sleeve portion **628** and the thrust disc **606** will push away from each other due to the interaction between the magnetic fields of their respective embedded magnets **650**, **652**. In the example of FIG. **8**, the sleeve **608** and/or the thrust disc **606** can return to the central position of FIG. **6** due to at least one of the increase in fluid pressure at the aft side **604**, the compression of the spring **634**, the tension in the spring **632**, or the magnetic repulsion of the magnets **650**, **652**.

(108) The third cross-sectional view **900** shows a cross-section of a portion of the forward side **602** of the thrust disc **606**. The illustrated example of FIG. **9A** shows the portion of the thrust disc **606** that has been bisected along a reference line **654** of FIG. **6**. As shown in FIG. **9A**, the thrust disc **606** can include multiple forward channels **614** distributed in a circumferential (e.g., arc shaped) pattern on the forward side **602** of the thrust disc **606**. In some examples, another portion of the thrust disc **606** on the aft side **604** can include multiple aft channels **616** distributed in a circumferential pattern in the thrust disc **606**.

(109) The side view **902** shows a side of a portion of the thrust disc **606** from a forward perspective. The illustrated example of FIG. **9B** shows the forward side **602** of the thrust disc **606** having outlets of the channel **614** distributed along the thrust disc **606** (e.g., a longitudinal axis of the thrust disc **606**). In other examples, the aft side **604** of the thrust disc **606** includes outlets of the channel **616** distributed along the thrust disc **606**.

(110) Thus, the system **600** includes the thrust disc **606** with the forward channels **614**, the aft channels **616**, the sleeve **608**, the springs **632**, **634**, the magnets **646**, **648**, **650**, **652**, and the branches **640**, **642**, **644** to be self-stabilizing and to dynamically adjust the position of the thrust disc **606** and the shaft **432** in response to unbalanced forward and aft thrusts.

(111) FIG. **10** is a schematic illustration of an example second dynamic thrust bearing system **1000** including an example thrust disc **1002** including magnets **1004**, **1006**, an example forward thrust pad **1008** including an example magnet **1010**, and an example aft thrust pad **1012** including an example magnet **1014**. The example magnets **1004**, **1006**, **1010**, **1014** can be an example magnet assembly. The example magnet **1010** is embedded in and/or adjacent to a surface of the forward thrust pad **1008**. For example, the magnet **1010** can extend along a surface of the forward thrust pad **1008**. In this example, the magnet **1010** is embedded in a surface of the forward thrust pad **1008** that faces the thrust disc **1002**.

(112) Further, the example magnet **1014** is embedded in and/or adjacent to a surface of the aft thrust pad **1012**. For example, the magnet **1014** can extend along a surface of the aft thrust pad **1012**. In this example, the magnet **1014** is embedded in a surface of the aft thrust pad **1012** that faces the thrust disc **1002**. The example magnets **1004**, **1006** are embedded in and/or adjacent to the thrust disc **1002**. In particular, the magnet **1004** is embedded in a surface of the thrust disc **1002** that faces the forward thrust pad **1008** (e.g., the magnet **1010** embedded in the forward thrust pad **1008**). Additionally, the magnet **1006** is embedded in a surface of the thrust disc **1002** that faces the aft thrust pad **1012** (e.g., the magnet **1014** embedded in the aft thrust pad **1012**).

(113) In some examples, the magnets **1004**, **1006** extend along the surfaces of the thrust disc **1002**. In some examples, the magnets **1004**, **1006**, **1010**, **1014** are substantially parallel (e.g., ± 2 degrees) to the thrust disc **1002**. In this example, like poles of the magnets **1004**, **1010** face each other and like poles of the magnets **1006**, **1014** face each other. Accordingly, the example magnet **1004** can repel the magnet **1010** embedded in the forward thrust pad **1008**. Additionally, the example magnet **1006** can repel the magnet **1014** embedded in the aft thrust pad **1012**. In some examples, the repelling force of the magnets **1004**, **1006**, **1010**, **1014** can cause the thrust disc **1002**

to move. In some examples, the force interactions between the magnets **1004**, **1006**, **1010**, **1014** can prevent the thrust disc **1002** from contacting the thrust pads **1008**, **1012**.

(114) In FIG. **10**, the forward thrust pad **1008** and the aft thrust pad **1012** are spaced at a distance by a spacer **1016** to define a bearing chamber **1018** when the fluid can collect and become pressurized by the rotating thrust disc **1002**. The system **1000** includes an opening **1020** to permit the fluid to enter the bearing chamber **1018**, become pressurized on forward and aft sides of the thrust disc **1002**, bear axial loads of the shaft **432**, and flow out of the bearing chamber **1018**.

(115) In some examples, a forward displacement of the thrust disc **1002** in the bearing chamber **1018** due to the forward thrust **448** of the shaft **432** can cause the thrust disc **1002** to move forward in the bearing chamber **1018**. In such examples, the magnets **1004**, **1010** move closer to one another. Accordingly, the magnetic repulsion of the magnets **1004**, **1010** increases as the distance between the magnets **1004**, **1010** (e.g., between like poles of the magnets **1004**, **1010**) decreases. Thus, the forward thrust pad **1008** and the thrust disc **1002** will push away from each other due to the interaction between the magnetic fields of their respective embedded magnets **1004**, **1010**. In some examples, the thrust disc **1002** can return to a central position (as shown in FIG. **10**) due to the magnetic repulsion of the magnets **1004**, **1010**.

(116) In another example, an aft displacement of the thrust disc **1002** in the bearing chamber **1018** due to the aft thrust **446** of the shaft **432** can cause the thrust disc **1002** to move aft in the bearing chamber **1018**. In such examples, the magnets **1006**, **1014** move closer to one another. Accordingly, the magnetic repulsion of the magnets **1006**, **1014** increases as the distance between the magnets **1006**, **1014** (e.g., between like poles of the magnets **1006**, **1014**) decreases. Thus, the aft thrust pad **1012** and the thrust disc **1002** will push away from each other due to the interaction between the magnetic fields of their respective embedded magnets **1006**, **1014**. In some examples, the thrust disc **1002** can return to a central position (as shown in FIG. **10**) due to the magnetic repulsion of the magnets **1006**, **1014**. Thus, the example system **1100** can dynamically balance fluid pressure on forward and aft sides of the thrust disc **1002** based on at least one of the magnets **1004**, **1006**, **1010**, **1014**.

(117) FIG. **11** is a schematic illustration of an example third dynamic thrust bearing system **1100** including a thrust disc **1102**, magnets **1104**, **1106**, and springs **1108**, **1110**. The example spring **1108** is positioned between the magnet **1106** and a forward thrust pad **1112** and the spring **1110** positioned between the magnet **1106** and an aft thrust pad **1114**. The forward thrust pad **1112** includes a cavity **1116** positioned in a surface of the forward thrust pad **1112**, and the aft thrust pad **1114** includes a cavity **1118** positioned in a surface of the aft thrust pad **1114**. Accordingly, the spring **1108** extends from an inner wall of the cavity **1116** towards the magnet **1106**. In this example, a first end of the magnet **1106** is coupled to the spring **1108**. Further, the spring **1110** extends from an inner wall of the cavity **1118** towards the magnet **1106**. The example spring **1110** is coupled to a second end of the magnet **1106**.

(118) In FIG. **11**, the magnet **1104** is positioned on a surface (e.g., circumferential surface) of the thrust disc **1102**. The example magnet **1104** can interact with (e.g., attract) the magnet **1106** positioned between the springs **1108**, **1110** and the thrust pads **1112**, **1114**. For example, poles **1120**, **1122**, **1124**, **1126** of the magnet **1104** are aligned to poles **1128**, **1130**, **1132**, **1134** of the magnet **1106**. Accordingly, the poles **1120**, **1128** are magnetically attracted to one another, the poles **1122**, **1130** are magnetically attracted to one another, the poles **1124**, **1134** are magnetically attracted to one another, and the poles **1126**, **1132** are magnetically attracted to one another.

(119) In some examples, a forward displacement of the thrust disc **1102** in a bearing chamber **1136** due to the forward thrust **448** of the shaft **432** can cause the thrust disc **1102** to move forward in the bearing chamber **1136**. In such examples, the magnet **1104** may become offset from the magnet **1106**. Accordingly, the magnetic attraction between the magnets **1104**, **1106** (e.g., between at least the poles **1120**, **1128**) can cause at least the magnetic poles **1120**, **1128** to move closer to each other. Thus, the forward thrust pad **1112** and the thrust disc **1102** will push away from each other due to

the attraction between the magnets **1104**, **1106**, and the magnet **1106** can divert more fluid to the forward side of the thrust disc **1102**. In some examples, the thrust disc **1102** can return to a central position (as shown in FIG. **11**) due to the magnetic attraction of the magnets **1104**, **1106**. In some examples, the stiffness in the spring **1108** and/or the spring **1110** can adjust (e.g., track, move, position, etc.) the magnet **1106** and, subsequently, the thrust disc **1102** back to a central position (as shown in FIG. **11**).

(120) In some examples, an aft displacement of the thrust disc **1102** in the bearing chamber **1136** due to the aft thrust **446** of the shaft **432** can cause the thrust disc **1102** to move aft in the bearing chamber **1136**. In such examples, the magnet **1104** may become offset from the magnet **1106**. Accordingly, the magnetic attraction between the magnets **1104**, **1106** (e.g., between at least the poles **1132**, **1126**) can cause at least the magnetic poles **1126**, **1132** to move closer to each other. Thus, the aft thrust pad **1114** and the thrust disc **1102** will push away from each other due to the attraction between the magnetic fields of the magnets **1104**, **1106**, and the magnet **1106** can divert more fluid to the aft side of the thrust disc **1102**. In some examples, the thrust disc **1102** can return to a central position (as shown in FIG. **11**) due to the magnetic attraction of the magnets **1104**, **1106**. Thus, the example system **1100** can dynamically balance fluid pressure on forward and aft sides of the thrust disc **1102** based on at least one of the magnets **1104**, **1106** and/or the springs **1108**, **1110**. In some examples, the magnet **1106** at least partially diverts (e.g., guides) the fluid to forward and aft sides of the thrust disc **1102**, as shown by example arrows **1138**.

(121) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include means for accelerating. For example, the means for accelerating may be implemented by the impeller shaft **432** in FIGS. **4**, **5**, **6**, **10**, and **11**, and/or any other impeller shafts described herein.

(122) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include means for separating (e.g., first means for separating). For example, the means for separating may be implemented by the thrust disc **438** in FIGS. **4** and **5**, the thrust disc **606** in FIGS. **6-9**, the thrust disc **1002** in FIG. **10**, the thrust disc **1102** in FIG. **11**, and/or any other thrust discs described herein.

(123) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include first means for supporting. For example, the first means for supporting may be implemented by the forward thrust pad **502** in FIG. **5**, the forward thrust pad **610** in FIGS. **6-8**, the forward thrust pad **1008** in FIG. **10**, the forward thrust pad **1112** in FIG. **11**, and/or any other forward thrust pads described herein.

(124) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include second means for supporting. For example, the second means for supporting may be implemented by the aft thrust pad **504** in FIG. **5**, the aft thrust pad **612** in FIGS. **6-8**, the aft thrust pad **1012** in FIG. **10**, the aft thrust pad **1114** in FIG. **11**, and/or any other aft thrust pads described herein.

(125) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include first means for coupling. For example, the first means for coupling may be implemented by the magnets **648**, **650** in FIGS. **6-8**, the magnets **1004**, **1006** in FIG. **10**, the magnet **1104** in FIG. **10**, and/or any other magnets described herein.

(126) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include second means for coupling. For example, the second means for coupling may be implemented by the magnet **646** in FIGS. **6-8**, the magnet **1010** in FIG. **10**, the magnet **1106** in FIG. **11**, and/or any other magnets described herein.

(127) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include third means for coupling. For example, the third means for coupling may be implemented by the magnet **652** in FIGS. **6-8**, the magnet **1014** in FIG. **10**, the magnet **1106** in FIG. **11**, and/or any other magnets described herein.

(128) In some examples, the systems **400**, **500**, **600**, **1000**, **1100** include fourth means for coupling. For example, the fourth means for coupling may be implemented by the magnet **650** in FIGS. **6-8**, the magnet **1006** in FIG. **10**, the magnet **1104** in FIG. **10**, and/or any other magnets described herein.

(129) In some examples, the systems **400, 500, 600, 1000, 1100** include second, third, and fourth means for separating. For example, the second means for separating may be implemented by the branch **640** in FIGS. **6-8** and/or any other branch described herein, the third means for separating may be implemented by the branch **642** in FIGS. **6-8** and/or any other branch described herein, the fourth means for separating may be implemented by the branch **644** in FIGS. **6-8** and/or any other branch described herein.

(130) In some examples, the systems **400, 500, 600, 1000, 1100** include means for sealing. For example, the means for sealing may be implemented by the sleeve **608** in FIGS. **6-8**, the forward sleeve portion **626** in FIGS. **6-8**, the aft sleeve portion **628** in FIGS. **6-8**, and/or any other sleeve described herein.

(131) In some examples, the systems **400, 500, 600, 1000, 1100** include first and second means for engaging. For example, the first means for engaging may be implemented by the spring **632** in FIGS. **6-8**, the spring **1108** in FIG. **11**, and/or any other spring described herein. Further, the second means for engaging may be implemented by the spring **634** in FIGS. **6-8**, the spring **1110** in FIG. **11**, and/or any other spring described herein.

(132) Magnetic thrust bearing systems for dynamically supporting shafts in pumps are disclosed herein. As a pump (e.g., a centrifugal pump) operates, an impeller/expeller of the pump experiences forward and aft thrusts which can cause an impeller shaft to axially move forward and aft by an amount (e.g., 0.001 in, 0.005 in, 0.010 in, etc.). Movements of the impeller shaft and/or prolonged rotation of the impeller shaft in displaced positions can cause the impeller shaft and/or parts coupled thereto to interfere with other internal parts (e.g., bearings, housings, motor(s), etc.) of the pump, which can cause damage to the pump and/or the internal parts and can cause energy losses due to friction forces at the interferences. Example magnetic thrust bearing systems disclosed herein reduce damage to the pump through reduced axial movement of the impeller shaft. Example magnetic thrust bearing systems disclosed herein increase the energy efficiency of the pump through dynamic adjustment of the axial position of the impeller shaft in response to axial displacements of the impeller shaft.

(133) Magnetic thrust bearing systems to dynamically support axial thrust in pumps are disclosed herein. Further examples and combinations thereof include the following:

(134) Example 1 includes a thrust bearing system to dynamically support thrust in a pump, the thrust bearing system comprising a thrust disc coupled to an impeller shaft, the thrust disc protruding radially outward from the impeller shaft, the impeller shaft coupled to an impeller, the thrust disc including a first magnet, the first magnet positioned on a surface of the thrust disc, a first thrust pad coupled to a body of the pump, the first thrust pad protruding radially inward toward the impeller shaft, the first thrust pad positioned on a forward side of the thrust disc, the first thrust pad including a second magnet positioned adjacent to a first surface of the first thrust pad, the first surface facing the thrust disc, and a second thrust pad coupled to the body of the pump, the second thrust pad protruding radially inward toward the impeller shaft, the second thrust pad positioned on an aft side of the thrust disc, the second thrust pad including a third magnet positioned adjacent to a second surface of the second thrust pad, the second surface facing the thrust disc.

(135) Example 2 includes the thrust bearing system of any preceding clause, wherein the first magnet and the second magnet repel each other, and the first magnet and the third magnet repel each other.

(136) Example 3 includes the thrust bearing system of any preceding clause, wherein the surface of the thrust disc is a circumferential surface.

(137) Example 4 includes the thrust bearing system of any preceding clause, wherein the first magnet is embedded in the surface of the thrust disc, the first magnet facing the second magnet, the thrust disc further including a fourth magnet embedded in the surface of the thrust disc, the fourth magnet facing the third magnet.

(138) Example 5 includes the thrust bearing system of any preceding clause, wherein the first magnet and the second magnet repel each other, and the fourth magnet and the third magnet repel each other.

(139) Example 6 includes the thrust bearing system of any preceding clause, wherein the thrust disc further includes a first branch, a second branch, and a third branch positioned on the surface of the thrust disc, the first, second, and third branches protruding radially outward from a central axis of the thrust bearing system, the second branch positioned between the first branch and the third branch, the first branch facing the first thrust pad, the third branch facing the second thrust pad, and a fourth magnet surrounding the third branch and the first magnet surrounding the first branch.

(140) Example 7 includes the thrust bearing system of any preceding clause, wherein the fourth magnet and the third magnet repel each other, and the first magnet and the second magnet repel each other.

(141) Example 8 includes the thrust bearing system of any preceding clause, wherein the thrust disc further includes a forward channel and an aft channel, the forward channel extending from the surface of the thrust disc to the forward side of the thrust disc, the aft channel extending from the surface of the thrust disc to the aft side of the thrust disc.

(142) Example 9 includes the thrust bearing system of any preceding clause, wherein an inlet of the forward channel is positioned between the first and second branches, and an inlet of the aft channel is positioned between the second and third branches.

(143) Example 10 includes the thrust bearing system of any preceding clause, further including a sleeve at least partially surrounding the thrust disc, the sleeve positioned between the first and second thrust pads, the second magnet embedded in the sleeve and the third magnet embedded in the sleeve, a first spring positioned between the sleeve and the first thrust pad, and a second spring positioned between the sleeve and the second thrust pad.

(144) Example 11 includes the thrust bearing system of any preceding clause, wherein the first spring extends from the first surface of the first thrust pad to a first portion of the sleeve, and the second spring extends from the second surface of the second thrust pad to a second portion of the sleeve.

(145) Example 12 includes the thrust bearing system of any preceding clause, wherein at least one of the second magnet or the third magnet are coupled to the first spring and the second spring.

(146) Example 13 includes the thrust bearing system of any preceding clause, wherein the sleeve further includes at least one aperture to permit fluid flow therethrough, the aperture extending through opposing surfaces of the sleeve.

(147) Example 14 includes a thrust bearing system to dynamically support axial thrust in a pump, the thrust bearing system comprising a first thrust pad and a second thrust pad, the first thrust pad opposing the second thrust pad, a thrust disc positioned between the first thrust pad and the second thrust pad, and a magnet assembly embedded in the first thrust pad, the second thrust pad, and the thrust disc.

(148) Example 15 includes the thrust bearing system of any preceding clause, wherein the magnet assembly includes a first magnet embedded in a surface of the first thrust pad, the first magnet extending along the surface of the first thrust pad, the surface of the first thrust pad facing the thrust disc, a second magnet embedded in a surface of the second thrust pad, the second magnet extending along the surface of the second thrust pad, the surface of the second thrust pad facing the thrust disc, and a third magnet and a fourth magnet embedded in the thrust disc, the third and fourth magnets positioned on opposing sides of the thrust disc, the third magnet facing the first magnet, the fourth magnet facing the second magnet.

(149) Example 16 includes the thrust bearing system of any preceding clause, wherein the first magnet and the third magnet repel each other, and the second magnet and the fourth magnet repel each other.

(150) Example 17 includes the thrust bearing system of any preceding clause, wherein the first,

second, third, and fourth magnets are substantially parallel to the thrust disc, the thrust disc protruding radially from an impeller shaft of the pump.

(151) Example 18 includes a thrust bearing system to dynamically support thrust in a pump, the thrust bearing system comprising a thrust disc coupled to an impeller shaft, the thrust disc protruding radially outward from the impeller shaft, the impeller shaft coupled to an impeller, the thrust disc including a first magnet, the first magnet positioned on a circumferential surface of the thrust disc, a first thrust pad coupled to a body of the pump, the first thrust pad protruding radially inward toward the impeller shaft, the first thrust pad positioned on a forward side of the thrust disc, the first thrust pad including a first spring extending from a surface of the first thrust pad, the surface of the first thrust pad facing the thrust disc, a second thrust pad coupled to the body of the pump, the second thrust pad protruding radially inward toward the impeller shaft, the second thrust pad positioned on an aft side of the thrust disc, the second thrust pad including a second spring extending from a surface of the second thrust pad, the surface of the second thrust pad facing the thrust disc, and a second magnet positioned between the first thrust pad and the second thrust pad, a first end of the second magnet coupled to the first spring and a second end of the second magnet coupled to the second spring.

(152) Example 19 includes the thrust bearing system of any preceding clause, wherein the first magnet and the second magnet magnetically attract each other.

(153) Example 20 includes the thrust bearing system of any preceding clause, wherein the first thrust pad includes a first cavity in the surface of the first thrust pad and the second thrust pad includes a second cavity in the surface of the second thrust pad, the first spring extending from an inner wall of the first cavity to the second magnet, the second spring extending from an inner wall of the second cavity to the second magnet.

(154) Example 21 includes the thrust bearing system of any preceding clause, further including an opening to allow fluid to flow into the thrust bearing system, the second magnet positioned between the first magnet and the opening.

(155) Example 22 includes the thrust bearing system of any preceding clause, wherein the second magnet at least partially diverts the fluid from the opening to forward and aft sides of the thrust disc.

(156) Example 23 includes an apparatus to dynamically support thrust in a pump, the apparatus comprising means for separating coupled to a means for accelerating, the means for separating protruding radially outward from the means for accelerating, the means for accelerating coupled to an impeller, the means for separating including a first means for coupling, the first means for coupling positioned on a surface of the means for separating, a first means for supporting coupled to a body of the pump, the first means for supporting protruding radially inward toward the means for accelerating, the first means for supporting positioned on a forward side of the means for separating, the first means for supporting including a second means for coupling positioned adjacent to a first surface of the first means for supporting, the first surface facing the means for separating, and a second means for supporting coupled to the body of the pump, the second means for supporting protruding radially inward toward the means for accelerating, the second means for supporting positioned on an aft side of the means for separating, the second means for supporting including a third means for coupling positioned adjacent to a second surface of the second means for supporting, the second surface facing the means for separating.

(157) Example 24 includes the apparatus of any preceding clause, wherein the first means for coupling and the second means for coupling repel each other, and the first means for coupling and the third means for coupling repel each other.

(158) Example 25 includes the apparatus of any preceding clause, wherein the first means for coupling is embedded in the surface of the means for separating, the first means for coupling facing the second means for coupling, the means for separating further including a fourth means for coupling embedded in the surface of the means for separating, the fourth means for coupling facing

the third means for coupling.

(159) Example 26 includes the apparatus of any preceding clause, wherein the first means for coupling and the second means for coupling repel each other, and the fourth means for coupling and the third means for coupling repel each other.

(160) Example 27 includes the apparatus of any preceding clause, wherein the means for separating is a first means for separating, wherein the first means for separating further includes a second means for separating, a third means for separating, and a fourth means for separating positioned on the surface of the first means for separating, the second, third, and fourth means for separating protruding radially outward from a central axis of the apparatus, the third means for separating positioned between the second means for separating and the fourth means for separating, the second means for separating facing the first means for supporting, the fourth means for separating facing the second means for supporting, and a fourth means for coupling surrounding the fourth means for separating and the first means for coupling surrounding the second means for separating.

(161) Example 28 includes the apparatus of any preceding clause, wherein the fourth means for coupling and the third means for coupling repel each other, and the first means for coupling and the second means for coupling repel each other.

(162) Example 29 includes the apparatus of any preceding clause, wherein the first means for separating further includes a forward channel and an aft channel, the forward channel extending from the surface of the means for separating to the forward side of the means for separating, the aft channel extending from the surface of the means for separating to the aft side of the means for separating.

(163) Example 30 includes the apparatus of any preceding clause, wherein an inlet of the forward channel is positioned between the second and third means for separating, and an inlet of the aft channel is positioned between the third and fourth means for separating.

(164) Example 31 includes the apparatus of any preceding clause, further including means for sealing at least partially surrounding the first means for separating, the means for sealing positioned between the first and second means for supporting, the second means for coupling embedded in the means for sealing and the third means for coupling embedded in the means for sealing, a first means for engaging positioned between the means for sealing and the first means for supporting, and a second means for engaging positioned between the means for sealing and the second means for supporting.

(165) Example 32 includes the apparatus of any preceding clause, wherein the first means for engaging extends from the first surface of the first means for supporting to a first portion of the means for sealing, and the second means for engaging extends from the second surface of the second means for supporting to a second portion of the means for sealing.

(166) Example 33 includes the apparatus of any preceding clause, wherein the means for sealing further includes at least one aperture to permit fluid flow therethrough, the aperture extending through opposing surfaces of the means for sealing.

(167) Example 34 includes a thrust bearing system comprising a thrust disc coupled to a shaft, the thrust disc protruding radially outward from the shaft, the thrust disc including at least one first magnet, the at least one first magnet positioned on a surface of the thrust disc, the at least one first magnet including a first pole positioned at a forward side of the thrust disc and a second pole positioned at an aft side of the thrust disc, a first thrust pad positioned on the forward side of the thrust disc, the first thrust pad including a first surface facing the forward side of the thrust disc, the first thrust pad including a second magnet with a third pole, the third pole positioned adjacent to the forward side of the thrust disc, the third pole and the first pole having the same polarity, a second thrust pad positioned on the aft side of the thrust disc, the second thrust pad including a second surface facing the aft side of the thrust disc, the second thrust pad including a third magnet with a fourth pole, the fourth pole positioned adjacent to the aft side of the thrust disc, the fourth pole and the second pole having the same polarity, and a sleeve at least partially surrounding the

thrust disc, the sleeve positioned between the first and second thrust pads, the second magnet embedded in the sleeve and the third magnet embedded in the sleeve.

(168) Example 35 includes the thrust bearing system of any preceding clause, wherein the shaft is an impeller shaft, the impeller shaft coupled to an impeller.

(169) Example 36 includes the thrust bearing system of any preceding clause, wherein the at least one first magnet is embedded in the surface of the thrust disc, the at least one first magnet facing the second magnet, the at least one first magnet includes at least two magnets, a first one of the at least two magnets positioned at the forward side and a second one of the at least two magnets positioned at the aft side, the first one including the first pole and the second one including the second pole.

(170) Example 37 includes the thrust bearing system of any preceding clause, wherein the thrust disc further includes a first wall, a second wall, and a third wall extending from the surface of the thrust disc, the first, second, and third walls protruding radially outward from a central axis of the thrust bearing system, the second wall positioned between the first wall and the third wall, the first wall facing the first thrust pad, the third wall facing the second thrust pad, and a fourth magnet surrounding the third wall and the at least one first magnet surrounding the first wall.

(171) Example 38 includes the thrust bearing system of any preceding clause, wherein the thrust disc further includes a forward channel and an aft channel, the forward channel extending from the surface of the thrust disc to the forward side of the thrust disc, the aft channel extending from the surface of the thrust disc to the aft side of the thrust disc.

(172) Example 39 includes the thrust bearing system of any preceding clause, wherein an inlet of the forward channel is positioned between the first and second walls, and an inlet of the aft channel is positioned between the second and third walls.

(173) Example 40 includes the thrust bearing system of any preceding clause, further including a first spring positioned between the sleeve and the first thrust pad, and a second spring positioned between the sleeve and the second thrust pad.

(174) Example 41 includes the thrust bearing system of any preceding clause, wherein the first spring extends from the first surface of the first thrust pad to a first portion of the sleeve, and the second spring extends from the second surface of the second thrust pad to a second portion of the sleeve.

(175) Example 42 includes the thrust bearing system of any preceding clause, wherein the first and second springs resist axial displacement of the sleeve.

(176) Example 43 includes the thrust bearing system of any preceding clause, wherein the sleeve further includes at least two apertures to permit fluid flow therethrough, the at least two apertures extending through opposing surfaces of the sleeve.

(177) Example 44 includes the thrust bearing system of any preceding clause, wherein fluid flows through a first one of the at least two apertures when the thrust disc moves forward in the system, the forward channel to permit fluid to flow to the forward side of the thrust disc.

(178) Example 45 includes the thrust bearing system of any preceding clause, wherein the at least one first magnet repels the second magnet when the thrust disc moves forward in the system, the at least one first magnet and the second magnet repel to move the thrust disc aft in the system.

(179) Example 46 includes the thrust bearing system of any preceding clause, wherein a portion of the sleeve blocks fluid flow through the aft channel.

(180) Example 47 includes the thrust bearing system of any preceding clause, wherein fluid flows through a second one of the at least two apertures when the thrust disc moves aft in the system, the aft channel to permit fluid flow to the aft side of the thrust disc.

(181) Example 48 includes the thrust bearing system of any preceding clause, wherein the fourth magnet repels the third magnet when the thrust disc moves aft in the system, the fourth and third magnets repel to move the thrust disc forward in the system.

(182) Example 49 includes a thrust bearing system to dynamically support axial thrust in a pump,

the thrust bearing system comprising a first thrust pad and a second thrust pad, the first thrust pad opposing the second thrust pad, a thrust disc positioned between the first thrust pad and the second thrust pad, a first magnet embedded in a surface of the first thrust pad, the first magnet extending along the surface of the first thrust pad, the surface of the first thrust pad facing the thrust disc, a second magnet embedded in a surface of the second thrust pad, the second magnet extending along the surface of the second thrust pad, the surface of the second thrust pad facing the thrust disc, and a third magnet and a fourth magnet embedded in the thrust disc, the third and fourth magnets positioned on opposing sides of the thrust disc, the third magnet facing the first magnet, the fourth magnet facing the second magnet.

(183) Example 50 includes the thrust bearing system of any preceding clause, wherein the first, second, third, and fourth magnets are substantially parallel to the thrust disc, the thrust disc protruding radially from an impeller shaft of a pump.

(184) Example 51 includes the thrust bearing system of any preceding clause, wherein the first magnet and the third magnet repel to move the thrust disc aft in the system.

(185) Example 52 includes the thrust bearing system of any preceding clause, wherein the second magnet and the fourth magnet repel to move the thrust disc forward in the system.

(186) Example 53 includes a method comprising in response to axial movement of a thrust disc in a thrust bearing system, aligning a first aperture of a sleeve and at least one channel of the thrust disc, the at least one channel permitting fluid flow to a side of the thrust disc, the sleeve positioned between thrust pads of the thrust bearing system, at least a portion of the sleeve blocking fluid flow through a second channel of the thrust disc, moving the thrust disc in a direction opposite of the axial movement via first and second magnets, the first magnet positioned on the thrust disc, the second magnet positioned on the sleeve, the first magnet and the second magnet having the same polarity, and aligning the thrust disc to a center position via first and second springs, the first spring positioned between the sleeve and a first one of the thrust pads and the second spring positioned between the sleeve and a second one of the thrust pads, the aligned thrust disc to permit fluid flow through the first aperture and a second aperture of the sleeve.

(187) The following claims are hereby incorporated into this Detailed Description by this reference. Although certain example systems, methods, apparatus, and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, methods, apparatus, and articles of manufacture fairly falling within the scope of the claims of this patent.

Claims

1. A thrust bearing system comprising: a thrust disc coupled to a shaft, the thrust disc protruding radially outward from the shaft, the thrust disc including at least one first magnet, the at least one first magnet positioned on a surface of the thrust disc, the at least one first magnet including a first pole positioned at a forward side of the thrust disc and a second pole positioned at an aft side of the thrust disc; a first thrust pad positioned on the forward side of the thrust disc, the first thrust pad including a first surface facing the forward side of the thrust disc, the first thrust pad including a second magnet with a third pole, the third pole positioned adjacent to the forward side of the thrust disc, the third pole and the first pole having the same polarity; a second thrust pad positioned on the aft side of the thrust disc, the second thrust pad including a second surface facing the aft side of the thrust disc, the second thrust pad including a third magnet with a fourth pole, the fourth pole positioned adjacent to the aft side of the thrust disc, the fourth pole and the second pole having the same polarity; and a sleeve at least partially surrounding the thrust disc, the sleeve positioned between the first and second thrust pads, the second magnet embedded in the sleeve and the third magnet embedded in the sleeve, wherein the thrust disc includes a first wall, a second wall, and a third wall extending from the surface of the thrust disc, the first, second, and third walls protruding

radially outward from a central axis of the thrust bearing system, the second wall positioned between the first wall and the third wall, the first wall facing the first thrust pad, the third wall facing the second thrust pad; and a fourth magnet surrounding the third wall and the at least one first magnet surrounding the first wall.

2. The thrust bearing system of claim 1, wherein the shaft is an impeller shaft, the impeller shaft coupled to an impeller.

3. The thrust bearing system of claim 1, wherein the first magnet is embedded in the surface of the thrust disc, the first magnet facing the second magnet, the thrust disc further including: a fourth magnet embedded in the surface of the thrust disc, the fourth magnet facing the third magnet, the fourth magnet including a fifth pole, the fifth pole and the fourth pole having the same polarity.

4. The thrust bearing system of claim 1, wherein the thrust disc further includes a forward channel and an aft channel, the forward channel extending from the surface of the thrust disc to the forward side of the thrust disc, the aft channel extending from the surface of the thrust disc to the aft side of the thrust disc.

5. The thrust bearing system of claim 4, wherein an inlet of the forward channel is positioned between the first and second walls, and an inlet of the aft channel is positioned between the second and third walls.

6. The thrust bearing system of claim 5, further including: a first spring positioned between the sleeve and the first thrust pad; and a second spring positioned between the sleeve and the second thrust pad.

7. The thrust bearing system of claim 6, wherein the first spring extends from the first surface of the first thrust pad to a first portion of the sleeve, and the second spring extends from the second surface of the second thrust pad to a second portion of the sleeve.

8. The thrust bearing system of claim 6, wherein the first and second springs resist axial displacement of the sleeve.

9. The thrust bearing system of claim 6, wherein the sleeve further includes at least two apertures to permit fluid flow therethrough, the at least two apertures extending through opposing surfaces of the sleeve.

10. The thrust bearing system of claim 9, wherein fluid flows through a first one of the at least two apertures when the thrust disc moves forward in the system, the forward channel to permit fluid to flow to the forward side of the thrust disc.

11. The thrust bearing system of claim 10, wherein the first magnet repels the second magnet when the thrust disc moves forward in the system, the first and second magnets repel to move the thrust disc aft in the system.

12. The thrust bearing system of claim 10, wherein a portion of the sleeve blocks fluid flow through the aft channel.

13. The thrust bearing system of claim 9, wherein fluid flows through a second one of the at least two apertures when the thrust disc moves aft in the system, the aft channel to permit fluid flow to the aft side of the thrust disc.

14. The thrust bearing system of claim 13, wherein the fourth magnet repels the third magnet when the thrust disc moves aft in the system, the fourth and third magnets repel to move the thrust disc forward in the system.

15. A thrust bearing system comprising: a first thrust pad and a second thrust pad, the first thrust pad opposing the second thrust pad; a thrust disc positioned between the first thrust pad and the second thrust pad, the thrust disc including at least one first magnet, the at least one first magnet positioned on a surface of the thrust disc, wherein the thrust disc includes: a first wall, a second wall, and a third wall extending from a surface of the thrust disc, the first wall, the second wall, and the third wall protruding radially outward from a central axis of the thrust bearing system, the second wall positioned between the first wall and the third wall, the first wall facing the first thrust pad, the third wall facing the second thrust pad; wherein the at least one first magnet is embedded

in a surface of the first thrust pad, the first magnet extending along the surface of the first thrust pad, the surface of the first thrust pad facing the thrust disc; a second magnet embedded in a surface of the second thrust pad, the second magnet extending along the surface of the second thrust pad, the surface of the second thrust pad facing the thrust disc; a third magnet and a fourth magnet embedded in the thrust disc, the third and fourth magnets positioned on opposing sides of the thrust disc, the third magnet facing the first magnet, the fourth magnet facing the second magnet; and a fourth magnet surrounding the third wall and the at least one first magnet surrounding the first wall.

16. The thrust bearing system of claim 15, wherein the first, second, third, and fourth magnets are substantially parallel to the thrust disc, the thrust disc protruding radially from an impeller shaft of a pump.

17. The thrust bearing system of claim 15, wherein the first magnet and the third magnet repel to move the thrust disc aft in the system.

18. The thrust bearing system of claim 15, wherein the second magnet and the fourth magnet repel to move the thrust disc forward in the system.

19. A method comprising: in response to axial movement of a thrust disc in a thrust bearing system, aligning a first aperture of a sleeve and at least one channel of the thrust disc, the at least one channel permitting fluid flow to a side of the thrust disc, the sleeve positioned between thrust pads of the thrust bearing system, at least a portion of the sleeve blocking fluid flow through a second channel of the thrust disc; moving the thrust disc in a direction opposite of the axial movement via first and second magnets, the first magnet positioned on the thrust disc, the second magnet positioned on the sleeve, the first magnet and the second magnet having the same polarity; and aligning the thrust disc to a center position via first and second springs, the first spring positioned between the sleeve and a first one of the thrust pads and the second spring positioned between the sleeve and a second one of the thrust pads, the aligned thrust disc to permit fluid flow through the first aperture and a second aperture of the sleeve.
