

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385449
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kupratis; Daniel Bernard et al.

Splitter and guide vane arrangement for gas turbine engines

Abstract

A section for a gas turbine engine according to an example of the present disclosure includes, among other things, a rotor including a row of blades extending in a radial direction outwardly from a hub. The row of blades deliver flow to a bypass flow path, an intermediate flow path, and a core flow path. A first case surrounds the row of blades to establish the bypass flow path. A first flow splitter divides flow between the bypass flow path and a second duct. An aftmost row of guide vanes extends in the radial direction across the bypass flow path. A second flow splitter radially inboard of the first flow splitter divides flow from the second duct between the intermediate flow path and the core flow path. A bypass port interconnects the intermediate and bypass flow paths.

Inventors: Kupratis; Daniel Bernard (Wallingford, CT), Hanrahan; Paul R. (Farmington, CT)

Applicant: RTX CORPORATION (Farmington, CT)

Family ID: 1000008749590

Assignee: RTX CORPORATION (Farmington, CT)

Appl. No.: 18/461709

Filed: September 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230407817 A1	Dec. 21, 2023

Related U.S. Application Data

continuation parent-doc US 16891492 20200603 US 11781506 child-doc US 18461709

Publication Classification

Int. Cl.: **F02K3/077** (20060101); **F01D5/14** (20060101); **F02K1/72** (20060101); **F02K3/06** (20060101); **F02K3/075** (20060101); **F04D29/54** (20060101); **F04D29/66** (20060101)

U.S. Cl.:

CPC **F02K3/077** (20130101); **F02K3/075** (20130101); F01D5/145 (20130101); F02K1/72 (20130101); F02K3/06 (20130101); F04D29/542 (20130101); F04D29/661 (20130101)

Field of Classification Search

CPC: F02C (7/18-185); F02C (7/052); F02C (6/08); F02C (9/18); F02C (7/04-057); F02K (1/72); F02K (1/68); F02K (1/54-766); F02K (3/077); F02K (3/075); F02K (3/115); F02K (3/04-06); F02K (3/068); F02K (3/045); F02K (3/044); F02K (3/00-77); F05D (2240/12-125); F05D (2260/231); F05D (2270/101-1024); F01D (5/146); F01D (9/00-048); F04D (29/464); F04D (29/542-545); F04D (29/681)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2258792	12/1940	New	N/A	N/A
2936655	12/1959	Peterson et al.	N/A	N/A
3021731	12/1961	Stoeckicht	N/A	N/A
3194487	12/1964	Tyler et al.	N/A	N/A
3287906	12/1965	McCormick	N/A	N/A
3352178	12/1966	Lindgren et al.	N/A	N/A
3412560	12/1967	Gaubatz	N/A	N/A
3664612	12/1971	Skidmore et al.	N/A	N/A
3747343	12/1972	Rosen	N/A	N/A
3754484	12/1972	Roberts	N/A	N/A
3765623	12/1972	Donelson et al.	N/A	N/A
3820719	12/1973	Clark et al.	N/A	N/A
3843277	12/1973	Ehrich	N/A	N/A
3892358	12/1974	Gisslen	N/A	N/A
3932058	12/1975	Harner et al.	N/A	N/A
3935558	12/1975	Miller et al.	N/A	N/A
3988889	12/1975	Chamay et al.	N/A	N/A
4055042	12/1976	Colley	415/77	F02K 3/06
4080785	12/1977	Koff et al.	N/A	N/A
4130872	12/1977	Haloff	N/A	N/A
4220171	12/1979	Ruehr et al.	N/A	N/A
4240250	12/1979	Harris	N/A	N/A
4284174	12/1980	Salvana et al.	N/A	N/A
4289360	12/1980	Zirin	N/A	N/A
4478551	12/1983	Honeycutt, Jr. et al.	N/A	N/A
4559784	12/1984	Jenny et al.	N/A	N/A
4649114	12/1986	Miltenburger et al.	N/A	N/A

4696156	12/1986	Burr et al.	N/A	N/A
4722357	12/1987	Wynosky	N/A	N/A
4896499	12/1989	Rice	N/A	N/A
4916894	12/1989	Adamson et al.	N/A	N/A
4979362	12/1989	Vershure, Jr.	N/A	N/A
5003773	12/1990	Beckwith	N/A	N/A
5058379	12/1990	Lardellier	N/A	N/A
5058617	12/1990	Stockman et al.	N/A	N/A
5102379	12/1991	Pagluica et al.	N/A	N/A
5141400	12/1991	Murphy et al.	N/A	N/A
5169288	12/1991	Gliebe et al.	N/A	N/A
5174525	12/1991	Schilling	N/A	N/A
5261227	12/1992	Giffin, III	N/A	N/A
5317877	12/1993	Stuart	N/A	N/A
5361580	12/1993	Ciokajlo et al.	N/A	N/A
5433674	12/1994	Sheridan et al.	N/A	N/A
5447411	12/1994	Curley et al.	N/A	N/A
5466198	12/1994	McKibbin et al.	N/A	N/A
5524847	12/1995	Brodell et al.	N/A	N/A
5634767	12/1996	Dawson	N/A	N/A
5677060	12/1996	Terentieva et al.	N/A	N/A
5694768	12/1996	Johnson et al.	N/A	N/A
5746391	12/1997	Rodgers et al.	N/A	N/A
5778659	12/1997	Duesler et al.	N/A	N/A
5794432	12/1997	Dunbar et al.	N/A	N/A
5857836	12/1998	Stickler et al.	N/A	N/A
5915917	12/1998	Eveker et al.	N/A	N/A
5975841	12/1998	Lindemuth et al.	N/A	N/A
5985470	12/1998	Spitsberg et al.	N/A	N/A
6134880	12/1999	Yoshinaka	N/A	N/A
6223616	12/2000	Sheridan	N/A	N/A
6315815	12/2000	Spadaccini et al.	N/A	N/A
6318070	12/2000	Rey et al.	N/A	N/A
6387456	12/2001	Eaton, Jr. et al.	N/A	N/A
6517341	12/2002	Brun et al.	N/A	N/A
6607165	12/2002	Manteiga et al.	N/A	N/A
6619030	12/2002	Seda et al.	N/A	N/A
6709492	12/2003	Spadaccini et al.	N/A	N/A
6732502	12/2003	Seda et al.	N/A	N/A
6814541	12/2003	Evans et al.	N/A	N/A
6883303	12/2004	Seda	N/A	N/A
7021042	12/2005	Law	N/A	N/A
7195456	12/2006	Aggarwala et al.	N/A	N/A
7219490	12/2006	Dev	N/A	N/A
7328580	12/2007	Lee et al.	N/A	N/A
7374403	12/2007	Decker et al.	N/A	N/A
7437877	12/2007	Kawamoto et al.	N/A	N/A
7484356	12/2008	Lair	N/A	N/A
7591754	12/2008	Duong et al.	N/A	N/A
7632064	12/2008	Somanath et al.	N/A	N/A

7662059	12/2009	McCune	N/A	N/A
7762086	12/2009	Schwark	N/A	N/A
7785066	12/2009	Bil et al.	N/A	N/A
7806651	12/2009	Kennepohl et al.	N/A	N/A
7824305	12/2009	Duong et al.	N/A	N/A
7828682	12/2009	Smook	N/A	N/A
7926260	12/2010	Sheridan et al.	N/A	N/A
7955046	12/2010	McCune et al.	N/A	N/A
7997868	12/2010	Liang	N/A	N/A
8075261	12/2010	Merry et al.	N/A	N/A
8128021	12/2011	Suciu et al.	N/A	N/A
8205432	12/2011	Sheridan	N/A	N/A
8277174	12/2011	Hasel et al.	N/A	N/A
9121412	12/2014	Gallagher et al.	N/A	N/A
9140188	12/2014	Kupratis	N/A	N/A
9623976	12/2016	James	N/A	B64D 33/04
9964037	12/2017	Snyder et al.	N/A	N/A
10030606	12/2017	Moon	N/A	F02K 1/46
10161316	12/2017	Kupratis et al.	N/A	N/A
10184426	12/2018	Schrell	N/A	N/A
10364750	12/2018	Rambo	N/A	F02K 3/115
10670040	12/2019	Nolcheff et al.	N/A	N/A
10774788	12/2019	Feulner	N/A	F02C 3/045
10927761	12/2020	Rambo	N/A	N/A
11448131	12/2021	Rambo	N/A	F02K 3/075
11994089	12/2023	Sidelkovskiy	N/A	F04D 29/323
2001/0035004	12/2000	Balzer	N/A	N/A
2002/0069637	12/2001	Becquerelle et al.	N/A	N/A
2006/0228206	12/2005	Decker et al.	N/A	N/A
2007/0245739	12/2006	Stretton et al.	N/A	N/A
2008/0003096	12/2007	Kohli et al.	N/A	N/A
2008/0092548	12/2007	Morford et al.	N/A	N/A
2008/0116009	12/2007	Sheridan et al.	N/A	N/A
2008/0149445	12/2007	Kern et al.	N/A	N/A
2008/0190095	12/2007	Baran	N/A	N/A
2008/0219849	12/2007	Decker et al.	N/A	N/A
2008/0224018	12/2007	Lafont et al.	N/A	N/A
2008/0317588	12/2007	Grabowski et al.	N/A	N/A
2009/0056343	12/2008	Suciu et al.	N/A	N/A
2009/0081035	12/2008	Merry et al.	N/A	N/A
2009/0293445	12/2008	Ress, Jr.	N/A	N/A
2009/0304518	12/2008	Kodama et al.	N/A	N/A
2009/0314881	12/2008	Suciu et al.	N/A	N/A
2010/0105516	12/2009	Sheridan et al.	N/A	N/A
2010/0146933	12/2009	Caruel	N/A	N/A
2010/0148396	12/2009	Xie et al.	N/A	N/A
2010/0212281	12/2009	Sheridan	N/A	N/A
2010/0218483	12/2009	Smith	N/A	N/A
2010/0219779	12/2009	Bradbrook	N/A	N/A
2010/0331139	12/2009	McCune	N/A	N/A

2011/0056208	12/2010	Norris et al.	N/A	N/A
2011/0159797	12/2010	Beltman et al.	N/A	N/A
2011/0293423	12/2010	Bunker et al.	N/A	N/A
2012/0099963	12/2011	Suciu et al.	N/A	N/A
2012/0124964	12/2011	Hasel et al.	N/A	N/A
2012/0247571	12/2011	Vauchel et al.	N/A	N/A
2012/0291449	12/2011	Adams et al.	N/A	N/A
2013/0008144	12/2012	Gallagher et al.	N/A	N/A
2013/0008170	12/2012	Gallagher et al.	N/A	N/A
2013/0149112	12/2012	Kohlenberg et al.	N/A	N/A
2013/0149113	12/2012	Kohlenberg et al.	N/A	N/A
2013/0192196	12/2012	Suciu et al.	N/A	N/A
2013/0192200	12/2012	Kupratis et al.	N/A	N/A
2013/0202415	12/2012	Karl et al.	N/A	N/A
2013/0216364	12/2012	Evans	N/A	N/A
2014/0157754	12/2013	Hasel et al.	N/A	N/A
2014/0165534	12/2013	Hasel et al.	N/A	N/A
2014/0271163	12/2013	Hue et al.	N/A	N/A
2014/0318149	12/2013	Guillon et al.	N/A	N/A
2014/0363276	12/2013	Vetters et al.	N/A	N/A
2015/0233250	12/2014	Gallagher et al.	N/A	N/A
2016/0040605	12/2015	Howarth	N/A	N/A
2016/0069275	12/2015	Lecordix et al.	N/A	N/A
2016/0131084	12/2015	Kupratis et al.	N/A	N/A
2016/0298550	12/2015	Kupratis	N/A	F02C 9/18
2017/0089299	12/2016	Kupratis	N/A	F02C 3/145
2017/0096945	12/2016	Mueller et al.	N/A	N/A
2017/0191500	12/2016	Lobocki et al.	N/A	N/A
2017/0314471	12/2016	Sennoun	N/A	N/A
2017/0314562	12/2016	Rose	N/A	N/A
2018/0030926	12/2017	Eckett et al.	N/A	N/A
2019/0017446	12/2018	Adams et al.	N/A	N/A
2019/0048826	12/2018	Pointon et al.	N/A	N/A
2019/0063370	12/2018	Phelps et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0791383	12/1996	EP	N/A
1142850	12/2000	EP	N/A
1340903	12/2002	EP	N/A
1712738	12/2005	EP	N/A
1976758	12/2009	EP	N/A
2374995	12/2010	EP	N/A
2383434	12/2010	EP	N/A
2428644	12/2011	EP	N/A
2480779	12/2011	EP	N/A
2610460	12/2012	EP	N/A
3070266	12/2015	EP	N/A
3489461	12/2018	EP	N/A
2991670	12/2013	FR	N/A

3002785	12/2013	FR	N/A
1516041	12/1977	GB	N/A
2041090	12/1979	GB	N/A
2165892	12/1985	GB	N/A
2426792	12/2005	GB	N/A
2007038674	12/2006	WO	N/A
2009148655	12/2008	WO	N/A
2010042215	12/2009	WO	N/A
2013064762	12/2012	WO	N/A
2013186475	12/2012	WO	N/A
2014091110	12/2013	WO	N/A
2014147343	12/2013	WO	N/A
2014176427	12/2013	WO	N/A
2015006005	12/2014	WO	N/A

OTHER PUBLICATIONS

McCune, M.E. (1993). Initial test results of 40,000 horsepower fan drive gear system for advanced ducted propulsion systems. AIAA 29th Joint Conference and Exhibit. Jun. 28-30, 1993. pp. 1-10. cited by applicant

McMillian, A. (2008) Material development for fan blade containment casing. Abstract. p. 1. Conference on Engineering and Physics: Synergy for Success 2006. Journal of Physics: Conference Series vol. 105. London, UK. Oct. 5, 2006. cited by applicant

Meier N. (2005) Civil Turbojet/Turbofan Specifications. Retrieved from <http://jet-engine.net/civtfspec.html>. cited by applicant

Merriam-Webster's collegiate dictionary, 10th Ed. (2001). p. 1125-1126. cited by applicant

Merriam-Webster's collegiate dictionary, 11th Ed. (2009). p. 824. cited by applicant

Meyer, A.G. (1988). Transmission development of TEXTRON Lycoming's geared fan engine. Technical Paper. Oct. 1988. pp. 1-12. cited by applicant

Middleton, P. (1971). 614: VFW's jet feederliner. Flight International, Nov. 4, 1971. p. 725, 729-732. cited by applicant

Misel, O.W. (1977). QCSEE main reduction gears test program. NASA CR-134669. Mar. 1, 1977. pp. 1-222. cited by applicant

Moxon, J. How to save fuel in tomorrow's engines. Flight International. Jul. 30, 1983. 3873(124). pp. 272-273. cited by applicant

Muhlstein, C.L., Stach, E.A., and Ritchie, R.O. (2002). A reaction-layer mechanism for the delayed failure of micron-scale polycrystalline silicon structural films subjected to high-cycle fatigue loading. Acta Materialia vol. 50. 2002. pp. 3579-3595. cited by applicant

Munt, R. (1981). Aircraft technology assessment: Progress in low emissions engine. Technical Report. May 1981. pp. 1-171. cited by applicant

Nanacor Technical Data for Epoxy Nanocomposites using Nanomer 1.30E Nanoclay. Nnacor, Inc. Oct. 2004. cited by applicant

NASA Conference Publication. (1978). CTOL transport technology. NASA-CP-2036-PT-1. Jun. 1, 1978. pp. 1-531. cited by applicant

NASA Conference Publication. Quiet, powered-lift propulsion. Cleveland, Ohio. Nov. 14-15, 1978. pp. 1-420. cited by applicant

Neitzel, R., Lee, R., and Chamay, A.J. (1973). Engine and installation preliminary design. Jun. 1, 1973. pp. 1-333. cited by applicant

Neitzel, R.E., Hirschcron, R. and Johnston, R.P. (1976). Study of unconventional aircraft engines designed for low energy consumption. NASA-CR-135136. Dec. 1, 1976. pp. 1-153. cited by applicant

Newton, F.C., Liebeck, R.H., Mitchell, G.H., Mooiweer, M.A., Platte, M.M., Toogood, T.L., and Wright, R.A. (1986). Multiple Application Propfan Study (MAPS): Advanced tactical transport. NASA CR-175003. Mar. 1, 1986. pp. 1-101. cited by applicant

Nexcelle Press Release. Nexcelle highlights its key role for CFM International's LEAP-1C integrated propulsion system on the COMAC C919. Retrieved Dec. 17, 2014, from <http://www.nexcelle.com/news-press-release/2008-2014/11-10-2014.asp>. cited by applicant

Norris, G. (2009). Aeronautics/propulsion laureate; Pratt Whitney's geared turbofan development team. Aviation Week Space Technology. Mar. 16, 2016. Republished in Pratt & Whitney Digital Press Kit. p. 10. cited by applicant

Norton, M. and Karczub, D. (2003). Fundamentals of noise and vibration analysis for engineers. Press Syndicate of the University of Cambridge. New York: New York. p. 524. cited by applicant

Notice of Opposition of European Patent No. 3239459 mailed Oct. 2, 2019 by Safran Aircraft Engines. cited by applicant

Oates, G.C. (Ed). (1989). Aircraft propulsion systems and technology and design. Washington, D.C.: American Institute of Aeronautics, Inc. pp. 341-344. cited by applicant

Parametric study of STOL short-haul transport engine cycles and operational techniques to minimize community noise impact. NASA-CR-114759. Jun. 1, 1974. pp. 1-397. cited by applicant

Parker, R.G. and Lin, J. (2001). Modeling, modal properties, and mesh stiffness variation instabilities of planetary gears. Prepared for NASA. NASA/CR-2001-210939. May 2001. pp. 1-111. cited by applicant

Patent Owner's Response in U.S. Pat. No. 9, 121,412, *General Electric Company*, Petition, V. *United Technologies Corporation*, Patent Owner: IPR2016-00952 filed Jan. 27, 2017, pp. 1-75. cited by applicant

Patentee's Request to Notice of Opposition to U.S. Pat. No. 2,776,677B, United Technologies Corporation opposed by SNECMA dated Sep. 12, 2016. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 9,121,412. *General Electric Company*, Petitioner, v. *United Technologies Corporation*, Patent Owner. IPR2017-00431. Filed Apr. 25, 2016. cited by applicant

Petition for Inter Parties Review of U.S. Pat. No. 8,277,174, *General Electric Company*, Petitioner v, *United Technologies Corporation*, Patent Owner: IPR2017-00999, filed Mar. 1, 2017, 71 pages. cited by applicant

Petition for Inter Parties Review of U.S. Pat. No. 8,337,149, *General Electric Company*, Petitioner v, *United Technologies Corporation*, Patent Owner: IPR2016-00855, filed Apr. 8, 2016, 72 pages. cited by applicant

Petrovic, J.J., Castro, R.G., Vaidya, R.U., Peters, M.I., Mendoza, D., Hoover, R.C., and Gallegos, D.E. (2001). Molybdenum disilicide materials for glass melting sensor sheaths. Ceramic Engineering and Science Proceedings. vol. 22(3). 2001. pp. 59-64. cited by applicant

Pratt & Whitney (2014). Evaluation of ARA catalytic hydrothermolysis (CH) fuel: Continuous lower energy, emissions and noise (CLEEN) program. FR-27652-2 Rev. 1. Apr. 30, 2014. pp. 1-17. cited by applicant

Press release. The GE90 engine. Retrieved from: <https://www.geaviation.com/commercial/engines/ge90-engine>; <https://www.geaviation.com/press-release/ge90-engine-family/ge90-115b-fan-completing-blade-testing-schedule-first-engine-test>; and <https://www.geaviation.com/press-release/ge90-engine-family/ge'scomposite-fan-blade-revolution-turns-20-years-old>. cited by applicant

Product Brochure. Garrett TFE731. Allied Signal. Copyright 1987. pp. 1-24. cited by applicant

Pyrograf-III Carbon Nanofiber. Product guide. Retrieved Dec. 1, 2015 from: http://pyrografproducts.com/Merchant5/merchant.mvc?Screen=cp_nanofiber. cited by applicant

QCSEE ball spline pitch-change mechanism whirligig test report. (1978). NASA-CR-135354. Sep. 1, 1978. pp. 1-57. cited by applicant

QCSEE hamilton standard cam/harmonic drive variable pitch fan actuation system derail design report. (1976). NASA-CR-134852. Mar. 1, 1976. pp. 1-172. cited by applicant

QCSEE main reduction gears bearing development program final report. (1975). NASA-CR-134890. Dec. 1, 1975. pp. 1-41. cited by applicant

QCSEE over-the-wing final design report. (1977). NASA-CR-134848. Jun. 1, 1977. pp. 1-460. cited by applicant

QCSEE over-the-wing propulsion system test report vol. III—mechanical performance. (1978). NASA-CR-135325. Feb. 1, 1978. pp. 1-112. cited by applicant

QCSEE Preliminary analyses and design report. vol. 1. (1974). NASA-CR-134838. Oct. 1, 1974. pp. 1-337. cited by applicant

QCSEE preliminary analyses and design report. vol. II. (1974). NASA-CR-134839. Oct. 1, 1974. pp. 340-630. cited by applicant

QCSEE the aerodynamic and mechanical design of the QCSEE under-the-wing fan. (1977). NASA-CR-135009. Mar. 1, 1977. pp. 1-137. cited by applicant

QCSEE the aerodynamic and preliminary mechanical design of the QCSEE OTW fan. (1975). NASA-CR-134841. Feb. 1, 1975. pp. 1-74. cited by applicant

QCSEE under-the-wing engine composite fan blade design. (1975). NASA-CR-134840. May 1, 1975. pp. 1-51. cited by applicant

QCSEE under-the-wing engine composite fan blade final design test report. (1977). NASA-CR-135046. Feb. 1, 1977. pp. 1-55. cited by applicant

QCSEE under-the-wing engine composite fan blade preliminary design test report. (1975). NASA-CR-134846. Sep. 1, 1975. pp. 1-56. cited by applicant

QCSEE under-the-wing engine digital control system design report. (1978). NASA-CR-134920. Jan. 1, 1978. pp. 1-309. cited by applicant

Quiet clean general aviation turbofan (QCGAT) technology study final report vol. I. (1975). NASA-CR-164222. Dec. 1, 1975. pp. 1-186. cited by applicant

Ramsden, J.M. (Ed). (1978). The new European airliner. Flight International, 113(3590). Jan. 7, 1978. pp. 39-43. cited by applicant

Ratna, D. (2009). Handbook of thermoset resins. Shawbury, UK: iSmithers. pp. 187-216. cited by applicant

Rauch, D. (1972). Design study of an air pump and integral lift engine ALF-504 using the Lycoming 502 core. Prepare for NASA. Jul. 1972. pp. 1-182. cited by applicant

Read, B. (2014). Powerplant revolution. AeroSpace. May 2014. pp. 28-31. cited by applicant

Reshotko, M., Karchmer, A., Penko, P.F. and McArdle, J.G. (1977). Core noise measurements on a YF-102 turbofan engine. NASA TM X-73587. Prepared for Aerospace Sciences Meeting sponsored by the American Institute of Aeronautics and Astronautics. Jan. 24-26, 1977. cited by applicant

Response to the Summons of Oral Proceedings for European Patent No. EP2949882 by Rolls-Royce, dated Oct. 9, 2019. cited by applicant

Response to the Summons of Oral Proceedings for European Patent No. EP2949882 by Safran, dated Oct. 9, 2019. cited by applicant

Response to the Summons of Oral Proceedings for European Patent No. EP3051078 by Rolls-Royce, dated Oct. 17, 2019. cited by applicant

Reynolds, C.N. (1985). Advanced prop-fan engine technology (APET) single- and counter-rotation gearbox/pitch change mechanism. Prepared for NASA. NASA CR-168114 (vol. I). Jul. 1985. pp. 1-295. cited by applicant

Riegler, C., and Bichlmaier, C. (2007). The geared turbofan technology—Opportunities, challenges and readiness status. Proceedings CEAS. Sep. 10-13, 2007. Berlin, Germany. pp. 1-12. cited by applicant

Rolls-Royce M45H. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 24, 2010. cited by applicant

Rossikhin, A. A., Pankov, S.V., Khaletskiy, Y.D., and Mileshehin, V.I. (2014). Computational study on acoustic features of fan model with leaned stators. Proceedings of ASME Turbo Expo 2014: Turbine Technical Conference and Exposition. Jun. 16-20, 2014. pp. 1-10. cited by applicant

Rossikhin, A., Pankov S., Brailko, I., and Mileshehin, V. (2014). Numerical investigation of high bypass ratio fan tine noise. Proceedings of ASME Turbo Expo 2014: Turbine Technical Conference and Exposition. Jun. 16-20, 2014. pp. 1-10. cited by applicant

Rotordynamic instability problems in high-performance turbomachinery. (1986). NASA conference publication 2443. Jun. 2-4, 1986. cited by applicant

Roux, E. (2007). Turbofan and turbojet engines database handbook. Editions Elodie Roux. Blagnac: France, pp. 1-595. cited by applicant

Salemme, C.T. and Murphy, G.C. (1979). Metal spar/superhybrid shell composite fan blades. Prepared for NASA. NASA-CR-159594. Aug. 1979. pp. 1-127. cited by applicant

Sargisson, D.F. (1985). Advanced propfan engine technology (APET) and single-rotation gearbox/pitch change mechanism. NASA Contractor Report-168113. R83AEB592. Jun. 1, 1985. pp. 1-476. cited by applicant

Savelle, S.A. and Garrard, G.D. (1996). Application of transient and dynamic simulations to the U.S. Army T55-L-712 helicopter engine. The American Society of Mechanical Engineers. Presented Jun. 10-13, 1996. pp. 1-8. cited by applicant

Schaefer, J.W., Sagerser, D.R., and Stakolich, E.G. (1977). Dynamics of high-bypass-engine thrust reversal using a variable-pitch fan. Technical Report prepared for NASA. NASA-TM-X-3524. May 1, 1977. pp. 1-33. cited by applicant

Seader, J.D. and Henley, E.J. (1998). Separation process principles. New York, NY: John Wiley & Sons, Inc. pp. 722-726 and 764-771. cited by applicant

Shah, D.M. (1992). MoSi₂ and other silicides as high temperature structural materials. Superalloys 1992. The Minerals, Metals, Materials Society. pp. 409-422. cited by applicant

Shorter Oxford English Dictionary, 6th Edition. (2007), vol. 2, N-Z, pp. 1888. cited by applicant

Silverstein, C.C., Gottschlich, J.M., and Meininger, M. The feasibility of heat pipe turbine vane cooling. Presented at the International Gas Turbine and Aeroengine Congress and Exposition, The Hague, Netherlands. Jun. 13-16, 1994. pp. 1-7. cited by applicant

Singh, A. (2005). Application of a system level model to study the planetary load sharing behavior. Journal of Mechanical Design. vol. 127. May 2005. pp. 469-476. cited by applicant

Singh, B. (1986). Small engine component technology (SECT) study. NASA CR-175079. Mar. 1, 1986. pp. 1-102. cited by applicant

Singh, R. and Houser, D.R. (1990). Non-linear dynamic analysis of geared systems. NASA-CR-180495. Feb. 1, 1990. pp. 1-263. cited by applicant

Smith, C.E., Hirschcron, R., and Warren, R.E. (1981). Propulsion system study for small transport aircraft technology (STAT). Final report. NASA-CR-165330. May 1, 1981. pp. 1-216. cited by applicant

Smith, L.H. Jr. (1993). NASA/GE fan and compressor research accomplishments. May 24-27, 1993. pp. 1-20. cited by applicant

Smith-Boyd, L. and Pike, J. (1986). Expansion of epicyclic gear dynamic analysis program. Prepared for NASA. NASA CR-179563. Aug. 1986. pp. 1-98. cited by applicant

Sowers, H.D. and Coward, W.E. (1978). QCSEE over-the-wing (OTW) engine acoustic design. NASA-CR-135268. Jun. 1, 1978. pp. 1-52. cited by applicant

Spadaccini, L.J., and Huang, H. (2002). On-line fuel deoxygenation for coke suppression. ASME, Jun. 2002. pp. 1-7. cited by applicant

Spadaccini, L.J., Sobel, D.R., and Huang, H. (2001). Deposit formation and mitigation in aircraft fuels. Journal of Eng. for Gas Turbine and Power, vol. 123. Oct. 2001. pp. 741-746. cited by applicant

Summons to Attend Oral Proceedings for European Patent Application No. EP13777804.9 dated

Dec. 10, 2019. cited by applicant

Summons to Attend Oral Proceedings for European Patent Application No. EP13778330.4 (EP2809922) dated Dec. 2, 2019. cited by applicant

Summons to Attend Oral Proceedings for European Patent Application No. EP13822569.3 (EP2841718), dated Oct. 23, 2019, 13 pages. cited by applicant

Sundaram, S.K., Hsu, J-Y., Speyer, R.F. (1994). Molten glass corrosion resistance of immersed combustion-heating tube materials in soda-lime-silicate glass. *J. Am. Ceram. Soc.* 77(6). pp. 1613-1623. cited by applicant

Sundaram, S.K., Hsu, J-Y., Speyer, R.F. (1995). Molten glass corrosion resistance of immersed combustion-heating tube materials in e-glass. *J. Am. Ceram. Soc.* 78(7). pp. 1940-1946. cited by applicant

Sutliff, D. (2005). Rotating rake turbofan duct mode measurement system. NASA TM-2005-213828. Oct. 1, 2005. pp. 1-34. cited by applicant

Suzuki, Y., Morgan, P.E.D., and Niihara, K. (1998). Improvement in mechanical properties of powder-processed MoSi₂ by the addition of Sc₂O₃ and Y₂O₃. *J. Am. Ceram. Soci.* 81(12). pp. 3141-3149. cited by applicant

Sweetman, B. and Sutton, O. (1998). Pratt Whitney's surprise leap. *Interavia Business & Technology*, 53.621, p. 25. cited by applicant

Taylor, W.F. (1974). Deposit formation from deoxygenated hydrocarbons. I. General features. *Ind. Eng. Chem., Prod. Res. Develop.*, vol. 13(2). 1974. pp. 133-138. cited by applicant

Taylor, W.F. (1974). Deposit formation from deoxygenated hydrocarbons. II. Effect of trace sulfur compounds. *Ind. Eng. Chem., Prod. Res. Dev.*, vol. 15(1). 1974. pp. 64-68. cited by applicant

Taylor, W.F. and Frankenfeld, J.W. (1978). Deposit formation from deoxygenated hydrocarbons. 3. Effects of trace nitrogen and oxygen compounds *Ind. Eng. Chem., Prod. Res. Dev.*, vol. 17(1). 1978. pp. 86-90. cited by applicant

Technical Data. Teflon. WS Hampshire Inc. Retrieved from: http://catalog.wshampshire.com/Asset/psg_teflon_ptfe.pdf. cited by applicant

Technical Report. (1975). Quiet Clean Short-haul Experimental Engine (Qcsee) Utw fan preliminary design. NASA-CR-134842. Feb. 1, 1975. pp. 1-98. cited by applicant

Technical Report. (1977). Quiet Clean Short-haul Experimental Engine (QCSEE) Under-the-Wing (UTW) final design report. NASA-CR-134847. Jun. 1, 1977. pp. 1-697. cited by applicant

Third Party Observations for EP Application No. EP13777804.9 (EP2809940), by Rolls-Royce, dated Nov. 21, 2019, 3 pages. cited by applicant

Third Party Observations for EP Application No. EP18191325.2 (EP3608515) by Rolls Royce dated Mar. 10, 2020. cited by applicant

Third Party Observations for EP Application No. EP18191325.2 (EP3608515) by Rolls Royce dated Mar. 6, 2020. cited by applicant

Third Party Observations for EP Application No. EP18191333.6 (EP3467273) by Rolls Royce dated Mar. 9, 2020. cited by applicant

Thompson L. Gamechanger: How Pratt & Whitney transformed itself to lead a revolution in jet propulsion. *Forbes*. Retrieved Apr. 28, 2016 from: <http://www.forbes.com/sites/lorenthompson/2016/01/21/gamechanger-how-pratt-whitney-transformed-itself-to-lead-a-revolution-in-jet-propulsion/print/>. cited by applicant

Thulin, R.D., Howe, D.C., and Singer, I.D. (1982). Energy efficient engine: High pressure turbine detailed design report. Prepared for NASA. NASA CR-165608. Received Aug. 9, 1984. pp. 1-178. cited by applicant

Gliebe, P.R., Ho, P.Y., and Mani, R. (1995). UHB engine fan and broadband noise reduction study. NASA CR-198357. Jun. 1995. pp. 1-48. cited by applicant

Grace, S.M., Sondak, D.L., Dorney, D.J., and Longue, M. (2007). CFD computation of fan interaction noise. *Proceedings of IMECE2007 2007 ASME International Mechanical Engineering*

Congress and Exposition. Nov. 11-14, 2007. pp. 1-11. cited by applicant

Grady, J.E., Weir, D.S., Lamoureux, M.C., and Martinez, M.M. (2007). Engine noise research in NASA's quiet aircraft technology project. Papers from the International Symposium on Air Breathing Engines (ISABE). 2007. cited by applicant

Gray, D.E. (1978). Energy efficient engine preliminary design and integration studies. NASA-CP-2036-PT-1. Nov. 1978. pp. 89-110. cited by applicant

Gray, D.E. (1978). Energy efficient engine preliminary design and integration studies. Prepared for NASA. NASA CR-135396. Nov. 1978. pp. 1-366. cited by applicant

Gray, D.E. and Gardner, W.B. (1983). Energy efficient engine program technology benefit/cost study—vol. 2. NASA CR-174766. Oct. 1983. pp. 1-118. cited by applicant

Greitzer, E.M., Bonnefoy, P.A., Delaroseblanco, E., Dorbian, C.S., Drela, M., Hall, D.K., Hansman, R.J., Hileman, J.I., Liebeck, R.H., Levegren, J. (2010). N+3 aircraft concept designs and trade studies, final report. vol. 1. Dec. 1, 2010. NASA/CR-2010-216794/vol. 1. pp. 1-187. cited by applicant

Griffiths, B. (2005). Composite fan blade containment case. Modern Machine Shop. Retrieved from: <http://www.mmsonline.com/articles/composite-fan-blade-containment-case> pp. 1-4. cited by applicant

Grose T.K. (2013). Reshaping flight for fuel efficiency: Five technologies on the runway. National Geographic. Mar. 16, 2016. Retrieved Apr. 23, 2013 from: <http://news.nationalgeographic.com/news/energy/2013/04/130423-reshaping-flight-for-fuel-efficiency.html>. cited by applicant

Groweneweg, J.F. (1994). Fan noise research at NASA. NASA-TM-106512. Prepared for the 1994 National Conference on Noise Control Engineering. Fort Lauderdale, FL. May 1-4, 1994. pp. 1-10. cited by applicant

Groweneweg, J.F. (1994). Fan noise research at NASA. Noise-CON 94. Fort Lauderdale, FL. May 1-4, 1994. pp. 1-10. cited by applicant

Gunston, B. (Ed.) (2000). Jane's aero-engines, Issue seven. Coulsdon, Surrey, UK: Jane's Information Group Limited. pp. 510-512. cited by applicant

Guynn, M. D., Berton, J.J., Fisher, K. L., Haller, W.J., Tong, M. T., and Thurman, D.R. (2009). Analysis of turbofan design options for an advanced single-aisle transport aircraft. American Institute of Aeronautics and Astronautics. pp. 1-13. cited by applicant

Guynn, M. D., Berton, J.J., Fisher, K. L., Haller, W.J., Tong, M. T., and Thurman, D.R. (2011). Refined exploration of turbofan design options for an advanced single-aisle transport. NASA/TM-2011-216883. pp. 1-27. cited by applicant

Guynn, M.D., Berton, J.J. & Haller, W.J. (2013). Advanced single-aisle transport propulsion design options revisited. AIAA 2013-4330. Aug. 12-14, 2013. p. 1-17. cited by applicant

Guynn, M.D., Berton, J.J., Fisher, K.L., Haller, W.J., Tong, M.T., and Thurman, D.R. (2009). Engine concept study for an advanced single-aisle transport. NASA/TM-2009-215784. pp. 1-97. cited by applicant

Haldenbrand, R. and Norgren, W.M. (1979). Airesearch QCGAT program [quiet clean general aviation turbofan engines]. NASA-CR-159758. pp. 1-199. cited by applicant

Hall, C.A. and Crichton, D. (2007). Engine design studies for a silent aircraft. Journal of Turbomachinery, 129, 479-487. cited by applicant

Han, J., Dutta, S., and Ekkad, S.V. (2000). Gas turbine heat transfer and cooling technology. New York, NY: Taylor Francis. pp. 1-25, 129-157, and 160-249. cited by applicant

Haque, A. and Shamsuzzoha, M., Hussain, F., and Dean, D. (2003). S20-glass/epoxy polymer nanocomposites: Manufacturing, structures, thermal and mechanical properties. Journal of Composite Materials, 37 (20), 1821-1837. cited by applicant

Hazlett, R.N. (1991). Thermal oxidation stability of aviation turbine fuels. Philadelphia, PA: ASTM. pp. 1-163. cited by applicant

Heidelberg, L.J., and Hall, D.G. (1992). Acoustic mode measurements in the inlet of a model turbofan using a continuously rotating rake. AIAA-93-0598. 31st Aerospace Sciences Meeting. Reno, NV. Jan. 11-14, 1993. pp. 1-30. cited by applicant

Heidelberg, L.J., and Hall, D.G. (1992). Acoustic mode measurements in the inlet of a model turbofan using a continuously rotating rake. NASA-TM-105989. Prepared for the 31st Aerospace Sciences Meeting. Reno, NV. Jan. 11-14, 1993. pp. 1-30. cited by applicant

Heingartner, P., Mba, D., Brown, D. (2003). Determining power losses in the helical gear mesh; Case Study. ASME 2003 Design Engineering Technical Conferences. Chicago, IL. Sep. 2-6, 2003. pp. 1-7. cited by applicant

Hemighaus, G., Boval, T., Bacha, J., Barnes, F., Franklin, M., Gibbs, L., . . . Morris, J. (2007). Aviation fuels: Technical review. Chevron Products Company. pp. 1-94. Retrieved from: https://www.cgabusinessdesk.com/document/aviation_tech_review.pdf. cited by applicant

Hendricks, E.S. and Tong, M.T. (2012). Performance and weight estimates for an advanced open rotor engine. NASA/TM-2012-217710. pp 1-13. cited by applicant

Hess, C. (1998). Pratt & Whitney develops geared turbofan. Flug Revue 43(7). Oct. 1998. cited by applicant

Hill, P.G. & Peterson, C.R. (2010). Mechanics and thermodynamics of propulsion, 2nd Edition. New Delhi, India: Dorling Kindersley. p. 225-6. cited by applicant

Hill, P.G., Peterson, C.R. (1965). Mechanics and thermodynamics of propulsion. Addison-Wesley Publishing Company, Inc. pp. 307-308. cited by applicant

Hill, P.G., Peterson, C.R. (1992). Mechanics and thermodynamics of propulsion, 2nd Edition. Addison-Wesley Publishing Company, Inc. pp. 400-406. cited by applicant

Holcombe, V. (2003). Aero-Propulsion Technology (APT) task V low noise ADP engine definition study. NASA CR-2003-212521. Oct. 1, 2003. pp. 1-73. cited by applicant

Honeywell Learjet 31 and 35/36 TFE731-2 to 2C Engine Upgrade Program. Sep. 2005. pp. 1-4. cited by applicant

Honeywell LF502. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 9, 2012. cited by applicant

Honeywell LF502. Jane's Aero-engines, Aero-engines—Turbofan. Aug. 17, 2016. cited by applicant

Honeywell LF507. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 9, 2012. cited by applicant

Honeywell Sabreliner 65 TFE731-3 to -3D Engine Upgrade Program. Oct. 2005. pp. 1-4. cited by applicant

Honeywell TFE731. Jane's Aero-engines, Aero-engines—Turbofan. Jul. 18, 2012. cited by applicant

Honeywell TFE731 Pilot Tips. pp. 1-143. cited by applicant

Honeywell TFE731-5AR to -5BR Engine Conversion Program. Sep. 2005. pp. 1-4. cited by applicant

Horikoshi, S. and Serpone, N. (2013). Introduction to nanoparticles. Microwaves in nanoparticle synthesis. Wiley-VCH Verlag GmbH Co. KGaA. pp. 1-24. cited by applicant

Horlock, J.H. (1958). Axial flow compressors: Fluid mechanics and thermodynamics. London: Butterworths Scientific Publications. pp. 29, 70. cited by applicant

Howard, D.F. (1976). QCSEE preliminary under the wing flight propulsion system analysis report. NASA CR-134868. Feb. 1, 1976. pp. 1-260. cited by applicant

Howe, D.C. and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study. NASA CR-174942. May 1, 1985. pp. 174. cited by applicant

Howe, D.C., and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study. NASA-CR-174942. May 1985. University of Washington dated Dec. 13, 1990. pp. 1-14. cited by applicant

Howe, D.C., and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study. NASA-CR-174942. May 1985. pp. 1-60. cited by applicant

Huang, H., Sobel, D.R., and Spadaccini, L.J. (2002). Endothermic heat-sink of hydrocarbon fuels for scramjet cooling. AIAA/ASME/SAE/ASEE, Jul. 2002. pp. 1-7. cited by applicant

Hughes, C. (2002). Aerodynamic performance of scale-model turbofan outlet guide vanes designed for low noise. Prepared for the 40th Aerospace Sciences Meeting and Exhibit. Reno, NV. NASA/TM-2001-211352. Jan. 14-17, 2002. pp. 1-38. cited by applicant

Hughes, C. (2010). Geared turbofan technology. NASA Environmentally Responsible Aviation Project. Green Aviation Summit. NASA Ames Research Center. Sep. 8-9, 2010. pp. 1-8. cited by applicant

Hughes, C., Jeracki, R.J., Woodward, R.P., and Miller, C.J. (2005). Fan noise source diagnostic test—Rotor alone aerodynamic performance results. NASA/TM-2005-211681. pp. 1-28. cited by applicant

Hughes, C.E., Podboy, G.G., Woodward, R.P., and Jeracki, R.J. (2005). The effect of bypass nozzle exit area on fan aerodynamic performance and noise in a model turbofan simulator. Proceedings of GT2005 ASME Turbo Expo 2005 Power for Land, Sea, and Air. Jun. 6-9, 2005. pp. 1-24. cited by applicant

2003 NASA seal/secondary air system workshop. (2003). NASA/CP-2004-212963/vol. 1. Sep. 1, 2004. pp. 1-408. cited by applicant

K2012). Gas Power Cycle—Jet Propulsion Technology, A case study. Machine Design Magazine. Nov. 5, 1998. Retrieved from: <http://machinedesign.com/content/pw8000-0820>. cited by applicant

About Gas Turb. Retrieved Jun. 26, 2018 from: <http://gasturb.de/about-gasturb.html>. cited by applicant

Adamson, A.P. (1975). Quiet Clean Short-Haul Experimental Engine (QCSEE) design rationale. Society of Automotive Engineers. Air Transportation Meeting. Hartford, CT. May 6-8, 1975. pp. 1-9. cited by applicant

Aeronautical Engineering: A cumulative index to the 1977 issues. National Aeronautics and Space Administration. NASA SP-7037. Washington, D.C. Jan. 1978. cited by applicant

Aerospace Information Report. (2008). Advanced ducted propulsor in-flight thrust determination. SAE International AIR5450. Aug. 2008. p. 1-392. cited by applicant

Agarwal, B.D and Broutman, L.J. (1990). Analysis and performance of fiber composites, 2nd Edition. John Wiley Sons, Inc. New York: New York. pp. 1-11, 13-23, 26-33, 50-51, 56-58, 60-61, 64-71, 87-89, 324-329, 436-437. cited by applicant

AGMA Standard (1997). Design and selection of components for enclosed gear drives. Alexandria, VA: American Gear Manufacturers Association. pp. 1-48. cited by applicant

AGMA Standard (1999) Flexible couplings-Mass elastic properties and other characteristics. Alexandria, VA: American Gear Manufacturers Association. pp. 1-46. cited by applicant

AGMA Standard (2006). Design manual for enclosed epicyclic gear drives. Alexandria, VA: American Gear Manufacturers Association. pp. 1-104. cited by applicant

Ahmad, F. and Mizramoghadam, A.V. (1999). Single v. two stage high pressure turbine design of modern aero engines. ASME. Prestend at the International Gast Turbine Aeroengine Congress & Exhibition. Indianapolis, Indiana. Jun. 7-10, 1999. pp. 1-9. cited by applicant

Amezket, M., Iriarte, X., Ros, J., and Pintor, J. (2009). Dynamic model of a helical gear pair with backlash and angle-varying mesh stiffness. Multibody Dynamics 2009, ECCOMAS Thematic Conference. 2009. pp. 1-36. cited by applicant

Anderson, N.E., Loewenthal, S.H., and Black, J.D. (1984). An analytical method to predict efficiency of aircraft gearboxes. NASA Technical Memorandum prepared for the Twentieth Joint Propulsion Conference. Cincinnati, OH. Jun. 11-13, 1984. pp. 1-25. cited by applicant

Anderson, R.D. (1985). Advanced Propfan Engine Technology (APET) definition study, single and counter-rotation gearbox/pitch change mechanism design. NASA CR-168115. Jul. 1, 1985. pp. 1-289. cited by applicant

Annexe Mesures—Methodologie de mesure et de calcul. STF495M-4 and STF495M-5. Cited in:

Documents cited by Rolls-Royce in anticipation of Oral Proceedings for Opposition of European Patent No. 2809932 dated Jan. 20, 2020. cited by applicant

Avco Lycoming Divison. ALF 502L Maintenance Manual. Apr. 1981. pp. 1-118. cited by applicant

Aviadvigatel D-110. Jane's Aero-engines, Aero-engines—Turbofan. Jun. 1, 2010. cited by applicant

Awker, R.W. (1986). Evaluation of propfan propulsion applied to general aviation. NASA CR-175020. Mar. 1, 1986. pp. 1-140. cited by applicant

Baker, R.W. (2000). Membrane technology and applications. New York, NY: McGraw-Hill. pp. 87-153. cited by applicant

Benzakein, M.J. (2001). Propulsion strategy for the 21st century—A vision into the future. pp. 1-9. cited by applicant

Berton, J.J. and Guynn, M.D. (2012). Multi-objective optimization of a turbofan for an advanced, single-aisle transport. NASA/TM-2012-217428. pp. 1-26. cited by applicant

Bessarabov, D.G., Jacobs, E.P., Sanderson, R.D., and Beckman, I.N. (1996). Use of nonporous polymeric flat-sheet gas-separation membranes in a membrane-liquid contactor: experimental studies. Journal of Membrane Sciences, vol. 113. 1996. pp. 275-284. cited by applicant

Bloomer, H.E. and Loeffler, I.J. (1982). QCSEE over-the-wing engine acoustic data. NASA-TM-82708. May 1, 1982. pp. 1-558. cited by applicant

Bloomer, H.E. and Samanich, N.E. (1982). QCSEE under-the-wing engine acoustic data. NASA-TM-82691. May 1, 1982. pp 1-28. cited by applicant

Bloomer, H.E. and Samanich, N.E. (1982). QCSEE under-the-wing enging-wing-flap aerodynamic profile characteristics. NASA-TM-82890. Sep. 1, 1982. pp. 1-48. cited by applicant

Bloomer, H.E., Loeffler, I.J., Kreim, W.J., and Coats, J.W. (1981). Comparison of NASA and contractor reslts from aeroacoustic tests of QCSEE OTW engine. NASA Technical Memorandum 81761. Apr. 1, 1981. pp. 1-30. cited by applicant

Bornstein, N. (1993). Oxidation of advanced intermetallic compounds. Journal de Physique IV, 1993, 03 (C9), pp. C9-367-C9-373. cited by applicant

Brennan, P.J. and Kroliczek, E.J. (1979). Heat pipe design handbook. Prepared for National Aeronautics and Space Administration by B & K Engineering, Inc. Jun. 1979. pp. 1-348. cited by applicant

Brief Communication from Opponent after Oral Proceedings for European Patent Application No. 13743283.7 (2809932), by Safran Aircraft Engines, dated Dec. 2, 2019. cited by applicant

Brines, G.L. (1990). The turbofan of tomorrow. Mechanical Engineering: The Journal of the American Society of Mechanical Engineers, 108(8), 65-67. cited by applicant

Bucknell, R.L. (1973). Influence of fuels and lubricants on turbine engine design and performance, fuel and lubircant analyses. Final Technical Report, Mar. 1971-Mar. 1973. pp. 1-252. cited by applicant

Bunker, R.S. (2005). A review of shaped hole turbine film-cooling technology. Journal of Heat Transfer vol. 127. Apr. 2005. pp. 441-453. cited by applicant

Carney, K., Pereira, M. Revilock, and Matheny, P. (2003). Jet engine fan blade containment using two alternate geometries. 4th European LS-DYNA Users Conference. pp. 1-10. cited by applicant

CFM International LEAP. (n.d.) In Wikipedia. Retrieved Dec. 17, 2014 from http://en.wikipedia.org/wiki/CFM_International_LEAP. cited by applicant

Chapman J.W., et al., “Control Design for an Advanced Geared Turbofan Engine”, AIAA Joint Propulsion Conference 2017, Jul. 10, 2017-Jul. 12, 2017, Atlanta, GA, pp. 1-12. cited by applicant

Cheryan, M. (1998). Ultrafiltration and microfiltration handbook. Lancaster, PA: Tecnominc Publishing Company, Inc. pp. 171-236. cited by applicant

Ciepluch, C. (1977). Quiet clean short-haul experimental engine (QCSEE) under-the-wing (UTW) final design report. Prepared for NASA. NASA-CP-134847. Retreived from: <https://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/19800075257.pdf>. cited by applicant

Clarke, D.R. and Levi, C.G. (2003). Materials design for the next generation thermal barrier

coatings. Annual. Rev. Mater. Res. vol. 33. 2003. pp. 383-417. cited by applicant

Cramoisi, G. Ed. (2012). Death in the Potomac: The crash of Air Florida Flight 90. Air Crash Investigations. Accident Report NTSB/AAR-82-8. p. 45-47. cited by applicant

Crichton, D., and Hall, T. (2007). Fan design and operation for ultra low noise. University of Cambridge Department of Engineering. Apr. 2007. pp. 1-241. cited by applicant

Croft, J. (2009). Integrated propulsion systems: The engine connection. Retrieved Dec. 17, 2014 from <http://www.flightglobal.com/news/articles/integrated-propulsion-systems-the-engine-connection-333001/>. cited by applicant

Cusick, M. (1981). Avco Lycoming's ALF 502 high bypass fan engine. Society of Automotive Engineers, Inc. Business Aircraft Meeting Exposition. Wichita, Kansas. Apr. 7-10, 1981. pp. 1-9. cited by applicant

Daggett, D.L., Brown, S.T., and Kawai, R.T. (2003). Ultra-efficient engine diameter study. NASA/CR-2003-212309. May 2003. pp. 1-52. cited by applicant

Dalton, III., W.N. (2003). Ultra high bypass ratio low noise engine study. NASA/CR-2003-212523. Nov. 2003. pp. 1-187. cited by applicant

Daly, M. Ed. (2008). Jane's Aero-Engine. Issue Twenty-three. Mar. 2008. p. 707-12. cited by applicant

Daly, M. Ed. (2010). Jane's Aero-Engine. Issue Twenty-seven. Mar. 2010. p. 633-636. cited by applicant

Damerau, J. (2014) What is the mesh stiffness of gears Screen shot of query submitted by Vahid Dabbagh, answered by Dr. Jochan Damerau, Research General Managerat Bosch Corp., Japan. Retrieved from: https://www.researchgate.net/post/What_is_the_mesh_stiffness_of_gears. cited by applicant

Darrah, S. (1987). Jet fuel deoxygenation. Interim Report for Period Mar. 1987-Jul. 1988. pp. 1-22. cited by applicant

Dassault Falcon 900EX Easy Systems Summary. Retrieved from: <http://www.smartcockpit.com/docs/F900EX-Engines.pdf> pp. 1-31. cited by applicant

Datasheet. CF6-80C2 high-bypass turbofan engines. Retrieved from <https://geaviation.com/sites/default/files/datasheet-CF6-80C2.pdf>. cited by applicant

Datasheet. CFM56-5B for the Airbus A320ceo family and CFM56-7B for the Boeing 737 family. <https://www.cfmaeroengines.com/>. cited by applicant

Datasheet. Genx™ high bypass turbofan engines. Retrieved from: <https://www.geaviation.com/sites/default/files/datasheet-genx.pdf>. cited by applicant

Davies, D. and Miller, D.C. (1971). A variable pitch fan for an ultra quiet demonstrator engine. 1976 Spring Convention: Seeds for Success in Civil Aircraft Design in the Next Two Decades. pp. 1-18. cited by applicant

Davis, D.G.M. (1973). Variable-pitch fans: Progress in Britain. Flight International. Apr. 19, 1973. pp. 615-617. cited by applicant

Decision Denying Institution of Inter Partes Review, *General Electric Company*, Petitioner v. *United Technologies Corporation*, Patent Owner, IPR 2016-00855, Entered Sep. 29, 2016. cited by applicant

Decision for Inter Partes Review of U.S. Pat. No. 9,121,412. Claims 1, 2, 4, 5, 7, 8, and 11. *General Electric Company*, Petitioner v. *United Technologies Corporation*, Patent Owner. Entered date of Oct. 27, 2016. cited by applicant

Decision Institution of Inter Parties Review, *General Electric Company*, Petitioner v, *United Technologies Corporation*, Patent Owner, IPR2017-00999, U.S. Pat. No. 8,277,174, Entered Jul. 6, 2017, pp. 1-4. cited by applicant

Decision of the Opposition Division for European Patent No. 2811120 (14155460.0), dated Jan. 15, 2020. cited by applicant

Decker, S. and Clough, R. (2016). GE wins shot at voiding pratt patent in jet-engine clash.

Bloomberg Technology. Retrieved from: <https://www.bloomberg.com/news/articles/2016-06-30/ge-wins-shot-to-invalidate-pratt-airplane-engine-patent-in-u-s>. cited by applicant

Declaration of Dr. Magdy Attia, In re U.S. Pat. No. 8,313,280, Executed Oct. 21, 2016, pp. 1-88. cited by applicant

Declaration of Dr. Magdy Attia, In re U.S. Pat. No. 8,517,668, Executed Dec. 8, 2016, pp. 1-81. cited by applicant

Declaration of John Eaton, Ph.D. In re U.S. Pat. No. 8,689,568, Executed Mar. 28, 2016, pp. 1-87. cited by applicant

Declaration of Reza Abhari, In re U.S. Pat. No. 8,227,174, IPR2017-00999, Executed Feb. 7, 2017, pp. 1-85. cited by applicant

Declaration of Reza Abhari, In re U.S. Pat. No. 8,448,895, Executed Nov. 28, 2016, pp. 1-81. cited by applicant

Declaration of Reza Abhari. In re U.S. Pat. No. 8,695,920, claims 1-4, 7-14, 17 and 19, Executed Nov. 29, 2016, pp. 1-102. cited by applicant

Declaration of Reza Abhari. In re U.S. Pat. No. 8,695,920. Executed Nov. 30, 2016, pp. 1-67. cited by applicant

Declaration of Reza Abhari, Ph.D. In re U.S. Pat. No. 8,337,149, Executed Apr. 5, 2016, pp. 1-77. cited by applicant

Declaration of Reza Abhari, Ph.D. In re U.S. Pat. No. 8,844,265, Executed Jun. 28, 2016, pp. 1-91. cited by applicant

Declaration of Reza Abhari, Ph.D. In re U.S. Pat. No. 9,121,412, Executed Apr. 23, 2016, pp. 1-71. cited by applicant

Defeo, A. and Kulina, M. (1977). Quiet clean short-haul experimental engine (QCSEE) main reduction gears detailed design final report. Prepared for Nasa. NASA-CR-134872. Jul. 1977. pp. 1-157. cited by applicant

Dickey, T.A. and Dobak, E.R. (1972). The evolution and development status of ALF 502 turbofan engine. National Aerospace Engineering and Manufacturing Meeting. San Diego, California. Oct. 2-5, 1972. pp. 1-12. cited by applicant

Digital Press Kit. Pratt Whitney PurePower Engine: This changes everything. pp. 4-6. cited by applicant

Dixon, S.L. (1998). Fluid mechanics, thermodynamics of turbomachinery. Oxford: Elsevier Butterworth-Heinemann. pp. 94-144. cited by applicant

Drago, R.J. (1974). Heavy-lift helicopter brings up drive ideas. Power Transmission Design. Mar. 1987. pp. 1-15. cited by applicant

Drago, R.J. and Margasahayam, R.N. (1987). Stress analysis of planet gears with integral bearings; 3D finite-element model development and test validation. 1987 MSC NASTRAN World Users Conference. Los Angeles, CA. Mar. 1987. pp. 1-14. cited by applicant

Dudley, D.W., Ed. (1954). Handbook of practical gear design. Lancaster, PA: Technomic Publishing Company, Inc. pp. 3.96-102 and 8.12-18. cited by applicant

Dudley, D.W., Ed. (1962). Gear handbook. New York, NY: McGraw-Hill. pp. 14-17 (TOC, Preface, and Index). cited by applicant

Dudley, D.W., Ed. (1962). Gear handbook. New York, NY: McGraw-Hill. pp. 3.14-18 and 12.7-12.21. cited by applicant

Dudley, D.W., Ed. (1994). Practical gear design. New York, NY: McGraw-Hill. pp. 119-124. cited by applicant

Edkins, D.P., Hirschcron, R., and Lee, R. (1972). TF34 turbofan quiet engine study. Final Report prepared for NASA. NASA-CR-120914. Jan. 1, 1972. pp. 1-99. cited by applicant

Edwards, T. and Zabarnick, S. (1993). Supercritical fuel deposition mechanisms. Ind. Eng. Chem. Res. vol. 32. 1993. pp. 3117-3122. cited by applicant

El-Sayad, A.F. (2008). Aircraft propulsion and gas turbine engines. Boca Raton, FL: CRC Press.

pp. 215-219 and 855-860. cited by applicant

Enoki, T. Kodama, H., Kusuda, S. (2013). Investigation of fan rotor interaction with pressure disturbance produced by downstream pylon. Proceedings of ASME Turbo Expo 2013: Turbine Technical Conference and Exposition Jun. 3-7, 2013. pp. 1-14. cited by applicant

Epstein, A.H. (2014). Aeropropulsion for commercial aviation in the twenty-first century and research directions needed. *AiAA Journal* 52(5). May 2014. pp. 901-911. cited by applicant

European Search Report for Application No. EP12861657 dated Sep. 3, 2014. cited by applicant

European Search Report for Application No. EP15166722.7 dated Sep. 2, 2015. cited by applicant

European Search Report for Application No. EP16154639, dated Jun. 16, 2016, 7 pages. cited by applicant

European Search Report for European Patent Application No. 19166650.2 completed Jul. 18, 2019. cited by applicant

European Search Report for European Patent Application No. 21177641.4 completed Oct. 15, 2021. cited by applicant

Faghri, A. (1995). Heat pipe and science technology. Washington, D.C.: Taylor Francis. pp. 1-60. cited by applicant

Falchetti, F., Quiniou, H., and Verdier, L. (1994). Aerodynamic design and 3D Navier-Stokes analysis of a high specific flow fan. ASME. Presented at the International Gas Turbine and Aeroengine Congress and Exposition. The Hague, Netherlands. Jun. 13-16, 1994. pp. 1-10. cited by applicant

File History for U.S. Appl. No. 12/131,876. cited by applicant

Fisher, K., Berton, J., Guynn, M., Haller B., Thurman, D., and Tong, M. (2012). NASA's turbofan engine concept study for a next-generation single-aisle transport. Presentation to ICAO's noise technology independent expert panel. Jan. 25, 2012. pp. 1-23. cited by applicant

Flack, R. (2005). Fundamentals of jet propulsion with applications. New York: Cambridge University Press. p. 281. cited by applicant

Fledderjohn, K.R. (1983). The TFE731-5: Evolution of a decade of business jet service. SAE Technical Paper Series. Business Aircraft Meeting Exposition. Wichita, Kansas. Apr. 12-15, 1983. pp. 1-12. cited by applicant

Frankenfeld, J.W. and Taylor, W.F. (1980). Deposit formation from deoxygenated hydrocarbons. 4. Studies in pure compound systems. *Ind. Eng. Chem., Prod. Res. Dev.*, vol. 19(1). 1978. pp. 65-70. cited by applicant

Garret TFE731 Turbofan Engine (Cat C). Chapter 79: Lubrication System. TTFE731 Issue 2. 2010. pp. 1-24. cited by applicant

Gates, D. Bombardier flies at higher market. *Seattle Times*. Jul. 13, 2008. pp. C6. cited by applicant

Gibala, R., Ghosh, A.K., Van Aken, D.C., Srolovitz, D.J., Basu, A., Chang, H., . . . Yang, W. (1992). Mechanical behavior and interface design of MoSi₂-based alloys and composites. *Materials Science and Engineering*, A155, 1992. pp. 147-158. cited by applicant

Gliebe, P.R. and Janardan, B.A. (2003). Ultra-high bypass engine aeroacoustic study. NASA/CR-2003-21252. GE Aircraft Engines, Cincinnati, Ohio. Oct. 2003. pp. 1-103. cited by applicant

Ivchenko-Progress Al-727M. *Jane's Aero-engines, Aero-engines—Turbofan*. Nov. 27, 2011. cited by applicant

Ivchenko-Progress D-436. *Jane's Aero-engines, Aero-engines—Turbofan*. Feb. 8, 2012. cited by applicant

Ivchenko-Progress D-727. *Jane's Aero-engines, Aero-engines—Turbofan*. Feb. 7, 2007. cited by applicant

Jacobson, N.S. (1993). Corrosion of silicon-based ceramics in combustion environments. *J. Am. Ceram. Soc.* 76 (1). pp. 3-28. cited by applicant

Jeng, Y.-L., Lavernia, E.J. (1994). Processing of molybdenum disilicide. *J. of Mat. Sci.* vol. 29. 1994. pp. 2557-2571. cited by applicant

Johnson, I.A. and Bullock, R.O. Ed. (1965). Aerodynamic design of axial-flow compressors. pp. 1-505. cited by applicant

Johnston, R.P. and Hemsworth, M.C. (1978). Energy efficient engine preliminary design and integration studies. Jun. 1, 1978. pp. 1-28. cited by applicant

Johnston, R.P., Hirschkron, R., Koch, C.C., Neitzel, R.E., and Vinson, P.W. (1978). Energy efficient engine: Preliminary design and integration study- final report. NASA CR-135444. Sep. 1978. pp. 1-401. cited by applicant

Jorgensen, P.J., Wadsworth, M.E., and Cutler, I.B. (1961). Effects of water vapor on oxidation of silicon carbide. J. Am. Ceram. Soc. 44(6). pp. 248-261. cited by applicant

Judgement and Final Written Decision. U.S. Pat. No. 8,448,895, *General Electric Company*, Petitioner, v. *United Technologies Corporation*, Patent Owner, IPR2017-00425, Entered Jul. 2, 2018, 52 pages. cited by applicant

Kahn, H., Tayebi, N., Ballarini, R., Mullen, R.L., Heuer, A.H. (2000). Fracture toughness of polysilicon MEMS devices. Sensors and Actuators vol. 82. 2000. pp. 274-280. cited by applicant

Kandebo, S.W. (1998). Geared-Turbofan engine design targets cost, complexity. Aviation Week Space Technology, 148(8). p. 34-5. cited by applicant

Kandebo, S.W. (1998). Pratt & Whitney launches geared turbofan engine. Aviation Week Space Technology, 148(8). p. 32-4. cited by applicant

Kaplan, B., Nicke, E., Voss, C. (2006), Design of a highly efficient low-noise fan for ultra-high bypass engines. Proceedings of GT2006 for ASME Turbo Expo 2006: Power for Land, Sea and Air. Barcelona, SP. May 8-11, 2006. pp. 1-10. cited by applicant

Kasuba, R. and August, R. (1984). Gear mesh stiffness and load sharing in planetary gearing. American Society of Mechanical Engineers, Design Engineering Technical Conference, Cambridge, MA. Oct. 7-10, 1984. pp. 1-6. cited by applicant

Kerrebrock, J.L. (1977). Aircraft engines and gas turbines. Cambridge, MA: The MIT Press, p. 11. cited by applicant

Kestner, B.K., Schutte, U.S., Gladin, J.C., and Mavris, D.N. (2011). Ultra high bypass ratio engine sizing and cycle selection study for a subsonic commercial aircraft in the N+2 timeframe. Proceedings of ASME Turbo Expo 2011. Jun. 6-10, 2011. pp. 1-11. cited by applicant

Kjelgaard, C. (2010). Gear up for the GTF. Aircraft Technology, 105. Apr.-May 2010. pp. 86, 88, 90, 92-95. cited by applicant

Knip, Jr., G. (1987). Analysis of an advanced technology subsonic turbofan incorporating revolutionary materials. NASA Technical Memorandum. May 1987. pp. 1-23. cited by applicant

Kollar, L.P. and Springer, G.S. (2003). Mechanics of composite structures. Cambridge, UK: Cambridge University Press, p. 465. cited by applicant

Kovich, G. and Steinke, R.J. (1976). Performance of low-pressure-ratio low-tip-speed fan stage with blade tip solidity of 0.65. NASA TM X-3341. Feb. 1976. pp. 1-95. cited by applicant

Krantz, T.L. (1990). Experimental and analytical evaluation of efficiency of helicopter planetary stage. NASA Technical Paper. Nov. 1990. pp. 1-19. cited by applicant

Krauskopf, L. & Shumaker, L. (2014). GE exec says avoided geared design in jet engine battle with Pratt. Reuters. Sep. 15, 2014. <http://www.reuters.com/article/us-general-electric-united-tech-engine-idUSKBN0HA2H620140915>. cited by applicant

Kurzke, J. (2001). GasTurb 9: A program to calculate design and off-design performance of gas turbines. Retrieved from: <https://www.scribd.com/document/92384867/GasTurb9Manual>. cited by applicant

Kurzke, J. (2008). Preliminary Design, Aero-engine design: From state of the art turbofans towards innovative architectures. pp. 1-72. cited by applicant

Kurzke, J. (2009). Fundamental differences between conventional and geared turbofans. Proceedings of ASME Turbo Expo: Power for Land, Sea, and Air 2009, Orlando, Florida. pp. 145-153. cited by applicant

Kurzke, J. (2012). GasTurb 12: Design and off-design performance of gas turbines. Retrieved from: <https://www.scribd.com/document/153900429/GasTurb-12>. cited by applicant

Larsson L., Gronstedt, T., and Kyprianidis, K.G. (2011). Conceptual design and mission analysis for a geared turbofan and an open rotor configuration. Proceedings of ASME turbo expo 2011. Jun. 6-10, 2011. pp. 1-12. cited by applicant

Leckie, F.A. and Dal Bello, D.J. (2009). Strength and stiffness of engineering systems. Mechanical Engineering Series. Springer. pp. 1-10, 48-51. cited by applicant

Lee, K.N. (2000). Current status of environmental barrier coatings for Si-Based ceramics. Surface and Coatings Technology 133-134, 2000. pp. 1-7. cited by applicant

Levintan, R.M. (1975). Q-Fan demonstrator engine. Journal of Aircraft. vol. 12(8). Aug. 1975. pp. 658-663. cited by applicant

Lewicki, D.G., Black, J.D., Savage, M., and Coy, J.J. (1985). Fatigue life analysis of a turboprop reduction gearbox. NASA Technical Memorandum. Prepared for the Design Technical Conference (ASME). Sep. 11-13, 1985. pp. 1-26. cited by applicant

Liebeck, R.H., Andrastek, D.A., Chau, J., Girvin, R., Lyon, R., Rawdon, B.K., Scott, P.W et al. (1995). Advanced subsonic airplane design economics studies. NASA CR-195443. Apr. 1995. pp. 1-187. cited by applicant

Litt, J.S. (2018). Sixth NASA Glenn Research Center propulsion control and diagnostics (PCD) workshop. NASA/CP-2018-219891. Apr. 1, 2018. pp. 1-400. cited by applicant

Lord, W.K., MacMartin, D.G., and Tillman, T.G. (2000). Flow control opportunities in gas turbine engines. American Institute of Aeronautics and Astronautics. pp. 1-15. cited by applicant

Lynwander, P. (1983). Gear drive systems: Design and application. New York, New York: Marcel Dekker, Inc. pp. 145, 355-358. cited by applicant

Macisaac, B. and Langston, R. (2011). Gas turbine propulsion systems. Chichester, West Sussex: John Wiley Sons, Ltd. pp. 260-265. cited by applicant

Mancuso, J.R. and Corcoran, J.P. (2003). What are the differences in high performance flexible couplings for turbomachinery Proceedings of the Thirty-Second Turbomachinery Symposium. 2003. pp. 189-207. cited by applicant

Matsumoto, T., Toshiro, U., Kishida, A., Tsutomu, F., Maruyama, I., and Akashi, M. (1996). Novel functional polymers: Poly (dimethylsiloxane)-polyamide multiblock copolymer. VII. Oxygen permeability of aramid-silicone membranes in a gas-membrane-liquid system. Journal of Applied Polymer Science, vol. 64(6). May 9, 1997. pp. 1153-1159. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 223-234, 462-479, 517-520, 757-767, and 862-864. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 85-87, 95-104, 121-123, 223-234, 242-245, 278-285, 303-309, 323-326, 462-479, 517-520, 563-565, 630-632, 668-670, 673-675, 682-685, 697-705, 726-727, 731-732, 802-805, 828-830 and appendices. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 85-87, 95-104, 121-123, 223-234, 242-245, 278-285, 303-309, 323-326, 462-479, 517-520, 563-565, 630-632, 673-675, 682-685, 697-699, 703-705, 802-805, 862-864, and 923-925. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 299-305. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 8-15. cited by applicant

Mattingly, J.D. (2006). Elements of propulsion gas turbines and rockets. . New York, New York: AAIA Education Series. p. 419. cited by applicant

Mattingly, J.D., Heiser, W.H., and Pratt, D.T. (2002). Aircraft engine design. Second Ed. Education Series. Reston, VA. pp. 1-687. cited by applicant

Mavris, D.N., Schutte, U.S. (2016). Application of deterministic and probabilistic system design methods and enhancements of conceptual design tools for ERA project final report. NASA/CR-2016-219201. May 1, 2016. pp. 1-240. cited by applicant

McArdle, J.G. and Moore, A.S. (1979). Static test-stand performance of the YF-102 turbofan engine with several exhaust configurations for the Quiet Short-Haul Research Aircraft (QSRA). Prepared for NASA. NASA-TP-1556. Nov. 1979. pp. 1-68. cited by applicant

McCracken, R.C. (1979). Quiet short-haul research aircraft familiarization document. NASA-TM-81149. Nov. 1, 1979. pp. 1-76. cited by applicant

Tong, M.T., Jones, S.M., Haller, W.J., and Handschuh, R.F. (2009). Engine conceptual design studies for a hybrid wing body aircraft. NASA/TM-2009-215680. Nov. 1, 2009. pp. 1-15. cited by applicant

Translation of European Opposition against European Patent Application No. EP2776677 held by United Technologies Corporation. Mailed Mar. 23, 2016. cited by applicant

Trembley, Jr., H.F. (1977). Determination of effects of ambient conditions on aircraft engine emissions. ALF 502 combustor rig testing and engine verification test. Prepared for Environmental Protection Agency. Sep. 1977. pp. 1-256. cited by applicant

Tsang D. (2011). Special report: The engine battle heats up (Update 1) Aspire Aviation. Retrieved Apr. 3, 2016 from: <http://www.aspireaviation.com/2011/05/10/pw-purepower-engine-vs-cfm-leap-x/>. cited by applicant

Tsirlin, M., Pronin, Y.E., Florina, E.K., Mukhametov, S. Kh., Khatsernov, M.A., Yun, H.M., . . . Kroke, E. (2001). Experimental investigation of multifunctional interphase coatings on SiC fibers for non-oxide high temperature resistant CMCs. High Temperature Ceramic Matrix Composites. 4th Int'l Conf. on High Temp. Ceramic Matrix Composites. Oct. 1-3, 2001. pp. 149-156. cited by applicant

Tsuchiya, N., Nakamura, Y., Goto, S., and Kodama, H. (2004). Low noise FEGV designed by numerical method based on CFD. Proceedings of ASME Turbo Expo 2004 Power for Land, Sea, and Air. Jun. 14-17, 2004. pp. 1-8. cited by applicant

Tummers, B. (2006). DataThief III. Retrieved from: <https://datathief.org/DatathiefManual.pdf> pp. 1-52. cited by applicant

Turbomeca Aubisque. Jane's Aero-engines, Aero-engines—Turbofan. Nov. 2, 2009. cited by applicant

Turner, M. G., Norris, A., and Veres, J.P. (2004). High-fidelity three-dimensional simulation of the GE90. Nasa/ TM-2004-212981. pp. 1-18. cited by applicant

Type Certificate Data Sheet No. E6NE. Department of Transportation Federal Aviation Administration. Jun. 7, 2002. pp. 1-10. cited by applicant

U.S. Department of Transportation: Federal Aviation Administration Advisory Circular, Runway overrun prevention, dated: Nov. 6, 2007, p. 1-8 and Appendix 1 pp. 1-15, Appendix 2 pp. 1-6, Appendix 3 pp. 1-3, and Appendix 4 pp. 1-5. cited by applicant

U.S. Department of Transportation: Federal Aviation Administration Advisory Circular. Standard operating procedures for flight deck crewmembers, Dated: Feb. 27, 2003, p. 1-6 and Appendices. cited by applicant

U.S. Department of Transportation: Federal Aviation Administration Type Certificate Data Sheet No. E6WE. Dated: May 9, 2000. p. 1-9. cited by applicant

Vasudevan, A.K. and Petrovic, J.J. (1992). A comparative overview of molybdenum disilicide composites. Materials Science and Engineering, A155, 1992. pp. 1-17. cited by applicant

Warwick, G. (2007). Civil engines: Pratt & Whitney gears up for the future with GTF. Flight International, Nov. 2007. Retrieved Jun. 14, 2016 from: <https://www.flightglobal.com/news/articles/civil-engines-pratt-amp-whitney-gears-up-for-the-future-with-219989/>. cited by applicant

Waters, M.H. and Schairer, E.T. (1977). Analysis of turbofan propulsion system weight and

dimensions. NASA Technical Memorandum. Jan. 1977. pp. 1-65. cited by applicant

Webster, J.D., Westwood, M.E., Hayes, F.H., Day, R.J., Taylor, R., Duran, A., . . . Vogel, W.D. (1998). Oxidation protection coatings for C/SiC based on yttrium silicate. Journal of European Ceramic Society vol. 18. 1998. pp. 2345-2350. cited by applicant

Wendus, B.E., Stark, D.F., Holler, R.P., and Funkhouse, M.E. (2003). Follow-on technology requirement study for advanced subsonic transport. Technical Report prepared for Nasa. NASA/CR-2003-212467. Aug. 1, 2003. pp. 1-47. cited by applicant

Whitaker, R. (1982). ALF 502: plugging the turbofan gap. Flight International, p. 237-241, Jan. 30, 1982. cited by applicant

Wie, Y.S., Collier, F.S., Wagner, R.D., Viken, J.K., and Pfenniger, W. (1992). Design of a hybrid laminar flow control engine nacelle. AIAA-92-0400. 30th Aerospace Sciences Meeting & Exhibit. Jan. 6-9, 1992. pp. 1-14. cited by applicant

Wikipedia. Stiffness. Retrieved Jun. 28, 2018 from: <https://en.wikipedia.org/wiki/Stiffness>. cited by applicant

Wikipedia. Torsion spring. Retrieved Jun. 29, 2018 from: https://en.wikipedia.org/wiki/Torsion_spring. cited by applicant

Wilfert, G. (2008). Geared fan. Aero-Engine Design: From State of the Art Turbofans Towards Innovative Architectures, von Karman Institute for Fluid Dynamics, Belgium, Mar. 3-7, 2008. pp. 1-26. cited by applicant

Willis, W.S. (1979). Quiet clean short-haul experimental engine (QCSEE) final report. NASA/CR-159473 pp. 1-289. cited by applicant

Winn, A. (Ed). (1990). Wide Chord Fan Club. Flight International, 4217(137). May 23-29, 1990. pp. 34-38. cited by applicant

Woodward, R.P., Bock, L.A., Heidelberg, L., and Hall, D.G. (1992). Far-field noise and internal modes from a ducted propeller at simulated aircraft takeoff conditions. NASA TM 105369. Jan. 6-9, 1992. pp. 1-15. cited by applicant

Wright, G.H. and Russell, J.G. (1990). The M.45SD-02 variable pitch geared fan engine demonstrator test and evaluation experience. Aeronautical Journal., vol. 84(836). Sep. 1980. pp. 268-277. cited by applicant

Xie, M. (2008). Intelligent engine systems: Smart case system. NASA/CR-2008-215233. pp. 1-31. cited by applicant

Xu, L. & Gronstedt, T. (2010). Design analysis of an intercooled turbofan engine. Journal of Engineering for Gas Turbine Engines and Power vol. 132. Nov. 2010. pp. 114503-1-114503-4. cited by applicant

Xu, Y., Cheng, L., Zhang, L., Ying, H., and Zhou, W. (1999). Oxidation behavior and mechanical properties of C/SiC composites with Si—MoSi₂ oxidation protection coating. J. of Mat. Sci. vol. 34. 1999. pp. 6009-6014. cited by applicant

Zalud, T. (1998). Gears put a new spin on turbofan performance. Machine Design, 70(20), p. 104. cited by applicant

Zamboni, G. and Xu, L. (2009). Fan root aerodynamics for large bypass gas turbine engines: Influence on the engine performance and 3D design. Proceedings of ASME Turbo Expo 2009: Power for Land, Sea and Air. Jun. 8-12, 2009, Orlando, Florida, USA. pp. 1-12. cited by applicant

Zhao, J.C. and Westbrook, J.H. (2003). Ultrahigh-temperature materials for jet engines. MRS Bulletin. vol. 28(9). Sep. 2003. pp. 622-630. cited by applicant

Primary Examiner: Cheng; Stephanie Sebasco

Attorney, Agent or Firm: Carlson, Gaskey & Olds, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/891,492, filed Jun. 3, 2020, the disclosure of which is incorporated by reference in its entirety herein.

BACKGROUND

(1) This disclosure relates generally to flow distribution for gas turbine engines, and more particularly to arranging guide vanes relative to one or more flow splitters.

(2) Gas turbine engines can include a fan section, a compressor section, a combustor section and a turbine section. The fan section includes a fan having fan blades for compressing a portion of incoming air to produce thrust and also for delivering a portion of air to the compressor section. Air entering the compressor section is compressed and delivered into the combustor section where it is mixed with fuel and ignited to generate a high-speed exhaust gas flow. The high-speed exhaust gas flow expands through the turbine section to drive the compressor section and the fan.

(3) Some fan sections may include guide vanes positioned in a bypass flow path downstream of the fan blades and a flow splitter. The guide vanes may direct the bypass airflow from the fan blades before being ejected from the bypass flow path.

SUMMARY

(4) A section for a gas turbine engine according to an example of the present disclosure includes a rotor including a row of blades extending in a radial direction outwardly from a hub. The hub is rotatable about a longitudinal axis such that the row of blades deliver flow to a bypass flow path, an intermediate flow path, and a core flow path. A first case surrounds the row of blades to establish the bypass flow path. A first flow splitter divides flow between the bypass flow path and a second duct. A row of guide vanes extends in the radial direction across the bypass flow path. A second flow splitter radially inboard of the first flow splitter divides flow from the second duct between the intermediate flow path and the core flow path. A forwardmost edge of the second flow splitter is axially aft of a forwardmost edge of the first flow splitter with respect to the longitudinal axis, and the forwardmost edges of the first and second flow splitters are axially forward of the row of guide vanes with respect to the longitudinal axis. A bypass port interconnects the intermediate and bypass flow paths at a position axially aft of a position of the row of guide vanes relative to the longitudinal axis.

(5) In a further embodiment of any of the foregoing embodiments, the hub is driven by a turbine through a geared architecture.

(6) In a further embodiment of any of the foregoing embodiments, each of the blades extends in the radial direction between a 0% span position at the hub and a 100% span position at a tip to establish a hub-to-tip ratio, and the hub-to-tip ratio is less than or equal to 0.4 measured relative to a forwardmost portion of a leading edge of the blades.

(7) In a further embodiment of any of the foregoing embodiments, a pressure ratio across the blades alone is less than 1.45 at cruise at 0.8 Mach and 35,000 feet.

(8) A further embodiment of any of the foregoing embodiments includes a first duct and a second duct. The first duct establishes the bypass flow path. The second duct branches between the intermediate and core flow paths at the second flow splitter. A first annulus area is established by the first duct at the forwardmost edge of the first flow splitter. A second annulus area is established by the second duct at the forwardmost edge of the first flow splitter. A bypass area ratio is defined as the first annulus area divided by the second annulus area, and the bypass area ratio is greater than or equal to 10.

(9) In a further embodiment of any of the foregoing embodiments, each of the blades extends in the radial direction between a 0% span position at the hub and a 100% span position at a tip. The

forwardmost edge of the first flow splitter is situated in the radial direction at a first splitter position. The first splitter position is radially aligned with or radially inward of a 25% span position of the blades. The forwardmost edge of the second flow splitter is situated in the radial direction at a second splitter position, and the second splitter position is radially aligned with or radially outward of a 5% span position of the blades.

(10) In a further embodiment of any of the foregoing embodiments, each of the blades extends in the radial direction between the 0% span position and the 100% span position to establish a hub-to-tip ratio, and the hub-to-tip ratio is between 0.16-0.36. The hub-to-tip ratio measured relative to a forwardmost portion of a leading edge of the blades.

(11) In a further embodiment of any of the foregoing embodiments, the leading edges of the blades at the 100% span position is established along a first reference plane, and leading edges of the guide vanes at a 100% span position are established along a second reference plane. The first and second reference planes are perpendicular to the longitudinal axis. A first axial length is established between the first and second reference planes. A tip radius of the blades is established between the tip and the longitudinal axis, and a ratio of the first axial length divided by the tip radius is greater than or equal to 0.5.

(12) In a further embodiment of any of the foregoing embodiments, the row of blades establishes a blade quantity (BQ), the blade quantity (BQ) is at least 12 but not more than 20 blades, the row of guide vanes establishes a vane quantity (VQ), and the vane quantity (VQ) is at least 20 but not more than 40 guide vanes.

(13) In a further embodiment of any of the foregoing embodiments, the ratio of VQ/BQ is between 2.0 and 2.6.

(14) In a further embodiment of any of the foregoing embodiments, the first splitter position radially is aligned with or radially outward of a 10% span position of the blades, and the second splitter position is radially aligned with or radially inward of a 15% span position of the blades. A second axial length is established between the first and second splitter positions relative to the longitudinal axis, and a ratio of the second axial length divided by the first axial length is between 0.1 and 0.3.

(15) A gas turbine engine according to an example of the present disclosure includes a fan section including a fan having a row of blades extending in a radial direction between a 0% span position at a hub and a 100% span position at a tip. The hub is rotatable about an engine longitudinal axis such that the row of blades deliver flow to a bypass flow path, an intermediate flow path and a core flow path. A compressor section establishes the core flow path. A turbine section drives the fan section and the compressor section. A fan case includes a bypass duct surrounding the row of blades to establish the bypass flow path. A housing includes a first flow splitter that divides flow between the bypass flow path and a second duct. A row of guide vanes in the bypass duct extend in the radial direction across the bypass flow path. An engine case includes a second flow splitter radially inboard of the first flow splitter and divides flow from the second duct between the intermediate flow path and the core flow path. A bypass port interconnects the intermediate and bypass flow paths at a position downstream of the row of guide vanes. Each of the blades extends in the radial direction between the 0% span position and 100% span position to establish a hub-to-tip ratio, and the hub-to-tip ratio is less than or equal to measured relative to a forwardmost portion of a leading edge of the blades.

(16) In a further embodiment of any of the foregoing embodiments, the turbine section includes a fan drive turbine, and a geared architecture drives the fan at a different speed than a speed of the fan drive turbine.

(17) In a further embodiment of any of the foregoing embodiments, a pressure ratio across the blades alone is less than 1.45 at cruise at 0.8 Mach and 35,000 feet.

(18) In a further embodiment of any of the foregoing embodiments, a forwardmost edge of the second flow splitter is axially aft of a forwardmost edge of the first flow splitter with respect to the

engine longitudinal axis, and the forwardmost edges of the first and second flow splitters are axially forward of the row of guide vanes with respect to the engine longitudinal axis.

(19) A further embodiment of any of the foregoing embodiments includes one or more blocker doors situated in the intermediate flow path downstream of the bypass port. The one or more blocker doors are moveable to selectively communicate flow in the intermediate flow path to a vent port.

(20) A further embodiment of any of the foregoing embodiments includes a thrust reverser including a cascade that selectively communicates airflow from the bypass duct. The cascade extends axially aft of both the row of guide vanes and the bypass port with respect to the engine longitudinal axis.

(21) A method of operation for a gas turbine engine according to an example of the present disclosure includes driving a rotor having a hub and a row of blades to deliver airflow to a bypass flow path, and an intermediate flow path and a core flow path. A first duct surrounds the row of blades to establish the bypass flow path. A first flow splitter divides airflow between the bypass flow path and the intermediate flow path. A row of guide vanes extend across the bypass flow path. A second flow splitter divides airflow between the intermediate flow path and the core flow path. The method includes communicating the airflow through a bypass port that interconnects the intermediate flow path to the bypass flow path at a position downstream of the row of guide vanes. Each of the blades extends in a radial direction between a 0% span position at the hub and a 100% span position at a tip to establish a hub-to-tip ratio, and the hub-to-tip ratio is less than or equal to 0.4 measured relative to a forwardmost portion of a leading edge of the blades.

(22) In a further embodiment of any of the foregoing embodiments, the method includes selectively moving one or more blocker doors to communicate airflow in the intermediate flow path to a vent port, the vent port established downstream of the bypass port.

(23) In a further embodiment of any of the foregoing embodiments, the driving step including driving the rotor through a geared architecture at a different speed than a turbine, the hub-to-tip ratio is between 0.16-0.36, a pressure ratio across the blades alone is less than 1.45 at cruise at 0.8 Mach and 35,000 feet, and a first annulus area is established at the forwardmost edge of the first flow splitter. A second annulus area is established at the forwardmost edge of the first flow splitter. A bypass area ratio is defined as the first annulus area divided by the second annulus area, and the bypass area ratio is greater than or equal to 10.

(24) The various features and advantages of this disclosure will become apparent to those skilled in the art from the following detailed description. The drawings that accompany the detailed description can be briefly described as follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a gas turbine engine.

(2) FIG. 2A illustrates an example arrangement of blades and guide vanes at a span position.

(3) FIG. 2B illustrates an example arrangement of blades and guide vanes at another span position.

(4) FIG. 3 is a schematic view of airfoil span positions for a blade.

(5) FIG. 4 is a schematic view of airfoil span positions for a guide vane.

(6) FIG. 5 illustrates a gas turbine engine according to another example including blocker doors in a closed position.

(7) FIG. 6 illustrates the blocker doors of FIG. 5 in an opened position.

(8) FIG. 7A is a partial cross section view of a thrust reverser and a variable area nozzle in stowed positions.

(9) FIG. 7B is a partial cross section view of the thrust reverser of FIG. 7A in the stowed position

and the variable area nozzle of FIG. 7A in a deployed position.

(10) FIG. 7C is a partial cross section view of the thrust reverser and the variable area nozzle of FIG. 7A in deployed positions.

(11) FIG. 8A illustrates a section of the engine of FIG. 5.

(12) FIG. 8B illustrates a sectional view taken along line 8B-8B of FIG. 8A.

(13) FIG. 8C illustrates an exemplary guide vane.

(14) FIG. 9A illustrates an example plot of bypass area ratio with respect to span position.

(15) FIG. 9B illustrates selected portions of the plot of FIG. 9A.

(16) FIG. 10A illustrates an example plot of fan pressure ratio with respect to span position.

(17) FIG. 10B illustrates selected portions of the plot of FIG. 10A.

(18) FIG. 11 illustrates another example plot of fan pressure ratio with respect to span position.

(19) FIG. 12 illustrates exemplary engine modes.

(20) Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

(21) FIG. 1 schematically illustrates a gas turbine engine 20. The gas turbine engine 20 is disclosed herein as a two-spool turbofan that generally incorporates a fan section 22, a compressor section 24, a combustor section 26 and a turbine section 28. The fan section 22 drives air along a bypass flow path B in a bypass duct defined within a housing 15 such as a fan case or nacelle, and also drives air along a core flow path C for compression and communication into the combustor section 26 then expansion through the turbine section 28. Although depicted as a two-spool turbofan gas turbine engine in the disclosed non-limiting embodiment, it should be understood that the concepts described herein are not limited to use with two-spool turbofans as the teachings may be applied to other types of turbine engines including three-spool architectures.

(22) The exemplary engine 20 generally includes a low speed spool 30 and a high speed spool 32 mounted for rotation about an engine central longitudinal axis A relative to an engine static structure 36 via several bearing systems 38. It should be understood that various bearing systems 38 at various locations may alternatively or additionally be provided, and the location of bearing systems 38 may be varied as appropriate to the application.

(23) The low speed spool 30 generally includes an inner shaft 40 that interconnects, a first (or low) pressure compressor 44 and a first (or low) pressure turbine 46. The inner shaft 40 is connected to the fan 42 through a speed change mechanism, which in exemplary gas turbine engine 20 is illustrated as a geared architecture 48 to drive a fan 42 at a lower speed than the low speed spool 30. The high speed spool 32 includes an outer shaft 50 that interconnects a second (or high) pressure compressor 52 and a second (or high) pressure turbine 54. A combustor 56 is arranged in exemplary gas turbine 20 between the high pressure compressor 52 and the high pressure turbine 54. A mid-turbine frame 57 of the engine static structure 36 may be arranged generally between the high pressure turbine 54 and the low pressure turbine 46. The mid-turbine frame 57 further supports bearing systems 38 in the turbine section 28. The inner shaft 40 and the outer shaft 50 are concentric and rotate via bearing systems 38 about the engine central longitudinal axis A which is collinear with their longitudinal axes.

(24) The core airflow is compressed by the low pressure compressor 44 then the high pressure compressor 52, mixed and burned with fuel in the combustor 56, then expanded through the high pressure turbine 54 and low pressure turbine 46. The mid-turbine frame 57 includes airfoils 59 which are in the core airflow path C. The turbines 46, 54 rotationally drive the respective low speed spool 30 and high speed spool 32 in response to the expansion. It will be appreciated that each of the positions of the fan section 22, compressor section 24, combustor section 26, turbine section 28, and fan drive gear system 48 may be varied. For example, gear system 48 may be located aft of the low pressure compressor, or aft of the combustor section 26 or even aft of turbine section 28, and fan 42 may be positioned forward or aft of the location of gear system 48.

(25) The engine 20 in one example is a high-bypass geared aircraft engine. In a further example,

the engine **20** bypass ratio is greater than about six (6), with an example embodiment being greater than about ten (10), the geared architecture **48** is an epicyclic gear train, such as a planetary gear system or other gear system, with a gear reduction ratio of greater than about 2.3 and the low pressure turbine **46** has a pressure ratio that is greater than about five. In one disclosed embodiment, the engine **20** bypass ratio is greater than about ten (10:1), the fan diameter is significantly larger than that of the low pressure compressor **44**, and the low pressure turbine **46** has a pressure ratio that is greater than about five 5:1. Low pressure turbine **46** pressure ratio is pressure measured prior to inlet of low pressure turbine **46** as related to the pressure at the outlet of the low pressure turbine **46** prior to an exhaust nozzle. The geared architecture **48** may be an epicycle gear train, such as a planetary gear system or other gear system, with a gear reduction ratio of greater than about 2.3:1 and less than about 5:1. It should be understood, however, that the above parameters are only exemplary of one embodiment of a geared architecture engine and that the present invention is applicable to other gas turbine engines including direct drive turbofans.

(26) A significant amount of thrust is provided by the bypass flow B due to the high bypass ratio. The fan section **22** of the engine **20** is designed for a particular flight condition—typically cruise at about 0.8 Mach and about 35,000 feet (10,668 meters). The flight condition of 0.8 Mach and 35,000 ft (10,668 meters), with the engine at its best fuel consumption —also known as “bucket cruise Thrust Specific Fuel Consumption (‘TSFCT’)”—is the industry standard parameter of lbm of fuel being burned divided by lbf of thrust the engine produces at that minimum point. “Low fan pressure ratio” is the pressure ratio across the fan blade alone, without a Fan Exit Guide Vane (“FEGV”) system. The low fan pressure ratio as disclosed herein according to one non-limiting embodiment is less than about 1.45. “Low corrected fan tip speed” is the actual fan tip speed in ft/sec divided by an industry standard temperature correction of $[(T_{\text{ram}} \text{ } ^\circ \text{R}) / (518.7^\circ \text{R})]^{\text{sup.}0.5}$. The “Low corrected fan tip speed” as disclosed herein according to one non-limiting embodiment is less than about 1150 ft/second (350.5 meters/second).

(27) The fan **42** includes at least one row **60** of airfoils or blades **62** that are circumferentially distributed about, and are supported by, a rotatable hub **64**. The row **60** of blades **62** can extend in a generally spanwise or radial direction R outwardly from the hub **64**. The radial direction R can be perpendicular to the engine axis A. The hub **64** is rotatable in a clockwise or counter-clockwise direction RR (FIG. 4) about the engine axis A such that the blades **62** deliver airflow to the bypass flow path B and core flow path C in operation. In the illustrative example of FIG. 1, the hub **64** is driven by the low pressure (or fan drive) turbine **46** through the geared architecture **48**. A spinner or nosecone **65** is supported relative to the hub **64** to provide an aerodynamic inner flow path into the fan section **22**.

(28) The fan section **22** includes at least one row **66** of turning or fan exit guide vanes **68**. The guide vanes **68** are positioned in the bypass flow path B axially aft of the row **60** of blades **62** relative to the engine axis A. The row **66** of guide vanes **68** extend in the radial direction R across the bypass flow path B between the fan (e.g., first) case **15** and a core engine (e.g., second case) **17**. The fan case **15** includes a bypass (e.g., first) duct **19** surrounding the row **60** of blades **62** and the row **66** of guide vanes **68** to establish the bypass flow path B. The engine case **17** is dimensioned to extend about and along the engine axis A to at least partially surround and house the compressors **44**, **52**, combustor **56** and turbines **46**, **54**. The fan case **15** and engine case **17** establish a portion of the engine static structure **36**.

(29) The engine case **17** includes a flow splitter **70** situated downstream and axially aft of the row **60** of blades **62** relative to the engine axis A. The flow splitter **70** can have a generally V-shaped cross sectional geometry and is arranged to divide airflow communicated from the row **60** of blades **62** between the bypass flow path B and a second duct **21** establishing the core flow path C. The second duct **21** can serve as an entrance or inlet to the compressor section **24** and is bounded by the flow splitter **70**.

(30) Referring to FIGS. 2-3, with continuing reference to FIG. 1, each of the blades **62** includes an

airfoil body **62A** that extends in the radial direction **R** from the hub **64** (FIG. **1**) between a root **62R** coupled to the hub **64** and a tip **62T**. Each airfoil body **62A** extends axially in an axial or chordwise direction **H** between a leading edge **62LE** and a trailing edge **62TE**, and extends circumferentially in a thickness or circumferential direction **T** between a pressure side **62P** and a suction side **62S**. The directions **R**, **H**, **T** are perpendicular to each other. The chordwise direction **H** can be substantially parallel or transverse to the engine axis **A**. The radial direction **R** can have a major component that extends generally from or toward an axis of rotation of the blades **62**, which in the illustrated example coincides with the engine axis **A**. It should be understood that the radial direction **R** can include a minor component in the axial and/or circumferential directions **H**, **T** such that the blades **62** have a predefined amount of sweep and/or lean, for example.

(31) The airfoil body **62A** has an exterior airfoil surface **62E** providing a contour that extends in the chordwise direction **H** between the leading and trailing edges **62LE**, **62TE**. The exterior airfoil surface **62E** generates lift based upon its geometry and directs flow along the core flow path **C** and bypass flow path **B**. Each blade **62** can be constructed from a composite material, a metallic material such as steel, an aluminum or titanium alloy, or a combination of one or more of these. Abrasion-resistant coatings or other protective coatings may be applied to the blade **62**.

(32) Referring to FIGS. **2** and **4**, with continuing reference to FIGS. **1** and **3**, each of the guide vanes **68** includes an airfoil body **68A** that extends in the radial direction **R** between inner and outer surfaces **19A**, **19B** of the duct **19**, axially in the chordwise direction **H** between a leading edge **68LE** and a trailing edge **68TE**, and circumferentially in the thickness direction **T** between a pressure side **68P** and a suction side **68S**. The inner surfaces **19A** of the first duct **19** can be provided by the engine case **17** at a location downstream of the flow splitter as illustrated in FIG. **1**.

(33) The airfoil body **68A** has an exterior airfoil surface **68E** providing a contour that extends in the chordwise direction **H** between the leading and trailing edges **68LE**, **68TE**. The exterior airfoil surface **68E** can be contoured to direct airflow **F** (FIGS. **2A**, **2B**) compressed by the blades **62** through a gas path such as the bypass flow path **B**. The guide vanes **68** can be constructed from a composite material, a metallic material such as steel, an aluminum or titanium alloy, or a combination of one or more of these. The guide vanes **68** can serve as a structural component to transfer loads between the fan case **15** and the engine case **17** or another portion of the engine static structure **36**. The fan section **22** of FIG. **1** includes a single stage fan **42** having only one row **60** of blades **62** and only one row **66** of guide vanes **68**. In other examples, the fan section **22** has more than one row of blades **62** and/or guide vanes **68** configured with respect to any of the quantities disclosed herein.

(34) FIGS. **3-4** schematically illustrate span positions of a blade **62** and guide vane **68**, respectively. Span positions are schematically illustrated from 0% to 100% in 25% increments, for example, to define a plurality of sections **62C** of the blade **62** and a plurality of sections **68C** of the guide vane **68**. Each section **62C**, **68C** at a given span position is provided by a conical cut that corresponds to the shape of segments of the respective gas path, such as the bypass flowpath **B** or core flow path **C**, as shown by the large dashed lines.

(35) In the case of a blade **62** with an integral platform, the 0% span position (or zero span) corresponds to the generally radially innermost location where airfoil body **62A** meets the fillet joining the airfoil body **62A** to an adjacent platform **69** (see also FIG. **1**). In the case of a blade **62** without an integral platform, the 0% span position corresponds to the generally radially innermost location where the discrete platform **69** meets the exterior blade surface **62E** of the airfoil body **62A**. A 100% span position (or full span) corresponds to a section **62C** of the blade **62** at the tip **62T**. The 50% position (or midspan) corresponds to a generally radial position halfway between the 0% and 100% span positions.

(36) The 0% span position of the vane **68** can correspond to the generally radially innermost location where the exterior surface **68E** of the airfoil body **68A** meets the inner surfaces **19A** of the duct **19**. The 100% span position can correspond to the generally radially outermost location where

the exterior surface **68E** of the airfoil body **68A** meets the outer surfaces **19B** of the duct **19**. The 50% span position (or midspan) corresponds to a generally radial position halfway between the 0% and 100% span positions. As illustrated in FIGS. 2A and 2B, each blade **62** is sectioned at a first generally radial position between the root **62R** and the tip **62T**, and each vane **68** is sectioned at a second generally radial position between the inner and outer surfaces **19A**, **19B** of the duct **19**. The first and second radial positions can be the same (e.g., both at 25%, 50% or 100% span) or can differ (e.g., one at 50% and the other at 100% span).

(37) Airfoil geometric shapes, stacking offsets, chord profiles, stagger angles, axial sweep and dihedral angles, tangential lean angles, bow, and/or other three-dimensional geometries, among other associated features, can be incorporated individually or collectively into the blades **62** and/or guide vanes **68** to improve various characteristics such as aerodynamic efficiency, structural integrity, and vibration mitigation.

(38) Referring to FIG. 2A, the blades **62** and guide vanes **68** can be arranged at various orientations relative to the engine axis A. Each blade **62** establishes a chord dimension BCD. Each vane **68** establishes a chord dimension VCD. The chord dimension BCD/VCD is a length between the respective leading and trailing edges **62LE/68LE**, **62TE/68TE**. The chord dimension BCD/VCD may vary along the span of the airfoil body **62A/68A**. The chord BCD/VCD forms a respective stagger angle α/β relative to the chordwise direction H or a plane parallel to the engine axis A.

(39) The stagger angles α , β can vary along the airfoil span to define a twist. For example, the blades **62** and guide vanes **68** in FIG. 2A may be at a first span position, such as at 0% span, and the blades **62** and guide vanes **68** in FIG. 2B may be at a second, different span position, such as at 100% span. Referring to FIG. 2B, the stagger angle α of the blades **62** is larger at 100% span than the stagger angle α of the blades **62** corresponding to the span position of FIG. 2A. In examples, the stagger angle α of the blade **62** is greater than or equal to about 5 degrees at 0% span, or more narrowly less than or equal to about 40 degrees, such as between about 10 and 30 degrees at 0% span. In examples, the stagger angle α is less than or equal to about 70 degrees at 100% span, or more narrowly less than or equal to about 60 degrees, such as between about 30 and 50 degrees at 100% span.

(40) The stagger angle β of the vane **68** can be substantially the same from 0% span to 100% span or can differ. In examples, the stagger angle β is greater than or equal about 10 degrees at 0% span, or more narrowly less than or equal to about 60 degrees, such as between about 20 and 40 degrees at 0% span. In examples, the stagger angle β is less than or equal about degrees at 100% span, or more narrowly less than or equal to about 60 degrees, such as between about 30 and 50 degrees at 100% span.

(41) Each of the blades **62** can be cambered. A mean camber line **62M** bisects the airfoil body **62A** between the leading and trailing edges **62LE**, **62TE** of the blade **62**. A leading edge metal angle $\alpha1^*$ at the leading edge **62LE** and a trailing edge metal angle $\alpha2^*$ at the trailing edge **62TE** are established with respect to the mean camber line **62M** and the chordwise direction H. The tip **62T** of the blade **62** can rotate at a relatively faster speed, and the stagger of the blade **62** can be aligned with a relative flow direction F' to achieve an optimum incidence of the flow F relative to the leading edge metal angle $\alpha1^*$ of the blade **62**. A camber $\kappa1$ of the blade **62** is equal to a difference between the leading edge metal angle $\alpha1^*$ and the trailing edge metal angle $\alpha2^*$. In the illustrative example of FIGS. 2A-2B, the camber $\kappa1$ of the blade **62** can be substantially less at 100% span (FIG. 2B) than the camber $\kappa1$ of the blade **62** at less than 100% span (FIG. 2A). The camber $\kappa1$ of the airfoil body **62A** contour that extends in the chordwise direction H between the leading and trailing edges **62LE**, **62TE** of the blade **62** can be less than or equal to about 80 degrees at 0% span, or more narrowly less than or equal to about 70 degrees, such as between about 40 and 60 degrees at 0% span. The camber $\kappa1$ can be greater than or equal to about 5 degrees at 100% span, or more narrowly less than or equal to about 50 degrees, such as between about 10 and 40 degrees at 100% span.

(42) Each of the vanes **68** can be cambered. A mean camber line **68M** bisects the airfoil body **68A** between the leading and trailing edges **68LE**, **68TE** of the vane **68**. A leading edge metal angle $\beta 1^*$ at the leading edge **68LE** and a trailing edge metal angle $\beta 2^*$ at the trailing edge **68TE** are established with respect to the mean camber line **68M** and the chordwise direction H. A camber $\kappa 2$ of the vane **68** is equal to a difference between the leading edge metal angle $\beta 1^*$ and the trailing edge metal angle $\beta 2^*$. The camber $\kappa 2$ of the airfoil body **68A** contour that extends in the chordwise direction H between the leading and trailing edges **68LE**, **68TE** of the vane **68** can be greater than or equal to about 5 degrees at 0% span, or more narrowly less than or equal to about 50 degrees, such as between about 10 and 40 degrees at 0% span. The camber $\kappa 2$ can be less than or equal to about 80 degrees at 100% span, or more narrowly less than or equal to about 70 degrees, such as between about 40 and 60 degrees at 100% span. For the purposes of this disclosure, the terms “about” and “approximately” mean $\pm 3\%$ of the stated value unless otherwise indicated.

(43) FIG. 5 illustrates a gas turbine engine **120** according to another example. In this disclosure, like reference numerals designate like elements where appropriate and reference numerals with the addition of one-hundred or multiples thereof designate modified elements that are understood to incorporate the same features and benefits of the corresponding original elements. The engine **120** includes a fan section **122** including a fan (or rotor) **142**, a compressor section **124**, a combustor section **126** and a turbine section **128**. The compressor, combustor and turbine sections **124**, **126**, **128** establish respective portions of the core flow path C. The turbine section **128** drives the fan section **122** and the compressor section **124**. The compressor section **124** includes a low pressure compressor **144** and a high pressure compressor **152**. The turbine section **128** includes a low pressure (or fan drive) turbine **146** and a high pressure turbine **154**.

(44) The fan **142** includes at least one row **160** of blades **162** carried by and mounted to a rotatable hub **164**. In examples, the blades **162** are incorporated into a fixed-pitch arrangement in which the blades **162** have a fixed stagger angle α . In other examples, the blades **162** are incorporated into a variable-pitch arrangement in which the stagger angle α varies in response to rotation of the blades **162** about a respective blade axis that extends between the blade root **162R** and tip **162T**.

(45) The engine **120** can include a geared architecture **148** that drives the fan **142** at a different speed than a speed of the fan drive turbine **146** in operation. In examples, the geared architecture **148** is an epicyclic gear system such as a planetary gear system having a fixed ring gear and a rotatable carrier, or such as a star gear system having a fixed carrier and a rotatable ring gear. The geared architecture **48** can establish a gear reduction ratio of greater than about 2.3 or 2.6, or more narrowly less than about 4.0 or 5.0, for example. In other examples, the geared architecture **148** is omitted such that the fan drive turbine **146** directly drives the fan **142** at a common speed and in a common direction.

(46) The fan section **122** includes a fan (e.g., first) case **115** including a bypass (e.g., first) duct **119** surrounding the row **160** of blades **162** to establish a bypass (e.g., first) flow path B. The engine **120** includes an engine (e.g., second) case **117** that establishes a core (e.g., second) flow path C.

(47) The engine **120** can include a nacelle **123** and core cowling (or housing) **125**. The nacelle **123** is mechanically attached or otherwise secured to the fan case **115** and establishes an engine inlet **1231**. The engine inlet **1231** conveys airflow F to the fan **142** in operation. The core cowling **125** is mechanically attached or otherwise secured to the engine case **117**. The core cowling **125** at least partially surrounds the engine case **117**. The bypass flow path B terminates at a bypass exit (or nozzle) **131** established by a trailing edge of the nacelle **123**.

(48) At least one row **166** of turning or fan exit guide vanes **168** are situated in the bypass duct **119**. The guide vanes **168** extend in a radial direction R across the bypass flow path B. Each guide vane **168** extends in the radial direction R between a 0% span position along an inner surface **119A** and a 100% span position along an outer surface **119B** of the bypass duct **119**.

(49) An airfoil body **168A** of the guide vane **168** extends along a longitudinal axis LA, as illustrated in FIG. 8C. A projection of the longitudinal axis LA intersects the engine axis A to

establish a vane angle ϕ . The vane angle ϕ can be approximately 90 degrees such that the guide vane is substantially perpendicular to the engine axis A, as illustrated by the guide vane **68** of FIG. **1**. In examples, the vane angle ϕ is less 90 degrees such that the guide vane has a component that extends aftwards in the axial direction from 0% to 100% span with respect to the engine axis A, as illustrated by the guide vane **168** of FIG. **8A**. The vane angle ϕ can be greater than or equal to 15 degrees, or more narrowly between 30 and 60 degrees, for example.

(50) Various quantities of blades **162** and guide vanes **168** can be incorporated into the engine **120**. The row **160** of blades **162** establishes a blade quantity (BQ). The row **166** of guide vanes **168** establishes a vane quantity (VQ), which can be the same or can differ from the blade quantity (BQ). The blade quantity (BQ) can be less than 24 or 26 blades, or more narrowly at least 12 but not more than 20 blades, such as 14 or 16 blades, for example. The vane quantity (VQ) can be no more than 40 guide vanes, or more narrowly at least 20 guide vanes, for example. In examples, the ratio of VQ/BQ is between 2.0 and 2.6, or more narrowly between 2.2 and 2.5, which may reduce noise due to flow interaction between the blades **162** and guide vanes **168**. For the purposes of this disclosure, the term “between” is inclusive of the stated value(s) unless otherwise stated.

(51) Various stage counts can be incorporated in the compressors **144**, **152** and turbines **146**, **154**. For example, the low pressure compressor **144** can include at least 3 but no more than 5 compressor stages, such as 3 compressor stages as illustrated by FIGS. **1** and **5**. In examples, the low pressure turbine **146** includes at least 3 but no more than 6 turbine stages, such as 3 turbine stages as illustrated by FIG. **5**, 4 turbine stages, or 5 turbine stages as illustrated by FIG. **1**. The high pressure turbine **154** can include a single stage, or can include two stages as illustrated by FIGS. **1** and **5**, for example. A ratio between the blade quantity (BQ) and a quantity of the stages of the low pressure turbine **146** can be between about 3.3 and about 8.6, or more narrowly less than or equal to about 4.0, such as about 3.5. The example low pressure turbine **146** provides the driving power to rotate the fan **142** and therefore the relationship between the number of turbine stages of the low pressure turbine **146** and the blade quantity (BQ) disclose an example gas turbine engine **120** with increased power transfer efficiency.

(52) The engine **120** includes a core bypass (or third) duct **127** established between the engine case **117** and core cowling **125**. The core bypass duct **127** establishes an intermediate (or third) flow path I. The core bypass duct **127** can be a separate and distinct structure or can be established by a volume of the core engine bay between the engine core and core cowling **125**. The core bypass duct **127** can be coupled to an annular core vent port (or nozzle) **129** established along an outer periphery of the core cowling **125**. In the illustrated example of FIG. **5**, the guide vanes **168** are an axially aftmost row of fan exit guide vanes in the bypass flow path B between the row **160** of blades **162** and the bypass exit **131** relative to the engine axis A. In other examples, one or more rows of vanes are arranged in the bypass flow path B axially forward and/or aft of the row **166** of guide vanes **168**. The hub **164** is rotatable about the engine axis A such that the row **160** of blades **162** deliver or convey airflow to the bypass, intermediate and core flow paths B, I, C in operation.

(53) The engine **120** includes a first flow splitter **170** and a second flow splitter **172** arranged in a cascade. The flow splitters **170**, **172** are situated downstream and axially aft of the row **160** of blades **162** relative to the engine axis A. The first flow splitter **170** can be incorporated into or mechanically attached to the core cowling **125**. The second flow splitter **172** can be incorporated into or mechanically attached to the engine case **117**. The first flow splitter **170** establishes a portion of the bypass duct **119** and a portion of the second duct **121**. The second flow splitter **172** establishes a portion of the second duct **121** and a portion of an entrance (e.g., fourth) duct **133**. The entrance duct **133** can establish an entrance or inlet to the compressor section **124**.

(54) The first flow splitter **170** is arranged to divide airflow conveyed by the row **160** of blades **162** between the bypass flow path B and the second duct **121**. The second flow splitter **172** is radially inboard of the first flow splitter **170** relative to the engine axis A. The second duct **121** branches between the core flow path C and the intermediate flow path I at the second flow splitter **172**. The

second flow splitter **172** is arranged to divide airflow conveyed to the second duct **121** between the intermediate flow path I and the core flow path C along the entrance duct **133**. The flow splitters **170**, **172** can have a generally V-shaped cross sectional geometry dimensioned to divide the airflow.

(55) A bypass port **174** is established along an outer periphery **125P** of the core cowling **125**. The bypass port **174** interconnects the intermediate flow path I and bypass flow path B at a position downstream of the row **166** of guide vanes **168** relative to a general direction of airflow through the bypass flow path B such that airflow conveyed by the intermediate flow path I through the bypass port **174** bypasses or otherwise is not communicated across the guide vanes **168** in operation. The bypass port **174** can interconnect the intermediate flow path I and bypass flow path B at a position axially aft of the 0% span position of the row **166** of guide vanes **168** relative to the engine axis A. In the illustrated example of FIG. 5, the vent port **129** is established downstream and axially aft of both the bypass port **174** and the bypass exit **131** relative to the engine axis A. In other examples, the vent port **129** is established upstream and axially forward of the bypass exit **131** such that airflow in the bypass flow path B mixes in the bypass duct **119** with airflow conveyed by the vent port **129** prior to exiting the bypass exit **131**.

(56) One or more louvers **176** can be situated in the bypass port **174**. The louvers **176** can have a generally airfoil-shaped cross sectional geometry and are arranged to direct airflow from the intermediate flow path I into the bypass flow path B in a direction generally downstream of the guide vanes **168** and toward the bypass exit **131**.

(57) The engine **120** can establish an adaptive fan flow arrangement in which a relative distribution of airflow conveyed by the fan **142** to the flow paths B, I and/or C varies during one or more modes. One or more blocker doors **184** can be moved between opened and closed positions to selectively communicate airflow through the bypass port **174** (open and closed positions indicated in dashed lines at **184**, **184'** of FIG. 8A for illustrative purposes).

(58) In the illustrative example of FIG. 6, the engine **120** includes one or more blocker doors **178** situated in the core bypass duct **127** to modulate airflow through the intermediate flow path I. The blocker doors **178** are situated in the intermediate flow path I downstream of the bypass port **174**. The blocker doors **178** are moveable between a closed position (FIG. 5) and an open position (FIG. 6) to selectively communicate airflow in the intermediate flow path I downstream to the vent port **129**. The blocker doors **178** at least partially or substantially block airflow through the intermediate flow path I in the closed position. In the illustrative example of FIGS. 5-6, the blocker doors **178** are pivotable flaps having a pivot point established along the core bypass duct **127**. It should be understood that other arrangements can be utilized to selectively communicate airflow downstream to the vent port **129**.

(59) Referring to FIGS. 7A-7C, with continuing reference to FIGS. 5-6, the nacelle **123** can include at least one thrust reverser **180** and/or a variable area fan nozzle (VAFN) **182** for adjusting various characteristics of the bypass flow. FIG. 7A illustrates the thrust reverser **180** and the variable area fan nozzle **182** in stowed positions. FIG. 7B illustrates the thrust reverser **180** in the stowed position and the variable area fan nozzle **182** in a deployed position. FIG. 7C illustrates the thrust reverser **180** in a deployed position and the variable area fan nozzle **182** in the stowed position. The nacelle **123** includes a stationary portion **123-1** mounted to the fan case **115**, a first moveable portion **123-2** and a second movable portion **123-3**. The moveable portions **123-2**, **123-3** are moveable relative to the stationary portion **123-1** and relative to each other.

(60) The thrust reverser **180** is operable to convey airflow in the bypass flow path B for producing reverse thrust such as during approach and/or landing conditions of an aircraft associated with the engine **120**. The thrust reverser **180** includes a thrust reverser body **180B**, which is configured with the first moveable portion **123-2** of the nacelle **123**. The thrust reverser body **180B** may have a generally tubular geometry. The thrust reverser **180** can include one or more blocker doors **180D**, one or more actuators **180A**, and/or one or more cascades **180C** of turning vanes **180V** arranged

circumferentially about the engine axis A.

(61) The thrust reverser body **180B** can include at least one recess **180R** that houses the cascades **180C** and the actuators **180A** when the thrust reverser **180** is in the stowed position. The cascades **180C** are dimensioned to span across a reversal port **180P** when the thrust reverser **180** is in the deployed position, as illustrated by FIG. 7C. The cascade **180C** selectively communicates airflow from the bypass duct **119** outwardly through the reversal port **180P** in the deployed position. The cascade **180C** can extend axially aft of both the row **166** of guide vanes **168** and the bypass port **174** with respect to the engine axis A, and the row **168** of guide vanes **168** can be situated axially forward of the blocker doors **180D** relative to the engine axis A, as illustrated by FIGS. 5-6.

(62) Each blocker door **180D** is pivotally connected to the thrust reverser body **180B**. The bypass port **174** can be established axially forward of the blocker doors **180D** with respect to the engine axis A, as illustrated in FIGS. 5-6. The actuators **180A** are operable to axially translate the thrust reverser body **180B** between the stowed and deployed positions. As the thrust reverser body **180B** translates aftwards, the blocker doors **180B** pivot radially inward into the bypass duct **119** and divert at least some or substantially all of the bypass airflow F as flow F1 through the cascades **180C** to provide the reverse engine thrust, as illustrated in FIG. 7C. In other examples, the cascades **180C** are configured to translate axially with a respective thrust reverser body **180B**. The thrust reverser body **180B** and/or cascades **180C** can include one or more circumferential segments that synchronously or independently translate or otherwise move between deployed and stowed positions.

(63) The variable area fan nozzle **182** includes a nozzle body **182B** and one or more actuators **182A**. The nozzle body **182B** is configured with the second movable portion **123-3** of the nacelle **123**, and is arranged radially within and may nest with the thrust reverser body **180B**. The nozzle body **182B** may have a generally tubular geometry that extends about an axially contoured outer periphery **125P** of the core cowling **125**. The actuators **182A** are operable to axially translate the nozzle body **182B** between the stowed position of FIG. 7A and the deployed position of FIG. 7B. As the nozzle body **182B** translates aftwards, a radial distance RD of the bypass exit **131** between a trailing edge or aft end **123TE** of the nacelle **123** and the outer periphery **125P** of the core cowling **125** established at the stowed position may change (e.g., increase) to a radial distance RD' and thereby change (e.g., increase) a flow area of the bypass exit **131**. In this manner, the variable area fan nozzle **182** may adjust a pressure drop or ratio across the bypass flowpath B defined by the bypass duct **119** by changing the flow area of the bypass exit **131**.

(64) The variable area fan nozzle **182** can define or otherwise include at least one auxiliary port **182P** to vary the bypass flow. The auxiliary port **182P** can be established in the nozzle body **182B**, as illustrated by FIGS. 7A-7C. The auxiliary port **182P** is moveable relative to a trailing edge portion **123P** of the first moveable portion **123-1** of the nacelle **123** to selectively block and open the auxiliary port **182P**. The auxiliary port **182P** is opened as the nozzle body **182B** translates axially aftwards relative to the engine axis A. A flow area through the auxiliary port **182P** augments the flow area of the bypass exit **131**, thereby increasing an effective flow area of the variable area fan nozzle **182**. The variable area fan nozzle **182** therefore may adjust a pressure drop or ratio across the bypass flowpath B defined by the bypass duct **119** while translating the nozzle body **182B** over a relatively smaller axial distance. In the illustrative example of FIGS. 5-6, the variable area fan nozzle **182** is omitted.

(65) Referring to FIG. 8A, with continuing reference to FIG. 5, the blades **162** can be dimensioned to provide a relatively radially compact engine arrangement. Each of the blades **162** extends in the radial direction R between a 0% span position at the hub **164** and a 100% span position at a tip **162T**. A tip radius RT of the blades **162** is established between a radially outermost portion of the tip **162T** and the engine axis A. A forwardmost portion of a leading edge **162LE** of each the blades **162** is arranged along a first reference plane REF1. The first reference plane REF1 is perpendicular to the engine axis A. A hub radius RH is established along the first reference plane REF1 between

an outer periphery of the hub **164** and the engine axis A. The tip radius RT can be between 35 and 60 inches, or more narrowly between 40 and 55 inches, for example.

(66) Each of the blades **162** extends in the radial direction R between the 0% span position and the 100% span position to establish a geometric hub-to-tip ratio (RH:RT). The hub-to-tip ratio (RH:RT) can be less than or equal to about 0.4, or more narrowly greater than or equal to about 0.1, measured relative to the forwardmost portion of the leading edge **162LE** of the blades **162**. In examples, the hub-to-tip ratio (RH:RT) is between 0.16-0.36, or more narrowly between 0.2-0.3. In examples, the hub-to-tip ratio (RH:RT) is established such that a maximum value of the fan pressure ratio across the blade **162** alone is less than or about equal to about 1.45 measured at cruise at 0.8 Mach and 35,000 feet. In further examples, a maximum value of the fan pressure ratio is greater than or equal to about 1.1, or more narrowly less than or equal to about 1.35. The fan pressure ratios and hub-to-tip ratios disclosed herein can be utilized alone or in combination to establish relatively high bypass turbo fan engine arrangements.

(67) The flow splitters **170**, **172** are arranged at respective positions relative to each other and the row **160** of blades **162** to establish a predetermined distribution of airflow through the bypass, intermediate and core flow paths B, I, C in operation. A forwardmost edge **170F** of the first flow splitter **170** is situated in the radial and axial directions R, H at a first splitter position P1 relative to the engine axis A. The first splitter position P1 is established along a second reference plane REF2. A forwardmost edge **172F** of the second flow splitter **172** is situated in the radial and axial directions R, H at a second splitter position P2 relative to the engine axis A. The second splitter position P2 is established along a third reference plane REF3. The reference planes REF2, REF3 are perpendicular to the engine axis A.

(68) The reference planes REF2, REF3 can be established at the same position, or at different positions relative to the engine axis A to establish a cascade arrangement. For example, the forwardmost edge **172F** of the second flow splitter **172** can be axially aft of the forwardmost edge **170F** of the first flow splitter **170** with respect to the engine axis A. The forwardmost edges **170F**, **172F** of the flow splitters **170**, **172** are axially forward of the leading edges **168LE** of the row **166** of guide vanes **168** at the 0% span position with respect to the engine axis A. The forwardmost edges **170F**, **172F** can be dimensioned to extend axially forward of the geared architecture **148** relative to the engine axis A, as illustrated by FIG. 8A, which can establish a relatively compact core engine arrangement.

(69) Referring to FIG. 8B, with continuing reference to FIG. 8A, a first annulus area A1 is established by, and between, inner and outer diameter surfaces **119A**, **119B** of the bypass duct **119** at the forwardmost edge **170F** of the first flow splitter **170**. A second annulus area A2 is established by, and between, inner and outer diameter surfaces **121A**, **121B** of the second duct **121** at the forwardmost edge **170F** of the first flow splitter **170**. A third annulus area A3 is established by, and between, inner and outer diameter surfaces **133A**, **133B** of the entrance duct **133** at the second flow splitter **172**. The annulus areas A1, A2, A3 extend about the engine axis A to establish a portion of the respective flow paths B, I, C.

(70) The annulus areas A1, A2, A3 can be dimensioned to establish a predetermined distribution of airflow to the flow paths B, I, C in operation. A first geometric bypass area ratio (A1:A2) associated with the first flow splitter **170** is defined as the first annulus area A1 divided by the second annulus area A2. A second geometric bypass area ratio (A1:A3) associated with the second flow splitter **172** is defined as the first annulus area A1 divided by the third annulus area A3. The annulus areas A1, A2, A3 can be dimensioned to establish a predetermined value of the first bypass area ratio (A1:A2) and a predetermined value of the second bypass area ratio (A1:A3). In examples, the first bypass area ratio (A1:A2) is greater than or equal to about 10 to establish a relatively high bypass turbo fan arrangement. In examples, the first bypass area ratio (A1:A2) is less than or equal to about 35, or more narrowly less than or equal to about 20. The second bypass area ratio (A1:A3) is greater than the first bypass area ratio (A1:A2). For example, a value of the

second bypass area ratio ($A1:A3$) can be between about 150-250% of the first bypass area ratio ($A1:A2$), such as approximately twice or 200% of the first bypass area ratio ($A1:A2$). In examples, the second bypass area ratio ($A1:A3$) is greater than or equal to about 15, or more narrowly greater than or equal to about 20.

(71) Referring back to FIG. 8A, the forwardmost edges **170F**, **172F** of the flow splitters **170**, **172** can be dimensioned relative to a span of the blades **162** to establish the predetermined distribution of airflow through the bypass, intermediate and core flow paths B, I, C in operation. In examples, the first splitter position **P1** can be radially aligned with or radially inward of a 25% span position of the blades **162**, or more narrowly can be radially aligned with or radially outward of a 10% span position of the blades **162** relative to the radial direction R, such as between about 16-22% span. The second splitter position **P2** can be radially aligned with or radially outward of a 5% span position of the blades **162**, or more narrowly can be radially aligned with or radially inward of a 15% span position of the blades **162** relative to the radial direction R, such as between about 8-13% span. The splitter positions **P1**, **P2** can be established at a radial distance of at least 5% span apart from each other relative to the blades **162** such that a relatively larger amount of airflow is communicated to the intermediate flow path I and bypasses the guide vanes **168**. In examples, the radial distance between the splitter positions **P1**, **P2** is between about 6-12% span, relative to the blades **162**. The blades **162** can have any of the stagger angles α and/or camber κ values disclosed herein at the respective spanwise positions of the first splitter position **P1** and/or second splitter position **P2** to convey airflow in a predetermined direction towards the splitters **170**, **172**, which can improve efficiency.

(72) The guide vanes **168** and flow splitters **170**, **172** can be arranged relative to the fan blades **162** to establish a relatively axially compact envelope. The leading edges **162LE** of the blades **162** at the 100% span position are established along a fourth reference plane REF4. The leading edges **168LE** of the guide vanes **168** at the 100% span position are established along a fifth reference plane REF5. The reference planes REF4, REF5 are perpendicular to the engine axis A. A first axial length L1 is established between the reference planes REF4, REF5. In examples, a ratio ($L1:RT$) of the first axial length L1 divided by the tip radius RT is greater than or equal to about 0.5, which can reduce fan noise propagation through the bypass flow path B. The ratio ($L1:RT$) can be less than or equal to about 0.75, which can establish a relatively axially compact fan section. A second axial length L2 is established between the first and second splitter positions **P1**, **P2** along the reference planes REF2, REF3 relative to the engine axis A. In examples, a ratio ($L2:L1$) of the second axial length L2 divided by the first axial length L1 is less than or equal to about 0.5, or more narrowly between about 0.1 and about 0.3, which can further establish a relatively axially compact engine.

(73) FIG. 9A illustrates a plot of bypass area ratio relative to airfoil span position, such as span positions of the blades **162**. FIG. 9B illustrates selected portions of FIG. 9A. Example profiles or curves C1-C6 are shown. The curves C1-C6 correspond to fan or rotor arrangements having hub-to-tip ratios ($RH:RT$) of 0.16, 0.20, 0.24, 0.28, 0.32, 0.36, respectively. The fan **142** can be dimensioned to establish any of the hub-to-tip ratios ($RH:RT$) and corresponding values along the curves C1-C6.

(74) Each curve C1-C6 can be established as function of annulus area associated with respective bypass area ratios. Splitter position values for each % span position along the respective curve C1-C6 can be defined in one of the following ways:

$$\% \text{ span position} = [(MR - RH) / (RT - RH)] * 100 \quad \text{Equation 1}$$

$$\% \text{ span position} = [(MR/RT - \lambda) / (1 - \lambda)] * 100 \quad \text{Equation 2}$$

where (MR) is the radial splitter position of the respective splitter **170**, **172**, (RH) is the hub radius and (RT) is the tip radius as previously defined, and (λ) is the hub-to-tip ratio ($RH:RT$). Since the annulus areas established by the splitters are non-linear, the corresponding curves C1-C6 are also non-linear.

(75) The plot of curves C1-C6 can serve as a nomograph utilized to select radial locations of the

first and second positions **P1**, **P2** of the flow splitters **170**, **172** with respect to hub-to-tip (RH:RT) ratio and/or bypass area ratio (**A1:A2**), (**A1:A3**), or vice versa. For example, referring to FIG. **9B**, the fan **142** can establish a hub-to-tip (RH:RT) ratio of 0.16 corresponding to the curve **C1**. The radial location of the first and second splitter positions **P1**, **P2** of the flow splitters **170**, **172** correspond to points **P1.sub.(0.16)**, **P2.sub.(0.16)** selected along the curve **C1**. The points **P1.sub.(0.16)**, **P2.sub.(0.16)** can be selected with respect to a predetermined bypass area ratio. For example, point **P1.sub.(0.16)** of the first flow splitter **170** can be established in the radial direction **R** at about a 21.5% span position of the blades **162**. Point **P1.sub.(0.16)** corresponds to a first bypass area ratio (**A1:A2**) of about 10 and a mass average fan pressure ratio of about 1.260. The radial location of the second flow splitter **172** can be determined by assuming analytically that the second flow splitter **172** is the first flow splitter **170** (e.g., a single flow splitter arrangement). The point **P2.sub.(0.16)** of the second flow splitter **172** can be established in the radial direction **R** at about a 13.1% span position of the blades **162**. Point **P2.sub.(0.16)** corresponds to a second bypass area ratio (**A1:A3**) of about 20 and a mass average fan pressure ratio of about 1.225. For the purposes of this disclosure, mass average fan pressure ratio is defined as an average pressure ratio across the blades **162** alone measured at cruise at 0.8 Mach and 35,000 feet between the 0% span position and the corresponding span position of the respective splitter **170**, **172**. The mass across the blades **162** associated with the mass average fan pressure ratio is approximately equal to the amount of the mass captured by the respective splitter **170**, **172**.

(76) As another example, the fan **142** can establish a hub-to-tip (RH:RT) ratio of 0.36 corresponding to the curve **C6**. The radial location of the first and second splitter positions **P1**, **P2** of the flow splitters **170**, **172** correspond to points **P1.sub.(0.36)**, **P2.sub.(0.36)** selected along the curve **C6**. Point **P1.sub.(0.36)** of the first flow splitter **170** can be established in the radial direction **R** at about a 15.5% span position of the blades **162**. Point **P1.sub.(0.36)** corresponds to a first bypass area ratio (**A1:A2**) of about 10 and a mass average fan pressure ratio of about 1.260. Point **P2.sub.(0.36)** of the second flow splitter **172** can be established in the radial direction **R** at about a 7.6% span position of the blades **162**. Point **P2.sub.(0.36)** corresponds to a second bypass area ratio (**A1:A3**) of about 20 and a mass average fan pressure ratio of about 1.185.

(77) The flow splitters **170**, **172** and other portions of the fan section **122** can be dimensioned with respect to any other values along the curves **C1-C6**. For example, points **P1'.sub.(0.16)**, **P2'.sub.(0.16)** can be established along the curve **C1** at about 11.0% and about 7.6% span corresponding to first and second bypass area ratios (**A1:A2**), (**A1:A3**) of about 25 and 35, respectively. As another example, points **P1'.sub.(0.36)**, **P2'.sub.(0.36)** can be established along the curve **C6** at about 7.0% and about 5.5% span corresponding to first and second bypass area ratios (**A1:A2**), (**A1:A3**) of about 20 and 35, respectively.

(78) As illustrated by the curves **C1-C6** of FIGS. **9B**, for the same bypass area ratio, a lower hub-to-tip ratio (RH:RT) can result in the splitter positions **P1**, **P2** of the splitters **170**, **172** being relatively further away from the 0% span position of the blades **162**. The splitters **170**, **172** can be dimensioned with respect to relatively lower % span positions to establish relatively larger bypass area ratios, as illustrated by the curves **C1-C6** of FIG. **9B**.

(79) FIG. **10A** illustrates a plot of fan pressure ratio relative to airfoil span position, such as span positions of the blades **162**. FIG. **10B** illustrates selected portions of the plot of FIG. **10A**. Curve **PR1** corresponds to discrete fan pressure ratios at each span position. Lines **LP1.sub.(0.16)**, **LP2.sub.(0.16)** correspond to the splitter positions **P1.sub.(0.16)**, **P2.sub.(0.16)** of the splitters **170**, **172** associated with a hub-to-tip ratio (RH:RT) equal to 0.16. Lines **MA1.sub.(0.16)**, **MA2.sub.(0.16)** are the mass averaged fan pressure ratios corresponding to the respective splitter positions **P1.sub.(0.16)**, **P2.sub.(0.16)**. FIG. **10B** depicts a curve **PR1(NT)** representing a spanwise integration of the discrete fan pressure ratios of curve **PR1**. An intersection of the lines **LP1.sub.(0.16)**, **LP2.sub.(0.16)** corresponding to the points **P1.sub.(0.16)**, **P2.sub.(0.16)** and the curve **PR1(INT)** establish a position of the respective lines **MA1.sub.(0.16)**, **MA2.sub.(0.16)** relative to

the y-axis. In the illustrative example of FIGS. **10A-10B**, lines **MA1.sub.(0.16)**, **MA2.sub.(0.16)** correspond to mass average fan pressure ratios of 1.260 and 1.225, respectively, which correspond to values previously discussed with respect to the points **P1.sub.(0.16)**, **P2.sub.(0.16)** along the curve **C1** of FIG. **9B**.

(80) FIG. **11** illustrates another plot of fan pressure ratio relative to airfoil span position, such as span positions of the blades **162**. Curve **PR2** corresponds to discrete fan pressure ratios at each span position of the blade **162**. Lines **LP1.sub.(0.36)**, **LP2.sub.(0.36)** correspond to splitter positions **P1.sub.(0.36)**, **P2.sub.(0.36)** of the splitters **170**, **172** associated with a hub-to-tip ratio (**RH:RT**) equal to 0.36. In the illustrative example of FIG. **11**, lines **MA1.sub.(0.36)**, **MA2.sub.(0.36)** correspond to mass average fan pressure ratios of 1.260 and 1.185, respectively, which correspond to values previously discussed with respect to the points **P1.sub.(0.36)**, **P2.sub.(0.36)** along the curve **C6** of FIG. **9B**.

(81) The engine **120** can include a controller **CONT** (shown in dashed lines in FIG. **5** for illustrative purposes). The controller **CONT** is operable to cause the blocker doors **178**, **184**, thrust reverser **180** and variable area fan nozzle **182** to move between the various disclosed positions or modes. The controller **CONT** can include one or more computing devices, each having one or more of a computer processor, memory, storage means, network device and input and/or output devices and/or interfaces according to some example. The memory may, for example, include **UVROM**, **EEPROM**, **FLASH**, **RAM**, **ROM**, **DVD**, **CD**, a hard drive, or other computer readable medium which may store data and/or the algorithms corresponding to the various functions of this disclosure. In other examples, the controller **CONT** is an analog or electromechanical device configured to provide the disclosed functions of this disclosure. The controller **CONT** can be a portion of a full-authority digital electronic control **FADEC** or an electronic engine control (**EEC**), another system, or a stand-alone system located within the aircraft remote from the engine **120**.

(82) FIG. **12** illustrates a plurality of discrete modes **M1-M4** established by the position of the blocker door(s) **178** and position of the blocker door(s) **184** across the bypass port **174**. The controller **CONT** can be programmed with logic or otherwise configured to cause the engine **120** to execute each of the modes **M1-M4**. During modes **M1** and **M3**, the blocker doors **178** are stowed to establish an open position to at least partially communicate airflow through vent port **129**. During modes **M2** and **M4**, the blocker doors **178** are deployed to establish a closed position to at least partially block airflow from being communicated to the vent port **129**. During modes **M1** and **M2**, the bypass port **174** is open or uncovered to at least partially communicate airflow from the intermediate flow path **I** to the bypass flow path **B**. During modes **M3** and **M4**, the bypass port **174** is closed or covered to at least partially block airflow being communicated from the intermediate flow path **I** to the bypass flow path **B**. The engine **120** can be operated in the first mode **M1** during takeoff, for example, which may be associated with relatively lower engine inlet airflow such that the fan **142** communicates relatively more airflow which may improve fan stability.

(83) The engine **120** can be operated in the first mode **M1** and/or the second mode **M2** during cruise, for example. The engine **120** can be operated in the second mode **M2** during a beginning of climb condition to increase fan pressure ratio and generate relatively greater thrust. The thrust reverser **180** can be deployed during the second mode **M2**, for example, to increase an amount of airflow being communicated to the bypass flow path to the thrust reverser **180** for generating reverse thrust. The engine **120** can be operated in the third mode **M3** during a middle of climb condition (i.e., between beginning climb and top of climb). The engine **120** can be operated in the fourth mode **M4** during a top of climb condition to increase airflow to the core flow path **C** and bypass flow path **B** to maximize or otherwise increase thrust. The modes **M1-M4** are exemplary and it should be appreciated the blocker door(s) **178** and bypass port **174** can be configured to establish fewer or more than four modes.

(84) The controller **CONT** can be coupled to one or more sensors to determine any of the conditions disclosed herein, such as temperature, pressure and/or speed sensors operable to

measure various conditions or states of the engine **120**. Temperature and/or pressure sensors can be situated along the bypass, intermediate and/or core flow paths B, I, C, for example. Speed sensors can be situated adjacent to the rotors to determine a speed of the fan rotor, low spool, and/or high spool, for example. The controller CONT can utilize other data and information to determine any of the conditions disclosed herein, including aircraft velocity, altitude and throttle position. One would understand how to situate the sensors and program or otherwise configure the controller CONT with logic to obtain data and other information from the sensors and other systems in view of the teachings disclosed herein.

(85) The engine **120** can be operated as follows. Referring to FIG. 5, the fan **142** is driven by the fan drive turbine **146** such that the blades **162** deliver airflow to the bypass, intermediate and core flow paths B, I, C. Driving the fan **142** can include driving the hub **164** of the fan **142** through the geared architecture **148** at a different speed than a speed of the fan drive turbine **146**. The engine **120** can be operated in any of the modes disclosed herein, including the modes M1-M4 of FIG. 12. Airflow in the intermediate flow path I can be ejected from the bypass port **174** into the bypass flow path B to bypass the guide vanes **168**. One or more blocker doors **178** can be selectively moved between open and closed positions to at least partially block airflow from the intermediate flow path I being communicated downstream to the core bypass duct **127** and vent port **129**. One or more of the blocker doors **184** can be moved between open and closed positions to selectively communicate airflow through the bypass port **174** (**184** shown in dashed lines in FIG. 8A for illustrative purposes).

(86) Referring to FIG. 6, an operating line of the fan **142** at an operating condition such as takeoff can be shifted relatively further away from the stall line by upflowing the fan **142** in response to selectively communicating airflow to the vent port **129**. One or more of the blocker doors **178** can be selectively moved to the open position to communicate airflow in the intermediate flow path I downstream to the vent port **129**. Airflow communicated to the core bypass duct **127** can be ejected from the vent port **129** downstream of the bypass port **174** and/or bypass exit **131**.

(87) The disclosed splitter arrangements can improve aerodynamic loading and efficiency of the guide vanes, including lowering inlet Mach number to the guide vanes and improving aerodynamic diffusion in the guide vanes. The disclosed splitter arrangements can improve blade and guide vane performance near 0% span, which can be utilized to achieve a relatively more efficient spanwise pressure ratio across the entire span of the blade and the entire span of the guide vane. Engines made with the disclosed architecture, and including arrangements as set forth in this application, and with modifications coming from the scope of the claims in this application, thus provide very high efficient operation, relatively high stall margins, and are compact and lightweight relative to their thrust capability. Two-spool and three-spool direct drive engine architectures can also benefit from the teachings herein.

(88) It should be understood that relative positional terms such as “forward,” “aft,” “upper,” “lower,” “above,” “below,” and the like are with reference to the normal operational attitude of the vehicle and should not be considered otherwise limiting.

(89) Although the different examples have the specific components shown in the illustrations, embodiments of this disclosure are not limited to those particular combinations. It is possible to use some of the components or features from one of the examples in combination with features or components from another one of the examples.

(90) Although particular step sequences are shown, described, and claimed, it should be understood that steps may be performed in any order, separated or combined unless otherwise indicated and will still benefit from the present disclosure.

(91) The foregoing description is exemplary rather than defined by the limitations within. Various non-limiting embodiments are disclosed herein, however, one of ordinary skill in the art would recognize that various modifications and variations in light of the above teachings will fall within the scope of the appended claims. It is therefore to be understood that within the scope of the

appended claims, the disclosure may be practiced other than as specifically described. For that reason the appended claims should be studied to determine true scope and content.

Claims

1. A section for a gas turbine engine comprising: a rotor including a row of blades extending in a radial direction outwardly from a hub, wherein the hub is rotatable about a longitudinal axis such that the row of blades deliver flow to a bypass flow path, an intermediate flow path and a core flow path; a first case surrounding the row of blades to establish the bypass flow path through a first duct; a first flow splitter that divides flow between the bypass flow path and a second duct; an aftmost row of guide vanes extending in the radial direction across the bypass flow path; a second case including a second flow splitter radially inboard of the first flow splitter, wherein the second flow splitter is axially forward of an axially forwardmost compressor blade row of the gas turbine engine relative to the longitudinal axis that is surrounded by the second case, the second flow splitter divides flow from the second duct between the intermediate flow path and the core flow path, a forwardmost edge of the second flow splitter is axially aft of a forwardmost edge of the first flow splitter with respect to the longitudinal axis, and the forwardmost edges of the first and second flow splitters are axially forward of the aftmost row of guide vanes with respect to the longitudinal axis; a bypass port that interconnects the intermediate and bypass flow paths at a position axially aft of a position of the aftmost row of guide vanes relative to the longitudinal axis, and the bypass port configured to direct flow from the intermediate flow path to the bypass flow path; wherein each of the blades extends in the radial direction between a 0% span position at the hub and a 100% span position at a tip, leading edges of the blades at the 100% span position are established along a first reference plane, leading edges of the guide vanes at a 100% span position of the respective guide vanes are established along a second reference plane, the first and second reference planes are perpendicular to the longitudinal axis, a first axial length is established between the first and second reference planes, a tip radius is established between the tip of one of the respective blades and the longitudinal axis, and a ratio of the first axial length divided by the tip radius is greater than or equal to 0.5; and wherein the forwardmost edge of the first flow splitter is situated in the radial direction at a first splitter position, the forwardmost edge of the second flow splitter is situated in the radial direction at a second splitter position, the first splitter position is radially aligned with or radially inward of a 25% span position of the blades, and the second splitter position being radially aligned with or radially outward of a 5% span position of the blades.

2. The section as recited in claim 1, wherein the hub is driven by a turbine through a geared architecture.

3. The section as recited in claim 1, wherein each of the blades extends in the radial direction between the 0% span position at the hub and the 100% span position at the tip to establish a hub-to-tip ratio, and the hub-to-tip ratio of each one of the blades is less than or equal to 0.4, the hub-to-tip ratio of each one of the blades measured relative to the forwardmost portion of the leading edge of the respective blade.

4. The section as recited in claim 1, wherein the first duct establishes the bypass flow path, the second duct branches between the intermediate and core flow paths at the second flow splitter, a first annulus area is established by the first duct at the forwardmost edge of the first flow splitter, a second annulus area is established by the second duct at the forwardmost edge of the first flow splitter, a bypass area ratio is defined as the first annulus area divided by the second annulus area, and the bypass area ratio is greater than or equal to 10, and less than or equal to 35.

5. The section as recited in claim 4, wherein a maximum value of a pressure ratio across the blades alone is less than 1.45 at cruise at 0.8 Mach and 35,000 feet.

6. The section as recited in claim 4, wherein only one row of guide vanes extends in the radial direction across the bypass flow path and the row of guide vanes comprises the aftmost row of

guide vanes.

7. The section as recited in claim 4, wherein each of the blades extends in the radial direction between the 0% span position at the hub and the 100% span position at the tip to establish a hub-to-tip ratio, and the hub-to-tip ratio of each one of the respective blades is between 0.16-0.36 measured relative to the forwardmost portion of the leading edge of the respective blade.

8. The section as recited in claim 7, wherein the row of blades establishes a blade quantity (BQ), the blade quantity (BQ) is at least 12 but not more than 20 blades, the aftmost row of guide vanes establishes a vane quantity (VQ), and the vane quantity (VQ) is at least 20 but not more than 40 guide vanes.

9. The section as set forth in claim 8, wherein a ratio of VQ/BQ is between 2.0 and 2.6.

10. The section as recited in claim 1, further comprising: one or more blocker doors situated in the intermediate flow path downstream of the bypass port, and wherein the one or more blocker doors are moveable to direct flow from the intermediate flow path to the bypass port.

11. The section as set forth in claim 10, wherein: the one or more blocker doors are configured to pivot from the second case towards the bypass flow path to direct flow from the intermediate flow path to the bypass port; and louvers are situated in the bypass port, the louvers have an airfoil-shaped geometry and are arranged to direct flow from the intermediate flow path to the bypass flow path.

12. A gas turbine engine comprising: a fan section including a fan having a row of blades, each extending in a radial direction between a 0% span position at a hub and a 100% span position at a respective tip, wherein the hub is rotatable about an engine longitudinal axis such that the row of blades deliver flow to a bypass flow path, an intermediate flow path and a core flow path; a compressor section establishing the core flow path; a turbine section that drives the fan section and the compressor section; a fan case including a bypass duct surrounding the row of blades to establish the bypass flow path; a housing including a first flow splitter that divides flow between the bypass flow path and a second duct; an aftmost row of guide vanes in the bypass duct that extend in the radial direction across the bypass flow path; an engine case including a second flow splitter radially inboard of the first flow splitter and that divides flow from the second duct between the intermediate flow path and the core flow path, wherein the second flow splitter is axially forward of an axially forwardmost compressor blade row of the compressor section that is surrounded by the engine case relative to the engine longitudinal axis, a forwardmost edge of the second flow splitter is axially aft of a forwardmost edge of the first flow splitter with respect to the engine longitudinal axis, and the forwardmost edges of the first and second flow splitters are axially forward of the row of aftmost guide vanes with respect to the engine longitudinal axis; a bypass port that interconnects the intermediate and bypass flow paths at a position downstream of the aftmost row of guide vanes, and the bypass port configured to direct flow from the intermediate flow path to the bypass flow path; wherein each of the blades extends in the radial direction between the 0% span position and 100% span position to establish a hub-to-tip ratio, and the hub-to-tip ratio of each one of the blades is less than or equal to 0.4 measured relative to a forwardmost portion of a leading edge of the respective blade; the leading edges of the blades at the 100% span position are established along a first reference plane, leading edges of the guide vanes at a 100% span position of the respective guide vanes are established along a second reference plane, the first and second reference planes are perpendicular to the engine longitudinal axis, a first axial length is established between the first and second reference planes, a tip radius is established between the tip of one of the respective blades and the longitudinal axis, and a ratio of the first axial length divided by the tip radius is greater than or equal to 0.5; and wherein the forwardmost edge of the first flow splitter is situated in the radial direction at a first splitter position, the forwardmost edge of the second flow splitter is situated in the radial direction at a second splitter position, the first splitter position is radially aligned with or radially inward of a 25% span position of the blades relative to the engine longitudinal axis, and the second splitter position is radially aligned with or radially

outward of a 5% span position of the blades relative to the engine longitudinal axis.

13. The gas turbine engine as recited in claim 12, further comprising a geared architecture, wherein the turbine section includes a fan drive turbine, and the geared architecture drives the fan at a different speed than a speed of the fan drive turbine.

14. The gas turbine engine as recited in claim 12, further comprising one or more blocker doors situated in the intermediate flow path downstream of the bypass port, wherein the one or more blocker doors are moveable between a first position and a second position, wherein the one or more blocker doors are configured to communicate flow in the intermediate flow path to a vent port in the first position but are configured to block flow in the intermediate flow path to the vent port in the second position.

15. The gas turbine engine as recited in claim 14, wherein the vent port is axially aft of an exit of the bypass flow path with respect to the engine longitudinal axis.

16. The gas turbine engine as recited in claim 14, further comprising a thrust reverser including a cascade that selectively communicates airflow from the bypass duct, wherein the cascade extends axially aft of both the aftmost row of guide vanes and the bypass port with respect to the engine longitudinal axis.

17. The gas turbine engine as recited in claim 12, wherein: the compressor section includes a first compressor and a second compressor, the first compressor comprises the axially forwardmost compressor blade row of the compressor section, and both the second flow splitter and an entrance of the intermediate flow path are axially forward of the compressor section relative to the engine longitudinal axis.

18. The gas turbine engine as recited in claim 17, wherein the first compressor includes three compressor blade rows.

19. The gas turbine engine as recited in claim 17, wherein the aftmost row of guide vanes extend in the radial direction across the intermediate flow path relative to the engine longitudinal axis.
