

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12387566
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Bennett; Nicholas

---

### Gaming device with fillable symbol position pattern

---

#### Abstract

A technique for using symbol position patterns includes performing a selection operation, using the random number generator and a data structure comprising a plurality of symbol position patterns to obtain one of the symbol position patterns, and modifying display of the plurality of symbol positions in accordance with the selected symbol position pattern. A symbol selection instance is performed using a lookup table comprising a plurality of reel strips, wherein the reel strips include a designated symbol with respect to the plurality of symbol positions until an end condition is met, and upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, an outcome is determined.

---

<b>Inventors:</b>	<b>Bennett; Nicholas (Manly Vale, AU)</b>
<b>Applicant:</b>	<b>Aristocrat Technologies Australia Pty Limited (North Ryde, AU)</b>
<b>Family ID:</b>	<b>1000008748974</b>
<b>Assignee:</b>	<b>Aristocrat Technologies Australia Pty Limited (North Ryde, AU)</b>
<b>Appl. No.:</b>	<b>18/152081</b>
<b>Filed:</b>	<b>January 09, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240046761 A1	Feb. 08, 2024

#### Foreign Application Priority Data

AU	2022211905	Aug. 05, 2022
----	------------	---------------

---

#### Publication Classification

**Int. Cl.:** G07F17/32 (20060101); G07F17/34 (20060101)

**U.S. Cl.:**

**CPC** G07F17/3267 (20130101); G07F17/3213 (20130101); G07F17/34 (20130101);

## Field of Classification Search

**CPC:** G07F (17/32); G07F (17/34); G07F (17/3213); G07F (17/3267)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0068623	12/2001	Gauselmann	463/20	G07F 17/3265
2003/0216165	12/2002	Singer	463/20	G07F 17/3211
2005/0049031	12/2004	Jackson	463/20	G07F 17/34
2007/0232381	12/2006	Sato	463/20	G07F 17/34
2008/0274786	12/2007	Wilson	463/20	G07F 17/3244
2009/0069080	12/2008	Pires	463/26	G07F 17/3244
2009/0124364	12/2008	Cuddy	463/31	G07F 17/32
2009/0131154	12/2008	Chim	463/25	G07F 17/32
2011/0028201	12/2010	Warner	463/19	G07F 17/34
2013/0102377	12/2012	Ballone	463/20	G07F 17/3267
2013/0217477	12/2012	Wright	463/25	G07F 17/3274
2014/0087858	12/2013	Cuddy	463/27	G07F 17/32
2014/0228092	12/2013	Inamura	463/20	G07F 17/3267
2014/0357342	12/2013	Elias	463/20	G07F 17/3262
2016/0086429	12/2015	Inamura	463/20	G07F 17/326
2017/0092041	12/2016	Kudo	N/A	G07F 17/3267
2018/0122184	12/2017	Wortmann	N/A	G07F 17/3213
2018/0130298	12/2017	Koshorek	N/A	G07F 17/3213
2019/0088088	12/2018	Foster	N/A	G07F 17/3267
2021/0295639	12/2020	Matos	N/A	G07F 17/3267

---

*Primary Examiner:* Rowland; Steve

*Attorney, Agent or Firm:* Blank Rome LLP

---

## Background/Summary

### FIELD OF THE INVENTION

(1) The present application relates to a gaming device, a method of operating a gaming device and a system with a fillable symbol position pattern.

### BACKGROUND

(2) Electronic gaming machines (“EGMs”) or gaming devices provide a variety of wagering games such as slot games, video poker games, video blackjack games, roulette games, video bingo games, keno games and other types of games that are frequently offered at casinos and other locations.

Play on EGMs typically involves a player establishing a credit balance by inputting money, or another form of monetary credit, and placing a monetary wager (from the credit balance) on one or more outcomes of an instance (or single play) of a primary or base game. In many games, a player may qualify for secondary games or bonus rounds by attaining a certain winning combination or triggering event in the base game. Secondary games provide an opportunity to win additional game instances, credits, awards, jackpots, progressives, etc. Awards from any winning outcomes are typically added back to the credit balance and can be provided to the player upon completion of a gaming session or when the player wants to “cash out.”

(3) “Slot” type games are often displayed to the player in the form of various symbols arrayed in a row-by-column grid or matrix. Specific matching combinations of symbols along predetermined paths (or paylines) through the matrix indicate the outcome of the game. The display typically highlights winning combinations/outcomes for ready identification by the player. Matching combinations and their corresponding awards are usually shown in a “pay-table” which is available to the player for reference. Often, the player may vary his/her wager to include differing numbers of paylines and/or the amount bet on each line. By varying the wager, the player may sometimes alter the frequency or number of winning combinations, frequency or number of secondary games, and/or the amount awarded.

(4) Typical games use a random number generator (RNG) to randomly determine the outcome of each game. The game is designed to return a certain percentage of the amount wagered back to the player (RTP = return to player) over the course of many plays or instances of the game. The RTP and randomness of the RNG are critical to ensuring the fairness of the games and are therefore highly regulated. Upon initiation of play, the RNG randomly determines a game outcome and symbols are then selected which correspond to that outcome. Notably, some games may include an element of skill on the part of the player and are therefore not entirely random.

#### SUMMARY

(5) There is disclosed a gaming device, a method of operating a gaming device and a system with a fillable symbol position pattern. A symbol position pattern is selected (for example, when a trigger condition is met) from a plurality of different symbol position patterns. Each symbol position pattern is a subset of the plurality of symbols positions for which symbols are selected during a game instance and the display is modified to indicate which of these symbol positions form part of the symbol position pattern. Symbol selection is then conducted using reel strips incorporating a designated symbol until an end condition is met. When the pattern is filled by designated symbols when the end condition is met, an award is made.

(6) An example embodiment describes a gaming device comprising a display, a random number generator, at least one input mechanism, a processor, and a memory storing (i) symbol position data defining a plurality of symbol positions, (ii) a plurality of different symbol position patterns, each comprising a subset of the plurality of symbol positions, (iii) symbol data defining at least a plurality of reel strips comprising a designated symbol, and (iv) instructions. When the instructions are executed by the processor, they cause the processor to control the display to display the plurality of symbol positions defined by the symbol position data, select, using the random number generator, one of the symbol position patterns, modify display of the plurality of symbol positions to indicate the subset of the plurality of symbol positions of the selected symbol position pattern, conduct symbol selection, from the plurality of reel strips comprising a designated symbol, in respect of the plurality of symbol positions until an end condition is met, and upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, make an award.

(7) Another example embodiment describes a method of operating a gaming device comprising a display, a random number generator, at least one input mechanism, a processor, and a memory storing (i) symbol position data defining a plurality of symbol positions, (ii) a plurality of different symbol position patterns, each comprising a subset of the plurality of symbol positions, and (iii)

symbol data defining at least a plurality of reel strips comprising a designated symbol. The method comprises controlling the display to display the plurality of symbol positions defined by the symbol position data, selecting, using the random number generator, one of the symbol position patterns, modifying display of the plurality of symbol positions to indicate the subset of the plurality of symbol positions of the selected symbol position pattern, conducting symbol selection, from the plurality of reel strips comprising a designated symbol, in respect of the plurality of symbol positions until an end condition is met, and upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, making an award.

(8) Another example embodiment describes a system comprising at least one display, a random number generator, at least one input mechanism, one or more processors, and a memory storing (i) symbol position data defining a plurality of symbol positions, (ii) a plurality of different symbol position patterns, each comprising a subset of the plurality of symbol positions, (iii) symbol data defining at least a plurality of reel strips comprising a designated symbol, and (iv) instructions. When the instructions are executed by the one or more processors, they cause the one or more processors to control the at least one display to display the plurality of symbol positions defined by the symbol position data, select, using the random number generator, one of the symbol position patterns, modify display of the plurality of symbol positions to indicate the subset of the plurality of symbol positions of the selected symbol position pattern,

(9) conduct symbol selection, from the plurality of reel strips comprising a designated symbol, in respect of the plurality of symbol positions until an end condition is met, and

(10) upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, make an award.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an exemplary diagram showing several EGMs networked with various gaming related servers.

(2) FIG. 2 is a block diagram showing various functional elements of an exemplary EGM.

(3) FIG. 3 illustrates an example reel strip layout.

(4) FIG. 4 is a flow chart of a symbol selection method.

(5) FIG. 5A to 5D show a flow chart of a method of operating a gaming device.

(6) FIGS. 6 to 17 are example screen displays resulting from operating the gaming device.

(7) FIG. 18 shows examples of symbol position patterns.

(8) FIGS. 19 to 25 are further example screen displays.

### DETAILED DESCRIPTION

(9) Embodiments described herein are generally related to a technique for employing dynamic symbol position patterns which affect the outcome of a game. In particular, embodiments described herein are directed to randomly selecting a symbol position pattern which directs the number and pattern of symbol positions to be used in a game. That is, a visual layout for symbol positions is selected. The particular layout selected thereby affects how outcomes are determined for the game.

(10) Embodiments described herein provide a technical improvement by employing additional game variations without requiring significant memory or compute resources to handle the additional permutations. In particular, embodiments described herein employ a data structure having a plurality of symbol position patterns for random selection. As such, the data structure comprising the plurality of symbol position patterns may be used in conjunction with a data structure having symbols for selection.

(11) FIG. 1 illustrates several different models of EGMs which may be networked to various

gaming related servers. The present invention can be configured to work as a system **100** in a gaming environment including one or more server computers **102** (e.g., slot servers of a casino) that are in communication, via a communications network, with one or more gaming devices **104A-104X** (EGMs, slots, video poker, bingo machines, etc.). The gaming devices **104A-104X** may alternatively be portable and/or remote gaming devices such as, but not limited to, a smart phone, a tablet, a laptop, or a game console.

(12) Communication between the gaming devices **104A-104X** and the server computers **102**, and among the gaming devices **104A-104X**, may be direct or indirect, such as over the Internet through a website maintained by a computer on a remote server or over an online data network including commercial online service providers, Internet service providers, private networks, and the like. In other embodiments, the gaming devices **104A-104X** may communicate with one another and/or the server computers **102** over RF, cable TV, satellite links and the like.

(13) In some embodiments, server computers **102** may not be necessary and/or preferred. For example, the present invention may, in one or more embodiments, be practiced on a stand-alone gaming device such as gaming device **104A**, gaming device **104B** or any of the other gaming devices **104C-104X**. However, it is typical to find multiple EGMs connected to networks implemented with one or more of the different server computers **102** described herein.

(14) The server computers **102** may include a central determination gaming system server **106**, a ticket-in-ticket-out (TITO) system server **108**, a player tracking system server **110**, a progressive system server **112**, and/or a casino management system server **114**. Gaming devices **104A-104X** may include features to enable operation of any or all servers for use by the player and/or operator (e.g., the casino, resort, gaming establishment, tavern, pub, etc.). For example, game outcomes may be generated on a central determination gaming system server **106** and then transmitted over the network to any of a group of remote terminals or remote gaming devices **104A-104X** that utilize the game outcomes and display the results to the players.

(15) Gaming device **104A** is often of a cabinet construction which may be aligned in rows or banks of similar devices for placement and operation on a casino floor. The gaming device **104A** often includes a main door **116** which provides access to the interior of the cabinet. Gaming device **104A** typically includes a button area or button deck **120** accessible by a player that is configured with input switches or buttons **122**, an access channel for a bill validator **124**, and/or an access channel for a ticket printer **126**.

(16) In FIG. 1, gaming device **104A** is shown as a Relm XL™ model gaming device manufactured by Aristocrat® Technologies, Inc. As shown, gaming device **104A** is a reel machine having a gaming display area **118** comprising a number (typically 3 or 5 of mechanical reels **130** with various symbols displayed on them. The reels **130** are independently spun and stopped to show a set of symbols within the gaming display area **118** which may be used to determine an outcome to the game. In embodiments where the reels are mechanical, mechanisms can be employed to implement greater functionality. For example, the boundaries of the gaming display area boundaries of the gaming display area **118** may be defined by one or more mechanical shutters controllable by a processor. The mechanical shutters may be controlled to open and close, to correspondingly reveal and conceal more or fewer symbol positions from the mechanical reels **130**. For example, a top boundary of the gaming display area **118** may be raised by moving a corresponding mechanical shutter upwards to reveal an additional row of symbol positions on stopped mechanical reels. Further, a transparent or translucent display panel may be overlaid on the gaming display area **118** and controlled to override or supplement what is displayed on one or more of the mechanical reel(s).

(17) In many configurations, the gaming machine **104A** may have a main display **128** (e.g., video display monitor) mounted to, or above, the gaming display area **118**. The main display **128** can be a high-resolution LCD, plasma, LED, or OLED panel which may be flat or curved as shown, a cathode ray tube, or other conventional electronically controlled video monitor.

(18) In some embodiments, the bill validator **124** may also function as a “ticket-in” reader that allows the player to use a casino issued credit ticket to load credits onto the gaming device **104A** (e.g., in a cashless ticket (“TITO”) system). In such cashless embodiments, the gaming device **104A** may also include a “ticket-out” printer **126** for outputting a credit ticket when a “cash out” button is pressed. Cashless TITO systems are well known in the art and are used to generate and track unique bar-codes or other indicators printed on tickets to allow players to avoid the use of bills and coins by loading credits using a ticket reader and cashing out credits using a ticket-out printer **126** on the gaming device **104A**. In some embodiments a ticket reader can be used which is only capable of reading tickets. In some embodiments, a different form of token can be used to store a cash value, such as a magnetic stripe card.

(19) In some embodiments, a player tracking card reader **144**, a transceiver for wireless communication with a player's smartphone, a keypad **146**, and/or an illuminated display **148** for reading, receiving, entering, and/or displaying player tracking information is provided in EGM **104A**. In such embodiments, a game controller within the gaming device **104A** can communicate with the player tracking server system **110** to send and receive player tracking information.

(20) Gaming device **104A** may also include a bonus topper wheel **134**. When bonus play is triggered (e.g., by a player achieving a particular outcome or set of outcomes in the primary game), bonus topper wheel **134** is operative to spin and stop with indicator arrow **136** indicating the outcome of the bonus game. Bonus topper wheel **134** is typically used to play a bonus game, but it could also be incorporated into play of the base or primary game.

(21) A candle **138** may be mounted on the top of gaming device **104A** and may be activated by a player (e.g., using a switch or one of buttons **122**) to indicate to operations staff that gaming device **104A** has experienced a malfunction or the player requires service. The candle **138** is also often used to indicate a jackpot has been won and to alert staff that a hand payout of an award may be needed.

(22) There may also be one or more information panels **152** which may be a back-lit, silkscreened glass panel with lettering to indicate general game information including, for example, a game denomination (e.g., \$0.25 or \$1), pay lines, pay tables, and/or various game related graphics. In some embodiments, the information panel(s) **152** may be implemented as an additional video display.

(23) Gaming devices **104A** have traditionally also included a handle **132** typically mounted to the side of main cabinet **116** which may be used to initiate game play.

(24) Many or all the above described components can be controlled by circuitry (e.g., a gaming controller) housed inside the main cabinet **116** of the gaming device **104A**, the details of which are shown in FIG. 2.

(25) Note that not all gaming devices suitable for implementing embodiments of the present invention necessarily include top wheels, top boxes, information panels, cashless ticket systems, and/or player tracking systems. Further, some suitable gaming devices have only a single game display that includes only a mechanical set of reels and/or a video display, while others are designed for bar counters or table tops and have displays that face upwards.

(26) An alternative example gaming device **104B** illustrated in FIG. 1 is the Arc™ model gaming device manufactured by Aristocrat® Technologies, Inc. Note that where possible, reference numerals identifying similar features of the gaming device **104A** embodiment are also identified in the gaming device **104B** embodiment using the same reference numbers. Gaming device **104B** does not include physical reels and instead shows game play functions on main display **128**. An optional topper screen **140** may be used as a secondary game display for bonus play, to show game features or attraction activities while a game is not in play, or any other information or media desired by the game designer or operator. In some embodiments, topper screen **140** may also or alternatively be used to display progressive jackpot prizes available to a player during play of gaming device **104B**.

(27) Example gaming device **104B** includes a main cabinet **116** including a main door **118** which opens to provide access to the interior of the gaming device **104B**. The main or service door **118** is typically used by service personnel to refill the ticket-out printer **126** and collect bills and tickets inserted into the bill validator **124**. The door **118** may also be accessed to reset the machine, verify and/or upgrade the software, and for general maintenance operations.

(28) Another example gaming device **104C** shown is the Helix™ model gaming device manufactured by Aristocrat® Technologies, Inc. Gaming device **104C** includes a main display **128A** that is in a landscape orientation. Although not illustrated by the front view provided, the landscape display **128A** may have a curvature radius from top to bottom, or alternatively from side to side. In some embodiments, display **128A** is a flat panel display. Main display **128A** is typically used for primary game play while secondary display **128B** is typically used for bonus game play, to show game features or attraction activities while the game is not in play or any other information or media desired by the game designer or operator.

(29) Many different types of games, including mechanical slot games, video slot games, video poker, video black jack, video pachinko, keno, bingo, and lottery, may be provided with or implemented within the depicted gaming devices **104A-1040** and other similar gaming devices. Each gaming device may also be operable to provide many different games. Games may be differentiated according to themes, sounds, graphics, type of game (e.g., slot game vs. card game vs. game with aspects of skill), denomination, number of paylines, maximum jackpot, progressive or non-progressive, bonus games, and may be deployed for operation in Class 2 or Class 3, etc.

(30) FIG. 2 is a block diagram depicting exemplary internal electronic components of a gaming device **200** connected to various external systems. All or parts of the example gaming device **200** shown could be used to implement any one of the example gaming devices **104A-X** depicted in FIG. 1. The games available for play on the gaming device **200** are controlled by a game controller **202** that includes one or more processors **204** and a game that may be stored as game software or a program **206** in a memory **208** coupled to the processor **204**. Processor **204** represents a general-purpose processor, a specialized processor intended to perform certain functional tasks, or a combination thereof. As an example, processor **204** can be a central processing unit (CPU) that has one or more multi-core processing units and memory mediums (e.g., cache memory) that function as buffers and/or temporary storage for data. Alternatively, processor **204** can be a specialized processor, such as an application specific integrated circuit (ASIC), graphics processing unit (GPU), field-programmable gate array (FPGA), digital signal processor (DSP), or another type of hardware accelerator. In another example, processor **204** is a system on chip (SoC) that combines and integrates one or more general-purpose processors and/or one or more specialized processors. Although FIG. 2 illustrates that game controller **202** includes a single processor **204**, game controller **202** is not limited to this representation and instead can include multiple processors **204** (e.g., two or more processors).

(31) The memory **208** may include one or more mass storage devices or media that are housed within gaming device **200**. Memory **208** is defined herein as including volatile and nonvolatile memory and other types of non-transitory data storage components. Volatile memory is memory that do not retain data values upon loss of power. Nonvolatile memory is memory that do retain data upon a loss of power. Examples of memory **208** include random access memory (RAM), read-only memory (ROM), hard disk drives, solid-state drives, universal serial bus (USB) flash drives, memory cards accessed via a memory card reader, floppy disks accessed via an associated floppy disk drive, optical discs accessed via an optical disc drive, magnetic tapes accessed via an appropriate tape drive, and/or other memory components, or a combination of any two or more of these memory components. In addition, examples of RAM include static random access memory (SRAM), dynamic random access memory (DRAM), magnetic random access memory (MRAM), and other such devices. Examples of ROM include a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable

read-only memory (EEPROM), or other like memory device. Even though FIG. 2 illustrates that game controller **202** includes a single memory **208**, game controller **202** could include multiple memories **208** for storing program instructions and/or data.

(32) Memory **208** can store one or more game programs **206** that provide program instructions, or computer readable code, and/or data for carrying out various implementations (e.g., game mechanics) described herein. Stated another way, game program **206** represents an executable program stored in any portion or component of memory **208**. In one or more implementations, game program **206** is embodied in the form of source code that includes human-readable statements written in a programming language or machine code that contains numerical instructions recognizable by a suitable execution system, such as a processor **204** in a game controller or other system. Examples of executable programs include: (1) a compiled program that can be translated into machine code in a format that can be loaded into a random access portion of memory **208** and run by processor **204**; (2) source code that may be expressed in proper format such as object code that is capable of being loaded into a random access portion of memory **208** and executed by processor **204**; and (3) source code that may be interpreted by another executable program to generate instructions in a random access portion of memory **208** to be executed by processor **204**.

(33) Within the mass storage devices and/or memory **208**, one or more databases **210** may be provided for use by the program **206**. A random number generator (RNG) **212** that can be implemented in hardware and/or software is typically used to generate random numbers that are used in the operation of game play to ensure that game play outcomes are random and meet regulations for a game of chance. In some embodiments, the random number generator **212** is a pseudo-random number generator.

(34) Alternatively, a game instance (i.e. a play or round of the game) may be generated on a remote gaming device such as a central determination gaming system server **106** (not shown in FIG. 2 but see FIG. 1). The game instance is communicated to gaming device **200** via the network **214** and then displayed on gaming device **200**. Gaming device **200** may execute game software, such as but not limited to video streaming software that allows the game to be displayed on gaming device **200**. When a game is stored on gaming device **200**, it may be loaded from a memory **208** (e.g., from a read only memory (ROM)) or from the central determination gaming system server **106** to memory **208**. The memory **208** may include RAM, ROM or another form of storage media that stores instructions for execution by the processor **204**.

(35) The gaming device **200** may include a topper display **216** or another form of a top box (e.g., a topper wheel, a topper screen, etc.) which sits above main cabinet **218**. The gaming cabinet **218** or topper display **216** may also house a number of other components which may be used to add features to a game being played on gaming device **200**, including speakers **220**, a ticket printer **222** which prints bar-coded tickets or other media or mechanisms for storing or indicating a player's credit value, a ticket reader **224** which reads bar-coded tickets or other media or mechanisms for storing or indicating a player's credit value, and a player tracking interface **232**. The player tracking interface **232** may include a keypad **226** for entering information, a player tracking display **228** for displaying information (e.g., an illuminated or video display), a card reader **230** for receiving data and/or communicating information to and from media or a device such as a smart phone enabling player tracking. Ticket printer **222** may be used to print tickets for a TITO system server **108**. The gaming device **200** may further include a bill validator **234**, buttons **236** for player input, cabinet security sensors **238** to detect unauthorized opening of the cabinet **218**, a primary game display **240**, and a secondary game display **242**, each coupled to and operable under the control of game controller **202**.

(36) Gaming device **200** may be connected over network **214** to player tracking system server **110**. Player tracking system server **110** may be, for example, an OASIS® system manufactured by Aristocrat® Technologies, Inc. Player tracking system server **110** is used to track play (e.g. amount wagered, games played, time of play and/or other quantitative or qualitative measures) for



individual players so that an operator may reward players in a loyalty program. The player may use the player tracking interface **232** to access his/her account information, activate free play, and/or request various information. Player tracking or loyalty programs seek to reward players for their play and help build brand loyalty to the gaming establishment. The rewards typically correspond to the players level of patronage (e.g., to the player's playing frequency and/or total amount of game plays at a given casino). Player tracking rewards may be complimentary and/or discounted meals, lodging, entertainment and/or additional play. Player tracking information may be combined with other information that is now readily obtainable by a casino management system.

(37) Gaming devices, such as gaming devices **104A-104X, 200**, are highly regulated to ensure fairness and, in many cases, gaming devices **104A-104X, 200** are operable to award monetary awards (e.g., typically dispensed in the form of a redeemable voucher). Therefore, to satisfy security and regulatory requirements in a gaming environment, hardware and software architectures are implemented in gaming devices **104A-104X, 200** that differ significantly from those of general-purpose computers. Adapting general purpose computers to function as gaming devices **200** is not simple or straightforward because of: 1) the regulatory requirements for gaming devices **200**, 2) the harsh environment in which gaming devices **200** operate, 3) security requirements, 4) fault tolerance requirements, and 5) the requirement for additional special purpose componentry enabling functionality of an EGM. These differences require substantial engineering effort with respect to game design implementation, hardware components and software.

(38) When a player wishes to play the gaming device **200**, he/she can insert cash or a ticket voucher through a credit input mechanism such as a coin acceptor (not shown) or bill validator **234** to establish a credit balance on the game machine. The credit balance is used by the player to place wagers on instances of the game and to receive credit awards based on the outcome of winning instances. The credit balance is decreased by the amount of each wager and increased upon a win. The player can add additional credits to the balance at any time. The credit balance may be stored in a meter in memory **208** (or in a separate hardware meter). In some embodiment, memory **208** implements a credit meter to monitor the credit balance and has a win meter that monitors any amounts won during any game instance(s) resulting from the wager. The balance of the win meter is transferred to the credit meter prior at the conclusion of the game instances. The player may also optionally insert a loyalty club card into the card reader **230**. In some embodiments, the loyalty club card may also act as a credit input mechanism, by allowing a player to transfer funds from a centrally stored balance in order to establish a credit balance. During the game, the player views the game outcome on the game displays **240, 242**. Other game and prize information may also be displayed.

(39) When the player is done, he/she cashes out the credit balance (typically by pressing a cash out button to receive a ticket from the ticket printer **222**). The ticket may be “cashed-in” for money or inserted into another machine to establish a credit balance for play.

(40) FIGS. **5A** to **5D** show a flow chart of an example embodiment of a method **500** of operating a gaming device **200**. At step **502**, the processor **204** receives a wager input by a player using an input mechanism, for example, a virtual button deck—that is a touch screen display that displays virtual buttons that the player can “press” by touching the virtual button deck where one of a plurality of buttons is displayed. In other examples, a physical button deck may be employed or a hybrid button deck having a mixture of virtual and physical buttons. The buttons may include a play button which allows the player to place the same wager placed in the previous game.

(41) At step **504**, the processor **204** controls the display **204** to display the symbol positions for which symbols will be selected. In an example, this step can be performed prior to receiving a wager, for example, by displaying the symbol positions occupied by symbols selected in a prior game instance. FIG. **6** is an example screen display **600**, showing an example where nineteen symbol positions are arranged in five columns **621-625** of symbol positions with three symbol positions in the first column **621** and fifth column **625**, four symbol positions in the second column

**622** and fourth column **624**, and five symbol positions in the third column **623**. Other arrangements of symbol positions can be used in other embodiments including arrangements where there are the same number of symbol positions in each column.

(42) At step **506**, the processor **204** selects symbols by selecting stopping positions for a plurality of reel strips stored in one or more reel strip data structures in memory **208**. FIG. **3** illustrates an example reel strip data structure having a set **300** of five reel strips **341**, **342**, **343**, **344**, **345**. In the example, for illustrative purposes, twenty-five reel strip positions **301-325** are shown for each reel strip **341-345**. In this example, each reel strip position of each reel has a symbol. In other examples, there may be one or more blank symbol positions. For example, a “Wild” symbol occupies the eight reel strip position **308** of the third reel strip **343**. The symbols shown on the reel strips **341-345** are generally indicative of symbols that may be employed in the embodiments, however, other reels strips to those illustrated in FIG. **3** can be used. Symbol position **330** indicates that the reel strips **341-345** will typically have more symbols than illustrated. For example, the reel strips **341-345** could have between 30 and 100 reel strip positions with the last reel strip position of a respective reel strip being treated as contiguous with the first reel strip position **301** as would be the case with a mechanical reel. The actual lengths of the game reel strips depend on factors such as the lengths of the stacks, the number of wild symbols (in general, the more wilds there are, the longer the reel strip needs to be to maintain the target RTP), and volatility (in general, the higher the prize value is, the longer the reel strip needs to be to lower the hit rate to maintain the target RTP). In some examples, the reel strips associated with different columns may be of different lengths to one another.

(43) As shown in FIG. **3**, in this example, each of the reel strips **341-345** has scatter symbols as indicated by the symbol “SCAT” (see, for example, the sixth position **306** of the first and second reel strips **341**, **342**). In some examples, scatter symbols are evaluated independently of the position at which they are selected by the processor **204**. In other examples, they are evaluated in a defined order like other symbols, e.g. left to right from the leftmost column of symbol positions **621**. While this example shows scatter symbols on each reel strip other examples may only have scatter symbols on some of the reel strips. For example, in a case where the scatter symbols also act as wild symbols, there may be no scatter symbols on a first reel strip.

(44) It will be observed that the symbols include a number of “PIC” or picture symbols which represents that the symbols include a number of different symbols that have pictures/icons that fit the theme of the game. The number of different PIC symbols can vary depending on the composition of the pay table.

(45) FIG. **4** is a flow chart of an example method **400** carried out by the processor **204** to select symbols from reel strips **341-345** at step **504**. At step **410**, the processor **204** starts the process of selecting symbols with a counter (n) set at zero as symbols have not yet been selected from any reel strips. At step **420**, the processor **204** increments the counter. In the first iteration, the counter is set to 1 to reflect that symbols are to be selected from a first reel strip. At step **430**, the processor obtains a randomly generated number from a true or pseudo random number generator **212**. At step **440** the processor maps the generated number to one of the reel positions of the nth reel strip. In the first iteration, this is the first reel strip. To map the generated number to one of the reel positions, the possible values that can be returned from the RNG **212** are divided into ranges and associated with specific ones of the reel positions in memory **208**. In one example, these ranges are stored as a look-up table in memory **208**. In one example, the ranges are each the same size so that each of the reel strip positions has the same chance of been selected. In other examples, the ranges may be arranged to weight the relative chances of selecting specific reel strip positions.

(46) At step **450**, the processor **204** maps symbols of the nth reel strip to and nth column of symbol display positions based on the mapped reel position and a reference position. In an example, the reference position is the bottom position of the symbol positions of each column of symbol positions. In this example, the selected reel position or “stopping position” (and hence the symbol

at this position) is mapped to the bottom symbol position of the column. Referring to the example reel strips of FIG. 3, if the value returned by the RNG 212 is mapped to reel position 313 when three symbols are being selected for the first column of symbol positions, then for the first reel strip 341, “10” is mapped to a bottom symbol position and the two symbols immediately above it (here “PIC3” and “A”) will be mapped to the symbol positions above the symbol position while preserving the reel strip order of the first reel strip. In this example, the number of symbols mapped depends on the number of symbol positions in a respective column such that three symbols are mapped to the first and fifth columns 621, 625, four symbols are mapped to the second and fourth columns 622, 624, and five symbols are mapped to the third column 623.

(47) At step 460, the processor 460 determines whether symbols have been selected for all of the reel strips, and if not the processor 204 reverts to step 420 and iterates through steps 430, 440 and 450 until it is determined at step 460 that symbols have been selected from all n reel strips and mapped to all n columns of symbol positions after which the symbol selection process ends 470.

(48) After the symbols of all reel strips have been mapped to symbol position, at step 508, the processor 204 controls display 240 to display the mapped symbols at the symbol positions, in this example by controlling the display 240 to animate the reel strips as spinning to the selected stopping positions.

(49) At step 510, the processor 204 evaluates the displayed symbols based on a pay table stored in memory 208. In this example, a graphical pay table display 660 above the symbol entries graphically represents some of the entries in the pay table, in this example, the five largest winning outcomes. In this example, the processor 204 applies a ways to win evaluation where winning outcomes are evaluated from left to right, winning symbols can occur anywhere on the reel, and winning combinations are made up of no more than one symbol from each reel. In this example, there are  $3 \times 4 \times 5 \times 4 \times 3 = 720$  ways to win.

(50) At step 512, the processor determines whether a feature trigger condition is met in respect of the game instance. In this example, each of the trigger condition involves the occurrence of a defined number of a relevant trigger symbols. In the example embodiment, there are three feature games that can be triggered, a symbol pattern feature (the ‘Star Sign’ feature game), an award path feature (the ‘Cosmic Climb’ feature), and a random prize award feature (the ‘UFO’) feature. The Star Sign and Cosmic Climb features share the same defined trigger symbol, in this example a scatter symbol in the form of a Planet symbol. The UFO feature has a separate defined symbol in the form of a UFO symbol.

(51) As indicated by feature game message 641, a “3 or more [Planet symbol] win awards either the Star Sign . . . Feature [or] Cosmic Climb . . . Feature”. FIG. 6 shows an example of a 3 Planet win in the form of 3 Planet symbols 651-653. When processor 204 determines that a 3 or more Planet symbol award has occurred, the processor 204 conducts a random determination using RNG 212 to determine whether to trigger the Star Sign feature or the Cosmic Climb feature. In this example, the random determination is configured so that there is an equal probability of either feature being triggered. This is graphically represented in screen display 700 by a two-sided coin 710 spinning on display 240 with one side of the coin having the message “Star Sign Feature” (as can be seen in FIG. 7) and “Cosmic Climb Feature” on the other side. In other examples, the relative probabilities of the features being triggered may be weighted. That is, for either feature to be triggered, two conditions need to be met: (i) that a 3 or more Planet win occurs; and (ii) that the result of the random determination is that the selection of the relevant feature. Once one of the features is awarded, a feature award message 810 is displayed as shown in example screen display 800 of FIG. 8, which in this example corresponds to award of the Cosmic Climb feature, with message 810 stating “You won the Cosmic Climb feature. Press Play to start feature”.

(52) Similarly, feature game message 642 indicates that a “3 or more [UFO symbol] win awards the UFO . . . Feature”.

(53) It will be appreciated that in other examples, all of the feature games could have entirely

separate trigger conditions or all of the features could potentially be triggered from a same combination of trigger symbols followed by a random determination. It will also be appreciated that there could be different numbers of feature games.

(54) As shown in FIG. 5A, if at step **512** processor **204** determines there is no feature trigger, the game instance ends at step **514**. In the case where there is a feature trigger and processor **204** determines **516** that the trigger is a random award feature, processor **204** proceeds to step **518** and makes five award selections from a set of prize awards which include a credit amounts, bonus or jackpot awards **630**, and awards of the pattern feature (Star Sign feature). The processor **204** makes the selections using a weighted table stored in memory **208** and RNG **212**. Where only credit awards are made, the game instance ends. Where processor **204** determines at step **520** the pattern feature is awarded, processor **204** proceeds to conduct the pattern feature. As indicated by connector B, description of this process continues in FIG. 5C at step **550**. FIG. **21** shows an example screen display **2100** of a random prize award feature. In order to indicate the awards made by the processor **204**, a UFO graphic **2110** is animated as moving relative to symbol positions having awardable prizes. Screen display **2100** shows a 250 credit prize **2122** being awarded with coins **2131** being animated as moving from credit prize **2122** to UFO **2131**. Screen display **2100** also shows a 400 credit prize **2121** that has already been awarded with display of the prize having been modified by removal of the coins behind the credit value as well as the border around the prize.

(55) At step **522**, processor **204** determines whether the Pattern Feature trigger occurred and, if so proceeds to step **550**. Alternatively, processor **204** will have determined that the Cosmic Climb feature has been triggered and as indicated by connector A, description of this process continues in FIG. 5B at step **524**.

(56) In this respect, a step **524**, processor **204** controls the display to produce an example screen display in which an award path **910** is displayed above the columns of symbol positions **621-623**. Award path has a start position **911** and fifteen progression indicating tiles ending with finish tile **926** which if reached results in an award of a “Super Star Sign Feature”. In the Cosmic Climb feature a number of game instances are conducted and each time a winning outcome occurs in a game instance, the processor **204** controls the display so that a UFO themed position indicator **931** is advanced by one tile and any award corresponding to that tile is applied for all future game instances of the Cosmic Climb Feature. The start tiles **911** is the initial location of position indicator **931**. Screen display **900** shows an example where a winning outcome has occurred in a first game instance and hence position indicator **931** has been advanced to second tile **912** which corresponds to the award of “+1 Wild” for subsequent game instances. In such game instance, a Wild symbol, here in the form of an Alien symbol is added to one of the symbol positions of the middle column **623** as exemplified below.

(57) In order to conduct the game instances, processor **204** sets a first counter to an awarded number of game instances at step **526**, in this example, to ten game instances. In this respect, it will be observed that with an award of ten game instances, it is not possible to obtain fifteen winning outcomes within the initial number of game instances and reach end tile **926**. However, additional game instances may be awarded during the game instances, resulting in first counter being incremented. Specifically, an additional ten game instances are awarded by processor **204** for a game outcome with three or more left to right Planet symbols and an additional two game instances are awarded for two left to right Planet symbols.

(58) At step **528**, processor **204** decrements the counter by one to reflect the initiation of a game instance. (Note that the same effect can be achieved by counting up towards an end number of game instances.)

(59) At step **530**, the processor **204** selects symbols from reel strips in memory **208** using the process described above in relation to FIGS. **3** and **4**. In an example, the Cosmic Climb feature reel strips are the same as those used in the base game. In another example, the reel strips have the same

symbols but differ in composition, for example, numbers of certain symbols, length of reel strips etc.

(60) At step **532**, the processor **204** evaluates the symbols of the current game outcome using a ways to win evaluation as described above and adds any winning amounts to a win meter stored in memory **208**.

(61) At step **534**, the processor determines whether the game outcome includes a two or more Planet symbol win and hence whether to increment the first counter by the relevant number of game instances. Upon making a positive determination at step **534**, processor **204** proceeds to step **536** and increments the counter by either ten or two game instances depending on the number of Planet symbols.

(62) At step **538**, processor **204** determines whether the current game instances included one or more winning outcomes, and if so, control the display **204** to show an advance of position indicator **931** along the path defined by the sequence of tiles to the next tile. At step **542**, processor **204** determines whether the relevant tile is associated with an award. Unless processor **204** determines that the award is the Super Star Sign Feature at step **544**, the award will be of a modifier, and processor applies the modifier at step **546**. Processor **204** then determines whether all the game instances have been conducted at step **546**, and if not, reverts to step **528**. When all game instances have been conducted without the Super Star Sign Feature being awarded, the process ends **512**. When the Super Sign Feature is awarded (i.e. the last tile **926** is reached), processing continues at step **550**.

(63) FIGS. **10** and **11** are example screen displays **1000**, **1100** showing the award of multipliers. In the example of screen display **1000**, progress indicator **931** has been moved to third tile **914** after a third game instance (i.e. there have been three wins), such that at this stage, processor **204** has made an award of the modifier of +1 Wild from first tile, and +2 Wild from third tile **914**. As a result, processor **204** has controlled the display **240** so that three Wild [Alien] symbols **1051-1053** are added and will be held in place for all subsequent game instances.

(64) Screen display **1100** shows a case where progress indicator **931** has been moved to the sixth tile **917** following a ninth game instance resulting in the application of an award of all future wins being multiplied by three as indicated by game message **1110** "All Future Wins  $\times 3$ ". It will also be observed that all the symbol positions of middle column **623** are now occupied by Wild [Alien] symbols as a result of the indicator **931** having previously reached fifth tile **916**.

(65) As indicated above, step **550** can follow on from (i) a positive determination at step **522** that a pattern feature is awarded by a feature trigger **512**, (ii) a positive determination at step **520** that one of the random award selections is a pattern feature, or (iii) the indicator **931** reaching the last tile **926** on path **910** resulting in the processor **204** making an award of the "Super Star Sign" version of the pattern feature.

(66) At step **550**, processor **204** performs a selection operation to select a random selection of a symbol position pattern from a set of symbol position patterns stored in a symbol position pattern store in memory **208** using RNG **212** and a weighted table stored in memory that determines the relative probability of individual symbol patterns being selected. The symbol position pattern store comprises one or more data structures stored in memory and/or storage and comprising a plurality of symbol position patterns for selection. FIG. **12** shows an example screen display **1200** of an awarded symbol position pattern **1241**. The symbol position patterns of the embodiments are themed as constellations and the symbol position pattern shown in FIG. **12** is referred to as "The Frog". In this respect, the symbol positions that make up The Frog constellation are initially represents as stars when overlayed on the display of symbol position. For example, star **1251** indicates that the second bottom symbol position of the third column **623** forms part of the constellation and hence the symbol pattern. Lines such as lines **1261** and **1262** join the start and a constellation graphic **1271** corresponds to the theme of the constellation, such that in this case, constellation graphic is in the form of a frog. The other symbol position patterns of the set of

available symbol position patterns are shown in FIG. 18 and these are “The Whale” **1811**, “The Bow Tie” **1812**, “The Swan” **1813**, “The Chili” **1814**, “The Dollar”, and “The Arrow”. Some of the symbol positions patterns have different numbers of symbol positions and/or symbol positions in different number of columns, both of which will affect the impact they have when selected. In this example, The Frog **1241**, The Whale **1811**, and The Dollar **1815** symbol position patterns have eleven symbol positions; The Swan **1813** symbol position pattern has nine symbol positions; The Chili **1814** and The Arrow **1816** have eight symbol positions; and The Bow Tie **1812** symbol position pattern has seven symbol positions. Also in this example, The Frog **1241**, The Bow Tie **1812**, The Chili **1814** and The Arrow **1816** have symbol positions in all five columns; The Whale **1811** and The Swan **1813** have symbol positions in four columns; and The Dollar **1815** has symbol positions in three columns.

(67) At step **552**, the processor **204** controls the display **240** to modify display of the symbol positions in order to show the symbol position pattern. FIG. 13 is an example screen display **1300** showing an example of such a modified display in which the star sign representation of The Frog symbol pattern **1241** has been modified to a circular target representation of The Frog symbol position pattern **1241A** for The Frog. In this respect, all of the symbol positions previously denoted by stars now have circular targets which are overlayed on greyed out symbols. For example, circular target **1351** is overlayed on greyed-out Queen symbol **1361** and corresponds to the symbol position previously indicated by star **1251**. Game message **1330** indicates the goal is to “Fill in all [Circular Targets **1331**] with [Planet symbols **1332**] to win a Progressive or Bonus!”. That is, the aim is to fill all the positions of the symbol position pattern **1241A** with a designated symbol in the form of Planet symbol **1332**.

(68) At step **554**, processor **204** determines whether to automatically fill the selected symbol pattern which the processor **204** will do in response to the Super Star Sign feature being awarded from the Cosmic Climb feature when fifteenth tile **926** was reached or as one of award selections at step **518**. If not, processor **204** proceeds to conduct a plurality of symbol selection instances from a set of overlay reel strips stored in memory **208**. Overlay reel strips differ from the reel strips **341-345** in that they have only instances of the Planet symbol **1332** or blank symbol positions. They are referred to overlay reel strips because they are displayed as spinning in superimposed relation to greyed-out symbols at the symbol positions in the same way that target **1351** is superimposed on Queen symbol **1361**. The blank symbols on the reel strips allow the underlying greyed-out symbols to be seen whereas the Planet symbols are superimposed as will be apparent from FIGS. 14 to 16.

(69) In order to conduct the plurality of symbol selection instances, at step **558**, processor **204** sets a second counter to the number of symbol selection instances, in this example to three selection instances. In an example, the number of symbol selection instances is fixed. In another example, the number of symbol selection is variable, for example, by being reset each time a designated symbol is selected for a symbol position of the symbol pattern. At step **560**, processor **204** decrements the second counter by one to reflect the conduct of a symbol selection instance and, at step **562**, processor **204** selects symbols from the overlay reel strip by selecting stopping positions and mapping symbols based on the selected stopping positions using a process as exemplified in relation to FIG. 4.

(70) FIG. 14 is an example screen display **1400** following an instance in which symbol selection has been conducted at step **562** and symbol pattern **1241A** has been part-filled by designated symbols. For example, symbol position **1351** is now occupied by a Planet symbol **1451**. It will be observed, the selection process conducted by processor **204** can result in designated symbols, such as Planet symbol **1432** being selected at positions that are no part of symbol position pattern **1241A**. In an example, if such a Planet symbol satisfies a movement condition it will be moved to a position of the symbol position pattern. In this example, the movement condition is that (i) the designated symbol is within a defined number of symbol positions of an empty target of the symbol position pattern (e.g. one symbol position); and (ii) that, following a random determination using

RNG **212** and a weighted table stored in memory **208**, processor **204** determines to move the symbol. In this example, the defined number of symbol positions is one.

(71) Accordingly, at step **563** processor **204** determines whether to move one or more symbols. First, processor **204** determines whether there are any candidate symbols to move. In the case, of FIG. **14**, Planet symbol **1432** has been selected at a neighbouring symbol position to empty symbol position **1431** of symbol pattern **1241A**. Accordingly, symbol **1432** is a candidate to be moved and processor **204** conducts a random determination to determine whether to move symbol **1432**. Example screen display **1500** of FIG. **15** shows an example of a symbol being moved at step **564** the result of a positive determination to move a symbol at step **563**. UFO graphic **1510** appears above symbol position **1431** and an animation shows the Planet symbol **1432** being moved by the UFO graphic **1510** to symbol position **1431**. In FIG. **15**, planet symbol is shown at an intermediary position **1432A** nearing completion of the move to symbol position **1431**.

(72) At step **565**, processor **204** determines whether the second counter has reached zero (that is whether all game instances have been conducted). If not, processor **204** proceeds to step **566** and determines whether the pattern is full (that is, have designated symbols been selected for all symbol positions of the symbol position pattern). If the pattern is not full, processor **204** holds all of the designated symbols in place at step **567** and proceeds to begin a further symbol selection instance at step **560**.

(73) After all of the game instances have been conducted, processor **204** proceeds to step **568** and determines whether the symbol position pattern **1241A** is full. An example, of symbol positions of symbol position pattern **1241A** being filled is shown in example screen display **1600** of FIG. **16**. Processor **204** can also proceed to step **570** and make an award upon it being determined at step **566** that the pattern is full. In examples, where selection of a designated symbol at a symbol position of a symbol position pattern results in the game instance counter being reset, step **568** is not needed as the counter will be non-zero at step **565** and the processor **204** will proceed to step **566**. It will be appreciated that in the above example, there are two possible end conditions for the game instances being conducted: the pattern being filled; and the counter reaching zero.

(74) Upon the symbol position pattern being full as shown in FIG. **16**, processor **204** proceeds to step **570** and makes an award. In an example, processor **204** makes an award by randomly selecting an award from a set of awards using RNG **212** and a weighted table stored in memory **208**. Example screen display **1700** shows an animation of an award process. Game message **1710** advises a player to “Look Up” and observe a prize indication moving relative to prize graphic **1721-1724**. Here the prize indication is that the prize graphic that is currently selected is lit up. In this case, Stellar progressive prize graphic **1722** is highlighted relative to Giant progressive prize graphic **1721**, Lunar bonus prize graphic **1723**, and Dwarf bonus prize graphic **1724** to indicate that Stellar progressive having a value of \$500.90 has been awarded at step **570**.

(75) At indicated above, in some circumstances, a Super Star Sign feature is awarded such that processor **204** will make a positive determination to automatically fill the symbol position pattern at step **554** and proceed to fill the pattern at step **556**. The processor **204** can animate filling of the symbol position pattern in a number of ways including by conducting one or more animations of a symbol section instance that results in all of the positions being filled. Processor **204** then proceeds to step **570** and makes an award.

(76) Irrespective of whether processor **204** makes an award at step **570**, processor **204** holds the designated (Planet) symbols at step **572** for subsequent processing in a second phase of the Star Sign Feature in which a further series of game instances are conducted (“free games”). In this phase, symbols are selected from free game reel strips which, in one example, may be the similar to the base game reel strips but with the Wild or Scatter symbols removed.

(77) At step **574**, processor **204** sets a counter to the number of games instances, e.g. to 5. At step **576**, processor **204** decrements the counter to reflect the conduct of one of the game instance.

(78) At step **578**, processor **204** selects symbols from the free game reel strips using the same

process described in relation to FIGS. 3 and 4. FIG. 19 shows an example of a screen display 1900 after such a selection process. In this respect, in this example, a completed symbol pattern 1241B is displayed with Planet symbols at all of the symbol positions of the pattern. In examples, where the pattern is not completely filled, the Planet symbols are still held but symbols are selected from free game reel strips for the positions of the symbol positions pattern not occupied by the Planet symbol. It will be observed that unlike Queen symbol 1361 in FIG. 13, the selected symbols such as Queen symbol 1911 are not-greyed out.

(79) At step 580 processor 204 selects a symbol for all symbol positions of the symbol pattern 1241B that are occupied by the designated symbol (here the Planet symbol) from a set of symbols, which in this example, is the same as the set of symbols on the free game reel strips. In an example, processor 204 selects the symbol using RNG 212 and a weight table stored in memory 208. An example screen display 2000 following such a selection is shown in FIG. 20, wherein Queen symbol has been selected for display at all symbol positions of symbol pattern 1241B. In examples, where the pattern is not completely filled.

(80) At step 582, processor 204 evaluates the symbols for winning outcomes based on pay table in memory 208 and adds any award to the win meter in memory 208. It will be appreciated that in this example, where there are larger number of symbol positions occupied by the same symbol, there are advantageous prospects of winning combinations of symbols occurring featuring the symbol selected for the symbol pattern.

(81) At step 584, processor 204 determines whether the third counter has reached zero (that is, whether all of the free games have been conducted), and if not reverts to step 576. When all of the free games have been conducted, the game instance ends.

(82) FIGS. 22 to 25 illustrate an alternative aspect where a path 2220 having awards at positions along the path is employed in an alternative manner to the Cosmic Climb Feature described above but which can also result in the award of a Star Sign feature if the end of the path is reached. In this example, processor 204 conducts blocks of game instances (referred to as “Cosmic Climb Games”) during which there is a chance to win a bonus prize in addition to the chance of winning prizes from the individual game instances. As shown in example screen display 2200 of FIG. 12 a game indicator 2210 has twelve indicator portions to indicate that the block of game instances comprises twelve game instances. The path has first award tile 2222, second award tile 2223, and third award tile 2224. Before the block of games is started, a progress indicator in the form of a UFO graphic 2250 is placed on a start tile 2221. There are three tiles between the start tile and the first award tile 2222, two tiles between the first award tile 2222 and the second award tile 2223, and two further tiles between second award tile 2223 and third award tile 2224 so that there are ten tile on the path 2220 in addition to start tile 2221. As in the Cosmic Climb feature, a winning outcome in a Cosmic Climb Game results in indicator 2250 being moved along the path 2210. However, unlike the Cosmic Climb feature, in the Cosmic Climb Games, an award is only made if the third award tile 2224 is reached or if the indicator is on the first award tile 2222 or second award tile 2223 when the block of games concludes. That is, awards are not accumulated once tiles are passed.

(83) Prior to the block of games commencing processor 204 determines what awards will occupy the award tiles. In an example, the third award tile 2224 is always determined to have a Star Sign feature as an award. In an example, the processor 204 uses RNG 212 and a weighted table stored in memory 208 to select the awards to occupy the award tiles from a set comprising a 10× multiplier, a 5× multiplier, a 2× multiplier, a 1× multiplier, a 0× multiplier and the Star Sign Feature. In some examples, each award tile 2222-2124 has a different weighted table. Where the awards on award tiles 2222 are positive multipliers, the player is awarded total prize value 2240 (that is the total prize awarded over the block of games) multiplied by the multiplier on the award tile.

(84) FIG. 23 illustrates an example where the processor 204 has selected a ×1 multiplier for first award tile 2222 and a ×2 multiplier for second award tile 2223. In the example screen display 2300 of FIG. 22, processor 204 has conducted a first game instance which is winning outcome of 10



credits as indicated by win meter **2360**. Accordingly, processor **204** has modified the display **240** by moving the progress indicator **2250** along path **2220** to a first tile immediately above start tile **2221**. Processor **20** has also controlled the display **240** to show a modified game indicator **2210A** where one of the indicating portions **2211** is greyed-out to indicate one game of the block of games has been conducted and that eleven game instances remain. In FIG. **23**, total prize value **2240** is 10 credits corresponding to the amount won in first game instance.

(85) FIG. **24** is an example screen display **2400** later in the block of game instances. At this modified game indicator **2210B** shows three game instances remaining. Progress indicator **2250** has moved to the seventh tile, here the second award tile **2223**. It will be observed that at this point in play if there are no more winning outcomes in individual games, the processor **204** will make a bonus award of the current total prize value of 240 credits; if there are one or two winning outcomes in the last three game instances, there will be no bonus award; and if there are three winning outcomes, there will be a bonus award of the Star Sign Feature which is conducted as described above in relation to FIG. **5**. Advantageously, this creates balance, particularly towards the end of the block of games, between benefits of achieving additional winning outcomes in individual games and benefits of receiving a bonus award.

(86) FIG. **25** is an example screen display **2500** after the last game instance of a current block of game instances has been conducted as indicated by modified game indicator **2210C**. In this example, the second and third last game instances were winning outcomes resulting in progress indicator **2250** moving to ninth tile immediately below third award tile **2224**. As a result, no bonus award is made by processor **204**.

(87) Subsequent to the end of the block of game instances, processor **204** starts a new block of game instances by selecting new award for the award tiles and resetting game progress indicator.

(88) While the invention has been described with respect to the figures, it will be appreciated that many modifications and changes may be made by those skilled in the art without departing from the spirit of the invention. Any variation and derivation from the above description and figures are included in the scope of the present invention as defined by the claims.

## Claims

1. A gaming device comprising: a display; a random number generator; at least one input mechanism; a processor; and a computer readable storage medium comprising instructions which, when executed by the processor, cause the processor to: control the display to display a plurality of symbol positions defined by symbol position data; perform a selection operation using the random number generator and a data structure comprising a plurality of symbol position patterns to obtain one of the symbol position patterns; modify display of the plurality of symbol positions in accordance with the selected symbol position pattern; perform a symbol selection instance using a plurality of reel strips, wherein the plurality of reel strips comprise a designated symbol, with respect to the plurality of symbol positions until an end condition is met; upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, determine an outcome; conduct symbol selection until the end condition is met by conducting a plurality of symbol selection instances using the plurality of reel strips comprising a designated symbol in which any designated symbol selected for a symbol position of the selected symbol position pattern is held in place for any subsequent instance of the symbol selection instances such that designated symbols accumulate over the plurality of symbol selection games instances; and upon determining a symbol selection instance results in a designated symbol being selected for a symbol position that does not form part of the selected symbol, determine whether the designated symbol selected for a symbol position that does not form part of the selected symbol pattern satisfies a movement condition, and upon the designated symbol satisfying the movement condition, moving the designated symbol to a symbol position of the selected

symbol pattern.

2. The gaming device of claim 1, wherein at least two of the symbol position patterns of the plurality of symbol position patterns comprise different numbers of symbol positions.
3. The gaming device of claim 1, wherein the computer readable medium comprises symbol data defining a plurality of base game reel strips, and wherein the instructions further cause the processor to: generate a base game outcome by selecting symbols from the base game reel strips for the plurality of symbol positions; control the display to display the selected symbols of the base game outcome; and determine whether the base game outcome satisfies a trigger condition as a pre-condition for selecting one of the symbol patterns.
4. The gaming device of claim 3, wherein the trigger condition comprises at least a threshold number of a trigger symbol being included in the base game outcome.
5. The gaming device of claim 3, wherein the trigger condition comprises (i) at least a threshold number of a trigger symbol being included in the base game outcome and (ii) the result of the processor using the random number generator to select between at least two game events being a selection of the game event of selecting one of the symbol patterns.
6. The gaming device of claim 1, further comprising instructions that cause the processor to, subsequent to conducting symbol selection from the plurality of reel strips comprising a designated symbol until the end condition is met, conduct at least one additional gaming instance comprising determining a symbol to occupy the symbol positions of the selected symbol position pattern occupied by the designated symbol when the end condition is met independently of selecting symbol positions for other symbol positions that do not form part of the symbol position pattern.
7. The gaming device of claim 6, further comprising instructions that cause the processor to determine the symbol to occupy the symbol positions of the selected symbol position pattern by using the random number generator to select the symbol from a set of symbols.
8. A method comprising: controlling a display to display a plurality of symbol positions defined by symbol position data; performing a selection operation, using the random number generator and a data structure comprising a plurality of symbol position patterns to obtain one of the plurality of symbol position patterns; modifying display of the plurality of symbol positions in accordance with the selected symbol position pattern; performing a symbol selection instance using a lookup table comprising a plurality of reel strips, wherein the plurality of reel strips comprise a designated symbol with respect to the plurality of symbol positions until an end condition is met, wherein performing symbol selection until the end condition is met comprises conducting a plurality of symbol selection instances using the plurality of reel strips comprising a designated symbol in which any designated symbol selected for a symbol position of the selected symbol position pattern is held in place for any subsequent instance of the symbol selection instances such that designated symbols accumulate over the plurality of symbol selection games instances; upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, determining an outcome; and upon determining a symbol selection instance results in a designated symbol being selected for a symbol position that does not form part of the selected symbol, determining whether the designated symbol selected for a symbol position that does not form part of the selected symbol pattern satisfies a movement condition, and upon the designated symbol satisfying the movement condition, moving the designated symbol to a symbol position of the selected symbol pattern.
9. The method of claim 8, further comprising: generating a base game outcome by selecting symbols from a plurality of base game reel strips for the plurality of symbol positions; controlling the display to display the selected symbols of the base game outcome; and determining whether the base game outcome satisfies a trigger condition as a pre-condition for selecting one of the symbol patterns.
10. The method as claimed in claim 9, wherein the trigger condition comprises at least a threshold number of a trigger symbol being included in the base game outcome.

11. The method of claim 8, further comprising subsequent to conducting symbol selection from the plurality of reel strips comprising a designated symbol until the end condition is met, conducting at least one additional gaming instance comprising determining a symbol to occupy the symbol positions of the selected symbol position pattern occupied by the designated symbol when the end condition is met independently of selecting symbol positions for other symbol positions that do not form part of the symbol position pattern.

12. The method of claim 11, further comprising determining the symbol to occupy the symbol positions of the selected symbol position pattern by using the random number generator to select the symbol from a set of symbols.

13. One or more non-transitory computer readable media comprising computer readable code executable by one or more processors to: perform a selection operation, using the random number generator and a data structure comprising a plurality of symbol position patterns to obtain one of the plurality of symbol position patterns; perform a symbol selection instance using a lookup table comprising a plurality of reel strips, wherein the plurality of reel strips comprise a designated symbol with respect to the plurality of symbol positions until an end condition is met, wherein performing symbol selection until the end condition is met comprises conducting a plurality of symbol selection instances using the plurality of reel strips comprising a designated symbol in which any designated symbol selected for a symbol position of the selected symbol position pattern is held in place for any subsequent instance of the symbol selection instances such that designated symbols accumulate over the plurality of symbol selection games instances; upon all the symbol positions of the selected symbol position pattern being occupied by the designated symbol when the end condition is met, determine an outcome; and upon determining a symbol selection instance results in a designated symbol being selected for a symbol position that does not form part of the selected symbol, determining whether the designated symbol selected for a symbol position that does not form part of the selected symbol pattern satisfies a movement condition, and upon the designated symbol satisfying the movement condition, moving the designated symbol to a symbol position of the selected symbol pattern.

14. The one or more non-transitory computer readable media of claim 13, wherein at least two of the symbol position patterns of the plurality of symbol position patterns comprise different numbers of symbol positions.

15. The one or more non-transitory computer readable media of claim 13, further comprising computer readable code to: generate a base game outcome by selecting symbols from a plurality of base game reel strips for the plurality of symbol positions; controlling the display to display the selected symbols of the base game outcome; and determining whether the base game outcome satisfies a trigger condition as a pre-condition for selecting one of the symbol patterns.

16. The one or more non-transitory computer readable media of claim 15, wherein the trigger condition comprises at least a threshold number of a trigger symbol being included in the base game outcome.

---