

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250257840

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

JUNG; Wonyeong et al.

VACUUM ADIABATIC BODY AND REFRIGERATOR

Abstract

A vacuum adiabatic body includes: a first plate member; a second plate member; a sealing part sealing the first plate member and the second plate member to provide a third space in a vacuum state; a supporting unit; a heat resistance unit for decreasing a heat transfer amount between the first plate member and the second plate member; and an exhaust port through which a gas in the third space is exhausted. The heat resistance unit includes a conductive resistance sheet capable of resisting heat conduction flowing along a wall for the third space, and a side frame fastened to the conductive resistance sheet to define at least one portion of the wall for the third space. Accordingly, a vacuum adiabatic body may be capable of resisting heat conduction.

Inventors: JUNG; Wonyeong (Seoul, KR), YOUN; Deokhyun (Seoul, KR), KIM; Daewoong (Seoul, KR)

Applicant: LG ELECTRONICS INC. (Seoul, KR)

Family ID: 1000008563579

Appl. No.: 19/194262

Filed: April 30, 2025

Foreign Application Priority Data

KR 10-2015-0109728

Aug. 03, 2015

Related U.S. Application Data

parent US continuation 18508279 20231114 parent-grant-document US 12320464 child US 19194262

parent US continuation 17030806 20200924 parent-grant-document US 11920723 child US 18508279

parent US division 15749162 20180131 parent-grant-document US 10816129 WO division PCT/KR2016/008466 20160801 child US 17030806

Publication Classification

Int. Cl.: **F16L59/065** (20060101); **F25D19/00** (20060101); **F25D23/02** (20060101); **F25D23/06** (20060101); **F25D23/08** (20060101)

U.S. Cl.:

CPC **F16L59/065** (20130101); **F25D19/006** (20130101); **F25D23/028** (20130101); **F25D23/062** (20130101); **F25D23/063** (20130101); **F25D23/087** (20130101); **F25D23/085** (20130101); **F25D2201/14** (20130101); **Y02B40/00** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation Application of prior U.S. patent application Ser. No. 18/508,279 filed Nov. 14, 2023, which is a Continuation Application of prior U.S. patent application Ser. No. 17/030,806 filed Sep. 24, 2020 (now U.S. Pat. No. 11,920,723), which is a Divisional Application of U.S. patent application Ser. No. 15/749,162 filed Jan. 31, 2018 (now U.S. Pat. No. 10,816,129), which is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2016/008466, filed Aug. 1, 2016, which claims priority to Korean Patent Application No. 10-2015-0109728, filed Aug. 3, 2015, whose entire disclosures are hereby incorporated by reference.

BACKGROUND

1. Field

[0002] The present disclosure relates to a vacuum adiabatic body and a refrigerator.

2. Background

[0003] A vacuum adiabatic body is a product for suppressing heat transfer by vacuumizing the interior of a body thereof. The vacuum adiabatic body can reduce heat transfer by convection and conduction, and hence is applied to heating apparatuses and refrigerating apparatuses. In a typical adiabatic method applied to a refrigerator, although it is differently applied in refrigeration and freezing, a foam urethane adiabatic wall having a thickness of about 30 cm or more is generally provided. However, the internal volume of the refrigerator is therefore reduced.

[0004] In order to increase the internal volume of a refrigerator, there is an attempt to apply a vacuum adiabatic body to the refrigerator.

[0005] First, Korean Patent No. 10-0343719 (Reference Document 1) of the present applicant has been disclosed. According to Reference Document 1, there is disclosed a method in which a vacuum adiabatic panel is prepared and then built in walls of a refrigerator, and the exterior of the vacuum adiabatic panel is finished with a separate molding as Styrofoam (polystyrene). According to the method, additional foaming is not required, and the adiabatic performance of the refrigerator is improved. However, manufacturing cost is increased, and a manufacturing method is complicated. As another example, a technique of providing walls using a vacuum adiabatic material and additionally providing adiabatic walls using a foam filling material has been disclosed in Korean Patent Publication No. 10-2015-0012712 (Reference Document 2). According to Reference Document 2, manufacturing cost is increased, and a manufacturing method is complicated.

[0006] As another example, there is an attempt to manufacture all walls of a refrigerator using a vacuum adiabatic body that is a single product. For example, a technique of providing an adiabatic structure of a refrigerator to be in a vacuum state has been disclosed in U.S. Patent Laid-Open Publication No. US 2004/0226956 A1 (Reference Document 3).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The embodiments will be described in detail with reference to the following drawings in which like reference numerals refer to like elements wherein:

[0008] FIG. 1 is a perspective view of a refrigerator according to an embodiment.

[0009] FIG. 2 is a view schematically showing a vacuum adiabatic body used in a main body and a door of the refrigerator.

[0010] FIGS. 3 (a) to (c) are views showing various embodiments of an internal configuration of a vacuum space part.

[0011] FIGS. 4 (a) to (c) are views showing various embodiments of conductive resistance sheets and peripheral parts thereof.

[0012] FIG. 5 is a view illustrating in detail a vacuum adiabatic body according to an embodiment.

[0013] FIG. 6 is a view a correlation between a supporting unit and a first plate member, which illustrates any one edge portion.

[0014] FIG. 7 is a view showing an experimental result obtained by comparing the vacuum adiabatic body provided in FIG. 5 and a vacuum adiabatic body provided in FIG. 11.

[0015] FIG. 8 illustrates graphs showing changes in adiabatic performance and changes in gas conductivity with respect to vacuum pressures by applying a simulation.

[0016] FIG. 9 illustrates graphs obtained by observing, over time and pressure, a process of exhausting the interior of the vacuum adiabatic body when a supporting unit is used.

[0017] FIG. 10 illustrates graphs obtained by comparing vacuum pressures and gas conductivities.

[0018] FIG. 11 illustrates a comparative example of the vacuum adiabatic body.

DETAILED DESCRIPTION

[0019] Reference will now be made in detail to the embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings.

[0020] In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration specific preferred embodiments in which the disclosure may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the disclosure, and it is understood that other embodiments may be utilized and that logical structural, mechanical, electrical, and chemical changes may be made without departing from the spirit or scope of the disclosure. To avoid detail not necessary to enable those skilled in the art to practice the disclosure, the description may omit certain information known to those skilled in the art. The following detailed description is, therefore, not to be taken in a limiting sense.

[0021] In the following description, the term 'vacuum pressure' means a certain pressure state lower than atmospheric pressure. In addition, the expression that a vacuum degree of A is higher than that of B means that a vacuum pressure of A is lower than that of B.

[0022] FIG. 1 is a perspective view of a refrigerator according to an embodiment.

[0023] Referring to FIG. 1, the refrigerator 1 includes a main body 2 provided with a cavity 9 capable of storing storage goods and a door 3 provided to open/close the main body 2. The door 3 may be rotatably or movably disposed to open/close the cavity 9. The cavity 9 may provide at least one of a refrigerating chamber and a freezing chamber.

[0024] Parts constituting a freezing cycle may include those in which cold air is supplied into the cavity 9. Specifically, the parts include a compressor 4 for compressing a refrigerant, a condenser 5 for condensing the compressed refrigerant, an expander 6 for expanding the condensed refrigerant, and an evaporator 7 for evaporating the expanded refrigerant to take heat. As a typical structure, a fan may be installed at a position adjacent to the evaporator 7, and a fluid blown from the fan may pass through the evaporator 7 and then be blown into the cavity 9. A freezing load is controlled by

adjusting the blowing amount and blowing direction by the fan, adjusting the amount of a circulated refrigerant, or adjusting the compression rate of the compressor, so that it is possible to control a refrigerating space or a freezing space.

[0025] FIG. 2 is a view schematically showing a vacuum adiabatic body used in the main body and the door of the refrigerator. In FIG. 2, a main body-side vacuum adiabatic body is illustrated in a state in which top and side walls are removed, and a door-side vacuum adiabatic body is illustrated in a state in which a portion of a front wall is removed. In addition, sections of portions at conductive resistance sheets are provided are schematically illustrated for convenience of understanding.

[0026] Referring to FIG. 2, the vacuum adiabatic body includes a first plate member (or first plate) **10** for providing a wall of a low-temperature space, a second plate member (or second plate) **20** for providing a wall of a high-temperature space, and a vacuum space part (or vacuum space, cavity) **50** defined as a gap part (or gap, space) between the first and second plate members **10** and **20**. Also, the vacuum adiabatic body includes the conductive resistance sheets **60** and **63** for preventing heat conduction between the first and second plate members **10** and **20**. A sealing part (or seal, sealing joint) **61** for sealing the first and second plate members **10** and **20** is provided such that the vacuum space part **50** is in a sealing state. When the vacuum adiabatic body is applied to a refrigerating or heating cabinet, the first plate member **10** may be referred to as an inner case, and the second plate member **20** may be referred to as an outer case. A machine chamber **8** in which parts providing a freezing cycle are accommodated is placed at a lower rear side of the main body-side vacuum adiabatic body, and an exhaust port **40** for forming a vacuum state by exhausting air in the vacuum space part **50** is provided at any one side of the vacuum adiabatic body. In addition, a pipeline **64** passing through the vacuum space part **50** may be further installed so as to install a defrosting water line and electric lines.

[0027] The first plate member **10** may define at least one portion of a wall for a first space provided thereto. The second plate member **20** may define at least one portion of a wall for a second space provided thereto. The first space and the second space may be defined as spaces having different temperatures. Here, the wall for each space may serve as not only a wall directly contacting the space but also a wall not contacting the space. For example, the vacuum adiabatic body of the embodiment may also be applied to a product further having a separate wall contacting each space.

[0028] Factors of heat transfer, which cause loss of the adiabatic effect of the vacuum adiabatic body, are heat conduction between the first and second plate members **10** and **20**, heat radiation between the first and second plate members **10** and **20**, and gas conduction of the vacuum space part **50**.

[0029] Hereinafter, a heat resistance unit provided to reduce adiabatic loss related to the factors of the heat transfer will be provided. The heat resistance unit may also be referred to as a thermal insulator, or the like, that provides one or more structural means configured to provide thermal insulation. Meanwhile, the vacuum adiabatic body and the refrigerator of the embodiment do not exclude that another adiabatic means is further provided to at least one side of the vacuum adiabatic body. Therefore, an adiabatic means using foaming or the like may be further provided to another side of the vacuum adiabatic body.

[0030] FIG. 3 is a view showing various embodiments of an internal configuration of the vacuum space part.

[0031] First, referring to FIG. 3a, the vacuum space part **50** is provided in a third space having a different pressure from the first and second spaces, preferably, a vacuum state, thereby reducing adiabatic loss. The third space may be provided at a temperature between the temperature of the first space and the temperature of the second space. Since the third space is provided as a space in the vacuum state, the first and second plate members **10** and **20** receive a force contracting in a direction in which they approach each other due to a force corresponding to a pressure difference between the first and second spaces. Therefore, the vacuum space part **50** may be deformed in a

direction in which it is reduced. In this case, adiabatic loss may be caused due to an increase in amount of heat radiation, caused by the contraction of the vacuum space part **50**, and an increase in amount of heat conduction, caused by contact between the plate members **10** and **20**.

[0032] A supporting unit (or support) **30** may be provided to reduce the deformation of the vacuum space part **50**. The supporting unit **30** includes bars **31**. The bars **31** may extend in a direction substantially vertical to the first and second plate members **10** and **20** so as to support a distance between the first and second plate members **10** and **20**. A support plate **35** may be additionally provided to at least one end of the bar **31**. The support plate **35** connects at least two bars **31** to each other, and may extend in a direction horizontal to the first and second plate members **10** and **20**. The support plate **35** may be provided in a plate shape, or may be provided in a lattice shape such that its area contacting the first or second plate member **10** or **20** is decreased, thereby reducing heat transfer. The bars **31** and the support plate **35** are fixed to each other at at least one portion, to be inserted together between the first and second plate members **10** and **20**. The support plate **35** contacts at least one of the first and second plate members **10** and **20**, thereby preventing deformation of the first and second plate members **10** and **20**. In addition, based on the extending direction of the bars **31**, a total sectional area of the support plate **35** is provided to be greater than that of the bars **31**, so that heat transferred through the bars **31** can be diffused through the support plate **35**.

[0033] A material of the supporting unit **30** may include a resin selected from the group consisting of PC, glass fiber PC, low outgassing PC, PPS, and LCP so as to obtain high compressive strength, low outgassing and water absorptance, low thermal conductivity, high compressive strength at high temperature, and excellent machinability.

[0034] A radiation resistance sheet **32** for reducing heat radiation between the first and second plate members **10** and **20** through the vacuum space part **50** will be described. The first and second plate members **10** and **20** may be made of a stainless material capable of preventing corrosion and providing a sufficient strength. The stainless material has a relatively high emissivity of 0.16, and hence a large amount of radiation heat may be transferred. In addition, the supporting unit **30** made of the resin has a lower emissivity than the plate members, and is not entirely provided to inner surfaces of the first and second plate members **10** and **20**. Hence, the supporting unit **30** does not have great influence on radiation heat. Therefore, the radiation resistance sheet **32** may be provided in a plate shape over a majority of the area of the vacuum space part **50** so as to concentrate on reduction of radiation heat transferred between the first and second plate members **10** and **20**. A product having a low emissivity may be preferably used as the material of the radiation resistance sheet **32**. In an embodiment, an aluminum foil having an emissivity of 0.02 may be used as the radiation resistance sheet **32**. Since the transfer of radiation heat cannot be sufficiently blocked using one radiation resistance sheet, at least two radiation resistance sheets **32** may be provided at a certain distance so as not to contact each other. In addition, at least one radiation resistance sheet may be provided in a state in which it contacts the inner surface of the first or second plate member **10** or **20**.

[0035] Referring to FIG. **3b**, the distance between the plate members is maintained by the supporting unit **30**, and a porous material **33** may be filled in the vacuum space part **50**. The porous material **33** may have a higher emissivity than the stainless material of the first and second plate members **10** and **20**. However, since the porous material **33** is filled in the vacuum space part **50**, the porous material **33** has a high efficiency for resisting the radiation heat transfer.

[0036] In this embodiment, the vacuum adiabatic body can be manufactured without using the radiation resistance sheet **32**.

[0037] Referring to FIG. **3c**, the supporting unit **30** maintaining the vacuum space part **50** is not provided. Instead of the supporting unit **30**, the porous material **33** is provided in a state in which it is surrounded by a film **34**. In this case, the porous material **33** may be provided in a state in which it is compressed so as to maintain the gap of the vacuum space part **50**. The film **34** is made of, for

example, a PE material, and may be provided in a state in which holes are formed therein.

[0038] In this embodiment, the vacuum adiabatic body can be manufactured without using the supporting unit **30**. In other words, the porous material **33** can serve together as the radiation resistance sheet **32** and the supporting unit **30**.

[0039] FIG. **4** is a view showing various embodiments of the conductive resistance sheets and peripheral parts thereof. Structures of the conductive resistance sheets are briefly illustrated in FIG. **2**, but will be understood in detail with reference to FIG. **4**.

[0040] First, a conductive resistance sheet proposed in FIG. **4a** may be preferably applied to the main body-side vacuum adiabatic body. Specifically, the first and second plate members **10** and **20** are to be sealed so as to vacuumize the interior of the vacuum adiabatic body. In this case, since the two plate members have different temperatures from each other, heat transfer may occur between the two plate members. A conductive resistance sheet **60** is provided to prevent heat conduction between two different kinds of plate members.

[0041] The conductive resistance sheet **60** may be provided with sealing parts **61** at which both ends of the conductive resistance sheet **60** are sealed to defining at least one portion of the wall for the third space and maintain the vacuum state. The conductive resistance sheet **60** may be provided as a thin foil in unit of micrometer so as to reduce the amount of heat conducted along the wall for the third space. The sealing parts **61** may be provided as welding parts. That is, the conductive resistance sheet **60** and the plate members **10** and **20** may be fused to each other. In order to cause a fusing action between the conductive resistance sheet **60** and the plate members **10** and **20**, the conductive resistance sheet **60** and the plate members **10** and **20** may be made of the same material, and a stainless material may be used as the material. The sealing parts **61** are not limited to the welding parts, and may be provided through a process such as cocking. The conductive resistance sheet **60** may be provided in a curved shape. Thus, a heat conduction distance of the conductive resistance sheet **60** is provided longer than the linear distance of each plate member, so that the amount of heat conduction can be further reduced.

[0042] A change in temperature occurs along the conductive resistance sheet **60**. Therefore, in order to block heat transfer to the exterior of the conductive resistance sheet **60**, a shielding part **62** (or shield) may be provided at the exterior of the conductive resistance sheet **60** such that an adiabatic action occurs. In other words, in the refrigerator, the second plate member **20** has a high temperature and the first plate member **10** has a low temperature. In addition, heat conduction from high temperature to low temperature occurs in the conductive resistance sheet **60**, and hence the temperature of the conductive resistance sheet **60** is suddenly changed. Therefore, when the conductive resistance sheet **60** is opened to the exterior thereof, heat transfer through the opened place may seriously occur. In order to reduce heat loss, the shielding part **62** is provided at the exterior of the conductive resistance sheet **60**. For example, when the conductive resistance sheet **60** is exposed to any one of the low-temperature space and the high-temperature space, the conductive resistance sheet **60** does not serve as a conductive resistor as well as the exposed portion thereof, which is not preferable.

[0043] The shielding part **62** may be provided as a porous material contacting an outer surface of the conductive resistance sheet **60**. The shielding part **62** may be provided as an adiabatic structure, e.g., a separate gasket, which is placed at the exterior of the conductive resistance sheet **60**. The shielding part **62** may be provided as a portion of the vacuum adiabatic body, which is provided at a position facing a corresponding conductive resistance sheet **60** when the main body-side vacuum adiabatic body is closed with respect to the door-side vacuum adiabatic body. In order to reduce heat loss even when the main body and the door are opened, the shielding part **62** may be preferably provided as a porous material or a separate adiabatic structure.

[0044] A conductive resistance sheet proposed in FIG. **4b** may be preferably applied to the door-side vacuum adiabatic body. In FIG. **4b**, portions different from those of FIG. **4a** are described in detail, and the same description is applied to portions identical to those of FIG. **4a**. A side frame **70**

is further provided at an outside of the conductive resistance sheet **60**. A part for sealing between the door and the main body, an exhaust port necessary for an exhaust process, a getter port for vacuum maintenance, and the like may be placed on the side frame **70**. This is because the mounting of parts is convenient in the main body-side vacuum adiabatic body, but the mounting positions of parts are limited in the door-side vacuum adiabatic body.

[0045] The side frame **70** may be provided to have a thinner thickness than each of the plate members **10** and **20**. Accordingly, the side frame **70** may function to resist heat conduction with respect to cold air passing through the conductive resistance sheet **60**.

[0046] In the door-side vacuum adiabatic body, it is difficult to place the conductive resistance sheet **60** at a front end portion of the vacuum space part, i.e., a corner side portion of the vacuum space part. This is because, unlike the main body, a corner edge portion of the door is exposed to the exterior. More specifically, if the conductive resistance sheet **60** is placed at the front end portion of the vacuum space part, the corner edge portion of the door is exposed to the exterior, and hence there is a disadvantage in that a separate adiabatic part should be configured so as to heat-insulate the conductive resistance sheet **60**.

[0047] A conductive resistance sheet proposed in FIG. **4c** may be preferably installed in the pipeline passing through the vacuum space part. In FIG. **4c**, portions different from those of FIGS. **4a** and **4b** are described in detail, and the same description is applied to portions identical to those of FIGS. **4a** and **4b**. A conductive resistance sheet having the same shape as that of FIG. **4a**, preferably, a wrinkled conductive resistance sheet (or folded conductive resistance sheet) **63** may be provided at a peripheral portion of the pipeline **64**. Accordingly, a heat transfer path can be lengthened, and deformation caused by a pressure difference can be prevented. In addition, a separate shielding part may be provided to improve the adiabatic performance of the conductive resistance sheet.

[0048] A heat transfer path between the first and second plate members **10** and **20** will be described with reference back to FIG. **4a**. Heat passing through the vacuum adiabatic body may be divided into surface conduction heat {circle around (1)} conducted along a surface of the vacuum adiabatic body, more specifically, the conductive resistance sheet **60**, supporter conduction heat {circle around (2)} conducted along the supporting unit **30** provided inside the vacuum adiabatic body, gas conduction heat (or convection) {circle around (3)} conducted through an internal gas in the vacuum space part, and radiation transfer heat {circle around (4)} transferred through the vacuum space part.

[0049] The transfer heat may be changed depending on various design dimensions. For example, the supporting unit may be changed such that the first and second plate members **10** and **20** can endure a vacuum pressure without being deformed, the vacuum pressure may be changed, the distance between the plate members may be changed, and the length of the conductive resistance sheet may be changed. The transfer heat may be changed depending on a difference in temperature between the spaces (the first and second spaces) respectively provided by the plate members. In the embodiment, a preferred configuration of the vacuum adiabatic body has been found by considering that its total heat transfer amount is smaller than that of a typical adiabatic structure formed by foaming polyurethane. In a typical refrigerator including the adiabatic structure formed by foaming the polyurethane, an effective heat transfer coefficient may be proposed as 19.6 mW/mK.

[0050] By performing a relative analysis on heat transfer amounts of the vacuum adiabatic body of the embodiment, a heat transfer amount by the gas conduction heat {circle around (3)} can become smallest. For example, the heat transfer amount by the gas conduction heat {circle around (3)} may be controlled to be equal to or smaller than 4% of the total heat transfer amount. A heat transfer amount by solid conduction heat defined as a sum of the surface conduction heat {circle around (1)} and the supporter conduction heat {circle around (2)} is largest. For example, the heat transfer amount by the solid conduction heat may reach 75% of the total heat transfer amount. A heat

transfer amount by the radiation transfer heat {circle around (4)} is smaller than the heat transfer amount by the solid conduction heat but larger than the heat transfer amount of the gas conduction heat {circle around (3)}. For example, the heat transfer amount by the radiation transfer heat {circle around (4)} may occupy about 20% of the total heat transfer amount.

[0051] According to such a heat transfer distribution, effective heat transfer coefficients (ek: effective K) (W/mK) of the surface conduction heat {circle around (1)}, the supporter conduction heat {circle around (2)}, the gas conduction heat {circle around (3)}, and the radiation transfer heat {circle around (4)} may have an order of Equation 1.

$$[00001] \text{ } eK_{\text{solidconductionheat}} > eK_{\text{radiationtransferheat}} > eK_{\text{gasconductionheat}} \quad \text{Equation1}$$

[0052] Here, the effective heat transfer coefficient (ek) is a value that can be measured using a shape and temperature differences of a target product. The effective heat transfer coefficient (ek) is a value that can be obtained by measuring a total heat transfer amount and a temperature at least one portion at which heat is transferred. For example, a calorific value (W) is measured using a heating source that can be quantitatively measured in the refrigerator, a temperature distribution (K) of the door is measured using heat respectively transferred through a main body and an edge of the door of the refrigerator, and a path through which heat is transferred is calculated as a conversion value (m), thereby evaluating an effective heat transfer coefficient.

[0053] The effective heat transfer coefficient (ek) of the entire vacuum adiabatic body is a value given by $k=QL/A\Delta T$. Here, Q denotes a calorific value (W) and may be obtained using a calorific value of a heater. A denotes a sectional area (m²) of the vacuum adiabatic body, L denotes a thickness (m) of the vacuum adiabatic body, and ΔT denotes a temperature difference.

[0054] For the surface conduction heat, a conductive calorific value may be obtained through a temperature difference (ΔT) between an entrance and an exit of the conductive resistance sheet **60** or **63**, a sectional area (A) of the conductive resistance sheet, a length (L) of the conductive resistance sheet, and a thermal conductivity (k) of the conductive resistance sheet (the thermal conductivity of the conductive resistance sheet is a material property of a material and can be obtained in advance). For the supporter conduction heat, a conductive calorific value may be obtained through a temperature difference (ΔT) between an entrance and an exit of the supporting unit **30**, a sectional area (A) of the supporting unit, a length (L) of the supporting unit, and a thermal conductivity (k) of the supporting unit. Here, the thermal conductivity of the supporting unit is a material property of a material and can be obtained in advance. The sum of the gas conduction heat {circle around (3)}, and the radiation transfer heat {circle around (4)} may be obtained by subtracting the surface conduction heat and the supporter conduction heat from the heat transfer amount of the entire vacuum adiabatic body. A ratio of the gas conduction heat {circle around (3)}, and the radiation transfer heat {circle around (4)} may be obtained by evaluating radiation transfer heat when no gas conduction heat exists by remarkably lowering a vacuum degree of the vacuum space part **50**.

[0055] When a porous material is provided inside the vacuum space part **50**, porous material conduction heat {circle around (5)} may be a sum of the supporter conduction heat {circle around (2)} and the radiation transfer heat {circle around (4)}. The porous material conduction heat {circle around (5)} may be changed depending on various variables including a kind, an amount, and the like of the porous material.

[0056] According to an embodiment, a temperature difference $\Delta T1$ between a geometric center formed by adjacent bars **31** and a point at which each of the bars **31** is located may be preferably provided to be less than 0.5° C. Also, a temperature difference $\Delta T2$ between the geometric center formed by the adjacent bars **31** and an edge portion of the vacuum adiabatic body may be preferably provided to be less than 0.5 0.5° C. In the second plate member **20**, a temperature difference between an average temperature of the second plate and a temperature at a point at which a heat transfer path passing through the conductive resistance sheet **60** or **63** meets the

second plate may be largest. For example, when the second space is a region hotter than the first space, the temperature at the point at which the heat transfer path passing through the conductive resistance sheet meets the second plate member becomes lowest. Similarly, when the second space is a region colder than the first space, the temperature at the point at which the heat transfer path passing through the conductive resistance sheet meets the second plate member becomes highest. [0057] This means that the amount of heat transferred through other points except the surface conduction heat passing through the conductive resistance sheet should be controlled, and the entire heat transfer amount satisfying the vacuum adiabatic body can be achieved only when the surface conduction heat occupies the largest heat transfer amount. To this end, a temperature variation of the conductive resistance sheet may be controlled to be larger than that of the plate member.

[0058] Physical characteristics of the parts constituting the vacuum adiabatic body will be described. In the vacuum adiabatic body, a force by vacuum pressure is applied to all of the parts. Therefore, a material having a strength (N/m²) of a certain level may be preferably used.

[0059] Under such circumstances, the plate members **10** and **20** and the side frame **70** may be preferably made of a material having a sufficient strength with which they are not damaged by even vacuum pressure. For example, when the number of bars **31** is decreased so as to limit the support conduction heat, deformation of the plate member occurs due to the vacuum pressure, which may be a bad influence on the external appearance of refrigerator. The radiation resistance sheet **32** may be preferably made of a material that has a low emissivity and can be easily subjected to thin film processing. Also, the radiation resistance sheet **32** is to ensure a strength high enough not to be deformed by an external impact. The supporting unit **30** is provided with a strength high enough to support the force by the vacuum pressure and endure an external impact, and is to have machinability. The conductive resistance sheet **60** may be preferably made of a material that has a thin plate shape and can endure the vacuum pressure.

[0060] In an embodiment, the plate member, the side frame, and the conductive resistance sheet may be made of stainless materials having the same strength. The radiation resistance sheet may be made of aluminum having a weaker strength than the stainless materials. The supporting unit may be made of resin having a weaker strength than the aluminum.

[0061] Unlike the strength from the point of view of materials, analysis from the point of view of stiffness is required. The stiffness (N/m) is a property that would not be easily deformed. Although the same material is used, its stiffness may be changed depending on its shape. The conductive resistance sheets **60** or **63** may be made of a material having a prescribed strength, but the stiffness of the material is preferably low so as to increase heat resistance and minimize radiation heat as the conductive resistance sheet is uniformly spread without any roughness when the vacuum pressure is applied. The radiation resistance sheet **32** requires a stiffness of a certain level so as not to contact another part due to deformation. Particularly, an edge portion of the radiation resistance sheet may generate conduction heat due to drooping caused by the self-load of the radiation resistance sheet. Therefore, a stiffness of a certain level is required. The supporting unit **30** requires a stiffness high enough to endure a compressive stress from the plate member and an external impact.

[0062] In an embodiment, the plate member and the side frame may preferably have the highest stiffness so as to prevent deformation caused by the vacuum pressure. The supporting unit, particularly, the bar may preferably have the second highest stiffness. The radiation resistance sheet may preferably have a stiffness that is lower than that of the supporting unit but higher than that of the conductive resistance sheet. The conductive resistance sheet may be preferably made of a material that is easily deformed by the vacuum pressure and has the lowest stiffness.

[0063] Even when the porous material **33** is filled in the vacuum space part **50**, the conductive resistance sheet may preferably have the lowest stiffness, and the plate member and the side frame may preferably have the highest stiffness.

[0064] FIG. 5 is a view illustrating in detail a vacuum adiabatic body according to an embodiment.

FIG. 5 shows a view of a distal end region of the vacuum space including a side part of the second plate member. The embodiment proposed in FIG. 5 may be preferably applied to the door-side vacuum adiabatic body, and the description of the vacuum adiabatic body shown in FIG. 4b among the vacuum adiabatic bodies shown in FIG. 4 may be applied to portions to which specific descriptions are not provided.

[0065] Referring to FIG. 5, the vacuum adiabatic body may include a first plate member **10**, a second plate member **20**, a conductive resistance sheet **60**, and a side frame **70**, which are parts that enable a vacuum space part **50** to be separated from an external atmospheric space.

[0066] The side frame **70** is formed in a bent shape, and may be provided such that the height of the side frame **70** is lowered at an outer portion, i.e., an edge portion or distal end portion when viewed from the entire shape of the vacuum adiabatic body. The side frame **70** may be provided in a shape in which a gap part between the side frame **70** and the second plate member **20** is divided into a portion having a high height h_1 and a portion having a low height h_2 .

[0067] According to the above-described shape, the portion having the low height in the side frame **70** can secure a predetermined space as compared with other portions outside the vacuum adiabatic body. An addition mounting part (or addition mounting portion or surface) **80** in which an addition such as an exhaust port **40** or a door hinge is mounted may be provided due to a height difference of the side frame **70**. Accordingly, it is possible to maximally secure the internal volume of a product such as the refrigerator provided by the vacuum adiabatic body, to improve an adiabatic effect, and to sufficiently ensure functions of the product.

[0068] One end of the side frame **70** is fastened to the conductive resistance sheet **60** by a sealing part **61**, and the other end of the side frame **70** is fastened to the second plate member **20** by an edge part **611** (or edge joint, seal). The edge part **611** may be provided as a welding part. The vacuum space part **50** extends up to the edge part **611**, thereby improving an adiabatic effect.

[0069] The side frame **70** provides a path through which solid conduction heat passing through the conductive resistance sheet **60** passes. In the refrigerator, cold air (or coldness from contact with cold air, heat transfer) passing through the conductive resistance sheet **60** may be transferred to the edge part **611** that is a contact point between the side frame **70** and a side part (or side portion or second section) **202** of the second plate member **20**. However, the cold air may not only be reduced by the conductive resistance sheet **60** but also sufficiently resist while flowing along the side frame **70**. Nevertheless, although dew may be formed, the formed dew may not be visible from the exterior.

[0070] Specifically, the second plate member **20** includes a front part (or front portion or first section) **201** and the side part **202** bent with respect to the front part **201**. However, the side part **202** is not exposed to the exterior. Thus, although dew may be formed on the side part **202**, a user cannot observe the formed dew with the naked eye, thereby improving a user's emotion. In addition, when the edge part **611** is provided as a welding part, a welding line inevitably generated due to heating is not viewed from the exterior, thereby improving a user's sense of beauty. It can be easily assumed that the side part **202** forms an outer wall of the vacuum space part **50**.

[0071] Although the edge part **611** is provided at a corner portion of the front part **201** adjacent to the side part **202** in addition to the side part **202**, the edge part may not be observed by the user. As another example, the edge part **611** may be provided to an edge portion of the second plate member **20**, to enhance convenience of manufacturing while not being observed with the naked eye.

[0072] The formation of dew can be easily understood through a dew forming region (or joint, contact point) **71** generated due to a decrease in temperature at a contact portion of the side frame **70** with the front part **201** in a comparative example proposed in FIG. 11.

[0073] In the refrigerator, the cold air passing through the conductive resistance sheet **60** is transferred to the side frame **70**, and hence the side frame **70** has a relatively higher temperature than the first plate member **10**. Thus, when assuming that the entire region of the second plate member **20** contacting the other ends of first and second bars **311** and **312** has the same

temperature, a temperature of the side frame **70** contacting one end of the second bar **313** can be maintained higher than that of the first plate member **10** contacting one end of the first bar **311**. Accordingly, although lengths of the first and second bars **311** and **313** are different from each other, heat conduction through the first bar **311** can be maintained equally to that through the second bar **313**. According to an experiment, it has been found that a second vacuum space part (or second vacuum space) **502** having a height of 1 to 2 mm can obtain a sufficient adiabatic effect equal to that of a first vacuum space part (or first vacuum space) **501** having a height of 10 to 20 mm.

[0074] The vacuum space part **50** includes the first vacuum space part **501** of which height is h_1 and the second vacuum space part **502** of which height is h_2 smaller than h_1 . The first and second vacuum space parts **501** and **502** can communicate with each other in a vacuum state. Accordingly, it is possible to reduce inconvenience of a manufacturing process in which a vacuum space part is separately formed.

[0075] A second support plate **352** may be provided to extend inside the second vacuum space part **502**. In addition, the second bar **312** having a lower height than the first bar **311** may be provided to the second support plate **352**. Thus, the gap of the second vacuum space part **502** can be maintained by the second bar **312**. The second bar **312** may be provided as a single body with the second support plate **352**. Since the heights of the first and second vacuum space parts **501** and **502** are different from each other, a first support plate **351** may not extend to the second vacuum space part **502**. However, the present disclosure is not limited thereto, and the first support plate **351** may extend to the second vacuum space part **502**. Although the first support plate **351** does not extend to the second vacuum space part **502**, the flow of heat conducted from the first plate member **10** to the side frame **70** is resisted by the conductive resistance sheet **60**, and thus conduction heat through the second bar **312** can obtain an equal effect of heat resistance as compared with heat conduction through the first bar **311**.

[0076] As already described above, the conductive resistance sheet **60** has one purpose to resist heat transfer from the first plate member **10**. Therefore, a rapid change in temperature occurs in the conductive resistance sheet **60** along the direction of the heat transfer. It has been described that the shielding part (or shield) **62** is provided to block heat transferred to the outside of the vacuum adiabatic body, corresponding to the rapid change in temperature. As the vacuum space part **50** is provided, heat transferred to the inside of the vacuum adiabatic body through the conductive resistance sheet **60** can obtain an adiabatic effect with respect to convection and solid conduction heat, but is weak against heat transfer caused by radiation and gas conduction. In order to solve such a problem, a radiation resistance sheet **32** may be placed even under a lower side of the conductive resistance sheet **60**.

[0077] Specifically, the radiation resistance sheet **32** may include first, second, and third radiation resistance sheets **321**, **322**, and **323** sequentially provided in a direction toward the second support plate **352** from the first support plate **351**. The first radiation resistance sheet **321** may extend up to the lower side of the conductive resistance sheet **60** by passing through an end portion of the first support plate **351**. The second radiation resistance sheet **322** may extend outward by w_2 as compared with the first radiation resistance sheet **321**. The third radiation resistance sheet **323** may extend outward by w_1 as compared with the second radiation resistance sheet **322**.

[0078] According to such a configuration, the radiation resistance sheet **32** provided as a thin plate may be deformed by an external impact and load. This is because, if any deformed radiation resistance sheet contacts another adjacent radiation resistance sheet or the conductive resistance sheet **60**, direct heat conduction occurs, and therefore, a large amount of adiabatic loss occurs. Therefore, the first radiation resistance sheet **321** may extend not to reach the center of the conductive resistance sheet **60** even when a predetermined deformation occurs in the first radiation resistance sheet **321**. Since it is less likely that the second radiation resistance sheet **322** will contact the conductive resistance sheet **60**, the second radiation resistance sheet **322** may extend

further outward by passing through the center of the conductive resistance sheet **60**. However, since it is likely that the second radiation resistance sheet **322** will contact another adjacent radiation resistance sheet, a length of the second radiation resistance sheet **322** extending from the first bar **311** is preferably limited to 10 to 15 mm when the radiation resistance sheet is an aluminum sheet having a thickness of 0.3 to 0.4 mm. The third radiation resistance sheet **323** may extend outward by **w1** as compared with the second radiation resistance sheet **322**. This is because the third radiation resistance sheet **323** is supported by the second support plate **352**.

[0079] In FIG. 5, it is illustrated that the radiation resistance sheet **32** does not extend inside the second vacuum space part **502**. However, the present disclosure is not limited thereto, and the third radiation resistance sheet **323** of which at least one portion is provided to contact the second support plate **352** may extend up to the inside of the second vacuum space part **502**, thereby reducing radiation conduction heat.

[0080] A mounting end part (or protrusion, tab) **101** is provided at a corner of the first plate member **10**, and a rib **102** is provided in the supporting unit **30**. As the mounting end part **101** is guided by the rib **102**, the first plate member **10** and the supporting unit **30** can be placed at accurate positions, respectively. Thus, it is possible to improve fastening accuracy between parts.

[0081] FIG. 6 is a view a correlation between the supporting unit and the first plate member, which illustrates any one edge portion.

[0082] Referring to FIG. 6, there may be provided a structure in which the rib **102** provided to the second support plate **352** and the mounting end part **101** provided to the first plate member **10** contact each other. Thus, when the first plate member **10** is fastened to the supporting unit **30** or when the supporting unit **30** is fastened to the first plate member **10**, a position between the first plate member **10** and the supporting unit **30** can be accurately placed. The mounting end part **101** and the rib **102** have structures corresponding to each other, and their sizes and numbers may be increased/decreased depending on sizes of the first plate member **10** and the supporting unit **30**.

[0083] The second bar **312** having a lower height than the first bar **311** is provided at an edge portion of the second support plate **352** provided in grid shape. Thus, it is possible to maintain the gap of the second vacuum space part **502**.

[0084] FIG. 7 is a view showing an experimental result obtained by comparing the vacuum adiabatic body provided in FIG. 5 and the vacuum adiabatic body provided in FIG. 11.

[0085] Referring to FIG. 7, when the vacuum adiabatic bodies were used for the door of the refrigerator, and the refrigerator performed a standard operation, temperatures at edge portions of the vacuum adiabatic bodies were measured. As a result obtained by performing an experiment, when typical foaming urethane is used, a temperature at a top side Top of the vacuum adiabatic body was 2.2 0.5° C., temperatures at both sides Mid having a middle height of the vacuum adiabatic body were 1.4 0.5° C., a temperature at a bottom side Bottom of the vacuum adiabatic body was 1.3 0.5° C., and a temperature at a center Center of the vacuum adiabatic body was 0.8 0.5° C. In the comparative example proposed in FIG. 11, a temperature at a top side Top of the vacuum adiabatic body was 1.0 0.5° C., temperatures at both sides Mid having a middle height of the vacuum adiabatic body were -0.3 0.5° C., a temperature at a bottom side Bottom of the vacuum adiabatic body was -0.5 0.5° C., and a temperature at a center Center of the vacuum adiabatic body was 1.3 0.5° C. According to the comparative example, dew may be formed at the top side Top, both the sides Middle having the middle height, and the bottom side Bottom. Particularly, it can be seen that dew may be formed at both the sides Middle having the middle height and the bottom side Bottom in a condition that an external air temperature is 25 0.5° C. and a relative humidity is 87% due to a low temperature below zero.

[0086] On the other hand, in the embodiment, a temperature at a top side Top of the vacuum adiabatic body was 2.4 0.5° C., temperatures at both sides Mid having a middle height of the vacuum adiabatic body were 1.3 0.5° C., a temperature at a bottom side Bottom of the vacuum adiabatic body was 1.2 0.5° C., and a temperature at a center Center of the vacuum adiabatic body

was 1.3 0.5° C. According to the embodiment, it is possible to obtain a better effect as compared with when the typical foaming urethane is used, and it can be seen that the formation of dew on a front surface of the door is prevented.

[0087] Hereinafter, a vacuum pressure preferably determined depending on an internal state of the vacuum adiabatic body. As already described above, a vacuum pressure is to be maintained inside the vacuum adiabatic body so as to reduce heat transfer. At this time, it will be easily expected that the vacuum pressure is preferably maintained as low as possible so as to reduce the heat transfer.

[0088] The vacuum space part may resist the heat transfer by applying only the supporting unit **30**. Alternatively, the porous material **33** may be filled together with the supporting unit in the vacuum space part **50** to resist the heat transfer. Alternatively, the vacuum space part may resist the heat transfer not by applying the supporting unit but by applying the porous material **33**.

[0089] The case where only the supporting unit is applied will be described.

[0090] FIG. **8** illustrates graphs showing changes in adiabatic performance and changes in gas conductivity with respect to vacuum pressures by applying a simulation.

[0091] Referring to FIG. **8**, it can be seen that, as the vacuum pressure is decreased, i.e., as the vacuum degree is increased, a heat load in the case of only the main body (Graph **1**) or in the case where the main body and the door are joined together (Graph **2**) is decreased as compared with that in the case of the typical product formed by foaming polyurethane, thereby improving the adiabatic performance. However, it can be seen that the degree of improvement of the adiabatic performance is gradually lowered. Also, it can be seen that, as the vacuum pressure is decreased, the gas conductivity (Graph **3**) is decreased. However, it can be seen that, although the vacuum pressure is decreased, the ratio at which the adiabatic performance and the gas conductivity are improved is gradually lowered. Therefore, it is preferable that the vacuum pressure is decreased as low as possible. However, it takes long time to obtain excessive vacuum pressure, and much cost is consumed due to excessive use of a getter. In the embodiment, an optimal vacuum pressure is proposed from the above-described point of view.

[0092] FIG. **9** illustrates graphs obtained by observing, over time and pressure, a process of exhausting the interior of the vacuum adiabatic body when the supporting unit is used.

[0093] Referring to FIG. **9**, in order to create the vacuum space part **50** to be in the vacuum state, a gas in the vacuum space part **50** is exhausted by a vacuum pump while evaporating a latent gas remaining in the parts of the vacuum space part **50** through baking. However, if the vacuum pressure reaches a certain level or more, there exists a point at which the level of the vacuum pressure is not increased any more ($\Delta t1$). After that, the getter is activated by disconnecting the vacuum space part **50** from the vacuum pump and applying heat to the vacuum space part **50** ($\Delta t2$). If the getter is activated, the pressure in the vacuum space part **50** is decreased for a certain period of time, but then normalized to maintain a vacuum pressure of a certain level. The vacuum pressure that maintains the certain level after the activation of the getter is approximately 1.8×10^{-6} Torr.

[0094] In the embodiment, a point at which the vacuum pressure is not substantially decreased any more even though the gas is exhausted by operating the vacuum pump is set to the lowest limit of the vacuum pressure used in the vacuum adiabatic body, thereby setting the minimum internal pressure of the vacuum space part **50** to 1.8×10^{-6} Torr.

[0095] FIG. **10** illustrates graphs obtained by comparing vacuum pressures and gas conductivities.

[0096] Referring to FIG. **10**, gas conductivities with respect to vacuum pressures depending on sizes of a gap in the vacuum space part **50** are represented as graphs of effective heat transfer coefficients (ek). Effective heat transfer coefficients (ek) were measured when the gap in the vacuum space part **50** has three sizes of 2.76 mm, 6.5 mm, and 12.5 mm. The gap in the vacuum space part **50** is defined as follows. When the radiation resistance sheet **32** exists inside vacuum space part **50**, the gap is a distance between the radiation resistance sheet **32** and the plate member adjacent thereto. When the radiation resistance sheet **32** does not exist inside vacuum space part **50**, the gap is a distance between the first and second plate members.

[0097] It can be seen that, since the size of the gap is small at a point corresponding to a typical effective heat transfer coefficient of 0.0196 W/mK , which is provided to a adiabatic material formed by foaming polyurethane, the vacuum pressure is $2.65 \times 10^{-1} \text{ Torr}$ even when the size of the gap is 2.76 mm . Meanwhile, it can be seen that the point at which reduction in adiabatic effect caused by gas conduction heat is saturated even though the vacuum pressure is decreased is a point at which the vacuum pressure is approximately $4.5 \times 10^{-3} \text{ Torr}$. The vacuum pressure of $4.5 \times 10^{-3} \text{ Torr}$ can be defined as the point at which the reduction in adiabatic effect caused by gas conduction heat is saturated. Also, when the effective heat transfer coefficient is 0.1 W/mK , the vacuum pressure is $1.2 \times 10^{-2} \text{ Torr}$.

[0098] When the vacuum space part **50** is not provided with the supporting unit but provided with the porous material, the size of the gap ranges from a few micrometers to a few hundreds of micrometers. In this case, the amount of radiation heat transfer is small due to the porous material even when the vacuum pressure is relatively high, i.e., when the vacuum degree is low. Therefore, an appropriate vacuum pump is used to adjust the vacuum pressure. The vacuum pressure appropriate to the corresponding vacuum pump is approximately $2.0 \times 10^{-4} \text{ Torr}$. Also, the vacuum pressure at the point at which the reduction in adiabatic effect caused by gas conduction heat is saturated is approximately $4.7 \times 10^{-2} \text{ Torr}$. Also, the pressure where the reduction in adiabatic effect caused by gas conduction heat reaches the typical effective heat transfer coefficient of 0.0196 W/mK is 730 Torr .

[0099] When the supporting unit and the porous material are provided together in the vacuum space part, a vacuum pressure may be created and used, which is middle between the vacuum pressure when only the supporting unit is used and the vacuum pressure when only the porous material is used.

[0100] In the description of the present disclosure, a part for performing the same action in each embodiment of the vacuum adiabatic body may be applied to another embodiment by properly changing the shape or dimension of the other embodiment. Accordingly, still another embodiment can be easily proposed. For example, in the detailed description, in the case of a vacuum adiabatic body suitable as a door-side vacuum adiabatic body, the vacuum adiabatic body may be applied as a main body-side vacuum adiabatic body by properly changing the shape and configuration of a vacuum adiabatic body.

[0101] Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

[0102] The vacuum adiabatic body proposed in the present disclosure may be preferably applied to refrigerators. However, the application of the vacuum adiabatic body is not limited to the refrigerators, and may be applied in various apparatuses such as cryogenic refrigerating apparatuses, heating apparatuses, and ventilation apparatuses.

[0103] According to the present disclosure, the vacuum adiabatic body can be industrially applied to various adiabatic apparatuses. The adiabatic effect can be enhanced, so that it is possible to improve energy use efficiency and to increase the effective volume of an apparatus.

[0104] However, it is difficult to obtain an adiabatic effect of a practical level by providing the walls of the refrigerator to be in a sufficient vacuum state. Specifically, it is difficult to prevent heat transfer at a contact portion between external and internal cases having different temperatures. Further, it is difficult to maintain a stable vacuum state. Furthermore, it is difficult to prevent deformation of the cases due to a sound pressure in the vacuum state. Due to these problems, the

technique of Reference Document 3 is limited to cryogenic refrigerating apparatuses, and is not applied to refrigerating apparatuses used in general households.

[0105] Embodiments provide a vacuum adiabatic body and a refrigerator, which can obtain a sufficient adiabatic effect in a vacuum state and be applied commercially.

[0106] In one embodiment, a vacuum adiabatic body includes: a first plate member defining at least one portion of a wall for a first space; a second plate member defining at least one portion of a wall for a second space having a different temperature from the first space; a sealing part sealing the first plate member and the second plate member to provide a third space that has a temperature between the temperature of the first space and the temperature of the second space and is in a vacuum state; a supporting unit maintaining the third space; a heat resistance unit for decreasing a heat transfer amount between the first plate member and the second plate member; and an exhaust port through which a gas in the third space is exhausted, wherein the heat resistance unit includes a conductive resistance sheet capable of resisting heat conduction flowing along a wall for the third space, and a side frame fastened to the conductive resistance sheet to define at least one portion of the wall for the third space.

[0107] The side frame may extend in a direction of an end portion of the vacuum adiabatic body. The side frame may be fastened to each of the first and second plate members at an edge portion of the vacuum adiabatic body. The side frame may be sealed with the conductive resistance sheet. The side frame may be provided in a bent shape. The supporting unit may include: at least one support plate capable of extending in a horizontal direction with respect to the first plate member and the second plate member; and at least one bar provided to the support plate to be interposed between the first plate member and the second plate member. The bar may contact the side frame. The support plate may have a plate shape or a grid shape. The vacuum adiabatic body may include at least two radiation resistance sheets provided in a plate shape inside the third space. At least one of the radiation resistance sheets may extend down to a lower side of the conductive resistance sheet. The radiation resistance sheet may further extend outward as it reaches from the first plate member to the second plate member.

[0108] In another embodiment, a vacuum adiabatic body includes: a first plate member defining at least one portion of a wall for a first space; a second plate member defining at least one portion of a wall for a second space having a different temperature from the first space; a sealing part sealing the first plate member and the second plate member to provide a third space that has a temperature between the temperature of the first space and the temperature of the second space and is in a vacuum state; a supporting unit maintaining the third space; a heat resistance unit for decreasing a heat transfer amount between the first plate member and the second plate member; and an exhaust port through which a gas in the third space is exhausted, wherein the heat resistance unit includes a conductive resistance sheet capable of resisting heat conduction flowing along a wall for the third space, and a side frame fastened to the conductive resistance sheet, and wherein the heat resistance unit includes at least one radiation resistance sheet provided in a plate shape inside the third space or includes a porous material to resist radiation heat transfer between the second plate member and the first plate member inside the third space.

[0109] One surface of the conductive resistance sheet may be heat-insulated by the third space, and another surface of the conductive resistance sheet may be shielded by a shielding part. The conductive resistance sheet may have a lower stiffness than each of the first and second plate members, the radiation resistance sheet, and the supporting unit. The conductive resistance sheet may define, together with each of the first and second plate members, at least one portion of the wall for the third space.

[0110] In still another embodiment, a refrigerator includes: a main body provided with an internal space in which storage goods are stored; and a door provided to open/close the main body from an external space, wherein, in order to supply a refrigerant into the main body, the refrigerator includes: a compressor for compressing the refrigerant; a condenser for condensing the compressed

refrigerant; an expander for expanding the condensed refrigerant; and an evaporator for evaporating the expanded refrigerant to take heat, wherein at least one of the main body and the door includes a vacuum adiabatic body, wherein the vacuum adiabatic body includes: a first plate member defining at least one portion of a wall for the internal space; a second plate member defining at least one portion of a wall for the external space; a sealing part sealing the first plate member and the second plate member to provide a vacuum space part that has a temperature between a temperature of the internal space and a temperature of the external space and is in a vacuum state; a supporting unit maintaining the vacuum space part; a heat resistance unit for decreasing a heat transfer amount between the first plate member and the second plate member; and an exhaust port through which a gas in the vacuum space part is exhausted, wherein the heat resistance unit includes a conductive resistance sheet capable of resisting heat conduction flowing along a wall for the vacuum space part, and a side frame fastened to the conductive resistance sheet.

[0111] The side frame may extend up to an outermost side of the vacuum adiabatic body. The side frame may be fastened to an edge portion of the second plate member. The side frame may define at least one partial outer wall for the vacuum space part. The heat resistance unit may include at least one radiation resistance sheet provided in a plate shape inside the vacuum space part or may include a porous material to resist radiation heat transfer between the second plate member and the first plate member inside the vacuum space part.

[0112] According to the present disclosure, it is possible to obtain a sufficient and stable vacuum adiabatic effect. According to the present disclosure, it is possible to prevent the formation of dew on an outer surface of the vacuum adiabatic body, which may occur in a severe situation, by controlling the flow of heat. According to the present disclosure, it is possible to provide a structurally stable vacuum adiabatic body.

[0113] The details of one or more embodiments are set forth in the accompanying drawings and the description below. Other features will be apparent from the description and drawings, and from the claims.

[0114] Any reference in this specification to “one embodiment,” “an embodiment,” “example embodiment,” etc., means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of such phrases in various places in the specification are not necessarily all referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with any embodiment, it is submitted that it is within the purview of one skilled in the art to effect such feature, structure, or characteristic in connection with other ones of the embodiments.

[0115] Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

Claims

1. A vacuum adiabatic body comprising: a first plate defining at least one portion of a wall for an internal space; a second plate defining at least one portion of a wall for the external space; a vacuum space provided between the first plate and the second plate, the vacuum space having a thickness in a first direction; and a side frame includes a first portion extending in a different direction from the first direction, and including a first end and a second end, the second end being

- disposed nearer to a side portion of the vacuum adiabatic body than the first end, wherein the first portion of the side frame includes a surface in contact with a front portion of the vacuum adiabatic body, the front portion being defined by the second plate, and wherein the second end of the side frame is spaced apart from the side portion of the vacuum adiabatic body, the side portion being defined by the second plate.
- 2.** The vacuum adiabatic body according to claim 1, wherein the front portion of the vacuum adiabatic body is defined by a front portion of the second plate, and the side portion of the vacuum adiabatic body is defined by a side portion of the second plate.
- 3.** The vacuum adiabatic body according to claim 2, wherein the side portion of the second plate is bent with respect to the front portion of the second plate.
- 4.** The vacuum adiabatic body according to claim 3, wherein the side portion of the second plate includes a portion extending from the second plate to the first plate.
- 5.** A vacuum adiabatic body comprising: a first plate defining at least one portion of a wall for an internal space; a second plate defining at least one portion of a wall for the external space; a vacuum space provided between the first plate and the second plate, the vacuum space having a thickness in a first direction; and a side frame includes a first portion extending in a different direction from the first direction, and including a first end and a second end, the second end being disposed nearer to a side portion of the vacuum adiabatic body than the first end, wherein the first portion of the side frame includes a surface in contact with a front portion of the vacuum adiabatic body, the front portion being defined by the second plate.
- 6.** The vacuum adiabatic body according to claim 5, wherein the front portion of the vacuum adiabatic body is defined by a front portion of the second plate, and the side portion of the vacuum adiabatic body is defined by a side portion of the second plate.
- 7.** The vacuum adiabatic body according to claim 6, wherein the side portion of the second plate is bent with respect to the front portion of the second plate.
- 8.** The vacuum adiabatic body according to claim 7, wherein the side portion of the second plate includes a portion extending from the second plate to the first plate.
- 9.** A vacuum adiabatic body comprising: a first plate defining at least one portion of a wall for an internal space; a second plate defining at least one portion of a wall for the external space; a vacuum space provided between the first plate and the second plate, the vacuum space having a thickness in a first direction; and a side frame includes a first portion extending in a different direction from the first direction, and including a first end and a second end, the second end being disposed nearer to a side portion of the vacuum adiabatic body than the first end, and wherein the second end of the side frame is spaced apart from the side portion of the vacuum adiabatic body, the side portion being defined by the second plate.
- 10.** The vacuum adiabatic body according to claim 9, wherein the front portion of the vacuum adiabatic body is defined by the front portion of the second plate, and the side portion of the vacuum adiabatic body is defined by the side portion of the second plate.
- 11.** The vacuum adiabatic body according to claim 10, wherein the side portion of the second plate is bent with respect to the front portion of the second plate.
- 12.** The vacuum adiabatic body according to claim 11, wherein the side portion of the second plate includes a portion extending from the second plate to the first plate.
- 13.** The vacuum adiabatic body according to claim 1, wherein the side frame includes a second portion extending in the first direction, and the first portion of the side frame defines a portion of the wall for the vacuum space.
- 14.** A refrigerator comprising: a main body provided with the internal space in which a storage good is stored; a door provided to open and close the main body from the external space; and a vacuum adiabatic body according to claim 1.
-