

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250254775

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

MEAD; KARL J. et al.

ENVIRONMENT OPTIMIZATION FOR SPACE BASED ON PRESENCE AND ACTIVITIES

Abstract

A method for facilitating space experiences for at least a first space user and for at least first and second different spaces, the method comprising the steps of storing first and second space experience specifications for the first and second different spaces, respectively, wherein the first and second space experience specifications indicate space affordance settings for the first and second spaces, respectively, sensing a trigger event associated with at least one of the first and second different spaces, where the sensed trigger event is associated with the first space, using the first space experience specification to control the first space affordances and where the sensed trigger event is associated with the second space, using the second space experience specification to control the second space affordances.

Inventors: MEAD; KARL J. (GRAND RAPIDS, MI), YOO; HYUN (GRAND RAPIDS, MI), JOHNSON; CHERIE (EAST GRAND RAPIDS, MI)

Applicant: STEELCASE INC. (GRAND RAPIDS, MI)

Family ID: 54770704

Appl. No.: 19/180452

Filed: April 16, 2025

Related U.S. Application Data

parent US continuation 18627601 20240405 parent-grant-document US 12324072 child US 19180452

parent US continuation 17528835 20211117 parent-grant-document US 11979959 child US 18627601

parent US continuation 16704436 20191205 parent-grant-document US 11212898 child US 17528835

parent US continuation 16041199 20180720 parent-grant-document US 10561006 child US 16704436

parent US continuation 15458376 20170314 parent-grant-document US 10057963 child US 16041199
parent US continuation 15184225 20160616 parent-grant-document US 9642219 child US 15458376
parent US continuation 14730996 20150604 parent-grant-document US 9380682 child US 15184225
us-provisional-application US 62008283 20140605

Publication Classification

Int. Cl.: **H05B47/155** (20200101); **G05B15/02** (20060101); **G05B19/042** (20060101); **H05B45/20** (20200101); **H05B47/115** (20200101); **H05B47/125** (20200101); **H05B47/16** (20200101); **H05B47/19** (20200101)

U.S. Cl.:

CPC **H05B47/155** (20200101); **G05B15/02** (20130101); **G05B19/042** (20130101); **H05B45/20** (20200101); **H05B47/115** (20200101); **H05B47/16** (20200101); **H05B47/19** (20200101); G05B2219/2664 (20130101); H05B47/125 (20200101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 18/627,601 filed on Apr. 5, 2024, which is a continuation application of U.S. patent application Ser. No. 17/528,835 filed on Nov. 17, 2021, which is a continuation application of U.S. patent application Ser. No. 16/704,436 filed on Dec. 5, 2019, which is a continuation application of U.S. patent application Ser. No. 16/041,199 filed on Jul. 20, 2018, which is a continuation application of U.S. patent application Ser. No. 15/458,376 filed Mar. 14, 2017, which is a continuation application of U.S. patent application Ser. No. 15/184,225 filed Jun. 16, 2016, which is a continuation application of U.S. patent application Ser. No. 14/730,996 filed Jun. 4, 2015, which claims the benefit of U.S. Provisional patent application Ser. No. 62/008,283 filed on Jun. 5, 2014, each of which is incorporated herein by reference in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT [0002] Not applicable.

BACKGROUND OF THE DISCLOSURE

[0003] The field of the invention is office spaces and more specifically spaces that automatically adapt to user presence and optimize for specific experiences or activities within spaces.

[0004] During the course of a typical work day, employees of a company or other business entity often perform various tasks or activities. For example, during a typical day, a specific employee may work individually, may work with one other employee in a dyadic fashion to share ideas and develop new ideas, may work with two or more other persons to share information or develop concepts in a larger conference setting, may spend a portion of her day on the phone conversing with colleagues or customers, may participate in a video conference with one or more remote colleagues or clients or may spend some time resting by either napping or simply meditating.

[0005] In the office space industry it is generally recognized that space affordances can facilitate or hinder activities and that recognition has lead to differently afforded spaces that have been at least somewhat optimized for different activities. For instance, a typical personal office space may

include a desk, a task chair and a computer including a display screen on the desk. In contrast, a typical conference space may include a large table, a plurality of chairs arranged about the edges of the table and a projector or large electronic display screen for presenting content from a computer or the like that is being shared within the conference space. Clearly office spaces and conference spaces are differently afforded and each set of affordances enhances the specific use assigned to the space.

[0006] In addition to assemblies that provide work surfaces, support chairs for space users and screens for accessing digital information, many spaces have other affordances that, while capable of enhancing specific activities within the spaces, are essentially ignored or are underutilized by space users for one reason or another. For instance, most office spaces include some type of lighting device(s) (e.g., a desk light, a floor lamp, overhead lighting, upward or downward directed shelf lighting, etc.) for illuminating general ambient space, work surfaces, wall surfaces, etc. Here, even where lighting devices are controllable so that light intensity can be adjusted, most lights are either off or turned on to their highest intensity level regardless of whether or not an intermediate intensity level may be optimal for some purpose. For example, in a conference room, lights are often completely on when digital content is not shared and off when digital content is not being shared with no in between. In personal office spaces lights are usually either on with high intensity or off despite the fact that other lighting settings may be optimal depending on the activity performed within the office space. Many spaces include several lighting devices which are often all on or all off regardless of whether those settings are optimized for specific activities.

[0007] Other space affordances that are rarely adjusted despite the fact that they can have a great impact on how well activities are performed within a space include temperature control devices (e.g., heaters, cooling devices, etc.), air flow devices (e.g., fans), audio devices (e.g., speakers and audio players that can play sound tracks), electronic display screens that are not being used to present content within a space, etc.

[0008] There are several reasons space users do not optimally adjust many affordances within office spaces. First, in many cases, a user simply does not have an understanding that each of the affordances can be adjusted to optimize specific activities. For instance, for many space users high intensity light on a primary work surface with dimmed ambient light optimizes the user's ability to focus on individual work being performed on the primary work surface. Nevertheless, many space users simply rely on a single intensity ambient light to light their work surfaces. As another instance, where a person uses a space to facilitate a resting activity (e.g., take a short nap), in many cases the resting activity would be enhanced where temperature is increased by a few degrees. Nevertheless, space temperature is only rarely adjusted by space users. As yet one other example, it is known that white noise can drown out voices or other noises within a walkway adjacent a space yet even where white noise sound tracks are available to space users, the tracks are rarely played. Many other examples of optimized environmental characteristics that are not understood by space users exist.

[0009] Second, even where a space user has a general understanding that certain activities can be enhanced by optimally adjusting affordances, in many cases the user has no understanding of which settings are optimal for which activities. Here, confused, a user often simply uses affordances as set when the user occupies a space without adjusting the affordances to optimize space use for specific activities.

[0010] Third, even where a space user recognizes that activities can be enhanced by optimally adjusting affordances and has a good understanding of how those affordances should be optimized for at least some activities, in many cases different affordances are controlled by different control systems or devices and therefore, to adjust several affordances to optimal settings, a user would have to adjust many (e.g., 4-6) different devices. The burden of optimally adjusting many devices each time the activity within a space is changed means that space users simply use space with affordances set "as is" and do not bother with optimizing the affordances to specific activities. This

is particularly true in cases where one person may use many different spaces during a day to perform many different tasks. For instance, in a case where an employer has remote employees that “hotel” in spaces in different facilities, most employees will not take the time to optimally set affordance characteristics even if they understand how the setting can affect their activities. In hotelling cases, often-times affordances and controls therefore are different in different spaces and, while a user may understand a control device in one space that is routinely used by the user, the user may not understand another interface for a similar affordances in a different space. The end result is that the user will not take advantage of the capability of setting optimized affordances in differently controlled spaces.

[0011] Fourth, in many cases, while a space user may understand how affordance settings can be optimized for that user for a specific activity (e.g., user preferences for individual focused work), the user often times will have no understanding of how the affordances can be optimized for other types of activities. Again, a user may understand that bright task lighting on a primary work surface with dimmed lighting in the ambient can optimally support individual focused work but may have no clue that the lighting should be changed for dyadic use of the same space where the user and another space user are sharing ideas in an open conversation and should be changed again for video conferencing and yet again during a resting activity. In these cases, instead of manually adjusting affordances to optimize for specific activities, users typically forego adjustment and simply use less than optimal settings for specific activities.

[0012] In addition to there being optimized environment characteristics for different activities performed in a space, it is believed that there are also different optimized characteristic sets for different phases of any given activity. For instance, in the case of a space optimized for facilitating a resting activity (e.g., a short nap), there may be several phases of the activity including an invite phase that invites a user to use the space for a rest activity, a welcome phase that helps a user take control of the space, an activity phase during which a resting activity is performed and an emerge phase that helps a user emerge from the resting activity. Here, there are optimal changes to a space environment that can enhance each of the different phases of the activity. Again, here, most users are unaware of optimized affordance settings for phases and even if they understand that optimized affordance settings for each phase exist, the burden of adjusting the affordance settings is too great to be performed for each activity within the space.

[0013] Thus, there is a need for a system where affordance settings within a space can be optimized for the space and for specific activities within the space in a simplified manner. There is also a need for a system where affordance settings can be optimized easily for specific users of spaces.

BRIEF SUMMARY OF THE DISCLOSURE

[0014] It has been recognized that the environment within a space substantially affects how well specific activities can be accomplished within the space. It has also been recognized that many affordances within spaces that can be adjusted to control space environment are poorly utilized and therefore that many space environments are not optimized for specific activities. Moreover it has been recognized that many of the poorly utilized affordances can be automatically controlled by a system server that, based on trigger events that occur within or proximate a space, adjust affordances either automatically or substantially independent of input from space users so that space environment can be optimized for specific activities or so that at least particularly advantageous environments for specific activities can be provided. In at least some cases actions that a space user would perform during normal use of a space such as closing a door to the space, presenting an identification (e.g., RF) device to take control of the space, sitting down within the space, standing up within the space, etc., may be used as triggers for adjusting space affordances to change environmental characteristics. Thus, space characteristics may be optimized or adjusted substantially automatically without requiring a user to understand how to operate a control interface associated with a specific space.

[0015] It has also been recognized that many space experiences have different generally repeatable

phases and that the environment within a space can facilitate each of the phases when adjusted appropriately. Thus, where a space is to be used for individual focused work for instance, while light may be high intensity on a primary work surface with dim ambient light there around (e.g., a focused light pattern) while a space user is focusing on work, there may be a phase in or welcome period when the user first takes control of the space, taking materials out of a book bag, setting up the space with materials on the primary work surface, etc. as well as an emerge or phase out period when the user is preparing to leave the space by packing up materials, making sure no materials are left behind, cleaning up the primary and other work spaces, etc., during which the focused lighting pattern is not optimal or even advantageous. Here, lighting and other space affordances (e.g., temperature, sound effects, air circulation, etc.) may all be adjusted differently during each of the different phases in ways designed to enhance activities performed during each phase. Again, actions by a user within the space during normal use of the space may be selected as triggers for commencing next sequential phases in a space experience so that changes to space affordance settings occur generally automatically without requiring any dedicated action, gesture or input from the user for controlling the settings. Thus, for instance, in one embodiment, a system server may control lighting devices within a first space to generate pulsing green light during an invite phase when the space is available for use (e.g., is not scheduled for use during a current or temporally immanent period of time). When a user enters the space and closes a door to a space egress, the door closing may trigger a welcome phase where lighting changes, a first sound track is played, etc. When the user presents an identification device to a reader in the space to schedule use of the space during the current period, upon reading the device, the system may again change to lighting as well as the sound track, temperature in the space, air circulation, notice capability of personal devices within the space (e.g., block delivery of e-mails, texts, etc., to devices in the space), etc. Near the end of the scheduled period of use, the system may, based on time, automatically trigger an emerge phase, again changing the lighting and sound effects, changing space temperature and air circulation, change the notice capability of personal devices within the space, etc. When the user opens the door to exist the space, settings may revert back to the invite settings to invite use of the space by another user.

[0016] Interruptions inevitably occur during space use. To deal with interruptions during an ongoing space experience, the system may be programmed to automatically recognize when conditions within a space have changed and to adjust space affordances accordingly. For instance, where a user is performing individual focused work activity in a space and the lighting is high intensity on a work surface and dim generally within the ambient and a second person opens a door to the space, the system may sense the door opening (e.g., the trigger) and immediately change the lighting setting to have an intermediate level of light intensity within the entire space and to dim the intensity on the primary work surface. Thereafter, when the second person leaves the space and closes the door, the lighting setting may revert back to the individual focused work setting automatically. Other affordance adjustments based on sensed interruptions are contemplated.

[0017] It has also been recognized that more than one space experience may be provided by affordances associated with a space even if the space is optimized for one type of space experience and that a system server or controller (e.g., a computer of some type either remote or local) may control affordances based on the set of affordances available within a space. For instance, where a space experience specification specifies seven optimal affordance settings for a space and a specific space only includes five of the seven affordances, the server will nevertheless control the five affordances according to the specification in at least some embodiments of the present disclosure to present as much of an optimized environment for a specific experience as possible.

[0018] In at least some embodiments separate spaces are optimally afforded for different space experiences. For instance, in at least some cases a first subset of spaces may be optimally fitted out to support resting activities, a second subset of spaces may be optimally fitted out to support dyadic activities, a third subset of spaces may be optimally fitted out to support individual focused work,

etc. In these cases, in at least some embodiments, when a user takes control of a space, the space experience associated with the optimal activity may be commenced automatically. In some cases a user may be able to select a different space experience causing the system server to control the space according to a specification for the different experience that was selected.

[0019] In some embodiments lighting devices used within the spaces are color controllable so that the lighting devices can generate illumination of virtually any color. For instance, in at least some cases RGB LEDs may be provided on lighting devices and may be controlled to generate any desired light color. The different color illumination may be used to enhance space experiences. For instance, during a rest (e.g., nap) activity, space lighting may be dark blue, during a welcome phase of a space experience the lighting may be a warm yellow/orange, where focused work is performed lighting may be bright white, etc. Light intensity and special effects may also be controlled to enhance specific activities and phases of different experiences. For instance, light intensity may be pulsed in a sinusoidal pattern or to follow a sound track in some cases. As another instance, lighting color and effect may be controlled to simulate different effects like a rising sun, lightening in a dark sky, etc. Other effects are contemplated.

[0020] In at least some cases a space or room control interface device may be provided adjacent or within a space for manually adjusting affordances via an intuitive interface. For instance, lighting, sound, temperature, circulation, etc., may be controlled via a touch screen interface.

[0021] In at least some embodiments a space user can adjust affordance settings for specific types of space experiences (e.g., rest, individual focused work, dyadic space use, etc.) and can store those personalized settings. Thereafter, the system may, when the specific user is identified in a space and a specific space experience is to be performed, use the personalized settings to present the experience to the space user.

[0022] In at least some embodiments where a space user has a personal portable device (e.g., a smart phone, a tablet type computing device, a laptop, etc.) in a space, the system may use one or more capabilities of the personal device to present at least some space experience effects. For instance, where a portable device includes speakers or an earphone jack, experience sound tracks may be played on the user device to be presented to the user.

[0023] Many personal devices include some type of data collector or sensor. For instance, many personal devices include an accelerometer, a gyroscope, an elevation detector, etc. As another instance, many personal devices include a camera that can obtain images. As yet another instance, some personal devices can now sense gestures proximate the devices (e.g., adjacent a display screen). In at least some embodiments it is contemplated that one or more of the sensors or data collectors on a personal device may be used to obtain information that can operate as a trigger for controlling space affordances. For instance, where a personal device is within a user's pocket and the user stands up during individual focused work, the accelerometer or some other sensor may sense the change in posture and send a wireless signal to a system server which may then change the lighting effect within the space according to an experience specification. As another instance, a portable device camera may be positioned within the space to obtain images transmitted to the system server for examination to identify other trigger activities.

[0024] These and other objects, advantages and aspects of the invention will become apparent from the following description. In the description, reference is made to the accompanying drawings which form a part hereof, and in which there is shown a preferred embodiment of the invention. Such embodiment does not necessarily represent the full scope of the invention and reference is made therefore, to the claims herein for interpreting the scope of the invention.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0025] FIG. **1** is a schematic diagram of a space experience control system according to at least some aspects of the present disclosure;

[0026] FIG. **2** is a perspective view of an exemplary space including various space affordances that is consistent with at least some aspects of the present disclosure;

[0027] FIG. **3** is a cross sectional view of a single sided LED light panel assembly that may be used to form various sections of a space defining wall as shown in FIG. **2** and in other figures in this disclosure;

[0028] FIG. **4** is a partial perspective view of an LED PCB board that may be used in the assembly of FIG. **3**;

[0029] FIG. **5** is a top plan view of an exemplary RGB LED that may be used in the assembly of FIG. **4**;

[0030] FIG. **6** is a cross sectional view of an indirect light assembly that may be used in a space defining wall that is consistent with some aspects of this disclosure;

[0031] FIG. **7** is a cross sectional view of a two sided light panel that is consistent with at least some aspects of the present disclosure;

[0032] FIG. **8** is a cross sectional view of a display assembly consistent with at least some aspects of the present disclosure;

[0033] FIG. **9** is a cross sectional view of another display assembly consistent with some aspects of the present disclosure;

[0034] FIG. **10** is a perspective view of a lounge assembly that is consistent with at least some aspects of the present disclosure;

[0035] FIG. **11** is a flow chart illustrating a method for controlling space affordances to facilitate several phases of a generic space experience;

[0036] FIG. **12** is a perspective view of another space optimized to facilitate a specific type of space experience according to at least some aspects of the present disclosure;

[0037] FIG. **13** is a flow chart similar to the FIG. **11** flow chart, albeit for facilitating a rest space experience within the space shown in FIG. **12**;

[0038] FIG. **14** is similar to FIG. **12**, albeit showing a space user standing within the space;

[0039] FIG. **15** is similar to FIG. **1**, albeit showing the user closing the door to the space illustrated;

[0040] FIG. **16** shows the user of FIG. **15** presenting an RFID card for reading by a reader within the space;

[0041] FIG. **17** shows the user of FIG. **16** in a seated position within the space;

[0042] FIG. **18** shows the user of FIG. **17** seated at the end of a rest activity and during an emerge phase of a space experience;

[0043] FIG. **19** shows the user of FIG. **18** opening a space door which acts as a trigger to start an invite phase of space control;

[0044] FIG. **20** is a perspective view of a space user in yet another space optimized for a specific activity that is consistent with at least some aspects of the present disclosure;

[0045] FIG. **21** shows the user of FIG. **21** in a seated position within the space and with the space door closed;

[0046] FIG. **22** is a partial side view of yet another space optimized for certain activities;

[0047] FIG. **23** is a partial side view of yet another space optimized for certain activities;

[0048] FIG. **24** is a schematic diagram of a database of space experience specifications;

[0049] FIG. **25** is a detailed schematic diagram of apportion of an exemplary rest activity specification of FIG. **24**;

[0050] specification of FIG. **24**;

[0051] FIG. **26** is a detailed schematic diagram of apportion of an exemplary rest activity specification of FIG. **24**;

[0052] FIG. **27** is a schematic representation of a screen shot for controlling light effects within a

space using a space control device according to at least some aspects of the present disclosure;
[0053] FIG. **28** is similar to FIG. **27**, albeit showing a screen shot for selecting sound tracks and effects to be presented within a space;
[0054] FIG. **29** is similar to FIG. **27**, albeit showing a screen shot for selecting temperature effects to be controlled within a space;
[0055] FIG. **30** is similar to FIG. **27**, albeit showing a screen shot for selecting air circulation effects to be controlled within a space;
[0056] FIG. **31** is similar to FIG. **27**, albeit showing a screen shot for selecting notice settings for a space during a space experience;
[0057] FIG. **32** is similar to FIG. **27**, albeit showing a screen shot for selecting a space experience to be presented within a space;
[0058] FIG. **33** is similar to FIG. **24**, albeit showing a database including space experience specifications that are customized for different space users;
[0059] FIG. **34** is similar to FIG. **20**, albeit illustrating a different set of display screens within a space;
[0060] FIG. **35** is a front plan view of some of the components shown in FIG. **34**;
[0061] FIG. **36** is similar to FIG. **35**, albeit illustrating a different virtual division of display screen space; and
[0062] FIG. **37** is similar to FIG. **36**, albeit illustrating a different virtual division of display screen space.

DETAILED DESCRIPTION OF THE DISCLOSURE

[0063] The various aspects of the subject disclosure are now described with reference to the drawings, wherein like reference numerals correspond to similar elements throughout the several views. It should be understood, however, that the drawings and detailed description hereafter relating thereto are not intended to limit the claimed subject matter to the particular form disclosed. Rather, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the claimed subject matter.

[0064] As used herein, the terms “component,” “system” and the like are intended to refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution. For example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a computer and the computer can be a component. One or more components may reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers or processors.

[0065] The word “exemplary” is used herein to mean serving as an example, instance, or illustration. Any aspect or design described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects or designs.

[0066] Furthermore, the disclosed subject matter may be implemented as a system, method, apparatus, or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof to control a computer or processor based device to implement aspects detailed herein. The term “article of manufacture” (or alternatively, “computer program product”) as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks (e.g., compact disk (CD), digital versatile disk (DVD) . . .), smart cards, and flash memory devices (e.g., card, stick). Additionally it should be appreciated that a carrier wave can be employed to carry computer-readable electronic data such as those used in transmitting and receiving electronic mail or in accessing a network such as the Internet or a local area network (LAN). Of course, those skilled in the art will recognize many modifications

may be made to this configuration without departing from the scope or spirit of the claimed subject matter.

[0067] Referring now to the drawings wherein like reference numerals correspond to similar elements throughout the several views and, more specifically, referring to FIG. 1, the present disclosure will be described in the context of an exemplary environment optimization system **100** for use with one or more facility spaces, an exemplary space **220** shown in FIG. 2. The exemplary space **220** is defined by wall structure including first and second lateral or side wall subassemblies **222** and **224**, end wall subassemblies **226** and **228**, a ceiling subassembly **240** and a floor subassembly (not labeled). U.S. patent application Ser. No. 14/028,928 titled “Floor-To-Ceiling Partition Wall System” that was filed on Sep. 17, 2013 is incorporated herein by reference in its entirety and describes one wall system that may be used to construct wall subassemblies **222**, **224**, **226** and **228**. Some of the walls in the '928 application include glass panel members and others include opaque panel members for blocking sightlines. In FIG. 2 the side wall subassemblies **222** and **224** are generally of the glass type while the end wall subassemblies **226** and **228** are of the opaque panel type. The wall subassembly **228** forms a door opening for entering/exiting the space **220** and subassembly **228** includes a glass door **105** mounted for sliding motion between an open position (as illustrated) and a closed position where the door **105** closes the door opening into space **220**.

[0068] Referring again to FIG. 1, the system **100** includes, among other components, a server **102**, at least one interface device **104**, **106**, **108**, **110**, one or more sensor devices **112**, **114**, **116**, **118**, **120**, **122**, **137**, a database **130**, a control system **150**, and a subset of output devices associated with specific spaces within a facility that, along with other components, define spaces and that are controllable to change environments within the spaces. For instance, the output devices may include overhead lighting or under shelf lighting **178**, upward facing lighting units **180** for on top of wall mounted storage bins (see **274** in FIG. 2), one sided panel light assemblies **182**, two sided panel light assemblies **228**, indirect wall mounted lighting devices **290**, lights including bulbs **192**, display screens **200**, speakers **202** for generating sound, indicators **204** of different types, etc., as well as controllers for controlling output of the output devices and sub-systems for implementing various affordances such as a video conferencing controller **164** and a content sharing controller **165**. In at least some cases one or more of the glass type wall panels may be constructed using glass where opacity of the glass can be controlled via a controller **147** or the like as another space experience affordance.

[0069] Server **102** may include any type of computing device having the capability to run space control software to take inputs from the interface devices and the sensors and to provide output control signals to the controller **150** for controlling various aspects of any given space. The server **102** may, for instance, include a remote or local stationary computer dedicated to controlling the devices in one or several different spaces within one or several facilities. As another instance, the server **102** may include a portable computer in some cases that runs software to perform various functions. The server **102** may be hard wired to the control system **150** or may be wirelessly connected in some cases.

[0070] Server **102** is linked to database **130**. Database **130** stores programs run by server **102** to perform various processes as described hereafter as well as specifications for how the affordances within specific spaces are controlled as a function of various sensed parameters. Hereinafter, unless indicated otherwise, any specific sequence of affordance control will be referred to as a “space experience”. The space experience specifications can be changed by a system administrator using a workstation **140** or other interface device in at least some cases. Also, in some cases, any or at least a subset of system users may be able to change a subset or all of the space experience specifications or may be able to customize one or more space experience specifications for their own use using an interface **140** or using a room controller device (e.g., **104**). Any changes to a space experience specification may be stored in database **130** for subsequent use.

[0071] Referring again to FIG. 1, one type of interface device **104** may include a space mounted and dedicated flat screen input device like the one sold by Steelcase Inc. that is referred to as the “Room Wizard”. The Room Wizard device was originally provided for the purpose of maintaining a schedule for spaces like conference rooms, offices, etc. To this end, a Room Wizard runs software to maintain a schedule and enabled users to reserve space remotely via a web based interface or locally by accessing screen shots presented by the flat screen and reserving time within an associated space. In the present disclosure, in at least some embodiments, a Room Wizard device or one similar thereto may also be programmed to include room control software algorithms to enable a user to control space affordances as well as to enable a conferee to save different space experiences for subsequent use. In at least some embodiments the interface **104** may also be used to select a space experience to be implemented during a period of use in a particular space. Hereinafter, unless indicated otherwise, a period of use in a particular space will be referred to as a “space session”.

[0073] RFID sensor **108** is a radio frequency sensor device that can be used to sense an RF identification card, badge, fob, etc. (e.g., an RFIF device), to obtain information therefrom. For instance, an RFID card may include information for determining the identity of a system user that is associated with the card so that one system user can be distinguished from others. As another instance, an RFID card may simply indicate characteristics of personalized space experiences for a system user associated with the card as opposed to indicating the identity of the user. RFID sensor devices are well known and therefore will not be described here in detail. It should suffice to say that when an RF identification device is placed within a sensing range or area associated with the sensor **108**, the sensor **108** obtains the information stored on the identification device and provides that information to server **102**. Here, the RF sensor may be any type of RF sensor including an NFC sensor or some type of conventional wireless communication (e.g., RF should be considered broadly to include any type of wireless communication unless indicated otherwise).

[0074] It is also contemplated that this information could be provided via traditional wireless connections to the user's devices or via an IR connection. It would also be possible to utilize a wired connection, although it is believed the wireless connection is particularly advantageous.

[0075] Portable device sensor **106** is a sensor for sensing that an electronic portable device associated with a specific user is within an area associated with a facility space. For instance, sensor **106** may include a blue tooth or sonic sensor device mounted within a doorway into a space to sense when a portable device passes through the doorway. Here, the Bluetooth or sonic signal may be transmitted periodically and may cause any portable device within the doorway or even within the space associated with the doorway to generate an identifying signal so that the identity of a user entering the space can be determined. Again, any signal obtained by device **106** is provided to server **102**.

[0076] Many spaces may be equipped with wireless access devices **132** mounted in ceiling structure or at other locations to facilitate communication between server **102** and personal portable electronic devices like tablet type devices, smart phones, laptop computers, **110**, etc. In at least some cases signals received by a set of access points proximate a space may be used to triangulate the location of a specific portable device and to determine when the device is located within a specific space. Triangulation algorithms are well known in the industry and therefore are not explained here in detail. Once a portable electronic device is associated with a space, control screens for the space may be presented via the interface device that are similar to the screens that can be presented via a Room Wizard interface screen.

[0077] Referring again to FIGS. 1 and 2, door sensor **112** includes one or more proximity or motion sensor devices mounted within a door for sensing when the door is either moving or is in an open or closed position or both moving and in an open or closed position. In FIG. 2 two sensors **112** are located along the top edge of the egress into a space where sliding glass door **105** is mounted to wall subassembly **228** for sliding movement between an open position (shown in FIG. 2) and a

closed position (not shown). The sensor **112** on the right as illustrated is located to sense either when the door is in the open position or to sense when the door starts to move from the open position toward the closed position by sensing the leading edge of the door. The sensor on the left as illustrated is located to sense either when the door **105** is closed or to sense when the door starts to move from the closed position toward the open position by sensing the leading edge of the door. In other embodiments a single sensor device may sense all door conditions. For instance, a single sensor device located at the location of the sensor **112** on the right in FIG. **2** may sense codes on a rear surface of the door **105** as the door slides between positions where different codes indicate different juxtapositions (e.g., opened, closed, etc.) of the door **105**.

[0078] Referring again to FIG. **1**, in at least some cases a temperature sensor **114** may be provided in one or a subset of spaces within a facility to sense and provide a temperature reading to server **102** for an associated space. In FIG. **2**, an exemplary temperature sensor **114** is shown mounted within the space defining wall **222**. Sensor **114** should be located at an intermediate height within the space to obtain a temperature reading at a height within the space that is commensurate with the location occupied by a system user within the space **220**.

[0079] In addition to or instead of the temperature sensor **114**, other types of sensors including a motion sensor **118**, a proximity sensor **120** or a presence sensor **122** may be provided within or adjacent space **220** (see again FIG. **2**) for sensing motion or presence of a system user within space **220**. While only one device is shown in FIG. **2** as representing each of several different types of sensors, it should be appreciated that each sensor may be a separate device, that is some embodiments there may be several instances of a single type of device associated with a space **220** and that any or a subset of the sensors may be positioned at other locations associated with space including in other walls subassemblies, in the egress into space **220**, in the ceiling subassembly **240**, in the floor subassembly, in any one of the furniture affordances within the space **220** (e.g., with a desk or table structure **250**, within a wall mounted bin structure **274**, etc.

[0080] In addition, a sensor may be located within a moveable affordance within space **220** such as within a lounge chair **252** for supporting a user in space **220**. Here, in at least some cases a wireless transceiver may be provided within the lounge chair for transmitting signals when a sensor therein senses something. For instance, the sensor in chair **252** may sense presence of a user in the chair via proximity, motion, weight, etc., and may wirelessly transmit a signal to an access point **132** associated with space **220**.

[0081] Furthermore, any of the motion, presence, proximity, etc., sensors may be mounted as at **115** in FIG. **2** within an egress into the space **220** to sense when a user moves through the egress and into the space and/or when a user exits the space **220**. Signals from each of sensors **118**, **120** and **122** are provided to server **102** for processing.

[0082] Referring again to FIGS. **1** and **2**, one or more cameras **116** may be mounted within a space **220** to obtain images within the space **220** that can be analyzed by the server **102** to assess activities occurring within the space. For instance, instead of using motion or proximity sensors to sense when someone is within space **220**, camera images can be examined to identify a person within the space **220**. In addition to simply determining if the space is occupied, images can be used for other purposes such as, for instance, counting persons within a space, determining the position of one person in the space or the relative juxtapositions of two or more persons within the space, recognizing posture of a person or persons within the space, identifying gestures by a person or persons within the space, etc.

[0083] Any of the conditions or circumstances identified using images from one or a plurality of cameras within the space can be used as a trigger for a specific space experience or for a space experience to transition from one phase to a next sequential phase. In FIG. **2**, two cameras **116** are mounted to the ceiling structure **240** where each has a different perspective on essentially the same field of view. Here the server **102** would use images from both cameras to assess circumstances within the space. In addition to using cameras **116** to obtain space images, in at least some

embodiments a camera **280** associated with a displays screen **200** or useable for teleconferencing or video conferencing may be used to obtain images of the space **220** useable to assess circumstances within the space.

[0084] Use of a video conferencing camera may be particularly useful where the space **220** is relatively small so that the cameras **280** is capable of obtaining images of a relatively large portion of the space **220**. In at least some cases camera **280** may have an adjustable/controllable field of view so that, when not being used to facilitate a video conference, the camera's field of view can be expanded to obtain images corresponding to a relatively large portion of the space area. Then, during a video conferencing session, the camera's field of view may be altered and optimized to obtain images of a conferee using the space **220**.

[0085] The video conferencing camera may also be located in a position to view the usable space with high definition (e.g., generating high definition images). The camera may be able to generate images useable by a processor running a face recognition program to determine the identity of a user within a space. This could in turn be used to adjust the affordances in accordance with the particular preferences of the user. In addition to identifying a user via facial features, other biometric information may be sensed via other types of features including an eye scanning sensor, a finger print reader, etc.

[0086] Referring again to FIG. **1**, control system **150** may include a room control system like the ones provided by Creston Corporation that can be used to manually control various environmental affordances within a space including lighting, video conferencing, data sharing, sound, etc. Known controllers enable space users to manually adjust environmental affordances as desired. For instance, temperature could be adjusted to suit a user's preference. Lighting could be turned on or off and in some cases light intensity may be adjusted. A video conferencing session may be initiated and controlled. The control system **150** has other capabilities as described here after.

[0087] Referring to FIG. **1**, control system **150** provides output control signals to various system components including, among others, a lighting controller **160** which in turn drives a lighting control **176** and/or another intermediate control bridge device **190**. The lighting control **176** drives lighting devices **178**, **180** and **182**. The lighting devices **178** include overhead ceiling mounted lighting devices. Each device **178** may be a simple white light generating device controllable to adjust light intensity and light color output within a relatively narrow range. In other cases each lighting device may include components controllable to generate many different lighting effects such as virtually any lighting color, pulsating lighting, flickering lighting, lighting that fades on and off, lighting that fades from one color to another, etc. For instance, in at least some embodiments RGB LEDs may be used to construct each of the lighting devices **178** where each RGB LED can be controlled to generate virtually any color of light. Here, in at least some embodiments, the LEDs may be mounted within a light assembly including one or more light pipes that guide and disperse light therefrom into the space **220** (see again FIG. **2**). Here, the idea is that the RGB LED light devices can be controlled to facilitate various space experiences as will be described in greater detail below. Although not shown, one or more devices **178** may be mounted to an undersurface **280** of one or more wall mounted bins **274** for generating downward directed light to wash a portion of the wall assembly **224** as well as the top surface of a table **250** there below.

[0088] Lighting devices **180** are similar to devices **178** and therefore, in at least some cases, will include RGB LEDs and other structure for generating various lighting effects to facilitate various space experiences. Referring to FIG. **2**, although not shown, devices **180** may be supported along top surfaces **276** of wall mounted bins **274** for generating upwardly directed light to wash a portion of the wall subassembly **224** that resides above the bin **274**.

[0089] Lighting device **182** is a light panel that, when illuminated, effectively glows as it emits light to one side of the device structure. This type of lighting device is generally described in U.S. patent application Ser. No. 13/913,254 titled "Panel Light Assembly" which was filed on Jun. 7, 2013 and which is incorporated herein in its entirety by reference. The basic structure of light panel

182 is shown in cross section in FIG. 3. Referring to FIG. 3, panel **182** includes a rigid frame structure **300** formed out of four extruded or otherwise formed rails (two shown in cross section at **300** in FIG. 3) that form a plurality of channels for receiving, supporting and separating three planar members **302**, **304** and **306** as well as LED sub-assemblies **308**. Member **302** is a reflector member that includes a reflective surface that, upon mounting in the frame **300**, faces member **304** and is separated therefrom by a gap.

[0090] Member **304** is a light pipe type member that is defined by edges and that is formed of a generally clear material selected to guide light from the edges while leaking light out surfaces thereof. Light that leaks toward reflector member **302** is reflected back through member **304** and out the front surface thereof. In some embodiments both surfaces of member **304** are polished. In other cases one or both surfaces of member **304** may have some treatment (e.g., mechanical machinations, frosting, etc.) to cause light to disperse there from. LED sub-assemblies **308** are mounted along one, two or each edge of member **308** to direct light there into.

[0091] Member **306** is a light transmitting cover member and includes an external surface when mounted that is substantially flush with adjacent surfaces of the frame member **300**. Light from member **304** passes through cover member **306** to illuminate a space adjacent thereto.

[0092] Referring to FIG. 4, an exemplary LED subassembly **308** includes a ribbon of printed circuit board (PCB) **310** or other support substrate and a line of RGB LEDs **314** mounted to a top surface **312** thereof. Referring to FIG. 5, each RGB LED **314** includes three different LEDs, one red, one green and one blue, that can be independently controlled to adjust intensity. When LEDs on two or more colors are illuminated at the same time and the light is directed in member **308**, the light mixes in member **308** and creates a combined color. Thus, for instance, a shade of yellow can be generated by turning on green and blue LEDs at the same time. LED intensity is controllable using a PWM technique or other control algorithm. Thus, each light panel **182** can be used to generate light having virtually any desired color. In addition, by controlling the LEDs in device **182** differently during a sequence, the lighting effect can be controlled to facilitate a different space experience.

[0093] Referring again to FIG. 2, one or more indirect lighting devices **290** may be mounted within one or more of the space defining wall structures. Referring also to FIG. 6, an exemplary indirect light structure **290** includes, among other things, a bent metal or extruded housing structure **330**, a reflector member **332**, a cover member **334** and an LED subassembly **336**. Housing structure **330** includes wall members that form a cavity and that have upward and downwardly facing edge channels for mating with lip members formed by cover member **334**. Reflector **332** is mounted within the cavity and forms a reflective surface that faces an internal surface of cover member **334**. The LED subassembly **336** may be similar to the subassembly described above with respect to FIGS. 4 and 5 and therefore may include RGB LEDs controllable to generate light of any desired color. Light from subassembly **336** is directed at the reflective surface of member **332** and reflects therefrom and passes through cover member **334** and into an adjacent space.

[0094] In the case of either of the lighting device **182** and **290** described above, after the device is mounted to a support frame structure, an opaque panel is usually mounted on the opposite side of the frame structure to give a finished appearance.

[0095] FIG. 7 shows a two sided light panel assembly **228** that is similar to the assembly shown in FIG. 3, albeit where the reflecting member **302** has been effectively replaced by a second cover member **346**. Assembly **228** includes a dual part frame structure **340** and **342** that snap together from opposite sides of a support frame to mount the assembly **228** to the support frame. Frame structures **340** and **342** form resilient mating ribs or lips **355** and **357** that engage in a friction fit to effectively sandwich the support frame structure there between. Although not shown additional locking structure may be provided for locking the frame structures **340** and **342** together on a frame. Structure **342** forms first and second channels **358** and **350** about its internal perimeter that receive and support a light transmissive cover member **348** and a light guide member **344** and LED

subassemblies **308**. Structure **340** forms a channel **356** about its internal perimeter that receives and supports a second light transmissive cover member **346**. Light from within guide **344** escapes there from and passes to either side of the assembly **228** lighting space on either side thereof. In at least some cases the guide **344** may include surface disturbances (e.g., etching, frosting) or internal doping with reflective specs or the like that varies or is uniform throughout its area to better disperse light passing there through to areas adjacent the assembly.

[0096] Referring again to FIG. **1**, bulbs **192** may include Phillips' Hue bulbs that each include RGB LEDs and control circuitry for generating virtually any light color and a range of different intensities. Each bulb may be mounted in any of several different types of lamp assemblies including a hanging lamp assembly **193** as shown in FIG. **2**. Other lamp assemblies are contemplated. The bridge **190** shown in FIG. **2** may be a Phillips' Hue bridge and may be used to wirelessly control one or more of the bulbs **192**.

[0097] Referring again to FIG. **1**, video conferencing controller **164** is a controller for controlling a video conference within the space **220** and is therefore linked to a display screen **200** as well as, perhaps, a camera **280** associated therewith. The conferencing system may be any one of the system provided by Cisco Systems or other video conferencing system manufacturers.

[0098] Referring again to FIG. **1**, display device(s) **200** may be any type of flat panel display device that is spatially associated with space **220**. For instance, display **200** may be mounted to or otherwise supported by a desk or table assembly **250** within space **220**. In other cases a display device may be mounted to one of the wall subassemblies. In still other cases it is contemplated that a display device may be mounted within one of the wall assemblies. To this end, see for instance the structure shown in FIG. **8** where a two part frame subassembly similar to the frame shown in FIG. **7** supports an electronic display screen **370**. In this case a first frame structure **362** forms a channel **366** for supporting a transparent cover member **374** that is substantially flush with the adjacent portion of the frame structure **362** and also forms a channel **364** for receiving the display screen **370**. In FIG. **8** the emissive surface of display **370** faces member **374**. The second frame structure **360** forms a single channel for supporting opaque panel member **372** to give a finished appearance on the opposite side of the wall structure.

[0099] Yet another configuration where a display screen **200'** is mounted within a wall structure is shown in FIG. **9**. In FIG. **9**, a frame includes a two part structure **390** and **392** where frame structure **390** is similar to frame structure **360** described above with respect to FIG. **8**. Frame structure **392**, however, is different in that structure **392** only forms a single channel **394** for receiving and support a display screen **398** so that a front surface of display **398** is substantially flush with adjacent portions of frame structure **392**.

[0100] In either of the two configurations shown in FIGS. **8** and **9** where a display screen is mounted within a wall structure, it is contemplated that different thickness display screens will be available for use. For this reason in at least some structure may be provided to compensate for different screen thicknesses. In this regard see in FIG. **9** that mounting blocks **391** are provided in some cases to clamp against a rear surface of a display screen during mounting. A fastening bolt **393** is provided for each mounting clamp which passes through a block opening and a slot in the frame structure **392**. A nut **395** on the distal end of each bolt can be tightened to sandwich a display screen between the block and a facing lip on the frame structure **392**. Thus, to install a screen, the screen is mounted via the blocks and bolts to a frame structure **392** and then the frame structures are clipped together from opposite sides of a support frame to secure the assembly **200'** to the support frame. Again, an additional locking mechanism may be provided to maintain the frame structures **390** and **392** secured together.

[0101] Although only a lounge chair **252** and a simple table assembly **250** are shown in FIG. **2**, additional or other furniture affordances may be provided within a space **220**. To this end, see for instance FIG. **10** that includes a sofa type lounge **400a** that is long enough to support at least two persons side by side comfortably. Here, the lounge includes a seat structure **402** and a back rest

support structure **404**. A utility well **406** is formed between end sections of the seat structure and a cover member **408** is hinged to the lounge **400a** to open and close thereby enabling access to the well **406**. In at least some embodiments control devices **410** (two shown) are provided within the well **406** (or within an arm rest structure, not shown) that can be used to link to a space mounted displays screen **200**. In at least some embodiments each control device **410** is cabled to a port within the well **406** and another end of the cable is linkable to a portable computing device like a laptop **418**, a tablet type device (not shown) or a smart phone device (not shown). U.S. patent application Ser. No. 13/912,442 titled "Personal Control Apparatus And Method For Sharing Information In A Collaboration Workspace" that was filed on June **78, 2013** describes one control device that may be used as device **410** and is incorporated herein in its entirety by reference for its teachings of a control apparatus for content presented on a display screen. Referring again to FIG. **1**, in addition to including the control devices **410**, the sub-system of FIG. **10** may also include a content sharing system controller **165** akin to the one described in the '442 application that manages who has control of a display screen **220** based on various rules.

[0102] Referring still to FIG. **10**, various events associated with use of the control devices within the well **410** may also be used to trigger specific space experiences or phases of those experiences. For instance, opening door or cover member **408** may be sensed and trigger a phase change. Connecting a control device **410** to a computer may be sensed and trigger a phase change. Selection of a button on a control device **410** may trigger a phase change. Disconnecting a device **410** from a source laptop or the like may trigger a phase change. Closing the cover **408** may trigger a phase change.

[0103] Referring again to FIGS. **1** and **2**, in other embodiments it is contemplated that the content sharing controller **165** may support wireless linkage within space **220** to one or more display screens. To this end, the '442 application referenced above also teaches a wireless process for associating a portable computing device with display screens within a space and for then controlling content presented on the screens the wireless teachings of the 3 442 patent are incorporated herein by reference.

[0104] Referring to FIG. **1**, a music player **166** is provided for playing audio clips. For instance, player **166** may be programmed to play various sound tracks including one or more white noise tracks, one or more nature tracks (e.g., a rainstorm track, a wind track, a waves crashing track, etc.), one or more scene tracks (e.g., a street café track, a bus terminal track, etc.). although not shown, player **166** may be equipped to fade one track in while simultaneously fading a second track out so that transitions between different tracks are not perceived as abrupt. Amplifier **168** links control system **150** to speakers **202** and controls the volume of the tracks played by player **166**.

[0105] Temperature controller **170** uses signals from control system **150** to regulate temperature within space **220**. To this end controller may be linked to a space heater and perhaps some type of cooling (e.g., air conditioning) unit associated with space **220**. Similarly air circulation controller **172** is used to regulate air circulation within space **220** and may be linked to a fan or the like that is mounted behind a circulation vent (see **254** in FIG. **2**).

[0106] Privacy indicator **204** in at least some embodiments, includes a simple light device that is spatially associated with space **220** and that can indicate when a certain level of privacy can be relied upon. For instance in FIG. **2**, when door **105** is completely closed, server **102** may cause indicator **204** to illuminate to indicate privacy. As another instance, where a microphone or other sound sensor is mounted outside space as shown at **137**, sound picked up at **137** may be compared to sound sensed within space **220** via an internal microphone **139** to identify when sound initiated in space **220** carries outside space **220** and to identify the volume of sound outside space **220**. Then, if sound that carries from inside space **220** to outside space **220** is below a threshold level, indicator light **204** may be illuminated and if the sound rises above that level the indicator light **204** may be turned off. Other ways of sensing privacy are contemplated.

[0107] Referring again to FIG. **2**, in still other embodiments one or more glass panels that form

parts of a space dividing structure (e.g., a wall) may include electronically controlled tinting or “dynamic” glass where transparency of the glass can be controlled by a system user or automatically by the server **102** to further facilitate certain space experiences. For instance, in some experiences a user may want transparent walls or panels while during others the user may desire opaque walls or panels. Two companies that have developed dynamic glass technology and products include Smart Shade and View, Inc., either of which could provide dynamic panel glass for embodiments of the disclosure.

[0108] While the above system includes a large number of different types of sensors, interface devices and output devices, it should be appreciated that the present disclosure contemplates systems with far fewer devices and sub-systems. For instance, while some embodiments may include dual sided light panels as described with reference to FIG. 7 above, other embodiments will not include such panels. As another instance, some embodiments may include display screens and/or speakers while other embodiments do not. As yet another instance, some embodiments may include control devices as described above with respect to FIG. 10 while others do not include such control devices.

[0109] It has been recognized that different subsets of the above described affordances may facilitate different optimized or enhanced multi-phase space experiences. For instance, in a case where a person intends to use a personal space to rest for a few minutes prior to a next meeting, a properly afforded space may automatically run through a multi-phase space experience to invite the user into the space, transition the user to a rest state, help the user maintain the rest state and help the conferee emerge from the rest state. As another example, in a case where two users intend to use a space to share content from personal portable devices with each other in a dyadic fashion, a properly afforded space may run through a space experience program to invite the users into the space, to help a first user that arrives to prepare for the dyadic session, to transition the users to a dyadic sharing environment where displays can be easily used to facilitate sharing and perhaps some content development and to help the user's transition out of the dyadic environment when the session is completed. Many other sequences

[0110] Referring now to FIG. 11, a process **430** that is consistent with at least some aspects of the present disclosure is illustrated. During the entire process shown in FIG. 121, server **102** (see again FIG. 2) monitors inputs from one or more sensor devices **112**, **114**, **116**, **118**, **120**, **122**, etc., and determine how to control space affordances as a function of the sensed inputs to facilitate a specific space experience. At block **432** server **102** controls the affordances associated with a specific space (e.g., lighting, sound, etc.) to present an “invite environment” within the space. Here, it is contemplated that in at least some embodiments, where two spaces within a facility have similar affordances and therefore similar capabilities to present space experiences, all invite environments will have similar characteristics so that system users can become accustomed to quickly recognizing an invite experience and distinguishing that experience from others. Here, the invite environments may only be similar because different spaces may and often do have different environmental affordances. For instance, a first space may include one or several display screens (see again **200** in FIG. 2) while other spaces may have no display screens. Nevertheless, each of the two spaces may include similar lighting, audio components for generating sound, sensor arrays, temperature and circulation affordances, etc. Here, the common affordances may be controlled in a similar fashion to facilitate a space experience and the screens in the first space may be used to enhance the experience.

[0111] An invite experience should be an experience that indicates that a particular space is available for use and that can be reflected in at least some fashion in each of several different spaces irrespective of the affordances within each space. For instance, where a facility includes thirty separate spaces within a general area that can be used by one person or a small group of persons and where each of the spaces includes at least some light device that is capable of generating various colors of light, a universal invite environment may include generating green

colored light using each light device in a space that is capable of generating green light. Thus, where fifteen of the thirty spaces are available for use, a user may simply observe which spaces are generating green light and therefore which spaces are inviting use. Other more complex invite environments are contemplated.

[0112] Referring again to FIG. 11, while the invite environment is presented at block 432, at block 434 server 102 monitors sensed inputs to identify specific circumstances or triggers that indicate that a user at least near the space has an interest in using the space. For example, an interest in using a space may be identified when the system senses that a user has entered the space, when a user closes a door after having entered the space, when a user verbally announces (e.g., announces “control space”) a desire to claim the space, etc. at block 436, if no trigger indicating interest is identified, control continues to loop back through blocks 432 and 434 where the invite environment persists.

[0113] Once a possible interest trigger is identified, control passes to block 438 where server 102 controls the output devices in an associated space to present a “welcome environment” (e.g., a second phase of a space experience). The welcome environment is designed to welcome a user and transition the user to an activity to be performed within the space. While many different welcome environments are contemplated, it is envisioned that the welcome environments associated with different activities to perform within a space will be different depending of the activity to which the space experience is transitioning to. For example, if the activity to be facilitated within a space is a rest or meditation type activity, the welcome environment may be one designed to, in addition to indicating a transition from the invite state, reduce stress and calm the user. For instance, the welcome state may call for the color of the lighting in the space to be changed from the universal green associated with an invite environment to a warm yellow/orange and may cause a relaxing sound track to be faded in at a low volume, may reduce air circulation within the space and may control one or more display screens within the space to present a color output that is similar to the color of the light generated by the lighting devices within the space.

[0114] As another example, where the activity to be facilitated includes focused individual work, the welcome environment may first include a change from green to warm yellow/orange light and a city sound track that includes the sounds of a busy street to indicate a transition from the invite state and then the light may slowly fade to extremely bright white light throughout the space 220 and a cool blast of air via the air circulation controller 172 to invigorate the user during a two minute period prior to the focused activity. During the two minute welcome phase the user could stow a bag and/or a garment, get materials out of a bag and set them up on the work surface and get seated in a comfortable position within the space.

[0115] As yet one other example, in a case where a space is to be used for dyadic collaboration between two persons, the welcome environment may, in addition to changing from green light to warm yellow/orange, call for turning on displays screens within the space and starting a process designed to enable two persons to share content via those screens. For instance, the process designed to enable sharing may include stepping through a password entry process enabling users in the space to associate their portable devices with the space whereby the system generates a random password which is presented on each screen in the space and each user enters the same password into their portable devices to associate each portable device with the space and hence with the displays mounted within the space 220. In other cases where the system includes hardware controllers like the controllers 410 described above with respect to FIG. 10, the system may simply instruct each user to plug one of the control devices 410 into their portable device as part of the welcome environment phase.

[0116] Referring again to FIG. 11, while the welcome environment is presented, server 102 monitors for a circumstance or trigger that indicates a transition to the activity phase to be facilitated. For instance, a successful RFID read may comprise a transition trigger, the end of a period (e.g., a 2 minute welcome environment process) may trigger a transition, a user in a space

assuming a different position such as a seated position may comprise a transition trigger, etc. If a trigger is not detected at **442**, control passes to block **452** where server **102** monitors for an end of space use trigger. Here, it is recognized that an interest trigger may be detected at **436** and thereafter a potential space user may not transition to an activity within the space and may instead end use of the space in some fashion. Transition to block **452** enables exit from the activity monitoring loop.

[0117] If a transition trigger occurs at block **442**, server **102** presents an “activity environment” at block **444** that is designed to enhance the specific activity to be facilitated within the space. For instance, where the activity is a rest activity, server **102** may automatically fade to a rainstorm sound track that mimics rain falling on pavement and light thunder noise and may also fade to a dark blue light that pulses along with the sound of the periodic thunder noise. As another instance, where the activity is focused individual work, server **102** may automatically lower the light intensity surrounding a work surface while maintaining high intensity white light on top of the work surface and the sound may fade to a low volume white noise track to drown out any ambient noises proximate the space.

[0118] In the case of a dyadic activity, the activity environment may include fading a sound track off and lowering lighting in a space generally while still having area lighting lit up above or proximate conferees in the space.

[0119] At block **446** server **102** monitors for a trigger or action that indicates the end of a specific activity or the end of a period assigned to the specific activity. For instance, in the case of a rest activity, the trigger may be the end of a period over which the activity was to occur. Thus, if a rest period or session was to include a total of thirty minutes including a two minute transition in during the welcome phase and a two minute transition out phase near the end of the session, server **102** would be programmed to recognize the end of a **28** minute period as a trigger and, at block **448**, would move to block **450** at the end of the period and would present an “emerge environment”.

[0120] As another instance, in the case of focused individual work, the trigger may be a conferee standing up within the space and opening the space door **105**. In another embodiment the trigger may be a conferee turning off or otherwise disassociating her personal portable device from the space. In still another case the trigger may be 5 minutes prior to a next scheduled time for the space (e.g., prior to the start time of use of the space by another person). Other triggers are contemplated.

[0121] In the case of dyadic activities, the trigger may include opening of the space door, one or both of two conferees leaving the space, at least one conferee leaving and remaining out of a space for at least a threshold time period (e.g., five minutes), delinking of portable devices from the space, etc.

[0122] Until an end of activity trigger occurs at block **448**, control continues to loop back through blocs **440**, **442**, **444** and **446**. Once an end of activity trigger occurs, control passes to block **450** where server **102** controls the space affordances to present an “emerge” environment to indicate the end of an activity period and to help transition a space user out of the space. For instance, in the case of a rest activity within a space, the system may fade lighting up to a bright yellow light that floods the space, present a video of the sun coming up, fade in a morning sounds track including chirping birds and light waves rolling in on a beach, increase air circulation and decrease temperature by a few degrees. In the case of individual focused work, the system may increase area light generally while decreasing intensity of light on a work surface so that the light in an entire space is essentially uniform but at an intensity that is less than optimal for individual focused work, fade in a different sound track and change other environmental characteristics. In the case of dyadic work, in addition to changing lighting, sound, temperature and air circulation characteristics, the system may also facilitate storing of any digitally developed work product by querying conferees if any content (e.g., documents or files opened in the space) should be stored for subsequent use, e-mailed to one or several accounts such as one or more e-mail accounts associated with the conferees in the space, etc.

[0123] At block **452**, server **102** monitors for an end of space use trigger. The end of space use trigger indicates that the person or persons that were most recently using the space no longer intend to use the space. For instance, an end of space use trigger may include a person leaving the space. In other cases an end of space trigger may require that a person remain outside a space for at least three minutes (e.g., some threshold duration). In other cases an end of space use trigger may require that a person affirmatively disconnect the person's portable device (e.g. a tablet, phone, etc.) from the space and leave the space for at least three minutes. In yet other cases a person may have to leave a larger space such as a building or a floor on a building or a depart on a floor of a building to disassociate from a personal or conference space.

[0124] Referring again to FIG. **11**, at block **454**, until an end of space use trigger is detected, control continues to loop back up to block **440** where server **102** monitors for circumstances indicating a transition to an activity. If a trigger is detected at **454**, control passes back up to block **432** where server **102** represents the invite environment (e.g., green light) to invite other persons to use the space.

[0125] The space experience described above with respect to FIG. **11** includes four stages or phases and four trigger based transitions between the four phases at blocks **436**, **442**, **448** and **454**. In other cases it is contemplated that less or more phases may occur, depending on the space experience that is being facilitated. It is also contemplated that more than one trigger may be specified for each of the phase transitions that occurs. For instance, referring again to FIG. **11**, at block **448** where server **102** monitors for an end of activity trigger, server **102** may be programmed to monitor for any one of a space user leaving a space, affirmatively indicating an end to use of the space via a Room Wizard or the like, disassociating the user's personal device from the space, etc.

[0126] In at least some embodiments it is contemplated that different spaces may be fitted out with different affordances that are optimized for different activities. For instance, some spaces may be optimized to facilitate individual rest activities while other spaces may be optimized to facilitate individual focused work and still other spaces may be optimized to facilitate dyadic conferencing activities or video conferencing activities. In these cases, when a user transitions to an activity within the space at block **442** in FIG. **11**, the server may automatically facilitate the activity that the space is optimized to present. For instance, when a user enters a space optimized for rest activities and closes a door to the space and causes the user's RFID device to be read (e.g., a block **442** trigger in FIG. **11**), server **102** may present the rest activity space experience. As another instance, when a user enters a different space optimized for dyadic activities and a claiming or activity trigger occurs, the system may immediately present the dyadic space experience.

[0127] In at least some cases it is contemplated that while a space may be optimally designed to facilitate one or another space experience, a user may be able to use the space to facilitate a different space experience, albeit one that is less than optimal given affordances within the space. For instance, where only a first space that is optimized for dyadic activities is available for use at a specific time (e.g., all other spaces are used by others) but a user wants **30** minutes of rest, the user may opt to use the dyadic space for rest. Here, the user would specify a rest activity and server **102** would identify the affordances associated with the dyadic space and present a rest space experience within the dyadic space even though the experience would not be optimized for rest.

[0128] Referring now to FIG. **12**, an exemplary space **460** that includes affordances that are optimized for presenting a rest space experience is shown. The space affordances include single sided illuminated wall panels **462**, **464**, **466** (see again the single sided light panel structure in FIGS. **3** through **5**) and a fourth panel (not shown) where one of the panels **464** forms an egress **468** that is closable via a sliding door **470** that includes a handle **472**. Sensors **474** and **476** are mounted within the egress **468** to detect the location of the door **470**. A speaker **202** is mounted in a ceiling structure, an RFID sensor/reader **472** is mounted in wall structure **464** and a room control device (e.g., a Room Wizard) **104** is also mounted within the wall structure **464**. A comfortable lounge chair **252** is provided within the space **460**. In at least some embodiments the lounge chair

452 may have at least some reclining capabilities.

[0129] Referring to FIG. **13**, a process **490** that shows an exemplary rest space experience that may be facilitated within the space **460** of FIG. **12** is shown. Referring also again to FIG. **1**, at block **492**, server **105** presents an invite environment by illuminating the wall light panels **462**, **464**, **466** and the fourth light panel (not shown) with pulsing green light. In FIG. **14**, a potential space user **501** has entered the space. At this point the invite environment is continually presented in this example. At block **494** server **105** monitors sensor **474** to determine when the door **470** starts to move to the closed position. In FIG. **15** it can be seen that the user has closed the door **470**. At block **496**, once door movement toward the closed position is sensed, control passes to block **498** where server **102** fades the light within the wall panels from the pulsing green to a non-pulsed warm orange/yellow and also fades on a city walk sound track.

[0130] At block **500** server **102** monitors sensor **472** for an RFID device read. IN FIG. **16** the user presents an RFID device to be read by sensor **478**. Once an RFID device is read at **502**, control passes to block **504** where server **102** fades in a rainstorm sound track and fades the lighting effect to a blue pulsing effect where the pulses are synchronized with the sound track. Here, the blue pulsing light and sound track are designed to facilitate rest. As shown in FIG. **17**, the user sits in the lounge **452** and assumes a comfortable position as the light and sound track fade into the rest phase states.

[0131] At block **506** server **102** monitors for an end of activity trigger. Here, in at least some embodiments, the end of activity trigger will be the end of a period (e.g., a **30** minute rest period). At block **508**, as the end of a period is approaching (e.g., two minutes prior to the end of the period during which the user has reserved the space for), control passes to block **510** where server **102** fades to the emerge environment. In this case the server **102** fades to a warm orange/yellow and fades in the city walk sound track again. This time the warm light may be pulsing and the city walk sound track may fade to a higher volume than presented at block **498**. Near the end of the reserved period, the system may identify a next scheduled event for the space user and may generate an audible message to the user indicating the next event. In the alternative, the server may identify two or more events scheduled for the user and present a full or truncated schedule in an audible message. In FIG. **18** it is shown that at the end of an activity the system will present an emerge environment.

[0132] At block **512** server **102** monitors for an end of space use trigger. In FIG. **13**, the end of space use trigger includes opening the space door. In FIG. **19** the user is shown opening the door **470** which triggers the end of space use. Once door **470** is opened, control passes back up to block **492** where server **102** again presents the invite environment (e.g., green pulsating walls).

[0133] As described above, other triggers and phase environments for a rest space experience are contemplated. For instance, the simple door open trigger at block **514** may be replaced by a door open and remains open for at least three minutes trigger if the period during which the space is reserved has not lapsed. As another instance, an RFID read may not be required to kick off a rest activity and closing a door within the rest space **460** may suffice for server **102** to present a rest space experience.

[0134] Referring now to FIG. **20**, an exemplary space optimized to facilitate dyadic activities is shown. The dyadic space includes four wall subassemblies **534**, **536**, **538** and **542** that form a rectilinear space **532** and a ceiling structure **540** that closes off the top of the space. Each of lateral walls **534** and **538** may include opaque panel assemblies generally. A storage bin **274a** **274b** is mounted to each of the lateral walls **534** and **536** at about head height (e.g., a lower floor member of each of the bins may be anywhere between four and a half feet and six feet above the floor structure). An upwardly shining light (see again **180** in FIG. **1**) may be mounted to the top surface of each of the bins **274a** and **274b** for directing light toward the upper portion of each of the walls **534** and **538**.

[0135] Each of the end walls **536** and **542** is similarly constructed and each includes double sided

RGB LED light panels that can be controlled to generate virtually any color light and that shine light to either side thereof when illumination is turned on. Each end wall **536** and **542** forms an egress and includes a sliding glass door **105**, **531** that can be opened or closed.

[0136] Referring still to FIG. **20**, a lounge structure **400a**, **400b** akin to the lounge structure described above with respect to FIG. **10** is provided against each of the lateral wall subassemblies **534** and **538** such that persons sitting on the different lounges face each other. Each lateral wall includes a flat panel display screen **200a** and **200b** mounted therein at a height below the bottom surface of one of the bins **274a** and **274b** and above the lounge **400a** or **400b** positioned there below. In at least some embodiments each of the displays **200a** and **200b** may be offset to one side (e.g., closer to one of the end walls **536** or **542** than the other) so that if a user sits on one end of a lounge **400a**, the display **200a** can be seen substantially unobstructed to the side of the user's head. In some embodiments display **200a** may be offset to one wall (e.g., **536**) while the other screen **200b** is offset to the other wall (e.g., **542**).

[0137] Where each of the lounges **400a** and **400b** includes control devices like the ones described above with respect to FIG. **10**, the control devices provided by one of the lounges may control one or both of the display screens **200a** and **200b** within the space **532**. Thus, for instance, where a user links a portable device to a controller **410**, output of the linked device may be presented on one or both of the displays **200a** and **200b** at the preference of the user. In other cases portable devices within space **532** may be wirelessly linked to server **102** for controlling output on the displays **200a** and **200b**.

[0138] Referring to FIG. **34**, in another embodiment each of the displays screens **200a** and **200b** within a space **960** may have large dimensions selected so that the display screens cover substantially the entire surface of a wall section behind each of the lounges **400a** and **400b** above the lounge backrest portions. Here, a space user may use all or a portion of one of the display screens **200a** or **200b** or all or different portions of each of the display screens to present content within the space **960**. In addition, a processor driving each of the display screens may be programmed to, in at least some cases, divide the space of each screen into two or more subspaces that can be controlled independently by one or different persons within the space **960** to present content. For instance, in FIG. **34** display **200a** is shown divided into two spaces **962** and **964** while display **200b** is shown divided into two spaces **966** and **968**, where each of the spaces may be controlled to present different content via a wireless personal portable device (e.g., see **970** and **972** in FIG. **34**) or via connection to one of the controllers **410** provided within one of the lounge assemblies **400a** or **400b** as described above.

[0139] Where one person is using space **960**, in most cases it will be advantageous for that person to present content on displays that are opposite that person within space **960** and that face that person. For instance, in FIG. **34**, a user seated on lounge **400a** would likely prefer presenting content on display **200b** while a user on lounge **200b** would likely prefer presenting content on display **200a**. In addition, a user on a right side of lounge **400a** facing screen **200b** would likely want content presented on display **200b** centered on the portion of display **200b** directly in front of that user (e.g., the left portion **968** of the display **200b** that is aligned with the user on the right portion of lounge **400a** while a user on the left side or portion of lounge **400a** would likely want content presented on the right portion **966** of display **200b** that is aligned with that portion. Where different sections of the display **200b** (and **200a** for that matter) are selectable for presenting content via a controller **410** or virtual on screen tools presented to a user via a portable device, the user could select the most suitable portion of a display in space **960** for presenting content based on the user's location.

[0140] In at least some cases the system server **102** may be programmed to use sensed information from within space **960** to determine user locations and may be programmed to automatically identify optimal emissive surface spaces for use by persons within the space **960** given intended use of the space. For instance, where a single person enters space **960** and closes the door **105**, the

system may recognize that a single person is in the space **960**. Images from one of cameras **116** may be used to sense a person, the location of the person, the juxtaposition of the person within space **960**, etc. When the person sits down on the right side of lounge **400a** facing screen **200b** and has a personal portable computing device (e.g., a tablet), the system may automatically start a process to link the portable device wirelessly to the server **102** to control content on the portion **968** of display **200b** aligned with and spaced from the user. Once the portable device is wirelessly linked to the server **102**, the server **102** may identify the location of the person on, for instance, the right side portion of lounge **400a** and may present content in space **966**. To this end, see also FIG. **35** where display **200b** is shown and is divided virtually into two spaces **966** and **968**. Here, the first person's content would be presented in space **968** apart from the first person.

[0141] Continuing, if a second person enters space **960** and sits across from the first person on the left section of lounge **400b** (see the person **980** in FIG. **35**), the server may recognize the second person's location and shift the first person's content on display **200b** to section **966**, to the side to the second person. In addition, in at least some cases, the system may automatically present the first person's content on the left portion **962** of display **200a** (see again FIG. **34**) to the side of the first person for the second person to view.

[0142] In some cases first and second person's can present content via the displays **200a** and **200b** at the same time. For instance, in FIG. **34**, the first person may present content via display sections **962** and **968** so that the first person and a second person on lounge **400b** can view the content at the same time without turning away from each other while the second person on lounge **400b** presents in spaces **964** and **966** for both persons to view. Here, each person may use one of the controllers **410** described above or may use a virtual wireless controller (see again FIG. **10** above).

[0143] Referring to FIG. **36**, in some cases when one person uses a space **960** to view content, the system may automatically recognize the single person use of space **960** and optimize content display size and display location for the specific user. For instance, in some cases the optimum size may be the largest size possible given formatting (e.g., dimensions) of content to be displayed. In FIG. **36**, a single person's virtual content space is labeled **982** and is as large as possible given dimensions of the content to be presented therein. The single person content window may be automatically placed in front of the single user based on current location within the space.

Referring to FIGS. **34** and **36**, space **282** is automatically located at a location that would be in front of a user seated on the right half of lounge **400a**. If the user moves from lounge **400a** to lounge **400b**, the content window may be moved from display **400b** to an aligned location on display **400a** automatically, based on images from cameras **116** or information generated by other sensors associated with space **960**.

[0144] When a single user requires two adjacent content spaces or each of two persons in space **960** requires a separate content window on one of the space walls, the sizes of the spaces used by each of the persons may again be automatically optimized. For instance, see FIG. **37** where spaces the size of each virtual space **986** and **988** is relatively smaller than the size of space **982** in FIG. **36** to optimize for presenting two content spaces automatically. In FIG. **37**, the height dimension of each space **986** and **988** is less than the maximum height allowed by display screen **200b** to maintain the relative dimensions of the content being presented.

[0145] Referring again to FIG. **20**, a speaker **202** is mounted in the ceiling structure **540**. Two cameras **116** are mounted to the ceiling for obtaining images of fields of view within space **532**. Images from the cameras **116** are provided to server **102** for processing. Door sensors **112** and **113** are provided for each of the doors **105** and **531**. A space control device (e.g., a Room Wizard) **104** is mounted to an external surface of wall subassembly **534**.

[0146] Referring yet again to FIG. **20**, in the case of a space **530** optimized for dyadic activities, prior to a user entering the space, the space may pulse green light within the two sided light panel wall subassemblies **536** and **542**. In addition, the display devices **200a** and **200b** may also pulse green to present an invite environment. When a user **501** walks into the space **532**, analysis of

images from cameras **116** may cause server **102** to recognize that a user is present within the space. User recognition within the space **532** may operate as an interest trigger and server **102** may then fade or otherwise present a welcome phase environment (e.g., warm yellow/orange light, a welcoming sound track, control of displays **200a**, **200b** to provide simple instructions, etc.).

[0147] Referring to FIG. **20**, change in the user's posture such as the user **501** sitting down on one of the lounges **400a** may be discernible within camera images and may operate as an activity trigger causing server **102** to recognize a claiming of the space **532**. Upon sensing that a user has assumed a seated position, server **102** may present an activity phase environment for a single person where for instance, a personal portable device **600** used by the user and present in the space **530** is automatically linked to the space **530** for controlling one or both of the display screens within the space. For example, where the user is facing screen **200b** as in FIG. **21**, the server **102** may only associate the user's device **600** with display **200b**. If the user were facing display **200a** instead, the server **102** may only associate the user's device **600** with display **200a**.

[0148] If a second user enters space **530** to confer with the first user, images from cameras **116** may be used to recognize the second person and to present a different space experience or to transition to a different phase in an experience being presented. For instance, where a first user has been using the space **530** to view a document on screen **200b**, when the second person enters the space **530**, the system may automatically “hide” the document on display **200b** and change the lighting in the space so that the lighting is optimized for a two person discussion. Where the second user assumes a seated position facing the first user, the system may control the lighting again to optimize for viewing display screens by dimming light in the walls **536** and **542** and increasing the intensity of light generated by the upwardly directed light fixtures mounted to the tops of bins **274a** and **274b**. Other changes may include coordinated light color changes and light effects (e.g., pulsing), sound track changes, temperature, air circulation, etc.

[0149] Other space affordance packages optimized for specific activities are contemplated. For instance, see FIG. **22** that shows another space configuration **640** including wall subassemblies (only three of four shown) **644**, **646** and **648** and a ceiling assembly **650** that define a space **642**. Wall subassembly **644** includes a plurality of single sided light panels while each of walls **646** and **648** includes opaque panels generally with indirect light panels **652** like the one described above in FIG. **6**. Ceiling lighting **178** and a speaker **202** are mounted in the ceiling substructure **650**. In addition, a wireless access point **112** is mounted in ceiling **650** for sensing personal devices (e.g., smart phones, a laptop, a tablet device, etc.). A video conferencing assembly **651** is positioned in front of a bench **653** where the bench **653** butts up against wall **644** so that the indirect light from panels **652** is directed at a user resting on bench **653** in an optimal fashion for video conferencing.

[0150] In FIG. **22**, prior to a person entering space **642**, server **102** may present the invite phase experience (e.g., green pulsing light). When a user enters space **642** with a personal portable computing device, signals received by access point **112** (and perhaps other access points within the general area of space **642**) are processed to identify the location of the device within the space **642**. Upon identifying a user's device in space **642**, server **102** controls the space **642** affordances to fade to the welcome phase environment. Again, in at least some cases, this will include changing light color to a warm yellow/orange and presenting a sound track via speaker **202**. In addition, server **102** may present a control interface to the user via the user's portable device asking the user if the user intends to claim the space **642** for video conferencing use. Here, the activity trigger may be selection of a video conferencing option on the portable device that is transmitted to the server **102** via access point **112**. Upon receiving the trigger, server **102** may control assembly **651** to initiate a video conference and may adjust other space affordances including lighting **652** and the light generated by wall subassembly **644** to optimize for video conferencing.

[0151] FIG. **23** shows a space configuration **680** that may be optimized for short individual activities like, for instance, fielding a phone call, generating an e-mail, reviewing a document, etc. To this end, configuration **680** includes wall subassemblies **684** and **686** (and a third wall now

shown) that generally include opaque panels, albeit where assembly **686** includes a single sided light panel assembly **226** adjacent a desk or shelf assembly **692** that forms a horizontal work surface. A hanging light **192** extends downward from a ceiling substructure and a speaker **202** and an access point **112** are mounted to the ceiling structure as well. A door (either hinged or sliding) **688** is mounted to the wall substructures and is moveable between open and closed positions enabling access to the space **682** defined by the wall substructures. A stool **22** is provided within space **682** adjacent shelf assembly **692**. Here again an invite phase environment is presented followed by a welcome phase environment, an activity environment and then an emerge environment during a space experience, with each transition between consecutive environments being initiated when one or more trigger activities occurs. In this case the activity phase environment may include illuminating panel light **226** with bright white light to illuminate the top surface of assembly **692** as well as playing a suitable sound track (e.g., white noise, etc.). Many other optimized spaces are contemplated.

[0152] In at least some embodiments, as explained above, the characteristics of any space experience of a specific type may all be substantially similar such that, for instance, any rest space experience presents the same phase characteristics to the extent possible given space affordances in specific spaces. To this end, referring again to FIG. **1** and now also to FIG. **24**, database **130** may include space experience specifications **700** through **112** for each of N different space experiences including a rest space experience specification **700**, a phone call space experience **702**, a video conference space experience specification **704**, an individual focus space experience specification **706**, a dyadic space experience specification **708**, a respite space experience specification **710**, etc. Each specification indicates triggers as well as phase characteristics to be presented upon occurrence of each trigger.

[0153] For instance, see FIGS. **25** and **26** that show an exemplary rest space experience specification **700** including a phase column **720**, a trigger column **722**, an environmental factor column **724** and a preference column **726**. The phase column **720** lists each of the four rest space experience phases including the welcome, activity, emerge and invite phased. For each phase in column **720**, the trigger column **722** lists a set of possible triggers for initiating the phase in column **720** where currently set triggers are shown with phantom boxes there around. For instance, for the welcome phase in column **720**, column **722** includes a set of possible triggers at **730** and the currently set or default trigger is the “door closing” trigger highlighted by a phantom box at **735**. In FIG. **26** it can be seen that for the emerge phase, the trigger column includes three possible independent triggers including “end of duration”, “door opening” and “space empty” triggers, any of which can trigger the emerge phase.

[0154] Referring still to FIGS. **25** and **26**, in column **724**, a set of possible controllable environmental factors are presented for each of the phases in column **720**. Thus, for instance, the factor set **732** in column **724** are associated with the welcome phase in column **720** and includes all of the environmental factors that can or are controlled by the system server **102** to present the specific phase. In some cases the set of controlled factors may only be a subset of the full set **732** present in the database. Where a specific space is controlled to present a specific phase and the space does not include all of the affordances required to control all of the factors associated with the phase, the server will only control the subset of factors that can be controlled given the specific affordances within the space.

[0155] Referring yet again to FIGS. **25** and **26**, preferences column **726** includes a set of effects that may be presented for each of the environmental factors in column **726**. For instance, the set of effects **734** is specified for a lighting color factor in column **724**, the set of effect **736** is presented for a lighting effect factor in column **724**, set **739** is provided for the sound effect factor in column **724**, set **738** is provided for a lighting brightness factor in column **724**, set **737** is provided for a sound factor in column **724**, set **743** is provided for an air circulation factor in column **724**, set **744** is provided for a privacy factor in column **724**, set **745** is provided for a display factor in column

724. Volume and temperature fields **739** and **740** are also indicated in preference column **736** for the welcome phase in column **720**.

[0156] Again, default preferences are indicated by phantom boxes about specific preferences in column **736**. Thus, for instance, the lighting color preference for the welcome phase is “fade to warm orange/yellow”, the lighting effect is “no pulse”, the sound effect is “fade to city walk”, etc. [0157] Some phases may have different subsets of triggers, environmental factors and preferences than others. For instance, see in FIG. **25** that there is a “duration” factor **750** associated with the activity phase while there is no duration factor associated with the welcome phase. FIGS. **25** and **26** represent default settings for the rest space experience. Referring again to FIG. **24**, specifications similar to the FIG. **25** and FIG. **26** specification would be provided for each of the other space experiences **702** through **712**.

[0158] In addition to including the experience specifications, database **130** also includes a sub-database **718** that associates different spaces with different default space experiences. Here the default experiences will usually be the experiences for which specific spaces have been optimized. Sub-database **718** includes a space column **716** and a default specification column **714**. Column **716** lists each space that is associated with the FIG. **1** system and, for instance, may include a listing of a large number of differently afforded spaces **00001** through **NNNNN**. Column **714** includes a default specification (e.g., one of the specifications **700** through **712** in FIG. **24**) for each of the spaces in column **716**. For instance, each of spaces **00001**, **00002** and **00003** are associated with the default rest specification **700**, each of spaces **00004** and **00005** are associated with the default video conference specification **704**, and so on.

[0159] Referring again to FIG. **1**, in at least some embodiments it is contemplated that a system administrator may be able to use an administrator's computer **140** to change characteristics of each type of space experience. For instance, triggers for each phase of each experience as well as the characteristics of each phase experience may be customized given space affordances as well as the effects that an administrator intends to present. In at least some cases an administrator may also be able to change the space experiences that a specific space presents including, for instance, the default space experience associated with each space. To alter space experiences (e.g., triggers, characteristics, defaults, etc.), the administrator may access an interface that presents the database information as shown in FIGS. **25** and **26** for a specific space and may then be able to select a default space experience and then set triggers and preferences as desired.

[0160] It has been recognized that, in at least some cases, a space user will want the ability to customize space experiences during different space sessions. For instance, while a rest space experience may, by default, present blue illumination that pulses with a sound track during the rest activity phase of the experience, a specific user may instead prefer a dark orange non-pulsing illumination during the activity phase. As another instance, the same user may prefer a different sound track and a higher volume than the default track and volume during the emerge phase of the rest experience.

[0161] To accommodate customization of space experiences by specific users, in at least some embodiments a space user may use a computer (e.g., **140** in FIG. **1**) to set personal parameters for each type of space experience or for a subset of the space experiences presentable by the system. Here, as in the case of a system administrator, the interface would present information akin to the FIGS. **25** and **26** database and allow the user to select different preferences and triggers.

[0162] In addition or instead of providing users the capability of setting parameters via a computer **140** that is separate from a space, an environment interface may be presented via a space or room controller (e.g., a Room Wizard) that is extremely intuitive and which can be used at the location of a space to set various space experience characteristics during any space session. To this end see the exemplary space controller interface screen shots in FIGS. **27** through **32**. In at least some cases when a user determines that a particular space experience was particularly effective, the user may store the experience for subsequent use when the user wants another similar experience.

[0163] Referring specifically to FIG. 27, the screen shot **770** presented via device **104** (see also **104** in FIGS. 1 and 2) will include, in at least some embodiments, a persistent ribbon of tool icons along a lower edge which is always presented when the environment control functionality of the control device **104** is accessed so that any user will be familiar with how to access and use the tools. In FIGS. 27 through 29 an abbreviated set of three tool icons is presented that includes a light control icon **774**, a sound control icon **776** and a temperature control icon **778**. An exit icon **780** is also provided in the lower right hand corner of the screen shot that can be selected to return to the Room Wizard scheduling screen or some other general control interface in the case of some other control system.

[0164] When light control icon **774** is selected, the screen shot **770** in FIG. 27 is presented which includes fourteen different light color option icons (three labeled **772**) and a light off icon **782**. Each color option icon can be selected to change the color of light generated by the light devices within an associated space. Off icon **782** can be selected to turn off the light in the space. In addition, in at least some embodiments screen shot **770** will include a light intensity icon **771** and icons **773**, **775** and **777** that can be used to select light pulsing characteristics for space lighting devices. Icon **771** is a slide button type icon where a user can select different points along the length of the icon to change light intensity along a range between a low level and a maximum level. The pulsing characteristic icons include a steady state or non-pulsing icon **773**, a smooth pulsing icon **775** and an icon **777** that ties light pulsing to sound of a current sound track being played within an associated space. Non-pulsing icon **773** is selectable to have a steady light intensity set by icon **771**. Smooth pulsing icon **775** sets the pulsing effect to follow a sinusoidal pattern where light intensity is faded on and off in a continuous pattern. Icon **777** is selectable to set the pulsing to follow the pattern of sound generated by a currently playing sound track. As the light control icons are selected, the light generated in the associated space may be controlled to present the selected light effect so that the user can see the effect selected and hunt for an optimized setting.

[0165] Referring to FIG. 28, when sound icon **776** is selected, a screen shot **790** presents sound control icons including sound track icons (four labeled **792**), volume control icons **794** and **796** and a mute control icon **798**. Each of the sound track icons **792** includes a text label that indicates the type of sound track generated. For instance, exemplary labels include a “city walk” icon, a “riverbank” icon, a “north woods” icon, etc., that are associated with different sound tracks. Icons **794** and **796** can be used to increase or decrease the volume of a selected sound track and icon **798** can be used to turn a selected sound track on and off.

[0166] Referring to FIG. 29. When temperature icon **778** is selected, a screen shot **800** for controlling space temperature is presented that includes “warmer”, “normal” and “cooler” icons **802**, **804** and **806**, respectively. The temperature within an associated space can be controlled using the icons **802**, **804** and **806**. Here, the normal icon **804** may correspond to a preset or default temperature such as, for instance, 74 degrees and can be selected to revert back to the default setting.

[0167] In other embodiments additional space control icons may be presented within the ribbon of control icons along the bottom edge of the space control interface. For instance, see in FIG. 30 that additional control icons **820**, **822** and **824** are included in the lower tool bar or tool ribbon. Icon **820** is an air circulation icon which can be selected to present the circulation control screen shot **825** that includes “off”, “normal” and “high” icons **826**, **828** and **830**, respectively. Icons **826**, **828** and **830** can be selected to turn off air circulation, revert back to a default circulation setting and increase air circulation, respectively, within an associated space.

[0168] Icon **822** is a notice control icon which can be selected to control electronic notifications such as e-mails, texts, social updates, etc., to a space user during a space experience or during a phase of one of the experiences. For instance, during the activity phase of a rest space experience, a space user likely would not want any electronic notifications/disturbances but the user may want all electronic notifications or updates received during a rest activity to be presented immediately at the

end of the rest activity and during the emerge phase of an experience. Icon **822** can be used to control notifications. When icon **822** is selected, screen shot **839** may be presented including notice control icons **840**, **842** and **844**. Icon **840** can be selected to turn off all electronic notifications to the user in the space. Icon **842** can be used to turn on notifications to the user. Icon **844** can be selected to selectively activate notifications. For instance, a space user may always want to receive notifications from the user's boss regardless of any activity the user is participating in. A set of message senders that are particularly important may be associated with icon **844** in the system database **130** for each system user so that notifications from any of those users are receivable within an associated space while notifications from others are blocked.

[0169] When a notice icon is selected from screen shot **839**, an indication of the selection is sent to system server **102** which uses the selection to control notice to the user in the space accordingly. Here, server **102** may send wireless signals to user devices within an associated space causing those devices to enter a no notice mode so that those devices do not provide notice during an experience or during one or more phases of an experience. At the end of a no notice phase, all notices received during the no notice phase may be provided as if they were received at that time.

[0170] Referring to FIG. **32**, an activity icon **824** can be selected to select a session experience other than a default experience associated with a specific space. To this end, when icon **824** is selected, a screen shot **843** may be presented that lists different space experiences as selectable icons **830** including, for instance, a “rest” icon, an “individual focus” icon, a “dyadic+” icon, etc. Here, for instance, if a space is optimized for individual focus but a user wants to use the space to facilitate a rest space experience, the user may select the “rest” icon to cause server **102** to control the space experience during a session to present the rest experience instead of the individual focus experience. In this case, while the space may be optimized for individual focus, the affordances may nevertheless be controlled to facilitate a rest experience and server **102** simply controls the affordances within the space accordingly.

[0171] In at least some embodiments a space may not include a dedicated space control device like **104**. In these cases it is contemplated that the functionality of the space control device **104** described above may be provided via portable user devices like smart phones, tablet computing devices, laptops, etc. Here, for instance, when a user is proximate or within a specific space, the system may enable the user to access a space control program that presents screen shots akin to the screen shots described above with respect to FIGS. **27** through **32** for customizing space experiences.

[0172] In at least some embodiments when space characteristics are set via interface screen shot **770**, the space characteristics may remain as set during an entire space session. For instance, where light characteristics are set by a user during a welcome phase of a rest experience, the light characteristics may remain set until the end of the rest experience without cycling through different activity and emerge phases. In other embodiments it is contemplated that users will always want an emerge phase to indicate that a session period is nearing an end and to help transition the users out of the space. In these cases, user set light and other characteristics may persist from the time set through the activity phase of a space experience and the emerge phase may always occur per the default settings. In still other cases user light and other characteristic settings may be set only for a specific phase of a space experience and the settings may revert to default settings at the end of a current phase.

[0173] It has also been recognized that a space user may perceive that a specific set of space characteristics are optimal for the specific user. For instance, a user may perceive that a specific set of space characteristics set during a rest activity phase of an experience were particularly effective. In this case, instead of requiring the user to remember the settings and reselect the settings the next time the user participates in a rest space experience, the system enables each user to store their preferred and customized settings for any of the space experiences. For instance, a user may customize settings for a rest space experience and each time the user participates in a rest space

experience thereafter in any space, the user's preferred phase settings may be replicated automatically. Thus, the next time a user claims or uses a space for a rest experience, the customized experience would be presented without requiring the user to set or select any settings. In this case, for example, a user may use a first space in a first facility for a rest experience on Monday and may use a second space in a second completely different facility for a rest experience on Friday and the same rest experience customized for the specific user may be presented in each space automatically.

[0174] To enable a user to save a customized particular type of space experience, referring again to FIG. 27, a control interface may present a “save” icon **799** that can be selected to save the settings associated with a current space experience for the specific user. Here, after all characteristics for an experience have been set via the interface screen shots (e.g., FIGS. 27 through 32), the settings are stored for the user in the system database **130** (see again FIG. 1). See also FIG. 33 that shows an exemplary database **130'** that, in addition to including the default space experience settings, also includes user specific settings **910, 912**, etc., for at least a subset of users **904, 906**, etc., that have customized settings for one or all of the possible space experiences. In this case each of the specifications in a space experience column **902** would be similar to the specifications described above with respect to FIGS. 25 and 26, albeit having different and customized selected settings where the settings have been changed from the default settings and saved. Here, many of the user specific settings in the specifications may be similar to the default settings as a user will often times like the default settings for some experiences or phases of experiences while only wanting to customize other settings.

[0175] In at least some embodiments it is contemplated that an invite phase may include different sub-phases to indicate status of a space prior to a user actually assuming control of or claiming the space for a session. For instance, where a first space is scheduled for use at 10 AM, server **102** may be programmed to control lighting in the space to present a standard invite phase (e.g., pulsing green light) within the space until fifteen minutes prior to the scheduled time (e.g., until 9:45 AM) and then the pulsing light may change to steady state green light for the 15 minute period preceding the scheduled use to indicate to perspective user's in the area that the space is only available for a relatively short period. Then, at 10 AM, if no user has assumed control of the space, server **102** may be programmed to start the welcome phase of the scheduled experience by changing the color of light associated with the space to warm orange/yellow, fade in a programmed sound track and adjust other parameters per the experience specification. If no one arrives in and assumes control of the space within a period (e.g., 10 minutes) of the start of the scheduled session, server **102** may perform some automated process designed to free up the space for others to use. In this regard, for instance, at 10:10 AM server **102** may change the space light again to a steady green and may discontinue the sound track. This change of conditions should prompt a user that intends to take control of the space to do so. This intermediate set of conditions may be presented for another short period (e.g., 5 minutes) after which server **102** may revert back to the invite phase so that other users in the area of the space can see that the space is available for use.

[0176] In at least some cases where one or more specific users are scheduled to use a specific space during a specific period, if other users are sensed within the space and the specific users are not sensed within the space, server **102** may be programmed to change conditions within the space to indicate that someone else has reserved the space during the period. For instance, where each space user includes a personal RFID badge, smart phone, tablet, or the like from which user identity can be determined, if users other than scheduled users are in a space, the server **102** may cause lighting in the space to turn bright red to indicate that the space is reserved for use by some other user.

[0177] While the system described above is described as one wherein invite phases for spaces used for different space experiences are similar (e.g., pulsing green light to invite use), in at least some embodiments the invite phase characteristics of spaces earmarked or optimized for different space experiences may be different so that users searching for specific experiences can find optimized

space for those experiences. For instance, all spaces optimized for facilitating a rest experience may pulse green to invite use while all spaces optimized for individual focused experiences may pulse red and still other spaces optimized for dyadic activities may pulse orange.

[0178] In at least some cases it is contemplated that a user that intends to use a space may indicate a specific space experience that the user would like and server **102** may control invite phases to, in effect, highlight spaces that are optimized or that are available for the specific experience. For instance, where there are thirty different spaces in an area and five of those spaces are optimized for rest space experiences, a user may use an application on the user's tablet or smart phone device to indicate that the user want a rest space experience. Upon receiving the request for a rest experience and identifying the location of the user in the general area, server **102** may be programmed to control space affordances only in available spaces optimized for rest experiences to present invite environments. In this case the user can simply walk about the space and identify one of the spaces presenting the invite environment and can assume control or use thereof in the way that is supported by the specific system (e.g., RFID reading, entering the space and closing the door, a verbal command within the space to take control, etc.).

[0179] In cases where a space user selects a space experience for a specific space where a different available space is better suited for the experience, server **102** may present an indication that the other space is better suited for the experience. For instance, referring again to FIG. **32**, where a user uses an interface to select the "individual focus" icon for a first space that is optimized for dyadic activities and a second space in the near vicinity that is optimized for individual focus is available, server **102** may present a message via device **104** asking the user to consider the other space. The message may simply be a notice or may include a scheduling tool so that the user can select the other space for a session to reserve the space as the user moves to the location of the other space. Here, if the user schedules the second space, the color of light in the second space may be controlled to indicate that the space has been claimed and will be used during a coming session.

[0180] In some cases space experiences may be programmed to mirror the natural light patterns people experience in nature. For instance, at the beginning of a rest period, light may fade from warm orange/yellow to dark blue to mimic the changing from day light to evening light. Here, at the beginning of an emerge phase, light may fade from dark blue to warm orange/yellow to mimic a sun rise. The fading from blue to the warm color may start with one light device and spread throughout a space to further mimic a rising sun. For instance, in a case where all walls that define a space are light emissive, centrally located LEDs along a lower edge of a first wall **466** may be controlled to fade from blue to orange/yellow initially followed by the laterally located LEDs along the lower edge of the first wall **466**, followed by LEDs along the lower edge of the other two walls (e.g., **464**) adjacent first wall **466** and that are near the side edges of the other two walls adjacent wall **466** and then followed by the LEDs in wall **462**.

[0181] As another instance, where a space include light emissive walls as well as a central globe type light device **193** as in FIG. **2** where each light device is capable of generating virtually any color light, the globe light device **193** may, at the end of a rest phase, fade slowly from dark blue to a warm orange/yellow. Here, as the globe light device color fades to warm, light generated by the light emissive walls may fade similarly and uniformly from dark blue to the warm orange/yellow to simulate a sun coming up. In other cases the fading to warm orange/yellow may be non-uniform with the portions of adjacent walls fading more quickly to the warm orange/yellow color than do other portions of the walls. For example, in FIG. **2**, because globe **193** is proximate wall **222**, wall **222** or portions thereof may fade to warm orange/yellow more rapidly than portions of wall **224**. In a similar fashion, where multiple speakers are present proximate space **220**, sound may fade in and out non-uniformly to give the effect of spreading sound within the space.

[0182] In still other cases where a space includes a display screen **200** (see again FIG. **2**), a video of a sun rising or setting may be presented during a phase change and the lighting in the space may be controlled to simulate how light fills a space during such an activity.

[0183] During any of the experience phases, server **102** may be programmed to detect other intermediate triggers and to present other non-persistent characteristic sets. For instance, during the activity phase of a rest space experience, if a user stands up in an associated space (e.g., to get something out of a book bag), images from a camera in the space may be examined to determine that the user is standing and server **102** may control the space affordances in a way designed to help the user. For example, when the user stands, server **102** may change lighting of at least a subset of light devices within the space to help the user see within the relatively dark space. As another example, during individual focus activity where light is bright on a work surface but dimmed throughout the rest of a space, server **102** may increase the intensity of ambient light generally in the space if the user stands up, if a second person enters the space or if a door to the space is opened. In either of the above cases, if the intermediate condition ceases (e.g., the user sits down, the second person leaves the space, etc.), server **102** control may revert back to the phase characteristics specified for a specific space and/or a specific user.

[0184] While at least some embodiments of the present disclosure contemplate essentially completely automatic systems where space experiences are presented with little or no specific controlling activities by a user, in other cases more specific controlling actions may also operate as triggers for experiences, phase changes, etc. To this end, referring again to FIG. 2, in at least some cases a system server **102** may be programmed to examine images from camera **116** to identify controlling gestures for starting an experience, changing experience phases, etc. For instance, cameras **116** may each include a Kinect type camera and processor from Microsoft Corporation that can distinguish gestures and generate control commands associated therewith. In this case, when a user enters a space, the user may signal a desire to control and use the space during a session by performing some gesture (e.g., form a circle in the air) within the field of view of at least one of the cameras **116**. As another instance, microphone **139** may be useable to obtain verbal commands from a space user (e.g., “start rest experience”) that can be used to start an experience or change experience phases.

[0185] While the systems described above include speakers, microphones and, in some cases, space control devices **104**, in at least some other embodiments a smart phone, tablet type computing device, etc., may be used to provide those components. For instance, once a space user's personal device (see **600** in FIG. 21) is associated with a space **530**, any audio to be presented to the space user as part of a space experience may be provided via a speaker in the user's device **600**. Similarly, the microphone in the device **600** may be used to obtain verbal commands from a space user and to provide the verbal commands via a wireless access point to the system server **102** (see again FIG. 1). For instance, if a space user wants to start a rest space experience upon entering a space, after associating the user's device **600** with the space, the user may verbally request a rest session via device **600** which in turn sends the verbal request to the system server. Thus, in at least some embodiments a personal device **600** may operate as a space microphone, a space speaker, a space control device akin to control device **104** for scheduling space use, setting affordance settings and selecting space experiences, a user identifying device enabling the system server to establish the identify of a system user in a space and allocation beacon useable with access points or the like to generate data useable to triangulate the location of a user device within an area and more specifically proximate one of the spaces within an area.

[0186] Referring again to FIG. 1, in some embodiments it is contemplated that most if not all of the functions described above with respect to server **102** may be performed by a portable personal device **110** (e.g., a tablet type device) running an application to generate control signals transmitted to control system **150** for controlling space affordances per default or customized space experience specifications. Thus, for instance, when a user enters a space and the user's device is spatially associated (either automatically or via some process performed by the user) with a specific space, user's device may identify the space that it is associated in, identify affordance associated with the space, ascertain the space experience to be presented by the space or an experience requested by

the user and then transmit control signals to control system **150** for controlling the space. Any triggers sensed by sensors (e.g., **112**, **114**, **116**, etc.) within the space may cause trigger signals to be sent to the user's portable device which the device then uses to control the space affordances accordingly. Here, an interface like the interfaces shown in FIGS. **27** through **32** may be presented to the user via the user's device for controlling the affordances differently than defined in the specifications and changes to affordance control may be stored in updated specifications for subsequent use.

[0187] In at least some cases panel light devices may be replaced by display screens that can generate virtually any light color.

[0188] In some cases a welcome phase may include playing an audible welcome message to a user in a space or presenting a welcome message via a display screen if one exists within the space. The welcome message may also invite the user to take some other action to transition to the experience to be facilitated within the space. For instance, in some cases the system may require a user to place an RFID card or other device within the reading range of an RFID reader device (see **108** in FIG. **2**). Here, the welcome message may instruct the user to swipe an ID tag in front of the reader **108** to claim the space for a period.

[0189] It should be appreciated from the above description that environmental factors or conditions may be controlled as a function of various factors and inputs, some being simple actions or activities that are not dedicated to initiating control but that are used as proxies to start some control action and others that are specifically dedicated to initiating control. For instance, presence of a personal portable device within a space may operate as a control trigger in some cases while in other cases some dedicated action may be required to initiate a control activity.

[0190] While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and have been described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Thus, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the following appended claims. To apprise the public of the scope of this invention, the following claims are made:

Claims

1-20. (canceled)

21. A method for controlling affordances within a facility space wherein a plurality of affordances are located within the facility space and each affordance is controllable to change at least one environmental characteristic within the space, the method for use with a portable computing device including at least one microphone and at least one wireless transmitter, the method comprising the steps of: detecting location of the portable computing device within the facility space; upon detecting location of the portable computing device within the facility space, independent of any user activity: (i) configuring the portable computing device so that the microphone receives voice signals from a user to control at least a subset of the affordances within the facility space; (ii) receiving a voice signal from a user via the microphone; (iii) in response to receiving the voice signal, transmitting a control signal to a space controller linked to at least one of the affordances; and (iv) based on the control signal, controlling the at least one of the affordances to modify at least one environmental characteristic within the space.

22. The method of claim 21 wherein the control signal transmitted to the space controller includes the voice signal.

23. The method of claim 21 wherein the portable computing device includes a device processor that runs an environment control application, the method further including the steps of the environment control application using the received voice signal to generate the control signal as a derivative of

the voice signal.

24. The method of claim 21 wherein the portable computing device further includes at least one output device and a receiver, the method further including the steps of configuring the portable computing device so that the receiver receives control signals from a space transmitter associated with the facility space and the output device provides output to the user as a function of received control signals from the facility space transmitter.

25. The method of claim 24 wherein the at least one output device includes a speaker.

26. The method of claim 21 wherein the portable computing device includes a device processor and a memory, the memory storing environmental preferences for a device user, the method further including, subsequent to associating the portable computing device with the facility space, accessing the environmental preferences and transmitting control signals to the space controller thereby causing the space controller to control at least a subset of the environmental characteristics within the facility space in a manner that is consistent with at least a subset of the environmental preferences.

27. The method of claim 26 wherein the control signal includes the voice signal.

28. The method of claim 21 wherein the control signal includes a signal specifying how at least one of the affordances within the space is to be controlled.

29. The method of claim 21 wherein at least a subset of the affordances includes light devices.

30. The method of claim 21 wherein at least a subset of the affordances includes speaker devices.

31. The method of claim 21 wherein the portable computing device includes one of a smart phone and a tablet type computing device.

32. The method of claim 21 further including the portable computing device transmitting a location signal to the space controller, the space controller using the location signal to determine the location of the portable computing device.

33. A method for controlling affordances within a facility space wherein a plurality of affordances are located within the facility space and each affordance is controllable to change at least one environmental characteristic within the space, the space further including a space controller and a space sensor, the space sensor configured to detect at least one condition within the facility space, the method for use with a portable computing device including at least one microphone, at least one speaker, at least one wireless transmitter and a wireless receiver, the method comprising the steps of: detecting location of the portable computing device within the facility space; upon detecting location of the portable computing device within the facility space, independent of any user activity, automatically configuring the space controller for wireless communication with the portable computing device such that the at least one microphone is usable to communicate with the space controller and the space controller uses the at least one speaker as an output device to provide audible output to a portable device user; receiving a voice signal from a user via the microphone; in response to receiving the voice signal, transmitting a control signal to the space controller linked to at least one of the affordances; based on the control signal, controlling the at least one of the affordances to modify at least one environmental characteristic within the space; receiving a trigger signal from the space sensor; in response to receiving the trigger signal from the space sensor, transmitting a control signal from the space controller to the portable computing device; based on the control signal received at the portable computing device, changing audible output of the at least one speaker.

34. The method of claim 33 wherein the space controller runs an environment control program, the control signal transmitted to the space controller including the voice signal, the control programming processing the voice signal and generating control signals to control at least a subset of the environmental affordances.

35. The method of claim 33 wherein the portable computing device includes a device processor that runs an environment control application, the method further including the steps of the environment control application using the received voice signal to generate the control signal as a derivative of

the voice signal.

36. The method of claim 21 wherein the portable computing device includes a device processor and a memory, the memory storing environmental preferences for a device user, the method further including accessing the environmental preferences and transmitting control signals to the space controller thereby causing the space controller to control at least a subset of the environmental characteristics within the facility space in a manner that is consistent with at least a subset of the environmental preferences.

37. The method of claim 33 wherein the control signal includes a signal specifying how at least one of the affordances within the space is to be controlled.

38. The method of claim 33 wherein at least the affordances include at least one of light devices and speaker devices.

39. The method of claim 33 wherein the portable computing device includes one of a smart phone and a tablet type computing device.

40. A method for controlling affordances within a facility space wherein a plurality of affordances are located within the facility space and each affordance is controllable to change at least one environmental characteristic within the space, the space further including a space controller and a space sensor, the space sensor configured to detect at least one condition within the facility space, the method for use with a portable computing device including at least one microphone, at least one speaker, at least one wireless transmitter and a wireless receiver, the method comprising the steps of: detecting location of the portable computing device within the facility space; and upon detecting location of the portable computing device within the facility space, independent of any user activity, automatically configuring the space controller for wireless communication with the portable computing device such that the at least one microphone is usable to communicate with the space controller and the space controller uses the at least one speaker as an output device to provide audible output to a portable device user.
