

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250251654

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

TIAN; Xintuan et al.

LASER SOURCE AND LASER PROJECTION APPARATUS

Abstract

A laser source includes a laser source housing, laser arrays and a beam path assembly. The laser source housing includes beam outlet and accommodating openings disposed at a same side wall or different side walls of the laser source housing. The laser arrays are respectively disposed in the accommodating openings. A laser array is configured to emit laser beams into the laser source housing. A laser-exit surface of the laser array includes a plurality of laser-exit regions configured to emit laser beams of multiple colors. The beam path assembly including a plurality of combining lens groups is disposed inside the laser source housing. The combining lens groups and the laser arrays are in one-to-one correspondence. A combining lens group is configured to combine laser beams of multiple colors emitted by a corresponding laser array, and combined laser beams are not located in beam output paths of other combining lens groups.

Inventors: TIAN; Xintuan (Qingdao City, CN), ZHOU; Boyu (Qingdao City, CN)

Applicant: Hisense Laser Display Co., Ltd (Qingdao City, CN)

Family ID: 79167714

Assignee: Hisense Laser Display Co., Ltd (Qingdao City, CN)

Appl. No.: 19/187444

Filed: April 23, 2025

Foreign Application Priority Data

CN	201911024312.5	Oct. 25, 2019
CN	201911024401.X	Oct. 25, 2019
CN	201911025064.6	Oct. 25, 2019

Related U.S. Application Data

parent US continuation 17481800 20210922 parent-grant-document US 12306519 child US 19187444

parent WO continuation-in-part PCT/CN2020/121934 20201019 PENDING child US 17481800
parent WO continuation-in-part PCT/CN2020/121935 20201019 PENDING child US
PCT/CN2020/121934
parent WO continuation-in-part PCT/CN2020/121936 20201019 PENDING child US
PCT/CN2020/121935

Publication Classification

Int. Cl.: G03B21/20 (20060101); G03B33/12 (20060101)

U.S. Cl.:

CPC G03B21/2033 (20130101); G03B21/2066 (20130101); G03B21/208 (20130101);
G03B33/12 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 17/481,800, filed on 22 Sep. 2021, pending, which is a continuation-in-part of International Application No. PCT/CN2020/121934, with an international filing date of 19 Oct. 2020, and claims the priority to Chinese Patent Application No. 201911025064.6, filed 25 Oct. 2019; and this application is a continuation-in-part of International Application No. PCT/CN2020/121935, with an international filing date of 19 Oct. 2020, which claims the priority to Chinese Patent Application No. 201911024312.5, filed 25 Oct. 2019; and this application is a continuation-in-part of International Application No. PCT/CN2020/121936, with an international filing date of 19 Oct. 2020, which claims the priority to Chinese Patent Application No. 201911024401.X, filed 25 Oct. 2019. The entire contents of the foregoing applications are hereby incorporated by reference herein.

TECHNICAL FIELD

[0002] The present disclosure relates to the field of laser projection technologies, and in particular, to a laser source and a laser projection apparatus.

BACKGROUND

[0003] A laser source has advantages of good monochromaticity, high luminance, and long service life. Therefore, the laser source is an ideal light source, and is widely used in laser projection apparatuses such as laser televisions and laser projectors. The laser source is an important component of laser projection apparatuses such as laser televisions and laser projectors, and is used to provide illumination beams.

SUMMARY

[0004] In an aspect, a laser source is provided. The laser source includes a laser source housing, a plurality of laser arrays and a beam path assembly. The laser source housing includes a beam outlet and a plurality of accommodating openings. The plurality of accommodating openings are disposed at a same side wall or different side walls of the laser source housing. The plurality of laser arrays are respectively disposed in the plurality of accommodating openings. A laser array of the plurality of laser arrays is configured to emit laser beams into the laser source housing. A laser-exit surface of the laser array includes a plurality of laser-exit regions. The plurality of laser-exit regions are configured to emit laser beams of multiple colors. The beam path assembly is disposed inside the laser source housing. The beam path assembly is configured to combine the laser beams of the multiple colors emitted by the laser array, and make the combined laser beams exit toward the

beam outlet. The beam path assembly includes a plurality of combining lens groups. The plurality of combining lens groups and the plurality of laser arrays are in one-to-one correspondence. A combining lens group of the plurality of combining lens groups is configured to combine laser beams of multiple colors emitted by a laser array corresponding to the combining lens group, and laser beams combined by the combining lens group are not located in beam output paths of other combining lens groups.

[0005] In another aspect, a laser projection apparatus is provided. The laser projection apparatus includes a laser source, an optical engine and a projection lens. The laser source is configured to provide illumination beams, and the laser source is the above laser source. The optical engine is configured to modulate the illumination beams with image display signals to obtain projection beams. The projection lens is configured to project the projection beams on a screen or a wall for imaging.

[0006] In yet aspect, a laser source is provided. The laser source includes a laser source housing, a plurality of laser arrays and a plurality of combining lens groups. The laser source housing includes a beam outlet and a plurality of accommodating openings. The plurality of accommodating openings are disposed at a same side wall or different side walls of the laser source housing. The plurality of laser arrays are respectively disposed in the plurality of accommodating openings. A laser-exit surface of a laser array of the plurality of laser arrays includes a plurality of laser-exit regions. The plurality of laser-exit regions are configured to emit laser beams of multiple colors. The plurality of combining lens groups and the plurality of laser arrays are in one-to-one correspondence. A combining lens group of the plurality of combining lens groups is configured to combine laser beams of multiple colors emitted by a laser array corresponding to the combining lens group, and make combined laser beams exit toward a direction of the beam outlet. The laser beams of the multiple colors emitted by the plurality of laser-exit regions are linearly polarized lights. Polarization directions of the laser beams of the multiple colors emitted by the plurality of laser-exit regions are different. A wave plate is disposed between the combining lens group and a laser-exit region of the laser array corresponding to the combining lens group. The wave plate is configured to change a polarization direction of a laser beam emitted by the laser-exit region, and then incident a changed laser beam to the combining lens group.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] In order to describe technical solutions in the present disclosure more clearly, accompanying drawings to be used in some embodiments of the present disclosure will be introduced briefly below. Obviously, the accompanying drawings to be described below are merely accompanying drawings of some embodiments of the present disclosure, and a person of ordinary skill in the art may obtain other drawings according to these drawings. In addition, the accompanying drawings in the following description may be regarded as schematic diagrams, and are not limitations on actual sizes of products, actual processes of methods and actual timings of signals to which the embodiments of the present disclosure relate.

[0008] FIG. 1 is a diagram showing a structure of a laser projection apparatus, in accordance with some embodiments;

[0009] FIG. 2 is a diagram showing a structure of a laser source, an optical engine, and a projection lens in a laser projection apparatus, in accordance with some embodiments;

[0010] FIG. 3 is a diagram showing a simplified structure of a laser source, an optical engine, and a projection lens in a laser projection apparatus, in accordance with some embodiments;

[0011] FIG. 4 is a schematic diagram showing a structure of a beam path in a laser projection apparatus, in accordance with some embodiments;

[0012] FIG. 5 is a diagram showing an arrangement of micromirrors in a digital micromirror device, in accordance with some embodiments;

[0013] FIG. 6 is a schematic diagram showing a swing position of a micromirror in the digital micromirror device shown in FIG. 5;

[0014] FIG. 7 is a schematic diagram showing operation of micromirrors, in accordance with some embodiments;

[0015] FIG. 8 is a perspective view of a laser source, in accordance with some embodiments;

[0016] FIG. 9 is a perspective view of the laser source in FIG. 8 with a radiator removed;

[0017] FIG. 10 is a diagram showing an internal structure of a laser source, in accordance with some embodiments;

[0018] FIG. 11 is a diagram showing a beam path of a laser source, in accordance with some embodiments;

[0019] FIG. 12A is a diagram showing a structure of a laser array in a laser source, in accordance with some embodiments;

[0020] FIG. 12B is a diagram showing a circuit package structure of the laser array in FIG. 12A;

[0021] FIG. 13 is a diagram showing a structure of a laser source when a first wave plate is used, in accordance with some embodiments;

[0022] FIG. 14 is a diagram showing a structure of a laser source when a second wave plate and a third wave plate are used, in accordance with some embodiments;

[0023] FIG. 15A is a diagram showing another beam path of a laser source, in accordance with some embodiments;

[0024] FIG. 15B is a schematic diagram from another angle of FIG. 15A;

[0025] FIG. 16A is a diagram showing a structure of a combining lens in a laser source, in accordance with some embodiments;

[0026] FIG. 16B is a diagram showing a structure of another combining lens in a laser source, in accordance with some embodiments;

[0027] FIG. 17 is a perspective view of another laser source, in accordance with some embodiments;

[0028] FIG. 18 is a diagram showing an internal structure of another laser source, in accordance with some embodiments;

[0029] FIG. 19 is a diagram showing a beam path of another laser source, in accordance with some embodiments;

[0030] FIG. 20 is a diagram showing another beam path of another laser source, in accordance with some embodiments;

[0031] FIG. 21 is a perspective view of yet another laser source, in accordance with some embodiments;

[0032] FIG. 22 is a perspective view of the laser source in FIG. 21 after being turned over;

[0033] FIG. 23 is a diagram showing a beam path of yet another laser source, in accordance with some embodiments;

[0034] FIG. 24 is a diagram showing another beam path of yet another laser source, in accordance with some embodiments;

[0035] FIG. 25A is a diagram showing yet another beam path of yet another laser source, in accordance with some embodiments; and

[0036] FIG. 25B is a schematic diagram from another angle of FIG. 25A.

DETAILED DESCRIPTION

[0037] Technical solutions in some embodiments of the present disclosure will be described clearly and completely below with reference to the accompanying drawings. Obviously, the described embodiments are merely some but not all embodiments of the present disclosure. All other embodiments obtained on a basis of the embodiments of the present disclosure by a person of ordinary skill in the art shall be included in the protection scope of the present disclosure.

[0038] Unless the context requires otherwise, throughout the specification and the claims, the term “comprise” and other forms thereof such as the third-person singular form “comprises” and the present participle form “comprising” are construed as being open and inclusive, meaning “including, but not limited to”.

[0039] In the description, the terms such as “one embodiment”, “some embodiments”, “exemplary embodiments”, “example”, “specific example” or “some examples” are intended to indicate that specific features, structures, materials or characteristics related to the embodiment(s) or example(s) are included in at least one embodiment or example of the present disclosure. Schematic representations of the above terms do not necessarily refer to the same embodiment(s) or example(s). In addition, the specific features, structures, materials, or characteristics described herein may be included in any one or more embodiments or examples in any suitable manner.

[0040] Hereinafter, the terms “first” and “second” are used for descriptive purposes only, and are not to be construed as indicating or implying the relative importance or implicitly indicating the number of indicated technical features. Thus, features defined with “first” and “second” may explicitly or implicitly include one or more of the features. In the description of the embodiments of the present disclosure, the term “a plurality of” means two or more unless otherwise specified.

[0041] In the description of some embodiments, the terms “coupled” and “connected” and their extensions may be used. For example, the term “connected” may be used in the description of some embodiments to indicate that two or more components are in direct physical or electrical contact with each other. For another example, the term “coupled” may be used in the description of some embodiments to indicate that two or more components are in direct physical or electrical contact. However, the term “coupled” or “communicatively coupled” may also mean that two or more components are not in direct contact with each other, but still cooperate or interact with each other. The embodiments disclosed herein are not necessarily limited to the contents herein.

[0042] The phrase “at least one of A, B and C” has a same meaning as the phrase “at least one of A, B or C”, and they both include the following combinations of A, B and C: only A, only B, only C, a combination of A and B, a combination of A and C, a combination of B and C, and a combination of A, B and C.

[0043] The phrase “A and/or B” includes the following three combinations: only A, only B, and a combination of A and B.

[0044] As used herein, the term “if” is optionally construed as “when” or “in a case where” or “in response to determining that” or “in response to detecting”, depending on the context. Similarly, the phrase “if it is determined that” or “if [a stated condition or event] is detected” is optionally construed as “in a case where it is determined that” or “in response to determining that” or “in a case where [the stated condition or event] is detected” or “in response to detecting [stated condition or event]”, depending on the context.

[0045] The use of the phrase “applicable to” or “configured to” herein means an open and inclusive expression, which does not exclude devices that are applicable to or configured to perform additional tasks or steps.

[0046] In addition, the use of the phrase “based on” is meant to be open and inclusive, since a process, step, calculation or other action that is “based on” one or more of the stated conditions or values may, in practice, be based on additional conditions or values exceeding those stated.

[0047] The term “about”, “substantially” or “approximately” as used herein includes a stated value and an average value within an acceptable range of deviation of a particular value. The acceptable range of deviation is determined by a person of ordinary skill in the art, considering measurement in question and errors associated with measurement of a particular quantity (i.e., limitations of a measurement system).

[0048] Terms such as “parallel”, “perpendicular”, or “equal” as used herein includes a stated condition and a condition similar to the stated condition. A range of the similar condition is within an acceptable deviation range, and the acceptable deviation range is determined by a person of

ordinary skill in the art, considering measurement in question and errors associated with measurement of a particular quantity (i.e., limitations of a measurement system). For example, the term “parallel” includes absolute parallel and approximate parallel, and the acceptable deviation range for the approximate parallel may be, for example, a deviation within 5°. The term “perpendicular” includes absolute vertical and approximate vertical, and the acceptable deviation range of the approximate vertical may also be, for example, a deviation within 5°. The term “equal” includes absolute equality and approximate equality, and the acceptable deviation range of the approximate equality may be that, for example, a difference between the two that are equal is less than or equal to 5% of either of the two.

[0049] Some embodiments of the present disclosure provide a laser projection apparatus. As shown in FIG. 1, the laser projection apparatus **10** includes a housing **101** (only part of the housing **101** is shown in FIG. 1), and a laser source **100**, an optical engine **200**, and a projection lens **300** that are assembled in the housing **101**. The laser source **100** is configured to provide illumination beams (laser beams). The optical engine **200** is configured to modulate the illumination beams provided by the laser source **100** with image display signals to obtain projection beams. The projection lens **300** is configured to project the projection beams on a screen or a wall for imaging. In some embodiments, the laser projection apparatus **10** further includes a screen. The screen is disposed in a laser-exit path of the projection lens **300**, and the projection beams emitted by the projection lens **300** form an image on the screen.

[0050] The laser source **100**, the optical engine **200**, and the projection lens **300** are sequentially connected in a propagation direction of the beams, and are each wrapped by a corresponding housing. The housings of the laser source **100**, the optical engine **200** and the projection lens **300** support their corresponding optical components respectively and make the optical components meet certain sealing or airtight requirements. For example, the laser source **100** is hermetically sealed through its corresponding housing, which may well solve a light attenuation problem of the laser source **100**.

[0051] One end of the optical engine **200** is connected to the projection lens **300**, and the optical engine **200** and the projection lens **300** are arranged in a direction of the projection beams of the laser projection apparatus **10** (refer to the N direction shown in FIG. 2). The other end of the optical engine **200** is connected to the laser source **100**. In the example, as shown in FIG. 2, the laser source **100**, the optical engine **200**, and the projection lens **300** are connected in an “L” shape. That is, the direction of the projection beams of the laser projection apparatus **10** (refer to the N direction shown in FIG. 2) is substantially perpendicular to a direction of the illumination beams of the laser projection apparatus **10** (refer to the M direction shown in FIG. 2). On one hand, such connection structure may adapt to characteristics of a beam path of a reflective light valve in the optical engine **200**, and on another hand, it is also conducive to shortening a length of a beam path in a one-dimensional direction, which is helpful for structural arrangement of the laser projection apparatus **10**. For example, in a case where the laser source **100**, the optical engine **200**, and the projection lens **300** are disposed in the one-dimension direction (e.g., the M direction), a length of a beam path in the direction is long, which is not conducive to the structural arrangement of the laser projection apparatus **10**.

[0052] In some embodiments, referring to FIG. 3, the laser source **100** may include three laser arrays. The three laser arrays may be a red laser array **130**, a green laser array **120**, and a blue laser array **110** respectively. That is, the laser source **100** is a tri-color laser source, but is not limited thereto. The three laser arrays may also all be blue laser arrays **110**, or two blue laser arrays **110** and one red laser array **130**.

[0053] In some embodiments, the laser source **100** may further include two laser arrays or one laser array (i.e., a mono-color laser source). The two laser arrays may be the blue laser array **110** and the red laser array **130**, that is, the laser source **100** is a dual-color laser source. The two laser arrays may also both be blue laser arrays **110**. In the mono-color laser source, the one laser array may be

the blue laser array **110**.

[0054] The illumination beams emitted by the laser source **100** enter the optical engine **200**. Referring to FIGS. **3** and **4**, the optical engine **200** may include a light pipe **210**, a lens assembly **220**, a reflector **230**, a digital micromirror device (DMD) **240** and a prism assembly **250**. The light pipe **210** may receive the illumination beams provided by the laser source **100** and homogenize the illumination beams. The lens assembly **220** may first collimate the illumination beams homogenized by the light pipe **210**, and then converge the collimated illumination beams and emit the converged illumination beams to the reflector **230**. The reflector **230** may reflect the illumination beams that are first collimated and then converged by the lens assembly **220** to the prism assembly **250**. The prism assembly **250** reflects the illumination beams reflected by the reflector **230** to the DMD **240**. The DMD **240** modulates the illumination beams to obtain the projection beams, and reflects the projection beams obtained by modulating the illumination beams into the projection lens **300**.

[0055] In the optical engine **200**, the DMD **240** is a core component, which plays a role of modulating the illumination beams provided by the laser source **100** through the image display signals. That is, the DMD **240** controls the projection beams to display different colors and luminance according to different pixels of an image to be displayed, so as to finally form an optical image. Therefore, the DMD **240** is also referred to as an optical modulator or a light valve. Depending on whether the optical modulator (or the light valve) transmits or reflects the illumination beams, the optical modulator (or the light valve) may be classified as a transmissive optical modulator (or light valve) or a reflective optical modulator (or light valve). For example, the DMD **240** shown in FIG. **4** reflects the illumination beams, and thus it is a reflective optical modulator. A liquid crystal light valve transmits the illumination beams, and thus it is a transmissive optical modulator. In addition, according to the number of the optical modulators (or the light valves) used in the optical engine, the optical engine may be classified as a single-chip system, a double-chip system, or a three-chip system. For example, only one DMD **240** is used in the optical engine **200** shown in FIG. **4**, and thus the optical engine **200** may be referred to as a single-chip system. In a case where three digital micromirror devices are used, the optical engine **200** may be referred to as a three-chip system.

[0056] The digital micromirror device **240** is applied to a digital light processing (DLP) projection architecture. The optical engine **200** shown in FIG. **4** uses the DLP projection architecture. As shown in FIG. **5**, the digital micromirror device **240** includes thousands of micromirrors **2401** that may be individually driven to rotate. These micromirrors **2401** are arranged in an array, and each micromirror **2401** corresponds to one pixel in the image to be displayed. As shown in FIG. **6**, in the DLP projection architecture, each micromirror **2401** is equivalent to a digital switch. The micromirror may swing by a range of plus or minus 12 degrees (i.e., $\pm 12^\circ$) or a range of plus or minus 17 degrees (i.e., $\pm 17^\circ$) due to action of an external force.

[0057] As shown in FIG. **7**, a laser beam reflected by the micromirror **2401** at a negative deflection angle is referred to as an OFF laser beam, and the OFF laser beam is an ineffective laser beam, and which is usually irradiated on the housing **101** of the laser projection apparatus **10** and the housing of the optical engine **200**, or is absorbed by a laser absorption unit **400**. A laser beam reflected by the micromirror **2401** at a positive deflection angle is referred to as an ON laser beam. The ON laser beam is an effective beam that enters the projection lens **300** at a positive deflection angle after the micromirror **2401** on a surface of the DMD **240** receives irradiation of the illumination beams, and is used to project an image. An ON state of the micromirror **2401** is a state that the micromirror **2401** is in and may be maintained when the illumination beams emitted by the laser source **100** may enter the projection lens **300** after being reflected by the micromirror **2401**. That is, the micromirror **2401** is in a state of a positive deflection angle. An OFF state of the micromirror **2401** is a state that the micromirror **2401** is in and may be maintained when the illumination beams emitted by the laser source **100** does not enter the projection lens **300** after being reflected by the

micromirror **2401**. That is, the micromirror **2401** is in a state of a negative deflection angle.

[0058] For example, for a micromirror **2401** with a deflection angle of $\pm 12^\circ$, a state at $+12^\circ$ is the ON state, and a state at -12° is the OFF state. For a deflection angle between -12° and $+12^\circ$, it is not used in practice, and actual operation states of the micromirror **2401** are only the ON state and the OFF state. For a micromirror **2401** with a deflection angle of $\pm 17^\circ$, a state at $+17^\circ$ is the ON state, and a state at -17° is the OFF state. The image display signals are converted into digital codes such as 0 or 1 after being processed, and these digital codes may drive the micromirrors **2401** to swing.

[0059] In a display cycle of a frame image, part or all of the micromirrors **2401** are switched once between the ON state and the OFF state, so that gray scales of pixels in the frame image are achieved according to durations of the micromirrors **2401** in the ON state and the OFF state. For example, in a case where the pixels have 256 gray scales from 0 to 255, micromirrors corresponding to a gray scale 0 are each in the OFF state in an entire display cycle of the frame image, micromirrors corresponding to a gray scale 255 are each in the ON state in the entire display cycle of the frame image, and micromirrors corresponding to a gray scale 127 are each in the ON state for a half of time and in the OFF state for the other half of time in the display cycle of the frame image. Therefore, by controlling a state that each micromirror in the DMD **240** is in and a duration of each state in the display cycle of the frame image through the image display signals, luminance (the gray scale) of a pixel corresponding to the micromirror **2401** may be controlled, and a purpose of modulating the illumination beams projected onto the DMD **240** may be achieved.

[0060] Referring to FIGS. **3** and **4**, the light pipe **210**, the lens assembly **220** and the reflector **230** in front of the DMD **240** form an illumination path. After passing through the illumination path, the illumination beams emitted by the laser source **100** are made to conform to a beam size and an incident angle required by the DMD **240**.

[0061] As shown in FIG. **3**, the projection lens **300** includes a combination of a plurality of lenses, which are usually divided by group, and are divided into a three-segment combination including a front group, a middle group and a rear group, or a two-segment combination including a front group and a rear group. The front group is a lens group proximate to a laser-exit side of the laser projection apparatus (a left side shown in FIG. **3**), and the rear group is a lens group proximate to a laser-exit side of the optical engine **200** (a right side shown in FIG. **3**). The projection lens **300** may be a zoom projection lens, or a prime adjustable-focus projection lens, or a prime projection lens. In some embodiments, the laser projection apparatus is an ultra-short-focus projection apparatus. The projection lens **300** is an ultra-short-focus projection lens, and a projection ratio of the projection lens **300** is usually less than 0.3, such as 0.24.

[0062] The laser source **100** according to some embodiments of the present disclosure will be described in detail below.

[0063] In some embodiments, as shown in FIGS. **8** and **9**, the laser source **100** includes a laser source housing **11**, two laser arrays **12** and a beam path assembly **13** (refer to FIGS. **10** and **11**).

[0064] The laser source housing **11** includes a first side wall **113** and a second side wall **114** perpendicular to each other. The first side wall **113** includes two accommodating openings **111**, and the second side wall **114** includes a beam outlet **112**. The two accommodating openings **111** penetrate the first side wall **113**, and the beam outlet **112** penetrates the second side wall **114**. In some embodiments, a direction of the two accommodating openings **111** penetrating the first side wall **113** is substantially perpendicular to a direction of the beam outlet **112** penetrating the second side wall **114**.

[0065] The two laser arrays **12** are respectively installed in the two accommodating openings **111**, and each laser array **12** emits laser beams into the laser source housing **11**. It can be understood that, arrangement positions of the plurality of accommodating openings **111** on side walls of the laser source housing **11** determine arrangement positions of the plurality of laser arrays **12**. The present disclosure does not limit the arrangement positions of the plurality of accommodating

openings **111** on the side walls.

[0066] In some embodiments, as shown in FIG. **9**, the plurality of accommodating openings **111** are arranged in a direction perpendicular to the second side wall **114**. For example, the plurality of accommodating openings **111** may be arranged substantially in a direction parallel to a center line of the beam outlet **112**. A direction of the center line of the beam outlet **112** is substantially parallel to the direction M of the illumination beams. In this way, a dimension of the laser source **100** in a direction parallel to the second side wall **114** (i.e., the direction F in FIG. **9**) is small. The direction parallel to the second side wall **114** is substantially parallel to the direction N of the projection beams.

[0067] It can be understood that, the larger the number of the laser arrays **12** is, the larger luminance of the laser source **100** is. The number of the laser arrays **12** may be one, two, three, four or more. The number of the laser arrays **12** may be determined according to luminance required by the laser source **100**, which is not limited in the present disclosure. For convenience of description, some embodiments are mainly described by taking an example in which the laser source **100** includes two laser arrays **12**, but this is not be understood as a limitation of the present disclosure.

[0068] In some embodiments, the laser array **12** may be a multi-chip laser diode (MCL) assembly. The MCL assembly includes an MCL device and a driving circuit board disposed on a periphery of the MCL device. The MCL device encapsulates a plurality of lamp beads on a substrate to form an area laser source. As shown in FIG. **12A**, the laser array **12** includes a metal substrate **124**. A plurality of lamp beads are encapsulated on the metal substrate **124**. The plurality of lamp beads may be connected in series for driving, or may be connected in parallel in rows or columns for driving. The plurality of lamp beads may be arranged in a 4×6 array, or may be arranged in other arrays, such as a 3×5 array, a 2×7 array, a 2×6 array, or a 4×5 array. Overall luminous power of lamp beads with different numbers of arrays is different. There are pins **125** protruding from two sides of the metal substrate **124**. Each pin is coupled to an electrical signal to drive the lamp beads to emit laser beams.

[0069] As shown in FIG. **12B**, the laser array **12** further includes a driving circuit board **127** disposed on the periphery of the MCL device. FIG. **12B** shows a back surface of the laser array **12** in FIG. **12A**. The driving circuit board **127** has a flat-plate structure, and the driving circuit board **127** is substantially parallel to or in a same plane as a laser-exit surface of the MCL device. There is at least one pin **125** on each of two opposite sides of the MCL device. Each pin **125** is soldered onto or plugged into the driving circuit board **127**, so that the MCL device is electrically connected to the driving circuit board **127**. The driving circuit board **127** is configured to provide a driving signal to the MCL device.

[0070] In some embodiments, the driving circuit board is integrally formed and surrounds an outside of the metal substrate **124** of the MCL device. In some other embodiments, the driving circuit board includes two separate circuit boards. That is, the driving circuit board **127** includes a first portion **1271** and a second portion **1272**, and the MCL device is enclosed by the two portions. In this way, the laser array **12** is also basically a flat-plate structure, which facilitates the installation, and saves space, and is also conducive to achieving miniaturization of the laser source apparatus. The plurality of accommodating openings **111** are provided on a same side wall of the laser source housing **11**, and the plurality of laser arrays **12** are respectively installed in the plurality of accommodating openings **111**, so that the driving circuit boards **127** of the plurality of laser arrays **12** (as shown in FIG. **9**) may be set to be coplanar. In this way, one radiator **16** may be used to cool the plurality of laser arrays **12** simultaneously (as shown in FIG. **8**). Therefore, in a case where the laser source **100** includes the radiator **16**, the cost of the laser source **100** can be reduced, the structural complexity of the laser source **100** can be reduced, and a volume of the laser source **100** can be reduced.

[0071] In some embodiments, as shown in FIG. **12A**, a laser-exit surface of each laser array **12** includes a plurality of laser-exit regions. The plurality of laser-exit regions are configured to emit

laser beams of multiple colors. Referring to FIGS. **10** and **11**, the beam path assembly **13** is able to combine the laser beams of multiple colors emitted by the two laser arrays **12**, and emit the combined laser beams toward the beam outlet **112**.

[0072] The number of the plurality of laser-exit regions included in the laser-exit surface of a laser array **12** is equal to the number of colors of the laser beams emitted by the laser-exit surface of the laser array **12**, and each laser-exit region emits a laser beam of one color. In some embodiments, the laser-exit surface of the laser array **12** may include two laser-exit regions, three laser-exit regions, or four laser-exit regions, which are not limited in the present disclosure.

[0073] In some embodiments, as shown in FIG. **12A**, the laser-exit surface of each laser array **12** includes a first laser-exit region **121**, a second laser-exit region **122**, and a third laser-exit region **123**. In FIG. **12A**, for convenience of distinction, each laser-exit region is separated by a dotted line. The first laser-exit region **121** is configured to emit a first color laser beam. The second laser-exit region **122** is configured to emit a second color laser beam. The third laser-exit region **123** is configured to emit a third color laser beam. The first color laser beam, the second color laser beam, and the third color laser beam are combined to form a white laser beam. Therefore, there is no need to provide a phosphor wheel in the laser source **100**. In a case where one or more laser arrays included in a laser source can only produce laser beams of one or two colors, it is necessary to use the laser beams of the existing color to excite the phosphor wheel to generate fluorescence beams of other colors, so that the laser beams and the fluorescence beams together form white beams. As a result, in some embodiments of the present disclosure, the structure of the laser source **100** can be simplified, and the volume of the laser source **100** can be reduced.

[0074] The present disclosure does not limit the colors of the first color laser beam, the second color laser beam, and the third color laser beam, as long as the first color laser beam, the second color laser beam, and the third color laser beam can be mixed to form the white laser beam.

[0075] In some embodiments, as shown in FIG. **12A**, the first color laser beam emitted by the first laser-exit region **121** is a blue laser beam, the second color laser beam emitted by the second laser-exit region **122** is a green laser beam, and the third color laser beam emitted by the third laser-exit region **123** is a red laser beam.

[0076] In some other embodiments, the first color laser beam emitted by the first laser-exit region **121** is a cyan laser beam, the second color laser beam emitted by the second laser-exit region **122** is a yellow laser beam, and the third color laser beam emitted by the third laser-exit region **123** is a magenta laser beam.

[0077] The first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** each may correspond to one lamp bead in the laser array **12**, or may correspond to a row of lamp beads in the laser array **12**, or may also correspond to multiple rows of lamp beads in the laser array **12**, which is not limited in the present disclosure. In some embodiments, as shown in FIG. **12A**, the first laser-exit region **121** and the second laser-exit region **122** each correspond to a row of lamp beads in the laser array **12**, and the third laser-exit region **123** corresponds to two rows of lamp beads in the laser array **12**. Each row of lamp beads includes six lamp beads.

[0078] In some embodiments, the beam path assembly **13** includes a plurality of combining lens groups **131**. The number of the plurality of combining lens groups **131** is the same as the number of the plurality of laser arrays **12**, and the plurality of combining lens groups **131** and the plurality of laser arrays **12** are in one-to-one correspondence. In a case where the laser source **100** includes only one laser array **12**, the laser source **100** may include only one combining lens group.

[0079] As shown in FIGS. **11**, **15A**, and **15B**, the beam path assembly **13** includes two combining lens groups **131**. The two combining lens groups **131** and two laser arrays **12** are arranged in one-to-one correspondence. The two combining lens groups **131** are configured to combine laser beams of multiple colors of a corresponding laser array **12**, and emit the laser beams exited from the two combining lens groups **131** toward the beam outlet **112**. In this way, the laser beams of multiple colors emitted by each laser array **12** are combined through a corresponding combining lens group

131, so that a structure of the beam path assembly **13** is simple and the cost is low. Moreover, each combining lens group **131** may be proximate to the corresponding laser array **12**, so that the laser beams emitted by the laser array **12** have a small beam spot when entering the combining lens group **131**, so as to avoid a problem of a large size of the combining lens group **131** due to a large beam spot of the laser beams emitted by the laser array **12** when entering the combining lens group **131**. As a result, the volume of the laser source **100** is made small, and the structure complexity is made low.

[0080] In order to enable a combining lens group **131** to combine the laser beams of multiple colors emitted by a corresponding laser array **12**, and to make the combined laser beams to be emitted toward the beam outlet **112**, in some embodiments, as shown in FIG. **11**, the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** are sequentially arranged in a direction perpendicular to an arrangement direction of the plurality of laser arrays **12** from an end away from the beam outlet **112** to an end proximate to the beam outlet **112**; alternatively, as shown in FIGS. **15A** and **15B**, the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** are sequentially arranged in an arrangement direction of the plurality of laser arrays **12** from an end away from the beam outlet **112** to an end proximate to the beam outlet **112** (i.e., they are arranged in a direction from left to right in FIG. **15B**).

[0081] As shown in FIGS. **8** and **11**, in a case where the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** are sequentially arranged in the direction perpendicular to the arrangement direction of the plurality of laser arrays **12** from the end away from the beam outlet **112** to the end proximate to the beam outlet **112**, an arrangement direction of the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** may not coincide with the direction of the center line of the beam outlet **112** (i.e., the direction M of the illuminating beams), but may be perpendicular to the direction of the center line of the beam outlet **112**.

[0082] In this case, after the combining lens group **131** combines the laser beams of multiple colors emitted by a corresponding laser array **12**, the combined laser beams can exit from the beam outlet **112** after using a reflector **132** to change a propagation direction of the combined laser beams; alternatively, the reflector **132** is firstly used to change the propagation direction of the laser beams of multiple colors, and then the combining lens group **131** is used to combine the laser beams of multiple colors emitted by a corresponding laser array **12**, so that the combined laser beams can exit from the beam outlet **112**. The reflector **132** will be described later.

[0083] However, as shown in FIGS. **15A** and **15B**, in a case where the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** are sequentially arranged in the arrangement direction of the plurality of laser arrays **12** from the end away from the beam outlet **112** to the end proximate to the beam outlet **112**, the arrangement direction of the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** coincides with the direction of the center line of the beam outlet **112** (i.e., the direction M of the illumination beams).

[0084] It can be seen therefrom that, the laser source **100** shown in FIG. **11** needs to use additional reflectors **132**, but a dimension of the laser source **100** in the arrangement direction of the plurality of laser arrays **12** is small. Although a dimension of the laser source **100** shown in FIG. **15A** in the arrangement direction of the plurality of laser arrays **12** is large, there is no need to use additional reflectors **132**.

[0085] In some embodiments, the combining lens group **131** may include three combining lenses, but this is not to be understood as a limitation of the present disclosure.

[0086] In some embodiments, the first laser-exit region **121** is configured to emit the first color laser beam, the second laser-exit region **122** is configured to emit the second color laser beam, and the third laser-exit region **123** is configured to emit the third color laser beam. Each combining lens group **131** includes a first combining lens **1311**, a second combining lens **1312**, and a third combining lens **1313**. The first combining lens **1311** reflects the first color laser beam. The second

combining lens **1312** reflects the second color laser beam and transmits the first color laser beam reflected by the first combining lens **1311**. The third combining lens **1313** reflects the third color laser beam, and transmits the first color laser beam reflected by the first combining lens **1311** and transmitted by the second combining lens **1312**, and the second color laser beam reflected by the second combining lens **1312**.

[0087] In some embodiments, as shown in FIG. **15B**, the first combining lens **1311** is located at a laser-exit side of the first laser-exit region **121**. The second combining lens **1312** is located at laser-exit sides of the second laser-exit region **122** and the first combining lens **1311**. The third combining lens **1313** is located at laser-exit sides of the third combining lens **123**, the first combining lens **1311** and the second combining lens **1312**.

[0088] As shown in FIG. **15B**, the first combining lens **1311**, the second combining lens **1312**, and the third combining lens **1313** of each combining lens group **131** are parallel to each other. In some embodiments, a reflection portion of the first combining lens **1311**, a reflection portion of the second combining lens **1312**, and a reflection portion of the third combining lens **1313** of each combining lens group **131** are parallel to each other.

[0089] As shown in FIG. **13**, an optical axis (e.g., the first optical axis O.sub.1) of the first color laser beam reflected by the first combining lens **1311**, an optical axis (e.g., the second optical axis O.sub.2) of the second color laser beam reflected by the second combining lens **1312** and an optical axis (e.g., the third optical axis O.sub.3) of the third color laser beam reflected by the third combining lens **1313** are approximately collinear. In this way, the laser beams of multiple colors emitted by the laser array **12** can be combined by the combining lens group **131**. The first combining lens **1311**, the second combining lens **1312**, and the third combining lens **1313** constitute a combining lens group **131** combining laser beams of three colors emitted by the laser array **12**. A structure of the combining lens group **131** is simple and easy to be implemented.

[0090] In the above embodiments, it can be understood that, it is difficult to ensure that the first optical axis O.sub.1, the second optical axis O.sub.2, and the third optical axis O.sub.3 are absolutely collinear in the actual processing and installation of the laser source **100**. Therefore, the “substantially collinear” of the first optical axis O.sub.1, the second optical axis O.sub.2 and the third optical axis O.sub.3 described in some embodiments of the present disclosure will be understood as “collinear or approximately collinear”.

[0091] In some embodiments, the first optical axis O.sub.1, the second optical axis O.sub.2 and the third optical axis O.sub.3 are substantially collinear, meaning that any two optical axes of the first optical axis O.sub.1, the second optical axis O.sub.2, and the third optical axis O.sub.3 satisfy one of the following conditions: 1) a distance between any two optical axes is less than a first pre-determined value, or 2) an included angle between any two optical axes is less than a second pre-determined value. The first pre-determined value may be within a range of 1 mm to 3 mm, such as 1 mm, 1.5 mm, 2 mm, 2.5 mm, or 3 mm. The second pre-determined value may be within a range of 1° to 3°, such as 1°, 1.5°, 2°, 2.5°, or 3°.

[0092] In some embodiments, the first combining lens **1311** may be a total reflection mirror or a dichroic lens, and the second combining lens **1312** and the third combining lens **1313** may be dichroic lenses.

[0093] In some embodiments, as shown in FIGS. **16A** and **16B**, the second combining lens **1312** includes a plurality of reflection portions **13121** and a plurality of transmission portions **13122**. The plurality of reflection portions **13121** are arranged in a laser-exit path of the second laser-exit region **122**, and are configured to reflect the second color laser beam. The plurality of transmission portions **13122** are arranged in a beam path of the first combining lens **1311** reflecting the first color laser beam, and are configured to transmit the first color laser beam. In some embodiments, the plurality of reflection portions **13121** and the plurality of transmission portions **13122** are alternately arranged. The number of the plurality of reflection portions **13121** is not limited, and it is set according to the number and the arrangement manner of the lamp beads in the second laser-

exit region **122**. The number of the plurality of transmission portions **13122** is not limited, and it is determined according to the number and the arrangement manner of the lamp beads in the first laser-exit region **121**.

[0094] In some embodiments, the second combining lens **1312** may include only one reflection portion **13121** and one transmission portion **13122**.

[0095] In some embodiments, the second combining lens **1312** includes a glass substrate **13123** and one or more strip-shaped reflection films **13124** plated on a surface of the glass substrate **13123** spaced apart from each other. The plurality of reflection portions **13121** correspond to portions of the second combining lens **1312** with the strip-shaped reflection films. In some examples, as shown in FIG. **16A**, the plurality of transmission portions **13122** correspond to portions of the second combining lens **1312** without the strip-shaped reflection films. In some other examples, as shown in FIG. **16B**, portions of the glass substrate **13123** that are not covered with the strip-shaped reflection films are removed to form hollowed-out portions. The plurality of transmission portions **13122** correspond to the hollowed-out portions.

[0096] In a case where the first combining lens **1311** is a dichroic lens, structures of the first combining lens **1311** and the third combining lens **1313** are similar to a structure of the second combining lens **1312**, which will not be repeated herein.

[0097] In some embodiments, as shown in FIG. **13** or **14**, an included angle between the reflection portion of the first combining lens **1311** of each combining lens group **131** and the laser-exit surface of the laser array **12** corresponding to the combining lens group **131**, an included angle between the reflection portion of the second combining lens **1312** of each combining lens group **131** and the laser-exit surface of the laser array **12** corresponding to the combining lens group **131**, and an included angle between the reflection portion of the third combining lens **1313** of each combining lens group **131** and the laser-exit surface of the laser array **12** corresponding to the combining lens group **131** are all within a range of 43° to 47° (i.e., $45^{\circ} \pm 2^{\circ}$). In this way, while the laser beams of three colors emitted by the laser array **12** are combined by the first combining lens **1311**, the second combining lens **1312**, and the third combining lens **1313**, the laser beams of three colors emitted by the laser array **12** may also be turned by about 90° . As a result, a dimension of the laser source **100** in a direction perpendicular to the laser-exit surface of the laser array **12** (e.g., a dimension in an up and down direction in FIG. **13** or **14**) can be reduced by a great degree, so as to achieve a purpose of reducing the volume of the laser source **100**.

[0098] The direction perpendicular to the laser-exit surface of the laser array **12** refers to a thickness direction of the laser source **100** in FIG. **8**, i.e., the T.sub.1 direction. It is conceivable that, in FIG. **8**, the laser-exit direction of the laser array **12** is T.sub.1; the laser beams of three colors emitted by the laser array **12** are respectively reflected by the first combining lens **1311**, the second combining lens **1312**, and the third combining lens **1313**, and then propagate toward the beam outlet **112** in the T.sub.2 direction.

[0099] The reflection portion of the first combining lens **1311**, the reflection portion of the second combining lens **1312** and the reflection portion of the third combining lens **1313** of each combining lens group **131** are all separated from the laser-exit surface of a corresponding laser array **12** by a predetermined distance. The predetermined distance is within a range of 1 mm to 6 mm.

[0100] In some embodiments, as shown in FIGS. **13** and **14**, a distance between the reflection portion of the first combining lens **1311** and the first laser-exit region **121** in the central axis L.sub.1 of the first laser-exit region **121** is the first distance h.sub.1. A distance between the reflection portion of the second combining lens **1312** and the second laser-exit region **122** in the central axis L.sub.2 of the second laser-exit region **122** is the second distance h.sub.2. A distance between the reflection portion of the third combining lens **1313** and the third laser-exit region **123** in the central axis L.sub.3 of the third laser-exit region **123** is the third distance h.sub.3. The first distance h.sub.1, the second distance h.sub.2 and the third distance h.sub.3 are all within a range of 1 mm to 6 mm, such as, 1 mm, 1.5 mm, 2 mm, 2.5 mm, 3 mm, 3.5 mm, 4 mm, 4.5 mm, 5 mm, 5.5

mm, or 6 mm.

[0101] In this way, a distance between the combining lens group **131** and a corresponding laser array **12** is moderate, which can reduce the dimension of the laser source **100** in the direction perpendicular to the laser-exit surface of the laser array **12**; moreover, it may also be possible to avoid collision between the combining lens group **131** and the laser array **12** caused by a close distance between the combining lens group **131** and the laser array **12** during installation, which causes the combining lens group **131** or the laser array **12** to be damaged.

[0102] It will be noted that, as shown in FIG. **13**, the central axis L.sub.1 of the first laser-exit region **121** is an axis perpendicular to the laser-exit surface of the laser array **12** and passing through a center of the first laser-exit region **121**. The central axis L.sub.2 of the second laser-exit region **122** is an axis perpendicular to the laser-exit surface of the laser array **12** and passing through a center of the second laser-exit region **122**. The central axis L.sub.3 of the third laser-exit region **123** is an axis perpendicular to the laser-exit surface of the laser array **12** and passing through a center of the third laser-exit region **123**.

[0103] In some embodiments, the beam path assembly **13** further includes a plurality of reflectors **132**. The number of the plurality of reflectors **132** and the number of the plurality of combining lens groups **131** are equal. The plurality of reflectors **132** and the plurality of combining lens groups **131** are in one-to-one correspondence. Each reflector **132** is configured to change a propagation path of the laser beams exited from a corresponding combining lens group **131**, so as to emit the laser beams exited from the combining lens group **131** toward the beam outlet **112**.

[0104] In some embodiments, as shown in FIG. **11**, the beam path assembly **13** includes two combining lens groups **131** and two reflectors **132**. The two combining lens groups **131** and the two laser arrays **12** are in one-to-one correspondence. Each combining lens group **131** is configured to combine the laser beams of multiple colors emitted by the laser array **12** corresponding to the combining lens group **131**. The two reflectors **132** and the two combining lens groups **131** are in one-to-one correspondence. Each reflector **132** is configured to change the propagation path of the laser beams exited from the combining lens group **131** corresponding to the reflector **132**, so as to emit the laser beams exited from the combining lens group **131** toward the beam outlet **112**. The beam path assembly with such structure has a simple structure and is easy to be implemented.

[0105] The arrangement direction of the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** may be any direction parallel to the laser-exit surface of the laser array **12**. As shown in FIG. **11**, the arrangement direction of the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** is perpendicular to the arrangement direction of the plurality of laser arrays **12**. For example, the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** of each laser array **12** may be arranged in an up and down direction in FIG. **11**. The plurality of laser arrays **12** may be arranged in a left and right direction in FIG. **11**.

[0106] In this way, a combining lens group **131** may emit laser beams in the direction perpendicular to the arrangement direction of the plurality of laser arrays **12**. The reflector **132** corresponding to the combining lens group **131** is located in a laser-exit path of the combining lens group **131**. An arrangement direction of the combining lens group **131** and the reflector **132** is perpendicular to the arrangement direction of the plurality of laser arrays **12**, which is conducive to reducing the dimension of the laser source **100** in the arrangement direction of the plurality of laser arrays **12**.

[0107] In order to avoid a large beam spot when the laser beams emitted by a laser array **12** propagate to the beam outlet **112** after passing through a corresponding combining lens group **131** and reflector **132**, in some embodiments, as shown in FIG. **11**, in two adjacent laser arrays **12**, a beam-shaping lens **134** is provided between the beam outlet **112** and the reflector **132** corresponding to a laser array **12** that is farther from the beam outlet **112**. The beam-shaping lens **134** is configured to reduce a divergence angle of the reflected laser beams of the reflector **132**

before the reflected laser beams of the reflector **132** farther from the beam outlet **112** enter the beam outlet **112**. As a result, a magnitude of a beam spot of the reflected laser beams is reduced when the reflected laser beams are transmitted to the beam outlet **112**.

[0108] Compared with the green laser beam and the blue laser beam, the red laser beam has a large divergence angle, and the divergence angle of the red laser beam is classified into a divergence angle in a fast axis direction and a divergence angle in a slow axis direction. The divergence angle of the red laser beam in the fast axis direction is much larger than the divergence angle thereof in the slow axis direction. Therefore, in order to effectively avoid a large beam spot when the laser beams emitted by the laser array **12** propagate to the beam outlet **112** after passing through a corresponding combining lens group **131** and reflector **132**, in some embodiments, the beam-shaping lens **134** is configured to reduce the divergence angles of the reflected laser beams in the fast axis direction of the red laser beam in the reflected laser beams before the reflected laser beams of the reflector **132** enter the beam outlet **112**.

[0109] In order to improve uniformity of the laser beams exited from the plurality of combining lens groups **131** when they are combined into one laser beam, as shown in FIG. **11**, a light homogenizing member **133** is provided at a beam inlet side of the beam outlet **112**. In some embodiments, the light homogenizing member **133** may be a diffusion sheet, a fish-eye lens, or the like. As a result, the light homogenizing member **133** can improve uniformity of the laser beams exited from the plurality of combining lens groups **131** when they are combined into one laser beam.

[0110] In some embodiments, as shown in FIG. **10**, a spherical lens **14** is installed in the beam outlet **112**, and the spherical lens **14** can converge the laser beams entering the beam outlet **112**. In this way, in a case where the laser source **100** is applied to the laser projection apparatus **10**, sizes of optical elements (e.g., the light pipe **210** in FIG. **11**) in the optical engine **200** receiving the illumination beams of the laser source **100** may be designed to be small, which is conducive to reducing the volume of the laser projection apparatus **10**.

[0111] The laser beams emitted from the laser-exit surface of a laser array **12** is emitted by the lamp beads inside the laser array **12**. Compared with the lamp beads that emit laser beams of other colors, a divergence angle of a laser beam emitted by the lamp bead that emits the red laser beam is large. On this basis, in order to avoid a large beam spot when the laser beams emitted by the laser array **12** propagate to the beam outlet **112** after passing through a corresponding combining lens group **131** and reflector **132**, in some embodiments, as shown in FIG. **12A**, the first color laser beam emitted by the first laser-exit region **121** is one of the blue laser beam and the green laser beam, the second color laser beam emitted by the second laser-exit region **122** is the other of the blue laser beam and the green laser beam, and the third color laser beam emitted by the third laser-exit region **123** is the red laser beam.

[0112] In this way, compared with the first color laser beam emitted by the first laser-exit region **121** and the second color laser beam emitted by the second laser-exit region **122**, the third color laser beam (i.e., the red laser beam) emitted by the third laser-exit region **123** has a relatively short propagation path between the laser-exit surface of the laser array **12** and the beam outlet **112**. Therefore, the red laser beam forms a small beam spot at the beam outlet **112**, which can avoid a large beam spot when the laser beams emitted by the laser array **12** propagate to the beam outlet **112** after passing through a corresponding combining lens group **131** and reflector **132**, and is conducive to reducing a diameter of the spherical lens **14** installed in the beam outlet **112**.

[0113] The laser emitted by each lamp bead in a laser array **12** is linearly polarized light. Mode of resonant cavity oscillation in laser emission process of red lamp beads is different from modes of resonant cavity oscillation in blue lamp beads and green lamp beads, which causes that a polarization direction of a red linearly polarized light is 90 degrees different from a polarization direction of a blue linearly polarized light or a polarization direction of a green linearly polarized light. That is, the red laser beam is a P laser beam, and the blue laser beam and green laser beam are

S laser beams. As a result, the polarization directions of the laser beams of three colors generated by the laser source **100** are different, and this may cause the projection image of the laser projection apparatus **10** using the laser source **100** to have a phenomenon of uneven chromaticity such as a “color spots” and a “color blocks”.

[0114] Reasons for this phenomenon are that, on one hand, optical lenses (e.g., lenses, prisms) in the laser projection apparatus **10** have different transmittances for the P laser beam and the S laser beam, for example, a transmittance of the optical lens to the P laser beam is greater than a transmittance of the S laser beam; on the other hand, it is because a transmittance and a reflectivity of the screen itself for the laser beams having different polarization directions will be obviously different.

[0115] A function of a wave plate is to make two laser beams whose vibration directions are perpendicular to each other produce a phase difference. The wave plate mainly includes quarter-wave plates, half-wave plates and full-wave plates. The half-wave plate can change a polarization direction of a laser beam by 90 degrees.

[0116] In order to increase uniformity of the laser beams emitted by the laser source **100**, in some embodiments, as shown in FIG. **13**, a first wave plate **135** is provided between the third laser-exit region **123** and the third combining lens **1313**. The first wave plate **135** is configured to rotate a polarization direction of the third color laser beam emitted by the third laser-exit region **123** by a range of 80° to 100° (i.e., $90^{\circ} \pm 10^{\circ}$). That is, the first wave plate **135** may be a half-wave plate. In this way, the polarization direction of the laser beam emitted from the third laser-exit region **123** may be changed through the first wave plate **135**, so that the polarization direction of the laser beam emitted from the third laser-exit region **123** is kept consistent with a polarization direction of the laser beam emitted from the first laser-exit region **121** or the second laser-exit region **122**, thereby improving uniformity of the laser beams emitted by the laser source **100**.

[0117] In some other embodiments, as shown in FIG. **14**, a second wave plate is provided between the first laser-exit region **121** and the first combining lens **1311**, a third wave plate is provided between the second laser-exit region **122** and the second combining lens **1312**. The second wave plate is configured to rotate the polarization direction of the first color laser beam emitted by the first laser-exit region **121** by a range of 80° to 100° (i.e., $90^{\circ} \pm 10^{\circ}$). The third wave plate is configured to rotate the polarization direction of the second color laser beam emitted by the second laser-exit region **122** by a range of 80° to 100° (i.e., $90^{\circ} \pm 10^{\circ}$). That is, both the second wave plate and the third wave plate may be half-wave plates. In this way, the polarization directions of the laser beams emitted by the first laser-exit region **121** and the second laser-exit region **122** are respectively changed through the second wave plate and the third wave plate, so that the polarization directions of the laser beams emitted by the first laser-exit region **121** and the second laser-exit region **122** are kept consistent with the polarization direction of the laser beam emitted by the third laser-exit region **123**, thereby improving uniformity of the laser beams emitted by the laser source **100**.

[0118] In some embodiments, as shown in FIG. **14**, the second wave plate and the third wave plate may be formed as an integral member **136**. In this way, the number of components included in the laser source **100** is small, and the structure complexity and assembly difficulty are low.

[0119] According to the laser source **100** in some embodiments of the present disclosure, the laser-exit surface of each laser array **12** includes a plurality of laser-exit regions. The plurality of laser-exit regions are configured to emit the laser beams of multiple colors. Therefore, there is no need to provide a large number of optical lenses in the laser source **100** in some embodiments of the present disclosure, thereby reducing the volume of the laser source **100** and reducing the structural complexity of the laser source **100**.

[0120] It will be noted that, the arrangement positions of the plurality of laser arrays **12** on the side walls of the laser source housing **11** may have numerous variations. Correspondingly, the beam path assembly **13** may further include numerous variations.

[0121] In some embodiments, as shown in FIGS. 17 to 20, the plurality of laser arrays **12** are still disposed on a same side wall (e.g., the first side wall **113**) of the laser source housing **11**. However, unlike the plurality of laser arrays shown in FIG. 9 which are arranged in a direction perpendicular to the second side wall **114**, in FIGS. 17 to 20, the plurality of laser arrays **12** are arranged in a direction approximately parallel to the second side wall **114**. In this case, a dimension of the laser source **100** in the direction perpendicular to the second side wall **114** (i.e., the direction E in FIG. 17) is small. The direction perpendicular to the second side wall **114** is substantially parallel to the direction M of the illumination beams.

[0122] In some embodiments, referring to FIGS. 18 to 20, the beam path assembly **13** still includes two combining lens groups **131** and two reflectors **132**. However, unlike the beam path assembly **13** shown in FIG. 11, in FIGS. 18 to 20, the laser-exit directions of the two combining lens groups **131** (i.e., the direction X and the direction Y in FIG. 18) are opposite. The beam path assembly with such structure has a simple structure and is easy to be implemented.

[0123] It will be noted that, the laser-exit directions of the two combining lens groups **131** are opposite, which means that the two combining lens groups **131** both emit laser beams to a region between the two combining lens groups **131**, and the laser-exit directions of the two combining lens groups **131** are opposite. The two combining lens groups **131** may emit laser beams to a same position in the region between the two combining lens groups **131**, or may emit laser beams to different positions in the region between the two combining lens groups **131**. In some embodiments, as shown in FIGS. 18 and 19, the two combining lens groups **131** may emit laser beams to different positions in the region between the two combining lens groups **131**.

[0124] In some embodiments, as shown in FIG. 12A, the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** of each laser array **12** are all sequentially arranged (i.e., they are arranged in the X1 direction shown in FIG. 12A). In some embodiments, as shown in FIGS. 18 and 19, the first laser-exit regions **121**, the second laser-exit regions **122**, and the third laser-exit regions **123** of two laser arrays **12** are arranged in opposite directions. For example, a first laser-exit region **121**, a second laser-exit region **122**, and a third laser-exit region **123** of a laser array **12** located at a left side in FIG. 18 are sequentially arranged in the direction X. A first laser-exit region **121**, a second laser-exit region **122**, and a third laser-exit region **123** of a laser array **12** at a right side in FIG. 18 are sequentially arranged in the direction Y.

[0125] An arrangement manner of the plurality of laser arrays **12** on the laser source housing **11** shown in FIGS. 17 to 20 may make the laser source housing **11** have an irregular shape, which may be adapted to a situation that installation space reserved for the laser source **100** in the laser projection apparatus **10** is narrow or irregular. This improves flexibility of an outer contour or an installation position of the laser source **100**.

[0126] In some embodiments, as shown in FIGS. 21 to 25B, the plurality of laser arrays **12** are disposed on two opposite side walls (e.g., a first side wall **113** and a third side wall **115**) of the laser source housing **11**. A second side wall **114** is located between the first side wall **113** and the third side wall **115**, and is perpendicular to both the first side wall **113** and the third side wall **115**.

[0127] In some embodiments, referring to FIGS. 21 and 22, FIG. 22 shows a back surface of the laser source **100** in FIG. 21. The first side wall **113** and the third side wall **115** may be oppositely arranged in a thickness direction of the laser source housing **11**. The first side wall **113** and the third side wall **115** may be parallel, and the first side wall **113** and the third side wall **115** each include an accommodating opening **111**. The second side wall **114** includes a beam outlet **112**.

[0128] In some embodiments, as shown in FIGS. 23 and 24, the beam path assembly **13** still includes two combining lens groups **131** and two reflectors **132**, and the two combining lens groups **131** each emits laser beams toward a corresponding reflector **132**. The two reflectors **132** are respectively configured to change the propagation paths of the laser beams emitted by the two combining lens groups **131**, so as to make the laser beams exited from the two combining lens groups **131** exit from the beam outlet **112**. In this way, the beam path assembly **13** has a simple

structure and the low cost. The laser source **100** has a small volume and low structure complexity, and is easy to be implemented.

[0129] In some embodiments, as shown in FIG. 23, the first laser-exit region **121**, the second laser-exit region **122**, and the third laser-exit region **123** of each laser array **12** are sequentially arranged in a direction proximate to the reflectors **132** (i.e., the direction X1 in FIGS. 23 and 24).

[0130] In some embodiments, as shown in FIGS. 25A and 25B, the beam path assembly **13** still includes two combining lens groups **131**. Unlike the two combining lens groups **131** shown in FIGS. 15A and 15B located at a same side of a corresponding laser array **12**, the two combining lens groups **131** in FIGS. 25A and 25B are located at different sides of a corresponding laser array **12**. For example, a combining lens group **131** corresponding to a laser array **12** at a left side in FIG. 25B is located at an upper side of the laser array **12**, and a combining lens group **131** corresponding to a laser array **12** at a right side in FIG. 25B is located at a lower side of the laser array **12**. The two combining lens groups **131** are located between the two laser arrays **12** in an up and down direction.

[0131] The foregoing descriptions are merely specific implementation manners of the present disclosure, but the protection scope of the present disclosure is not limited thereto. Any person skilled in the art could conceive of changes or replacements within the technical scope of the present disclosure, which shall be included in the protection scope of the present disclosure. Therefore, the scope of the present disclosure shall be subject to the protection scope of the claims.

[0132] Those skilled in the art will understand that the scope of disclosure involved in the present disclosure is not limited to the technical solutions formed by the specific combinations of the above technical features, and will also cover other technical solutions formed by any combination of the above technical features or their equivalent features without departing from the disclosed concept. For example, a technical solution formed by replacing the above features with technical features disclosed in some embodiments (but not limited to) having similar functions.

Claims

1. A laser source, comprising: a laser source housing, the laser source housing including a beam outlet and a plurality of accommodating openings, and the plurality of accommodating openings being disposed at a same side wall or different side walls of the laser source housing; a plurality of laser arrays, the plurality of laser arrays being respectively disposed in the plurality of accommodating openings, a laser array of the plurality of laser arrays being configured to emit laser beams into the laser source housing, a laser-exit surface of the laser array including a plurality of laser-exit regions, and the plurality of laser-exit regions being configured to emit laser beams of multiple colors; and a beam path assembly, the beam path assembly being disposed inside the laser source housing, and the beam path assembly being configured to combine the laser beams of the multiple colors emitted by the laser array, and make combined laser beams exit toward the beam outlet, wherein the beam path assembly includes a plurality of combining lens groups, the plurality of combining lens groups and the plurality of laser arrays being in one-to-one correspondence, a combining lens group of the plurality of combining lens groups is configured to combine laser beams of multiple colors emitted by a laser array corresponding to the combining lens group, and laser beams combined by the combining lens group are not located in beam output paths of other combining lens groups.
2. The laser source according to claim 1, wherein at least one combining lens group of the plurality of combining lens groups includes at least one total reflection mirror and at least one dichroic lens.
3. The laser source according to claim 1, wherein the laser source housing includes a first side wall and a second side wall that are perpendicular to each other, the first side wall includes the plurality of accommodating openings, and the second side wall includes the beam outlet.
4. The laser source according to claim 3, wherein the plurality of accommodating openings are

arranged in a direction perpendicular to the second side wall; or the plurality of accommodating openings are arranged in a direction substantially parallel to the second side wall.

5. The laser source according to claim 3, wherein the first side wall includes two accommodating openings, and two laser arrays are respectively disposed in the two accommodating openings.

6. The laser source according to claim 1, wherein the laser source housing includes a first side wall and a third side wall that are opposite to each other, and a second side wall perpendicular to the first side wall and the third side wall; the first side wall and the third side wall each includes at least one accommodating opening, and the second side wall includes the beam outlet; and a part of the plurality of laser arrays are disposed in the at least one accommodating opening of the first side wall, and another part of the plurality of laser arrays are disposed in the at least one accommodating opening of the third side wall.

7. The laser source according to claim 2, wherein the plurality of laser-exit regions includes: a first laser-exit region, the first laser-exit region being configured to emit a first color laser beam; a second laser-exit region, the second laser-exit region being configured to emit a second color laser beam; and a third laser-exit region, the third laser-exit region being configured to emit a third color laser beam, wherein colors of the first color laser beam, the second color laser beam and the third color laser beam are different from each other.

8. The laser source according to claim 7, wherein the combining lens group includes: a first combining lens located at a laser-exit side of the first laser-exit region, to reflect the first color laser beam emitted by the first laser-exit region; a second combining lens located at laser-exit sides of the second laser-exit region, to reflect the second color laser beam emitted by the second laser-exit region; and a third combining lens located at laser-exit sides of the third laser-exit region, to reflect the third color laser beam emitted by the third laser-exit region, to transmit the first color laser beam reflected by the first combining lens, and to transmit the second color laser beam reflected by the second combining lens, wherein at least one of the first combining lens and the second combining lens is a total reflection mirror, and the third combining lens is a dichroic lens; and the first combining lens, the second combining lens and the third combining lens each are disposed at an incline relative to corresponding laser-exit regions.

9. The laser source according to claim 8, wherein the first color laser beam emitted by the first laser-exit region is a blue laser beam, the second color laser beam emitted by the second laser-exit region is a green laser beam, and the third color laser beam emitted by the third laser-exit region is a red laser beam; or the first color laser beam emitted by the first laser-exit region is a cyan laser beam, the second color laser beam emitted by the second laser-exit region is a yellow laser beam, and the third color laser beam emitted by the third laser-exit region is a magenta laser beam.

10. The laser source according to claim 9, wherein the first laser-exit region, the second laser-exit region and the third laser-exit region each correspond to a plurality of lamp beads in the laser array.

11. The laser source according to claim 7, wherein laser-exit directions of the first laser-exit region, the second laser-exit region and the third laser-exit region of the laser array are same; or the first laser-exit region, the second laser-exit region and the third laser-exit region of the laser array are located on a same laser-exit surface.

12. The laser source according to claim 7, wherein an included angle between the reflection portion of the first combining lens and a laser-exit surface of the laser array corresponding to the combining lens group, an included angle between the reflection portion of the second combining lens and the laser-exit surface of the laser array corresponding to the combining lens group, and an included angle between the reflection portion of the third combining lens and the laser-exit surface of the laser array corresponding to the combining lens group are all within a range of 43° to 47° ($45^{\circ} \pm 2^{\circ}$); and/or the reflection portion of the first combining lens, the reflection portion of the second combining lens, and the reflection portion of the third combining lens are each separated from a laser-exit surface of the laser array corresponding to the combining lens group by a predetermined distance.

13. The laser source according to claim 8, wherein in the laser array, a polarization direction of the first color laser beam emitted by the first laser-exit region is same as a polarization direction of the second color laser beam emitted by the second laser-exit region, and the polarization direction of the second color laser beam emitted by the second laser-exit region intersects a polarization direction of the third color laser beam emitted by the third laser-exit region; the laser source comprises a first wave plate; and the first wave plate is located between the third laser-exit region and the third combining lens, and the first wave plate is configured to change the polarization direction of the third color laser beam emitted by the third laser-exit region.

14. The laser source according to claim 13, wherein the first wave plate is configured to change the polarization direction of the third color laser beam emitted by the third laser-exit region by 90° .

15. The laser source according to claim 1, wherein a light homogenizing member is disposed at the beam outlet, and the light homogenizing member is a diffusion sheet or a fish-eye lens.

16. A laser projection apparatus, comprising: a laser source, the laser source being configured to provide illumination beams, and the laser source being the laser source according to claim 1; an optical engine, the optical engine being configured to modulate the illumination beams with image display signals to obtain projection beams; and a projection lens, the projection lens being configured to project the projection beams on a screen or a wall for imaging.

17. A laser source, comprising: a laser source housing, the laser source housing including a beam outlet and a plurality of accommodating openings, and the plurality of accommodating openings being disposed at a same side wall or different side walls of the laser source housing; a plurality of laser arrays, the plurality of laser arrays being respectively disposed in the plurality of accommodating openings, a laser-exit surface of a laser array of the plurality of laser arrays including a plurality of laser-exit regions, and the plurality of laser-exit regions being configured to emit laser beams of multiple colors; and a plurality of combining lens groups, the plurality of combining lens groups and the plurality of laser arrays being in one-to-one correspondence, and a combining lens group of the plurality of combining lens groups being configured to combine laser beams of multiple colors emitted by a laser array corresponding to the combining lens group, and make combined laser beams exit toward a direction of the beam outlet; wherein the laser beams of the multiple colors emitted by the plurality of laser-exit regions are linearly polarized lights, and polarization directions of the laser beams of the multiple colors emitted by the plurality of laser-exit regions are different; and a wave plate is disposed between the combining lens group and a laser-exit region of the laser array corresponding to the combining lens group, and the wave plate is configured to change a polarization direction of a laser beam emitted by the laser-exit region, and then incident a changed laser beam to the combining lens group.

18. The laser source according to claim 17, wherein the wave plate is half-wave plates.

19. The laser source according to claim 17, wherein the plurality of laser-exit regions includes a first laser-exit region, a second laser-exit region and a third laser-exit region, and the first laser-exit region, the second laser-exit region and the third laser-exit region are configured to emit a first color laser beam, a second color laser beam and a third color laser beam respectively, wherein a polarization direction of the third color laser beam is different from polarization directions of the first color laser beam and the second color laser beam; and the wave plate is disposed relative to the third laser-exit region, and the wave plate is configured to change the polarization direction of the third color laser beam.

20. The laser source according to claim 17, wherein a light homogenizing member is disposed at the beam outlet, and the light homogenizing member is a diffusion sheet or a fish-eye lens.
