

US012383463B1

# (12) United States Patent

Vitello et al.

## (10) Patent No.: US 12,383,463 B1

(45) **Date of Patent:** Aug. 12, 2025

## (54) TAMPER EVIDENT SEAL FOR A VIAL COVER

(71) Applicants: Jonathan Vitello, Fort Lauderdale, FL (US); Santiago Paredes, Boca Raton, FL (US); Peter Lehel, Boca Raton, FL (US)

(72) Inventors: **Jonathan Vitello**, Fort Lauderdale, FL (US); **Santiago Paredes**, Boca Raton, FL (US); **Peter Lehel**, Boca Raton, FL (US)

(73) Assignee: MEDICAL DEVICE
ENGINEERING, LLC, Pompano
Beach, FL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 18/414,244

(22) Filed: Jan. 16, 2024

### Related U.S. Application Data

- (63) Continuation of application No. 17/563,371, filed on Dec. 28, 2021, now Pat. No. 11,872,187.
- (60) Provisional application No. 63/131,124, filed on Dec. 28, 2020.
- (51) Int. Cl.

  A61J 1/14 (2023.01)

  B65D 41/46 (2006.01)

  B65D 51/24 (2006.01)

(52) **U.S. CI.** CPC ............. *A61J 1/1425* (2015.05); *B65D 41/465* (2013.01); *B65D 51/245* (2013.01); *A61J* 2205/10 (2013.01)

(58) **Field of Classification Search**CPC ........... A61J 1/1425; A61J 1/2205; A61J 1/10;
B65D 41/465; B65D 51/245

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

722,943 A 3/1903 Chappell 732,662 A 6/1903 Smith 1,678,991 A 7/1928 Marschalek 1,970,631 A 8/1934 Sherman 2,186,888 A 1/1940 Tullar et al. (Continued)

### FOREIGN PATENT DOCUMENTS

DE 202008018507 2/2015 EP 0148116 7/1985 (Continued)

### OTHER PUBLICATIONS


Arai Tsugio, Pilfering Proof Cap, Jan. 9, 1996.

Primary Examiner — Orlando E Aviles
Assistant Examiner — Niki M Eloshway
(74) Attorney, Agent, or Firm — Malloy & Malloy PL

### (57) ABSTRACT

A tamper evident seal structure for a vial septum or other cover having a housing including a sidewall terminating in oppositely disposed open and closed ends. A retainer is fixedly disposed within the housing and structured for retaining engagement with a portion of a vial, substantially adjacent the vial cover. The housing also includes a pressure member disposed within an interior thereof in attached, relation to the closed-end. The pressure member and the retainer are cooperatively disposed and structured to respectively exert pressure on the vial cover concurrent to retaining engagement with the vial. Tamper evident capabilities are at least partially defined by a detachment of a removable sidewall section from a remainder of said sidewall.

## 17 Claims, 2 Drawing Sheets





(56)	Referen	ces Cited	4,842,592			Caggiani et al.
11	C DATENT	DOCUMENTS	4,844,906 4,863,451			Hermelin et al. Marder
U	.S. PATENT	DOCUMENTS	4,906,231		3/1990	
2,277,936 A	3/1942	Rosenblatt	4,919,285	A	4/1990	Roof et al.
2,459,304 A			4,936,445 5,007,535			Grabenkort Meseke et al.
2,477,598 A 2,734,665 A			5,009,323			Montgomery et al.
2,739,590 A		Yochem	5,024,323	A	6/1991	Bolton
2,811,283 A	10/1957		5,049,129			Zdeb et al.
2,823,674 A 2,834,346 A		Yochem	5,057,093 D323,392		1/1991	Clegg et al. Bryne
2,875,761 A		Helmer et al.	5,078,696	A	1/1992	Nedbaluk
2,888,015 A	5/1959	Hunt	5,085,332			Gettig et al.
2,952,255 A 3,122,280 A		Hein, Jr.	5,090,564 5,119,975			Chimienti Jemielita
3,180,532 A			5,133,454	A	7/1992	Hammer
3,245,567 A	4/1966	Knight	5,135,496			Vetter et al.
3,323,798 A			5,148,652 5,163,922		9/1992	McElveen, Jr. et al.
3,364,890 A 3,368,673 A		Andersen Johnson	5,165,560			Ennis, III et al.
3,489,268 A	1/1970	Meierhoefer	5,230,429			Etheredge, III
3,568,673 A		Cowley	5,267,983 5,292,308		3/1994	Oilschlager et al.
3,574,306 A 3,598,120 A			5,293,993		3/1994	
3,610,241 A	10/1971	LeMarie	5,295,599		3/1994	
3,674,181 A		Marks et al.	5,312,367 5,312,368			Nathan Haynes
3,700,215 A 3,706,307 A		Hardman et al.	5,312,368			von Schuckmann
3,712,749 A		Roberts	5,328,466			Denmark
3,726,445 A		Ostrowsky et al.	5,328,474 5,332,113		7/1994	Raines Kusler, III et al.
3,747,751 A 3,850,329 A		Miller et al. Robinson	5,356,380			Hoekwater et al.
3,872,867 A		Killinger	5,370,226	A		Gollobin et al.
3,904,033 A			5,380,295 5,402,887		1/1995	Vacca Shillington
3,905,375 A 3,937,211 A		Toyama Morton	5,405,339		4/1995	Kohnen et al.
3,987,930 A			5,456,668	A	10/1995	Ogle, II
4,005,739 A	2/1977	Winchell	5,458,580 5,468,224			Hajishoreh
4,043,334 A 4,046,145 A		Brown et al. Choksi et al.	5,474,178		11/1995 12/1995	DiViesti et al.
4,068,696 A		Winchell	5,505,705	A	4/1996	Galpin et al.
4,085,845 A	4/1978	Perfect	5,531,695			Swisher
4,106,621 A 4,216,585 A		Sorenson	5,540,324 5,540,666		7/1996 7/1996	Barta et al.
4,216,872 A			5,549,571	A	8/1996	Sak
4,244,366 A	1/1981	Raines	5,558,648		9/1996	Shields van den Haak
4,252,122 A 4,271,972 A		Halvorsen	5,584,817 5,588,239			Anderson
4,271,972 A			5,611,445	A	3/1997	Kano et al.
4,286,640 A	9/1981	Knox et al.	5,617,954		4/1997 4/1997	Kato et al.
4,313,539 A 4,369,781 A		Raines Gilson et al.	5,624,402 5,662,233		9/1997	
4,420,085 A		Wilson et al.	5,674,209	A	10/1997	Yarger
4,430,077 A	2/1984	Mittleman et al.	5,695,470			Roussigne et al.
4,433,790 A 4,457,445 A		Gibson Hanks et al.	5,699,913 5,700,247			Richardson Grimard et al.
4,482,071 A		Ishiwatari	5,702,374	A	12/1997	Johnson
D277,783 S	2/1985	Beck	5,706,985		1/1998	
4,520,942 A 4,521,237 A		Dwinell Logothetis	5,713,485 5,776,124		7/1998	Liff et al. Wald
4,521,237 A 4,530,697 A	7/1985	Kuhlemann et al.	5,785,691	A	7/1998	Vetter et al.
4,558,554 A	12/1985	Herbert	5,797,885		8/1998	Rubin Tucker et al.
4,571,242 A 4,589,171 A		Klien et al.	5,807,343 5,829,589			Nguyen et al.
4,664,259 A			D402,766	S	12/1998	Smith et al.
4,667,837 A	5/1987	Vitello et al.	5,842,567			Rowe et al.
4,676,530 A 4,693,707 A		Nordgren et al.	5,876,381 5,883,806		3/1999	Pond et al. Meador et al.
4,093,707 A			5,884,457		3/1999	
4,735,617 A	4/1988	Nelson et al.	5,901,866		5/1999	Storar
4,742,910 A		Staebler	5,902,269 5,926,922		5/1999 7/1999	Jentzen Stottle
4,743,229 A 4,743,231 A		Kay et al.	5,920,922		9/1999	Rosato et al.
4,753,345 A	6/1988	Goodsir et al.	5,951,525		9/1999	Thorne et al.
4,760,847 A		Vaillancourt	5,954,203			Marconi
4,813,564 A 4,832,695 A		Cooper et al. Rosenberg et al.	5,954,657 5,957,166		9/1999 9/1999	
4,832,695 A 4,834,706 A		Beck et al.	5,957,100			Nishida et al.
.,-2.,,.00 1.			, , •	-		


(56)		Referen	ces Cited	7,608,057			Woehr et al.
	IIS	PATENT	DOCUMENTS	7,611,487 7,632,244			Woehr et al. Buehler et al.
	0.5	. 17111111	DOCOMENTS	D608,900			Giraud et al.
	5,963,136 A	10/1999	O'Brien	7,641,636			Moesli et al.
	5,983,596 A		Corniani et al.	D612,939 7,681,606			Boone, III et al. Khan et al.
	5,989,227 A 5,993,437 A		Vetter et al. Raoz	7,698,180			Fago et al.
	6,000,548 A		Tsals	7,708,035			Windmiller
	D419,671 S	1/2000		7,735,664 7,748,892			Peters et al. McCoy
	6,021,824 A 6,027,482 A	2/2000 2/2000	Larsen et al.	7,762,988		7/2010	
	6,068,614 A		Kimber et al.	7,766,919	B2	8/2010	Delmotte
	D430,293 S	8/2000		7,802,313 7,886,908		9/2010	Czajka Farrar et al.
	6,112,951 A D431,864 S	9/2000 10/2000	Mueller	7,918,830			Langan et al.
	6,126,640 A		Tucker et al.	7,922,213	B2	4/2011	Werth
	6,190,364 B1	2/2001		7,988,004 8,034,041			Marret et al. Domkowski et al.
	6,193,688 B1 6,196,593 B1		Balestracci et al. Petrick et al.	8,079,518			Turner et al.
	6,196,998 B1		Jansen et al.	8,091,727	B2	1/2012	Domkowwski
	6,216,885 B1	4/2001	Guillaume	8,118,788		2/2012	
	6,235,376 B1		Miyazaki et al.	8,120,484 8,137,324		3/2012	Chisholm Bobst
	6,279,746 B1 6,280,418 B1		Hussaini et al. Reinhard et al.	8,140,349		3/2012	Hanson et al.
	6,287,671 B1	9/2001	Bright et al.	8,252,247		8/2012	
	6,322,543 B1		Singh et al.	8,257,286 8,328,082			Meyer et al. Bochenko et al.
	6,338,200 B1 6,358,241 B1		Baxa et al. Shapeton et al.	8,348,895		1/2013	
	6,375,640 B1		Teraoka	8,353,869			Ranalletta et al.
	6,394,983 B1		Mayoral et al.	8,413,410 8,413,811		4/2013	Ulm et al.
	6,439,276 B1 6,485,460 B2		Wood et al. Eakins et al.	8,443,999			Reinders
	6,488,666 B1	12/2002		D684,057		6/2013	
	6,491,665 B1		Vetter et al.	8,512,277 8,528,757		8/2013 9/2013	Del Vecchio
	6,500,155 B2 6,520,935 B1	12/2002	Sasso Jansen et al.	8,556,074			Turner et al.
	6,540,697 B2	4/2003		8,579,116	B2		Pether et al.
	6,565,529 B1		Kimber et al.	8,591,462 8,597,255		11/2013	Vitello Emmott et al.
	6,581,792 B1 6,585,691 B1	6/2003 7/2003	Limanjaya Vitallo	8,597,233			Langan et al.
	6,592,251 B2		Edwards et al.	8,616,413	B2	12/2013	Koyama
	6,666,852 B2	12/2003	Niedospial, Jr.	D701,304			Lair et al.
	6,682,798 B1 6,726,652 B2		Kiraly Eakins et al.	8,672,902 8,702,674			Ruan et al. Bochenko
	6,726,672 B1		Hanly et al.	8,777,910	B2	7/2014	Bauss et al.
	6,764,469 B2	7/2004	Broselow	8,777,930			Swisher et al.
	6,796,586 B2	9/2004	Werth Balestracci	8,852,561 8,864,021		10/2014	Wagner et al. Vitello
	6,821,268 B2 D501,549 S		McAllister et al.	8,864,707	B1	10/2014	Vitello
	6,921,383 B2	7/2005	Vitello	8,864,708		10/2014	
	6,935,560 B2		Andreasson et al.	8,911,424 8,945,082			Weadock et al. Geiger et al.
	6,942,643 B2 6,991,126 B2	1/2006	Eakins et al.	8,978,909		3/2015	Kakutani et al.
	7,036,661 B2	5/2006	Anthony et al.	9,016,473			Tamarindo
	7,055,273 B2		Roshkoff	9,027,769 9,082,157			Willows et al. Gibson
	7,100,771 B2 7,125,397 B2		Massengale et al. Woehr et al.	9,101,534			Bochenko
	7,141,286 B1	11/2006	Kessler et al.	D738,495		9/2015	Strong et al.
	7,175,081 B2		Andreasson et al.	9,125,976 D743,019		11/2015	Uber, III et al.
	7,182,256 B2 7,232,066 B2		Andreasson et al. Anderasson et al.	9,192,443			Tennican
	7,240,926 B2	7/2007	Dalle et al.	9,199,042			Farrar et al.
	7,299,981 B2		Hickle et al.	9,199,749 9,220,486			Vitello et al. Schweiss et al.
	7,374,555 B2 7,404,500 B2		Heinz et al. Marteau et al.	9,220,577			Jessop et al.
	7,410,803 B2		Nollert et al.	9,227,019			Swift et al.
	7,425,208 B1		Vitello	D750,228 9,272,099			Strong et al. Limaye et al.
	7,437,972 B2 7,438,704 B1	10/2008 10/2008	Yeager Kawashima et al.	9,272,099	B1		Vitello et al.
	D581,046 S	11/2008	Sudo	D756,777	S	5/2016	Berge et al.
	D581,047 S	11/2008	Koshidaka	9,336,669			Bowden et al.
	D581,049 S	1/2008	Sudo Nollert et al.	D759,486 D760,384			Ingram et al. Niunoya et al.
	7,482,166 B2 D589,612 S	3/2009	Sudo	D760,384 D760,902	S		Persson
	7,497,330 B2	3/2009	Anthony et al.	9,402,967		8/2016	
	7,503,453 B2		Cronin et al.	9,427,715			Palazzolo et al.
	7,588,563 B2		Guala	9,433,768			Tekeste et al.
	7,594,681 B2	9/2009	DeCarlo	9,463,310	ום	10/2016	viieno

(56) Refer	ences Cited	2002/0046962 A1		Vallans et al.
IIS PATEN	IT DOCUMENTS	2002/0079281 A1 2002/0097396 A1		Hierzer et al. Schafer
0.5.171121	T DOCOMENTO	2002/0099334 A1		Hanson et al.
	6 Ingram et al.	2002/0101656 A1 2002/0104770 A1		Blumenthal et al. Shapeton et al.
*	7 Schultz	2002/01047/0 A1 2002/0133119 A1		Eakins et al.
	7 Woehr 7 Davis et al.	2003/0041560 A1		Kemnitz
9,687,249 B2 6/201	7 Hanlon et al.	2003/0055685 A1		Cobb et al.
	7 Pakhomov et al.	2003/0146617 A1 2003/0183547 A1		Franko, Sr. Heyman
	7 Swift et al. 7 Davis et al.			Balestracci
	7 Davis et al.	2004/0008123 A1		Carrender et al.
	7 Hund et al.	2004/0064095 A1 2004/0116858 A1	4/2004 6/2004	Vitello Heinz et al.
	7 Vitello et al. 7 Swinney et al.	2004/0110838 A1 2004/0129738 A1	7/2004	
	8 Davis et al.	2004/0173563 A1*	9/2004	Kim B65D 41/48
	8 Vitello et al.	2004/0186437 A1	0/2004	Frenette et al.
	8 Fischer 8 Stillson			Balestracci
	8 Davis et al.	2005/0146081 A1	7/2005	MacLean et al.
	8 Yeh et al.	2005/0148941 A1 2005/0209555 A1		Farrar et al. Middleton et al.
	8 Holtz et al. 8 Ryan	2005/0209333 AT 2006/0049948 AT		Chen et al.
	8 Zenker	2006/0084925 A1	4/2006	Ramsahoye
	9 Hunt et al.	2006/0089601 A1		Dionigi Prindle
	9 Vitello 9 Vitello	2006/0169611 A1 2006/0173415 A1		Cummins
	9 Vitello	2006/0189933 A1	8/2006	Alheidt et al.
D842,464 S 3/201	9 Davis et al.	2007/0060898 A1		Shaughnessy et al.
	9 Hurwit et al. 9 Sattig et al.	2007/0106234 A1 2007/0142786 A1	5/2007 6/2007	Lampropoulos et al.
	9 Hunt	2007/0191690 A1	8/2007	Hasse et al.
10,307,548 B1 6/201	9 Hunt et al.	2007/0219503 A1		Loop et al.
	9 Vitello et al. 9 Taylor et al.	2007/0257111 A1 2008/0068178 A1	11/2007 3/2008	
	9 Pupke et al.	2008/0078146 A1	4/2008	
D859,125 S 9/201	9 Weagle et al.	2008/0097310 A1		Buehler et al.
	9 Niese et al. 0 Thorne	2008/0106388 A1 2008/0140020 A1	5/2008 6/2008	Shirley
	0 Perazzo et al.		10/2008	
10,758,684 B1 9/202	0 Vitello et al.			Windmiller
	0 Davis et al. 0 Thorne et al.		12/2008	Schnell et al. Neer
	0 Banik et al.	2009/0008356 A1	1/2009	
	1 Vitello	2009/0084804 A1		Caspary et al.
	1 Vitello et al. 1 Vitello et al.	2009/0099552 A1 2009/0149815 A1		Levy et al. Kiel et al.
	1 Banik	2009/0166311 A1	7/2009	Claessens
10,940,087 B2 3/202	1 Thorne et al.	2009/0212954 A1	8/2009 12/2009	Adstedt et al. Swisher et al.
	1 Hunt et al. 1 Banik	2009/0326481 A1 2010/0050351 A1		Colantonio et al.
	1 Vitello et al.	2010/0051491 A1	3/2010	Lampropoulos et al.
	1 Hunt et al.	2010/0084403 A1		Popish et al. Schmitt
	2 Banik et al. 2 Banik	2010/0089862 A1 2010/0126894 A1		Koukol et al.
	2 Vitello et al.	2010/0179822 A1	7/2010	Reppas
	2 Vitello et al.	2010/0211016 A1 2010/0228226 A1		Palmer-Felgate Nielsen
	2 Ollmann et al. 2 Banik A61M 39/20			Martinez et al.
11,523,970 B1 12/202	2 Vitello et al.	2010/0283238 A1	11/2010	Deighan et al.
	3 Vitello et al.	2010/0307108 A1 2011/0009836 A1		Sink et al. Chebli et al.
	3 Banik et al. 3 Hendren et al.	2011/00044850 A1		Solomon et al.
11,779,520 B1 10/202	3 Vitello	2011/0046550 A1		Schiller et al.
	3 Vitello et al.	2011/0046603 A1 2012/0064515 A2		Felsovalyi et al. Knapp et al.
	4 Vitello 4 Vitello et al.	2012/0096957 A1		Ochman
11,904,149 B1 2/202	4 Vitello et al.	2012/0110950 A1		Schraudolph
	4 Lehel et al.	2013/0018356 A1 2013/0018536 A1		Prince et al. Prince et al.
	4 Vitello 4 Vitello et al.	2013/0018330 A1 2013/0056130 A1		Alpert et al.
12,195,241 B1 1/202	5 Vitello et al.	2013/0088354 A1	4/2013	Thomas
	5 Bell	2013/0145725 A1		Bianco et al.
	1 Imbert 1 Hirschman et al.	2013/0237949 A1 2013/0269592 A1	9/2013	Miller Heacock et al.
	1 Evans	2014/0000781 A1		Franko, Jr.
2002/0007147 A1 1/200	2 Capes et al.	2014/0034536 A1	2/2014	Reinhardt et al.
2002/0023409 A1 2/200	2 Py	2014/0069202 A1	3/2014	Fisk

(56)		Referen	ces Cited			361235 367439		12/2016	Swisher Davis et al.
	TIC 1	DATENIT	DOCUMENTS			007771 .			Duinat et al.
	U.S. I	PALENT	DOCUMENTS			014310			Hyun et al.
2014/00/0020	4.1	2/2014	P			124289			Hasan et al.
2014/0069829		3/2014		DC5D 41/4C5		173321			Davis et al.
2014/0076840	A1 *	3/2014	Graux					7/2017	
2014/0127720	4.1	5/2014	D '	215/341		203086 . 225843 .			Glaser et al.
2014/0135738			Panian Nelson et al.						Davis et al.
2014/0155868						239141			
2014/0163465 2014/0257843			Bartlett, II et al. Adler et al.			297781			Kawamura B65D 51/18
2014/0237843			Stratis et al.			319438			Davis et al.
2014/0319141			Jouin et al.			328758		11/2017	
2014/0320727		12/2014				349335 .			Sattig B65B 55/10
2015/0013811			Carrel	A611 1/1/25		354792		12/2017	
2013/0013811	AI	1/2013	Carrer	137/798		001540		1/2018	
2015/0048045	A 1	2/2015	Miceli et al.	137/198		014998			Yuki et al.
2015/0048045			Ishiwata	A611 1/1/25		064604 .			Drmanovic
2013/0112290	Λ1	7/2013	15111 wata	604/406	2018/0	078684 .	A1		Peng et al.
2015/0136632	A 1	5/2015	Moir et al.	004/400	2018/0	089593 .	A1	3/2018	Patel et al.
2015/0182686			Okihara		2018/0	098915 .	A1		Rajagopal et al.
2015/0191633			De Boer et al.		2018/0	147115 .	A1*	5/2018	Nishioka A61J 1/1425
2015/0191035		9/2015			2018/0	312305	A1	11/2018	Rognard
2015/0240183			Glaser et al.		2019/0	308006	A1	10/2019	Erekovcanski et al.
2015/0302232			Strassburger et al.		2019/0	388626	A1	12/2019	Okihara
2015/0305982			Bochenko		2022/0	008645	A1	1/2022	Ukai et al.
2015/0310771			Atkinson et al.		2022/0	024630	A1	1/2022	Bohamed
2016/0067144		3/2016			2022/0	339067	A1*	10/2022	Christie B65B 7/2821
2016/0067422			Davis	A61M 5/3134					
				604/192		FOR	REIG	N PATE	NT DOCUMENTS
2016/0090456	A1	3/2016	Ishimaru et al.			101	CLIO.	11111	TO BOCOMENTS
2016/0136352	A1	5/2016	Smith et al.		EP		269	920	6/1988
2016/0144119	A1	5/2016	Limaye et al.		EP			980	12/1993
2016/0158110	A1		Swisher et al.		EP		2724		4/2014
2016/0158449	A1	6/2016	Limaye et al.		GB			367	6/1938
2016/0176550	A1	6/2016	Viitello et al.		JP		08002		1/1996
2016/0194121	A1*	7/2016	Ogawa	A61J 1/05	KR		01159		6/2012
				215/249			1/2008		
2016/0250420	A1	9/2016	Maritan et al.		WO	WO20			5/2015
2016/0279032	A1	9/2016	Davis						
2016/0328586	A1	11/2016	Bowden et al.		* cited	by exan	niner		







# TAMPER EVIDENT SEAL FOR A VIAL COVER

The present application is a Continuation Patent Application of and claims priority to a previously filed U.S. 5 Non-Provisional patent application, namely, that having Ser. No. 17/563,371 and a filing date of Dec. 28, 2021, which is set to mature into U.S. Pat. No. 11,872,187, on Jan. 16, 2024, and further claims priority under 35 U.S.C. Section 119(e) to a U.S. Provisional patent application, namely, that having 10 Ser. No. 63/131,124 and a filing date of Dec. 28, 2020, with the contents of both prior applications being incorporated herein by reference in their entireties.

#### BACKGROUND OF THE INVENTION

#### Field of the Invention

This invention is directed to a closure or cover type of seal structure for a septum or other cover for a vial including a 20 housing disposable in enclosing, retaining engagement with the upper end of the vial and the septum or cover attached thereto. The housing further includes tamper evident capabilities, which prevent reattachment or reuse of the housing in the intended manner.

### DESCRIPTION OF THE RELATED ART

In the medical field, it is relatively common procedure to administer fluids to a patient by syringes, intravenous infusion (IV), etc. Such administration devices or assemblies are useful in the treatment of a number of medical conditions because a variety of fluids and/or medications can be administered to a patient utilizing such assemblies. By way of example, it is common for medical personnel to order that a 35 patient be given a medication by injection. However, there are a number of safety issues associated with administering injections. One concern relates to avoiding contamination by bacteria, germs, or other harmful organisms. Because of this, and also due to the potential for theft of the medication 40 and/or tampering in order to access the medication, one important concern relates to minimizing the number of people handling syringes. This concern is perhaps even more pronounced with regard to pre-filled syringes.

More specifically it is relatively common in a number of 45 hospital settings for a number of syringes to be pre-loaded or pre-filled with certain medications by pharmacists or other authorized personnel, at an appropriate location, for subsequent dispensing of such prefilled syringes to one or more nursing stations or distribution areas and then, subse- 50 quently to the patient for direct use. The pharmacy or location where syringes are filled are often located in a remote part of the health facility relative to the location of the patient and the site of administration of the injection. From the foregoing, it may be understood that during the 55 course of loading a syringe with a drug, and also afterwards when a prefilled syringe is delivered to a nurse's station, the syringe can easily be handled by a number of different individuals. This, in turn, increases the chance for the syringe to become contaminated which in turn, could pos- 60 sibly result in introduction of a contaminated substance into the body tissues of a patient. Consequently, a high level of importance is associated with maintaining the sterility of a syringe, from the time of it being filled to the time of injection administration.

Also, in the case of a very expensive drug or addictive drug such as, but not limited to, morphine, there is some 2

danger that a prefilled syringe will be tampered with by person seeking to improperly gain access to the drug. A resulting danger also exists in the possibility of a saline solution or other substance being substituted for a dose of the medication intended to be administered. This could have extremely serious consequences to the patient, possibly including death. Therefore, the growing use of prefilled syringes raises problems relating to the determination of whether a prefilled syringe has been tampered with and and/or exposed to contamination. In order to address such problems, there is a need in the medical field for closures for syringes and/or other medical containers or administering devices, which maintain sterility while providing sufficient assurances that the contents of the syringe, medical con-15 tainer, administering devices, etc. have not been compromised.

Accordingly, tamper evident capabilities and/or structures associated with medical closures, covers, caps, etc. are important to protect the integrity of prefilled syringes, as well as other types of medical containers. Thus, and as a further example, vials are often filled with a previously prepared medication and are utilized in combination with a syringe. In use, the needle of the syringe penetrates and passes through a septum and into the interior of vial to establish access to the medication contained therein. As is well recognized in the medical profession, vials are medical containers recognized by appropriate governmental bodies and/or legislation (e.g., 503b) and hospital pharmacies for the containment of medications such as, but not limited to, medication prepared for the distribution of vaccines. As such, the open-end or access opening of the vial include a lid crimped or otherwise secured to the open end of the vial, wherein a penetrable septum may be structured as part of the vial lid.

In many cases, vials contain more than one dose of the contained medication or drug. After the first use, medical personnel commonly use tape placed over the septum and other portions of the vial lid to protect the contents of the vial. In other instances, and by way of example, a vial lid can also be utilized with a chemo vent needle, which is used to reconstitute medication at the hospital pharmacy. More specifically, vials used for chemotherapy drugs may contain a powder material. In order to accomplish conversion to a final drug it must be reconstituted, which in turn may involve breaking the original vial lid. To practice the aforementioned procedure, needles are required to prevent any toxic fumes escaping during the preparation and/or conversion. Once preparation is complete, an additional closure, cover, seal, etc. can be applied to the fully converted or prepared medication.

In order to address the problems and disadvantages of the type set forth above, especially with regard to protecting the contents of a vial containing one or more doses and/or the aforementioned chemotherapy medication, there is a need in the medical profession and related supply industries for a cover type seal structured to be secured to the vial and/or lid or cover of the vial in a manner which closes or seals the septum associated with the vial lid or cover. In addition, if any such proposed seal structure were developed, it would preferably also include tamper evident capabilities and/or structure which provides clear evidence that authorized or unauthorized prior access to the vial has been attempted.

### SUMMARY OF THE INVENTION

The present invention is directed to a cover or closure type seal structure for a vial and/or vial cover including a

housing. The housing includes a sidewall surrounding and at least partially defining the boundaries of the interior of the housing, wherein the interior of the housing is at least partially hollow. In addition, the sidewall terminates in a closed-end and an open-end which are substantially, oppositely disposed to one another. As will be explained in greater detail hereinafter, the open-end is dimensioned and configured to facilitate passage therethrough of the vial and a vial cover or lid, secured to the open-end or access opening of the vial.

Additional features of the seal structure include a retainer disposed within the interior of the housing. In at least one embodiment, the retainer is fixedly or integrally secured to the interior surface of the housing and more specifically, to the interior surface of the sidewall. Also, the retainer extends 15 there-from, inwardly towards the center of the open or hollow interior of the housing. In the one or more preferred embodiments of the retainer, as explained in greater detail hereinafter, it is disposed and structured for retaining engagement with the vial and/or the vial cover or lid.

It is emphasized that the term "vial", as used herein, is meant to include the vial itself as well as the cover or lid secured in overlying relation to the open end thereof. Moreover, as typically structured, the vial cover or lid may include a septum formed of a penetrable material which 25 facilitates passage of a needle of a syringe or other medical device to pass therethrough into direct contact and/or communication with the medication contained within the vial. Accordingly, when describing the retainer being disposed in retaining engagement with the vial it is to be recognized that 30 the actual "retaining engagement" may comprise the retainer being disposed, in whole or in part, in operative engagement with the vial itself or in the alternative with the vial cover and more specifically the periphery thereof, as will be described in greater detail hereinafter.

One or more embodiments of the retainer include it being at least partially defined by a plurality of retainer segments disposed in spaced, substantially coplanar relation to one another and collectively having an annular or circular configuration. As indicated, each of the retainer segments may 40 be fixedly or integrally secured to the interior surface of the sidewall and extend inwardly, substantially towards the center of the hollow interior of the housing. The plurality of retainer segments are cooperatively disposed and structured to establish the aforementioned "retaining engagement" of 45 the retainer with the vial and/or more specifically with an under portion of the outer periphery of the vial cover or lid.

The plurality of retainer segments may vary in size and configuration, and may be collectively dimensioned with a remainder of the housing to accommodate a vial and/or vial 50 cover or lid of different sizes. Further, in order to establish the intended "retaining engagement" with the vial each or at least a majority of the retainer segments have a cooperative configuration. In more specific terms, the undersurface portion of each of the retainer segments has a curved or beveled 55 configuration which facilitates a sliding engagement of the vial and/or vial cover or lid with such beveled undersurface. In addition, the sidewall of the housing is structured to include at least a minimal degree of outward flexure. As a result, as the vial and/or vial cover or lid enter through the 60 open end of the housing, they will be forced into the aforementioned sliding engagement with the beveled or curved undersurface portions of each or at least a majority of the plurality of retainer segments. Such forced, sliding engagement will cause at least a minimal outward flexure of 65 the housing, which in turn will allow passage of at least a portion of the vial, such as the vial cover or lid to pass

4

through the retainer and/or plurality of retainer segments and be operatively disposed between the retainer and the inner surface of the closed-end.

The aforementioned retaining engagement is further facilitated by the upper surface of each or at least a majority of the retainer segments being configured to establish an abutting, "removal preventing" engagement with the vial and/or vial cover or lid. More specifically, the upper surface of the one or more retainer segments may be substantially flat or planar and be operatively disposed immediately beneath and in engagement with the under portion of the neck of the vial and/or most probably the undersurface of the outer periphery of the vial cover and/or lid. It is to be noted that both the undersurface and upper surface of the plurality of retainer segments may vary in configuration from that specifically described herein. However, the configurations of the undersurface and the upper surface of the plurality of retainer segments should be sufficient to respectively facilitate the aforementioned sliding engagement of the under-20 surface of the retainer segments with the vial and the removal preventing engagement of the upper surface.

In addition, and in cooperation with the retainer, one or more preferred embodiments of the seal structure of the present invention further includes a pressure member. The pressure member has an at least minimally elongated configuration fixedly secured to the interior surface of the housing. As such, the pressure member includes a proximal end fixedly or integrally secured to the interior surface of the closed-end and extending downwardly or inwardly therefrom and in depending relation thereto. Moreover, the pressure member includes a distal end substantially oppositely located to the proximal end and in outwardly spaced relation from the interior surface of the closed-end of the housing. The dimension and configuration of the pressure member is 35 cooperatively determined relative to the location and structure of the retainer. Therefore, the distal end of the pressure member is disposed in substantially aligned relation to the retainer and/or plurality of retainer segments so as to be substantially coplanar or minimally spaced out of such a coplanar relation with the retainer.

Accordingly, the pressure member is disposed, configured and structured such that the aforementioned distal end thereof is disposed in a pressure exerting engagement with the vial cover or lid and more specifically with the septum of the vial. Due to the cooperative configurations and dispositions of the retainer and the pressure member, specifically including the distal end of the pressure member, the distal end will be disposed in the aforementioned pressure exerting, at least partially sealing engagement with the vial cover or lid and even more specifically the septum associated with the vial cover or lid. Concurrently the retainer, including the plurality of retainer segments, will be disposed in the retaining engagement comprising the engaging relation with an under portion of the outer periphery of the vial cover or lid. As a result, the vial and more specifically the vial cover or lid will be securely retained on the interior of the housing by virtue of a substantially clamping action and engagement between the retainer and/or plurality of retainer segments and the pressure member and/or distal end thereof exerting pressure on the septum or other portion of the vial cover or lid. Such clamping action will result in a sealing engagement and or action of the vial cover and in particular the sealing, pressure exerting engagement of the distal end of the pressure member with the septum.

With further reference to the pressure member, at least one embodiment includes the provision of an antiseptic or disinfected connected to, mounted on or otherwise opera-

tively associated with the distal end. Moreover, the antiseptic, disinfectant or like composition may be on or within a pad, wherein the pad is fixedly secured to the distal end at a location which facilitates its direct engagement with the exterior surface of the septum, during the pressure exerting 5 engagement of the pressure member/distal end with the vial cover. The aforementioned antiseptic, etc. pad may be made of a foam or other appropriate cushion-like material in order to engage the septum of the vial cover or lid without causing damage thereto.

As emphasized herein, the seal structure of the present invention includes tamper evident capabilities and/or structure. In at least one embodiment the tamper evident capability or structure includes a removable sidewall section 15 initially integral with a remainder of the sidewall. Further, the removable sidewall section includes a detachable connection to the remainder of the sidewall. Such a detachable connection may comprise at least one, but preferably two elongated weakened seam lines each disposed on a different 20 opposite side of the removable section and extending along a length thereof from the open end to the closed-end of the housing. The weakened seam lines are structured such that exertion of a pulling or other appropriately directed force on the removable section will cause a breakage, disconnection 25 after with reference to the accompanying drawings in which and/or separation of one or both of the weakened seam lines from the remainder of the sidewall, due to at least in part to reduction in the thickness of the sidewall along and entirety or at least a portion of the length of the weakened seam lines. In addition, the aforementioned pulling or other appropri- 30 ately directed force exerted on the removable sidewall section may be facilitated by the inclusion of a pull tab secured to the removable section preferably at one end thereof coincident with the open end of the housing. The pull tab will extend outwardly from the exterior surface of the 35 sidewall and otherwise be structured to facilitate the gripping or securement thereof by the hand or fingers of a user.

As should be apparent, partial or complete removal of the removable sidewall section will result in an inability to reconnect the replaceable sidewall section with remainder of 40 the housing. As a result, the housing will not be able to be reconnected in its original operative configuration. In turn, the retainer and the pressure member will not be able to be disposed in retaining, clamping, sealing engagement with the vial and/or the vial cover. Clear evidence of authorized 45 or unauthorized prior attempted access to or tampering with the vial will thereby be apparent.

Yet additional features of one or more embodiments of the seal structure of the present invention may include the dimensioning and configuring of the sidewall to include a 50 display field disposed on the exterior surface of the sidewall. In addition, a machine-readable code will be disposed on the display field. The machine-readable code may take a variety of different code configurations or structures including conventional barcode, quick response code (QR), RFID tag, etc. 55 As a result, the code may be an operative part of a tracking system or tracking capabilities associated with the seal structure of the present invention. Such a tracking system or tracking capability may be operative to facilitate the tracking of each such seal structure along a "path of distribution" from an initial point of manufacture, assembly, distribution, etc. to an endpoint such as a location of authorized use. Such a machine-readable code may be on or at least partially within the display field and include visually observable coded indicia providing adequate information or data 65 regarding the origin, structure, utilization, etc. of the seal structure.

6

These and other objects, features and advantages of the present invention will become clearer when the drawings as well as the detailed description are taken into consideration.

### BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the nature of the present invention, reference should be had to the following detailed description taken in connection with the accompanying drawings in which:

FIG. 1 is a perspective view of a tamper evident seal structure for a vial cover of the present invention.

FIG. 2 is an interior sectional view of the embodiment of FIG. 1.

FIG. 3 is an interior sectional view of another preferred embodiment of the present invention including an antiseptic component.

Like reference numerals refer to like parts throughout the several views of the drawings.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention will now be described more fully hereinillustrative embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

The present invention is directed to a cover or closure type seal structure generally indicated as 10 for a vial and/or vial cover (not shown in FIG. 1). The seal structure 10 includes a housing generally indicated as 12 having a sidewall 14 surrounding and at least partially defining the boundaries of the interior 16 of the housing 12. The interior 16 of the housing 12 is at least partially hollow, as represented in at least FIGS. 2 and 3. In addition, the sidewall 14 terminates in a closed-end 18 and an open-end 20 which are substantially oppositely disposed to one another. Further, the openend 20 is dimensioned and configured to facilitate passage therethrough of the vial and a vial cover or lid secured to the open-end or access opening of the vial.

Additional features of the seal structure 10 include a retainer generally indicated as 22 disposed within the interior 16 of the housing 12. In at least one embodiment, the retainer 22 is fixedly or integrally secured to the interior surface 24 of the sidewall and extends therefrom inwardly towards the center of the hollow interior 16 of the housing 12. In one or more embodiments and as will be explained in greater detail hereinafter, the retainer 22 is disposed and structured for retaining engagement with the vial and/or the vial cover or lid.

It is emphasized that the term "vial" as used herein is meant to include the vial itself as well as the cover or lid crimped or otherwise secured in overlying, covering relation to the open end thereof. Moreover, as typically structured, the vial cover or lid may include a septum formed of a penetrable material which facilitates passage of a needle of a syringe or other medical device to pass therethrough into direct contact, access and/or communication with the medication contained within the vial. Accordingly, when describing the retainer 22 being disposed in retaining engagement with the vial, it is to be recognized that the actual "retaining engagement" may comprise the retainer 22 being disposed,

in whole or in part, in operative engagement with the vial cover or lid and more specifically the periphery thereof, as described hereinafter.

One or more additional embodiments of the retainer 22 include it being at least partially defined by a plurality of 5 retainer segments 26 disposed in spaced relation to one another and collectively having an annular or circular configuration, as represented in FIGS. 2 and 3. As indicated, each of the retainer segments 26 may be fixedly or integrally secured to the interior surface 24 of the sidewall and extend 10 inwardly, substantially towards the center of the hollow interior 16 of the housing 12. The plurality of retainer segments 26 are cooperatively disposed and structured to establish the aforementioned "retaining engagement" of the retainer 22 with the vial and/or more specifically with an 15 under portion of the outer periphery of the vial cover or lid.

The plurality of retainer segments 26 may vary in size and configuration and may be collectively dimensioned with a remainder of the housing 12 to accommodate a vial and/or vial cover or lid of different sizes. Further, in order to 20 establish the intended "retaining engagement" with the vial, each or at least a majority of the retainer segments have a cooperative configuration. In more specific terms, the undersurface portion 28 of each of the retainer segments 26 has a curved or beveled configuration, as represented in FIGS. 2 25 and 3, which facilitates a sliding engagement of the vial and/or vial cover or lid with such beveled undersurface 28. In addition, the sidewall 14 of the housing is structured to include at least a minimal degree of flexibility in order to facilitate an outward flexure. As a result, as the vial and/or 30 vial cover or lid enter through the open end 20 of the housing 12, it will be forced into the aforementioned sliding engagement with the beveled or curved undersurface portion 28 of each or at least a majority of the plurality of retainer segments 26. Such forced, sliding engagement will cause at 35 least a minimal outward flexure of the sidewall 14 and/or the housing 12, which in turn will allow passage of at least a portion of the vial, such as the vial cover or lid to pass through and beyond the plurality of retainer segments 26 and be operatively disposed with in an interior portion 16' of the 40 housing 12, located between the retainer 22 and the inner surface of the closed-end 18'.

The aforementioned retaining engagement is further facilitated by the upper surface of each or at least a majority of the retainer segments 26 being configured to establish an 45 abutting, "removal preventing" engagement with the vial and/or vial cover or lid. More specifically, the upper surface 30 of the one or more retainer segments 26 may be substantially flat or planar and be operatively disposed immediately beneath and in engagement with the under portion of 50 the neck of the vial and/or most probably the undersurface of the outer periphery of the vial cover and/or lid. It is to be noted that both the undersurface portion 28 and upper surface portion 30 of the plurality of retainer segments 26 may vary in configuration from that specifically described 55 herein. However, the configurations of the undersurface 28 and the upper surface 30 of the plurality of retainer segments 26 should be sufficient to respectively facilitate the aforementioned sliding engagement of the undersurface 28 of the retainer segments 26 with the vial and the removal prevent- 60 ing, abutting engagement of the upper surface 30.

In addition, and in cooperation with the retainer 22, one or more preferred embodiments of the seal structure 10 of the present invention further includes a pressure member 34. The pressure member 34 has an at least minimally elongated 65 configuration fixedly secured to the interior surface of the housing 12. As such, the pressure member 34 includes a

8

proximal end 34' fixedly or integrally or fixedly secured to the interior surface 18' of the closed-end 18 and extending downwardly or inwardly therefrom and in depending relation thereto. Moreover, the pressure member 34 includes a distal end 34" substantially oppositely located to the proximal end 34' and in outwardly spaced relation from the interior surface 18' of the closed-end 18 of the housing 12. The dimension and configuration of the pressure member 34 is cooperatively determined relative to the location and structure of the retainer 22. Therefore, the distal end 34" of the pressure member 34 is disposed in substantially aligned relation to the retainer 22 and/or plurality of retainer segments 26 so as to be substantially coplanar or minimally spaced out of such a coplanar relation with the retainer 22.

Accordingly, the pressure member 34 is disposed, configured and structured such that the aforementioned distal end 34" thereof is disposed in a pressure exerting engagement with the vial cover or lid and more specifically with the septum of the vial lid. Due to the cooperative configurations and dispositions of the retainer 22 and the pressure member 34, specifically including the distal end 34" of the pressure member 34, the distal end 34" will be disposed in the aforementioned pressure exerting, at least partially sealing engagement with the vial cover or lid and the septum associated therewith. Concurrently, the retainer 22, including the plurality of retainer segments 26 will be disposed in the retaining engagement, which comprises the engaging relation of the upper surfaces 30 with an under portion of the outer periphery of the vial cover or lid. As a result, the vial and the vial cover or lid will be securely retained on the interior 16 of the housing 12 by virtue of a substantially clamping action and engagement between the retainer 22 and plurality of retainer segments 26 and the pressure member 34 and distal end 34" thereof exerting pressure on the septum or other portion of the vial cover or lid. Such clamping action will result in a sealing engagement and or action of the vial cover and in particular the sealing, pressure exerting engagement of the distal end 34" of the pressure member 34 with the septum.

With further reference to the pressure member 34 and as represented in FIG. 3, at least one embodiment includes the provision of an antiseptic or disinfectant composition and/or solution operatively associated with the distal end 34". Moreover, the antiseptic, disinfectant or like composition/solution may be on or within a pad 38 which is fixedly secured to the distal end 34" at a location which facilitates the direct engagement of the pad 38 with the exterior surface of the septum, during the pressure exerting engagement of the pressure member 34 or more specifically the distal end 34" with the vial cover.

As emphasized herein, the seal structure 10 of the present invention includes tamper evident capabilities and/or structure. Therefore, in at least one embodiment the tamper evident capability or structure includes a removable sidewall section 40 initially integral with a remainder of the sidewall 14. Further, the removable sidewall section 40 includes a detachable connection to the remainder of the sidewall 14. Such a detachable connection may be defined by and/or comprise at least one but preferably two elongated weakened seam lines 42 each disposed on a different opposite side of the removable section 40 and extending along a length thereof from the open end to the closed-end 18 of the housing 12. The weakened seam lines 42 are structured such that exertion of a pulling or other appropriately directed force on the removable section 40 will cause a breakage, disconnection and/or separation of one or both of the weakened seam lines 42 from the remainder of the sidewall 14,

g

due to at least in part to a reduction in the thickness of the sidewall 14 along and entirety or at least a portion of the length of the weakened seam lines 42. In addition, the aforementioned pulling or other appropriately directed force exerted on the removable sidewall section 40 may be facilitated by the inclusion of a pull tab 44 secured to the removable section 40 preferably at one end thereof which is aligned and/or coincident with the open end 20 of the housing 12. The pull tab 44 is fixedly secured to the removable sidewall section 40 and movable/removable there with as the removable section 40 breaks away from the remainder of the sidewall 14. As represented throughout the Figures, the pull tab 44 will extend outwardly from the exterior surface of the sidewall. To facilitate gripping of the pull tab 44, the exterior surface or other portion of the full tab 44 may be raised, roughened or otherwise structured, as at 48, to facilitate the gripping or securement thereof by the hand or fingers of a user.

As should be apparent, partial or complete removal of the removable sidewall section 40 will result in an inability to 20 reconnect the replaceable sidewall section 40 with remainder of the sidewall 14 or housing 12. As a result, the housing 12 and/or sidewall 14 will not be able to be "closed" or reconnected in its original operative configuration, as represented in at least FIG. 1. In turn, the retainer 22 and the 25 pressure member 34 will not be able to be disposed in retaining, clamping, sealing engagement with the vial and/or the vial cover, as described herein. Clear evidence of authorized or unauthorized prior attempted access to or tampering with the vial will thereby be apparent.

Yet additional features of one or more embodiments of the seal structure of the present invention may include the dimensioning and configuring of the sidewall 14 to include a display field 50 disposed on the exterior surface of the sidewall 14, as clearly represented in FIG. 1. In addition, a 35 machine-readable code 52 will be disposed on or within the display field 50. The machine-readable code 52 may take a variety of different code configurations or structures including a conventional barcode, a quick response code (QR), an RFID tag, etc. As a result, the code 52 may be an operative 40 part of a tracking system or tracking capabilities associated with the seal structure 10 of the present invention.

Yet another structural and operative feature which may be included in at least one embodiment of the seal structure 10 is represented in FIG. 1 and includes at least one but 45 preferably a plurality of openings 54 formed in the closedend 18 and disposed in communicating relation with the interior 16 and/or 16' of the housing 12.

Since many modifications, variations and changes in detail can be made to the described preferred embodiment of 50 the invention, it is intended that all matters in the foregoing description and shown in the accompanying drawings be interpreted as illustrative and not in a limiting sense. Thus, the scope of the invention should be determined by the appended claims and their legal equivalents.

What is claimed is:

- 1. A seal structure for a vial cover, said seal structure comprising:
  - a housing including a sidewall disposed in surrounding 60 relation to an interior of said housing,
  - said housing including an open-end and a closed-end oppositely disposed to one another,
  - a retainer fixedly disposed to the interior of said housing and structured for retaining engagement with a vial,
  - a pressure member disposed within said housing in attached relation to said closed-end,

**10** 

- said pressure member dimensioned and disposed in pressure exerting relation to the vial cover concurrent to said retaining engagement of said retainer with the vial cover, and
- said pressure member including a distal end, said distal end disposed in substantially aligned relation with said retainer, concurrent to pressure exerting engagement with the vial cover.
- 2. The seal structure as recited in claim 1 wherein said retainer is fixedly secured to an inner surface of said housing and extends inwardly therefrom in substantially surrounding relation to said pressure member.
  - 3. The seal structure as recited in claim 2 wherein said retainer comprises a plurality of retainer segments disposed in spaced relation to one another and collectively disposed in substantially surrounding relation to said pressure member.
  - 4. The seal structure as recited in claim 3 wherein each of said plurality of retainer segments includes a substantially beveled undersurface portion, said beveled undersurface portions collectively configured to facilitate sliding engagement of the vial through said retainer, into said retaining engagement.
  - 5. The seal structure as recited in claim 4 wherein each of said plurality of retainer segments include an upper surface configured to prevent passage of the vial out of said retaining engagement and through said open-end.
  - **6**. The seal structure as recited in claim **3** wherein each of said plurality of retainer segments include an upper surface configured to prevent passage of the vial out of said with retaining engagement.
  - 7. The seal structure as recited in claim 1 wherein said sidewall comprises a removable section, said removable section including a detachable connection to a remainder of said sidewall.
  - 8. The seal structure as recited in claim 7 wherein said removable connection comprises weakened seam lines disposed on opposite sides of and extending along a length of said removable section, from said open-end to said closed-
  - **9**. The seal structure as recited in claim **7** further comprising a pull tab, said pull tab fixedly connected to said removable section and removable there with upon detachment of said removable section from a remainder of said sidewall.
  - 10. The seal structure as recited in claim 9 wherein said pull tab is fixedly connected to said removable section at one end thereof adjacent said open-end; said pull tab extending transversely outward from said removable section.
  - 11. The seal structure as recited in claim 9 wherein said detachment of said removable section and said pull tab at least partially defines a tamper evident structure.
  - 12. The seal structure as recited in claim 7 further comprising tamper evident capabilities at least partially defined by a detachment of said removable section from a remainder of said sidewall.
  - 13. The seal structure as recited in claim 1 wherein said sidewall comprises a display field at least partially disposed on an exterior surface thereof, said display field including a machine-readable code.
  - 14. The seal structure as recited in claim 1 wherein said pressure member includes a proximal end fixedly connected to an interior surface of said closed-end and wherein said distal end is disposed into said interior of said housing, in spaced, depending relation to said closed-end.
  - 15. The seal structure as recited in claim 1 further comprising an antiseptic composition disposed on said pressure

member in engaging relation to the vial cover, concurrent to said retaining engagement of said retainer with said vial.

**16.** The seal structure as recited in claim **15** said antiseptic composition disposed on said distal end, in engaging relation to the vial cover.

17. The seal structure as recited in claim 15 wherein said antiseptic composition comprises an antiseptic composition disposed in a pad, said pad connected to a distal end of said pressure member and disposed in engageable ration to the vial cover.

\* \* \* \* \*