

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389002
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kypreos; Jean et al.

Systems and methods for multiple channel video encoding in a shared resource environment

Abstract

Disclosed herein are systems, devices, and methods for encoding a plurality of video channels in a shared resource environment. For a plurality of frames in the video channels, complexity metrics are computed, each estimating content complexity of a corresponding frame; and encoding budget metrics are computed, each defining an allocation of bits for encoding the corresponding frame. The encoding budget metrics of a particular video channel are computed to reduce anticipated encoding distortion in the particular video channel. A resource allocation is determined that allocates a portion of total resources of the shared resource environment for encoding each of the video channels. The resource allocation is determined to reduce anticipated encoding distortion across the video channels based on the encoding budgets and the complexity metrics. Encoding configurations are selected based on the resource allocation, each for encoding a corresponding video channel.

Inventors:	Kypreos; Jean (Rennes, FR), Ropert; Michael (Rennes, FR)
Applicant:	MK Systems USA Inc. (Wilmington, DE)
Family ID:	1000008751521
Assignee:	MK Systems USA Inc. (Wilmington, DE)
Appl. No.:	18/306772
Filed:	April 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230362380 A1	Nov. 09, 2023

Foreign Application Priority Data

EP	22305667	May. 04, 2022
----	----------	---------------

Publication Classification

Int. Cl.: **H04N19/00** (20140101); **H04N19/127** (20140101); **H04N19/14** (20140101)

U.S. Cl.:

CPC **H04N19/127** (20141101); **H04N19/14** (20141101);

Field of Classification Search

CPC: H04N (19/127); H04N (19/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5719632	12/1997	Hoang	375/E7.218	H04N 19/177
6160846	12/1999	Chiang	375/E7.14	H04N 19/517
6688714	12/2003	Bailleul	375/E7.184	H04N 19/61
9100509	12/2014	Jia	N/A	H04N 7/00
10171804	12/2018	Wang	N/A	H04N 19/127
10506266	12/2018	Yadav et al.	N/A	N/A
2006/0215760	12/2005	Monaco	375/E7.157	H04N 19/149
2008/0181308	12/2007	Wang	375/E7.125	H04N 19/156
2009/0073005	12/2008	Normile	341/51	H04N 19/103
2010/0124274	12/2009	Cheok	375/E7.125	H04N 19/70
2014/0119432	12/2013	Wang	375/240.2	H04N 19/177
2014/0226724	12/2013	Sorin	375/240.12	H04N 19/19
2014/0301460	12/2013	Karczewicz	375/240.12	H04N 19/18
2017/0164018	12/2016	Yadav	N/A	H04N 7/06
2017/0201752	12/2016	Wang	N/A	H04N 19/426
2017/0208335	12/2016	Ramamurthy	N/A	H04N 19/156
2018/0220133	12/2017	Pattichis	N/A	H04N 19/127
2020/0128242	12/2019	Aristarkhov	N/A	H04N 19/14
2024/0205415	12/2023	Huang	N/A	H04N 19/146

OTHER PUBLICATIONS

European Patent Office, Communication, Extended European Search Report issued for European Patent Application No. 22305667.2, dated Oct. 11, 2022, 11 pages. cited by applicant

Nunes et al. "Joint Bit-Allocation for Multi-Sequence H.264/AVC Video Coding Rate Control," Picture Coding Symposium, Lisboa, Portugal, Nov. 2007, 4 pages. cited by applicant

Huang et al. "Rate-Distortion-Complexity Optimized Coding Mode Decision for HEVC," IEEE Transactions on Circuits and Systems for Video Technology, vol. 30, No. 3, Mar. 2020, 15 pages. cited by applicant

Kannangara et al. "Computational Management of an H.264 Encoder," XP007902539, 25th Picture Coding Symposium, Beijing, China, 2006, 6 pages. cited by applicant

Lu et al. "Complexity-Aware Live Streaming System," IEEE International Conference on Image Processing, Sep. 2005, 4 pages. cited by applicant

Primary Examiner: Zhou; Zhihan

Attorney, Agent or Firm: Norton Rose Fulbright US LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is claiming priority to European Patent Application No. 22305667.2, titled "SYSTEMS AND METHODS FOR MULTIPLE CHANNEL VIDEO ENCODING IN A SHARED RESOURCE ENVIRONMENT," filed on May 4, 2022, the disclosure of which is incorporated

herein by reference in its entirety.

FIELD

(2) This disclosure relates to video data, and more particularly relates to processing multiple channels of video data in a shared resource environment.

BACKGROUND

(3) Streaming of video content to end users over the Internet, such as via over-the-top media services, typically requires processing such video content to be suitable for streaming. For example, one or more video channels containing video content may need to be encoded for streaming.

Encoding is resource intensive. The number of channels that can be processed on a given service platform (i.e., density) may have a significant impact on both capital and operating expenditures. Service platforms may make various trade-offs between density and video quality given available encoding resources, when allocating resources for encoding multiple video channels. Such trade-offs are often complex and may result, for example, degraded video quality, under-utilization of available resources, and/or other undesirable outcomes. Therefore, improvements in allocation of resources are desired.

SUMMARY

(4) In accordance with an aspect, there is provided a computer-implemented method for encoding a plurality of video channels in a shared resource environment. The method includes: for a plurality of frames in the plurality of video channels: computing a plurality of complexity metrics, each estimating content complexity of a corresponding frame of the plurality of frames; computing a plurality of encoding budget metrics, each of the encoding budget metrics defining an allocation of bits for encoding the corresponding frame, wherein the encoding budget metrics corresponding to the frames of a particular video channel of the plurality of video channels are computed to reduce anticipated encoding distortion in the particular video channel based on the complexity metrics corresponding to the frames of the particular video channel. The method also includes determining a resource allocation that allocates a portion of total resources of the shared resource environment for encoding each of the video channels, wherein the resource allocation is determined to reduce anticipated encoding distortion across the video channels based on the encoding budgets and the complexity metrics; and selecting a plurality of encoding configurations based on the resource allocation, each of the encoding configurations for encoding a corresponding video channel of the plurality of video channels.

(5) The determining the resource allocation may include allocating resources on a frame-by-frame basis.

(6) The selecting the encoding configuration may include selecting on a frame-by-frame basis.

(7) The complexity metrics may define a number of bits.

(8) The encoding budget metrics may define a number of bits.

(9) The resource allocation may define an allocated encoding time.

(10) The determining the resource allocation may be further based on a minimum resource allocation.

(11) The determining the resource allocation may be further based on a maximum resource allocation.

(12) The method may further include receiving an indicator of the total resources of the shared resource environment.

(13) The plurality of frames may correspond to a group of pictures in an encoded video stream.

(14) The method may further include encoding the video channels using the selected encoding configurations.

(15) The encoding may be constant bit rate encoding for each of the frames.

(16) In accordance with another aspect, there is provided a computer-implemented system for encoding a plurality of video channels in a shared resource environment. The system includes: at least one processor; memory in communication with said at least one processor; software code

stored in said memory. The software code when executed at said at least one processor causes the system to: for a plurality of frames in the plurality of video channels: compute a plurality of complexity metrics, each measuring content complexity of a corresponding frame of the plurality of frames; and compute a plurality of encoding budget metrics, each of the encoding budget metrics defining an allocation of bits for encoding the corresponding frame, wherein the encoding budget metrics corresponding to the frames of a particular video channel of the plurality of video channels are computed to reduce anticipated encoding distortion in the particular video channel based on the complexity metrics corresponding to the frames of the particular video channel. The software code when executed at said at least one processor also causes the system to determine a resource allocation that allocates a portion of total resources of the shared resource environment for encoding each of the video channels, wherein the resource allocation is determined to reduce anticipated encoding distortion across the video channels based on the encoding budgets and the complexity metrics; and select a plurality of encoding configurations based on the resource allocation, each of the encoding configurations for encoding a corresponding video channel of the plurality of video channels.

(17) The resource allocation may be determined on a frame-by-frame basis.

(18) The encoding configuration may be selected on a frame-by-frame basis.

(19) Many further features and combinations thereof concerning embodiments described herein will appear to those skilled in the art following a reading of the instant disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the Figures,

(2) FIG. 1 is a network diagram of a network environment of an example over-the-top (OTT) media service including a content processing system, in accordance with an embodiment;

(3) FIG. 2 is a schematic diagram of the content processing system of FIG. 1, in accordance with an embodiment;

(4) FIG. 3 is an entity and data flow diagram of the content processing system of FIG. 1, in accordance with an embodiment;

(5) FIG. 4 is a graph of a function for mapping resource allocations to encoding configurations, in accordance with an embodiment;

(6) FIG. 5 is a schematic diagram of various encoding variables and options for defining an encoding configuration, in accordance with an embodiment;

(7) FIG. 6 is a flowchart of example operations performed at the content processing system of FIG. 1, in accordance with an embodiment; and

(8) FIG. 7 is a schematic diagram for a computing device, in accordance with an embodiment.

(9) These drawings depict exemplary embodiments for illustrative purposes, and variations, alternative configurations, alternative components and modifications may be made to these exemplary embodiments.

DETAILED DESCRIPTION

(10) FIG. 1 is a diagram depicting a network environment of an example over-the-top (OTT) media service for delivering video content to end users, in accordance with an embodiment. The OTT media service includes a content processing system **100** that processes video content in manners disclosed herein to facilitate streaming to end users.

(11) As depicted, content processing system **100** is interconnected with a plurality of content sources **10** and a plurality of client devices **200**, by way of a communication network **50**. Content processing system **100** receives source content spanning a plurality of video channels from one or more of content sources **10** and processes such content to facilitate streaming to end users at client

devices **200**. Such processing includes, for example, encoding the content to be suitable for streaming to end users.

(12) Content processing system **100** has finite available resources (e.g., encoding time given available processors, memory, etc.) which must be shared among the video channels to encode such video channels. Thus, content processing system **100** may be considered a shared resource environment. As detailed herein, in some embodiments, content processing system **100** allocates available resources across the video channels in manners that take into account resource consumption needs of video content of the video channels while increasing overall resource utilization. For example, in some embodiments, available resources are allocated to ensure that video quality across the video channels meet minimum quality standards and also that no more resources are allocated for particular video channels than are required to meet such minimum standards.

(13) Embodiments of content processing system **100** may produce various technical effects and provide various technical advantages. For example, in some embodiments, encoding density (i.e., the number of video channels that can be encoded) at processing system **100** is increased, without a need to provide additional resources or unduly degrading video quality for end users. For example, in some embodiments, utilization rate at processing system **100** is increased, thereby reducing idle time and wasted resources.

(14) Referring again to FIG. **1**, in the depicted embodiment, each content source **10** may be a conventional source of video content (including audio-video content) such as, for example, a television station or an Internet live stream. For example, a content source **10** may receive linear content by way of a satellite signal, a radio frequency (RF) antenna signal, or a dedicated portion of network **50**. Content may be received by content processing system **100** in various formats and bitrates, where it is processed for streaming to client devices **200**.

(15) Each client device **200** is a device operable by an end user to play streamed video content. For example, a client device **200** may be a digital media player, a set-top box, a video game console, each connected to a display device for playing streamed content. A client device **200** may also be smart TV device or a personal computing device such as a laptop computer, a tablet computer or a smartphone, each having an integrated display screen.

(16) Network **50** may include a packet-switched network portion, a circuit-switched network portion, or a combination thereof. Network **50** may include wired links, wireless links such as radio-frequency links or satellite links, or a combination thereof. Network **50** may include wired access points and wireless access points. Portions of network **50** could be, for example, an IPv4, IPv6, X.25, IPX or similar network. Portions of network **50** could be, for example, a GSM, GPRS, 3G, LTE or similar wireless networks. Network **50** may include or be connected to the Internet. When network **50** is a public network such as the public Internet, it may be secured as a virtual private network.

(17) In the depicted embodiment, portions of network **50** interconnecting content processing system **100** with client devices **200** are adapted for transmission of video streams (including audio-video streams) over HTTP. In other embodiments, other protocols may be used for transmission of video streams.

(18) FIG. **1** is a high-level schematic of content processing system **100**, in accordance with an embodiment.

(19) As depicted, content processing system **100** includes a complexity estimator **102**, a rate controller **104**, a resource allocator **106**, an encoder configurator **108**, and an encoder **110**.

(20) Content processing system **100** is configured to process data of video content spanning a plurality video channels, where each video channel refers to a specific portion of the video content. Each video channel includes a plurality of frames (e.g., pictures) defining its portion of the video content.

(21) In the description herein, a video channel of the plurality of video channels may be referred to

as a channel i , where i is a numerical index that may have a value, for example, between 1 and I , where I is the total number of video channels. Further, a frame of the plurality of frames of a particular video channel may be referred to as a frame t , where t is a numerical index that may have a value, for example, between 1 and $T_{\text{sub},i}$, where $T_{\text{sub},i}$ is the total number of frames in the particular video channel i .

(22) In processing the plurality of video channels, content processing system **100** uses resources shared for the video channels. Content processing system **100** allocates the shared resources across the video channels taking into account the resource consumption requirement of each of the video channels. The resource consumption requirement of a video channel depends at least in part on the content complexity of the frames defining the video content of that video channel. As used herein, complexity refers to an encoding cost of a particular frame in bits, i.e., the number of bits required to encode that frame.

(23) Complexity estimator **102** analyzes the frames of each of the video channels to estimate content complexity on a frame-by-frame basis. In particular, complexity estimator **102** computes a plurality of complexity metrics $\alpha_{\text{sub},it}$, each estimating content complexity of a particular frame t of a particular video channel i . The set of frames of a video channel i may correspond, for example, to a group of pictures (GOP).

(24) Complexity estimator **102** computes a complexity metric $\alpha_{\text{sub},it}$ by estimating the spatial and/or temporal complexity of a particular frame t of video channel i . In some embodiments, computing a complexity metric $\alpha_{\text{sub},it}$ takes into account the type of encoder expected to be used (e.g., Versatile Video Codec (VVC), H.265/High Efficiency Video Coding (HEVC), H.264/Advanced Video Coding (AVC), MPEG-2, or the like). In some embodiments, computing a complexity metric $\alpha_{\text{sub},it}$ includes estimating the motion vectors in the frame t . In some embodiments, computing a complexity metric $\alpha_{\text{sub},it}$ includes predicting the type of frame t , e.g., whether the frame t is an inter-coded frame, an intra-coded frame, or the like.

(25) In one specific embodiment, complexity estimator **102** computes a complexity metric $\alpha_{\text{sub},it}$ in accordance with the computations described in U.S. Patent Publication 2014/0226724, entitled “System and Method for the Dynamic Reduction of the Entropy of a Signal Upstream to a Data Compression Device”, the contents of which are hereby incorporated by reference.

(26) Because complexity estimator **102** is configured to analyze complexity of frames ahead of when they need to be encoded, it may also be referred to as a “look ahead.”

(27) FIG. 3 is an entity and dataflow diagram for content processing system **100**, in accordance with an embodiment. As depicted, complexity estimator **102** is configured to be instantiated in multiple instances, and each instance may be referred to as complexity estimator **102-1** . . . **102-i**, and so on. In the depicted embodiment, each instance of complexity estimator **102** is dedicated to a corresponding video channel and computes the complexity metrics for that video channel. So, for example, the instance of complexity estimator **102-i** computes the complexity metrics for the corresponding video channel i . The total number of instances of complexity estimator **102** may be equal to the total number of video channels. During operation, two or more instances of complexity estimator **102** may operate in parallel.

(28) Rate controller **104** controls a budget in bits (e.g., a bitrate) allocated for encoding the video channels by computing encoding budgets on a frame-by-frame basis. Rate controller **104** receives the complexity metrics $\alpha_{\text{sub},it}$ from complexity estimator **102** and computes a plurality of encoding budgets $R_{\text{sub},it}$. Each of the encoding budgets $R_{\text{sub},it}$ defines an allocation of bits for encoding a particular frame t of a particular video channel i , computed based on the complexity metric $\alpha_{\text{sub},it}$ for that particular frame t of that particular video channel i .

(29) Rate controller **104** computes the encoding budgets $R_{\text{sub},it}$ to reduce anticipated encoding distortion, i.e., anticipated errors or differences between the original video contents and the final video contents, e.g., after encoding at content processing system **100**. In some embodiments, anticipated encoding distortion may be modeled and predicted as a mean-square-error of

differences in pixel values between the original video contents and the final video contents after encoding. In some embodiments, anticipated encoding distortion may be modeled and predicted using a Structural Similarity Index (SSIM) or other perception-based metrics. In one specific embodiment, anticipated encoding distortion may be modeled and predicted in accordance with the models and calculations described in U.S. Patent Publication 20210160544, entitled “Systems and methods for measuring visual quality degradation in digital content”, the contents of which are hereby incorporated by reference.

(30) The encoding budgets $R_{sub,i}$ are computed with the following constraints:

$$(31) \begin{cases} \min(\text{Math}_t D_{it}) \\ s.t. \text{Math}_t R_{it} = R_i \end{cases}$$

where $D_{sub,it}$ is the anticipated distortion caused by encoding of particular frame t of a particular video channel i , and $R_{sub,i}$ is a total budget in bits allocated to encode the plurality of frames of a video channel i . The value of $R_{sub,i}$ may be pre-determined, e.g., based on available resources (e.g., bandwidth) of content processing system **100** or and/or end user preferences. The value of $R_{sub,i}$ may be pre-determined based on one or more characteristics of the video content of the particular video channel i . For example, the value of $R_{sub,i}$ may be pre-determined based on a desired overall bitrate for the video channel i . The desired bitrate may be based on, for example, the pixel resolution of the video content. The value of $R_{sub,i}$ may be pre-determined based on, for example, the type of content; for example, a higher budget may be desirable for sports content and a lower budget may be desirable for news content. Of note, the total distortion $\sum_{sub,t} D_{sub,it}$ of a plurality of frames of a particular video channel i is minimized, wherein the plurality of frames may belong, for example, to a given GOP.

(32) Given the complexities metrics $\alpha_{sub,it}$, the encoding budget for each frame is computed as:

$$(33) R_{it} = R_i \frac{\alpha_{it}}{\text{Math}_t \alpha_{it}^r}$$

where r is a pre-defined constant. In the depicted embodiment, r may be defined to have a value of $\frac{1}{3}$. In other embodiments, the value of r may vary, for example, between 0 and 1. The value of r may be selected, for example, based on a particular distortion model used at content processing system **100**. For example, the above example value of r is selected for an MSE distortion model. In another embodiment, r may be defined to have a value of 0.5, for example.

(34) Referring again to FIG. 3, similar to complexity estimator **102**, rate controller **104** is configured to be instantiated in multiple instances, and each instance may be referred to as rate controller **104-1** . . . **104-i**, and so on. In the depicted embodiment, each instance of rate controller **104** is dedicated to a corresponding video channel, and cooperates with a corresponding instance of complexity estimator **102** to compute the encoding budget for that video channel. So, for example, the instance of complexity estimator **104-i** receives complexity metrics $\alpha_{sub,it}$ for each frame of corresponding channel i from complexity estimator **102-i**, and computes the encoding budget for each frame of the corresponding video channel i . The total number of instances of rate controller **104** may be equal to the total number of video channels. During operation, two or more instances of rate controller **104** may operate in parallel.

(35) Resource allocator **106** determines a resource allocation that allocates a portion of total resources of the shared resource environment for encoding video content in the video channels. The resource allocation defines a quantity of a resource that will be consumed to encode the video content, which may be, for example, an encoding time. In other embodiments, resource allocator **106** may be configured to allocate other types of resources necessary for processing video data (e.g., volatile memory, non-volatile memory, cache, bandwidth, electrical power, monetary resources, etc.).

(36) Referring again to FIG. 3, resource allocator **106** receives the complexities metrics $\alpha_{sub,it}$ from each of the instances of complexity estimator **102** and receives encoding budgets $R_{sub,it}$ from each of the instances of rate controller **104**.

(37) Based on the received complexities metrics $\alpha_{\text{sub},it}$ and encoding budgets $R_{\text{sub},it}$, resource allocator **106** determines a resource allocation. In the depicted embodiment, the resource allocation is determined on a frame-by-frame basis, i.e., the resource allocation includes a plurality of per-frame resource allocations, $C_{\text{sub},it}$, each defining resources available to be consumed for a particular frame t in a particular video channel i .

(38) The per-frame resource allocations $C_{\text{sub},it}$ are computed with the following constraints:

$$\begin{aligned} & \min(\text{Math}_i D_{it}) \\ (39) \quad & \left\{ \begin{array}{l} s.t. \text{Math}_t R_{it} = R_i \\ \text{and } \text{Math}_i C_{it} = C \\ C_{\min} \leq C_{it} \leq C_{\max} \end{array} \right. \end{aligned}$$

where C is a resource capacity (e.g., total resources allocable) for encoding at content processing system **100**, and $C_{\text{sub},\min}$ and $C_{\text{sub},\max}$ are minimum and maximum resources allocable for a frame, respectively. The values of $C_{\text{sub},\min}$ and $C_{\text{sub},\max}$ may be pre-defined.

(40) The anticipated encoding distortion $D_{\text{sub},it}$ is computed in manners similar to that described for rate controller **104**. In contrast to the distortion minimization performed by rate controller **104**, the distortion minimization performed by resource allocator **106** is such that distortion is also minimized across the video channels (e.g., with a summation over i).

(41) Given the complexity metrics $\alpha_{\text{sub},it}$ and the encoding budgets $R_{\text{sub},it}$, the per-frame resource allocation defined as:

$$(42) \quad C_{it} = C \frac{\alpha_{it}^p R_{it}^{-q}}{\text{Math}_i \alpha_{it}^p R_{it}^{-q}}$$

where p and q are two constants. In the depicted embodiment, p may be defined to have a value of 0.5 and q may be defined to have a value of 1. In other embodiments, the value of p may vary, for example, between 0 and 2, and the value of q may vary, for example, between 0 and 2. The values of p and q may be selected, for example, based on a particular distortion model used at content processing system **100**. For example, the above example values of p and q are selected for an MSE distortion model.

(43) In some embodiments, the determination of complexity metrics $\alpha_{\text{sub},it}$ may utilize inequality constraints. In one particular embodiment, the utilization of inequality constraints may adapt methodologies described in M. Blestel, M. Ropert and W. Hamidouche, "Generic statistical multiplexer with a parametrized bitrate allocation criterion," 2016 IEEE International Conference on Image Processing (ICIP), Phoenix, AZ, 2016, pp. 2127-2131.

(44) Encoding configurator **108** determines encoding configurations for encoding video content in the video channels. An encoding configuration includes a selection of various encoding variables, parameters, algorithms, features, or the like, that are used by encoder **110** to encode video content. In the depicted embodiment, encoding configurator **108** determines encoding configurations on a frame-by-frame basis to provide a plurality of per-frame configurations $E_{\text{sub},it}$, each for encoding a particular frame t in a particular video channel i . Each $E_{\text{sub},it}$ is selected based on a per-frame resource allocation $C_{\text{sub},it}$.

(45) Referring again to FIG. 3, encoding configurator **108** receives the resource allocations $C_{\text{sub},it}$ from resource allocator **106**. Encoding configurator **108** applies a mapping function f that maps a particular value of a resource allocation $C_{\text{sub},it}$ to an encoding configuration $E_{\text{sub},it}$ that will consume the resource allocated for a particular frame t of a particular video channel i . The mapping function f , may be expressed, for example, as $E_{\text{sub},it}=f(C_{\text{sub},it})$. In some embodiments, the mapping function may be defined using empirical data. In some embodiments, the mapping function may be defined using a suitable mathematical model.

(46) FIG. 4 depicts an example mapping f , in accordance with an embodiment. As depicted, $C_{\text{sub},\min}$ is mapped to a minimal encoding configuration that ensures a minimum video quality for a video channel after encoding. The minimum video quality (and hence the corresponding

minimal encoding configuration) may be set, for example, according to a particular platform, a particular product, a particular type of client device **200**, or the like.

(47) As depicted, C.sub.max is mapped to a maximal encoding configuration to limit resource consumption. The maximal encoding configuration may be set based on, for example, total resources of a particular shared resource environment, and the total number of video channels to be encoded using the environment's shared resources.

(48) Various encoding configurations (e.g., a minimal configuration, a maximal configuration, one or more intermediate configurations) may be defined based on encoders available at content processing system **100** (e.g., available at encoder **110**).

(49) FIG. 5 shows schematically various encoding variables and options that may be set to define an encoding configuration E.sub.it, in accordance with an embodiment. For example, these variations and options may include: (A) various algorithms implemented by an encoder (e.g., algorithms for motion estimation to predict motion vectors between two frames); (B) various parameters of an encoder (e.g., the number of frames of a particular type such as a B frame); (C) various decisions to be made by an encoder (e.g., a decision based on SAD (sum absolute of difference), or RDO (rate distortion optimization)) (D) when the encoder utilizes a neural network such as a deep learning network for feature extraction, various features that can be extracted (e.g., spatial activity, gradients, motion vectors, or the like).

(50) Given a set of possible encoding configurations, encoding configurator **108** selects an appropriate encoding configuration E.sub.it on a frame-by-frame basis, i.e., each for encoding a particular frame t of a particular video channel i.

(51) Encoder **110** encodes video content of the video channels. Encoder **110** may implement one or more conventional encoding algorithms. For example, encoder **110** may implement one or more of VVC, H.265/HEVC, H.264/AVC, MPEG-2 encoding, or the like. In the depicted embodiment, encoder **110** implements a constant bit rate (CBR) encoding algorithm, e.g., capable of encoding a frame at a prescribed bitrate defined in an encoding budget R.sub.it.

(52) Referring again to FIG. 3, encoder **110** is configured to be instantiated in multiple instances, and each instance may be referred to as encoder **110-1**, . . . **110-i**, and so on. In the depicted embodiment, each instance of encoder **110** is dedicated to encoding video content of a corresponding video channel. So, for example, the instance of encoder **110-i** receives encoding configurations E.sub.it for corresponding channel i from encoding configurator **108** and receives encoding budgets R.sub.it for corresponding channel i from an instance of rate controller **104-i**. Based on the received encoding configurations E.sub.it and encoding budgets R.sub.it encoder **110-i** encodes the frames of video channel i. The total number of instances of encoder **110** may be equal to the total number of video channels. During operation, two or more instances of encoder **110** may operate in parallel.

(53) Content processing system **100** is configured to transmit video content encoded by encoder **110** to one or more client devices **200**.

(54) In some embodiments, content processing system **100** does not include encoder **110**. In such embodiments, content processing system **100** may provide one or more encoding configurations to another system that performs encoding.

(55) Each of complexity estimator **102**, rate controller **104**, resource allocator **106**, encoder configurator **108**, and encoder **110** may be implemented using conventional programming languages such as Java, J#, C, C++, C#, Perl, Visual Basic, Ruby, Scala, etc. These components of system **100** may be in the form of one or more executable programs, scripts, routines, statically/dynamically linkable libraries, or the like.

(56) Electronic data store **114** may include a combination of non-volatile and volatile memory. In some embodiments, electronic data store **114** stores a plurality of pre-defined encoding configurations for selection for encoder configurator **108**.

(57) The operation of content processing system **100** is further described with reference to the

flowchart depicted in FIG. 6. Content processing system **100** performs the example operations depicted at blocks **600** and onward, in accordance with an embodiment.

(58) Operation begins when content processing system **100** receives video content for a plurality of video channels, for encoding.

(59) At block **602**, complexity estimator **102** computes a plurality of complexity metrics $\alpha_{sub,i,t}$, each estimating content complexity of a corresponding frame t of a corresponding video channel i . Instances of complexity estimator **102** may be instantiated as required, e.g., to provide an instance dedicated to each video channel i .

(60) At block **604**, rate controller **104** computes a plurality of encoding budget metrics $R_{sub,i,t}$, each defining an allocation of bits for encoding the corresponding frame t of a corresponding video channel i . Each of the encoding budget metrics corresponding to the frames of a particular video channel i are computed to reduce anticipated encoding distortion in the particular video channel i based on the complexity metrics $\alpha_{sub,i,t}$ corresponding to the frames of the particular video channel i . In some embodiments, rate controller **104** may receive an indicator of each $R_{sub,i}$ (total budget in bits allocated to encode the plurality of frames of a video channel i).

(61) Instances of rate controller **104** may be instantiated as required, e.g., to provide an instance dedicated to each video channel i .

(62) At block **606**, resource allocator **106** determines a resource allocation that allocates a portion of total resources of the shared resource environment for encoding each of the video channels. The resource allocation is determined to reduce anticipated encoding distortion across the video channels based on the encoding budgets $R_{sub,i,t}$ and the complexity metrics $\alpha_{sub,i,t}$. The resource allocation may be performed on a frame-by-frame basis, and thus include a plurality of per-frame resource allocations, $C_{sub,i,t}$, each defining resources available to be consumed for encoding a particular frame t in a particular video channel i . In some embodiments, encoding configurator **108** receives an indicator of $C_{sub,min}$ (minimum resources allocable for a frame) for determining resource allocations. In some embodiments, encoding configurator **108** receives an indicator of $C_{sub,max}$ (maximum resources allocable for a frame) for determining resource allocations. In some embodiments, encoding configurator **108** receives an indicator of C (i.e., capacity or total resources allocable) for determining resource allocations.

(63) At block **608**, encoding configurator **108** selects an encoding configuration for each of the video channels based on the resource allocation determined by resource allocator **106**. The selection of encoding configurations may be performed on a frame-by-frame basis, and thus include a plurality of per-frame encoding configurations $E_{sub,i,t}$.

(64) Optionally, encoder **110** may encode the video content of the video channels using the encoding configurations.

(65) Instances of encoder **110** may be instantiated as required, e.g., to provide an instance dedicated to each video channel i .

(66) It should be understood that steps of one or more of the blocks depicted in FIG. 6 may be performed in a different sequence or in an interleaved or iterative manner. Further, variations of the steps, omission or substitution of various steps, or additional steps may be considered.

(67) In some embodiments, the blocks depicted in FIG. 6 may be performed for each of the frames in each of the video channels. In some embodiments, these blocks may be performed for a subset of the frames. In one example, the blocks are performed for subset of frames spanning a particular time period. In another example, some blocks (e.g., blocks **602** and/or blocks **604**) are only performed for certain frames (e.g., every second frame, every tenth frame, or the like) based on an assumption that the content complexity and hence the encoding budget is unlikely to change significantly within such a range.

(68) FIG. 7 is a schematic diagram of computing device **700** which may be used to implement content processing system **100**, in accordance with an embodiment.

(69) As depicted, computing device **700** includes at least one processor **702**, memory **704**, at least

one I/O interface **706**, and at least one network interface **708**.

(70) Each processor **702** may be, for example, any type of general-purpose microprocessor or microcontroller, a digital signal processing (DSP) processor, an integrated circuit, a field programmable gate array (FPGA), a reconfigurable processor, a programmable read-only memory (PROM), or any combination thereof.

(71) Memory **704** may include a suitable combination of any type of computer memory that is located either internally or externally such as, for example, random-access memory (RAM), read-only memory (ROM), compact disc read-only memory (CDROM), electro-optical memory, magneto-optical memory, erasable programmable read-only memory (EPROM), and electrically-erasable programmable read-only memory (EEPROM), Ferroelectric RAM (FRAM) or the like.

(72) Each I/O interface **706** enables computing device **700** to interconnect with one or more input devices, such as a keyboard, mouse, camera, touch screen and a microphone, or with one or more output devices such as a display screen and a speaker.

(73) Each network interface **708** enables computing device **700** to communicate with other components, to exchange data with other components, to access and connect to network resources, to serve applications, and perform other computing applications by connecting to a network (or multiple networks) capable of carrying data including the Internet, Ethernet, plain old telephone service (POTS) line, public switch telephone network (PSTN), integrated services digital network (ISDN), digital subscriber line (DSL), coaxial cable, fiber optics, satellite, mobile, wireless (e.g. Wi-Fi, WiMAX), SS7 signaling network, fixed line, local area network, wide area network, and others, including any combination of these.

(74) For simplicity only, one computing device **700** is shown but system **100** may include multiple computing devices **700**. The computing devices **700** may be the same or different types of devices. The computing devices **700** may be connected in various ways including directly coupled, indirectly coupled via a network, and distributed over a wide geographic area and connected via a network (which may be referred to as “cloud computing”).

(75) In such a cloud environment, as capacity may vary dynamically, the quantity of processes or memory (or other resources) may be pre-defined to provide a measure of allocable resources such as C.

(76) For example, a computing device **700** may be a server, network appliance, set-top box, embedded device, computer expansion module, personal computer, laptop, personal data assistant, cellular telephone, smartphone device, UMPC tablets, video display terminal, gaming console, or any other computing device capable of being configured to carry out the methods described herein.

(77) In some embodiments, a computing device **700** may function as a client device **200**.

(78) The foregoing discussion provides many example embodiments of the inventive subject matter. Although each embodiment represents a single combination of inventive elements, the inventive subject matter is considered to include all possible combinations of the disclosed elements. Thus if one embodiment comprises elements A, B, and C, and a second embodiment comprises elements B and D, then the inventive subject matter is also considered to include other remaining combinations of A, B, C, or D, even if not explicitly disclosed.

(79) The embodiments of the devices, systems and methods described herein may be implemented in a combination of both hardware and software. These embodiments may be implemented on programmable computers, each computer including at least one processor, a data storage system (including volatile memory or non-volatile memory or other data storage elements or a combination thereof), and at least one communication interface.

(80) Program code is applied to input data to perform the functions described herein and to generate output information. The output information is applied to one or more output devices. In some embodiments, the communication interface may be a network communication interface. In embodiments in which elements may be combined, the communication interface may be a software communication interface, such as those for inter-process communication. In still other

embodiments, there may be a combination of communication interfaces implemented as hardware, software, and combination thereof.

(81) Throughout the foregoing discussion, numerous references will be made regarding servers, services, interfaces, portals, platforms, or other systems formed from computing devices. It should be appreciated that the use of such terms is deemed to represent one or more computing devices having at least one processor configured to execute software instructions stored on a computer readable tangible, non-transitory medium. For example, a server can include one or more computers operating as a web server, database server, or other type of computer server in a manner to fulfill described roles, responsibilities, or functions.

(82) The technical solution of embodiments may be in the form of a software product. The software product may be stored in a non-volatile or non-transitory storage medium, which may be a compact disk read-only memory (CD-ROM), a USB flash disk, or a removable hard disk. The software product includes a number of instructions that enable a computer device (personal computer, server, or network device) to execute the methods provided by the embodiments.

(83) The embodiments described herein are implemented by physical computer hardware, including computing devices, servers, receivers, transmitters, processors, memory, displays, and networks. The embodiments described herein provide useful physical machines and particularly configured computer hardware arrangements.

(84) Of course, the above described embodiments are intended to be illustrative only and in no way limiting. The described embodiments are susceptible to many modifications of form, arrangement of parts, details and order of operation. The disclosure is intended to encompass all such modification within its scope, as defined by the claims.

Claims

1. A computer-implemented method for encoding a plurality of video channels in a shared resource environment, the method comprising: for a plurality of frames in the plurality of video channels: computing a plurality of complexity metrics, each estimating content complexity of a corresponding frame of the plurality of frames; computing a plurality of encoding budget metrics, each of the encoding budget metrics defining an allocation of bits for encoding the corresponding frame, wherein the encoding budget metrics corresponding to the frames of a particular video channel of the plurality of video channels are computed to reduce anticipated encoding distortion predicted to exist after encoding the particular video channel, wherein the encoding budget metrics are computed based on the complexity metrics corresponding to the frames of the particular video channel, and wherein the anticipated encoding distortion comprises anticipated errors or differences predicted to exist between the frames of the particular video channel and the frames of the particular video channel after being encoded; determining a resource allocation that allocates a portion of total resources of the shared resource environment for encoding each of the video channels, wherein the resource allocation is determined to reduce the anticipated encoding distortion across the video channels based on the encoding budgets and the complexity metrics; and selecting a plurality of encoding configurations based on the resource allocation, each of the encoding configurations comprising a selection of a plurality of encoding variables for encoding a corresponding video channel of the plurality of video channels.
2. The computer-implemented method of claim 1, wherein said determining the resource allocation includes allocating resources on a frame-by-frame basis.
3. The computer-implemented method of claim 1, wherein said selecting the encoding configuration includes selecting on a frame-by-frame basis.
4. The computer-implemented method of claim 1, wherein the complexity metrics define a number of bits.
5. The computer-implemented method of claim 1, wherein the encoding budget metrics define a

number of bits.

6. The computer-implemented method of claim 1, wherein the resource allocation defines an allocated encoding time.

7. The computer-implemented method of claim 1, wherein said determining the resource allocation is further based on a minimum resource allocation.

8. The computer-implemented method of claim 1, wherein said determining the resource allocation is further based on a maximum resource allocation.

9. The computer-implemented method of claim 1, further comprising: receiving an indicator of the total resources of the shared resource environment.

10. The computer-implemented method of claim 1, wherein the plurality of frames correspond to a group of pictures in an encoded video stream.

11. The computer-implemented method of claim 1, further comprising: encoding the video channels using the selected encoding configurations and the encoding budget metrics.

12. The computer-implemented method of claim 11, wherein said encoding is constant bit rate encoding for each of the frames.

13. A computer-implemented system for encoding a plurality of video channels in a shared resource environment, the system comprising: at least one processor; memory in communication with said at least one processor; software code stored in said memory, which when executed at said at least one processor causes the system to: for a plurality of frames in the plurality of video channels: compute a plurality of complexity metrics, each measuring content complexity of a corresponding frame of the plurality of frames; compute a plurality of encoding budget metrics, each of the encoding budget metrics defining an allocation of bits for encoding the corresponding frame, wherein the encoding budget metrics corresponding to the frames of a particular video channel of the plurality of video channels are computed to reduce anticipated encoding distortion predicted to exist after encoding the particular video channel, wherein the encoding budget metrics are computed based on the complexity metrics corresponding to the frames of the particular video channel, and wherein the anticipated encoding distortion comprises anticipated errors or differences predicted to exist between the frames of the particular video channel and the frames of the particular video channel after being encoded; determine a resource allocation that allocates a portion of total resources of the shared resource environment for encoding each of the video channels, wherein the resource allocation is determined to reduce the anticipated encoding distortion across the video channels based on the encoding budgets and the complexity metrics; and select a plurality of encoding configurations based on the resource allocation, each of the encoding configurations comprising a selection of a plurality of encoding variables for encoding a corresponding video channel of the plurality of video channels.

14. The computer-implemented system of claim 13, wherein the resource allocation is determined on a frame-by-frame basis.

15. The computer-implemented system of claim 13, wherein the encoding configuration is selected on a frame-by-frame basis.
