

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260717

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Stransky-Heilkron; Philippe

SECURED HOME NETWORK

Abstract

Malware detection logic executed by a secured device residing in a home network may receive a message from an unsecured device of a first unsecured network and intended for a destination device of the home network, the destination device comprising a security client. The malware detection logic may establish a secure communication channel between the malware detection logic of the secured device and the security client of the destination device. The malware detection logic may execute a validation test on the message to determine that the message includes malware. The malware detection logic may report an alarm to the security client of the destination device. The malware detection logic may transmit information related to the malware to a cloud computing server. The malware detection logic may prevent an application associated with the destination device from processing the message.

Inventors: Stransky-Heilkron; Philippe (Cheseaux, CH)

Applicant: NAGRAVISION SARL (CHESEAUX-SUR-LAUSANNE, CH)

Family ID: 1000008563479

Assignee: NAGRAVISION SARL (CHESEAUX-SUR-LAUSANNE, CH)

Appl. No.: 19/192604

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 18495956 20231027 parent-grant-document US 12316670 child US 19192604

parent US continuation 17894276 20220824 parent-grant-document US 11838315 child US 18495956

parent US continuation 16903712 20200617 parent-grant-document US 11457039 child US 17894276

parent US continuation 16281963 20190221 parent-grant-document US 10728278 child US

Publication Classification

Int. Cl.: H04L9/40 (20220101); H04W12/12 (20210101); H04W12/128 (20210101)

U.S. Cl.:

CPC H04L63/145 (20130101); H04L63/1416 (20130101); H04W12/12 (20130101); H04W12/128 (20210101);

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/495,956 filed Oct. 27, 2023, which is a continuation of U.S. patent application Ser. No. 17/894,276 filed Aug. 24, 2022, which is a continuation of U.S. patent application Ser. No. 16/903,712 filed Jun. 17, 2020, which is a continuation of U.S. patent application Ser. No. 16/281,963 filed Feb. 21, 2019, which is a continuation of U.S. patent application Ser. No. 14/976,441 filed Dec. 21, 2015, all of which are incorporated herein by reference in their entirety for all purposes.

TECHNICAL FIELD

[0002] The present disclosure is generally related to home networks, and is more specifically related to systems and methods for providing protection to home networks.

BACKGROUND

[0003] Many homes are equipped with home networks. Most frequently, the home network may be an IEEE 802.11 (WiFi) network provided by and installed by a cable television provider, a fiber optic telephone service provider, a satellite network service provider, etc. Devices may be connected in the home network through a router, which provides connectivity with one or more external networks. The router may be provided with encryption software for encrypting messages with compatible devices that also employ the same type of encryption using an encryption client.

[0004] Unfortunately, home networks provided with encryption software may still be subject to attacks, leading users to feel that their home network is exposed and unsecure. It is difficult for the users of home networks to install and maintain tools available to restore trust, e.g., firewalls, antivirus, etc. In addition, many users do not have sufficient expertise to install, maintain, and configure these tools. This leads to additional user distrust when the user desires to install devices such as baby cams, web cams, door and window security systems, etc., that can be pirated. Users may be very hesitant to add unsecure devices to their home network. Users do not want to see their baby-cam or door and window security system hacked.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. 1 is a block diagram that illustrates an example network in which examples of the present disclosure may operate.

[0006] FIG. 2 is a block diagram of the elements of FIG. 1 adapted to add an unsecured device to a trusted home network, wherein messages are routed through an existing device having malware

detection logic in the trusted home network.

[0007] FIG. 3 is a block diagram of the elements of FIG. 1 adapted to add an unsecured device to a trusted home network, wherein messages are routed through a new device having malware detection logic in the trusted home network.

[0008] FIG. 4 is a diagram illustrating an exemplary method to permit a secured device of FIG. 1 to receive a message from an unsecured device of a first network and intended for a destination device of the home network of FIG. 1, wherein the determination of the presence of malware is made by malware detection logic executed by a processing device (e.g., a gateway server).

[0009] FIG. 5 is a diagram illustrating an exemplary method to permit a secured device of FIG. 3 to receive a message from an unsecured device of a first network and intended for a destination device of the home network of FIG. 1, wherein the determination of the presence of malware is made by cloud malware detection logic of the cloud computer server.

[0010] FIG. 6 is a diagram illustrating an exemplary method to configure a secure communication session between two devices in the network of FIG. 1, a first device (e.g., the gateway server) having malware detection logic and a second device having a security client.

[0011] FIG. 7 is a diagram illustrating an exemplary method to add an unsecured device to a home network of FIG. 2, wherein messages are routed through an existing device (e.g., a networking device) having malware detection logic in the home network.

[0012] FIG. 8 is a diagram illustrating an exemplary method to add an unsecured device to the home network of FIG. 3, wherein messages are routed through a new secured device having malware detection logic in the home network.

[0013] FIG. 9 is a diagram illustrating an exemplary method to configure a home network to respond to a modification of a configuration of a secured device (e.g., the gateway server) in the home network of FIG. 1.

[0014] FIG. 10 illustrates a diagrammatic representation of a machine in the example form of a computer system within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed.

DETAILED DESCRIPTION

[0015] As used herein, malware may refer to any software used to disrupt computer operations, gather sensitive information, or gain access to private computer systems. Malware may be defined by its malicious intent, acting against the requirements of the computer user, and does not include software that causes unintentional harm due to some deficiency. ‘Malware’ is an umbrella term used to refer to a variety of forms of hostile or intrusive software, including, but not limited to computer viruses, worms, Trojan horses, ransomware, spyware, adware, scareware, and other malicious programs. It can take the form of executable code, scripts, active content, and other software.

[0016] In the following description, numerous details are set forth. It will be apparent, however, to one skilled in the art, that the present disclosure may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form, rather than in detail, in order to avoid obscuring the present disclosure.

[0017] FIG. 1 is a block diagram that illustrates an example network 100 in which examples of the present disclosure may operate. The network 100 may include a secured processing device/host/server 102 (hereinafter the “secured gateway 102”) provided with malware detection logic 104, according to examples of the present disclosure. As used herein, malware detection logic may refer to processing logic intended to detect the presence of malware. The terms “computer”, “computer platform”, processing device, host, server are intended to include any data processing device, such as a desktop computer, a laptop computer, a tablet computer, a mainframe computer, a server, a handheld device, a digital signal processor (DSP), an embedded processor (an example of which is described in connection with FIG. 10), or any other device able to process data. The computer/computer platform is configured to include one or more microprocessors

communicatively connected to one or more non-transitory computer-readable media and one or more networks. The term “communicatively connected” is intended to include any type of connection, whether wired or wireless, in which data may be communicated. The term “communicatively connected” is intended to include, but not limited to, a connection between devices and/or programs within a single computer or between devices and/or separate computers over a network. The term “network” is intended to include, but not limited to, OTA (over-the-air transmission, ATSC, DVB-T), packet-switched networks (TCP/IP, e.g., the Internet), satellite (microwave, MPEG transport stream or IP), direct broadcast satellite, analog cable transmission systems (RF), and digital video transmission systems (ATSC, HD-SDI, HDMI, DVI, VGA), etc. [0018] The secured gateway **102** may be communicatively connected to an unsecured external network **106**, such as the Internet, to one or more unsecured processing devices/hosts/servers **111**, and to a cloud computing system/server **108** (hereinafter the “cloud computing server **108**”) having cloud malware detection logic **110** thereon. The secured gateway **102** may be communicatively connected to the unsecured external network **106** by a router **112** provided by a cable, fiber, satellite, etc. based Internet service provider. The router **112** may be configured to have one or more encryption protocols (not shown) and/or malware detection software (not shown).

[0019] The network **100** may further include a secured home sub-network **114** (hereinafter the “secured home network **114**”) and an unsecured home sub-network **116** (hereinafter the “unsecured home network **116**”) communicatively connected to the unsecured external network **106**. The secured home network **114** may include one or more devices **118a-118n**, wherein all of the one or more secured devices **118a-118n** are provided with security clients **120a-120n**. The secured home network **114** may be further provided with a networking device **122** having malware detection logic **126**, through which the one or more secured devices **118a-118n** may communicate with the external network **106** directly or through the router **112**. The unsecured home network **116** may include one or more unsecured devices **124a-124n**, wherein at least one of the untrusted devices **124a-124n** is not provided with a security client and hence may be referred to as an unsecured device (e.g., **124a**). The one or more secured devices **118a-118n** and the one or more unsecured devices **124a-124n** may include, but are not limited to, advanced sensors, cameras, Internet-of-Things machines, home appliance, etc. The unsecured home network **116** may include a networking device **128** having malware detection logic **130**, through which the one or more unsecured devices **124a-124n** may communicate with the external network **106** directly or through the router **112**.

[0020] The malware detection logic **104**, **110**, **126**, **130** and the security clients **120a-120n** may have one or more components of a type of firewall and security layer (hereinafter a “Security Wall”) configured to perform a plurality of malware detection, protection, and other security functions including, but not limited to, one or more validation tests comprising at least one of a port verification, content verification for virus detection, a deep packet inspection for detection of known attacks, or generation of alarms. In one example, the security clients **120a-120n** may be further configured to receive only encrypted message. The malware detection logic **104**, **110**, **126**, **130** and the security clients **120a-120n** may be implemented in either hardware as an external device or in software as a plug-in, installed, or downloaded module.

[0021] The Security Wall may be configured to provide a secure booting process, a secure download process, and/or a generation process for generating one or more keys for encrypting messages. The Security Wall may be configured to encrypt/decrypt messages to create a secure channel between less-powerful Security Wall-equipped security clients (e.g., **120a**), to provide communication channels between various instances of the Security Wall in the network **100**, for dynamic reaction and threat reporting, communicated between the Security Wall and cloud services provided by the cloud malware detection logic **110** residing on the cloud server **108** when more detailed expertise is required, and rerouting of messages/streams through the cloud malware detection logic **110** residing on the cloud server **108** for threat detection or highly sensitive data

transfer.

[0022] The malware detection logic **104** executed by a secured device (e.g., the secured gateway **102**) residing in the network **100** may be configured to receive a message from an unsecured device (e.g., the router **112**) of a first network (e.g., the untrusted external network **106**) intended for a destination device (e.g., **118a** or **102**) of the home network (e.g., the secured home network **114**). The destination device (e.g., **118a** or **102**) may comprise a security client (e.g., **120a**). The malware detection logic **104** may be configured to establish a secure communication channel between the malware detection logic **104** of the secured device (e.g., the secured gateway **102**) and the security client (e.g., **120a**) of the destination device (e.g., **118a** or **102**). The malware detection logic **104** may be configured to execute a validation test on the message to determine that the message includes malware. The malware detection logic may be configured to report an alarm to the security client (e.g., **120a**) of the destination device (e.g., **118a** or **102**). The malware detection logic **104** may be configured to transmit information related to the malware to the cloud malware detection logic **110** of the cloud computing server **108**. The malware detection logic **104** may be configured to prevent an application associated with the destination device (e.g., **118a** or **102**) from processing the message.

[0023] The secured device (e.g., the secured gateway **102**) may transmit the message over the secured home network **114** to the destination device (e.g., **118a**). Before transmitting the message, the malware detection logic **104** may encrypt the message.

[0024] In another example, the application may reside on the secured device (e.g., the secured gateway **102**).

[0025] The malware detection logic **104** may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks. The malware detection logic **104** may transmit an indication of the presence of the malware to the cloud malware detection logic **110** of the cloud computing server **108**.

[0026] The malware detection logic **104** may transmit an alarm indicative of the presence of the malware to the security client (e.g., **120a**) of the destination device (e.g., **118a**).

[0027] The malware detection logic **104** may be operable to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys for encrypting the message.

[0028] The secured device (e.g., the secured gateway **102**) may be configured to receive a message from an unsecured device (e.g., the router **112**) of a first network (e.g., the unsecured external network **106**) intended for a destination device (e.g., **118a** or **102**) of the home network (e.g., the secured home network **114**), wherein the determination of the presence of malware is made by the cloud malware detection logic **110** of the cloud computer server **108**. The malware detection logic **104** executed by the secured device (e.g., the secured gateway **102**) residing in the network **100**, may receive the message intended for the destination device (e.g., **118a** or **102**) of the network **100**. If the malware detection logic **104** decides not to determine whether the message includes malware, then the malware detection logic **104** may be configured to transmit the message to cloud malware detection logic **110** of the cloud computing server **108**.

[0029] The malware detection logic **104** may determine that the secured device (e.g., the secured gateway **102**) has insufficient processing power or needs more expertise to determine whether the message includes malware. In an example, the malware detection logic **104** may receive an indication (e.g., from one of the secured device (e.g., the secured gateway **102**, the cloud computing server **108**, the networking device **124**, or one of the security clients **120a-120n**)) that an alert level of the secured home network **114** has increased. The determination of whether the message includes malware may be based on the security sensitivity of one of the secured device (e.g., the secured gateway **102**), the cloud computing server **108**, the networking device **124**, or one of the security clients **120a-120n**.

[0030] The malware detection logic **104** may be configured to receive from the cloud malware detection logic **110** of the cloud computing server **108**, an indication that the message contains malware. The malware detection logic **104** may be configured to report an alarm to the security client (e.g., **120a**) of the destination device (e.g., **118a**). The malware detection logic **104** may be configured to prevent an application (not shown) associated with the destination device (e.g., **118a**) from processing the message. The malware detection logic **104** may be configured to receive from the cloud malware detection logic **110** of the cloud computing server **108**, an indication that the message does not contain malware. Accordingly, the malware detection logic **104** may be configured to permit the application associated with the destination device (e.g., **118a**) to process the message.

[0031] The secured device (e.g., the secured gateway **102**) may transmit the message over the secured home network **114** to the destination device (e.g., **118a**). Before transmitting the message, the malware detection logic **104** may encrypt the message. The application may reside on the secured device (e.g., the secured gateway **102**).

[0032] The malware detection logic **104** of the secured device (e.g., the secured gateway **102** and/or the cloud malware detection logic **110** of the cloud computing server **108**) may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0033] The malware detection logic **104** of the secured device (e.g., the secured gateway **102**) may transmit an indication of the presence of the malware to the cloud malware detection logic **110** of the cloud computing server **108**. In an example, the malware detection logic **104** may transmit an alarm indicative of the presence of the malware to the security client (e.g., **120a**) of the destination device (e.g., **118a**).

[0034] The malware detection logic **104** may be operable to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys for encrypting the message.

[0035] The malware detection logic **104** of the secured device (e.g., the secured gateway **102**) may be configured to route all incoming messages received from the router **112** and originating in the untrusted external network **106** to the cloud malware detection logic **110** of the cloud computing server **108**. In one example, the malware detection logic **104** of the secured device (e.g., the secured gateway **102**) routing all incoming messages may be the result of the sensitivity of the security client (e.g., **120a**), or because the alert level of the network has been increased. As used herein, sensitivity may be determined by the type of device and/or by the consequence of a successful attack. For example, a door lock has a higher sensitivity than a webcam, because a successful attack on the door lock may result in opening the door to intruders. A heating regulator in Canada may have higher sensitivity in winter than in summer. If the heating is stopped in winter, the water pipes may freeze and become damaged. The same regulator in Florida may be less sensitive. The alert level may be increased by security services located in the cloud computing server **108** as a result of monitoring activities of the cloud malware detection logic **110**.

[0036] A first secured device (e.g., the secured gateway **102**) having malware detection logic **104** may configure a secure communication session with a second secured device (e.g., the device **118b**) having a security client (e.g., **120b**). The malware detection logic **104** executed by the first secured device (e.g., the secured gateway **102**) residing in the network **100**, may receive the message intended for the second secured device (e.g., **118b**) of the network **100** from an unsecured device (e.g., the server **111**) of an untrusted network (e.g., the external network **106**). The malware detection logic **104** may be configured to establish a secure communication channel with the second secured device (e.g., **118b**) in view of a security level associated with the malware detection logic **104** or a threat level associated with the message. The malware detection logic **104** may employ at least one of a session key creation mechanism, creating one or more certificates, a cloud-generated session key, or one or more home domain keys.

[0037] The malware detection logic **104** may be configured to receive an indication that the security level associated with the malware detection logic **104** or the threat level associated with the message has changed. The security level change may be the result of one or more alarms triggered by the detection of the presence of malware in the message or a change in the secured home network **114** requiring new authentication. The malware detection logic **104** may be configured to discontinue a session associated with the secure communication channel in view of the indication. The malware detection logic **104** may be configured to prevent an application (not shown) of a secured device (e.g., the device **118b**) from processing the message.

[0038] If the malware detection logic **104** determines that the session associated with the secure communication channel is to continue in view of the indication, then the malware detection logic **104** may permit the application of the second secured device (e.g., the device **118b**) to process the message. The secured gateway **102** may transmit the message over the secured home network **114** to the second secured device (e.g., the device **118b**). In an example, before the first secured device (e.g., the secured gateway **102**) transmits the message, the malware detection logic **104** may encrypt the message.

[0039] The malware detection logic **104** may be configured to report the creation of the session to the cloud malware detection logic **110** of the cloud computing server **108**. The malware detection logic **104** may be configured to provide approval to start the session. In an example, providing approval may be based on a security level of the secured home network **114** or a security sensitivity of the secured device (e.g., the secured gateway **102**) or the second secured device (e.g., the device **118b**).

[0040] During the session, the malware detection logic **104** of the secured gateway **102** may be informed about the security level of its correspondents (e.g., **118a-118n**) and may decide if the session can continue or if the session is to be interrupted based on the security level. For example, the security level can be a consequence of alarms triggered during the execution of the setup in the examples above. In another example, the security level may change if there is a change in the environment that requires a new authentication. The change in the environment may be triggered by messages issued by the cloud malware detection logic **110**.

[0041] FIG. 2 is a block diagram of the elements of FIG. 1 adapted for adding an unsecured device **132** to the secured home network **114**, wherein messages are routed through an existing secured device (e.g., the networking device **122**) having malware detection logic **126** in the secured home network **114**. In an example, malware detection logic **126** of the existing secured device (e.g., the networking device **124**) in the secured home network **114** may be configured to receive an identifier associated with an unsecured device (e.g., **132**) of the secured home network **114**. The malware detection logic **126** may be configured to inform one or more other secured devices (e.g., **118a-118n**, **102**) in the secured home network **114** to re-route messages through the malware detection logic **126** of the existing device (e.g., the networking device **122**) in the secured home network **114** in view of the identifier. The malware detection logic **126** may receive a message intended for the unsecured device (e.g., **132**) from one of the one or more other secured devices (e.g., **118a**) in the secured home network **114**. The malware detection logic **126** may be configured to execute a validation test on the message to determine whether the message includes malware. The malware detection logic **126** may transmit the message to the cloud malware detection logic **110** of the cloud computing server **108** and receive from the cloud malware detection logic **110** of the cloud computing server **108** an indication of whether the message includes malware. The malware detection logic **126** may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks. The malware detection logic **126** may transmit an indication of the presence of the malware to a cloud computing server **108**.

[0042] If the malware detection logic **126** determines that the message does not include malware, then the malware detection logic **126** may transmit the message over the secured home network **114**

to the unsecured device (e.g., **132**). If the malware detection logic **126** determines that the message does include malware, then the malware detection logic **126** does not transmit the message over the secured home network **114** to the unsecured device (e.g., **132**).

[0043] The malware detection logic **126** may report the presence of the unsecured device (e.g., **132**) to the cloud malware detection logic **110** of the cloud computing server **108**.

[0044] Before the malware detection logic **126** transmits the message to the unsecured device (e.g., **132**), the malware detection logic **126** may be configured to encrypt the message.

[0045] The malware detection logic **126** may route all communications to the cloud malware detection logic **110** of the cloud computing server **108**, for recording, inspection, logging, etc.

[0046] FIG. **3** is a block diagram of the elements of FIG. **1** adapted to add an unsecured device **134** to the secured home network **114**, wherein messages are routed I. through a secured device (e.g., **136**) having malware detection logic (e.g., **138**) in the secured home network **114**. An unsecured device (e.g., **132**, e.g., a baby cam) may be inserted in the secured home network **114**. The secured device (e.g., **136**) having malware detection logic (e.g., **138**) is added to the secured home network **114**. The malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may be configured to receive an identifier associated with the unsecured device **134** inserted in the secured home network **114**. The malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may be configured to inform one or more other secured devices (e.g., **118a-118n**) in the secured home network **114** to re-route messages through the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) in view of the identifier. The malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may be configured to receive a message intended for the unsecured device **134** from one of the one or more other secured devices (e.g., **118a**) in the secured home network **114**. The malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may be configured to execute a validation test on the message to determine whether the message includes malware.

[0047] If the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) determines that the message does not include malware, then the malware detection logic **138** of the secured device **136** transmits the message over the secured home network **114** to the unsecured device **134**. If the malware detection logic **138** of the secured device **136** determines that the message does include malware, then the malware detection logic **138** of the new secured device **136** does not transmit the message over the secured home network **114** to the unsecured device **134**. The malware detection logic **138** may be configured to report the presence of the new networking device **136** to the cloud malware detection logic **110** of the cloud computing server **108**.

[0048] The malware detection logic **138** may transmit the message to the cloud malware detection logic **110** of the cloud computing server **108** and receive from the cloud malware detection logic **110** of the cloud computing server **108** an indication of whether the message includes malware.

[0049] Before the malware detection logic **138** of the secured device **134** transmits the message, the malware detection logic **138** of the new secured device **136** may be configured to encrypt the message.

[0050] The malware detection logic **138** of the secured device **136** may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0051] The malware detection logic **138** may transmit an indication of the presence of the malware to the cloud malware detection logic **110** of the cloud computing server **108**.

[0052] Referring to FIG. **1**, a configuration of a secured device (e.g., the secured gateway **102**) may change in the secured home network **114**. The malware detection logic (e.g., **104**) executed by the secured device (e.g., the secured gateway **102**) in the secured home network **114** may be configured to receive an indication that a first signature associated with the secured device (e.g., of the secured gateway **102**) has changed in view of a change in configuration of the secured device (e.g., the secured gateway **102**). The malware detection logic (e.g., **104**) executed by a secured device (e.g., the secured gateway **102**) may be configured to calculate a second signature associated with the

secured device (e.g., of the secured gateway **102**) in view of the indication. The malware detection logic (e.g., **104**) may be configured to transmit the second signature to malware detection logic **110** of the cloud computing server **108**. The malware detection logic (e.g., **104**) may be configured to receive from the malware detection logic **110** of the cloud computing server **108** an update of a security status of the secured device (e.g., the secured gateway **102**) in view of the second signature.

[0053] The first signature may be determined based on a configuration of the secured device (e.g., of the secured gateway **102**), one or more features of secured device (e.g., of the secured gateway **102**), or one or more behaviors of the secured device (e.g., of the secured gateway **102**). The malware detection logic **110** of the cloud computing server **108** receives and prohibits further communications with the secured device (e.g., the secured gateway **102**).

[0054] The malware detection logic **110** of the cloud computing server **108** may inform other secured devices (e.g., **118a-118n**) in the secured home network **114** about the change in security status of the secured device (e.g., the secured gateway **102**). As a result, the other secured devices (e.g., **118a-118n**) in the secured home network **114** may take one or more individual actions. Example of what actions the other secured devices (e.g., **118a-118n**) may take may include, but are not limited to, deciding to stop communicating with the secured device (e.g., the secured gateway **102**), reinitialize the communication with the secured device (e.g., the secured gateway **102**), reset themselves and/or rollback to a known configuration or to known parameters, etc. The individual action may lead to the malware detection logic **110** of the cloud computing server **108** prohibiting any further communications (e.g., by the other secured devices (**118a-118n**)) with the secured device that was modified (e.g., the secured gateway **102**).

[0055] FIG. **4** is a diagram illustrating an exemplary method **400** to permit a secured device (e.g., the secured gateway **102**) of FIG. **1** to receive a message from an unsecured device (e.g., the server **111**) of a first network (e.g., the untrusted external network **106**) and intended for a destination device (e.g., **118a** or **102**) of the home network (e.g., the secured home network **114**), wherein the determination of the presence of malware is made by the malware detection logic **104** executed by a processing device of a secured device (e.g., the secured gateway **102**). The method **400** may be performed by malware detection logic (e.g., **104**) of the secured device (e.g., the secured gateway **102**) of FIG. **1** and may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions run on a processing device), or a combination thereof.

[0056] As shown in FIG. **4**, at block **405**, the malware detection logic **104** executed by the secured device (e.g., the secured gateway **102**) residing in the network **100**, may receive the message intended for the destination device (e.g., **118a** or **102**) of the network **100**. The destination device (e.g., **118a** or **102**) may comprise a security client (e.g., **120a**). At block **410**, the malware detection logic **104** may establish a secure communication channel between the malware detection logic **104** of the secured device (e.g., the secured gateway **102**) and the security client (e.g., **120a**) of the destination device (e.g., **118a**). At block **415**, the malware detection logic **104** may execute a validation test on the message to determine whether the message includes malware. If, at block **420**, the malware detection logic **104** determines that the message includes malware, then at block **425**, the malware detection logic **104** may report an alarm to the security client (e.g., **120a**) of the destination device (e.g., **118a**). The malware detection logic **104** may transmit information related to the malware to a cloud computing server **108**. At block **430**, the malware detection logic **104** may prevent an application (not shown) associated with the destination device (e.g., **118a**) from processing (e.g., receiving, reading, extracting information from, and/or executing portions of, etc.) the message. If, at block **420**, the malware detection logic **104** determines that the message does not include malware, then at block **435**, the malware detection logic **104** may permit the application associated with the destination device (e.g., **118a**) to process the message.

[0057] Permitting the application to process the message may comprise transmitting, by the secured device (e.g., the secured gateway **102**), the message over the secured home network **114** to

the destination device (e.g., **118a**). Before transmitting the message, the malware detection logic **104** may encrypt the message. The application may reside on the secured device (e.g., the secured gateway **102**).

[0058] The malware detection logic **104** may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks. In another example, the malware detection logic **104** may transmit an indication of the presence of the malware to the cloud malware detection logic **110** of the cloud computing server **108**.

[0059] The malware detection logic **104** may transmit an alarm indicative of the presence of the malware to the security client (e.g., **120a**) of the destination device (e.g., **118a**).

[0060] The malware detection logic **104** may provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys for encrypting the message.

[0061] FIG. 5 is a diagram illustrating an exemplary method **500** to permit the secured device (e.g., the secured gateway **102** of FIG. 1) to manage communication between an unsecured device (e.g., **122**) of a first network (e.g., the external network **106**) and a destination device (e.g., **118a**) of a home network (e.g., the secured home network **114**). The method **500** may be performed by malware detection logic (e.g., **104**) of the secured device (e.g., the secured gateway **102**) of FIG. 1 and may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions run on a processing device), or a combination thereof.

[0062] As shown in FIG. 5, at block **505**, malware detection logic **104** executed by a secured device (e.g., the secured gateway **102**) residing in a home network (e.g., the secured home network **114**) receives message intended for the destination device (e.g., **118a** or **102**) of the home network (e.g., the secured home network **114**). At block **510**, the malware detection logic **104** decides not to determine whether the message includes malware. At block **915**, the malware detection logic **104** may transmit the message to cloud malware detection logic **110** of the cloud computing server **108**.

[0063] The malware detection logic **104** may determine that the secured device (e.g., the secured gateway **102**) has insufficient processing power or needs more expertise to determine whether the message includes malware. The malware detection logic **104** may receive an indication (e.g., from one of the secured device (e.g., the secured gateway **102**), the cloud computing server **108**, the networking device **124**, or one of the security clients **120a-120n**) that an alert level of the secured home network **114** has increased. The determination of whether the message includes malware may be based on the security sensitivity of one of the secured device (e.g., the secured gateway **102**), the cloud computing server **108**, the networking device **124**, or one of the security clients **120a-120n**.

[0064] If, at block **520**, the malware detection logic **104** receives from the cloud malware detection logic **110** of the cloud computing server **108**, an indication that the message contains malware, then at block **525**, the malware detection logic **104** may report an alarm to the security client (e.g., **120a**) of the destination device (e.g., **118a**). At block **530**, the malware detection logic **104** may prevent an application (not shown) associated with the destination device (e.g., **118a**) from processing the message. If, at block **520**, the malware detection logic **104** receives from the cloud malware detection logic **110** of the cloud computing server **108**, an indication that the message does not contain malware, then at block **535**, the malware detection logic **104** may permit the application associated with the destination device (e.g., **118a**) to process the message.

[0065] A secured device (e.g., the secured gateway **102**) may transmit the message over the secured home network **114** to the destination device (e.g., **118a**). In an example, before transmitting, the message, the malware detection logic **104** may encrypt the message. The application may reside on the secured device (e.g., the secured gateway **102**).

[0066] The malware detection logic **104** of the secured device (e.g., the secured gateway **102**), and/or the cloud malware detection logic **110** of the cloud computing server **108** may conduct one or more validation tests comprising at least one of a port verification, content verification for virus

detection, or a deep packet inspection for detection of known attacks.

[0067] The malware detection logic **104** of the secured device (e.g., the secured gateway **102**) may transmit an indication of the presence of the malware to the cloud malware detection logic **110** of the cloud computing server **108**. In an example, the malware detection logic **104** may transmit an alarm indicative of the presence of the malware to the security client (e.g., **120a**) of the destination device (e.g., **118a**).

[0068] The malware detection logic **104** may be operable to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys for encrypting the message.

[0069] The malware detection logic **104** of the secured device (e.g., the secured gateway **102**), may be configured to route all incoming messages received from the router **112** and originating in the unsecured external network **106** to the cloud malware detection logic **110** of the cloud computing server **108**. In one example, routing all incoming messages may be the result of the sensitivity of the security client (e.g., **120a**), or because the alert level of the network has been increased. Alert level can be increased by the security services located in the cloud computing server **108** as a result of monitoring activities of the cloud malware detection logic **110**.

[0070] FIG. **6** is a diagram illustrating an exemplary method **600** to configure a secure communication session between two secured devices in the network of FIG. **1**, a first secured device (e.g., the secured gateway **102**) having malware detection logic **104** and a second secured device (e.g., the device **118b**) having a security client (e.g., **120b**). The method **600** may be performed by malware detection logic (e.g., **104**) of the first secured device (e.g., the secured gateway **102**) of FIG. **1** and may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions run on a processing device), or a combination thereof.

[0071] As shown in FIG. **6**, to setup a secure communication session between two secured devices in the network of FIG. **1**, at block **605**, the malware detection logic **104** executed by the first secured device (e.g., the secured gateway **102**), residing in the network **100**, may receive the message intended for the second secured device (e.g., **118b**) of the network **100** from an unsecured device (e.g., **122**) of an untrusted network (e.g., the external network **106**). At block **610**, the malware detection logic **104** may establish a secure communication channel with the unsecured device (e.g., the server **111**) in view of a security level associated with the malware detection logic **104** or a threat level associated with the message. The malware detection logic **104** may employ at least one of a session key creation mechanism, creating one or more certificates, a cloud-generated session key, or one or more home domain keys.

[0072] At block **615**, the malware detection logic **104** may receive an indication that the security level associated with the malware detection logic **104** or the threat level associated with the message has changed. The security level change may be the result of one or more alarms triggered by the detection of the presence of malware in the message or a change in the secured home network **114** requiring new authentication. At block **620**, the malware detection logic **104** may discontinue a session associated with the secure communication channel in view of the indication. At block **625**, the malware detection logic **104** may prevent an application (not shown) of the second secured device (e.g., **118b**) from processing the message.

[0073] If the malware detection logic **104** determines that the session associated with the secure communication channel is to continue in view of the indication, then the malware detection logic **104** may permit the application of the second secured device (e.g., **118b**) to process the message. The first secured device (e.g., the secured gateway **102**), may transmit the message over the secured home network **114** to the second secured device (e.g., **118b**). In an example, before the first secured device (e.g., the secured gateway **102**) transmits the message, the malware detection logic **104** may encrypt the message.

[0074] The malware detection logic **104** may report the creation of the session to the cloud

malware detection logic **110** of the cloud computing server **108**. The malware detection logic **104** may give approval to start the session. Giving approval may be based on a security level of the secured home network **114** or a security sensitivity of the secured gateway **102** or the second secured device **118b**.

[0075] During the session, the malware detection logic **104** of the first secured device (e.g., the secured gateway **102**), may be informed about the security level of its correspondents (e.g., **118a-118n**) and may decide if the session can continue and/or if the session is to be interrupted based on the security level. For example, the security level can be a consequence of alarms triggered in during the execution of the setup of FIG. 2 or 3. In another example, the security level may change if there is a change in the environment that may require new authentication.

[0076] FIG. 7 is a diagram illustrating an exemplary method **700** to add an unsecured device (e.g., **122**) to a home network (e.g., the secured home network **114**) of FIG. 2, wherein messages are routed through a secured device (e.g., the networking device **124**) having malware detection logic (e.g., **116**) in home network (e.g., the secured home network **114**). The method **600** may be performed by malware detection logic (e.g., **116**) of the secured device (e.g., the networking device **124**) of FIG. 2 and may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions run on a processing device), or a combination thereof.

[0077] As shown in FIG. 7, at block **705**, the malware detection logic **126** of the secured device (e.g., the networking device **124**) in the secured home network **114** may be receive an identifier associated with an unsecured device (e.g., **128**) inserted in the secured home network **114**. At block **710**, the malware detection logic **126** may inform one or more other secured devices (e.g., **118a-118n**, **102**) in the secured home network **114** to re-route messages through the malware detection logic **126** of the secured device (e.g., the networking device **124**) in the secured home network **114** in view of the identifier. At block **715**, the malware detection logic **126** may receive a message intended for the unsecured device (e.g., **128**) from one of the one or more other secured devices (e.g., **118a**) in the secured home network **114**. At block **720**, the malware detection logic **126** may execute a validation test on the message to determine whether the message includes malware. The malware detection logic **126** may transmit the message to the cloud malware detection logic **110** of the cloud computing server **108** and receive from the cloud malware detection logic **110** of the cloud computing server **108** an indication of whether the message includes malware. The malware detection logic **126** may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks. The malware detection logic **126** may transmit an indication of the presence of the malware to a cloud computing server **108**.

[0078] If, at block **725**, the malware detection logic **126** determines that the message does not include malware, then at block **730**, the malware detection logic **126** may transmit the message over the secured home network **114** to the unsecured device (e.g., **128**). If, at block **725**, the malware detection logic **126** determines that the message does include malware, then at block **735**, the malware detection logic **126** does not transmit the message over the secured home network **114** to the unsecured device (e.g., **128**).

[0079] The malware detection logic **126** may report the presence of the unsecured device (e.g., **128**) to the cloud malware detection logic **110** of the cloud computing server **108**.

[0080] Before the malware detection logic **126** transmits the message to the unsecured device (e.g., **128**), the malware detection logic **126** may be configured to encrypt the message.

[0081] The malware detection logic **126** may route all communications to the cloud malware detection logic **110** of the cloud computing server **108**, for recording, inspection, logging, etc.

[0082] FIG. 8 is a diagram illustrating an exemplary method **800** to add an unsecured device (e.g., **132**) to a home network (e.g., the secured home network **114**), wherein messages are routed through a new secured device (e.g., **136**) having malware detection logic (e.g., **132**) in the home network (e.g., the secured home network **114**). The method **800** may be performed by the secured

device (e.g., **136**) having malware detection logic (e.g., **134**) of FIG. **3** and may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions run on a processing device), or a combination thereof.

[0083] As shown in FIG. **8**, at block **805**, an unsecured device (e.g., **132**, e.g., a baby cam) is inserted in the secured home network **114**. At block **810**, the secured device (e.g., **136**) having malware detection logic (e.g., **138**) is added to the secured home network **114**. At block **815**, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may receive an identifier associated with the unsecured device **132** inserted in the secured home network **114**. At block **820**, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may inform one or more other secured devices (e.g., **118a-118n**) in the secured home network **114** to re-route messages through the malware detection logic (e.g., **138**) of the new secured device (e.g., **136**) in view of the identifier. At block **825**, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may receive a message intended for the unsecured device **132** from one of the one or more other secured devices (e.g., **118a**) in the secured home network **114**. At block **830**, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may execute a validation test on the message to determine whether the message includes malware.

[0084] If, at block **835**, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) determines that the message does not include malware, then at block **840**, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may transmit the message over the secured home network **114** to the unsecured device **132**. If, at block **835**, the malware detection logic (e.g., **138**) of the new secured device (e.g., **136**) determines that the message does include malware, then at block **845**, the malware detection logic (e.g., **138**) of the new secured device (e.g., **136**) does not transmit the message over the secured home network **114** to the unsecured device **132**. The malware detection logic (e.g., **138**) may be configured to report the presence of the new secured device (e.g., **136**) to the cloud malware detection logic **110** of the cloud computing server **108**.

[0085] The malware detection logic (e.g., **138**) may transmit the message to the cloud malware detection logic **110** of the cloud computing server **108** and receive from the cloud malware detection logic **110** of the cloud computing server **108**, an indication of whether the message includes malware.

[0086] Before the malware detection logic (e.g., **138**) of the new secured device (e.g., **136**) transmits the message, the malware detection logic (e.g., **138**) of the secured device (e.g., **136**) may be configured to encrypt the message.

[0087] The malware detection logic (e.g., **138**) of secured device (e.g., **136**) may conduct one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0088] The malware detection logic (e.g., **138**) may transmit an indication of the presence of the malware to the cloud malware detection logic **110** of the cloud computing server **108**.

[0089] FIG. **9** is a diagram illustrating an exemplary method **900** of a home network (secured home network **114**) responding to a change in configuration of a secured device (e.g., the secured gateway **102**) in the home network (e.g., the secured home network **114**). The method **900** may be performed by malware detection logic (e.g., **104**) executed by a processing device (e.g., of the secured gateway **102**) of FIG. **1** and may comprise hardware (e.g., circuitry, dedicated logic, programmable logic, microcode, etc.), software (e.g., instructions run on a processing device), or a combination thereof.

[0090] As shown in FIG. **9**, at block **905**, the malware detection logic (e.g., **104**) executed by a secured device (e.g., the secured gateway **102**) in the secured home network **114** may receive an indication that a first signature associated with the secured device (e.g., of the secured gateway **102**) has changed in view of a modification of a configuration of the secured device (e.g., the secured gateway **102**). At block **910**, the malware detection logic (e.g., **104**) executed by a secured device (e.g., of the secured gateway **102**) may calculate a second signature associated with the

secured device (e.g., of the secured gateway **102**) in view of the indication. At block **915**, the malware detection logic (e.g., **104**) may transmit the second signature to malware detection logic **110** of the cloud computing server **108**. At block **920**, the malware detection logic (e.g., **104**) may receive from the malware detection logic **110** of the cloud computing server **108** an update of a security status of the secured device (e.g., the secured gateway **102**) in view of the second signature.

[0091] The first signature may be determined based on a configuration of the secured device (e.g., of the secured gateway **102**), one or more features of the secured device (e.g., of the secured gateway **102**), or one or more behaviors of the secured device (e.g., of the secured gateway **102**).

[0092] The malware detection logic **110** of the cloud computing server **108** may not permit further communications with the secured device (e.g., the secured gateway **102**) in view of the updated security status.

[0093] The malware detection logic **110** of the cloud computing server **108** may inform other secured devices (e.g., **118a-118n**) in the secured home network **114** about the change in security status of the secured device (e.g., the secured gateway **102**). As a result, the other secured devices (e.g., **118a-118n**) in the secured home network **114** may take individual actions. The individual action may lead to the malware detection logic **110** of the cloud computing server **108** not permitting any further communications (e.g., by the other secured devices (**118a-118n**) with the secured device that was modified (e.g., the secured gateway **102**).

[0094] FIG. **10** illustrates a diagrammatic representation of a machine in the example form of a computer system **1000** within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed. In some examples, the machine may be connected (e.g., networked) to other machines in a LAN, an intranet, an extranet, or the Internet. The machine may operate in the capacity of a server machine in client-server network environment. The machine may be a personal computer (PC), a set-top box (STB), a server, a network router, switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while only a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

[0095] The example computer system **1000** includes a processing device (processor) **1002**, a main memory **1004** (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM)), a static memory **1006** (e.g., flash memory, static random access memory (SRAM)), and a data storage device **1016**, which communicate with each other via a bus **1008**.

[0096] Processor **1002** represents one or more general-purpose processing devices such as a microprocessor, central processing unit, or the like. More particularly, the processor **702** may be a complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or a processor implementing other instruction sets or processors implementing a combination of instruction sets. The processor **1002** may also be one or more special-purpose processing devices such as an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital signal processor (DSP), network processor, or the like. The malware detection logic **104**, **110**, **126**, **130**, **138** in FIGS. **1** and **3** may be executed by processor **1002** configured to perform the operations and steps discussed herein.

[0097] The computer system **1000** may further include a network interface device **1022**. The computer system **1000** also may include a video display unit **1010** (e.g., a liquid crystal display (LCD) or a cathode ray tube (CRT)), an alphanumeric input device **1012** (e.g., a keyboard), a cursor control device **1014** (e.g., a mouse), and a signal generation device **1020** (e.g., a speaker).

[0098] A drive unit **1016** may include a computer-readable medium **1024** on which is stored one or

more sets of instructions (e.g., instructions of the malware detection logic **104, 110, 126, 130, 138** in FIGS. **1** and **3**) embodying any one or more of the methodologies or functions described herein. The instructions of the malware detection logic **104, 110, 126, 130, 138** in FIGS. **1** and **3** may also reside, completely or at least partially, within the main memory **1004** and/or within the processor **1002** during execution thereof by the computer system **1000**, the main memory **1004** and the processor **1002** also constituting computer-readable media. The instructions of the malware detection logic **104, 110, 126, 130, 138** in FIGS. **1** and **3** may further be transmitted or received over a network **1026** via the network interface device **1022**.

[0099] While the computer-readable storage medium **1024** is shown in an example to be a single medium, the term “computer-readable storage medium” should be taken to include a single non-transitory medium or multiple non-transitory media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term “computer-readable storage medium” shall also be taken to include any medium that is capable of storing, encoding or carrying a set of instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present disclosure. The term “computer-readable storage medium” shall accordingly be taken to include, but not be limited to, solid-state memories, optical media, and magnetic media.

[0100] The following examples pertain to further embodiments.

[0101] Example 1 is a method comprising receiving, by malware detection logic executed by a secured device residing in a home network, a message from an unsecured device of a first network and intended for a destination device of the home network, the destination device comprising a security client; establishing, by the malware detection logic, a secure communication channel between the malware detection logic of the secured device and the security client of the destination device; executing, by the malware detection logic, a validation test on the message to determine that the message includes malware; reporting, by the malware detection logic, an alarm to the security client of the destination device; transmitting, by the malware detection logic, information related to the malware to a cloud computing server; and preventing, by the malware detection logic, an application associated with the destination device from processing the message.

[0102] Example 2 may optionally extend the subject matter of example 1. In example 2, the method may further comprise before the transmitting, encrypting, by the malware detection logic, the message.

[0103] Example 3 may optionally extend the subject matter of any of examples 1-2. In example 3, the application resides on the secured device.

[0104] Example 4 may optionally extend the subject matter of any of examples 1-3. In example 4, determining that the message includes malware comprises conducting one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0105] Example 5 may optionally extend the subject matter of any of examples 1-4. In example 5, the method further comprises transmitting, by the malware detection logic, an indication of the presence of the malware to a cloud computing server.

[0106] Example 6 may optionally extend the subject matter of any of examples 1-5. In example 6, the method further comprises transmitting, by the malware detection logic, an alarm indicative of the presence of the malware to the security client of the destination device.

[0107] Example 7 may optionally extend the subject matter of any of examples 1-6. In example 7, the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

[0108] Example 8 is a system comprising a memory to store instructions; and a processing device operatively coupled to the memory; the processing device residing in a home network, the processing device to: receive a message from an unsecured device of a first network and intended for a destination device of the home network, the destination device comprising a security client;

establish a secure communication channel between the secured device and the security client of the destination device; execute a validation test on the message to determine that the message includes malware; report an alarm to the security client of the destination device; transmit information related to the malware to a cloud computing server; and prevent an application associated with the destination device from processing the message.

[0109] Example 9 is a method comprising receiving, by malware detection logic executed by a secured device residing in a home network, a message from an unsecured device of a first network and intended for a destination device of the home network, the destination device comprising a security client; responsive to the malware detection logic not determining whether the message includes malware: transmitting, by the malware detection logic, the message to a cloud computing server; responsive to receiving, from the cloud computing server, an indication that the message contains malware: reporting, by the malware detection logic, an alarm to the security client of the destination device; and preventing, by the malware detection logic, an application associated with the destination device from processing the message.

[0110] Example 10 may optionally extend the subject matter of example 9. In example 10, the method may further comprise before the transmitting, encrypting, by the malware detection logic, the message.

[0111] Example 11 may optionally extend the subject matter of any of examples 9-10. In example 11, the method may further comprise determining that the secured device has insufficient processing power or needs more expertise to determine whether the message includes malware.

[0112] Example 12 may optionally extend the subject matter of any of examples 9-11. In example 12, the method may further comprise receiving an indication that an alert level of the home network has increased.

[0113] Example 13 may optionally extend the subject matter of any of examples 9-12. In example 13, not determining whether the message includes malware is in view of the security sensitivity of the secured device.

[0114] Example 14 may optionally extend the subject matter of any of examples 9-13. In example 14, the application resides on the secured device.

[0115] Example 15 may optionally extend the subject matter of any of examples 9-14. In example 15, the method may further comprise conducting one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0116] Example 16 may optionally extend the subject matter of any of examples 9-15. In example 16, the method may further comprise transmitting, by the malware detection logic, an indication of the presence of the malware to a cloud computing server.

[0117] Example 17 may optionally extend the subject matter of any of examples 9-16. In example 17, the method may further comprise transmitting, by the malware detection logic, an alarm indicative of the presence of the malware to the security client of the destination device.

[0118] Example 18 may optionally extend the subject matter of any of examples 9-17. In example 18, the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

[0119] Example 19 is a system comprising a memory to store instructions; and a processing operatively coupled to the memory; the processing device residing in a home network, the processing device to: receive a message from an unsecured device of a first network and intended for a destination device of the home network, the destination device comprising a security client; responsive to the malware detection logic not determining whether the message includes malware: transmit the message to a cloud computing server; responsive to receiving, from the cloud computing server, an indication that the message contains malware: report an alarm to the security client of the destination device; and prevent an application associated with the destination device from processing the message.

[0120] Example 20 may optionally extend the subject matter of example 19. In example 20, the system may further comprise the processing device to: before the transmitting, encrypt the message.

[0121] Example 21 is a method comprising receiving, by malware detection logic executed by a secured device residing in a home network, a message from an unsecured device of a first network, the message intended for a destination device of the home network, the destination device comprising a security client; establishing, by the malware detection logic, a secure communication channel with at least one of the unsecured device in view of a security level associated with the malware detection logic or a threat level associated with the message; receiving, by the malware detection logic, an indication that the at least one of the security level associated with the malware detection logic or the threat level associated with the message has changed; discontinuing a session associated with the secure communication channel in view of the indication; and preventing, by the malware detection logic, an application of the destination device from processing the message.

[0122] Example 22 may optionally extend the subject matter of example 21. In example 22, the method may further comprise before the transmitting, encrypting, by the malware detection logic, the message.

[0123] Example 23 may optionally extend the subject matter of any of examples 21-22. In example 23, the security level change is the result of one or more alarms triggered by the detection of the presence of malware in the message or a change in the home network requiring new authentication.

[0124] Example 24 may optionally extend the subject matter of any of examples 21-23. In example 24, the method may further comprise employing at least one of a session key creation mechanism, creating one or more certificates, a cloud-generated session key, or one or more home domain keys.

[0125] Example 25 may optionally extend the subject matter of any of examples 21-24. In example 25, malware detection logic reports the creation of the session to a cloud computing server.

Example 26 may optionally extend the subject matter of any of examples 21-25. In example 26, the method may further comprise, giving approval, by the malware detection logic, to start the session.

[0126] Example 26 may optionally extend the subject matter of example 25. In example 26, giving approval is in view of a security level of the home network or a security sensitivity of the secured device.

[0127] Example 27 may optionally extend the subject matter of any of examples 21-25. In example 27, the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

[0128] Example 28 is a system comprising a memory to store instructions; and a processing device operatively coupled to the memory; the processing device residing in a home network, processing device to: receive from an unsecured device of a first network, the message intended for a destination device of the home network, the destination device comprising a security client; establish a secure communication channel with at least one of the unsecured device in view of a security level associated with the malware detection logic or a threat level associated with the message; receive an indication that the at least one of the security level associated with the malware detection logic or the threat level associated with the message has changed; discontinue a session associated with the secure communication channel in view of the indication; and prevent an application of the destination device from processing the message.

[0129] Example 29 is a method comprising receiving, by malware detection logic executed by an existing secured device residing in a home network, an identifier associated with an unsecured device inserted in the home network; informing, by the malware detection logic, one or more other secured devices in the home network to re-route messages through the malware detection logic of the secured device in view of the identifier; receiving, by the malware detection logic, a message intended for the unsecured device from one of the one or more other secured devices in the home network; executing, by the malware detection logic, a validation test on the message to determine whether the message includes malware; and responsive to the malware detection logic detecting

that the message does not include malware: transmitting, by the malware detection logic, the message over the home network to the unsecured device.

[0130] Example 30 may optionally extend the subject matter of example 29. In example 30, the method may further comprise wherein executing a validation test further comprises: transmitting the message to a cloud computing server; and receiving, by the malware detection logic from the cloud computing server, an indication of whether the message includes malware.

[0131] Example 31 may optionally extend the subject matter of any of examples 29-30. In example 30, the method may further comprise before the transmitting, encrypting, by the malware detection logic, the message.

[0132] Example 32 may optionally extend the subject matter of any of examples 29-31. In example 32, the method may further comprise conducting one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0133] Example 33 may optionally extend the subject matter of any of examples 29-32. In example 33, the method may further comprise transmitting, by the malware detection logic, an indication of the presence of the malware to a cloud computing server.

[0134] Example 34 may optionally extend the subject matter of any of examples 29-33. In example 34, the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

[0135] Example 35 is a system comprising a memory to store instructions; and a processing device operatively coupled to the memory; the processing device residing in a home network, the processing device to: receive an identifier associated with an unsecured device inserted in the home network; inform one or more other secured devices in the home network to re-route messages through the malware detection logic of the secured device in view of the identifier; receive a message intended for the unsecured device from one of the one or more other secured devices in the home network; execute a validation test on the message to determine whether the message includes malware; and responsive to detecting that the message does not include malware: transmit the message over the home network to the unsecured device.

[0136] Example 36 is a method comprising inserting an unsecured device in a home network; adding a new secured device having malware detection logic in the home network; receiving, by the malware detection logic, an identifier associated with the unsecured device inserted in the home network; informing, by the malware detection logic, one or more other secured devices in the home network to re-route messages through the malware detection logic of the new secured device in view of the identifier; receiving, by the malware detection logic, a message intended for the unsecured device from one of the one or more other secured devices in the home network; executing, by the malware detection logic, a validation test on the message to determine whether the message includes malware; and responsive to the malware detection logic detecting that the message does not include malware: transmitting, by the malware detection logic, the message over the home network to the unsecured device.

[0137] Example 37 may optionally extend the subject matter of example 36. In example 37, the method may further comprise wherein: responsive to the malware detection logic detecting that the message includes malware, not transmitting, by the malware detection logic, the message over the home network to the unsecured device.

[0138] Example 38 may optionally extend the subject matter of any of examples 36-37. In example 38, the method may further comprise reporting, by the malware detection logic, the presence of the processing device to a cloud computing server.

[0139] Example 39 may optionally extend the subject matter of any of examples 36-38. In example 39, executing a validation test further comprises: transmitting the message to a cloud computing server; and receiving, by the malware detection logic from the cloud computing server, an indication of whether the message includes malware.

[0140] Example 40 may optionally extend the subject matter of any of examples 36-39. In example 40, the method may further comprise before the transmitting, encrypting, by the malware detection logic, the message.

[0141] Example 41 may optionally extend the subject matter of any of examples 36-40. In example 41, the method may further comprise conducting one or more validation tests comprising at least one of a port verification, content verification for virus detection, or a deep packet inspection for detection of known attacks.

[0142] Example 42 may optionally extend the subject matter of any of examples 36-41. In example 42, the method may further comprise transmitting, by the malware detection logic, an indication of the presence of the malware to a cloud computing server.

[0143] Example 43 may optionally extend the subject matter of any of examples 36-42. In example 43, the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

[0144] Example 44 is a system comprising a secured device having malware detection logic added to a home network; an unsecured device inserted in the home network; a memory to store instructions; and a processing device operatively coupled to the memory; the processing device residing in the secured device of a home network, the processing device to: receive an identifier associated with the unsecured device inserted in the home network; inform one or more other secured devices in the home network to re-route messages through the malware detection logic of the new secured device in view of the identifier; receive a message intended for the unsecured device from one of the one or more other secured devices in the home network; execute a validation test on the message to determine whether the message includes malware; and responsive to detecting that the message does not include malware: transmit the message over the home network to the unsecured device.

[0145] Example 45 is a method comprising receiving, by malware detection logic executed by a secured device in a home network, an indication that a first signature associated with the secured device has changed in view of a modification of a configuration of the trusted first device; calculating, by the malware detection logic of the secured device a second signature associated with the secured device in view of the indication; transmitting, by the malware detection logic, the second signature to a cloud computing server; and receiving, by the malware detection logic from the cloud computing server, an update of a security status of the secured device in view of the second signature.

[0146] Example 46 may optionally extend the subject matter of example 45. In example 46, the first signature is determined in view of at least one of a configuration of the secured device, one or more features of the secured device, or one or more behaviors of the secured device.

[0147] Example 47 may optionally extend the subject matter of any of examples 45-46. In example 47, receiving an update of a security status comprises not permitting further communications with the secured device.

[0148] Example 48 is a system comprising a memory to store instructions; a processing device operatively coupled to the memory; and the processor residing in a home network, the processing device to: receive an indication that a first signature associated with the secured device has changed in view of a modification of a configuration of the trusted first device; calculate a second signature associated with the secured device in view of the indication; transmit the second signature to a cloud computing server; and receive, from the cloud computing server, an update of a security status of the secured device in view of the second signature.

[0149] In the above description, numerous details are set forth. It is apparent, however, to one of ordinary skill in the art having the benefit of this disclosure, that examples of the disclosure may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form, rather than in detail, in order to avoid obscuring the description.

[0150] Some portions of the detailed description are presented in terms of algorithms and symbolic

representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of steps leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

[0151] It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the above discussion, it is appreciated that throughout the description, discussions utilizing terms such as “receiving”, “writing”, “maintaining”, or the like, refer to the actions and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (e.g., electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

[0152] Examples of the disclosure also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may comprise a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions.

[0153] The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct a more specialized apparatus to perform the required method steps. Example structure for a variety of these systems appears from the description herein. In addition, the present disclosure is not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the disclosure as described herein.

[0154] Accordingly, an efficient method and system provides protection to home networks. Innovation resides in the use of cloud computing server and groups of devices having malware detection logic to increase the capability of detecting attacks and intrusions and preventing the attacks and intrusions. The development of dedicated device malware detection logic helps in securing devices that are exposed, such as Internet of Things (IoT) devices (e.g., webcams, media devices, etc.).

[0155] It is to be understood that the above description is intended to be illustrative, and not restrictive. Many other examples will be apparent to those of skill in the art upon reading and understanding the above description. The scope of the disclosure should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

Claims

1. A method for secure communication, the method comprising: receiving, by malware detection logic executed by a secured device residing in a home network, a message from an unsecured

device of a first network, the message intended for a destination device in the home network; establishing, by the malware detection logic, a secure communication channel with the unsecured device in view of a security level associated with the malware detection logic; receiving, by the malware detection logic, an indication that the security level associated with the malware detection logic has changed; discontinuing a session associated with the secure communication channel in view of the indication; and preventing an application of the destination device from processing the message.

2. The method of claim 1, further comprising: determining to continue the session associated with the secure communication channel; and transmitting, by the malware detection logic, the message to the destination device.

3. The method of claim 1, further comprising, before transmitting the message, encrypting the message.

4. The method of claim 1, wherein, the security level changed based on one or more alarms triggered by detection of malware in the message.

5. The method of claim 1, wherein, the security level changed based on a change in the home network requiring new authentication.

6. The method of claim 1, further comprising at least one of creating a session key, creating one or more certificates, requesting a cloud-generated session key, creating or one or more home domain keys.

7. The method of claim 1, further comprising reporting, by the malware detection logic, creation of the session to a cloud computing server.

8. The method of claim 1, further comprising giving approval, by the malware detection logic, to start the session.

9. The method of claim 8, wherein the approval is given in view of a security level of the home network or a security sensitivity of the secured device.

10. The method of claim 1, wherein the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

11. A method for secure communication, the method comprising: receiving, by malware detection logic executed by a secured device residing in a home network, a message from an unsecured device of a first network, the message intended for a destination device in the home network; establishing, by the malware detection logic, a secure communication channel with the unsecured device in view of a threat level associated with the message; receiving, by the malware detection logic, an indication that the threat level associated with the message has changed; discontinuing a session associated with the secure communication channel in view of the indication; and preventing an application of the destination device from processing the message.

12. The method of claim 11, further comprising: determining to continue the session associated with the secure communication channel; and transmitting, by the malware detection logic, the message to the destination device.

13. The method of claim 12, further comprising, before transmitting the message, encrypting the message.

14. The method of claim 11, further comprising at least one of creating a session key, creating one or more certificates, requesting a cloud-generated session key, creating or one or more home domain keys.

15. The method of claim 11, further comprising reporting, by the malware detection logic, creation of the session to a cloud computing server.

16. The method of claim 11, further comprising giving approval, by the malware detection logic, to start the session.

17. The method of claim 16, wherein the approval is given in view of a security level of the home network or a security sensitivity of the secured device.

18. The method of claim 11, wherein the malware detection logic is to provide one or more of a secure booting process, a secure download process, or a generation process for generating one or more keys to encrypt the message.

19. An apparatus for secure communication, the apparatus comprising: at least one memory; and at least one processor coupled to the at least one memory and configured to: receive, by malware detection logic executed by a secured device residing in a home network, a message from an unsecured device of a first network, the message intended for a destination device in the home network; establish, by the malware detection logic, a secure communication channel with the unsecured device in view of a security level associated with the malware detection logic; receive, by the malware detection logic, an indication that the security level associated with the malware detection logic has changed; discontinue a session associated with the secure communication channel in view of the indication; and prevent an application of the destination device from processing the message.

20. The apparatus of claim 19, wherein the indication comprise a first indication, wherein the at least one processor is configured to: receive, by the malware detection logic, a second indication, wherein the second indication is indictive that a threat level associated with the message has changed; and discontinue a session associated with the secure communication channel in view of the second indication.
