

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250251124

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Brown; Matthew S.

CONTAINER APPARATUS AND METHOD OF USING SAME

Abstract

A container apparatus can include a container and an insert assembly. The insert assembly can include four elongate members. The four elongate members can include light emitting devices for illuminating the interior of the container and/or temperature altering elements for cooling and/or heating the interior of the container. The container can have a rectangular base and a rectangular sidewall extending upwardly from the base. The sidewall can define four corners of the container, and four elongate recesses can be formed in the sidewall proximate the four corners of the sidewall to receive the elongate light members. The recesses can be sized and shaped to conform to the elongate insert members so that the insert members can be releasably retained within the elongate recesses.

Inventors: Brown; Matthew S. (Falkner, MS)

Applicant: FUSE, LLC (Memphis, TN)

Family ID: 55067299

Assignee: FUSE, LLC (Memphis, TN)

Appl. No.: 19/027824

Filed: January 17, 2025

Related U.S. Application Data

parent US continuation 18430002 20240201 parent-grant-document US 12203647 child US 19027824

parent US continuation 18129608 20230331 parent-grant-document US 12195235 child US 18430002

Publication Classification

Int. Cl.: **F21V33/00** (20060101); **B65D25/02** (20060101); **B65D25/10** (20060101); **B65D43/16** (20060101); **B65D81/18** (20060101); **B65D81/38** (20060101); **F21L4/00** (20060101); **F21V21/092** (20060101); **F25D3/08** (20060101); **F25D23/02** (20060101); **F25D23/12** (20060101); **F25D27/00** (20060101)

U.S. Cl.:

CPC **F21V33/008** (20130101); **B65D25/02** (20130101); **B65D25/10** (20130101); **B65D43/16** (20130101); **B65D43/163** (20130101); **B65D81/18** (20130101); **B65D81/3813** (20130101); **F21L4/00** (20130101); **F21V21/0925** (20130101); **F21V33/0004** (20130101); **F21V33/0044** (20130101); **F25D3/08** (20130101); **F25D23/026** (20130101); **F25D23/028** (20130101); **F25D23/12** (20130101); **F25D27/00** (20130101); **F25D2303/08222** (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/430,002, filed Feb. 1, 2024, which is a continuation of U.S. patent application Ser. No. 18/129,608, filed Mar. 31, 2023, now U.S. Pat. No. 12,195,235, which is a continuation of U.S. patent application Ser. No. 17/734,785, filed May 2, 2022, now U.S. Pat. No. 11,619,378, which is a continuation of U.S. patent application Ser. No. 17/239,787, filed Apr. 26, 2021, now U.S. Pat. No. 11,320,140, which is a continuation of U.S. patent application Ser. No. 16/937,834, filed Jul. 24, 2020, now U.S. Pat. No. 11,009,227, which is a continuation of U.S. patent application Ser. No. 16/694,321, filed Nov. 25, 2019, now U.S. Pat. No. 10,738,994, which is a continuation of U.S. patent application Ser. No. 16/364,848, filed Mar. 26, 2019, now U.S. Pat. No. 10,514,164, which is a continuation of U.S. patent application Ser. No. 16/127,659, filed Sep. 11, 2018, now U.S. Pat. No. 10,267,509, which is a continuation of U.S. patent application Ser. No. 15/396,598, filed Dec. 31, 2016, now U.S. Pat. No. 10,088,147, which is a continuation of U.S. patent application Ser. No. 14/862,941, filed Sep. 23, 2015, now U.S. Pat. No. 9,568,186, which is a continuation-in-part of U.S. patent application Ser. No. 14/534,110, filed Nov. 5, 2014, now U.S. Pat. No. 10,018,350, which is a continuation-in-part of International Application No. PCT/US2014/056433, filed Sep. 19, 2014, which claims priority to U.S. patent application Ser. No. 14/031,260, filed Sep. 19, 2013, now U.S. Pat. No. 8,931,910. In addition, U.S. patent application Ser. No. 14/534,110, filed Nov. 5, 2014, is a continuation-in-part of U.S. patent application Ser. No. 14/031,260, filed Sep. 19, 2013. All of the above-referenced applications are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present invention relates to a container apparatus. One embodiment of the invention comprises an insulated cooler that is adapted to receive a removable lighting assembly. The lighting assembly can be secured in the cooler so that it does not move during use, and can be easily removed from the cooler when desired.

BACKGROUND

[0003] It is common when using a container, such as an insulated cooler or toolbox, for the user to desire a light to illuminate the interior of the container. For example, such a light can aid the user in getting a certain food item contained in a cooler or a particular tool in a toolbox at night or in a dimly lit area. Attempts have been made in the prior art to address this need. However, many such prior art devices comprise containers in which lights are electrically wired to the container itself. Such a system can be relatively expensive, and if the lights fail it is generally difficult and

impractical to repair. Also, it can be relatively difficult to replace batteries in such containers.

SUMMARY

[0004] Therefore, one object of the present invention is to provide a container apparatus that can receive and engage an assembly for illuminating the interior of the container.

[0005] Another object of the invention is to provide a container apparatus having an interior lighting assembly that can be easily removed from the container when desired. Yet another object of the invention is to provide a container apparatus having an interior lighting assembly that need not be functionally connected to the container. Yet another object of the invention is to provide a container apparatus having a removable insert assembly comprising a temperature altering element for cooling the interior of the container. These and other objects of the present invention can be achieved in various embodiments of the invention described herein.

[0006] One embodiment of the invention comprises a container apparatus comprising an enclosure having an interior surface, and at least one substantially concave recess formed in the interior surface sized and shaped to receive and engage a light assembly for illuminating an interior area of the enclosure.

[0007] According to another embodiment of the invention, the enclosure comprises a rectangular base and a rectangular sidewall extending upwardly from the base defining four corners of the enclosure.

[0008] According to another embodiment of the invention, at least one elongate recess is formed at one of the four corners defined by the sidewall.

[0009] According to another embodiment of the invention, the container apparatus includes a light assembly having at least one elongate light member, which is positioned within the elongate recess.

[0010] According to another embodiment of the invention, each elongate light member comprises a cooling or heating element. The cooling or heating element can be battery powered.

[0011] According to another embodiment of the invention, the container apparatus includes at least one elongate member positioned within the elongate recess. The elongate recess comprises a cooling or heating element. The cooling or heating element can be battery powered.

[0012] According to another embodiment of the invention, four elongate recesses are formed at the four corners defined by the sidewall.

[0013] According to another embodiment of the invention, four elongate light members are positioned within the four elongate recesses.

[0014] According to another embodiment of the invention, the rectangular sidewall comprises an outer wall section and an inner wall section, the inner wall section having an upper edge positioned below an upper edge of the outer wall section, such that the upper edge of the inner wall section defines a rest platform.

[0015] According to another embodiment of the invention, four elongate recesses are formed at the four corners of the sidewall. The elongate recesses begin at the upper edge of the inner wall section and extending downwardly to the base.

[0016] According to another embodiment of the invention, the container apparatus includes a light assembly comprising a rectangular frame having a perimeter approximately equal to a perimeter defined by the rest platform and defining four corners corresponding to the corners of the enclosure, and four elongate light members extend downwardly from the rectangular frame member. The light members are attached at the corners of the frame and are positioned within the four elongate recesses of the enclosure.

[0017] According to another embodiment of the invention, the rectangular frame of the light assembly rests on the rest platform of the enclosure.

[0018] According to another embodiment of the invention, the enclosure is a thermally insulated cooler.

[0019] According to another embodiment of the invention, the container apparatus includes a lid pivotally attached to the enclosure. The lid can be operatively connected to the light assembly, such

that the light assembly emits light when the lid is opened.

[0020] According to another embodiment of the invention, the container apparatus includes a lid having a transparent or translucent section. As such, light emitting from the light assembly can be visible through the lid.

[0021] According to another embodiment of the invention, the enclosure is a tool box.

[0022] According to another embodiment of the invention, a substantially circular shaped recess is formed in the base of the enclosure.

[0023] According to another embodiment of the invention, a light assembly comprising a circular shaped light is positioned within the circular recess. At least one attachment member is connected to a bottom surface of the light and is releasably attached to the base of the enclosure.

[0024] According to another embodiment of the invention, the attachment member is a suction cup, and a plurality of suction cups are connected to a bottom surface of the light.

[0025] Another embodiment of the invention comprises a container kit comprised of a light assembly having four elongate light members, and a container. The container can comprise a rectangular base and a rectangular sidewall extending upwardly from the base. The sidewall defines four corners of the container, and four elongate recesses are formed in the sidewall proximate the four corners of the sidewall to receive the elongate light members. The recesses are sized and shaped to conform to the elongate light members so that the light members can be releasably retained within the elongate recesses.

[0026] According to another embodiment of the invention, the rectangular sidewall comprises an outer wall section and an inner wall section. The inner wall section has an upper edge positioned below an upper edge of the outer wall section, such that the upper edge of the inner wall section defines a rest platform.

[0027] According to another embodiment of the invention, the light assembly includes a rectangular frame having a perimeter approximately equal to the perimeter of the rest platform, and has four corners corresponding to the corners of the container. The four elongate light members are attached at the four corners of the frame, and the rectangular frame rests on the rest platform of the container.

[0028] A container apparatus according to another preferred embodiment of the invention comprises an enclosure having a base and at least one sidewall extending upwardly from the base. At least one recess is formed in an interior surface of the enclosure and is sized and shaped to receive and engage a light assembly for illuminating an interior area of the enclosure. A lid can be pivotally attached to the sidewall and moveable between a closed position, in which the lid covers the interior of the enclosure and an open position, in which the interior of the enclosure is open and exposed. The lid can have an opening formed therethrough and a translucent or transparent insert section positioned within the opening, so that light emitted by the light assembly is visible through the insert section when the lid is in the closed position.

[0029] According to another embodiment of the invention, the insert section can have a logo formed thereon, such that the logo is illuminated by light emitted from the light assembly.

[0030] Another embodiment of the invention comprises a method of illuminating a container interior that includes providing a container comprising an interior surface having at least one recess formed therein, and a light assembly comprising at least one light member adapted to be received and retained within the recess. The light member is inserted into the recess and illuminates the interior area of the container. The light assembly can be removed from the container by pulling the light member out of the recess.

[0031] A container apparatus according to another embodiment of the invention comprises an enclosure defining an interior area and a light assembly adapted for illuminating the interior area. A substantially concave recess is formed in the interior surface of the enclosure and is adapted for receiving and maintaining the light assembly therein.

[0032] According to another embodiment of the invention, the enclosure comprises a body section

and a lid section connected to the body section.

[0033] According to another embodiment of the invention, the substantially concave recess is formed in the lid section.

[0034] According to another embodiment of the invention, the substantially concave recess is formed in the body section.

[0035] According to another embodiment of the invention, the light assembly comprises at least one light emitting device selected from the group consisting of a light emitting diode, an incandescent light bulb, and an illuminated fiber optic cable.

[0036] According to another embodiment of the invention, the enclosure is comprised of a body section and a lid section. The body section comprises a substantially rectangular base and a substantially rectangular sidewall extending upwardly from the base, and the lid section is pivotally connected to the sidewall of the body section. The substantially concave recess can be formed in the interior surface of the lid section.

[0037] According to another embodiment of the invention, the enclosure comprises a body section comprising a substantially rectangular base and a substantially rectangular sidewall having a top edge, and the substantially concave recess is formed in the top edge of the sidewall.

[0038] According to another embodiment of the invention, the light assembly comprises a substantially rectangular frame adapted for positioning in the recess formed in the top edge of the sidewall, and at least one light emitting device positioned within the frame.

[0039] According to another embodiment of the invention, the enclosure comprises a base for positioning substantially horizontally on a floor surface and a sidewall extending substantially vertically from the base. The substantially concave recess comprises a first channel formed in an interior surface of the sidewall and a complementary second channel formed in the interior surface of the sidewall at a position opposed to the first channel, the first channel and the second channel extending substantially vertically from proximate a top of the sidewall to proximate a bottom of the sidewall.

[0040] According to another embodiment of the invention, the light assembly comprises a substantially flat member received in the first channel and the second channel and adapted for sliding movement therein, such that the light assembly can provide a barrier dividing the interior area defined by the enclosure into a first interior area and a second interior area.

[0041] According to another embodiment of the invention, the base is substantially rectangular and the sidewall is substantially rectangular. The sidewall comprises first and second opposed sides and third and fourth opposed sides. The first channel is formed in the first side and the second channel is formed in the second side.

[0042] A container apparatus according to another embodiment of the invention comprises a body section comprising a base and at least one sidewall extending upwardly from the base, a light emitting device adapted for illuminating at least a portion of the container apparatus, and a lid section pivotally attached to the sidewall. The lid is moveable between a closed position in which the lid covers an interior area of the body and an open position in which the interior area of the body is exposed. The lid has an opening formed therethrough and an insert section positioned within the opening. The insert section is translucent or transparent, such that light emitted by the light assembly is visible through the insert section when the lid is in the closed position.

[0043] A container apparatus according to another embodiment of the invention comprises an enclosure defining an interior area, and at least one substantially concave recess formed in the interior surface of the enclosure. The recess is adapted for receiving and maintaining an insert assembly therein.

[0044] According to another embodiment of the invention, the apparatus includes an insert assembly. The insert assembly can be comprised of a light emitting device adapted for illuminating the interior area of the enclosure, an audio speaker adapted for emitting sound, and/or a dry box container adapted for storing items.

[0045] According to another embodiment of the invention, the insert assembly can be comprised of at least one temperature altering element. The temperature altering element can be a cooling element adapted for cooling the interior area of the enclosure and/or a heating element adapted for heating the interior area of the enclosure.

[0046] According to another embodiment of the invention, the enclosure comprises a body comprising a substantially rectangular base and a substantially rectangular sidewall extending upwardly from the base defining four corners of the body, and wherein the at least one recess comprises four recesses formed at said four corners.

[0047] According to another embodiment of the invention, the enclosure further comprises a lid pivotally connected to the body.

[0048] According to another embodiment of the invention, the apparatus includes an insert assembly comprising four elongate insert members positioned within the four recesses. Each of the four elongate insert members comprises at least one temperature altering element, such as a cooling element or a heating.

[0049] According to another embodiment of the invention, the insert assembly includes a substantially rectangular insert member positioned above the four elongate insert members and supported by a top edge of the sidewall. The substantially rectangular insert member includes at least one light emitting device adapted for illuminating the interior area of the enclosure.

[0050] According to another embodiment of the invention, one or more recesses can be formed in a vehicle, such as a boat or ship. The recesses can be formed in the ship's hull. Each recess can be sized and shaped to receive and engage a complementary insert member. Each insert member can be comprised of a battery powered light emitting device for illuminating the water around the ship. The light emitting devices can project light of various colors. Wireless technology, such as the wireless communication technology sold under the mark "BLUETOOTH", can be used to operatively connect the light emitting devices to a remote control that can turn the light emitting devices on and off.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0051] FIG. 1 is a perspective view of a container apparatus of according to a preferred embodiment of the invention;

[0052] FIG. 2 is another perspective view of the container apparatus of FIG. 1;

[0053] FIG. 3 is a top plan view of the container apparatus of FIG. 1, without a light assembly;

[0054] FIG. 4 is a perspective view of a light assembly according to another preferred embodiment of the invention;

[0055] FIG. 5 is a partial perspective view of a container apparatus according to another preferred embodiment of the invention;

[0056] FIG. 6 is another partial perspective view of the container apparatus of FIG. 5;

[0057] FIG. 7 is a top plan view of a container apparatus according to another preferred embodiment of the invention;

[0058] FIG. 8 is a side cross sectional view of the container apparatus of FIG. 7;

[0059] FIG. 9 is an exploded cross sectional view of a light assembly according to another preferred embodiment of the invention;

[0060] FIG. 10 is a top plan view of the light assembly of FIG. 9;

[0061] FIG. 11 is a side elevation of the light assembly of FIG. 9;

[0062] FIG. 12 is a perspective view of a lid portion of a container apparatus according to a preferred embodiment of the invention;

[0063] FIG. 13 is a cross sectional perspective view of the lid of FIG. 12, taken along lines 13-13

in FIG. **12**;

[0064] FIG. **14** is an exploded perspective view of the lid of FIG. **12**;

[0065] FIG. **15** is an enlarged partial perspective view of the lid of FIG. **12**;

[0066] FIG. **16** is a perspective view of a container apparatus with a lid according to a preferred embodiment of the invention;

[0067] FIG. **17** is a perspective view of a light assembly insert according to another preferred embodiment of the invention;

[0068] FIG. **18** is a perspective view of a container apparatus according to another preferred embodiment of the invention;

[0069] FIG. **19** is another perspective view of the container apparatus of FIG. **18**;

[0070] FIG. **20** is a perspective view of a container apparatus according to another preferred embodiment of the invention;

[0071] FIG. **21** is another perspective view the container apparatus of FIG. **20**;

[0072] FIG. **22** is a perspective view of a container apparatus according to another preferred embodiment of the invention;

[0073] FIG. **23** is a front elevation view of a light assembly insert according to another preferred embodiment of the invention;

[0074] FIG. **24** is a top perspective view of the container apparatus of FIGS. **22**; and

[0075] FIG. **25** is a perspective view of a container apparatus according to another preferred embodiment of the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0076] A container apparatus according to a preferred embodiment of the invention is illustrated in FIGS. **1-3**, and shown generally at reference numeral **10**. As shown in FIG. **1**, the apparatus **10** comprises a container **12** and a light assembly insert **50**. The word “container” as used herein refers generally to any kind of enclosure. For example, the apparatus **10** can comprise a thermally insulated cooler adapted for storing food and beverages. Alternatively, the container **10** can comprise a tool box for storing tools, or other type of enclosure.

[0077] As shown in FIGS. **1-3**, the container **12** comprises a substantially rectangular base **14**, and a substantially rectangular sidewall **16** extending upwardly from the base **14**. The sidewall **16** has four sides defining four corners **21, 22, 23, 24**. The sidewall **16** is comprised of an outer wall section **26** and an inner wall section **36**, as shown in FIGS. **1** and **2**. The surface of the inner wall section **36** defines an interior surface of the container **12**. The top **38** of the inner wall section **36** is lower than the top **28** of the outer wall section **26**, thereby creating a tiered rest platform **38**, as shown in FIG. **1**. The container **12** can be made of plastic or other suitable material, and can be made by injection molding or other suitable manufacturing process. It is to be noted that while container apparatus **10** comprises a substantially rectangular container **12**, the invention is not so limited. Alternatively, the container **12** can be a variety of shapes, such as substantially circular, oval and square.

[0078] Four substantially concave and elongate recesses **31, 32, 33, 34** are formed in the inner wall section **36** proximate the four corners **21, 22, 23, 24**, respectively, of the sidewall **16**, as shown in FIG. **1**. The recesses **31, 32, 33, 34** begin at the top **38** of the inner wall section **36** and extend downwardly to the base **14** of the container **12**, as shown at reference numeral **32** in FIG. **1**. The recesses **31, 32, 33, 34** can have a substantially pentagonal shape, as shown in FIG. **3**.

[0079] The light assembly **50** comprises four elongate light members **51, 52, 53, 54** attached to a rectangular top frame **55**, as shown in FIG. **1**. Each of the four light members **51** are attached at one of the four corners of the rectangular frame **55**, and extend downwardly from the rectangular frame member at an angle of about ninety degrees, as shown in FIG. **1**.

[0080] The elongate recesses **31, 32, 33, 34** in the container **12** are sized and shaped to conform to the elongate light members **51, 52, 53, 54**, in order to receive and retain the light members **51, 52, 53, 54** therein. Accordingly, light members **51, 52, 53, 54** have a length approximately equal to the

length of the recesses **31, 32, 33, 34** extending from the top **38** of the inner wall section **36** to the base **14**, and have a perimeter slightly less than the effective perimeter of the recesses **31, 32, 33, 34**, such that the light members **51, 52, 53, 54** can be inserted into the recesses **31, 32, 33, 34**, as shown in FIGS. **1** and **2**, and retained within the recesses **31, 32, 33, 34** by frictional engagement. [0081] The rectangular frame **55** of the light assembly **50** has a perimeter approximately equal to the perimeter of the rectangular rest platform **38**. As such, the frame **55** rests on the rest platform **38** of the inner wall section **36** when the light members **51, 52, 53, 54** are fully inserted into the recesses **31, 32, 33, 34**, as shown in FIG. **2**. The frame **55** has a height approximately equal to the difference in height between the top edge **28** of the outer wall section **26** and the top edge **38** of the inner wall section **36**, such that the top of the frame **55** sits flush with the top **28** of the outer wall section **26** when the light members **51, 52, 53, 54** are fully inserted into the recesses **31, 32, 33, 34**, as shown in FIG. **2**.

[0082] Alternative embodiments can utilize an additional engagement mechanism for facilitating retention of the light members **51, 52, 53, 54** within the recesses **31, 32, 33, 34**. For example, a plurality of protuberances can be positioned on the outer surface of the light members **51, 52, 53, 54** to engage a plurality of corresponding openings formed on the portion of the inner wall section **36** defining the recesses **31, 32, 33, 34** when the light members **51, 52, 53, 54** are fully inserted into the recesses **31, 32, 33, 34**. The protuberances residing within the openings further retain the light members **51, 52, 53, 54** within the recesses **31, 32, 33, 34**. Alternatively, a plurality of protuberances can be formed on the portion of the inner wall section **36** defining the recesses **31, 32, 33, 34** to engage a plurality of corresponding apertures formed in the light members **51, 52, 53, 54** when the light members **51, 52, 53, 54** are inserted into the recesses **31, 32, 33, 34**.

[0083] Each elongate light member **51, 52, 53, 54** is comprised of a light emitting device, such as a light emitting diode (LED), a low-voltage incandescent light bulb, illuminated fiber optic cables, or other suitable light emitting device. As such, whenever it is desired to illuminate the interior of the container **12**, the light assembly **50** is positioned within the container **12** by inserting the light members **51, 52, 53, 54** into the recesses **31, 32, 33, 34**, as shown in FIGS. **1** and **2**, and turning on the light emitting devices of the light members **51, 52, 53, 54**. In an alternative embodiment, each light member **51, 52, 53, 54** can include a battery powered cooling or heating element. In another alternative embodiment, each elongate member **51, 52, 53, 54** comprises a battery powered cooling or heating element, with no light emitting device.

[0084] Preferably, the light emitting device is powered by disposable or rechargeable batteries. The light emitting devices can be set on a timer such that they automatically turn off after a certain period of time to avoid draining of the batteries. The light assembly **50** is not wired to or otherwise electrically connected to the container **12**, and no electric wiring is located within the container **12**. As such, the light assembly **50** can be easily removed from the container **12** to repair a malfunction in one of the light members **51, 52, 53, 54**, or replace drained batteries. Also, the light assembly **50** can be removed when there is no desire for illumination within the container **12** or when it is desired to replace the light assembly **50** with a new unit. Since the light assembly **50** is not operatively connected to or functionally dependent upon the container **12**, and can be easily removed from the container **12**, the light assembly **50** and container **12** can be manufactured, distributed and/or sold as separate units. Alternatively, the light assembly **50** and container **12** can be distributed and/or sold as components of a container kit.

[0085] In an alternative embodiment, the apparatus **10** can include a lid **70**, shown in FIGS. **12-16**. The lid **70** can be pivotally attached to top of the sidewall **16** of the container **10** via two hinge members **71, 72**, shown in FIGS. **14** and **16**. The lid **70** can be operatively connected to the light assembly **50**, so that the light assembly **50** comes on when the lid **70** is opened. Alternatively, the lid **70** can be operatively connected to the light assembly **50**, such that the light assembly **50** comes on when the lid is closed. The lid **70** includes a center insert **80** positioned within a central opening **74** formed in the center of the lid **70**, as shown in FIGS. **12-14**. The center insert **80** and the central

opening **74** can be substantially rectangular, as shown in FIGS. **12** and **14**. The center insert **80** is comprised of an upper insert section **81** and a lower insert section **82**, and two sealing rings **84**, **85**. The insert sections **81**, **82** are made of a transparent or translucent material, such as polycarbonate plastic. The sealing rings **84**, **85** are made of a sealing material, such as injection molded silicone. One sealing ring **84** is positioned along a recessed top edge of the central opening **74**, below the top surface of the upper insert section **81**, as shown in FIGS. **13** and **15**. The other sealing ring **85** is positioned below the lower insert section **82** on a recessed ledge formed within the central opening **74**, as shown in FIG. **13**. Because the insert sections **81**, **82** are translucent or transparent, light emitting from the light assembly **50** is visible through the insert section **80**. A logo **89**, shown as "LIT" in FIG. **12**, can be engraved on the top surface of the upper insert section **81**. The logo **89** can comprise any alphanumeric characters and/or graphics, such as a company name, trademark, sports team and/or school name or insignia. Light emitting from the light assembly **50** can shine through the insert **80** when the lid **70** is closed on the container **10**, thereby illuminating the logo **89** and making it more visible. Alternatively, the insert section **80** can also include a light emitting device, such as a light emitting diode. It should be noted that while the lid **70** is described above as being a part of container **10**, the lid **70** can also be used with other embodiments of the invention, including the container **100** described below.

[0086] Alternatively, the center insert **80** can be comprised of an audio speaker unit, such as a wireless audio speaker having wireless communications technology sold under the mark "BLUETOOTH". In another alternative embodiment, the center insert **80** can be a dry box container for holding personal items, such as keys, wallets and the like. The container can be made of rubber, plastic or other suitable material.

[0087] In another preferred embodiment of the invention, shown in FIGS. **4-6**, the light assembly comprises a plurality of separate elongate light members **51'**. As such, the light assembly does not include a rectangular frame joining the light members **51'** together, as in the previously described light assembly **50**. In this alternative embodiment, each light member **51'** is separately positioned into a recess **31'**, as shown in FIGS. **5** and **6**.

[0088] A container apparatus according to another preferred embodiment of the invention is illustrated in FIGS. **7-11**, and shown generally at reference numeral **100**. As shown in FIG. **7**, the apparatus **100** comprises a container **112** and a light assembly **150**.

[0089] As shown in FIG. **7**, the container **112** comprises a substantially rectangular base **114**, and a substantially rectangular sidewall **116** extending upwardly from the base **114**. A concave recess **130** is formed proximate the center of the base, as shown in FIG. **8**. The recess **130** can have a circular shape, as shown in FIG. **7**.

[0090] As shown in FIGS. **9-11**, the light assembly **150** comprises a disc shaped light emitting member **151** containing a battery compartment **152**, and a plurality of suction cups **154** attached to the base section **153** of the light emitting member **151**. The light emitting member **151** can be comprised of any light emitting device, such as a light emitting diode (LED), an incandescent light bulb, or illuminated fiber optic cables.

[0091] As shown in FIG. **8**, the light assembly **150** can be positioned within the circular recess **130** formed in the center of the base **114**. Firmly pressing down on the light assembly **150** causes suction cups **154** to engage the base **114**, and prevent the light assembly from coming out of the recess **130** during transport of the container **112**.

[0092] A container apparatus according to another preferred embodiment of the invention is illustrated in FIGS. **17-19**, and shown generally at reference numeral **200**. As shown in FIG. **18**, the apparatus **200** comprises a container **212** and a light assembly insert **250** that can be positioned within the container **212**. The container **212** can be made of plastic or other suitable material, and can be made by injection molding or other suitable manufacturing process.

[0093] The light assembly insert **250** comprises a substantially rectangular frame **255**, and a plurality of light emitting devices **251**, **252**, **253**, **254** positioned in the frame **255** as shown in FIG.

17. The light emitting devices **251-254** can be comprised of light emitting diodes (LED). Alternatively, the light emitting devices **251-254** can comprise low-voltage incandescent light bulbs, illuminated fiber optic cables, or other suitable light emitting devices. The light assembly **250** can include a power source for powering the light emitting devices **251-254**, such as a battery **256** housed within the frame **255** and operatively connected to the light emitting devices **251-254**, as shown in FIG. 17.

[0094] The light assembly insert **250** can be positioned within a substantially concave recess formed in the interior surface of the container **212**. As shown in FIGS. 18-19, the container **212** comprises a substantially rectangular base **214**, and a substantially rectangular sidewall **216** extending upwardly from the base **214**. The sidewall **216** has four sides defining four corners **221**, **222**, **223**, **224**. The sidewall **216** is comprised of an outer wall section **226** and an inner wall section **236**, as shown in FIGS. 18 and 19. The top **238** of the inner wall section **236** is lower than the top **228** of the outer wall section **226**, forming a substantially concave recess in the sidewall **216** defining a tiered rest platform **238**, as shown in FIG. 18.

[0095] The rectangular frame **255** of the light assembly **250** has a perimeter approximately equal to the perimeter of the substantially rectangular rest platform **238**. The rest platform **238** is sized and shaped to receive the light assembly **250** and support the light assembly **250** thereon, as shown in FIGS. 18 and 19. The light assembly frame **255** has a depth (or height) approximately equal to the difference in height between the top edge **228** of the outer wall section **226** and the top edge **238** of the inner wall section **236**, such that the top of the frame **255** sits substantially flush with the top **228** of the outer wall section **226** when the light assembly **250** is positioned in the rest platform **238**, as shown in FIG. 19.

[0096] As such, the light assembly **250** can be easily installed and removed from the container **212** depending on the needs or desires of the user. When the user wishes to illuminate the interior of the container **212**, the light assembly **250** is positioned on the rest platform **238**, as shown in FIG. 19. The light assembly **250** is securely retained within the rest platform **238** during movement of the container **212**. When the user does not want to illuminate the interior of the container **212**, the user can lift up on the light assembly **250** and remove it from the container **212**.

[0097] A container apparatus according to another preferred embodiment of the invention is illustrated in FIGS. 20 and 21, and shown generally at reference numeral **300**. The container apparatus **300** comprises a container **312** having an interior surface that is adapted for receiving and releasably maintaining an insert assembly **350** therein. The container **312** can be made of plastic or other suitable material, and can be made by injection molding or other suitable manufacturing process.

[0098] As shown in FIGS. 20 and 21, the container **312** comprises a substantially rectangular base **314**, and a substantially rectangular sidewall **316** extending upwardly from the base **314**. The sidewall **316** has four sides defining four corners **321**, **322**, **323**, **324**. The sidewall **316** is comprised of an outer wall section **326** and an inner wall section **336**, as shown in FIGS. 20 and 21. The surface of the base **314** and the surface of the inner wall section **336** define interior surfaces of the container **312**. The top **238** of the inner wall section **236** is lower than the top **328** of the outer wall section **326**, thereby creating a tiered rest platform **338**, as shown in FIG. 20.

[0099] Four substantially concave and elongate recesses **331**, **332**, **333**, **334** are formed in the inner wall section **336** proximate the four corners **321**, **322**, **323**, **324**, respectively, of the sidewall **316**, as shown in FIG. 20. The recesses **331**, **332**, **333**, **334** begin at the top **338** of the inner wall section **336** and extend downwardly to the base **314** of the container **312**, as shown at reference numeral **332** in FIG. 20. The recesses **331**, **332**, **333**, **334** can have a substantially pentagonal shape.

[0100] The insert assembly **350** comprises four elongate temperature altering members **351**, **352**, **353**, **354**, shown in FIG. 20. Each temperature altering member **351**, **352**, **353**, **354** can be comprised of a vessel containing a refrigerant gel, such as a gel formulation comprised of propylene glycol and water or other suitable materials. Other refrigerant gel compositions are

disclosed in U.S. Pat. No. 4,357,809, which is incorporated herein.

[0101] The elongate recesses **331**, **332**, **333**, **334** in the container **312** are sized and shaped to conform to the elongate members **351**, **352**, **353**, **354**, in order to receive and retain the elongate members **351**, **352**, **353**, **354** therein. Accordingly, elongate members **351**, **352**, **353**, **354** have a length approximately equal to the length of the recesses **331**, **332**, **333**, **334** extending from the top **338** of the inner wall section **336** to the base **314**, and have a perimeter slightly less than the effective perimeter of the recesses **331**, **332**, **333**, **334**, such that the elongate members **351**, **352**, **353**, **354** can be inserted into the recesses **331**, **332**, **333**, **334**, as shown in FIGS. **20** and **21**, and retained within the recesses **331**, **332**, **333**, **334** by frictional engagement.

[0102] Prior to being positioned into the container **312**, the temperature altering members **351**, **352**, **353**, **354** can be stored in a freezer or refrigerator. When the container **312** is to be used to keep items cool, the elongate members **351**, **352**, **353**, **354** are removed from the freezer/refrigerator and positioned into the elongate recesses **331**, **332**, **333**, **334** of the container **312**, as described above. As such, the cooled elongate members **351**, **352**, **353**, **354** cool the interior surface and interior area of the container **312**, thereby helping to maintain the stored items at a cooler temperature for a longer period of time. Alternatively, the temperature altering members **351**, **352**, **353**, **354** can comprise a heating gel, such as gels that can be heated in the microwave typically used in heating packs. Each member **351**, **352**, **353**, **354** comprises a vessel made of material such as plastic that is safe for placement in a microwave. As such, the heated elongate members **351**, **352**, **353**, **354** can heat the interior area of the container **312** to maintain the stored items at a warmer temperature for a longer period of time. In yet another alternative embodiment, the elongate members **351**, **352**, **353**, **354** comprise a gel material that can be used for both heating and cooling. As such, the user can selectively use the elongate members **351**, **352**, **353**, **354** for cooling by storing them in a freezer or refrigerator prior to use, or use the members **351**, **352**, **353**, **354** for heating by heating the members **351**, **352**, **353**, **354** in a microwave before use.

[0103] The insert assembly **350** comprises a substantially rectangular top frame **355** having a plurality of light emitting devices **361**, **362**, **363**, **364** positioned in the frame **355** as shown in FIGS. **20** and **21**. The light emitting devices **361-364** can be comprised of light emitting diodes (LED). Alternatively, the light emitting devices **361-364** can comprise low-voltage incandescent light bulbs, illuminated fiber optic cables, or other suitable light emitting devices. The frame **355** can include a power source for powering the light emitting devices **361-364**, such as a battery housed within the frame **355** and operatively connected to the light emitting devices **361-364**, as shown in FIG. **17**.

[0104] As shown in FIGS. **20** and **21**, the top **338** of the inner wall section **336** is lower than the top **328** of the outer wall section **326**, forming a substantially concave recess in the sidewall **316** defining a tiered rest platform **338**, as shown in FIG. **20**. The rectangular frame **355** of the light assembly **350** has a perimeter approximately equal to the perimeter of the substantially rectangular rest platform **338**. The rest platform **338** is sized and shaped to receive the frame **350** and support the frame **350** thereon, as shown in FIGS. **20** and **21**. The frame **355** has a depth (or height) approximately equal to the difference in height between the top edge **328** of the outer wall section **326** and the top edge **338** of the inner wall section **336**, such that the top of the frame **355** sits substantially flush with the top **328** of the outer wall section **326** when the frame **355** is positioned in the rest platform **338**, as shown in FIG. **21**. As such, the interior of the container **312** can be illuminated by the light emitting devices **361-364** of the top frame **355**, and the interior of the container **312** can be cooled or heated by the temperature altering members **351**, **352**, **353**, **354**.

[0105] A container apparatus according to another preferred embodiment of the invention is illustrated in FIGS. **22-24**, and shown generally at reference numeral **400**. The apparatus **400** comprises a container body **412**, and a light assembly insert **450**. A lid **470** can be connected to the container body **412**. The container body **412** and the lid **470** can be made of plastic or other suitable material, and can be made by injection molding or other suitable manufacturing process.

[0106] The container body **412** comprises a substantially rectangular base **414** for positioning substantially horizontally on a floor surface, and a substantially rectangular sidewall **416** extending substantially vertically from the base **414**. The sidewall **416** has four sides **421**, **422**, **423**, **424**. Two substantially concave and elongate recesses **431**, **432** are formed in the interior surface on opposing sides **401**, **402** of the sidewall **416**, as shown in FIG. 22. The recesses **431**, **432** define channels beginning at the top edge **418** of the sidewall **416** and extending downwardly to the base **414** of the container **412**, as shown in FIG. 22. The channels **431**, **432** extend substantially vertically, and are substantially perpendicular to the container base **414**.

[0107] As shown in FIGS. 22-24, the insert **450** comprises a substantially flat and rectangular member having a first group of light emitting devices **461** positioned on one side of the insert **450**, and a second group of light emitting devices **462** positioned on the opposite side of the insert **450**. The light emitting devices can comprise light emitting diodes (LED), a low-voltage incandescent light bulb, illuminated fiber optic cables, or other suitable light emitting devices. A power source such as a battery **466** can be positioned within the insert **450** and operatively connected to the light emitting devices **461**, **462**.

[0108] The recessed channels **431**, **432** are shaped and sized to receive and conform to the side edges **451**, **452** of the light assembly insert **450** and are positioned in opposed complementary alignment, as shown in FIGS. 22 and 24, such that the side edges **451**, **452** can slide up and down within the channels **431**, **432**. As shown in FIG. 22, the insert side edges **451**, **452** and the recessed channels **431**, **432** can have a substantial arrow head shape. The insert **450** can include an opening **455** formed therein through which the user can grasp the light assembly **450**. Alternatively, the insert **450** can include a temperature altering element, such as a refrigerant gel. The refrigerant gel can be a gel formulation comprised of propylene glycol and water or other suitable materials.

[0109] When the user wishes to illuminate the interior of the container body **412**, the insert **450** is slid down the recessed channels **431**, **432** until the bottom edge of the insert **450** rests on the base **414** of the container body **412**. The insert **450** is retained in an upright position within the channels **431**, **432**, as shown in FIG. 24. As such, the light emitting devices **461**, **462** of the insert **450** can illuminate the interior of the container body **412**. In addition, the insert **450** acts as a divider that separates the interior of the container body **412** into two separate sections, as shown in FIG. 24. When desired, the insert **450** can be easily removed by grasping through the opening **455** and lifting the insert **450** upwardly out of the recessed channels **431**, **432**.

[0110] It is to be noted that while the container apparatus **400** is described and shown in the drawings as having a substantially rectangular container body **412**, the invention is not so limited. Alternatively, the container body **412** can be a variety of shapes, such as substantially circular, oval and square.

[0111] A container apparatus according to another preferred embodiment of the invention is illustrated in FIG. 25, and shown generally at reference numeral **500**. As shown in FIG. 25, the apparatus **500** comprises a substantially rectangular body section **512**, a lid section **570** connected to the body **512**, and an insert assembly **550**. The body **512** comprises a substantially rectangular base **514** and a substantially rectangular sidewall **516** extending upwardly from the base. The lid **570** can be pivotally attached to the sidewall **516** of the body **512** by hinges **571**, **572**. The body **512** and the lid **570** define an enclosure in which items such as food and beverages can be stored. The apparatus **500** can be made of plastic or other material suitable for a thermally insulated cooler.

[0112] The insert assembly **550** can be positioned within a substantially concave recess **530** formed in the interior surface of the lid **570**, as shown in FIG. 25. The recess **530** is sized and shaped to conform to the size and shape of the light assembly **550** so as to receive and retain the light assembly **550** therein by frictional engagement. Alternatively, the insert assembly **550** can be held within the recess **530** by other attachment means, such as suction cups or adhesive. As shown in FIG. 25, the insert assembly **550** and the recess **530** can be substantially rectangular. Alternatively, the insert assembly **550** and the recess **530** can be other shapes, such as circular or oval.

[0113] The insert assembly 550 can comprise at least one light emitting device, such as a light emitting diode (LED), a low-voltage incandescent light bulb, illuminated fiber optic cables, or other suitable light emitting device. Whenever it is desired to illuminate the interior of the container 500, the insert assembly 550 can be positioned within the recess 530 and the light emitting device turned on. Alternatively, the insert assembly 550 can include a battery powered cooling or heating element. In another alternative embodiment, the insert assembly 550 can be comprised of an audio speaker unit, such as a wireless audio speaker having wireless communications technology sold under the mark “BLUETOOTH”. In yet another alternative embodiment, the insert assembly 550 can be a dry box container for holding personal items, such as keys, wallets and the like. The container can be made of rubber, plastic or other suitable material.

[0114] It should be noted that the invention is not limited to the embodiments described above. In particular, the light assembly of the invention can be a variety of sizes and shapes, and the container can have one or more recesses sized and shaped to compliment the particular size and shape of the light assembly and facilitate insertion of the light assembly into the container. For example, the light assembly can comprise one or more rectangular panels containing light emitting devices that are inserted into one more recesses in the container. Also, while particular embodiments of the invention comprise substantially rectangular containers, the invention is not so limited. Containers of the invention can be a variety of shapes, including substantially square, circular and oval. U.S. Provisional Application Ser. No. 61/204,016, filed Jan. 2, 2009, titled “LIGHTED ENCLOSURE ASSEMBLY”, is incorporated herein by reference.

[0115] A container apparatus and a method of using same are described above. Various changes can be made to the invention without departing from its scope. The above description of preferred embodiments and best mode of the invention are provided for the purpose of illustration only and not limitation-the invention being defined by the claims and equivalents thereof.

Claims

1. A container kit comprising: (a) an enclosure comprising a substantially rectangular base and a substantially rectangular sidewall extending upwardly from the base, the sidewall comprising first and second opposed sides and third and fourth opposed sides, the base and the sidewall defining an interior area of the enclosure; (b) a first substantially concave channel formed in the first side of the sidewall and a complementary second substantially concave channel formed in the second side of the sidewall at a position opposed to the first concave channel, the first substantially concave channel and the second substantially concave channel extending substantially vertically from proximate a top of the sidewall to proximate a bottom of the sidewall; and (c) at least one insert assembly comprising a temperature altering element adapted to alter a temperature within the interior area of the enclosure, the insert assembly comprising a substantially flat member partially received in the first substantially concave channel and the second substantially concave channel and adapted for sliding movement therein, whereby the insert assembly provides a barrier dividing the interior area of the enclosure into a first interior area and a second interior area.
2. The container apparatus according to claim 1, wherein the at least one insert assembly is not electrically connected to the enclosure.
3. The container kit according to claim 1, wherein the at least one insert assembly has an opening therethrough, whereby the at least one insert assembly can be grasped by a user.
4. The container kit according to claim 1, wherein the temperature altering element comprises a cooling element adapted to lower a temperature within the container.
5. The container kit according to claim 4, wherein the enclosure comprises a thermally insulated cooler.
6. The container kit according to claim 4, wherein the at least one insert assembly contains a refrigerant gel.

7. The container kit according to claim 6, wherein the refrigerant gel comprises propylene glycol.
8. The container kit according to claim 1, wherein the at least one insert assembly is substantially rectangular and includes a first side edge and a second side edge opposed to the first side edge, further wherein the first substantially concave channel is shaped and sized to receive the first side edge of the insert assembly, and the second substantially concave channel is adapted to receive the second side edge of the insert assembly.
9. The container kit according to claim 8, wherein the at least one insert assembly has an opening therethrough, whereby a user can grasp the at least one insert assembly.
10. The container kit according to claim 1, wherein the at least one insert assembly can be removed from the container without removing any other component of the enclosure.
11. The container kit according to claim 1, further comprising a lid pivotally connected to an upper edge of the first side of the sidewall.
12. The container kit according to claim 1, wherein the at least one insert assembly includes an audio speaker adapted for emitting sound.
13. The container kit according to claim 1, wherein the at least one insert assembly includes a light emitting device adapted to illuminate at least a portion of the interior area of the enclosure.
14. The container apparatus according to claim 13, wherein the at least one light emitting device is selected from the group consisting of a light emitting diode, an incandescent light bulb, and an illuminated fiber optic cable.
-