

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250254475

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Solum; Jeffrey Paul

MULTI-MODE RADIO FOR HEARING ASSISTANCE DEVICES

Abstract

The present disclosure relates to the wireless communication of information for a hearing assistance device including a multi-mode radio adapted to provide communications at different frequencies using frequency control. In applications of hearing aids, the processor is adapted to perform correction of sound for a hearing impaired user. In certain examples the present subject matter provides an inductive portion for inductive communications. In various applications the multi-mode radio can be used for long range and short range communications.

Inventors: Solum; Jeffrey Paul (Greenwood, MN)
Applicant: Starkey Laboratories, Inc. (Eden Prairie, MN)
Family ID: 44513287
Appl. No.: 19/008040
Filed: January 02, 2025

Related U.S. Application Data

parent US continuation 18452371 20230818 parent-grant-document US 12212933 child US 19008040
parent US continuation 17750962 20220523 parent-grant-document US 11770661 child US 18452371
parent US continuation 16906459 20200619 parent-grant-document US 11343622 child US 17750962
parent US continuation 15963461 20180426 parent-grant-document US 10694300 child US 16906459
parent US continuation 15250130 20160829 parent-grant-document US 9967683 child US 15963461
parent US continuation 12830290 20100703 parent-grant-document US 9432780 child US 15250130

Publication Classification

Int. Cl.: H04R25/00 (20060101); H04B7/26 (20060101)

U.S. Cl.:

CPC H04R25/554 (20130101); H04B7/26 (20130101); H04R25/558 (20130101);
H04R2225/51 (20130101)

Background/Summary

PRIORITY CLAIM [0001] This application is a continuation of U.S. application Ser. No. 18/452,371, filed Aug. 18, 2023, which is a continuation of U.S. application Ser. No. 17/750,962, filed May 23, 2022, now issued as U.S. Pat. No. 11,770,661, which is a continuation of U.S. application Ser. No. 16/906,459, filed Jun. 19, 2020, issued as U.S. Pat. No. 11,343,622, which is a continuation of U.S. application Ser. No. 15/963,461, filed Apr. 26, 2018, issued as U.S. Pat. No. 10,694,300, which application is a continuation of U.S. application Ser. No. 15/250,130, filed Aug. 29, 2016, issued as U.S. Pat. No. 9,967,683, which is a continuation of U.S. application Ser. No. 12/830,290, filed Jul. 3, 2010, issued as U.S. Pat. No. 9,432,780, each of which are incorporated by reference herein in their entirety.

FIELD OF THE INVENTION

[0002] The present subject matter relates generally to hearing assistance devices, including, but not limited to hearing aids, and in particular to a multi-mode radio for hearing assistance devices.

BACKGROUND

[0003] Modern hearing assistance devices typically include digital electronics to enhance the wearer's experience. In the specific case of hearing aids, current designs employ digital signal processors rich in features. Their functionality is further benefited from wireless communications. However, different countries have different frequency bands available for use. And the amount of absorption of radio signals changes significantly with frequency of the signals. Furthermore, communications at different frequencies can require substantially different electronics in various cases.

[0004] What is needed in the art is an improved radio for communications for hearing assistance devices.

SUMMARY

[0005] Disclosed herein, among other things, are methods and apparatus for hearing assistance devices, including, but not limited to hearing aids, and in particular to a multi-mode radio for hearing assistance devices.

[0006] The present disclosure relates to the wireless communication of information for a hearing assistance device including a multi-mode radio adapted to provide communications at different frequencies using frequency control. In applications of hearing aids, the processor is adapted to perform correction of sound for a hearing impaired user. In certain examples the present subject matter provides an inductive portion for inductive communications. In various applications the multi-mode radio can be used for long range and short range communications.

[0007] This Summary is an overview of some of the teachings of the present application and not intended to be an exclusive or exhaustive treatment of the present subject matter. Further details about the present subject matter are found in the detailed description and appended claims. The scope of the present invention is defined by the appended claims and their legal equivalents.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a block diagram of a hearing assistance device with a communications module including a multi-mode radio, according to one embodiment of the present subject matter.

[0009] FIG. 2 is a block diagram of a multi-mode radio system for long and short range communications in a hearing assistance device, according to one embodiment of the present subject matter.

[0010] FIG. 3 is a block diagram of a receiver design for a communications module according to one embodiment of the present subject matter.

[0011] FIG. 4 is a block diagram of a receiver design for a communications module according to one embodiment of the present subject matter.

[0012] FIG. 5 is a block diagram of a receiver design for a communications module according to one embodiment of the present subject matter.

[0013] FIG. 6 is a block diagram of a receiver design for a communications module according to one embodiment of the present subject matter.

DETAILED DESCRIPTION

[0014] The following detailed description of the present subject matter refers to subject matter in the accompanying drawings which show, by way of illustration, specific aspects and embodiments in which the present subject matter may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the present subject matter. References to “an”, “one”, or “various” embodiments in this disclosure are not necessarily to the same embodiment, and such references contemplate more than one embodiment. The following detailed description is demonstrative and not to be taken in a limiting sense. The scope of the present subject matter is defined by the appended claims, along with the full scope of legal equivalents to which such claims are entitled.

[0015] The present subject matter relates generally to hearing assistance devices, including, but not limited to hearing aids, and in particular to a multi-mode radio system for long and short range communications for hearing assistance device applications.

[0016] Frequencies available for wireless communication such as the ISM frequencies at 900 MHz and 2.4 GHz offer a large amount of bandwidth and allow sufficient RF power to cover many uses for hearing assistance devices. However the frequencies around 900 MHz are not allocated for worldwide coverage. In addition frequencies above 900 MHz are absorbed by human tissue such that a body shadow effect must be accounted for when computing the link budget for ear to ear and ear to body worn electronics. Magnetic links below 30 MHz work well for ear to ear communication and ear to body worn devices since these frequencies are not absorbed significantly by human tissue. Magnetic links also have the advantage of world-wide regulatory acceptance. Frequencies from 100 MHz to 400 MHz have been shown to propagate on the skin of the body and exhibit a loss that is less than that of free space when worn on or near the human body. In addition, legacy narrow band analog FM assisted listening devices exist that have a frequency allocation in the 164-217 MHz band throughout the world.

[0017] FIG. 1 is a block diagram of a hearing assistance device **100** with a communications module **160** including a multi-mode radio **150** according to one embodiment of the present subject matter. The radio **150** receives a frequency control signal **120** that can be set by a variety of mechanisms in various embodiments. In one embodiment, frequency control signal **120** is controlled by processor **130**. In one embodiment, frequency control signal **120** is controlled by combinational logic. In one embodiment, frequency control signal **120** is controlled by radio circuits, including, but not limited to a received signal strength indication (RSSI) module to provide input to the selection of frequency by the multi-mode radio **150**. These and other types of controls may be used singularly

or in combination without departing from the scope of the present subject matter.

[0018] In various embodiments the control signal **120** is used to control the frequency of operation of multi-mode radio **150**. In various embodiments the control signal **120** is used to control modulation mode of multi-mode radio **150**. In various embodiments the control signal **120** is used to select high frequency communications. In various embodiments the control signal **120** is used to select low frequency communications. In various embodiments the control signal **120** is used to select a mode of operation of the multi-mode radio **150**. Some embodiments include but are not limited to near range communications, long range communications, and/or combinations of near range and long range communications. Various communication parameters including, but not limited to, combinations of frequencies, modulation techniques, and signal strengths can be controlled in various embodiments. Other communications parameters can be selected without departing from the scope of the present subject matter.

[0019] In various embodiments the information signal **140** includes information received by multi-mode radio **150**. In various embodiments the information signal **140** includes information transmitted by multi-mode radio **150**. In various embodiments the information signal **140** includes control information. In various embodiments information signal **140** is unidirectional. In various embodiments information signal **140** is bidirectional. In various embodiments information signal **140** is half duplex. In various embodiments information signal **140** is full duplex. Other modes and uses of information signal **140** are possible without departing from the scope of the present subject matter.

[0020] In various embodiments, the information signal **140** is an output from communications module **160**. In various embodiments, the information signal **140** is an input to the communications module **160**. In various embodiments, the information signal **140** is communicated as a bidirectional signal from and to the processor **130**.

[0021] In one embodiment multi-mode radio **150** is a receiver. In one embodiment, multi-mode radio **150** is a transmitter. In various embodiments multi-mode radio **150** performs transmitter and receiver (transceiver) functions. Thus, antenna **110** is used for reception and/or transmission depending on the embodiment of the present subject matter. It is understood that antenna **110** can be any of a variety of antenna types, including a tuned antenna, a multiband antenna, and a broadband antenna. It is understood that antenna **110** can be a variety of structures, including, but not limited to a single element or an antenna array. In various embodiments the antenna **110** is part of the electronics and designed to be integral with the communication module **160**. In various embodiments the antenna **110** is electrically connected to communications module **160** but is integral with some other structure. Such other structures include but are not limited to: an antenna element disposed in or on a receiver connector, such as used in a receiver-in-canal (RIC) or receiver-in-the-ear (RITE) designs; an antenna that is integral to the hearing assistance device housing; or a flex tape antenna that can be disposed at least partially within the housing.

[0022] Some antenna configurations and related teachings include but are not limited to the following patent applications, which are all hereby incorporated by reference in their entirety: U.S. patent application Ser. No. 10/768,735 (now issued as U.S. Pat. No. 7,256,747); Ser. No. 11/676,420 (now issued as U.S. Pat. No. 7,446,720); Ser. No. 11/357,751 (now issued as U.S. Pat. No. 7,593,538); Ser. No. 12/027,151, filed Feb. 6, 2008; Ser. No. 12/550,821, filed Aug. 31, 2009; Ser. No. 12/340,600, filed Dec. 19, 2008; Ser. No. 12/340,604, filed Dec. 19, 2008; and Ser. No. 12/638,720, filed Dec. 15, 2009. Other antenna configurations and hardware are possible without departing from the scope of the present subject matter.

[0023] It is understood that various tuning approaches can be used including, but not limited to, selection of a tuned antenna appropriate for the frequency of operation from a plurality of tuned antennas, automatic matching of an antenna for a selected frequency of operation, a broadband antenna approach and combinations of the foregoing.

[0024] In various embodiments processor **130** is adapted to perform hearing assistance processing

on the information signal **140**. In various embodiments processor **130** includes a digital signal processor. In various embodiments processor **130** includes a microprocessor. In various embodiments processor **130** includes combinational logic. In various embodiments processor **130** is a microcontroller. For example, in hearing aid applications processor **130** is adapted to perform functions associated with programmable gain to improve hearing of a subject with hearing loss. Some embodiments may include one or more aspects including, but not necessarily limited to sub band processing, acoustic feedback cancellation, entrainment reduction, adjustable gain, compression, and/or limiting.

[0025] In various embodiments processor **130** is adapted to provide an information signal **140** to communications module **160**. In various applications, processor **130** is further adapted to control the frequency of operation of the multi-mode radio **150**. In various embodiments, processor **130** is adapted to provide mode control of communications module **160** and/or multi-mode radio **150**. For example, one type of mode selection is that the communications module **160** can be used to receive, transmit, or transceive information, in various embodiments of the present subject matter. In various embodiments of the present subject matter communications module **160** is adapted to perform different demodulation and/or modulation techniques, including, but not limited to one or more of frequency frequency shift keying (FSK), frequency modulation (FM), amplitude modulation (AM), single sideband (SSB), spread spectrum, quaternary amplitude modulation (QAM), phase shift keying (PSK), quaternary phase shift keying (QPSK) or pulse width modulation (PWM). In various embodiments the multi-mode radio **150** is adapted to perform transmission and reception at different frequencies. In various embodiments the multi-mode radio **150** is adapted to perform transmission and reception using different modulation techniques. In various embodiments the multi-mode radio **150** is adapted to support hybrid modulation techniques. One such example includes the combination of digital and analog communications, including, but not limited to the communications discussed in U.S. patent application Ser. No. 12/645,007, which is hereby incorporated by reference in its entirety. In various embodiments the multi-mode radio **150** includes control of one or more of the following aspects including but not limited to antenna selection and/or antenna matching. Thus, the present system can provide flexibility and programmability of operation that can be controlled by processor **130**, communications module **160**, or combinations including one or both of processor **130** and communications module **160**.

[0026] The multi-mode radio with frequency control allows a hearing assistance device to use a variety of frequencies with minimal or no change in hardware. It also allows a system to use multiple bands to enhance communications based on conditions and/or applications. For example, in designs where signals may have to be received through body tissue, lower frequencies with less absorption can be used. Thus, the system allows for frequency or band diversification with minimal impact to the hardware design. Such designs also allow for programmable channel applications.

[0027] In various applications where hearing assistance device **100** is a hearing aid, the device can include one or more of a microphone (or a plurality of microphones), a receiver (also known as a speaker), a telecoil, signal processing electronics, wireless electronics, an antenna, and a housing for the electronics. In some embodiments, the hearing aid includes a connector between the receiver and the housing. In some embodiments, the hearing aid includes a sound tube. In various applications the hearing assistance device is an implant, such as a cochlear implant, which includes one or more electrodes adapted to provide an electrical signal for hearing. These applications are for demonstration only and not intended to be exclusive or exhaustive applications of the present subject matter.

[0028] FIG. **3** is a block diagram of a receiver design for the communications module **160** according to one embodiment of the present subject matter. A signal from the antenna **110** is amplified by low noise amplifier **314** and sent to mixer **320** which receives a local oscillator signal from local oscillator **322**. The frequency of the local oscillator is controlled by frequency control

signal **120**. The mixed signal is sent to bandpass filter **326** which is adapted to pass the information signals of interest to demodulator **328**. Demodulator **328** provides an information signal **140** as its output. In various embodiments the frequency control is provided internally by the multi-mode radio. For example, in various embodiments communications module **160** includes additional hardware to receive and process control signal **120** and/or information signal **140**. The receiver design shown is intended to demonstrate a receive function of communications module **160**. It is understood that variations in components, connections, and implementation may be performed without departing from the scope of the present subject matter and that the demonstrated embodiments are not intended to be exhaustive or exclusive.

[0029] FIG. **5** is a block diagram of a receiver design for the communications module **160** according to one embodiment of the present subject matter. A signal from the antenna **110** is amplified by low noise amplifier **314** and sent to switch **551** which can direct the signal directly to switch **552** via connection **560** or to mixer **320** which receives a local oscillator signal from local oscillator **322**. In various embodiments, the switching of switches (or multiplexer/demultiplexer) **551** and **552** are controlled by control signal **120**. In various embodiments the frequency of the local oscillator is controlled by frequency control signal **120**. The signal from switch **552** is sent to bandpass filter **326** which is adapted to pass the information signals of interest to demodulator **328**. Demodulator **328** provides an information signal **140** as its output. In various embodiments the frequency control is provided internally by the multi-mode radio. For example, in various embodiments communications module **160** includes additional hardware to receive and process control signal **120** and/or information signal **140**. The receiver design shown is intended to demonstrate a receive function of communications module **160**. In various embodiments the control signals to the switches **551** and **552** are different than the control signal to the local oscillator **322**. It is understood that variations in components, connections, and implementation may be performed without departing from the scope of the present subject matter and that the demonstrated embodiments are not intended to be exhaustive or exclusive.

[0030] In various embodiments the present subject matter provides an inductive communication mode that can be used in conjunction with the multi-mode radio **150** described above in FIG. **1**.

[0031] FIG. **2** is a block diagram of a multi-mode radio system for long and short range communications in a hearing assistance device, according to one embodiment of the present subject matter. FIG. **2** shows a communications module **160** that includes a high frequency radio **210** with antenna **211** and a low frequency radio **220** and antenna **221**. In various embodiments the high frequency radio **210** and low frequency radio **220** are selectable for communications of information signal **140** using interface **230**. In various embodiments, the information signal **140** is unidirectional. In various embodiments the information signal **140** is bidirectional. In various embodiments the information signal **140** is provided by reception by the high frequency radio **210** or the low frequency radio **220** or both. In various embodiments the information signal **140** is transmitted by the high frequency radio **210** or the low frequency radio **220** or both. In various embodiments a transceiver function is supported by the high frequency radio **210** or the low frequency radio **220** or both. In various embodiments the low frequency radio **220** is an inductive radio **210**. In various embodiments the interface **230** is realized in a processor. In various applications the radio system can support concurrent receive or transmit events using the high frequency radio **210** and the low frequency radio **220**. Thus, the system is highly programmable and adaptable.

[0032] In various embodiments the interface **230** provides information including, but not limited to, one or both of frequency control information or device enable information to the high frequency radio **210** and the low frequency radio **220** using one or both of the information signal **140** and/or the control signal **120**. In various embodiments, the present subject matter provides encryption to the transmissions which is supported by communications between the blocks in the system of hearing assistance device **200**. In various embodiments, the present subject matter provides

decryption to receptions of hearing assistance device **200**. In various embodiments antenna **211** and antenna **221** are realized using a single antenna structure. In various embodiments the single antenna structure is provided using multiplexing of signals between the high frequency radio **210** and the low frequency radio **220**. In various embodiments the single antenna structure is provided using multiband antenna designs adapted to operate with the high frequency radio **210** and the low frequency radio **220**. In various embodiments antenna **211** and antenna **221** are separate antennas. [0033] Thus, high frequency radio **210**, low frequency radio **220**, and interface **230** are the blocks of multi-mode radio **150** in various embodiments. It is understood that the discussion above for multi-mode radio **150** applies to the operation of high frequency radio **210**, low frequency radio **220**, and interface **230**.

[0034] FIG. **4** is a block diagram of a receiver design for the communications module **160** according to one embodiment of the present subject matter. In a first mode a signal from the antenna **211** is amplified by low noise amplifier **314** and sent to mixer **320** which receives a local oscillator signal from local oscillator **322**. The frequency of the local oscillator is controlled by frequency control signal **120**. In the first mode the multiplexer **441** connects the output of mixer **320** with bandpass filter **326** which is adapted to pass the information signals of interest to demodulator **328**. Demodulator **328** provides an information signal **140** as its output. In various embodiments the frequency control is provided internally by the multi-mode radio. In a second mode communications received by antenna **221** are amplified by low noise amplifier **418** and sent to mixer **420** which also receives a local oscillator signal from local oscillator **422**. The output of mixer **420** is sent to bandpass filter **326** via multiplexer **441**, depending on the input to multiplexer **441**. In various embodiments the input to multiplexer comes from control signal **120**. In various embodiments other signals are used to control multiplexer **441**.

[0035] The output of bandpass filter **326** is demodulated using demodulator **328** to provide information signal **140**. The receiver design shown is intended to demonstrate a receive function of communications module **160**. It is understood that variations in components, connections, and implementation may exist without departing from the scope of the present subject matter and that the demonstrated embodiments are not intended to be exhaustive or exclusive. For example, it is understood that in various embodiments separate channels can be used for demodulation to provide concurrent reception of signals from antennas **211** and **221**. Thus, the present design is demonstrative of only one approach which uses the same baseband demodulation modules, but other embodiments are contemplated by the present disclosure.

[0036] FIG. **6** is a block diagram of a receiver design for the communications module **160** according to one embodiment of the present subject matter. The embodiment shown in FIG. **6** is similar to that of FIG. **4** except mixer **320** and local oscillator **322** are omitted and the signal from LNA **314** is transferred directly to multiplexer **441**. Therefore, this design employs a single local oscillator **422**.

[0037] In various applications hearing assistance device (**100**) is a hearing aid. In various applications the wireless communications are between two hearing assistance devices. In various applications the wireless communications are between a first hearing aid and a second hearing aid. In various applications the wireless communications are between a hearing assistance device and any other wireless device. In various applications, the hearing assistance device communicates with a second device that is a wireless audio controller. Some examples of wireless audio controllers are found in U.S. Patent Application Publication 2006/0274747, titled: COMMUNICATION SYSTEM FOR WIRELESS AUDIO DEVICES, and PCT Application Publication WO 2006/133158, titled: COMMUNICATION SYSTEM FOR WIRELESS AUDIO DEVICES, which are both hereby incorporated by reference in their entirety. In various applications, the second wireless device can be any wireless device, and the examples provided herein are intended to demonstrate the present subject matter, but not to limit it to the examples provided herein.

[0038] The present subject matter provides various communications, including, but not limited to,

one or more of: ear-to-ear communications; ear-to-remote device communications; wireless programming, configuration and data logging; streaming audio; bi-directional audio; and/or remote control. It is understood that these communications can be unidirectional, bidirectional, or combinations of both. Such communications can also include far field communications (e.g., radio frequency communications), or combinations of near field (e.g., inductive link using substantially the magnetic field) and far field communications. Several modes of modulation and demodulation are possible and the examples given herein are demonstrative and not intended to be exclusive or limiting.

[0039] In various embodiments the wireless communications can include standard or nonstandard communications. Some examples of standard wireless communications include link protocols including, but not limited to, Bluetooth™, IEEE 802.11 (wireless LANs), 802.15 (WPANs), 802.16 (WiMAX), cellular protocols including, but not limited to CDMA and GSM, ZigBee, and ultra-wideband (UWB) technologies. Such protocols support radio frequency communications and some support infrared communications. Although the present system is demonstrated as a radio system, it is possible that other forms of wireless communications can be used such as ultrasonic, optical, and others. It is understood that the standards which can be used include past and present standards. It is also contemplated that future versions of these standards and new future standards may be employed without departing from the scope of the present subject matter.

[0040] The wireless communications support a connection from other devices. Such connections include, but are not limited to, one or more mono or stereo connections or digital connections having link protocols including, but not limited to 802.3 (Ethernet), 802.4, 802.5, USB, ATM, Fibre-channel, Firewire or 1394, InfiniBand, or a native streaming interface. In various embodiments, such connections include all past and present link protocols. It is also contemplated that future versions of these protocols and new future standards may be employed without departing from the scope of the present subject matter.

[0041] In various embodiments a protocol is used, such as the protocol described in U.S. Patent Application Publication 2006/0274747, entitled: COMMUNICATION SYSTEM FOR WIRELESS DEVICES, and PCT Application Publication WO 2006/133158, titled: COMMUNICATION SYSTEM FOR WIRELESS AUDIO DEVICES, which are both hereby incorporated by reference in their entirety. In various embodiments, a protocol is used such as the protocol in U.S. Pat. No. 7,529,565, which is hereby incorporated by reference in its entirety. Other protocols may be used without departing from the scope of the present subject matter.

[0042] Thus, the present subject matter provides a multi-mode radio where long range electromagnetic waves can propagate to and from the hearing aids to off body devices including, but not limited to programmers, remote controls, wireless microphones, and/or assisted listening devices.

[0043] Since the devices are very programmable and can be set to bands acceptable over the world, the present subject matter can be used to provide reliable ear-to ear links with world-wide acceptance from a regulatory point of view. For example, in various countries operation can be performed by multiple bands such as 902-928 MHz in the US and 863-865 MHz in Europe. The present subject matter also allows for legacy narrow band analog FM receivers used for assistive listening to be successfully received by the same radio in certain embodiments. When one band of frequencies has interference, then another band of frequencies may be free of interference. Thus, a multiband radio provides communication redundancy in the face of interference.

[0044] In various embodiments the present approach provides a radio transceiver that has dual, triple, or other modes and bands of operation. For example, a 900 MHz transceiver can be built to operate at 200 MHz as well. In various embodiments, the radio has a mode that supports communication using a carrier that is less than about 30 MHz for ear-to-ear or ear-to-body worn device communication. In various embodiments, a system that has an RF front end capable of 900 MHz operation is built as a single or dual conversion radio having an internal frequency (IF) that is

less than about 30 MHz and that can be adapted to transmit and receive a signal directly at frequencies below 30 MHz, thus bypassing the RF front end of the transceiver. In various embodiments the transceiver uses similar modulation schemes at both frequencies so that the demodulator and modulator sections of the transceiver can be used for both frequencies of operation. Alternatively, the transceiver may use a different modulation (multi-mode) scheme at each of the frequencies that best satisfies the link budget and power budget for that band of frequencies. In various embodiments the transceiver incorporates a narrowband analog FM demodulator as part of the receiver for receiving analog FM signals from assisted listening devices in the 169-217 MHz RF spectrum.

[0045] The present subject matter provides, among other things, in various embodiments a multi-band transceiver capable of sending and receiving digital or analog information over an RF link using multiple carrier frequencies for use in a hearing aid. The IF frequency of the transceiver can be used to directly receive and transmit information at a different frequency by bypassing the RF front end. In other variations an alternate front end tuned to operate at multiple frequency bands is used. Such a system can use an IF frequency consistent with analog FM assisted listening devices in the 200 MHz region and has an RF front end capable of operating at higher frequencies such as 900 MHz or 2.4 GHz. Variations of the present subject matter include in various embodiments a radio system that uses an IF frequency consistent with magnetic induction (frequencies less than 30 MHz) by bypassing or retuning the front end receiver and transmitter.

[0046] The present subject matter provides, among other things, in various embodiments a multi-mode transceiver capable of sending and receiving digital or analog information over an RF link using multi-modes of operation each mode being adapted for use at a different frequency band of operation.

[0047] It is understood that variations in communications protocols, antenna configurations, and combinations of components may be employed without departing from the scope of the present subject matter. It is understood that in various embodiments the microphone is optional. It is understood that in various embodiments the receiver is optional. Antenna configurations may vary and may be included within an enclosure for the electronics or be external to an enclosure for the electronics. Thus, the examples set forth herein are intended to be demonstrative and not a limiting or exhaustive depiction of variations.

[0048] The present subject matter can be used for a variety of hearing assistance devices, including but not limited to, cochlear implant type hearing devices, hearing aids, such as behind-the-ear (BTE), in-the-ear (ITE), in-the-canal (ITC), or completely-in-the-canal (CIC) type hearing aids. It is understood that behind-the-ear type hearing aids may include devices that reside substantially behind the ear or over the ear. Such devices may include hearing aids with receivers associated with the electronics portion of the behind-the-ear device, or hearing aids of the type having receivers in the ear canal of the user. Such devices are also known as receiver-in-the-canal (RIC) or receiver-in-the-ear (RITE) hearing instruments. It is understood that other hearing assistance devices not expressly stated herein may fall within the scope of the present subject matter.

[0049] This application is intended to cover adaptations or variations of the present subject matter. It is to be understood that the above description is intended to be illustrative, and not restrictive. The scope of the present subject matter should be determined with reference to the appended claims, along with the full scope of legal equivalents to which such claims are entitled.

Claims

1. (canceled)
2. A hearing device, comprising: a multiband antenna configured for wireless communication; and a communications module including a multi-mode radio in communication with the multiband antenna, the multi-mode radio configured to receive a frequency control signal to provide input for

- matching of an operational frequency band for the multiband antenna by the multi-mode radio.
3. The hearing device of claim 2, further comprising a processor configured to process signals to correct for hearing impairment of a wearer of the hearing device.
 4. The hearing device of claim 3, wherein the frequency control signal is received from the processor.
 5. The hearing device of claim 2, wherein the frequency control signal is received from combination logic.
 6. The hearing device of claim 2, wherein the frequency control signal is received from a received signal strength indication (RSSI) module.
 7. The hearing device of claim 2, wherein the multi-mode radio is programmable to provide separate communication channels supporting concurrent communications.
 8. The hearing device of claim 3, further comprising a microphone configured to receive sound and convert the sound to an electrical signal that is provided to the processor.
 9. The hearing device of claim 3, further comprising a receiver configured to receive processed signals from the processor and to play sound for the wearer using the signals.
 10. The hearing device of claim 2, wherein the multi-mode radio is configured to support hybrid modulation techniques.
 11. The hearing device of claim 2, wherein the hearing device includes a hearing assistance device.
 12. The hearing device of claim 11, wherein the hearing assistance device includes a hearing aid.
 13. A method of operating a hearing device including a multiband antenna, the method comprising: receiving, using a multi-mode radio, a frequency control signal configured to control frequency of operation of the multi-mode radio; and matching, using the multi-mode radio, an operational frequency band for the multiband antenna based on the received frequency control signal.
 14. The method of claim 13, further comprising: processing, using a processor in communication with the multi-mode radio, a signal received from the multi-mode radio to correct for hearing impairment of a wearer of the hearing device.
 15. The method of claim 13, further comprising: communicating, using the multi-mode radio, with a second hearing device.
 16. The method of claim 13, further comprising: communicating, using the multi-mode radio, with a body-worn device.
 17. The method of claim 13, further comprising: communicating, using the multi-mode radio, with a remote device.
 18. The method of claim 13, further comprising: providing, using the multi-mode radio, separate communication channels supporting concurrent communications.
 19. The method of claim 13, wherein the multi-mode radio is configured to support hybrid modulation techniques.
 20. The method of claim 13, wherein the hearing device includes a hearing assistance device.
 21. The method of claim 20, wherein the hearing assistance device is a hearing aid.
-