

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260921

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

REAL; Richmond Andrew et al.

RAISED FEATURE ON EARBUD BODY

Abstract

Aspects describe a raised feature to help a user remove an in-ear audio output device from a case. Aspects describe a device comprising an earbud housing shaped to fit in a concha of an ear of a wearer of the device, and a body coupled to the earbud housing, the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn, the body comprising a top cap comprising a flat external portion and a raised feature proximate to a concha cymba of the wearer and external to the ear when the device is worn.

Inventors: REAL; Richmond Andrew (Uxbridge, MA), MOSGROVE; Colin Taylor (Needham, MA)

Applicant: BOSE CORPORATION (Framingham, MA)

Family ID: 1000008560391

Appl. No.: 19/193752

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 18674812 20240524 parent-grant-document US 12317022 child US 19193752

parent US continuation 17662277 20220506 parent-grant-document US 12047723 child US 18674812

Publication Classification

Int. Cl.: H04R1/10 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/674,812, filed May 24, 2024, which is a continuation of U.S. patent application Ser. No. 17/662,277, filed May 6, 2022, now U.S. Pat. No. 12,047,723, each of which is incorporated by reference herein in its entirety.

FIELD

[0002] Aspects of the present disclosure describe a raised feature on an external surface of an earbud body. The feature allows a user to more easily remove earbuds from an earbud case. The placement of the feature does not alter existing design features of the device providing user comfort, fit and portability.

BACKGROUND

[0003] In-ear devices are small and designed to be comfortable and portable. Due to the size of the device and accompanying case, and smooth surfaces of in-ear devices, users may have difficulty gripping or pinching the device to remove it from the case. It is desirable to improve a user's ability to quickly and efficiently remove an in-ear device from a case.

SUMMARY

[0004] Aspects provide an in-ear audio output device including a raised feature that both does not contact human tissue and aids in removal of the device from a protective and/or charging case. Due to the location of the feature, it does not adversely impact the fit and comfort of the device in the wearer's ear. Further, the feature provides a surface for better adherence to the device, so that the device may be removed more easily from its case.

[0005] Aspects provide an in-ear audio output device, comprising: an earbud housing shaped to fit in a concha of an ear of a wearer of the device, and a body coupled to the earbud housing; the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn; the body comprising a top cap comprising a flat external portion and a raised feature proximate to a concha cymba of the wearer and external to the ear when the device is worn.

[0006] In aspects, the raised feature comprises a crescent shaped feature. In aspects, the crescent shape features comprises a first point on a first end of the crescent shaped feature, a second point on a second end of the crescent shaped feature, and a middle portion between the first point and the second point, and the middle portion extends further from the flat external portion of the body as compared to the first point and the second point.

[0007] In aspects, at least a portion of the raised feature is at least 0.6 mm in height from the flat external portion. In aspects, the raised feature is less than or equal to 1 mm in height from the flat external portion.

[0008] In aspects, a bottom portion of the raised feature is contoured to a shape of a human figure. In aspects, the top cap comprises a cosmetic cap.

[0009] Aspects provide in-ear audio output device comprising: an earbud housing shaped to fit in a concha of an ear of a wearer of the device, and a body coupled to the earbud housing, the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn, the body comprising a top cap comprising a flat external portion and a raised feature; and a charging case comprising a case bottom, a case top, and a hinge configured to allow the case top to pivot open and closed relative to the case bottom, wherein the raised feature protrudes from the case bottom when the in-ear audio output device is seated in the charging case.

[0010] In aspects, the case top pivots relative to the case bottom to a closed position and encases the raised feature when the in-ear audio output device is seated in the charging case.

[0011] In aspects, the raised feature is proximate to a concha cymba of the wearer and external to the ear when the device is worn. In aspects, the raised feature comprises a crescent shaped feature.

[0012] In aspects, the crescent shape feature comprises a first point on a first end of the crescent shaped feature, a second point on a second end of the crescent shaped feature, and a middle portion between the first point and the second point; and the middle portion extends further from the flat external portion of the body as compared to the first point and the second point.

[0013] In aspects, at least a portion of the raised feature is at least 0.6 mm in height from the flat external portion. In aspects, the raised feature is less than or equal to 1 mm in height from the flat external portion.

[0014] In aspects, a bottom portion of the raised feature is contoured to a shape of a human figure. In aspects, top cap comprises a cosmetic cap.

[0015] Aspects provide an in-ear audio output device, comprising: an earbud housing shaped to fit in a concha of an ear of a wearer of the device, and a body coupled to the earbud housing, the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn, the body comprising a top cap comprising a flat external portion and a curved raised feature proximate to a concha cymba of the wearer, along a top perimeter of the top cap, and external to the ear when the device is worn.

[0016] In aspects, the curved raised feature comprises a crescent shaped feature. In aspects, the crescent shape feature comprises a first point on a first end of the crescent shaped feature, a second point on a second end of the crescent shaped feature, and a middle portion between the first point and the second point; and the middle portion extends further from the flat external portion of the body as compared to the first point and the second point.

[0017] In aspects, the curved raised feature is less than or equal to 1 mm in height from the flat external portion.

[0018] All examples and features mentioned herein can be combined in any technically possible manner. Other features, objects, and advantages will become apparent from the following detailed description, when read in connection with the following drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a view of the lateral surface of the human ear.

[0020] FIG. 2 is a back perspective of an in-ear audio output device including the earbud housing positioned in a wearer's ear.

[0021] FIG. 3 is a side perspective of the in-ear audio output device including the earbud housing having acoustic ports and a stability band.

[0022] FIG. 4 is a bottom perspective of the in-ear audio output device including the earbud housing having acoustic ports and a stability band.

[0023] FIG. 5 is a top view of a charging case in an open position for a pair of in-ear audio output devices.

[0024] FIG. 6 is a side view of the charging case in an open position including an in-ear audio output device.

[0025] FIG. 7 is a cross section view of an in-ear audio output device disposed in the charging case.

[0026] FIG. 8 is a back perspective of an in-ear audio output device including a raised feature on an external portion of the body, according to aspects of the present disclosure.

[0027] FIG. 9 is a side perspective of an in-ear audio output device including the raised feature, according to aspects of the present disclosure.

[0028] FIG. 10 is a bottom perspective of the in-ear audio output device including the raised feature, according to aspects of the present disclosure.

[0029] FIG. **11** is a top view of a charging case in an open position for a pair of in-ear audio output devices including the raised feature, according to aspects of the present disclosure.

[0030] FIG. **12** is a side view of the charging case in an open position including an in-ear audio output device including the raised feature, according to aspects of the present disclosure.

[0031] FIG. **13** is a cross section view of an in-ear audio output device including the raised feature disposed in the charging case, according to aspects of the present disclosure.

DETAILED DESCRIPTION

[0032] In-ear audio output devices have become a prevalent part and convenient aspect of daily life. Some examples of such devices include audio headphones, hearing aids, hearing assistance headphones, noise-masking earbuds, and ANR headphones. In-ear devices allow hands-free listening, so that a user may listen to audio and/or block sound while doing something else. While working, people use in-ear devices to help concentrate and help avoid distracting others. Finally, in-ear devices are convenient while in transit or exercising due to their portability, wireless connectivity, and fit in a user's ear.

[0033] Given the small size of in-ear devices and desired portability, when not in-use, in-ear devices typically are stored in a compact protective case (e.g., carrying and/or charging cases). It is desirable for a user to be able to easily and efficiently remove an in-ear device from its case.

[0034] FIG. **1** shows the lateral surface of a human's right ear **100**, with some features identified. There are many different ear sizes and geometries and include features not illustrated in FIG. **1**. The in-ear audio output device described herein includes a body **202** that is coupled to an earbud housing **204**. The body is configured to sit outside the human ear and the housing of the device is shaped to fit in the concha cavum.

[0035] FIGS. **2-4** show an in-ear audio output device. FIG. **2** is a back perspective view **200** of the device positioned in a wearer's ear. FIG. **3** is a side perspective view **300** of the device. FIG. **4** is a bottom perspective view **400** of the device.

[0036] The device includes a body **202**, an earbud housing **204**, a nozzle **206**, and a sealing structure **208**.

[0037] The body **202** is coupled to an external surface of earbud housing **204** extending away from an ear canal of the wearer. As illustrated in FIG, **2**, the body **202** is shaped like a rectangular pill and is situated outside the wearer's ear when the device is worn. When the device is worn, the body **202** is proximate to the concha and sits against the outside of the wearer's ear. In some cases, the body **202** sits against the wearer's face, to help hold the device in place. The external surface of the body **202** is called a top cap. The top cap is the portion of the body **202** that is visible to the outside world.

[0038] The top cap is a flat, or substantially flat, cosmetic cap. The cosmetic top cap covers a non-cosmetic, functional plate. In aspects, the functional plate covers a printed circuit board. The top cap provides a smooth, aesthetic external body while covering the functional plate.

[0039] In aspects, earbud housing **204** is shaped to extend toward and fit in the concha cavum. Earbud housing **204** defines an acoustic chamber which houses the acoustic driver and other electronics for the device.

[0040] The nozzle **206** extends from earbud housing **204** towards sealing structure **208**. In aspects, earbud housing **204** extends into nozzle **206**, or in other words, forms part of nozzle **206**. Nozzle **206** includes an acoustic passage for sound waves to pass to the ear canal of the wearer. In aspects, nozzle **206** has a planar end with a substantially elliptical-shaped opening.

[0041] The sealing structure **208** creates a seal with a typical wearer's ear canal. Sealing structure **208** is substantially spherically-dome shaped. Sealing structure **208** extends from the planar end of nozzle **206** and folds back towards the wearer's outer ear.

[0042] In aspects, as illustrated in FIG. **2**, when the device is inserted in the wearer's ear, resistive port **210** is aligned with the intertragal notch of the ear. The port **226** for a feedforward microphone may be situated outside the wearer's ear when the device is positioned in the wearer's ear. The

device may include other non-illustrated ports such as, for example, a mass port.

[0043] In aspects, the in-ear audio output device includes a stability band **216**. The stability band may include an attachment feature **218** used to attach the stability band **216** to the device, and more specifically, to the earbud housing **204**. In aspects, stability band **216** is removably attached to earbud housing **204**. In other words, attachment feature **218** allows stability band **216** to be removed and added to the audio device. In other aspects, attachment feature **218** is integrally formed with earbud housing **204**.

[0044] FIG. **5** is a top view **500** of the device in a case that is in an open position. FIG. **6** is a side view **600** of the device in the case that is in an open position. FIG. **7** is a cross section **700** of the device in the case in an open position.

[0045] The case has a top portion **502**, bottom portion **504**, and a hinge **506**. The top portion **502** pivots via the hinge **506** relative to a base portion **504** to open and close the case. As seen by the top view **500**, the device is tightly constrained in the case. As illustrated in FIG. **6** and FIG. **7**, when the case is in an open position, a small portion of the earbud body **202** extends from the top plane **508** of the bottom portion **504** of the case. To remove the device from the case, a user grips the body **202** and the housing **204** and pulls the device out of the case. In an example, each of the user's thumb and pointer finger grip or press on the body **202** and housing **204** of the device. Given the smooth surface of the body **202** and housing **204**, and the position of the device in the case, the user may not be able to apply enough force to grip and remove the device from the case. In some cases, even though the user may successfully remove the device from the case, opportunities exist for a more comfortable and efficient user interaction with the device.

[0046] Therefore, aspects provide a feature to assist a user to more easily remove an in-ear audio output device from its case. The feature does not interfere with how the device fits in the user's ear and does not create additional contact points with the user's body. Therefore, without compromising fit and comfort, the placement of the feature increases the user's ability to remove the device from the case.

[0047] FIGS. **8-10** show an in-ear audio output device including a raised feature, according to aspects of the present disclosure. FIG. **8** is a back perspective view **800** of the device positioned in a wearer's ear. FIG. **9** a side perspective view **900** of the device. FIG. **10** is a bottom perspective view **1000** of the device.

[0048] In aspects, the body **202** includes a flat or substantially flat portion called the top cap (e.g., as described with reference to FIGS. **2-7**) and a raised feature **802**. The raised feature is positioned on the top outer surface of the body **202**. When the device is worn, the feature **802** does not contact human skin. In aspects, the raised feature **802** is between 0.6 mm to 1 mm in height, measured from the outer surface of the body **202**. The raised feature **802** may have a non-constant height.

[0049] In aspects the raised feature **802** is crescent shaped. The crescent shape has a first point **802a** on a first end and a second point **802b** on a second end and a middle portion **804** between the first point **802a** and the second point **802b**. In some designs, the middle portion **804** extends further from the body **202** as compared to the first point **802a** and **802b**. In an example, the middle portion **804** is approximately 0.6 mm to 1 mm in height from the surface of the body **202**. The first point **802a** and second point **802b** taper from the middle portion **804**. The bottom portion **806** of the feature (when the device is positioned in-ear) is contoured to the shape of a finger with the feature **802** and tapers from the middle portion **804** to each of the points **802a** and **802b**.

[0050] FIG. **11** is a top view **1100** of the device, including the raised feature **802**, in a case that is in an open position. FIG. **12** is a side view **1200** of the device, including the raised feature **802**, in the case that is in an open position. FIG. **13** is a cross section **1300** of the device, including the raised feature **802**, in the case in an open position. Each of FIGS. **11-13** illustrate the minimal size and subtlety of the raised feature **802**. As illustrated in, for example, FIG. **11**, in the tightly constrained case, the device including the raised feature is virtually the same size as the device not including the feature. Therefore, the raised feature does not compromise case design.

[0051] As shown in FIGS. 12 and 13, the raised feature 802 sits slightly proud of the top plane 508 of the bottom portion 504 of the case when the case is open. When the case is opened, the raised feature 802 is exposed. The orientation of the raised feature 802 on the body 202 when the device is in the case allows the user to use the raised feature 802 as a grip to help remove the device from the case. Without the feature, the user may apply 1-1.5 N of force to remove the device. With the feature 802, the user may apply approximately 4-6 times the amount of force (e.g., 5-10 N) to remove the device from the case.

[0052] FIGS. 8-13 illustrate various aspects of a raised feature, on an external surface of a body of the device that does not come in contact with human tissue and provides a gripping surface for a user to more easily remove the device from a case. The feature, and aspects of the feature, may be applied to devices having a varied design as compared to the devices illustrated in FIGS. 2-4.

[0053] While the raised shape 802 is described and illustrated as a crescent shape, it may be any raised feature that provides a surface for a user to grip the device. When gripped, the raised feature offers affordance for a user's finger to remain in contact with the otherwise smooth body of the device, and not slide off the device. The feature is positioned on one of the few locations on an in-ear audio output device that will not come in contact with human skin. The size of the design remains largely unchanged. The ergonomics of the device is not impacted. Finally, the case for the device may remain the same. The size, orientation, and nature of the feature allow the device and case to maintain existing competitive advantages associated with size, fit, comfort, and design.

[0054] Numerous uses of and departures from the specific apparatus and techniques disclosed herein may be made without departing from the inventive concepts. Consequently, the invention is to be construed as embracing each and every novel feature and novel combination of features disclosed herein.

Claims

1. An in-ear audio output device, comprising: an earbud housing shaped to fit in a concha of an ear of a wearer of the device; a body coupled to the earbud housing, the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn, the body comprising a top cap comprising a top end oriented towards a helix of the wearer and a bottom end opposite the top end; and a raised feature disposed on the top end of the top cap, wherein a bottom portion of the raised feature is contoured to a shape of a human finger.
2. The in-ear audio output device of claim 1, wherein the raised feature is proximate to a concha cymba of the wearer and external to the ear when the device is worn.
3. The in-ear audio output device of claim 1, wherein the raised feature comprises a first point, a second point, and a middle portion disposed between the first and second points, wherein the first and second points taper from the middle portion.
4. The in-ear audio output device of claim 3, wherein the top cap further comprises a flat portion, wherein the middle portion extends further from the flat portion than the first and second points.
5. The in-ear audio output device of claim 3, wherein at least a portion of the raised feature is at least 0.6 mm in height from the flat portion.
6. The in-ear audio output device of claim 1, wherein the raised feature is crescent shaped.
7. The in-ear audio output device of claim 1, wherein the raised feature is less than or equal to 1 mm in height from the flat external portion.
8. An in-ear audio output device, comprising: an earbud housing shaped to fit in a concha of an ear of a wearer of the device; a body coupled to the earbud housing, the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn, the body comprising a top cap comprising a top end oriented towards a helix of the wearer and a bottom end opposite the top end; and a raised feature disposed on the top end of the top cap, the raised feature comprising a first point, a second point, and a middle portion disposed between the first and second

points, wherein the first and second points taper from the middle portion.

9. The in-ear audio output device of claim 8, wherein the top cap further comprises a flat portion, wherein the middle portion extends further from the flat portion than the first and second points.

10. The in-ear audio output device of claim 8, wherein the raised feature is proximate to a concha cymba of the wearer and external to the ear when the device is worn, and wherein the raised feature is crescent shaped.

11. The in-ear audio output device of claim 8, wherein at least a portion of the raised feature is at least 0.6 mm in height from the flat external portion.

12. The in-ear audio output device of claim 8, wherein the raised feature is less than or equal to 1 mm in height from the flat external portion.

13. The in-ear audio output device of claim 8, wherein the raised feature has a non-constant height.

14. A system comprising: an in-ear audio output device comprising: an earbud housing shaped to fit in a concha of an ear of a wearer of the device; a body coupled to the earbud housing, the body extending away from an ear canal of the wearer and oriented outside of the ear when the device is worn, the body comprising a top cap comprising a top end oriented towards a helix of the wearer and a bottom end opposite the top end; and a raised feature disposed on the top end of the top cap, wherein a bottom portion of the raised feature is contoured to a shape of a human finger.

15. The system of claim 14, further comprising a charging case comprising a case bottom, a case top, and a hinge configured to allow the case top to pivot open and closed relative to the case bottom, wherein the raised feature protrudes from the case bottom when the in-ear audio output device is seated in the charging case.

16. The system of claim 15, wherein the case top pivots relative to the case bottom to a closed position and encases the raised feature when the in-ear audio output device is seated in the charging case.

17. The system of claim 14, wherein the raised feature is proximate to a concha cymba of the wearer and external to the ear when the device is worn, and wherein the raised feature is crescent shaped.

18. The system of claim 14, wherein the raised feature comprises a first point, a second point, and a middle portion disposed between the first and second points, wherein the first and second points taper from the middle portion, wherein the top cap further comprises a flat portion, and wherein the middle portion extends further from the flat portion than the first and second points.

19. The system of claim 14, wherein the raised feature is less than or equal to 1 mm in height from the flat external portion.

20. The system of claim 14, wherein the raised feature is less than or equal to 1 mm in height from the flat external portion.
