

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386568
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Hikichi; Atsushi

Image forming apparatus and control method for image forming apparatus

Abstract

An image forming apparatus capable of transitioning between at least a standby state and a termination state, the image forming apparatus including a controller and a printer device configured to form an image on a recording sheet. The controller is configured to receive an event for transitioning a state of the image forming apparatus, and the controller is configured to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state. When a reboot event is received by the controller, the controller controls to execute a termination process of the controller without executing a termination process of the printer device.

Inventors:	Hikichi; Atsushi (Tokyo, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008747599
Assignee:	Canon Kabushiki Kaisha (Tokyo, JP)
Appl. No.:	18/473892
Filed:	September 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240103782 A1	Mar. 28, 2024

Foreign Application Priority Data

JP	2022-153335	Sep. 27, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G06F3/12 (20060101); G03G15/00 (20060101)

U.S. Cl.:

CPC G06F3/1229 (20130101); G03G15/50 (20130101); G06F3/1221 (20130101);

Field of Classification Search

CPC: G06F (3/1229); G06F (3/1221); G03G (15/50)

USPC: 358/1.14

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8488141	12/2012	Kaneko	358/1.14	G03G 15/5012
2009/0303517	12/2008	Kaneko	358/1.14	G03G 15/5012
2018/0349074	12/2017	Nagai	N/A	G06F 3/1229

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012128705	12/2011	JP	N/A

Primary Examiner: Nguyen; Allen H

Attorney, Agent or Firm: Canon U.S.A., Inc.

Background/Summary

BACKGROUND

Field of the Disclosure

(1) The present disclosure relates to an image forming apparatus and a control method for an image forming apparatus.

Description of the Related Art

(2) An image forming apparatus, in its standby state, can transition to a termination state upon receiving a termination event as a trigger, thereby reaching the termination state. The image forming apparatus has the function of terminating while protecting devices such as a printer and a scanner in order to extend the durability of paper printing. In other words, the image forming apparatus performs, as a termination process, both a printer termination process for printer protection and a controller termination process. In Japanese Patent Laid-Open No. 2012-128705, whether transitioning to a suspended state is possible is checked when a termination process is started, and if it is not possible, a shutdown process is initiated in the case where the termination process is a shutdown or a reboot.

SUMMARY

(3) Some embodiments of an image forming apparatus are an image forming apparatus capable of transitioning between at least a standby state and a termination state, the image forming apparatus including a controller and a printer device configured to form an image on a recording sheet. The controller is configured to receive an event for transitioning a state of the image forming apparatus,

and the controller is configured to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state. When a reboot event is received by the controller, the controller controls to execute a termination process of the controller without executing a termination process of the printer device.

(4) Further features of various embodiments will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example of an image forming apparatus (101).
- (2) FIG. 2 is a block diagram of an example of an operation unit (105).
- (3) FIG. 3 is a block diagram of an example of a controller (103).
- (4) FIG. 4 is a power supply system diagram of an example of the image forming apparatus (101).
- (5) FIG. 5 is an example of a flowchart in a first embodiment.
- (6) FIG. 6 is an example of a flowchart in a second embodiment.
- (7) FIG. 7 is an example of a flowchart in a third embodiment.
- (8) FIG. 8 is an example of a flowchart in a fourth embodiment.

DESCRIPTION OF THE EMBODIMENTS

- (9) First, the state transition and reboot processing of an image forming apparatus will be described.
- (10) A printer termination process may last more than one hour. In other words, even if the image forming apparatus starts rebooting, rebooting takes a long time in the case where the time taken by the printer termination process is long. Accordingly, when the system setting information is changed, for example, even if rebooting is performed to reflect the settings, rebooting may take a long time in the case where the time taken by the printer termination process is long, and the downtime of the image forming apparatus may increase, which may result in reduced convenience.
- (11) Some embodiments of the present disclosure provide an image forming apparatus, which requires time for a printer termination process, capable of shortening the time taken by a reboot process to enhance convenience.
- (12) Termination State, Termination Event, and Transition to Termination State
- (13) An image forming apparatus, in its standby state, can transition to a termination state upon receiving a termination event as a trigger, thereby reaching the termination state.
- (14) In other words, the image forming apparatus has the standby state, which displays functions provided by the image forming apparatus when an operation unit is operated by a user. Meanwhile, the image forming apparatus has the termination state, which energizes only a device for detecting a power switch operation while stopping the supply of power to devices other than the device for detecting a power switch operation. The image forming apparatus also has a function for accepting termination events such as shutdowns, reboots, and the like. Furthermore, the image forming apparatus performs state transition processes from the standby state to the termination state, such as device termination processes for protecting devices such as a printer and a scanner, and data storage processes for protecting data of applications.
- (15) Reboot Issuance Timing
- (16) The image forming apparatus starts a reboot process by receiving a reboot event, which is one of termination events. The reboot issuance timing includes when the image adjustment of a printer or a scanner is completed, or when a connection is retried in order to eliminate a communication error with a device such as a printer, a scanner, or the like. In addition, the reboot issuance timing includes when the update of the system or firmware controlling printing is completed, or upon reflection of changes made to the system configuration information.

(17) Printer Termination Process and Execution Time

(18) Furthermore, due to the prolonged printer termination process, the execution time of the overall system termination process in the image forming apparatus may be extended. The printer performs a printer termination process in order to extend its durability, which is the maximum number of paper prints. The printer termination process includes fan rotation control for printer cooling in order to prevent component degradation due to prolonged high temperatures, and fan rotation control for external ozone discharge in order to prevent toner from not adhering to the fixing unit and causing the printed image to smear. Cooling the printer by fan rotation can take up to an hour, and the printer termination process involves prolonged operation. Additionally, although the printer termination process crimps a fixing drum that fixes the paper and toner for printing at a high speed in its standby state, the printer termination process also involves the separation movement of the fixing drum in order to prevent the occurrence of image streaks during printing, caused by the prolonged crimping and hardening of the fixing drum. Furthermore, the printer termination process includes the closing operation of a charging shutter in order to prevent drying, which is for preventing the fixing drum from drying out and losing toner adhesion. The separation movement of the fixing drum and the closing operation of the charging shutter do not require time compared to the fan rotation control, and are operations performed in a short time.

(19) Configuration of Power Supply Control of System

(20) Meanwhile, the image forming apparatus may change the control entity of the power supply control unit of the image forming apparatus, such as in the case where the controller controls the power supply of the overall system or in the case where the printer controls the power supply of the overall system. In the former case, the printer can be rebooted by rebooting the controller. However, in the latter case, when the controller is rebooted, the printer cannot be rebooted, and the entire system is not reset, which may result in an error at the next activation.

(21) Hereinafter, embodiments for implementing the present disclosure will be described using the drawings. Note that the following embodiments are not intended to limit every embodiment according to the claims. Although a plurality of features are described in the embodiments, not all of these features are essential to every embodiment, and the features may be arbitrarily combined. Furthermore, in the accompanying drawings, the same or similar configurations are given the same reference numerals, and overlapping descriptions are omitted.

First Embodiment

(22) Configuration of System

(23) FIG. 1 is a block diagram illustrating the configuration of an image forming system according to the present embodiment. This example is an example of a multi-function peripheral equipped with a printing function, a scanner function, a data communication function, and so on.

(24) In FIG. 1, an image forming apparatus **101** is configured to be capable of receiving jobs from a computer **109** via a local area network (LAN) **108**. Note that the number of connections to the computer **109** may be one or more. A scanner device **102** reads an image optically from a document and converts it into a digital image. A printer device **104** outputs the digital image to a recording sheet, such as a paper device called a sheet of paper. A printer device is also referred to as a printer unit. An operation unit **105** includes a touchscreen and hardware keys for accepting settings for the apparatus from a user and displaying a processing state. A hard disk **106** (also referred to as a hard disk drive (HDD)) stores digital images, control programs, and the like. The HDD **106** is a non-volatile storage device, which may be a solid state drive (SSD), an embedded multimedia card (eMMC), or the like. A FAX device **107** transmits and receives digital images to and from telephone lines and the like. A controller **103** is connected to the scanner device **102**, the printer device **104**, the operation unit **105**, the hard disk **106**, and the FAX device **107**, and executes jobs on the image forming apparatus **101** by issuing instructions to the individual modules.

(25) The image forming apparatus **101** is also capable of receiving and outputting digital images, issuing jobs, giving instructions to equipment, and so on using the computer **109** via the LAN **108**.

The scanner device **102** includes a document feed unit **121**, which can automatically and sequentially replace a bunch of documents, and a scanner unit **122**, which can optically scan a document and convert it into a digital image. The converted image data is transmitted to the controller **103**.

(26) The printer device **104** includes a sheet feed unit **142**, which can sequentially feed one sheet at a time from a bunch of sheets of paper, a marking unit **141** for printing image data on the sheet of paper that has been fed, and a sheet discharge unit **143** for discharging the printed sheet. A finisher device **150** performs processing on a paper device output from the sheet discharge unit **143** of the printer device **104** of the image forming apparatus **101**, such as discharging, sorting, stapling, punching, cutting, and so on.

(27) Functions of System

(28) Hereinafter, an example of executable jobs (functions) of the image forming apparatus **101** will be described.

(29) Copy Function

(30) The image forming apparatus **101** is equipped with a copy function that records an image read from the scanner device **102** to the hard disk **106** and simultaneously prints it using the printer device **104**.

(31) Image Transmission Function

(32) The image forming apparatus **101** is equipped with an image transmission function that transmits an image read from the scanner device **102** to the computer **109** via the LAN **108**.

(33) Image Saving Function

(34) The image forming apparatus **101** is equipped with an image saving function that records an image read from the scanner device **102** to the hard disk **106**, and transmits the image or prints the image if necessary.

(35) Image Printing Function

(36) The image forming apparatus **101** is equipped with an image printing function that interprets, for example, a page description language transmitted from the computer **109**, and prints it with the printer device **104**.

(37) Configuration of Operation Unit (**105**)

(38) The operation unit **105** will be described using FIG. 2.

(39) The operation unit **105** is connected to the controller **103** and provides a user interface for operating the image forming apparatus **101**. The user interface is configured of a liquid crystal display (LCD) touchscreen **600**, a backlight, a power saving button, a copy button, a cancel button, a reset button, a numeric keypad, a user mode key, a power supply tally light **619**, and the like.

(40) The LCD touchscreen **600** has a backlight that can be turned on and off, and performs main mode settings and state indications. Note that the LCD touchscreen **600** is also referred to as an operation panel. The control of turning the backlight on and off is under control of the controller **103** as a display control unit. The numeric keypad **601** is used to enter numerals from 0 to 9. An identification (ID) key **602** is used to enter a department number and a PIN mode when the device is under departmental control.

(41) A reset key **603** is used to reset the set mode. A guide key **604** is used to display a description screen for each mode. A user mode key **605** is used to display a user mode screen. An interrupt key **606** is used to make interrupt copies.

(42) A start key **607** is used to start a copy operation or the like. A stop key **608** is used to abort a copy job being executed.

(43) A software power switch **609** triggers power supply control, power saving control, and sleep control when pressed. A power saving key **610**, when pressed, triggers a transition to the sleep state, where the backlight of the LCD touchscreen **600** is turned off, and, when pressed again, triggers a resumption from the sleep state, where the backlight of the LCD touchscreen **600** is turned on. The software power switch **609** and the power saving key **610** may be made into a single

switch, which, when pressed, triggers a transition to or a resumption from the sleep state.

(44) Function keys are used to transition to the function screens of copy **611**, transmit **612**, box **613**, and extend **614**. The box **613** displays a function screen that saves an image to the hard disk **106**. The LCD touchscreen **600** is in the state of displaying a standard screen of copy **611**, and, when the other function keys, namely, transmit **612**, box **613**, and extend **614**, are pressed, displays standard screens of the respective functions.

(45) An adjustment key **615** is used to adjust the screen contrast of the LCD touchscreen **600**. A counter checking key **616** displays a count screen that displays aggregations, such as the number of copies and the number of prints used so far.

(46) A job tally light **617** indicates LED flicker patterns and color display that indicate that a job is being executed or that an image is being accumulated in an image memory. An error tally light **618** indicates LED flicker patterns and color display that indicate that the image forming apparatus **101** is in an error state, such as a paper jam or the door being open. The power supply tally light **619** indicates flicker patterns and color display that indicate that the main power switch of the image forming apparatus **101** is turned on or off, in a state transition, or the like.

(47) These keys can also be implemented with hardware keys, or software keys displayed on the LCD touchscreen **600**, and the presence of hardware is not necessarily required.

(48) Block Diagram of Controller (**103**)

(49) Next, a block diagram of the controller **103** and peripheral devices will be described using FIG. **3**. The controller **103** is composed of a main board **200** and a sub-board **220**.

(50) The main board **200** is a so-called general-purpose central processing unit (CPU) system. The main board **200** includes a CPU **340** controlling the entire board, a boot ROM **202** including a boot program, and a memory **341** used by the CPU **340** as work memory. The main board **200** also includes a bus controller **204** having a bridge function with an external bus, and a non-volatile memory **205** retaining data even when power is cut off. Meanwhile, the CPU **340** controls a watchdog timer **230** (also referred to as a WDT), which resets the controller **103**.

(51) The CPU **340** controls a network controller **211** in order to transmit and receive data to and from the computer **109** via the LAN **108**. The CPU **340** controls a real-time clock (RTC) **212** in order to set a current time and a resumption time. The main board **200** further includes a disk controller **206** controlling a storage device, and a flash disk **207** including an SSD, an eMMC, or the like, which is a relatively small-capacity storage device configured of a semiconductor device. The main board **200** also includes a Universal Serial Bus (USB) controller **208** capable of controlling the USB, and so on. A USB memory **209**, the operation unit **105**, the hard disk **106**, and the like are connected externally to the main board **200**.

(52) The sub-board **220** is composed of a relatively small general-purpose CPU system and image processing hardware. The sub-board **220** includes a CPU **221** controlling the entire board, a memory **223** used by the CPU **221** as work memory, a bus controller **224** having a bridge function with an external bus, and a non-volatile memory **225** retaining data even when power is cut off. The sub-board **220** further includes an image processor **227** performing real-time digital image processing, and a device controller **226**. The scanner device **102** and the printer device **104**, which are connected externally to the controller **103**, pass digital image data through the device controller **226**. A paper device discharged from the printer device **104** is processed with the finisher device **150**. The FAX device **107** is directly controlled by the CPU **221**.

(53) Note that this drawing is a block diagram and is simplified. For example, the CPU **340**, the CPU **221**, and the like include a large number of CPU peripheral hardware items, such as chipsets, bus bridges, clock generators, and the like, but they are simplified for the sake of simplification and unnecessary granularity in the explanation, and this block configuration is not intended to limit every embodiment.

(54) The operation of the controller **103** will be described using image copying using a paper device by way of example. When the user gives a copy instruction using the operation unit **105**, the

CPU **340** sends an image reading instruction to the scanner device **102** via the CPU **221**. The scanner device **102** optically scans a paper document into digital image data and inputs it to the image processor **227** via the device controller **226**. The image processor **227** performs a direct memory access (DMA) transfer to the memory **223** via the CPU **221** and temporarily saves the digital image data.

(55) Having confirmed that a certain amount or all of the digital image data has entered the memory **223**, the CPU **340** issues an image output instruction to the printer device **104** via the CPU **221**.

(56) The CPU **221** notifies the image processor **227** of the address of the image data on the memory **223**. The image data on the memory **223** is transmitted to the printer device **104** via the image processor **227** and the device controller **226** in accordance with a synchronization signal from the printer device **104**. The printer device **104** prints the digital image data to the paper device.

(57) When printing multiple copies, the CPU **340** saves the image data on the memory **223** to the hard disk **106**. From the second copy onward, the image data can be sent from the hard disk **106** or the memory **223** to the printer device **104** without receiving it from the scanner device **102**.

(58) Power Supply Configuration

(59) FIG. **4** is a block diagram illustrating the power supply configuration of the image forming apparatus **101** illustrated in FIG. **1**. Hereinafter, regarding the configurations of the power supply **301**, the power supply control unit **303**, the controller **103**, the operation unit **105**, the scanner device **102**, and the printer device **104** in the image forming apparatus **101**, portions that are related to the present disclosure will be described using FIG. **4**.

(60) In FIG. **4**, the power supply control unit **303** is constantly supplied with power from the power supply **301** via a power line. However, to maintain minimal power consumption, only the power supply control unit **303** is energized during power-off, and power control is performed.

(61) In the image forming apparatus **101**, when the power switch **110** is pressed, the power supply control unit **303** senses this, controls the power switch (P) **310**, and supplies power to the CPU **340** of the controller **103**. Similarly, the power supply control unit **303** controls the power switch (Q) **311** to supply power to the CPU **305** of the operation unit **105**, controls the power switch (R) **312** to supply power to the scanner device **102**, and controls the power switch (L) **313** to supply power to the printer device **104**.

(62) The CPU **340** of the controller **103** can also control the power switch (Q) **311** by notifying the power supply control unit **303**, thereby individually supplying power to the CPU **305** of the operation unit **105**. At the same time, the CPU **340** can also control the power switch (R) **312** to supply power to the scanner device **102**, and control the power switch (L) **313** to supply power to the printer device **104** individually from the power supply **301**. At this time, the power supply of the marking unit **141**, the sheet feed unit **142**, and the sheet discharge unit **143** of the printer device **104** can also be individually controlled.

(63) Note that the power supply for each block as illustrated in FIG. **4** can be realized by, for example, configuring the power switch **310** in two systems, and in the sleep state, turning off only a relay switch leading to a block that is to be powered off, while leaving the other on. In the shutdown state, relay switches of both systems are turned off. In that case, a power supply control signal is not a binary value, but a multi-value control signal in accordance with the energized state. Although such descriptions are particularly omitted in this example, power is supplied through such control in each of the aforementioned power states, including the sleep state and the shutdown state. This control may be performed by the power supply control unit **303** performing multi-value control of the power switch (P) **310** to supply power to each block of the controller **103**. This control may also be performed by the CPU **340** of the controller **103** notifying the power supply control unit **303** to perform multi-value control of the power switch (P) **310**, thereby supply power to each block of the controller **103**, or may be in any form.

(64) Power Supply when Power Supply Control Unit **303** is Restarted (Rebooted)

(65) Next, a process of reactivating the image forming apparatus **101** will be described.

(66) The CPU **340** of the controller **103** of the image forming apparatus **101** receives a reboot event in the standby state after activation. The reboot event may be issued by an application running on the CPU **340**, or may be received by the CPU **340** via the LAN **108** from the computer **109**.

(67) Next, the CPU **340** performs a process of terminating the application, a process of saving information on the memory **341** to the HDD **106**, a process of terminating the peripherals, and a process of terminating the printer device **104**, the scanner device **102**, the FAX device **107**, the finisher device **150**, and so on. The CPU **340** notifies the power supply control unit **303** and transitions to a power-off state.

(68) In the power-off state, the power supply control unit **303** turns off the respective power switches (**310**, **311**, **312**, and **313**) and cuts off the power to the controller **103**, the printer device **104**, the scanner device **102**, the FAX device **107**, the finisher device **150**, and so on. The power supply control unit **303** waits for the time for the analog signal of the power supply to decay and reaches zero. It is also possible to shorten the signal waiting time by setting the power-off of each device as a reset instead of turning off the power.

(69) Next, the power supply control unit **303** turns on the respective power switches (**310**, **311**, **312**, and **313**) and energizes the controller **103**, the printer device **104**, the scanner device **102**, the FAX device **107**, the finisher device **150**, and so on. The CPU **340** of the controller **103** performs an activation process, and performs a process of initializing the peripherals. The printer device **104**, the scanner device **102**, the FAX device **107**, and the finisher device **150** also perform respective activation processes. Note that, in the present specification, the peripherals refer to configurations other than the CPU **340** mounted on the main board **200**, such as the RTC **212** and the watchdog timer (WDT) **230**.

(70) Power Supply when Power Supply Control Unit **303** Transitions to Sleep

(71) Next, a sleep transition process of the controller **103** will be described. When the user remains inactive in the active state for a certain period of time, the CPU **340** transitions to the sleep state through the auto sleep timer. The CPU **340** notifies the power supply control unit **303** of the transition to the sleep state, and changes the power supply to the controller **103**.

(72) As described above, the power supply for each block can be realized by, for example, configuring the power switch **310** in two systems, such as relay switches, and in the sleep state, turning off only a relay switch leading to a block that is to be powered off, while leaving the other on.

(73) At this time, the CPU **340** can also transition to the sleep state by notifying the power supply control unit **303**, turning off the power switch (Q) **311**, and stopping power supply from the power supply **301** to the operation unit **105**.

(74) At this time, the CPU **340** can transition to the sleep state by notifying the CPU **305** of the operation unit **105** through serial communication or the like, which then allows the CPU **305** of the operation unit **105** to set the operation panel and the peripherals to the power saving state.

(75) Similarly, the scanner device **102** and the printer device **104** can also transition to the sleep state, but its description will be omitted in the present embodiment.

(76) Power Supply when Power Supply Control Unit **303** is in Sleep State

(77) Next, the sleep state of the image forming apparatus **101** will be described. The sleep state is a state which enables a faster activation time compared to a normal activation time while reducing power consumption.

(78) The image forming apparatus **101** transitions to the sleep state when a certain period of time has elapsed while the user remains inactive, when the power saving key on the touchscreen of the operation unit **105** has been pressed, when the set time has been reached, or the like. In the sleep state, power is supplied to the memory **341**, an interrupt controller, the network controller **211**, the RTC **212**, the USB controller **208**, and the like of the controller **103**. Power is also supplied to the power saving key of the operation unit **105**, a portion of the FAX device **107**, various sensors, and

the like. However, since the factors for resuming from the sleep state differ from system to system, the power supply in the sleep state is not bound to this configuration.

(79) Power Supply when Power Supply Control Unit **303** Resumes from Sleep State

(80) The operation of software when resuming from the sleep state will be described. During the sleep state, the power supply control unit **303** receives one or more interrupts from a network, the RTC **212** detecting a timer or an alarm, the FAX device **107** detecting an incoming call or an off-hook, a software switch, various sensors, a USB detecting plugging or unplugging, communication, or the like, and starts supplying power. More specifically, the interrupts include the cover of the front door of the printer device **104** being opened/closed, a printing sheet being placed/removed on/from the multi-manual feed unit of the printer device **104**, the platen of the scanner device **102** being opened/closed, and a document being detected on the auto document feeder of the scanner device **102**. The interrupts further include card detection by a near field communication (NFC) card reader, motion sensor detection, an off hook of the handset of the FAX device **107**, a FAX incoming call, and so on. The power supply control unit **303** notifies the CPU **340** of the cause of the interrupt, and the CPU **340** receives the notification and performs a process of restoring the state of the software to a normal state, that is, a sleep recovery process.

(81) Next, the sleep recovery process of the controller **103** will be described. On receipt of a pressing event handler of the power saving key, which is one of the sleep recovery factors, during the sleep state, the power supply control unit **303** turns on the power switch **310** and resumes the CPU **340** of the controller **103** from the sleep state. At this time, for example, the power supply control unit **303** performs the multi-value control of the power switch **310** to supply power to each block of the controller **103**. Furthermore, the power supply control unit **303** can also resume the CPU **340** from the sleep state by issuing an interrupt signal to the CPU **340**; however, its description will be omitted because the sequence is complicated. The CPU **340** notifies the power supply control unit **303**, which in turn turns on the power switches (**311**, **312**, and **313**) and supplies power to the operation unit **105**, the scanner device **102**, and the printer device **104**. Although the power supply to devices such as the FAX device **107** is not illustrated, it can also be prepared as signals (not illustrated).

(82) Although the aforementioned sleep recovery factor is pressing of the power saving key, it is also possible to resume from the sleep state in response to a network packet and to process the network packet in a sleep intermediate state. On receipt of a network packet which is a sleep recovery factor during the sleep state, the power supply control unit **303** turns on the power switch **310**, and resumes the CPU **340** of the controller **103** from the sleep state. At this time, if the received network packet is interpreted as a print job, the CPU **340** notifies the power supply control unit **303**, and the power supply control unit **303** turns on the power switch **313** to supply power to the printer device **104**. In this case, processing can be performed without supplying power to the operation unit **105** and the scanner device **102**. In other words, it is not necessary to supply power to the operation unit **105** if the user does not use the touchscreen, for example. In addition, it is not necessary to supply power to the printer device **104** or the scanner device **102** when no print job has been generated or when it is unnecessary to obtain device information.

(83) Power Supply when Power Supply Control Unit **303** Enters Sleep State Again

(84) The CPU **340** again transitions to the sleep state when copying by the user or a print job over the network is completed. In other words, the CPU **340** notifies the power supply control unit **303** of a transition to the sleep state. With a power supply control signal, the power supply control unit **303** turns off the power switches (**311**, **312**, and **313**), and stops supplying power except to the controller **103**. At this time, for example, the power supply control unit **303** can also allow the CPU **340** to transition to the sleep state by having the CPU **340** in an interrupt signal standby state, performing the multi-value control of the power switch **310**, and turning off each block of the controller **103**. However, its detailed description will be omitted because the sequence is complicated.

(85) Description of Flowchart of First Embodiment

(86) FIG. 5 is a flowchart of the first embodiment, which most plainly represents the features of some embodiments.

(87) The issue with the first embodiment is that a termination process of the printer device **104** may take a long time.

(88) The first embodiment is different from the conventional technology in the point that, although a termination process of the controller **103** is performed on receipt of a reboot event, a termination process of the printer device **104** is skipped even if the printer device **104** is attached.

(89) The flowchart of FIG. 5 will be described.

(90) The CPU **340** of the image forming apparatus **101** starts from the standby state where an executable event is receivable.

(91) The CPU **340** receives a system termination process event (**S401**). Termination process events include shutdowns, reboots, transitions to a fast bootable standby state, and so on. If the received termination process event is an event other than a reboot (**S402**; No), the CPU **340** performs a termination process of the printer device **104** (**S450**), and performs a termination process of the controller **103** (**S460**). In contrast, if the received termination process event is a reboot (**S402**; Yes), the CPU **340** does not perform a termination process of the printer device **104**, but performs a termination process of the controller **103** (**S460**).

(92) The termination process event may be in any form, whether the CPU **340** starts processing through system operation or the CPU **340** starts processing in response to an event received from the computer **109** via the LAN **108**.

(93) If the received termination process event is a reboot, a termination process of the controller **103** is performed in **S460**, and the power supply control unit **303** then turns on the respective power switches (**310**, **311**, **312**, and **313**). Then, the CPU **340** initiates power supply to the controller **103**, the printer device **104**, the scanner device **102**, the FAX device **107**, the finisher device **150**, and so on. The CPU **340** of the controller **103** performs an activation process, and performs a process of initializing the peripherals. The printer device **104**, the scanner device **102**, the FAX device **107**, and the finisher device **150** also perform respective activation processes.

(94) If the termination process event is a reboot, the power switch **110** remains on while a shutdown process is being performed. Therefore, if the termination process event is a reboot, when a termination process of the controller **103** is performed in **S460**, the power supply control unit **303** turns on the respective power switches (**310**, **311**, **312**, and **313**) in response to the power switch **110** being on. Accordingly, the image forming apparatus **101** is rebooted. The above description describes the case where the power switch **110** is a seesaw switch. Depending on the shape of the switch, such as a tact switch, there may be switches that do not have an off and on state. In such a case, the CPU **340** can also reboot the system by notifying the power supply control unit **303** of a reboot. The detailed description of a method of controlling the reboot is omitted.

(95) Effect of First Embodiment

(96) An effect of the first embodiment is that the downtime when the image forming apparatus **101** reboots can be shortened. In other words, when the image forming apparatus **101** starts rebooting, a controller termination process is executed without notifying the printer device **104** of the termination. Accordingly, when the system setting information is changed, for example, if rebooting is performed to reflect the settings, a termination process of the printer device **104** can be skipped, and the downtime of the image forming apparatus **101** can be shortened.

(97) Description of Flowchart of Second Embodiment

(98) FIG. 6 is a flowchart of a second embodiment.

(99) The issue with the second embodiment is that, when the printer termination process time is short, it may not be possible to implement a termination process of the printer device **104**, which should be performed if possible. As a result, after reactivation, the initialization process cannot recover properly, leading to an error state.

(100) Accordingly, in the second embodiment, a termination process of the controller **103** is performed on receipt of a reboot event. At that time, it is different from the conventional technology in the point that it is checked whether the termination process time of the printer device **104** is greater than or equal to a certain period of time, and, if the termination process time is greater than or equal to the certain period of time, a termination process of the printer device **104** is skipped.

(101) The flowchart of FIG. **6** will be described.

(102) The CPU **340** of the image forming apparatus **101** starts from the standby state where an executable event is receivable.

(103) The CPU **340** receives a system termination process event (S501). Termination process events include shutdowns, reboots, transitions to a fast bootable standby state, and so on. If the received termination process event is an event other than a reboot (S502; No), the CPU **340** performs a termination process of the printer device **104** (S550), and performs a termination process of the controller **103** (S560). In contrast, if the received termination process event is a reboot (S502; Yes), the CPU **340** determines whether the termination process time of the printer device **104** is greater than or equal to a certain period of time (S510). If a termination process of the printer device **104** takes time less than or equal to the certain period of time, the CPU **340** performs a termination process of the printer device **104** (S550), and performs a termination process of the controller **103** (S560). In contrast, if a termination process of the printer device **104** takes time greater than or equal to the certain period of time, the CPU **340** does not perform a termination process of the printer device **104**, but performs a termination process of the controller **103** (S560).

(104) As the termination process time of the printer device **104**, the CPU **340** of the controller **103** may obtain a static value saved in the hard disk **106** or the like. In addition, as the termination process time of the printer device **104**, the CPU **340** of the controller **103** may obtain a dynamic value by inquiring the CPU **307** of the printer device **104** and receiving a response. In addition, the termination process time of the printer device **104** may be determined by a method that determines whether the time is greater than or equal to a certain period of time using a flag, or may be in any form.

(105) Effect of Second Embodiment

(106) An effect of the second embodiment is that the downtime when the image forming apparatus **101** reboots can be shortened. In other words, when the image forming apparatus **101** starts rebooting, if the termination process time of the printer device **104** is long, a controller termination process is executed without notifying the printer device **104** of the termination. As a result, when the system setting information is changed, rebooting is performed to reflect the settings. At this time, if the termination process time of the printer device **104** is long, a termination process of the printer device **104** can be skipped, and the downtime of the image forming apparatus **101** can be shortened.

(107) Description of Flowchart of Third Embodiment

(108) FIG. **7** is a flowchart of a third embodiment.

(109) The issue with the third embodiment is that, when the printer controls the power supply of the entire system, if the controller is simply rebooted as in the first embodiment, the entire image forming apparatus is not rebooted. As a result, an error state may occur after reactivation.

(110) Accordingly, in the third embodiment, a termination process of the controller **103** is performed upon receipt of a reboot event. At that time, the power supply configuration of the image forming apparatus **101** is checked, and if the printer device **104** does not control the power supply of the entire image forming apparatus **101**, a termination process of the printer device **104** is skipped, which is different from the conventional technology.

(111) Power Supply Configuration of Third Embodiment

(112) The power supply configuration in which the controller **103** controls the power supply has been previously described in the power supply configuration of the first embodiment illustrated in

FIG. 4. The power supply configuration in which the printer device **104** controls the power supply will be described below using the power supply configuration in FIG. 4 in the third embodiment. (113) FIG. 4 is a block diagram illustrating the power supply configuration of the image forming apparatus **101** illustrated in FIG. 1. Hereinafter, regarding the power supply **301**, the power supply control unit **303**, the controller **103**, the operation unit **105**, the scanner device **102**, and the printer device **104** in the image forming apparatus **101**, portions that are related to the present disclosure will be described using FIG. 4.

(114) In FIG. 4, the power supply control unit **303** is constantly supplied with power from the power supply **301** via a power line. However, to maintain minimal power consumption, only the power supply control unit **303** is energized during power-off, and power control is performed.

(115) In the image forming apparatus **101**, when the power switch **110** is pressed, the power supply control unit **303** senses this, controls the power switch (L) **313**, and supplies power to the CPU **307** of the printer device **104**. Similarly, the power supply control unit **303** controls the power switch (P) **310** to supply power to the controller **103**, controls the power switch (Q) **311** to supply power to the CPU **305** of the operation unit **105**, and controls the power switch (R) **312** to supply power to the scanner device **102**.

(116) The CPU **307** of the printer device **104** can also control the power switch (P) **310** by notifying the power supply control unit **303**, thereby individually supplying power to the CPU **340** of the controller **103**.

(117) The CPU **140** of the controller **103** can also control the power switch (Q) **311** by notifying the power supply control unit **303**, thereby individually supplying power from the power supply **301** to the CPU **305** of the operation unit **105**. The CPU **140** of the controller **103** can also control the power switch (R) **311** by notifying the power supply control unit **303**, thereby individually supplying power from the power supply **301** to the scanner device **102**.

(118) At this time, the CPU **307** of the printer device **104** can individually control the power supply of the marking unit **141**, the sheet feed unit **142**, and the sheet discharge unit **143** of the printer device **104** by notifying the power supply control unit **303**.

(119) Note that the power supply for each block as illustrated in FIG. 4 can be realized by, for example, configuring the power switch (L) **313** in two systems, and in the sleep state, turning off only a relay switch leading to a block that is to be powered off, while leaving the other on. In the shutdown state, relay switches of both systems are turned off. In that case, a power supply control signal is not a binary value, but a multi-value control signal in accordance with the energized state. Although such descriptions are particularly omitted in this example, power is supplied through such control in each of the aforementioned power states, including the sleep state and the shutdown state. This control may be performed by the power supply control unit **303** performing multi-value control of the power switch (P) **313** to supply power to each block of the printer device **104**. This control may also be performed by the CPU **307** of the printer device **104** notifying the power supply control unit **303** to perform multi-value control of the power switch (L) **313**, thereby supplying power to each block of the printer device **104**, or may be in any form.

(120) In the power supply system diagram of FIG. 4 in the third embodiment, the printer device **104** controls the power supply of the entire image forming apparatus **101**, and the power supply from the power supply **301** has a hierarchical structure. The printer device **104** controls the power supply to the controller **103**. The controller **103** controls the power supply to the operation unit **105** and the scanner device **102**. If the CPU **307** of the printer device **104** controls the power supply of the entire image forming apparatus **101**, rebooting the printer device **104** allows the controller **103**, the operation unit **105**, and the scanner device **102** to reboot. In addition, if the CPU **307** of the printer device **104** controls the power supply of the entire image forming apparatus **101**, controlling the controller **103** to reboot allows the operation unit **105** and the scanner device **102** to reboot, while allowing the printer device **104** not to reboot.

(121) Description of Flowchart of Third Embodiment

(122) The flowchart of FIG. 7 will be described.

(123) The CPU **340** of the image forming apparatus **101** starts from the standby state where an executable event is receivable.

(124) The CPU **340** receives a system termination process event (**S601**). Termination process events include shutdowns, reboots, transitions to a fast bootable standby state, and so on. If the received termination process event is an event other than a reboot (**S602**; No), the CPU **340** performs a termination process of the printer device **104** (**S650**), and performs a termination process of the controller **103** (**S660**). If the received termination process event is a reboot (**S602**; Yes), the CPU **340** determines whether the printer device **104** controls the power supply of the entire image forming apparatus **101** (**S620**). If the printer device **104** controls the power supply of the entire image forming apparatus **101** (**S620**; Yes), the CPU **340** performs a termination process of the printer device **104** (**S650**), and a termination process of the controller **103** (**S660**). In contrast, if the printer device **104** does not control the power supply of the entire image forming apparatus **101** (**S620**; No), the CPU **340** does not perform a termination process of the printer device **104**, but performs a termination process of the controller **103** (**S660**).

(125) As to whether the printer device **104** controls the power supply of the entire image forming apparatus **101**, the CPU **340** of the controller **103** may obtain a static value saved in the hard disk **106** or the like. In addition, as to whether the printer device **104** controls the power supply of the entire image forming apparatus **101**, the CPU **340** of the controller **103** may obtain a dynamic value by obtaining a value from a register of the power supply control unit **303**. A detailed description of the above will be omitted, but any form may be used.

(126) Effect of Third Embodiment

(127) An effect of the third embodiment is that the downtime when the image forming apparatus **101** reboots can be shortened. In other words, the image forming apparatus **101** starts rebooting. At this time, if the printer device **104** does not control the power supply of the entire image forming apparatus **101**, the printer device **104** is not notified of the termination, and a controller termination process is executed. As a result, when the system configuration information is changed, rebooting is performed to reflect the settings. At this time, if the printer device **104** does not control the power supply of the entire image forming apparatus **101**, a termination process of the printer device **104** can be skipped, and the downtime of the image forming apparatus **101** can be shortened.

(128) Description of Flowchart of Fourth Embodiment

(129) FIG. 8 is a flowchart of a fourth embodiment.

(130) The issue with the fourth embodiment is that, when the printer termination process time is short, it may not be possible to implement a termination process of the printer device **104**, which should be performed if possible. As a result, after reactivation, the initialization process cannot recover properly, leading to an error state.

(131) Therefore, in the fourth embodiment, on receipt of a reboot event, an event for shortening a termination process, such as a reboot, is sent to the printer device **104**, and a termination process of the printer device **104** is shortened when rebooting. In contrast, in the case of a shutdown or a transition to a fast bootable state, an event that does not shorten a termination process, such as a shutdown, is sent, and a termination process of the printer device **104** is not shortened, which is different from the conventional technology.

(132) The flowchart of FIG. 8 will be described.

(133) The CPU **340** of the image forming apparatus **101** starts from the standby state where an executable event is receivable.

(134) The CPU **340** receives a system termination process event (**S701**). Termination process events include shutdowns, reboots, transitions to a fast bootable standby state, and so on. If the received termination process event is an event other than a reboot (**S702**; No), the CPU **340** performs a termination process of the printer device **104** (**S750**), and performs a termination process of the controller **103** (**S760**). In contrast, if the received termination process event is a

reboot (S702; Yes), the CPU **340** notifies the printer device **104** of a termination shortening event (S730). Subsequently, the CPU **340** performs a termination process of the printer device **104** (S750) and performs a termination process of the controller **103** (S760).

(135) Here, the termination shortening event refers to performing a portion of a printer termination process. As described above, there are two types of printer termination processes, one that takes time and the other that does not take time. Time-consuming processes include controlling fan rotation for printer cooling, controlling fan rotation for out-of-machine ozone discharge, and so on. Time-non-consuming processes include the separation movement of the fixing drum, the closing operation of the charging shutter, and so on. Here, upon notification of a termination shortening event, a printer termination process performed in S750 is performed by performing either or both of the separation movement of the fixing drum and the closing operation of the charging shutter, which do not take time, while not performing fan rotation control.

(136) Effect of Fourth Embodiment

(137) An effect of the fourth embodiment is that the downtime when the image forming apparatus **101** reboots can be shortened. In other words, when the image forming apparatus **101** starts rebooting, the image forming apparatus **101** notifies the printer device **104** of a termination shortening event, performs a termination process of the printer device **104**, and executes a termination process of the controller **103**. Accordingly, when the system setting information is changed, for example, if rebooting is performed to reflect the settings, part of a termination process of the printer device **104** can be skipped, and the downtime of the image forming apparatus **101** can be shortened.

OTHER EMBODIMENTS

(138) Although various examples and embodiments of the present disclosure have been described above, the spirit and scope of the present disclosure are not limited to the specific descriptions in the present specification.

(139) Some embodiments can also be realized by a process of supplying a program that realizes one or more functions of the above-described embodiments to a system or apparatus via a network or a storage medium, and reading and executing the program by one or more processors in a computer of the system or apparatus. Some embodiments can also be realized by a circuit (e.g., an application specific integrated circuit (ASIC)) that realizes one or more functions.

Other Embodiments

(140) Some embodiment(s) can also be realized by a computer of a system or apparatus that reads out and executes computer-executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a 'non-transitory computer-readable storage medium') to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer-executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer-executable instructions. The computer-executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)), a flash memory device, a memory card, and the like.

(141) While the present disclosure has described exemplary embodiments, it is to be understood

that some embodiments are not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(142) This application claims priority to Japanese Patent Application No. 2022-153335, which was filed on Sep. 27, 2022 and which is hereby incorporated by reference herein in its entirety.

Claims

1. An image forming apparatus capable of transitioning between at least a standby state and a termination state, the image forming apparatus comprising: a controller; and a printer device configured to form an image on a recording sheet, wherein the controller is configured to receive an event for transitioning a state of the image forming apparatus, wherein the controller is configured to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state, and wherein, when a reboot event is received by the controller, the controller controls whether to execute a termination process of the printer device based on a certain condition of the image forming apparatus.
2. The image forming apparatus according to claim 1, further comprising: a power supply control unit configured to control energization of the controller, wherein, when a reboot event is received and a termination process of the controller is completed, the power supply control unit supplies power to the controller.
3. The image forming apparatus according to claim 1, wherein, when a reboot event is received by the controller, the controller determines a time taken for a termination process of the printer device as the certain condition, and, if it is determined that the time taken is greater than or equal to a certain period of time, controls not to execute a termination process of the printer device.
4. The image forming apparatus according to claim 1, wherein: when a reboot event is received by the controller, it is determined, as the certain condition, whether the printer device controls power supply of the image forming apparatus; and when the printer device controls power supply of the image forming apparatus, the controller controls to execute a termination process of the printer device.
5. The image forming apparatus according to claim 1, wherein, when a termination process of the printer device ends, a termination process of the controller is then executed.
6. The image forming apparatus according to claim 1, wherein a termination process of the printer device includes at least a process of rotating a fan included in the printer device.
7. The image forming apparatus according to claim 1, wherein, when a reboot event is received by the controller, the controller controls not to execute a termination process of the printer device by not notifying the printer device of the termination notification.
8. The image forming apparatus according to claim 1, wherein: a termination process of the printer device includes a first termination process and a process of rotating a fan included in the printer device; when a reboot event is received by the controller, the controller controls to execute, as a shortened version of a termination process of the printer device, the first termination process of the printer device but not to execute a process of rotating the fan.
9. The image forming apparatus according to claim 8, wherein the first termination process is a termination process that does not take time.
10. The image forming apparatus according to claim 8, wherein the first termination process includes at least one or more of a separation movement of a fixing drum and a closing operation of a charging shutter.
11. The image forming apparatus according to claim 1, wherein the reboot event is an event for bringing the image forming apparatus, which is in the standby state, to the termination state and then back to the standby state again.
12. A control method for an image forming apparatus including a controller and a printer device

configured to form an image on a recording sheet, the control method comprising: receiving an event for transitioning a state of the image forming apparatus; and controlling to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state, wherein, when a reboot event is received, it is controlled, in the controlling, whether to execute a termination process of the printer device based on a certain condition of the image forming apparatus.

13. The control method according to claim 12, wherein: the image forming apparatus includes a power supply control unit configured to control energization of the controller, and when a reboot event is received and a termination process of the controller is completed, the power supply control unit supplies power to the controller.

14. The control method according to claim 12, wherein, when a reboot event is received, a time taken for a termination process of the printer device is checked as the certain condition, and, if it is determined that the time taken is greater than or equal to a certain period of time, control is performed not to execute a termination process of the printer device.

15. A non-transitory computer-readable medium storing computer-executable instructions that, when executed by a computer, cause the computer to execute a control method for an image forming apparatus including a controller and a printer device that is configured to form an image on a recording sheet, the control method comprising: receiving an event for transitioning a state of the image forming apparatus; and controlling to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state, wherein, when a reboot event is received, it is controlled, in the controlling, whether to execute a termination process of the printer device based on a certain condition of the image forming apparatus.

16. An image forming apparatus capable of transitioning between at least a standby state and a termination state, the image forming apparatus comprising: a controller; and a printer device configured to form an image on a recording sheet, wherein the controller is configured to receive an event for transitioning a state of the image forming apparatus, wherein the controller is configured to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state, and wherein, when a reboot event is received by the controller, the controller controls to execute a termination process of the controller without executing a termination process of the printer device.

17. The image forming apparatus according to claim 16, further comprising: a power supply control unit configured to control energization of the controller, wherein, when a reboot event is received and a termination process of the controller is completed, the power supply control unit supplies power to the controller.

18. The image forming apparatus according to claim 16, wherein, when a termination process of the printer device ends, a termination process of the controller is then executed.

19. The image forming apparatus according to claim 16, wherein a termination process of the printer device includes at least a process of rotating a fan included in the printer device.

20. The image forming apparatus according to claim 16, wherein, when a reboot event is received by the controller, the controller controls not to execute a termination process of the printer device by not notifying the printer device of the termination notification.

21. The image forming apparatus according to claim 16, wherein the reboot event is an event for bringing the image forming apparatus, which is in the standby state, to the termination state and then back to the standby state again.

22. A control method for an image forming apparatus including a controller and a printer device configured to form an image on a recording sheet, the control method comprising: receiving an event for transitioning a state of the image forming apparatus; and controlling to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state, wherein, when a reboot event is received, a termination

process of the controller is executed without executing a termination process of the printer device.

23. A non-transitory computer-readable medium storing computer-executable instructions that, when executed by a computer, cause the computer to execute a control method for an image forming apparatus including a controller and a printer device that is configured to form an image on a recording sheet, the control method comprising: receiving an event for transitioning a state of the image forming apparatus; and controlling to, by executing a termination process of the printer device and a termination process of the controller, transition from the standby state to the termination state, wherein, when a reboot event is received, a termination process of the controller is executed without executing a termination process of the printer device.
