

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261350

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Lu; Mugui et al.

ALL-IN-ONE POWER SUPPLY APPARATUS, ALL-IN-ONE POWERTRAIN, AND ELECTRIC VEHICLE

Abstract

An all-in-one power supply apparatus. The power supply apparatus includes an integrated groove housing, a radiator, an upper-layer circuit board, and a lower-layer circuit board. The integrated groove housing includes a bottom plate which includes a first flow channel and a second flow channel, and the first flow channel is configured to communicate the second flow channel and the radiator. The first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in a third direction, and the first flow channel and the radiator are configured to cool the upper-layer circuit board. The second flow channel and the lower-layer circuit board are stacked in the third direction, and the second flow channel is configured to cool the lower-layer circuit board. The first flow channel and the second flow channel are arranged in a flat manner, thereby improving heat dissipation efficiency.

Inventors: Lu; Mugui (Dongguan, CN), Du; Lin (Dongguan, CN), Yao; Zirong (Dongguan, CN)

Applicant: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 1000008522051

Assignee: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Appl. No.: 19/038797

Filed: January 28, 2025

Foreign Application Priority Data

CN

202410179470.2

Feb. 08, 2024

Publication Classification

Int. Cl.: **H05K7/20** (20060101); **B60K11/02** (20060101); **B60K17/04** (20060101); **B60L50/64** (20190101); **B60L53/302** (20190101); **H01M10/46** (20060101); **H01M50/249** (20210101); **H02J7/00** (20060101); **H02K7/116** (20060101); **H02K9/19** (20060101); **H02K9/26** (20060101); **H02K11/33** (20160101); **H05K1/02** (20060101)

U.S. Cl.:

CPC **H05K7/20927** (20130101); **B60L50/64** (20190201); **B60L53/302** (20190201); **H01M10/46** (20130101); **H01M50/249** (20210101); **H02J7/0063** (20130101); **H02K7/116** (20130101); **H02K9/19** (20130101); **H02K9/26** (20130101); **H02K11/33** (20160101); **H05K1/0203** (20130101); **B60K11/02** (20130101); **B60K17/04** (20130101); **H01M2220/20** (20130101); **H02K2211/03** (20130101); **H05K2201/064** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to Chinese Patent Application No. 202410179470.2, filed on Feb. 8, 2024, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The embodiments relate to the field of electric vehicle technologies, and to an all-in-one power supply apparatus, an all-in-one powertrain, and an electric vehicle.

BACKGROUND

[0003] An existing electric vehicle usually uses a powertrain as a power source. Currently, the powertrain includes a plurality of components such as a motor, a reducer, a motor control unit, and a heat exchanger. To diversify functions of the powertrain, more functional modules are integrated into the motor control unit. As a result, a temperature of an internal component in the motor control unit increases during operating, and operating efficiency of the internal functional modules of the motor control unit is affected. Generally, heat is dissipated for a device by attaching a water channel to the device. This cannot meet a heat dissipation requirement of the motor control unit.

SUMMARY

[0004] The embodiments provide an all-in-one power supply apparatus, an all-in-one powertrain, and an electric vehicle.

[0005] According to a first aspect, an embodiment provides an all-in-one power supply apparatus. The power supply apparatus is configured to: charge and discharge a battery, and drive a motor. The power supply apparatus includes an integrated groove housing, a radiator, an upper-layer circuit board, and a lower-layer circuit board. The integrated groove housing includes a bottom plate, the bottom plate includes a first flow channel and a second flow channel, and the first flow channel is configured to communicate the second flow channel and the radiator. The first flow channel and the second flow channel are arranged in a first direction. The first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in a third direction, and the first flow channel and the radiator are configured to cool an electrical component in an on-board charger carried on the upper-layer circuit board. The second flow channel and the lower-layer circuit board are stacked in the third direction, and the second flow channel is configured to cool a power module of a motor control unit carried on a lower surface of the lower-layer circuit board.

[0006] In this embodiment, the integrated groove housing is configured to fasten and mount the radiator, the upper-layer circuit board, and the lower-layer circuit board. The radiator, the upper-layer circuit board, and the lower-layer circuit board are supported by the integrated groove housing, so that the radiator, the upper-layer circuit board, and the lower-layer circuit board are

fastened to the integrated groove housing with high stability. In this way, overall structural strength of the power supply apparatus is stronger, and an electrical connection is more stable. When an external environment exerts external force on the power supply apparatus, the radiator, the upper-layer circuit board, the lower-layer circuit board, and the integrated groove housing are not easily displaced relative to each other. This helps the power supply apparatus operate in a stable state.

[0007] In this embodiment, the power supply apparatus generates a large amount of heat in an operating process, and heat dissipation needs to be performed on the power supply apparatus to ensure that a component in the power supply apparatus operates normally. The bottom plate includes the first flow channel and the second flow channel. The first flow channel and the second flow channel are configured to cool the electrical components carried by the upper-layer circuit board and the lower-layer circuit board in the power supply apparatus. The first flow channel is configured to communicate the second flow channel and the radiator, to facilitate communication of a coolant in the power supply apparatus. In an embodiment, after entering the power supply apparatus, the coolant sequentially passes through the radiator, the first flow channel, and the second flow channel, to implement series circulation cooling of the coolant in the power supply apparatus. In an embodiment, after the coolant enters the power supply apparatus, one part of the coolant flows through the radiator and the first flow channel to the second flow channel, and the other part of the coolant directly flows from the first flow channel to the second flow channel without passing through the radiator. The two parts of the coolant converge in the second flow channel, to implement parallel circulation of the coolant in the power supply apparatus for cooling.

[0008] In this embodiment, the first flow channel and the second flow channel are arranged in the first direction, and primary regions of the upper-layer circuit board and the lower-layer circuit board are also arranged in the first direction. This helps the first flow channel and the second flow channel cool the lower-layer circuit board and the upper-layer circuit board.

[0009] In this embodiment, the first flow channel and the radiator are configured to cool the electrical component that is of the on-board charger and that is carried by the upper-layer circuit board. The first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in the third direction. The upper-layer circuit board is sandwiched between the first flow channel and the radiator. This helps the coolant in the first flow channel and the radiator dissipate heat for the electrical component in the on-board charger on the upper-layer circuit board, improves heat dissipation efficiency, and improves cooling effect of the coolant on the power supply apparatus.

[0010] In this embodiment, the second flow channel is configured to cool the power module of the motor control unit carried on the lower surface of the lower-layer circuit board. The second flow channel and the lower-layer circuit board are stacked in the third direction. Therefore, the second flow channel covers a mounting region in which the power module of the motor control unit is mounted on the bottom plate. In this way, the second flow channel cools the power module of the motor control unit as much as possible, thereby improving cooling efficiency.

[0011] In an embodiment, the first flow channel is configured to cool at least one of a transformer, a plurality of inductors, and a plurality of capacitors in the on-board charger carried on a lower surface of the upper-layer circuit board, and the radiator is configured to cool a plurality of power switching transistors of the on-board charger carried on an upper surface of the upper-layer circuit board.

[0012] In this embodiment, the first flow channel is located on the bottom plate. The transformer, the plurality of inductors, and the plurality of capacitors in the on-board charger are sequentially arranged on the lower surface of the upper-layer circuit board in a second direction. The first flow channel is configured to cool at least one of the transformer, the plurality of inductors, and the plurality of capacitors in the on-board charger that are carried on the lower surface of the upper-layer circuit board. In this way, at least one of the transformer, the plurality of inductors, and the plurality of capacitors in the on-board charger can be cooled in time when the on-board charger

operates. This helps reduce a temperature in the power supply apparatus, and ensures normal operating of the power supply apparatus.

[0013] In this embodiment, the radiator is configured to cool the plurality of power switching transistors of the on-board charger carried on the upper surface of the upper-layer circuit board. The plurality of power switching transistors of the on-board charger is closer to the radiator than the first flow channel, so that the radiator can cool the plurality of power switching transistors of the on-board charger. This helps reduce the temperature in the power supply apparatus, and ensures normal operating of the power supply apparatus.

[0014] In this embodiment, the first flow channel and the radiator are respectively configured to cool the electrical components carried on the lower surface and the lower surface of the upper-layer circuit board. Some electrical components in the upper-layer circuit board are stacked between the upper-layer circuit board and the bottom plate, and some electrical components are stacked between the upper-layer circuit board and the radiator. This not only improves cooling and heat dissipation effect of the electrical components, but also can fully use space of the upper surface and the lower surface of the upper-layer circuit board, so that the components are arranged more compactly, a heat dissipation and cooling region is more centralized, and heat dissipation effect is better. This improves power density and operating efficiency of the power supply apparatus.

[0015] In an embodiment, the lower-layer circuit board includes a primary region and a secondary region, a lower surface of the primary region is configured to fasten the power module of the motor control unit, and the secondary region is configured to fasten at least a part of power switching transistors of a direct current converter. The primary region and the secondary region are arranged in the first direction. The first flow channel, the secondary region, and the upper-layer circuit board are stacked in the third direction. The second flow channel and the primary region are stacked in the third direction.

[0016] In this embodiment, the lower surface of the primary region of the lower-layer circuit board is configured to fasten the power module of the motor control unit, and the secondary region of the lower-layer circuit board is configured to fasten the at least a part of power switching transistors of the direct current converter, so that the power module of the fastened motor control unit and the at least a part of power switching transistors of the direct current converter are integrated into the lower-layer circuit board. This helps improve integration of the power supply apparatus and reduce a quantity of used circuit boards.

[0017] In this embodiment, the primary region and the secondary region are arranged in the first direction, and the first flow channel and the second flow channel are arranged in the first direction. This makes it possible for the first flow channel and the second flow channel to jointly cool the lower-layer circuit board, and helps improve cooling efficiency of the lower-layer circuit board. The first flow channel, the secondary region, and the upper-layer circuit board are stacked in the third direction, so that the first flow channel can not only cool the upper-layer circuit board, but also cool the secondary region of the lower-layer circuit board, thereby improving efficiency of cooling the power supply apparatus by the coolant. The second flow channel and the primary region are stacked in the third direction, so that the second flow channel cools the primary region of the lower-layer circuit board, to ensure normal operating of the electrical component in the lower-layer circuit board.

[0018] In an embodiment, the bottom plate includes a first flow channel groove and a second flow channel groove, the first flow channel groove is recessed in the third direction from a lower surface of the bottom plate to the upper-layer circuit board, the first flow channel groove is configured to form the first flow channel, the second flow channel groove is recessed in the third direction from the upper surface of the bottom plate and away from the lower-layer circuit board, and the second flow channel groove is configured to form the second flow channel.

[0019] In this embodiment, the first flow channel groove and the second flow channel groove of the bottom plate make it possible for the coolant to flow in the power supply apparatus. The first

flow channel groove is recessed in the third direction from the lower surface of the bottom plate to the upper-layer circuit board, to help form the first flow channel on the lower surface of the bottom plate. In this way, arrangement of the first flow channel does not affect mounting and arrangement of the electrical components in the upper-layer circuit board and the lower-layer circuit board in the power supply apparatus. The second flow channel groove is recessed in the third direction from the upper surface of the bottom plate to the direction away from the lower-layer circuit board. This helps form the second flow channel on the upper surface of the bottom plate. The second flow channel is formed on the upper surface of the bottom plate, and the second flow channel is closer to the lower-layer circuit board. This helps the second flow channel cool the lower-layer circuit board. This helps enable a difference between heights of a primary region corresponding to an inner cavity of the integrated groove housing and two parts of the upper-layer circuit board in the third direction to be small, so that components in the inner cavity of the integrated groove housing are arranged in a more regular and orderly manner.

[0020] In an embodiment, in the third direction, a spacing between a groove bottom of the first flow channel groove and the radiator is less than a spacing between a groove bottom of the second flow channel groove and the radiator.

[0021] In this embodiment, the first flow channel groove is located on the lower surface of the bottom plate. In the third direction, the spacing between the groove bottom of the first flow channel groove and the radiator is small. In other words, the coolant in the radiator and the coolant in the first flow channel are closer to the upper-layer circuit board. This helps cool the upper-layer circuit board. The second flow channel groove is located on the upper surface of the bottom plate. In the third direction, the spacing between the groove bottom of the second flow channel groove and the radiator is large, to provide larger space for the second flow channel groove to form the second flow channel, so that more coolants flow through the second flow channel. In this way, the lower-layer circuit board is better cooled, and more space is provided for mounting the electrical component in the lower-layer circuit board.

[0022] In this embodiment, the groove bottom of the first flow channel groove and the groove bottom of the second flow channel groove are staggered in the third direction toward each other. In comparison with a solution in which the groove bottom of the first flow channel groove and the groove bottom of the second flow channel groove are staggered in the third direction away from each other, or in comparison with a solution in which the groove bottom of the first flow channel groove and the groove bottom of the second flow channel groove are aligned in the third direction, in this solution, a length of the first flow channel groove and a length of the second flow channel groove in the third direction can be reduced, so that a length of the power supply apparatus in the third direction can be reduced, thereby facilitating miniaturization of the power supply apparatus.

[0023] In an embodiment, a length of the first flow channel groove in the first direction is greater than a length of the second flow channel groove in the first direction, and a length of the first flow channel groove in the second direction is greater than a length of the second flow channel groove in the second direction.

[0024] In this embodiment, the length of the first flow channel groove in the first direction is large, so that a surface area of the first flow channel adjacent to the electrical component in the upper-layer circuit board is larger, and more coolants flow through the first flow channel in the first flow channel groove. This helps improve efficiency of cooling the upper-layer circuit board by the first flow channel. The length of the second flow channel groove in the first direction is small, so that more mounting space is provided for the plurality of chips of a vehicle control unit.

[0025] In this embodiment, the length of the first flow channel groove in the second direction is large. This helps the first flow channel dissipate heat for more electrical components in the upper-layer circuit board in the second direction and improves cooling efficiency on the upper-layer circuit board. Because the second flow channel groove is disposed on the upper surface of the bottom plate, the length of the second flow channel groove in the second direction is small, and

more mounting space is provided for a bus capacitor and a power distribution unit of the motor control unit.

[0026] In an embodiment, a groove peripheral wall of the second flow channel groove includes a communication hole, and the communication hole is configured to communicate with the first flow channel groove. A part of the groove peripheral wall of the second flow channel groove is adjacent to a part of the groove peripheral wall of the first flow channel groove in the first direction. The communication hole penetrates, in the first direction, the part of the groove peripheral wall of the second flow channel groove and the part of the groove peripheral wall of the first flow channel groove that are adjacent to each other.

[0027] In this embodiment, the communication hole communicates the first flow channel groove with the second flow channel groove, so that the coolant in the first flow channel can flow into the second flow channel from the communication hole. This facilitates circulation of the coolant in the power supply apparatus and helps improve a fusion degree of the power supply apparatus.

[0028] In this embodiment, the part of the groove peripheral wall of the second flow channel groove is adjacent to the part of the groove peripheral wall of the first flow channel groove in the first direction, so that it is possible to provide the communication hole on the groove peripheral wall of the second flow channel groove to communicate the second flow channel groove with the first flow channel groove.

[0029] In this embodiment, the communication hole penetrates, in the first direction, the part of the groove peripheral wall of the second flow channel groove and the part of the groove peripheral wall of the first flow channel groove that are adjacent to each other, so that the coolant in the first flow channel flows into the second flow channel in the first direction, and a flow path between the first flow channel and the second flow channel is shortened.

[0030] In an embodiment, a groove peripheral wall of the second flow channel groove includes a communication hole, and the communication hole is configured to communicate with the first flow channel groove. A part of a groove bottom wall of the second flow channel groove is adjacent to a part of a groove bottom wall of the first flow channel groove in the third direction. The communication hole penetrates, in the third direction, the part of the groove bottom wall of the second flow channel groove and the part of the groove bottom wall of the first flow channel groove that are adjacent to each other.

[0031] In this embodiment, the communication hole communicates the first flow channel groove with the second flow channel groove, so that the coolant in the first flow channel can flow into the second flow channel from the communication hole. This facilitates circulation of the coolant in the power supply apparatus and helps improve a fusion degree of the power supply apparatus.

[0032] In this embodiment, the groove bottom of the first flow channel groove is located on the lower surface of the bottom plate, the groove bottom of the second flow channel groove is located on the upper surface of the bottom plate, and the part of the groove bottom wall of the second flow channel groove is adjacent to the part of the groove bottom wall of the first flow channel groove in the third direction. This provides space for the coolant in the first flow channel in the first flow channel groove to flow into the second flow channel in the second flow channel groove.

[0033] In this embodiment, the communication hole penetrates, in the third direction, the part of the groove bottom wall of the second flow channel groove and the part of the groove bottom wall of the first flow channel groove that are adjacent to each other, so that the coolant in the first flow channel flows into the second flow channel through the communication hole in the third direction, and a flow path between the first flow channel and the second flow channel is shortened. This helps improve the overall fusion degree in the power supply apparatus.

[0034] In an embodiment, a peripheral side wall of the integrated groove housing includes a liquid inlet, the bottom plate includes a liquid outlet, the groove peripheral wall of the second flow channel groove includes the communication hole, the liquid inlet is configured to communicate with the radiator and the first flow channel groove, the liquid outlet is configured to communicate

with the second flow channel, and the communication hole is configured to communicate with the first flow channel groove and the second flow channel groove. The liquid outlet, the communication hole, and the liquid inlet are sequentially spaced in the first direction. The liquid outlet penetrates the groove bottom of the second flow channel groove in the third direction. An opening of the liquid inlet faces away from an inner cavity of the integrated groove housing in the first direction.

[0035] In this embodiment, the liquid inlet is configured to input a coolant in a vehicle cooling system into the power supply apparatus, the liquid outlet is configured to output the heated coolant obtained after the power supply apparatus is cooled, and the liquid inlet is located on the peripheral side wall of the integrated groove housing. This facilitates arrangement of an external cooling pipe connected to the liquid inlet. The liquid outlet is located on the bottom plate of the integrated groove housing. This helps the coolant flowing out of the power supply apparatus in a gravity direction after a temperature rises and helps reduce a power loss.

[0036] In this embodiment, the liquid inlet is configured to communicate with the radiator and the first flow channel groove, and the coolant in the vehicle cooling system flows into the radiator and the first flow channel groove from the liquid inlet, so that the coolant in the radiator and the coolant in the first flow channel groove simultaneously cool the upper-layer circuit board. This helps improve cooling efficiency of the power supply apparatus. The liquid outlet is configured to communicate with the second flow channel, so that the coolant in the second flow channel can flow out of the power supply apparatus from the liquid outlet. The coolant from the vehicle cooling system sequentially flows through the liquid inlet, the first flow channel, the communication hole, the second flow channel, and the liquid outlet, or sequentially flows through the liquid inlet, the radiator, the first flow channel, the communication hole, the second flow channel, and the liquid outlet.

[0037] In this embodiment, the liquid outlet, the communication hole, and the liquid inlet are sequentially spaced in the first direction, so that the first flow channel and the second flow channel are arranged in the first direction, and the coolant smoothly flows through the liquid inlet, the communication hole, and the liquid outlet in sequence.

[0038] In this embodiment, the liquid outlet penetrates the groove bottom of the second flow channel groove in the third direction, so that the external cooling pipe connected to the liquid outlet is arranged below the power supply apparatus in the third direction, and the coolant flows out of the power supply apparatus from the groove bottom of the second flow channel groove in the gravity direction, thereby reducing a power loss. The opening of the liquid inlet faces away from the inner cavity of the integrated groove housing in the first direction, to facilitate connection and mounting of the external pipe connected to the liquid inlet.

[0039] In an embodiment, the first flow channel groove includes a separation rib, the separation rib is configured to separate the first flow channel groove into two flow channel sub-grooves, and the two flow channel sub-grooves are spaced in the second direction. An inlet of one of the flow channel sub-grooves is configured to communicate with the liquid inlet through an internal oil channel of the integrated groove housing, the other one of the flow channel sub-grooves is configured to communicate with an outlet of the radiator through the internal oil channel of the integrated groove housing, and outlets of the two flow channel sub-grooves are configured to communicate with the communication hole of the second flow channel groove.

[0040] In this embodiment, the separation rib is fastened to the lower surface of the bottom plate and extends in the third direction, and the separation rib separates the first flow channel groove into two flow channel sub-grooves, so that the coolant input from the liquid inlet flows through one of the flow channel sub-grooves in a more centralized manner. A flowing speed of the coolant in the one flow channel sub-groove is increased, so that a coolant with a low temperature is continuously input into the one flow channel sub-groove. This helps improve cooling efficiency of the power supply apparatus. In addition, after the coolant is input into the radiator from the liquid inlet, the

coolant in the radiator may flow out of the power supply apparatus through the other flow channel sub-groove.

[0041] In this embodiment, the coolant from the vehicle cooling system may flow out of the power supply apparatus through the liquid inlet, the inlet of the one flow channel sub-groove, the one flow channel sub-groove, the outlet of one flow channel sub-groove, the communication hole, the second flow channel groove, and the liquid outlet in sequence. The coolant may flow out of the power supply apparatus through the liquid inlet, the radiator, the outlet of the radiator, the other flow channel sub-groove, the outlet of the other flow channel sub-groove, the communication hole, the second flow channel groove, and the liquid outlet in sequence. The first flow channel groove is separated into the two flow channel sub-grooves. When the coolant flowing in the other flow channel sub-groove is a coolant whose temperature increases in the radiator, it can be ensured that the coolant in the one flow channel sub-groove is a coolant with a low temperature that is directly from the vehicle cooling system. This helps ensure cooling effect of the first flow channel groove on the upper-layer circuit board.

[0042] In an embodiment, the bottom plate further includes a power distribution groove, a bus capacitor groove, and a three-phase connector mounting hole, the power distribution groove is configured to accommodate a copper bar of the power distribution unit, the bus capacitor groove is configured to accommodate a bus capacitor of the motor control unit, and the three-phase connector mounting hole is configured to fasten a connector between the motor control unit and a motor winding. The three-phase connector mounting hole, the second flow channel groove, the bus capacitor groove, and the power distribution groove are sequentially arranged in the second direction.

[0043] In this embodiment, the power distribution groove is configured to accommodate the copper bar of the power distribution unit. The power distribution unit converts a high voltage direct current output by the battery into a direct current voltage or an alternating current required by a load when the load operates, to supply power to the load. The copper bar of the power distribution unit is further connected to a connector in a direct current input connector mounting hole and a connector in a battery charge and discharge connector mounting hole, and is configured to transmit a direct current of a direct current power supply to the battery to charge the battery. The bus capacitor groove is configured to accommodate the bus capacitor of the motor control unit. The bus capacitor can smooth a bus voltage, so that the bus voltage of the motor control unit is still smooth when the power switching transistor is turned on or off, can further reduce an inductance parameter of a line from a power switching transistor end of the motor control unit to an end of the battery, to weak a peak voltage of the bus, can further absorb a high pulse current at a bus end of the motor control unit, and can further prevent overcharge of a voltage at the bus end and impact of an instantaneous voltage on the motor control unit. The three-phase connector mounting hole is configured to fasten the connector between the motor control unit and the motor winding. The connector between the motor control unit and the motor winding transmits an alternating current of the motor control unit to the motor winding, to drive a rotor and a motor shaft of the motor to rotate.

[0044] In this embodiment, the three-phase connector mounting hole, the second flow channel groove, the bus capacitor groove, and the power distribution groove are sequentially arranged in the second direction. This helps regular arrangement of the electrical components on the power supply apparatus. In addition, a three-phase copper bar component, the power module, the bus capacitor, and the copper bar of the power distribution unit are sequentially arranged in the second direction. This helps cool the power module by using the coolant in the second flow channel groove.

[0045] In this embodiment, the second flow channel groove and the power distribution groove are spaced through the bus capacitor groove, to prevent a cooling medium penetrating the second flow channel groove in an extreme case from affecting power transmission of the copper bar in the power distribution groove and ensure cooling effect and stability of transmission power of the copper bar.

[0046] In an embodiment, the bottom plate further includes a communication connector mounting hole, and the communication connector mounting hole is configured to fasten a connector between a vehicle control unit and a vehicle-mounted load. The communication connector mounting hole, the second flow channel groove, and the first flow channel groove are sequentially arranged in the first direction.

[0047] In this embodiment, the communication connector mounting hole is configured to fasten the connector between the vehicle control unit and the vehicle-mounted load. The vehicle control unit is configured to transmit a communication signal of the vehicle-mounted load to the power supply apparatus, to control the power supply apparatus. The communication connector mounting hole, the second flow channel groove, and the first flow channel groove are sequentially arranged in the first direction, to facilitate arrangement and normalization of the electrical components on the power supply apparatus. The liquid outlet is located between the second flow channel groove and the communication connector mounting hole, so that when the coolant in the first flow channel groove and the coolant in the second flow channel groove are discharged from the external cooling pipe connected to the liquid outlet, the external cooling pipe connected to the liquid outlet does not occupy too much space of the power supply apparatus in the first direction. This facilitates a compact layout of the powertrain and optimizes vehicle performance.

[0048] In this embodiment, the communication connector mounting hole and the three-phase connector mounting hole are distributed on two adjacent sides of the second flow channel groove, so that the cooling medium of the second flow channel groove can absorb heat of the connectors in the communication connector mounting hole and the three-phase connector mounting hole, to cool the connectors in the communication connector mounting hole and the three-phase connector mounting hole. This helps signal transmission of the communication connector in the communication connector mounting hole be more stable and helps the connector in the three-phase connector mounting hole transmit power more quickly, to avoid heat generation.

[0049] In an embodiment, the upper surface of the bottom plate further includes a transformer groove, an inductor groove, and a direct current filter groove, the transformer groove is configured to accommodate the transformer of the on-board charger, the inductor groove is configured to accommodate the plurality of inductors in the on-board charger, and the direct current filter groove is configured to accommodate a magnetic component in a direct current filter. At least one of the transformer groove, the inductor groove, and the direct current filter groove is stacked between the first flow channel groove and the upper-layer circuit board in the third direction. The transformer groove, the inductor groove, the direct current filter groove, and the first flow channel groove are arranged on a same side of the second flow channel groove in the first direction.

[0050] In this embodiment, the transformer groove and the inductor groove are arranged in the second direction, and the transformer groove and the direct current filter groove are arranged in the first direction. The transformer groove is configured to accommodate the transformer of the on-board charger, the inductor groove is configured to accommodate the plurality of inductors in the on-board charger, and the direct current filter groove is configured to accommodate the magnetic component in the direct current filter. The transformer groove, the inductor groove, and the direct current filter groove are disposed, so that structural firmness of the integrated groove housing can be improved. This helps improve stability of the power supply apparatus and reduce electrical impact between module components.

[0051] In this embodiment, at least one of the transformer groove, the inductor groove, and the direct current filter groove is stacked between the first flow channel groove and the upper-layer circuit board in the third direction. This helps the coolant in the first flow channel groove cool at least one of the transformer of the on-board charger, the plurality of inductors in the on-board charger, and the magnetic component in the direct current filter.

[0052] In this embodiment, the transformer groove, the inductor groove, the direct current filter groove, and the first flow channel groove are arranged on a same side of the second flow channel

groove in the first direction. This helps arrange the transformer of the on-board charger, the plurality of inductors in the on-board charger, and the magnetic component in the direct current filter on the lower surface of the upper-layer circuit board. This helps improve integration and fusion of the power supply apparatus, and further helps the first flow channel groove cool the transformer of the on-board charger in the transformer groove, the plurality of inductors in the on-board charger in the inductor groove, and the magnetic component in the direct current filter in the direct current filter groove. In this way, cooling of the power supply apparatus is implemented, and stable running of the power supply apparatus is ensured.

[0053] According to a second aspect, an embodiment provides an all-in-one powertrain. The powertrain includes a motor, a reducer, and the power supply apparatus according to any one of the foregoing implementations. The power supply apparatus is connected to a winding of the motor through a motor control unit to drive the motor. A motor shaft of the motor is in transmission connection to an input shaft of the reducer.

[0054] In this embodiment, the power supply apparatus is configured to charge and discharge a battery and drive the motor. The power supply apparatus is configured to receive a direct current transmitted by the battery, convert the direct current into an alternating current, and transmit the alternating current to the motor. The power supply apparatus is connected to the winding of the motor through the motor control unit to drive the motor. The motor shaft of the motor is in transmission connection to the input shaft of the reducer, to drive the reducer to operate. The first flow channel and the radiator in the power supply apparatus are communicated in series or in parallel. The first flow channel and the radiator simultaneously cool the upper-layer circuit board. The second flow channel cools the power module. The first flow channel and the second flow channel are arranged in a flat manner. In this way, a heat dissipation path of the coolant in the power supply apparatus is longer, thereby effectively improving heat dissipation efficiency of the power supply apparatus, and further improving heat dissipation efficiency of the powertrain.

[0055] According to a third aspect, an embodiment provides an electric vehicle. The electric vehicle includes a vehicle frame, a power battery, and the foregoing powertrain. The vehicle frame is configured to fasten the power battery and the powertrain. The power battery is configured to connect to the power supply apparatus.

[0056] In this embodiment, the power supply apparatus is configured to charge and discharge the power battery and drive the motor of the powertrain. The power supply apparatus in the powertrain is provided with the first flow channel, the second flow channel, and the radiator. The first flow channel and the radiator simultaneously cool the upper-layer circuit board in the power supply apparatus. The second flow channel cools the power module of the lower-layer circuit board. The first flow channel and the second flow channel are arranged in a flat manner, so that a heat dissipation path of the coolant in the power supply apparatus is longer. This effectively improves heat dissipation efficiency of the power supply apparatus, and further improves heat dissipation efficiency of the powertrain. In this way, vehicle performance is improved.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0057] To describe solutions in embodiments more clearly, the following describes accompanying drawings used in embodiments.

[0058] FIG. 1 is a diagram of a structure of an electric vehicle according to an embodiment;

[0059] FIG. 2A is a diagram of a structure of a powertrain according to an embodiment;

[0060] FIG. 2B is a diagram of another structure of a powertrain according to an embodiment;

[0061] FIG. 2C is a diagram of another structure of a powertrain according to an embodiment;

[0062] FIG. 3 is a schematic exploded view of a powertrain according to an embodiment;

[0063] FIG. 4 is a diagram of a structure of a power supply apparatus according to an embodiment;
[0064] FIG. 5 is an exploded view of a power supply apparatus according to an embodiment;
[0065] FIG. 6 is a diagram of another structure of a power supply apparatus according to an embodiment;
[0066] FIG. 7 is another exploded view of a power supply apparatus according to an embodiment;
[0067] FIG. 8 is another exploded view of a power supply apparatus according to an embodiment;
[0068] FIG. 9 is another exploded view of a power supply apparatus according to an embodiment;
[0069] FIG. 10 is a diagram of another structure of a power supply apparatus according to an embodiment;
[0070] FIG. 11 is a diagram of a structure of an integrated groove housing according to an embodiment;
[0071] FIG. 12 is a diagram of another structure of an integrated groove housing according to an embodiment;
[0072] FIG. 13 is a bottom view of an integrated groove housing according to an embodiment;
FIG. 14 is an AA cross sectional view of FIG. 13;
[0073] FIG. 15 is a diagram of a partial structure of an integrated groove housing according to an embodiment; and
[0074] FIG. 16 is a diagram of structures of a first flow channel groove and a second flow channel groove according to an embodiment.

DETAILED DESCRIPTION OF EMBODIMENTS

[0075] The following describes the solutions in embodiments with reference to the accompanying drawings. It is clear that the described embodiments are merely a part, rather than all, of the embodiments.

[0076] For ease of understanding, English abbreviations and related terms used in embodiments are first explained and described below.

[0077] NVH: NVH is short for noise, vibration, harshness.

[0078] DCDC: DC is short for direct current. DCDC represents an apparatus that converts a direct current power supply of a voltage level into a direct current power supply of another voltage level. DCDC is classified into a boost power supply and a buck power supply based on a voltage level conversion relationship. For example, a DCDC converter connected to a vehicle-mounted power supply system converts a high voltage direct current into a low voltage direct current.

[0079] Parallel: This may be understood as basically parallel, and is not limited to absolute parallel or an included angle of 180 degrees. An included angle that is not absolutely parallel and that is less than or greater than 180 degrees due to factors such as assembly tolerance, design tolerance, and process tolerance is also basically parallel.

[0080] Vertical: This may be understood as basically vertical, and is not limited to absolute vertical intersection or an included angle of 90 degrees. An included angle that is not absolutely vertical intersection and that is less than or greater than 90 degrees due to factors such as assembly tolerance, design tolerance, and process tolerance is also basically vertical.

[0081] First direction, second direction, and third direction: The first direction is vertical to the second direction and the third direction, the second direction is vertical to the first direction and the third direction, the third direction is vertical to the first direction and the second direction, and the second direction is parallel to an axial direction of a powertrain or an axial direction of a motor.

[0082] To improve heat dissipation efficiency of a power supply apparatus and ensure stable running of the power supply apparatus, the embodiments provide an all-in-one power supply apparatus. The power supply apparatus is configured to: charge and discharge a battery, and drive a motor. The power supply apparatus includes an integrated groove housing, a radiator, an upper-layer circuit board, and a lower-layer circuit board. The integrated groove housing includes a bottom plate, the bottom plate includes a first flow channel and a second flow channel, and the first flow channel is configured to communicate the second flow channel and the radiator. The first flow

channel and the second flow channel are arranged in a first direction. The first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in a third direction, and the first flow channel and the radiator are configured to cool an electrical component in an on-board charger carried on the upper-layer circuit board. The second flow channel and the lower-layer circuit board are stacked in the third direction, and the second flow channel is configured to cool a power module of a motor control unit carried on a lower surface of the lower-layer circuit board. The upper-layer circuit board is stacked between the first flow channel and the radiator, and the upper-layer circuit board is cooled by a coolant in the first flow channel and the radiator, thereby improving heat dissipation efficiency of the power supply apparatus. The first flow channel and the second flow channel are arranged in a flat manner. In this way, a heat dissipation path for the coolant in the power supply apparatus is longer, thereby further improving heat dissipation efficiency of the power supply apparatus and ensuring normal operating of the power supply apparatus.

[0083] The all-in-one power supply apparatus provided in embodiments is used in an all-in-one powertrain, and the all-in-one powertrain is used in an electric vehicle, to improve overall performance of the electric vehicle.

[0084] FIG. 1 is a diagram of a structure of an electric vehicle 1 according to an embodiment.

[0085] As shown in FIG. 1, in this embodiment, the electric vehicle 1 is a wheeled device driven or pulled by a power apparatus.

[0086] In this embodiment, the electric vehicle 1 includes a powertrain 10, a vehicle frame 20, a battery 30, and wheels 40. The powertrain 10 and the battery 30 are fastened to the vehicle frame 20. The powertrain 10 is configured to receive power supplied by the battery 30, and is configured to drive the wheels 40. In this embodiment, the battery 30 may also be referred to as a battery pack or a power battery. In this embodiment, the powertrain 10 includes a motor 300, a reducer 200, and a power supply apparatus 100. In this embodiment, the motor 300 includes a motor shaft, a motor stator, and a motor rotor. In this embodiment, the reducer 200 is a single-level reduction gear assembly, a two-level reduction gear assembly, or a multi-level reduction gear assembly. The motor rotor in the motor 300 is fastened to and sleeved on the motor shaft. After receiving an alternating current, the motor stator drives the motor rotor to rotate, to drive the motor shaft to rotate. The motor shaft of the motor 300 is configured to be in transmission connection to the reducer 200. In an embodiment, the reducer 200 includes a gear assembly, an input shaft, a middle shaft, and an output shaft. The motor shaft of the motor 300 is configured to be in transmission connection to the input shaft of the reducer 200, and the input shaft is in transmission connection to the output shaft through the gear assembly and the middle shaft.

[0087] FIG. 2A is a diagram of a structure of the powertrain 10 according to an embodiment. FIG. 2B is a diagram of another structure of the powertrain 10 according to an embodiment. FIG. 2C is a diagram of another structure of the powertrain 10 according to an embodiment. FIG. 3 is a schematic exploded view of the powertrain 10 according to an embodiment.

[0088] As shown in FIG. 2A, the reducer 200 includes an input shaft 230, a middle shaft 240, and an output shaft 250. An input wheel is fastened to the input shaft 230, a middle wheel is fastened to the middle shaft 240, and an output wheel is fastened to the output shaft 250. The input shaft 230 is in transmission connection to the motor shaft. The input shaft 230 drives the input wheel of the reducer 200 to rotate, the input wheel drives the middle wheel to rotate, and then the middle wheel transmits power to the output wheel. In an embodiment, outer diameters of gears of the input wheel, the middle wheel, and the output wheel sequentially increase, and quantities of bevel teeth of outer rings of the input wheel, the middle wheel, and the output wheel gradually increase, to facilitate two-level deceleration and implement deceleration and torque increase. This better matches a power requirement of a vehicle.

[0089] As shown in FIG. 2A, the powertrain 10 further includes a heat exchanger 400. In this embodiment, the motor 300 and the reducer 200 are cooled and lubricated by using cooling oil. The

heat exchanger **400** is configured to cool the cooling oil.

[0090] In an embodiment, the heat exchanger **400** includes a liquid inlet **410** of the heat exchanger and a liquid outlet **420** of the heat exchanger. The liquid inlet **410** of the heat exchanger is configured to receive a coolant. The coolant exchanges heat with the cooling oil in the heat exchanger **400**, to take away heat in the cooling oil with a high temperature. Then, the coolant flows out of the heat exchanger **400** from the liquid outlet **420** of the heat exchanger. In this way, the coolant cools the entire powertrain **10**.

[0091] In this embodiment, the heat exchanger **400** and the reducer **200** are stacked in a second direction Y, so that the heat exchanger **400** does not occupy a height of the powertrain **10** in a third direction Z, and a height of the powertrain **10** is small. This helps mount the powertrain **10** on the electric vehicle.

[0092] In this embodiment, the power supply apparatus **100**, the motor **300**, and the reducer **200** may be of a split structure or an integrated structure. In an embodiment, the motor **300** and the power supply apparatus **100** share one housing. This helps reduce a volume of the powertrain **10**, so that the powertrain **10** is more centralized. In an embodiment, the reducer **200** and the power supply apparatus **100** share one housing. This helps reduce the volume of the powertrain **10**, so that the powertrain **10** is more centralized. In an embodiment, the motor **300**, the reducer **200**, and the power supply apparatus **100** share one housing. This helps reduce the volume of the powertrain **10**, so that the powertrain **10** is more centralized.

[0093] In an embodiment, the motor **300** and the reducer **200** are of an integrated structure. As shown in FIG. 2A, the motor **300** and the reducer **200** share an integrated housing **500**. The integrated housing **500** for the motor **300** and the reducer **200** and a housing of the power supply apparatus **100** are of a split structure. The housing of the power supply apparatus **100** is fastened above the integrated housing **500** of the motor **300** and the reducer **200**.

[0094] In an embodiment, the housing of the powertrain **10** further includes a motor end cover **600** and a reducer end cover **700**. As shown in FIG. 2A, in an axial direction of the motor **300**, the integrated housing **500** is arranged between the motor end cover **600** and the reducer end cover **700**. The integrated housing **500** and the motor end cover **600** are enclosed to form a motor accommodating cavity, and the integrated housing **500** and the reducer end cover **700** are enclosed to form a reducer accommodating cavity. The motor accommodating cavity is configured to fasten the stator of the motor **300** and accommodate the rotor of the motor **300**, and the reducer accommodating cavity is configured to accommodate the gear assembly of the reducer **200**.

[0095] In an embodiment, the reducer end cover **700** includes an input shaft bearing hole **210**, a middle shaft bearing hole **220**, and an output shaft bearing hole **260**. As shown in FIG. 2A, the input shaft bearing hole **210** is configured to accommodate a bearing sleeved on the input shaft **230** of the reducer **200**. The input shaft **230** of the reducer **200** is in transmission connection to the motor shaft of the motor **300**. The middle shaft bearing hole **220** is configured to accommodate a bearing sleeved on the middle shaft **240** of the reducer **200**. The output shaft bearing hole **260** is configured to accommodate a bearing sleeved on the output shaft **250** of the reducer **200**.

[0096] In an embodiment, the reducer end cover **700** includes a plurality of compressor mounting bosses **11**. The plurality of compressor mounting bosses **11** are configured to fasten a compressor. The plurality of compressor mounting bosses **11** are disposed on the reducer end cover **700**, so that the compressor can be fastened to the powertrain **10**, the powertrain **10** is integrated with the compressor, and the powertrain **10** is more integrated.

[0097] In an embodiment, the plurality of compressor mounting bosses **11a** are distributed on peripheral sides of the input shaft bearing hole **210** and the middle shaft bearing hole **220**. As shown in FIG. 2A, the plurality of compressor mounting bosses **11a** are distributed on the peripheral sides of the input shaft bearing hole **210** and the middle shaft bearing hole **220**, so that the compressor is mounted and arranged on an outer side of the reducer end cover **700** in the second direction Y. Arrangement in the peripheral sides of the input shaft bearing hole **210** and the

middle shaft bearing hole **220** can further enable a contact area between the compressor mounting boss **11a** and the compressor to be large, so that the compressor is more securely mounted, and structural reliability is improved.

[0098] In an embodiment, the reducer end cover **700** further includes an oil filler plug **201** and an oil drain plug **202**. As shown in FIG. 2A, the oil filler plug **201** is located at an axis center of the middle shaft **240** of the reducer **200**, and the middle shaft **240** of the reducer **200** is a hollow shaft, to form an oil filler port of the powertrain **10** for delivery or maintenance. The oil drain plug **202** is located at a lowest point of the powertrain **10**, and the oil drain plug **202** communicate with an oil stirring tank **203**. The oil drain plug **202** may be used to drain oil in the powertrain **10**, and replace the oil stored in the powertrain **10**.

[0099] In an embodiment, the motor end cover **600** includes an annular fastening boss **12**, and the annular fastening boss **12** is configured to fasten a resolver cover plate **800**. As shown in FIG. 2B, the resolver cover plate **800**, the motor end cover **600**, and the annular fastening boss **12** are enclosed to form a motor wiring end accommodating cavity. In an embodiment, the motor wiring end accommodating cavity is configured to accommodate a resolver sensor of the motor **300**. In an embodiment, the motor wiring end accommodating cavity is configured to accommodate a three-phase copper bar of the motor **300**.

[0100] In an embodiment, the motor end cover **600** includes a plurality of compressor mounting bosses **11b**, and the compressor mounting bosses **11b** are configured to fasten the compressor. As shown in FIG. 2B, the plurality of compressor mounting bosses **11b** are distributed on a peripheral side of the annular fastening boss **12**. The compressor is mounted and fastened on an outer side of the resolver cover plate **800** in the second direction Y, and the plurality of compressor mounting bosses **11b** are distributed on the periphery side of the annular fastening boss **12**, so that the compressor is mounted more evenly, and the compressor is mounted more stably. This improves reliability of the structure.

[0101] In an embodiment, the resolver cover plate **800** is a damping cover plate, so that noise radiation can be effectively reduced, and NVH performance of the powertrain **10** can be improved.

[0102] As shown in FIG. 2B, in an embodiment, the integrated housing **500** includes a differential side suspension point **13**, the motor end cover **600** includes a motor end cover side suspension point **14**, and the reducer end cover **700** includes a reducer side suspension point **15** (as shown in FIG. 2A). The reducer **200** and the motor **300** are connected to a vehicle suspension and a bracket through the differential side suspension point **13**, the motor end cover side suspension point **14**, and the reducer side suspension point **15**. The suspension is connected to a secondary vehicle frame, so that the powertrain **10** is mounted on the secondary frame of the vehicle.

[0103] As shown in FIG. 2B, the integrated housing **500** further includes an oil pump mounting hole **16** and a filter mounting hole **17**. The oil pump mounting hole **16** is configured to mount an oil pump. The oil pump is configured to drive cooling oil to flow in the motor **300** and the reducer **200**. The filter mounting hole **17** is configured to mount a filter, and the filter is used to filter impurities in the cooling oil.

[0104] As shown in FIG. 2A, FIG. 2B, and FIG. 2C, the integrated housing **500** further includes a plurality of power supply apparatus fastening points **133**, and the plurality of power supply apparatus fastening points **133** are configured to fasten the integrated housing **500** to the housing of the power supply apparatus **100**.

[0105] In an embodiment, the motor **300** and the reducer **200** are of the integrated structure. As shown in FIG. 3, the housings of the motor **300** and the reducer **200** and a housing of the power supply apparatus **100** are of the split structure, and the housing of the power supply apparatus **100** is fastened above the housings of the motor **300** and the reducer **200**.

[0106] In an embodiment, the housing of the power supply apparatus **100** includes a liquid inlet **115** and a liquid outlet **116**. As shown in FIG. 3, the liquid inlet **115** is configured to communicate with the liquid outlet **116** through an internal flow channel of the power supply apparatus **100**. The

liquid inlet **115** is configured to receive a coolant, and the liquid outlet **116** is configured to output the coolant through an external cooling pipe **116a**. The external cooling pipe **116a** is arranged between the housing of the power supply apparatus **100** and the integrated housing **500** of the motor **300** and the reducer **200**. The external cooling pipe **116a** is configured to communicate the liquid outlet **116** of the housing of the power supply apparatus **100** with the heat exchanger **400**, in this way, so that the powertrain **10** is arranged more compactly

[0107] In an embodiment, the housing of the power supply apparatus **100** includes a motor winding connector **177**. As shown in FIG. 3, the motor winding connector **177** passes through the housing of the power supply apparatus **100**, the housing of the motor **300**, and the housing of the reducer **200**. The power supply apparatus **100** outputs a three-phase alternating current through the motor winding connector **177** to drive the motor **300**, so that the powertrain **10** is arranged more compactly

[0108] Refer to FIG. 2C and FIG. 3. Two bolts **132** are disposed in a middle region of a lower surface of a bottom plate **120** of the power supply apparatus **100** and a middle region of the housing of the motor **300**, to further fasten an integrated groove housing **110** to the housing of the motor **300**. This helps reduce vibration amplitudes of the integrated groove housing **110** and the housing of the motor **300**, improve a structural modality, reduce noise, and improve NVH performance of the powertrain **10**.

[0109] In this embodiment, the power supply apparatus **100** is configured to charge and discharge the battery **30** and drive the motor **300**. The power supply apparatus **100** is configured to receive a direct current transmitted by the battery **30**, convert the direct current into an alternating current, and transmit the alternating current to the motor **300**. In addition, the power supply apparatus **100** is further configured to charge the battery **30**. In an embodiment, the power supply apparatus **100** is configured to receive the alternating current and convert the alternating current into a direct current to charge the battery **30**. The alternating current includes a mains power supply or a civil alternating current. In an embodiment, the power supply apparatus **100** receives a high voltage direct current and provides the direct current for charging the battery **30**.

[0110] FIG. 4 is a diagram of a structure of a power supply apparatus **100** according to an embodiment. As shown in FIG. 4, in an embodiment, the power supply apparatus **100** includes a motor control unit **101**, an on-board charger **102**, a power distribution unit **103**, and a vehicle control unit **104**.

[0111] A full name of the motor control unit **101** is motor control unit, and an abbreviation is MCU. In an embodiment, the motor control unit **101** is configured to: receive a direct current of a power battery **30**, convert the direct current into an alternating current, and transmit the alternating current to a stator winding of a motor **300**, to drive the motor **300** to run.

[0112] A name of the on-board charger **102** is on-board charger, and an abbreviation is OBC. In an embodiment, the on-board charger **102** is configured to: convert an alternating current of a power grid into a direct current, or directly transmit the direct current to the power battery **30** for charging or supplying power to a load of the vehicle.

[0113] A name of the power distribution unit **103** is power distribution unit, and an abbreviation is PDU. In this embodiment, the power distribution unit **103** is also referred to as a high voltage power distribution box. In an embodiment, the power distribution unit **103** is responsible for power distribution and management in a high voltage system of the electric vehicle **1**, provides functions such as charging and discharging control, high voltage component power-on control, circuit overload and short-circuit protection, high voltage sampling, and low voltage control for the vehicle, and protects and monitors running of the high voltage system.

[0114] A name of the vehicle control unit **104** is vehicle control unit, and an abbreviation is VCU. In an embodiment, the vehicle control unit **104** is responsible for functions such as normal driving of the vehicle, braking energy feedback, fault diagnosis and processing of an energy pipeline of a vehicle drive system and the power battery **30** and a network pipeline, and vehicle status

monitoring.

[0115] In an embodiment, the housing of the power supply apparatus **100** includes the integrated groove housing **110** and a cover plate **130**. As shown in FIG. 4, the cover plate **130** and the integrated groove housing **110** are jointly enclosed to form an accommodating cavity **140**. The accommodating cavity **140** is configured to accommodate a plurality of electrical components of each of the motor control unit **101**, the on-board charger **102**, the power distribution unit **103**, and the vehicle control unit **104** in the power supply apparatus **100**.

[0116] In an embodiment, the integrated groove housing **110** is further configured to fasten a plurality of connectors. As shown in FIG. 4, the plurality of connectors includes a battery charge and discharge connector **171**, a direct current power supply connector **172**, a power supply connector **173**, an alternating current power supply connector **175**, a low voltage load connector **176**, a motor winding connector **177** (as shown in FIG. 3), and a communication connector **178** (as shown in FIG. 3). In an embodiment, the integrated groove housing **110** further includes the liquid inlet **115** and the liquid outlet **116** (as shown in FIG. 3). The liquid inlet **115** is configured to communicate with the liquid outlet **116** through the internal flow channel of the integrated groove housing **110**.

[0117] In an embodiment, the power supply apparatus **100** receives, through the battery charge and discharge connector **171**, the direct current transmitted by the battery **30**, converts the direct current into the alternating current, and transmits the alternating current to the stator winding of the motor **300** through the motor winding connector **177**, to drive the rotor and the motor shaft of the motor **300** to rotate. The motor shaft rotates to drive the input shaft **230** of the reducer **200** to rotate. The input shaft **230** of the reducer **200** transmits power to an internal gear of the reducer **200**. The output shaft **250** of the reducer **200** transmits power of the motor **300** to the wheels **40**.

[0118] In an embodiment, the power supply apparatus **100** is connected to a direct current power supply through the direct current power supply connector **172** to charge the battery **30**. The direct current power supply is configured to connect to the direct current power supply connector **172**. The direct current power supply charges the battery **30** sequentially through the direct current power supply connector **172** in the power supply apparatus **100**, the electrical component in the power distribution unit **103**, and the battery charge and discharge connector **171**. In an embodiment, the direct current power supply is a direct current charging pile.

[0119] In an embodiment, the power supply apparatus **100** is connected to an alternating current power supply through the alternating current power supply connector **175**, to charge the battery **30**. The alternating current power supply is configured to connect to the alternating current power supply connector **175**. The alternating current power supply charges the battery **30** sequentially through the alternating current power supply connector **175** in the power supply apparatus, the electrical component in the on-board charger **102**, and the battery charge and discharge connector **171**. In an embodiment, the alternating current power supply is an alternating current charging pile or an alternating current power grid.

[0120] In an embodiment, the power supply apparatus **100** is connected to the compressor through the power supply connector **173** to supply power to the compressor. The compressor receives, through the power supply connector **173**, the internal electrical component in the power supply apparatus **100**, and the battery charge and discharge connector **171**, a current provided by the battery **30**. The compressor is a component in an air conditioner system in the vehicle and cools or heats the vehicle.

[0121] In an embodiment, the power supply apparatus **100** is connected to a low voltage load through the low voltage load connector **176**, to supply power to the low voltage load. The low voltage load connector **176** connects the low voltage load to the power supply apparatus **100**. The low voltage load includes at least one of a low voltage battery, a vehicle lamp, a wiper, an air conditioner, a speaker, a USB interface, a dashboard, and a control display screen. In an embodiment, the low voltage battery may also supply power to another low voltage load. In an

embodiment, the battery **30** sequentially supplies power to the low voltage load through the battery charge and discharge connector **171**, the electrical component in the power supply apparatus **100**, and the low voltage load connector **176**.

[0122] In an embodiment, the communication connector **178** is connected to the vehicle control unit **104**, and the communication connector **17** is configured to receive and send a signal.

[0123] In this embodiment, the power supply apparatus **100** integrates the motor control unit **101**, the on-board charger **102**, the power distribution unit **103**, and the vehicle control unit **104**. The motor control unit **101**, the on-board charger **102**, the power distribution unit **103**, and the vehicle control unit **104** respectively communicate with a plurality of external functional apparatuses through a plurality of connectors fastened by the integrated groove housing **110**, to implement structural integration and functional integration of the power supply apparatus **100** and the powertrain **10**.

[0124] FIG. **5** is an exploded view of the power supply apparatus **100** according to an embodiment. FIG. **6** is a diagram of another structure of the power supply apparatus **100** according to an embodiment. FIG. **7** is another exploded view of the power supply apparatus **100** according to an embodiment. FIG. **8** is another exploded view of the power supply apparatus **100** to an embodiment.

[0125] As shown in FIG. **5**, the power supply apparatus **100** includes the integrated groove housing **110** and the cover plate **130**. The integrated groove housing **110** and the cover plate **130** are enclosed to form the accommodating cavity **140**. The accommodating cavity **140** is configured to accommodate a motor control unit **101**, an on-board charger **102**, a power distribution unit **103**, and a vehicle control unit **104**. Each includes an electrical component that implements a function of the electrical component.

[0126] In an embodiment, the cover plate **130** is a damping cover plate. This helps reduce an amplitude of the cover plate **130** in an operating process of the power supplying apparatus **100**, and helps improve a structural modality, reduce noise, and improve NVH performance of the power supplying apparatus **100**.

[0127] In an embodiment, the cover plate **130** is detachably connected to the integrated groove housing **110**. When an internal component in the power supply apparatus **100** needs to be repaired or replaced, a detachable connection relationship helps reduce operation difficulty and costs. In an embodiment, the detachable connection may be a screw connection.

[0128] As shown in FIG. **4** and FIG. **5**, there are two bolts **131** in the middle of the cover plate **130**, and the direct current power supply connector **172**, the two bolts **131**, and the low voltage load connector **176** are sequentially arranged in the second direction Y. The cover plate **130** has a large surface area, and the bolts **131** are disposed at a middle location of the cover plate **130**. This helps enhance mounting stability between the cover plate **130** and the integrated groove housing **110**, can further reduce a vibration amplitude of the cover plate **130**, and reduces noise generated by vibration of the cover plate **130** when the power supply apparatus **100** operates. This helps improve NVH performance of the vehicle.

[0129] In an embodiment, the power supply apparatus **100** includes the radiator **105**, the upper-layer circuit board **150**, and the lower-layer circuit board **160**. As shown in FIG. **5** and FIG. **6**, the accommodating cavity **140** is configured to accommodate the radiator **105**, the upper-layer circuit board **150**, and the lower-layer circuit board **160**.

[0130] In an embodiment, the integrated groove housing **110** includes a bottom plate **120** and a peripheral side wall **112**. As shown in FIG. **5** and FIG. **6**, the bottom plate **120** and the peripheral side wall **112** are enclosed to form an accommodating groove. The cover plate **130**, and the bottom plate **120** and the peripheral side wall **112** of the integrated groove housing **110** are enclosed to form the accommodating cavity **140**.

[0131] In an embodiment, the peripheral side wall **112** of the integrated groove housing **110** includes a liquid inlet **115**, and the bottom plate **120** of the integrated groove housing **110** includes

a liquid outlet **116**. Refer to FIG. 3, FIG. 4, and FIG. 5. The radiator **105** receives a coolant through the liquid inlet **115**, and outputs the coolant through the liquid outlet **116**.

[0132] In an embodiment, the bottom plate **120** of the integrated groove housing **110** includes an internal flow channel. The internal flow channel of the bottom plate **120** receives the coolant through the liquid inlet **115**, and outputs the coolant through the liquid outlet **116**. As shown in FIG. 5 and FIG. 6, the upper-layer circuit board **150** is sandwiched between the bottom plate **120** and the radiator **105**, and the internal flow channel of the bottom plate **120** and the radiator **105** dissipate, by using the coolant, heat for an electrical component carried on the upper-layer circuit board **150**, thereby improving heat dissipation efficiency, and improving cooling effect of the coolant on the power supply apparatus **100**.

[0133] In an embodiment, the bottom plate **120**, the lower-layer circuit board **160**, the upper-layer circuit board **150**, the radiator **105**, and the cover plate **130** are sequentially stacked in the third direction Z. Refer to FIG. 5, FIG. 6, and FIG. 7, the bottom plate **120**, the lower-layer circuit board **160**, the upper-layer circuit board **150**, the radiator **105**, and the cover plate **130** are sequentially stacked, so that lengths of the integrated groove housing **110** in the first direction X and the second direction Y are small. This facilitates miniaturization of the power supply apparatus **100**.

[0134] FIG. 9 is another exploded view of the power supply apparatus **100** according to an embodiment. FIG. 10 is a diagram of another structure of the power supply apparatus **100** according to an embodiment.

[0135] In an embodiment, a motor control unit **101** includes electrical components such as a bus capacitor **163**, a power module **164**, a Hall copper bar component **166**, and a three-phase copper bar component **177**. As shown in FIG. 9 and FIG. 10, the bus capacitor **163** is configured to smooth a bus voltage, so that the bus voltage of the motor control unit **101** is still smooth when a power switching transistor is turned on or off, can further reduce an inductance parameter of a line from a power switching transistor end of the motor control unit **101** to an end of the battery **30**, to weak a peak voltage of the bus, can further absorb a high pulse current at a bus end of the motor control unit **101**, and can further prevent overcharge of a voltage at the bus end and impact of an instantaneous voltage on the motor control unit **101**.

[0136] In an embodiment, the bus capacitor **163**, the power module **164**, the Hall copper bar component **166**, and the three-phase copper bar component **177** are sequentially arranged in the second direction Y. As shown in FIG. 10, the bus capacitor **163** is connected to the battery charge and discharge connector **171** through a copper bar. The three-phase copper bar component **177** passes through one mounting hole **111f** (as shown in FIG. 3), and the three-phase copper bar component **177** transmits an alternating current in the motor control unit **101** to the motor winding to drive the motor **300**. In an embodiment, the three-phase copper bar component **177** is the motor winding connector **177**. In this embodiment, the electrical components in the motor control unit **101** are arranged in the second direction Y, so that power flow is smoother, and a power loss is reduced.

[0137] In an embodiment, the three-phase copper bar component **177**, the power module **164**, and the bus capacitor **163** are pre-mounted as a whole module through laser welding or screw fastening, and then are mounted in the power supply apparatus **100**. This helps improve assembly and welding quality of the power supply apparatus **100**.

[0138] In an embodiment, an on-board charger **141** is configured to connect the battery charge and discharge connector **171**, the power supply connector **173**, and the alternating current power supply connector **175**. The on-board charger **102** includes the on-board charger **141** and a direct current converter **142**. As shown in FIG. 9 and FIG. 10, the on-board charger **141** includes a power switching transistor **141a**, an inductor **141b**, and a capacitor **141c**. The direct current converter **142** includes a power switching transistor **142a** and a magnetic component. In this embodiment, the magnetic component includes at least one of a capacitor and an inductor.

[0139] In an embodiment, the power distribution unit **103** includes a plurality of copper bars. As

shown in FIG. 10, the power distribution unit **103** is configured to connect the direct current power supply connector **172** and the battery charge and discharge connector **171**.

[0140] In an embodiment, the vehicle control unit **104** includes a plurality of chips **144**. The vehicle control unit **104** is configured to connect to the communication connector **178**. FIG. 9 shows a location of the chip **144**.

[0141] In this embodiment, the power supply apparatus **100** carries electrical components in the motor control unit **101**, the on-board charger **141**, the direct current converter **142**, the power distribution unit **103**, and the vehicle control unit **104** by using the upper-layer circuit board **150** and the lower-layer circuit board **160** that are stacked. In this way, functional circuits in the power supply apparatus **100** are deeply integrated and achieve higher integration.

[0142] FIG. 11 is a diagram of a structure of the integrated groove housing **110** according to an embodiment. FIG. 12 is a diagram of another structure of the integrated groove housing **110** according to an embodiment.

[0143] In an embodiment, the integrated groove housing **110** includes a plurality of mounting holes **111**, and the plurality of mounting holes **111** are configured to fasten connectors. As shown in FIG. 11 and FIG. 12, the integrated groove housing **110** includes the plurality of mounting holes **111**. This helps mount a plurality of electrical components in the integrated groove housing **110** and helps electrically connect an external electrical component to the power supply apparatus **100**, thereby improving integration of the power supply apparatus **100**.

[0144] In an embodiment, the integrated groove housing **110** includes the bottom plate **120** and the peripheral side wall **112**, and the bottom plate **120** and the peripheral side wall **112** are enclosed to form an accommodating groove.

[0145] As shown in FIG. 11, the peripheral side wall **112** of the integrated groove housing **110** includes a first side wall **112a**, a second side wall **112b**, a third side wall **112c**, and a fourth side wall **112d**. The first side wall **112a** and the second side wall **112b** are arranged opposite to each other in the first direction X. The third side wall **112c** and the fourth side wall **112d** are arranged opposite to each other in the second direction Y. The first side wall **112a**, the third side wall **112c**, the second side wall **112b**, and the fourth side wall **112d** are sequentially connected and enclosed to form the peripheral side wall **112** of the integrated groove housing **110**. Three mounting holes **111a**, **111b**, and **111c** penetrate the third side wall **112c** in the second direction Y. Two mounting holes **111e** and **111d** penetrate the fourth side wall **112d** in the second direction Y. The liquid inlet **115** is located on the second side wall **112b**.

[0146] In an embodiment, the mounting holes **111a**, **111b**, and **111c** are respectively used to fasten connectors **171**, **172**, and **173**. As shown in FIG. 10 and FIG. 11, mounting holes **111d** and **111e** are respectively used to fasten connectors **175** and **176**. Two bottom plate mounting holes **111f** and **111g** are respectively used to fasten a connector **177** and a connector **178**.

[0147] In this embodiment, the three mounting holes **111a**, **111b**, and **111c** respectively include a battery charge and discharge connector mounting hole **111a**, a direct current power supply connector mounting hole **111b**, and a power supply connector mounting hole **111c**. The battery charge and discharge connector mounting hole **111a**, the direct current power supply connector mounting hole **111b**, and the power supply connector mounting hole **111c** are respectively configured to fasten the connectors **171**, **172**, and **173** that are of the power supply apparatus **100** and that are configured to connect the battery **30**, the direct current power supply, and the compressor.

[0148] In this embodiment, the two mounting holes **111d** and **111e** are respectively an alternating current power supply connector mounting hole **111d** and a low voltage load connector mounting hole **111e**. The alternating current power supply connector mounting hole **111d** is configured to fasten the connector **175** that is of the power supply apparatus **100** and that is configured to connect to an alternating current power supply. The low voltage load connector mounting hole **111e** is configured to fasten the connector **176** that is of the power supply apparatus **100** and that is

configured to connect to a low voltage load. The connector **175** of the alternating current power supply is configured to connect to the alternating current power supply.

[0149] In this embodiment, the two bottom plate mounting holes **111g** and **111f** are respectively a communication connector mounting hole **111g** and a three-phase connector mounting hole **111f**. The three-phase connector mounting hole **111f** is configured to fasten the connector **177** that is of the power supply apparatus **100** and that is configured to connect to a motor winding. After converting a direct current in the battery **30** into an alternating current, the power supply apparatus **100** outputs the alternating current to the motor winding through the connector **177** connected to the motor winding, to drive the motor **300** to run. The communication connector mounting hole **111g** is configured to fasten the vehicle control unit **104** in the power supply apparatus **100** and is configured to connect to the communication connector **178** of a vehicle-mounted load. The vehicle control unit **104** is configured to send a control signal to the power supply apparatus **100**, to optimize energy distribution of the vehicle and running of the vehicle.

[0150] In this embodiment, through a layout of the plurality of mounting holes **111**, power flow is smoother, and a power loss is reduced, so that the connectors are electrically isolated from each other, crosstalk is avoided, and safety performance is improved. Through the layout of the plurality of mounting holes **111**, a volume of the power supply apparatus **100** is small, and miniaturization of the powertrain **10** is facilitated.

[0151] As shown in FIG. **9**, in an embodiment, the power supply connector mounting hole **111c** is further configured to fasten the connector **174** that is of the power supply apparatus **100** and that is configured to connect to a heater.

[0152] In this embodiment, the connector **174** of the heater is configured to connect to the heater (not shown in the figure). The heater is configured to heat the vehicle, and the heater is configured to heat a seat, including heating a front seat, a rear seat, or a middle seat. In some embodiments, when the electric vehicle **1** is a caravan, the heater may also heat a seat and a lying position in the caravan. In addition, after increasing a temperature of the vehicle, the heater may further perform defrosting and defogging.

[0153] In an embodiment, a housing of the connector **173** connected to the compressor and a housing of the connector **174** connected to the heater are integrated into an integrated structure. The connector **173** of the compressor and the connector **174** of the heater share one housing, so that integration of the power supply apparatus **100** is improved, and deep fusion of the power supply apparatus **100** and the powertrain **10** is facilitated. In addition, sharing one housing further helps reduce circuit arrangement in the power supply apparatus **100**, saves materials, and reduces production costs.

[0154] In an embodiment, the bottom plate **120** of the integrated groove housing **110** further has a plurality of accommodating grooves. As shown in FIG. **12**, the plurality of accommodating grooves is configured to accommodate a plurality of electrical components in the power supply apparatus **100**.

[0155] In an embodiment, the plurality of accommodating grooves includes a power distribution groove **121**, a bus capacitor groove **122**, a transformer groove **123**, an inductor groove **124**, and a direct current filter groove **125**. As shown in FIG. **12**, the power distribution groove **121** is configured to accommodate a copper bar of the power distribution unit **103**. The bus capacitor groove **122** is configured to accommodate a bus capacitor **163** of the motor control unit **101**. The transformer groove **123** is configured to accommodate a transformer **141d** of the on-board charger **141**. The inductor groove **124** is configured to accommodate a plurality of inductors **141b** in the on-board charger **141**. The direct current filter groove **125** is configured to accommodate a magnetic component in a direct current filter **146**.

[0156] In this embodiment, the plurality of accommodating grooves are formed on the bottom plate **120**, so that the electrical components in the power supply apparatus **100** are arranged more regularly. This helps reduce internal space of the power supply apparatus **100** and helps reduce a

volume of the power supply apparatus **100**.

[0157] In an embodiment, the integrated groove housing **110** includes a plurality of shielding walls **113a**, **113b**, **113c**, **113d**, **113e** and **113f**. As shown in FIG. **11**, a plurality of mounting regions is formed between the peripheral side wall **112** and the shielding wall or between the plurality of shielding walls, and the plurality of mounting regions are used to fasten and mount electrical components in the motor control unit **101**, the on-board charger **141**, the direct current converter **142**, the vehicle control unit **104**, and the power distribution unit **103**.

[0158] The integrated groove housing **110** of the all-in-one power supply apparatus **100** provided in this embodiment includes the plurality of mounting holes **111**. With reference to FIG. **11** and FIG. **12**, the three mounting holes **111a**, **111b**, and **111c** are respectively used to fasten the connectors **171**, **172**, and **173** that are of the power supply apparatus **100** and that are configured to connect the battery **30**, the direct current power supply (not shown in the figure), and the compressor (not shown in the figure).

[0159] As shown in FIG. **11** and FIG. **12**, the three mounting holes **111a**, **111b**, and **111c** penetrate the peripheral side wall **112** of the integrated groove housing **110** in the second direction Y. The three mounting holes **111a**, **111b**, and **111c** are arranged on a same side of the integrated groove housing **110**, and the three mounting holes **111a**, **111b**, and **111c** are spaced in the first direction X. In this embodiment, the power supply apparatus **100** integrates a function of charging and discharging the battery, a function of driving the motor, and a function of supplying power to the compressor. In addition, the connectors **171**, **172**, and **173** configured to connect the battery, the direct current power supply, and the compressor are fastened to the mounting hole **111** of the integrated groove housing **110** of the power supply apparatus **100**, so that the power supply apparatus **100** has higher integration.

[0160] In an embodiment, the three mounting holes **111a**, **111b**, and **111c** penetrate the peripheral side wall **112** of the integrated groove housing **110** in the second direction Y. In this way, when the connectors **171**, **172**, and **173** that connect the battery **30**, the direct current power supply, and the compressor are connected to the electrical components in the power supply apparatus **100**, no excessive cables are required. Connection lines between the power supply apparatus **100** and the battery **30**, the direct current power supply, and the compressor are simplified, so that wiring of the electric vehicle is simpler.

[0161] In an embodiment, the three mounting holes **111a**, **111b**, and **111c** penetrate the peripheral side wall **112** of the integrated groove housing **110** in the second direction Y, so that the connectors **171**, **172**, and **173** that connect the battery **30**, the direct current power supply, and the compressor are arranged in the power supply apparatus **100** in the second direction Y. Space occupied by the power supply apparatus **100** in the first direction X and the third direction Z is reduced. This facilitates miniaturized arrangement and deep fusion of the power supply apparatus **100** and facilitates miniaturized arrangement of the powertrain **10**.

[0162] In an embodiment, the three mounting holes **111a**, **111b**, and **111c** are arranged on the same side of the integrated groove housing **110**, so that the battery **30**, the direct current power supply, and the connectors **171**, **172**, and **173** of the compressor can be integrated on the same side of the integrated groove housing **110** of the power supply apparatus **100**. In this way, the power supply apparatus **100** has higher integration, and space occupied by the power supply apparatus **100** in the first direction X is reduced. Therefore, another connector or an electrical component may be mounted on another side surface of the integrated groove housing **110**. This facilitates miniaturized arrangement and more diversified arrangement of the power supply apparatus **100** and the powertrain **10**. The three mounting holes **111a**, **111b**, and **111c** are spaced in the first direction X. This helps provide more space when the battery **30**, the direct current power supply, and the connectors **171**, **172**, and **173** of the compressor are connected to the battery **30**, the direct current power supply, and the compressor, and a layout is more appropriate.

[0163] In an embodiment, the three mounting holes **111a**, **111b**, and **111c** are respectively the

battery charge and discharge connector mounting hole **111a**, the direct current power supply connector mounting hole **111b**, and the power supply connector mounting hole **111c**. As shown in FIG. **11**, the power supply connector mounting hole **111c**, the direct current power supply connector mounting hole **111b**, and the battery charge and discharge connector mounting hole **111a** are sequentially spaced in the first direction X.

[0164] In this embodiment, the battery charge and discharge connector mounting hole **111a** is configured to mount the connector **171** for arranging the battery **30**. The battery **30** receives charging from the external power supply through the connector **171** of the battery **30** of the power supply apparatus **100**. Alternatively, electric energy stored in the battery **30** may be released to the power supply apparatus **100** through the connector **171** of the battery **30**, to provide a current for the electrical component in the power supply apparatus **100** to operate. The direct current power supply connector mounting hole **111b** is configured to mount the direct current power supply connector **172**. The direct current power supply connector **172** is connected to an external direct current power supply, to implement fast charging of the battery **30**. In an embodiment, the direct current power supply is a direct current charging pile. The power supply connector mounting hole **111c** is configured to mount a connector **173** for arranging a compressor. The compressor receives a current provided by the power supply apparatus **100**. The compressor is a component in an air conditioner system in the vehicle and cools or heats the vehicle.

[0165] In this embodiment, the power supply connector mounting hole **111c**, the direct current power supply connector mounting hole **111b**, and the battery charge and discharge connector mounting hole **111a** are arranged on the same side of the integrated groove housing **110**. This helps improve integration of the integrated groove housing **110**. The power supply connector mounting hole **111c**, the direct current power supply connector mounting hole **111b**, and the battery charge and discharge connector mounting hole **111a** are sequentially spaced in the first direction X.

Therefore, the connector **173** of the compressor, the connector **172** of the direct current power supply, and the connector **171** of the battery **30** are sequentially spaced in the first direction X. This helps arrange connection cables between the connectors **171**, **172**, and **173**, the power battery **30**, the direct current power supply, and the compressor be on a same side of the power supply apparatus **100**, so that the connection cables are more regular, and a layout is more appropriate.

[0166] In this embodiment, in the first direction X, the direct current power supply connector mounting hole **111b** is closer to the battery charge and discharge connector mounting hole **111a** than the power supply connector mounting hole **111c**. This helps the direct current power supply charge the battery **30** in a shorter path, helps save materials, and reduces production costs.

[0167] As shown in FIG. **11**, in the first direction X, a spacing between the power supply connector mounting hole **111c** and the direct current power supply connector mounting hole **111b** is less than a spacing between the direct current power supply connector mounting hole **111b** and the battery charge and discharge connector mounting hole **111a**.

[0168] In this embodiment, in the first direction X, a spacing between the power supply connector mounting hole **111c** and the direct current power supply connector mounting hole **111b** is denoted as L1, in the first direction X, a spacing between the direct current power supply connector mounting hole **111b** and the battery charge and discharge connector mounting hole **111a** is denoted as L2, and L1 is small. This helps a layout between the connector **173** of the compressor and the connector **172** of the direct current power supply be more compact, helps reduce space occupation in the first direction X, and helps improve integration of the power supply apparatus **100**.

[0169] In this embodiment, L2 is large. This facilitates arrangement of the connector **172** of the direct current power supply and the connector **171** of the battery **30** on the integrated groove housing **110**, and also helps provide sufficient space for arrangement of the copper bar in the power supply apparatus **100** required by the direct current power supply to charge the battery **30**. A general direct current power supply transmits a high voltage direct current to the battery **30**. The direct current power supply is electrically connected to the battery **30** through a wide copper bar.

The copper bar is configured to transmit the high voltage direct current, and L2 is large. In this way, a distance between the connector **172** of the direct current power supply and the connector **171** of the battery **30** is large. In this way, there is sufficient space inside the integrated groove housing **110** for mounting a plurality of copper bars between the connector **172** of the direct current power supply and the connector **171** of the battery **30**, and electrical insulation between the plurality of copper bars can be ensured.

[0170] In an embodiment, two mounting holes **111d** and **111e** of the plurality of mounting holes **111** are respectively configured to fasten the connectors **175** and **176** that are of the power supply apparatus **100** and that are configured to connect the alternating current power supply and the low voltage load. As shown in FIG. **10** and FIG. **11**, the two mounting holes **111d** and **111e** penetrate the peripheral side wall **112** of the integrated groove housing **110** in the second direction Y. The two mounting holes **111e** and **111d** are arranged opposite to the three mounting holes **111a**, **111b**, and **111c** in the second direction Y.

[0171] In this embodiment, the two mounting holes **111d** and **111e** penetrate the peripheral side wall **112** of the integrated groove housing **110** in the second direction Y, so that the connectors **175** and **176** that connect the alternating current power supply and the low voltage load do not need to be connected to the electrical component in the power supply apparatus **100** through excessive cables. In this embodiment, the two mounting holes **111e** and **111d** penetrate the peripheral side wall **112** of the integrated groove housing **110** in the second direction Y, so that the connectors **175** and **176** of the alternating current power supply and the low voltage load are disposed in the power supply apparatus **100** in the second direction Y. In this case, space occupied by the power supply apparatus **100** in the first direction X and the third direction Z is reduced, to facilitate miniaturized arrangement of the powertrain **10**.

[0172] In this embodiment, the two mounting holes **111d** and **111e** are respectively the alternating current power supply connector mounting hole **111d** and the low voltage load connector mounting hole **111e**, and the two mounting holes **111d** and **111e** are arranged opposite to the three mounting holes **111a**, **111b**, and **111c** in the second direction Y. In other words, the alternating current power supply connector mounting hole **111d** and the low voltage load connector mounting hole **111e** are arranged opposite to the battery charge and discharge connector mounting hole **111a**, the direct current power supply connector mounting hole **111b**, and the power supply connector mounting hole **111c** in the second direction Y. This helps the plurality of mounting holes **111** of the power supply apparatus **100** be arranged in a regular manner, and a layout is appropriate. In addition, this further facilitates an overall arrangement layout of the plurality of mounting holes **111**, reduces space occupied by the power supply apparatus **100** in the first direction X, improves integration of the power supply apparatus **100**, and facilitates a miniaturized layout of the power supply apparatus **100**.

[0173] In this embodiment, the alternating current power supply connector mounting hole **111d** and the direct current power supply connector mounting hole **111b** are arranged opposite to each other in the second direction Y, so that the alternating current power supply and the direct current power supply supply power to the power supply apparatus **100** from different sides of the power supply apparatus **100**. The alternating current power supply and the direct current power supply are electrically isolated, to avoid mutual electrical impact.

[0174] In an embodiment, a spacing between the two mounting holes **111e** and **111d** in the first direction X is less than half of a length of the integrated groove housing **110**. As shown in FIG. **11**, a spacing between two mounting holes **111a** and **111c** that are farthest from each other in the three mounting holes **111a**, **111b**, and **111c** in the first direction X is greater than the half of the length of the integrated groove housing **110**.

[0175] As shown in FIG. **10** and FIG. **11**, the spacing between the two mounting holes **111e** and **111d** in the first direction X is denoted as L3, that is, a spacing between the alternating current power supply connector mounting hole **111d** and the low voltage load connector mounting hole

111e in the first direction X is **L3**. The length of the integrated groove housing **110** in the first direction X is denoted as **L4**, and $L3 < 0.5L4$. Therefore, the alternating current power supply connector mounting hole **111d** and the low voltage load connector mounting hole **111e** are arranged more compactly. More arrangement space is provided for the motor control unit **101** and the vehicle control unit **104** that are of the power supply apparatus **100** and that are close to the alternating current power supply connector mounting hole **111d** and the low voltage load connector mounting hole **111e** in the first direction X.

[0176] As shown in FIG. **11**, a spacing between two mounting holes **111a** and **111c** that are farthest from each other in the three mounting holes **111a**, **111b**, and **111c** in the first direction X is denoted as **L5**. A length of the integrated groove housing **110** in the first direction X is denoted as **L6**. In the three mounting holes **111a**, **111b**, and **111c** in the first direction X, two mounting holes **111a** and **111c** that are farthest from each other are the power supply connector mounting hole **111c** and the battery charge and discharge connector mounting hole **111a**, and $L5 < 0.5L6$. Therefore, more space is provided for arranging the connector **173** of the compressor and the connector **171** of the battery **30**, so that space of the integrated groove housing **110** of the power supply apparatus **100** is fully utilized, and the three mounting holes **111a**, **111b**, and **111c** of the power supply apparatus **100** are arranged more properly. In addition, the direct current power supply connector mounting hole **111b** can be disposed between the power supply connector mounting hole **111c** and the battery charge and discharge connector mounting hole **111a**.

[0177] As shown in FIG. **10** and FIG. **11**, one mounting hole **111** (**111d**) of the connector **175** for fastening and connecting to the alternating current power supply and one mounting hole **111** (**111c**) of the connector **173** for fastening and connecting to the compressor are arranged opposite to each other in the second direction Y. One mounting hole **111** (**111e**) of the connector **176** for fastening and connecting to the low voltage load and one mounting hole **111** (**111b**) of the connector **172** for fastening and connecting to the direct current power supply are arranged opposite to each other in the second direction Y.

[0178] In this embodiment, the one mounting hole **111** of the connector **175** for fastening and connecting to the alternating current power supply is the alternating current power supply connector mounting hole **111d**, and the one mounting hole **111** of the connector **173** for fastening and connecting to the compressor is the power supply connector mounting hole **111c**. The alternating current power supply connector mounting hole **111d** and the power supply connector mounting hole **111c** are arranged opposite to each other in the second direction Y. This facilitates regular arrangement of the plurality of mounting holes **111** on the power supply apparatus **100**.

[0179] In this embodiment, the one mounting hole **111** of the connector **176** for fastening and connecting the low voltage load is the low voltage load connector mounting hole **111e**, and the one mounting hole **111** of the connector **172** for fastening and connecting to the direct current power supply is the direct current power supply connector mounting hole **111b**. The low voltage load connector mounting hole **111e** and the direct current power supply connector mounting hole **111b** are arranged opposite to each other in the second direction Y. This facilitates regular arrangement of the plurality of mounting holes **111** on the power supply apparatus **100**.

[0180] In this embodiment, the alternating current power supply connector mounting hole **111d** and the power supply connector mounting hole **111c** are arranged opposite to each other in the second direction Y. The low voltage load connector mounting hole **111e** and the direct current power supply connector mounting hole **111b** are arranged opposite to each other in the second direction Y. This helps a more compact layout of the mounting holes **111** on the integrated groove housing **110**. The alternating current power supply connector mounting hole **111d**, the power supply connector mounting hole **111c**, the low voltage load connector mounting hole **111e**, and the direct current power supply connector mounting hole **111b** are centrally arranged on one side of the integrated groove housing **110** of the power supply apparatus **100**. This helps provide sufficient space for an electrical component layout of the battery charge and discharge connector mounting hole **111a**, the

motor control unit **101**, and the vehicle control unit **104**, and can avoid electrical interference.

[0181] In an embodiment, two bottom plate mounting holes **111f** and **111g** in the plurality of mounting holes **111** are respectively configured to fasten the connector **177** that is of the power supply apparatus **100** and that is configured to connect to the motor winding and the communication connector **178** that is of the vehicle control unit **104** in the power supply apparatus **100** and that is configured to connect to the vehicle-mounted load. As shown in FIG. **10** and FIG. **11**, the two bottom plate mounting holes **111g** and **111f** penetrate the bottom plate **120** of the integrated groove housing **110** in the third direction Z. In this embodiment, the two bottom plate mounting holes **111f** and **111g** are respectively the three-phase connector mounting hole **111f** and the communication connector mounting hole **111g**, and the three-phase connector mounting hole **111f** penetrates the bottom plate **120** of the integrated groove housing **110** in the third direction Z. This helps the connector **177** connected to the motor winding to be connected to the motor winding through a shorter line and helps the power supply apparatus **100** output an alternating current to the motor winding through a shorter path with less power consumption, to drive the rotor and the motor shaft of the motor **300** to rotate. The three-phase connector mounting hole **111f** penetrates the bottom plate **120** of the integrated groove housing **110** in the third direction Z, so that space below the power supply apparatus **100** in the third direction Z can be fully used. This facilitates a miniaturized layout of the power supply apparatus **100**, implements a miniaturized layout of the powertrain **10**, and optimizes a vehicle layout. The communication connector mounting hole **111g** penetrates the bottom plate **120** of the integrated groove housing **110** in the third direction Z, so that a first shielding cover **114a** on the vehicle control unit **104** and the communication connector mounting hole **111g** are arranged in a stacked manner in the third direction Z. This further helps the power supply apparatus **100** connect to the communication device in the powertrain **10** in the third direction Z, and does not additionally occupy space of the powertrain **10** in the first direction X and the second direction Y. This facilitates a miniaturized layout of the powertrain **10**.

[0182] As shown in FIG. **10** and FIG. **11**, in an embodiment, in the first direction X, one mounting hole **111a** that is in the three mounting holes **111a**, **111b**, and **111c** and that is used to fasten the connector **171** connected to the battery **30** is arranged between the two bottom plate mounting holes **111g** and **111f**.

[0183] In this embodiment, one mounting hole **111a** that is in the three mounting holes **111a**, **111b**, and **111c** and that is configured to fasten the connector **171** connected to the battery **30** is the battery charge and discharge connector mounting hole **111a**. In the first direction X, the battery charge and discharge connector mounting hole **111a** is arranged between the three-phase connector mounting hole **111f** and the communication connector mounting hole **111g**. This helps the bus capacitor **163** and the power module **164** in the motor control unit **101** of the power supply apparatus **100** output a current in the battery **30** to the motor winding smoothly. A layout of the communication connector mounting hole **111g** close to the peripheral side wall **112** of the integrated groove housing **110** facilitates arrangement of the power module **164** and the bus capacitor **163** in the motor control unit **101**, and further facilitates connection between the vehicle control unit **104** and the communication device by using a shorter line. This helps save materials and reduces production costs.

[0184] As shown in FIG. **10** and FIG. **12**, in the second direction Y, a spacing between a bottom plate mounting hole **111g** for fastening the vehicle control unit **104** (as shown in FIG. **4**) in the power supply apparatus **100** and for connecting the communication connector **178** to the vehicle-mounted load and any one of the three mounting holes **111a**, **111b**, and **111c** is less than a spacing between a bottom plate mounting hole **111f** for fastening the power supply apparatus **100** and for connecting the connector **177** of the motor winding and any one of the three mounting holes **111a**, **111b**, and **111c**.

[0185] As shown in FIG. **12**, in the second direction Y, a spacing between the communication connector mounting hole **111g** and any one of the three mounting holes **111a**, **111b**, and **111c** is L7,

in the second direction Y, a spacing between the three-phase connector mounting hole **111f** and any one of the three mounting holes **111a**, **111b**, and **111c** is **L8**, and $L7 < L8$. **L8** is large, so that sufficient space is provided for arranging the circuit board in the power supply apparatus **100**. **L7** is small, so that the communication connector **178** is close to the peripheral side wall **112** of the integrated groove housing **110**. In this way, there is a sufficient region in the middle of the bottom plate **120** for fastening the electrical component in the power supply apparatus **100**. In this embodiment, **L7** is small, so that the communication connector **178** is close to the peripheral side wall **112** of the integrated groove housing **110**, and the communication connector **178** is isolated from another electrical component in the power supply apparatus **100**. This avoids electric wire interference from another electrical component to the communication connector **178**.

[0186] In an embodiment, the integrated groove housing **110** further includes the liquid inlet **115** and the liquid outlet **116**. As shown in FIG. 12, the liquid inlet **115** and the liquid outlet **116** are communicated through an internal flow channel of the integrated groove housing **110**. The liquid inlet **115** is located on the peripheral side wall **112** of the integrated groove housing **110**, and the liquid outlet **116** is located on the bottom plate **120** of the integrated groove housing **110**. An opening of the liquid inlet **115** faces an inner cavity that is in the first direction X and that faces away from the integrated groove housing **110**. An opening of the liquid outlet **116** faces away from the inner cavity of the integrated groove housing **110** in the third direction Z. A spacing between the liquid inlet **115** and the liquid outlet **116** in the first direction X is greater than a spacing between two mounting holes **111a** and **111c** that are farthest from each other in the three mounting holes **111a**, **111b**, and **111c**.

[0187] In this embodiment, the integrated groove housing **110** further includes the liquid inlet **115** and the liquid outlet **116**, to facilitate coolant flowing in the power supply apparatus **100**. The liquid inlet **115** is configured to input the coolant from a vehicle cooling system, the liquid outlet **116** is configured to output the coolant obtained after the power supply apparatus **100** is cooled and heated, and the coolant sequentially flows through the liquid inlet **115**, the internal flow channel of the integrated groove housing **110**, and the liquid outlet **116**. The liquid inlet **115** is located on the peripheral side wall **112** (**112b**) of the integrated groove housing **110**, to facilitate arrangement of an external cooling pipe connected to the liquid inlet **115**. The liquid outlet **116** is located on the bottom plate **120** of the integrated groove housing **110**. This helps the heated coolant flow out of the power supply apparatus **100** in a gravity direction and helps reduce a power loss.

[0188] In this embodiment, the opening of the liquid inlet **115** faces away from the inner cavity of the integrated groove housing **110** in the first direction X, so that the liquid inlet **115** is connected to the external cooling pipe, and the coolant is input to the power supply apparatus **100** to cool the power supply apparatus **100**. The opening of the liquid outlet **116** faces away from the inner cavity of the groove housing in the third direction Z, so that the coolant flows out of the power supply apparatus **100** from the liquid outlet **116** in the third direction Z by gravity. This also helps arrange the external cooling pipe **116a** (as shown in FIG. 3) connected to the liquid outlet **116** in space downwards in the third direction Z of the powertrain **10** and helps reduce space occupied in the third direction Z and the second direction Y of the powertrain **10**.

[0189] As shown in FIG. 12, a spacing between the liquid inlet **115** and the liquid outlet **116** in the first direction X is denoted as **L9**, and a spacing between two mounting holes **111a** and **111c** that are farthest from each other in the three mounting holes **111a**, **111b**, and **111c** in the first direction X is denoted as **L10**. In other words, a spacing between the power supply connector mounting hole **111c** and the battery charge and discharge connector mounting hole **111a** in the first direction X is **L10**. In this embodiment, $L9 > L10$. This helps the coolant flow in the power supply apparatus **100** with a long path and long flow time, helps the coolant better cool the power supply apparatus **100**, and improves cooling efficiency.

[0190] In an embodiment, the reducer end cover **700** is arranged on a same side as the three mounting holes **111a**, **111b**, and **111c**. Refer to FIG. 4 and FIG. 11. The motor end cover **600** is

arranged on a same side as the two mounting holes **111e** and **111d** in the plurality of mounting holes **111**.

[0191] In this embodiment, the connector **177** that is in the general three-phase connector mounting hole **111f** and that is configured to connect to the motor winding is connected to the motor winding connector led out from the motor end cover **600**. In this embodiment, the motor end cover **600** is arranged on the same side as the two mounting holes **111e** and **111d** in the plurality of mounting holes **111**, so that the connector **177** of the three-phase connector mounting hole **111f** can be connected to the motor winding in the motor end cover **600** through a short path. The reducer end cover **700** is arranged on a same side as the three mounting holes **111a**, **111b**, and **111c**, so that wiring is generally not performed on an outer side of the reducer end cover **700**. The three mounting holes **111a**, **111b**, and **111c** are arranged on a same side as the reducer end cover **700**. In this way, the connector in the three mounting holes **111a**, **111b**, and **111c** leads out from one side of the reducer end cover **700**. Therefore, space on an outer side of the reducer end cover **700** is fully used, but space of the powertrain **10** in the first direction X is not excessively occupied. This further facilitates arrangement and normalization of the powertrain **10**.

[0192] In an embodiment, the lower-layer circuit board **160** of the power supply apparatus **100** includes a primary region **161** and a secondary region **162**, and the primary region **161** and the secondary region **162** are adjacently arranged in the first direction X. As shown in FIG. 7, FIG. 8, FIG. 9, and FIG. 10, the integrated groove housing **110** includes the bottom plate **120**. The bottom plate **120**, the secondary region **162** of the lower-layer circuit board **160**, and the upper-layer circuit board **150** are sequentially stacked in the third direction Z. The primary region **161** and the upper-layer circuit board **150** are spaced in the third direction Z. The primary region **161** is configured to carry the bus capacitor **163** and the power module **164** of the motor control unit **101** and the plurality of chips **144** of the vehicle control unit **104**. The secondary region **162** is configured to carry at least a part of power switching transistors **142a** of the direct current converter **142**. The upper-layer circuit board **150** is configured to carry the plurality of power switching transistors **141a**, the plurality of inductors **141b**, and the plurality of capacitors **141c** in the on-board charger **141**.

[0193] In this embodiment, both the upper-layer circuit board **150** and the lower-layer circuit board **160** are fastened to the integrated groove housing **110**, and are supported by the integrated groove housing **110**, so that the upper-layer circuit board **150** and the lower-layer circuit board **160** are fastened to the integrated groove housing **110** with high stability. Overall structural strength of the power supply apparatus **100** is stronger, and electrical connection is stable. When an external environment exerts external force on the power supply apparatus **100**, the upper-layer circuit board **150**, the lower-layer circuit board **160**, and the integrated groove housing **110** are not easily displaced relative to each other. This helps the power supply apparatus **100** operate in a stable state.

[0194] In this embodiment, the lower-layer circuit board **160** includes the primary region **161** and the secondary region **162**, and the primary region **161** and the secondary region **162** are adjacently arranged in the first direction X, so that the circuit components of the lower-layer circuit board **160** are arranged in the first direction X.

[0195] In this embodiment, the bottom plate **120**, the secondary region **162** of the lower-layer circuit board **160**, and the upper-layer circuit board **150** are sequentially stacked in the third direction Z, so that the electronic components of the power supply apparatus **100** can be stacked in the third direction Z, and space occupied by the power supply apparatus **100** in the first direction X and the second direction Y can be reduced. The primary region **161** and the upper-layer circuit board **150** are spaced in the third direction Z, so that space that is in the first direction X and that is occupied when the upper-layer circuit board **150** and the lower-layer circuit board **160** are tiled can be reduced. A plurality of circuits such as the motor control unit **101**, the vehicle control unit **104**, the direct current converter **142**, and the on-board charger **141** are integrated and arranged in smaller space, to facilitate a miniaturized layout of the power supply apparatus **100**.

[0196] As shown in FIG. 9, the upper-layer circuit board **150** is configured to carry the plurality of power switching transistors **141a**, the plurality of inductors **141b**, and the plurality of capacitors **141c** in the on-board charger **141**, so that the on-board charger **141** is integrated into the upper-layer circuit board **150**. The on-board charger **141** may convert an alternating current input by an external power supply into a direct current for charging the battery **30**.

[0197] It should be noted that, to show a structure relationship more clearly, in FIG. 9 and FIG. 10, a lower surface of the lower-layer circuit board **160** is separated from an electrical component (for example, the bus capacitor **163** and the power module **164**) carried on the lower-layer circuit board **160**. After assembly, the electrical component on the lower surface of the lower-layer circuit board **160** is electrically connected to the lower-layer circuit board **160**. In an embodiment, the bus capacitor **163** is plug-connected to the lower surface of the primary region **161**. It should be understood that a lower surface of the upper-layer circuit board **150** is separated from an electrical component carried on the upper-layer circuit board **150**. After assembly, the electrical component on the lower surface of the upper-layer circuit board **150** is electrically connected to the upper-layer circuit board **150**.

[0198] In an embodiment, the integrated groove housing **110** further includes the first side wall **112a**, the second side wall **112b**, and a first shielding wall **113a**. As shown in FIG. 10 and FIG. 11, an upper surface of the bottom plate **120** in the third direction Z is configured to fasten the first side wall **112a**, the second side wall **112b**, and the first shielding wall **113a**. In the first direction X, the first side wall **112a**, the first shielding wall **113a**, and the second side wall **112b** are sequentially spaced. Space between the first side wall **112a** and the first shielding wall **113a** is used to accommodate the primary region **161**. Space between the first shielding wall **113a** and the second side wall **112b** is used to accommodate the upper-layer circuit board **150**. In the first direction X, the secondary region **162** protrudes from the first shielding wall **113a** towards the second side wall **112b** in the first direction.

[0199] In this embodiment, the first side wall **112a**, the second side wall **112b**, and the first shielding wall **113a** are fastened to the upper surface of the bottom plate **120** of the integrated groove housing **110** and may be configured to support and fasten the upper-layer circuit board **150** and the lower-layer circuit board **160**, to improve stability of the power supply apparatus **100**. In the first direction X, the first side wall **112a**, the first shielding wall **113a**, and the second side wall **112b** are sequentially spaced, so that the first shielding wall **113a** isolates the electrical component in the power supply apparatus **100** in the first direction X, to implement electrical shielding on the electrical component in the power supply apparatus **100**.

[0200] In this embodiment, space between the first side wall **112a** and the first shielding wall **113a** is used to accommodate the primary region **161**, and the first side wall **112a** and the first shielding wall **113a** form a mounting region of the motor control unit **101** and the vehicle control unit **104**. Refer to FIG. 10 and FIG. 11. The first shielding wall **113a** may reduce electrical interference caused by the electrical component carried on the upper-layer circuit board **150** to the bus capacitor **163** of the motor control unit **101** of the primary region **161**, the power module **164**, and the plurality of chips **144** of the vehicle control unit **104**, to improve electromagnetic compatibility of the power supply apparatus **100**.

[0201] In this embodiment, space between the first shielding wall **113a** and the second side wall **112b** is used to accommodate the upper-layer circuit board **150**, and the first shielding wall **113a** and the second side wall **112b** form a mounting region of the on-board charger **141**. The first shielding wall **113a** can reduce electrical interference caused by the motor control unit **101** and the vehicle control unit **104** of the lower-layer circuit board **160** to the electrical component carried by the upper-layer circuit board **150**, to improve electromagnetic compatibility of the power supply apparatus **100**.

[0202] Refer to FIG. 7, FIG. 9, and FIG. 11. In the first direction X, the secondary region **162** protrudes from the first shielding wall **113a** towards the second side wall **112b**. This helps the

secondary region **162** be disposed below the upper-layer circuit board **150** in the third direction Z, improves space utilization of the power supply apparatus **100**, and reduces space occupied by the power supply apparatus **100** in the first direction X.

[0203] Refer to FIG. **9**, FIG. **10**, and FIG. **11**. In the first direction X, the primary region **161**, the secondary region **162**, and the second side wall **112b** are sequentially arranged, and the secondary region **162** is spaced from the second side wall **112b**. Space between the secondary region **162** and the second side wall **112b** is used to accommodate the plurality of inductors **141b** in the on-board charger **141**.

[0204] As shown in FIG. **10**, in the first direction X, the primary region **161**, the secondary region **162**, and the second side wall **112b** are sequentially arranged, and the secondary region **162** is spaced apart from the second side wall **112b**, to provide space for arranging the plurality of inductors **141b** in the on-board charger **141** in the power supply apparatus **100**.

[0205] In this embodiment, the space between the secondary region **162** and the second side wall **112b** is used to accommodate the plurality of inductors **141b** in the on-board charger **141**. This helps fully utilize space in the accommodating cavity **140** of the power supply apparatus **100**, improve space utilization, and further improve a fusion degree of the power supply apparatus **100**.

[0206] In an embodiment, the lower surface of the upper-layer circuit board **150** is configured to carry the plurality of capacitors **141c** in the on-board charger **141** and a plurality of magnetic components of the alternating current filter **145**. Refer to FIG. **9**, FIG. **10**, and FIG. **11**. The integrated groove housing **110** further includes a third shielding wall **113c**, and in the third direction Z, the upper surface of the bottom plate **120** is configured to fasten the third shielding wall **113c**. In the first direction X, the secondary region **162**, the third shielding wall **113c**, and the second side wall **112b** are sequentially spaced. Space between the secondary region **162** and the third shielding wall **113c** is used to accommodate the plurality of capacitors **141c** in the on-board charger **141**. Space between the third shielding wall **113c** and the second side wall **112b** is used to accommodate the plurality of magnetic components in the alternating current filter **145**.

[0207] In this embodiment, the plurality of capacitors **141c** in the on-board charger **141** and the plurality of magnetic components in the alternating current filter **145** are fastened to the bottom plate **120** of the integrated groove housing **110**. Space between the upper-layer circuit board **150** and the bottom plate **120** is used to accommodate the plurality of capacitors **141c** in the on-board charger **141** and the plurality of magnetic components in the alternating current filter **145**. The third shielding wall **113c** is fastened to the upper surface of the bottom plate **120** of the integrated groove housing **110**, and the third shielding wall **113c** may be configured to support the upper-layer circuit board **150**. This helps improve fastening strength between the upper-layer circuit board **150** and the integrated groove housing **110**.

[0208] In this embodiment, in the first direction X, the secondary region **162**, the third shielding wall **113c**, and the second side wall **112b** are sequentially spaced, so that the third shielding wall **113c** isolates the electrical component in the power supply apparatus **100** in the first direction X, to implement electrical shielding on the electrical component in the power supply apparatus **100**. The third shielding wall **113c** may reduce electrical interference caused by the secondary region **162** to the plurality of magnetic components in the alternating current filter **145** between the third shielding wall **113c** and the second side wall **112b** in the first direction X, may reduce electrical interference caused by the electrical component between the third shielding wall **113c** and the second side wall **112b** to the direct current converter **142** in the secondary region **162**, and improves electromagnetic compatibility of the power supply apparatus **100**. The third shielding wall **113c** and the second side wall **112b** are spaced, to help provide mounting space for the plurality of magnetic components in the alternating current filter **145**.

[0209] In this embodiment, the space between the secondary region **162** and the third shielding wall **113c** is used to accommodate the plurality of capacitors **141c** in the on-board charger **141**. This helps fully use space of the lower surface of the upper-layer circuit board **150** and improve

integration of the power supply apparatus **100**.

[0210] In this embodiment, the space between the third shielding wall **113c** and the second side wall **112b** is used to accommodate the plurality of magnetic components in the alternating current filter **145**. The alternating current filter **145** includes an alternating current filter, and the alternating current filter is configured to filter out a harmonic in an alternating current.

[0211] Refer to FIG. **9**, FIG. **10**, and FIG. **11**. In the second direction Y, the alternating current input connector mounting hole **111d** is located between the third shielding wall **113c** and the second side wall **112b** (as shown in FIG. **11**). In this way, an alternating current input from the connector **175** in the alternating current input mounting hole **111d** can be directly filtered by the alternating current filter **145** between the third shielding wall **113c** and the second side wall **112b**. This reduces a line path and reduces a loss.

[0212] In an embodiment, the lower surface of the upper-layer circuit board **150** is configured to carry the plurality of inductors **141b** in the on-board charger **141** and the plurality of magnetic components in the direct current filter **146**. Refer to FIG. **9**, FIG. **10**, and FIG. **11**. The integrated groove housing **110** further includes a fourth shielding wall **113d**, and in the third direction Z, the upper surface of the bottom plate **120** is configured to fasten the fourth shielding wall **113d**. In the first direction X, the first shielding wall **113a**, the fourth shielding wall **113d**, and the second side wall **112b** are sequentially spaced. Space between the fourth shielding wall **113d** and the first shielding wall **113a** is used to accommodate the plurality of magnetic components in the direct current filter **146**. Space between the fourth shielding wall **113d** and the second side wall **112b** is used to accommodate the plurality of inductors **141b** in the on-board charger **141**.

[0213] In this embodiment, the plurality of inductors **141b** in the on-board charger **141** and the plurality of magnetic components in the direct current filter **146** are arranged in the second direction Y, and the direct current filter **146** is configured to filter out a harmonic in a high voltage direct current. The fourth shielding wall **113d** is configured to support the upper-layer circuit board **150**, to enhance mounting stability of the upper-layer circuit board **150** and the integrated groove housing **110** and improve electrical connection stability of the power supply apparatus **100**, so that the power supply apparatus **100** runs stably.

[0214] In this embodiment, the first shielding wall **113a**, the fourth shielding wall **113d**, and the second side wall **112b** are sequentially spaced in the first direction X, so that the circuit in the power supply apparatus **100** is divided more carefully. This helps reduce electrical interference between modules on the power supply apparatus **100**, improve electromagnetic compatibility of the power supply apparatus **100**, and ensure normal running of the power supply apparatus **100**.

[0215] In this embodiment, mounting space of the plurality of magnetic components in the direct current filter **146** is provided between the first shielding wall **113a** and the fourth shielding wall **113d**, and the plurality of inductors **141b** in the on-board charger **141** are provided between the fourth shielding wall **113d** and the second side wall **112b**. The fourth shielding wall **113d** helps reduce electrical interference caused by the plurality of magnetic components in the direct current filter **146** to the plurality of inductors **141b** in the on-board charger **141**, and further helps reduce interference caused by the plurality of inductors **141b** in the on-board charger **141** to the plurality of magnetic components in the direct current filter **146**. This facilitates stable running of the power supply apparatus **100**.

[0216] Refer to FIG. **9**, FIG. **10**, and FIG. **11**. The direct current input connector mounting hole **111b** corresponds to the space between the first shielding wall **113a** and the fourth shielding wall **113d**. In this way, the direct current input through the direct current input mounting hole **111b** can be filtered by the direct current filter **146** between the first shielding wall **113a** and the fourth shielding wall **113d**, to reduce a line path and reduce a loss.

[0217] Refer to FIG. **9**, FIG. **10**, and FIG. **11**. The power supply connector mounting hole **111c** corresponds to a region between the fourth shielding wall **113d** and the second side wall **112b**, so that the power supply connector **173** fastened by the power supply connector mounting hole **111c**

can be shielded by the fourth shielding wall **113b**, to improve electromagnetic compatibility of the power supply apparatus **100**.

[0218] In an embodiment, the integrated groove housing **110** further includes a fifth shielding wall **113e**, and in the third direction Z, the upper surface of the bottom plate **120** is configured to fasten the fifth shielding wall **113e**. Refer to FIG. 9, FIG. 10, and FIG. 11. The fifth shielding wall **113e** and the secondary region **162** are spaced in the second direction Y. Space between the fifth shielding wall **113e** and the secondary region **162** is used to accommodate the plurality of magnetic components in the direct current converter **142**. A region enclosed by the fifth shielding wall **113e**, the fourth shielding wall **113d**, and the first shielding wall **113a** is configured to accommodate the plurality of magnetic components in the direct current filter **146**.

[0219] In this embodiment, the fifth shielding wall **113e** is configured to support the upper-layer circuit board **150**. This helps enhance mounting stability between the upper-layer circuit board **150** and the integrated groove housing **110**, and helps improve electrical connection stability of the power supply apparatus **100**, so that the power supply apparatus **100** runs stably.

[0220] In this embodiment, in the second direction Y, the fifth shielding wall **113e** and the secondary region **162** are spaced, to help provide a mounting region for the plurality of magnetic components in the direct current to direct current converter **142**. The space between the fifth shielding wall **113e** and the secondary region **162** is used to accommodate the plurality of magnetic components in the direct current converter **142**, so that when a high voltage current is converted into a low voltage direct current through the plurality of magnetic components in the direct current converter **142**, the high voltage current can be converted into another current with a smaller voltage and transmitted to the low voltage load for power supply.

[0221] In this embodiment, the plurality of magnetic components in the direct current filter **146** are accommodated in the region jointly enclosed by the fifth shielding wall **113e**, the fourth shielding wall **113d**, and the first shielding wall **113a**. This helps reduce electrical interference caused by the motor control unit **101** circuit in the primary region **161** of the lower-layer circuit board **160**, the direct current converter **142** of the upper-layer circuit board **150**, and the transformer **141d** to the direct current filter **146**, so that the direct current filter **146** operates normally, and electromagnetic compatibility of the power supply apparatus **100** is improved.

[0222] In an embodiment, the integrated groove housing **110** further includes a sixth shielding wall **113f**, in the third direction Z, the upper surface of the bottom plate **120** is configured to fasten the sixth shielding wall **113f**, and the sixth shielding wall **113f** extends in the first direction X. Refer to FIG. 9, FIG. 10, and FIG. 11. The fourth shielding wall **113d**, the sixth shielding wall **113f**, and the second side wall **112b** are sequentially arranged in the first direction X. In the second direction Y, the secondary region **162**, the fifth shielding wall **113e**, and the sixth shielding wall **113f** are sequentially spaced. The sixth shielding wall **113f** is configured to separate the space between the fourth shielding wall **113d** and the second side wall **112b** into two regions **126**, **127** arranged in the second direction Y. In the two regions **126** and **127**, one region **126** closer to the secondary region **162** is configured to accommodate the plurality of inductors **141b** in the on-board charger **141**, and the other region **127** is configured to accommodate the transformer **141d** of the on-board charger **141** and the compressor power supply connector **173**.

[0223] In this embodiment, in the third direction Z, the upper surface of the bottom plate **120** is configured to fasten the sixth shielding wall **113f**, the sixth shielding wall **113f** extends in the third direction Z, and the sixth shielding wall **113f** may be configured to support the upper-layer circuit board **150**. This helps enhance mounting stability between the upper-layer circuit board **150** and the integrated groove housing **110** and helps improve electrical connection stability of the power supply apparatus **100**, so that the power supply apparatus **100** runs stably.

[0224] In this embodiment, in the first direction X, the fourth shielding wall **113d**, the sixth shielding wall **113f**, and the second side wall **112b** are sequentially spaced. The fourth shielding wall **113d** may electrically shield the direct current filter **146** from the transformer **141d** and the

plurality of inductors **141b** in the on-board charger **141**. The sixth shielding wall **113f** is disposed between the fourth shielding wall **113d** and the second side wall **112b**, and a length direction of the sixth shielding wall **113f** is parallel to the first direction X, so that the transformer **141d** arranged in the second direction Y and the plurality of inductors **141b** in the on-board charger **141** are electrically shielded. This helps reduce electrical interference between the direct current filter **146**, the transformer **141d**, and the plurality of inductors **141b** in the on-board charger **141**, so that these modules run more smoothly.

[0225] In this embodiment, in the second direction Y, the secondary region **162**, the fifth shielding wall **113e**, and the sixth shielding wall **113f** are sequentially spaced. In the second direction Y, the secondary region **162** and the fifth shielding wall **113e** are spaced to provide a mounting region for the direct current converter **142**. The fifth shielding wall **113e** and the sixth shielding wall **113f** are spaced. Therefore, more mounting space is provided for mounting regions of the plurality of magnetic components in the alternating current filter **145** between the plurality of capacitors **141c** in the on-board charger **141** and the sixth shielding wall **113f**.

[0226] In this embodiment, the sixth shielding wall **113f** is configured to separate the space between the fourth shielding wall **113d** and the second side wall **112b** into the two regions **126** and **127** arranged in the second direction Y. This helps electrically shield the plurality of inductors **141b** in the on-board charger **141** from the transformer **141d**. The region **126** that is in the two regions **126** and **127** and that is closer to the secondary region **162** is used to accommodate the plurality of inductors **141b** in the on-board charger **141**. The other region **127** is configured to accommodate the transformer **141d** of the on-board charger **141** and the compressor power supply connector **173**. In other words, the sixth shielding wall **113f** may reduce electrical interference caused by the plurality of inductors **141b** in the on-board charger **141** to the transformer **141d** of the on-board charger **141** and the compressor power supply connector **173**, and may reduce electrical interference caused by the transformer **141d** of the on-board charger **141** and the power supply connector **173** of the compressor to the plurality of inductors **141b** in the on-board charger **141**. This improves electromagnetic compatibility of the power supply apparatus **100** and ensures stable running of the power supply apparatus **100**.

[0227] In an embodiment, the power supply apparatus **100** further includes the first shielding cover **114a**, and the first shielding cover **114a** is configured to shield at least a part of the plurality of chips **144** of the vehicle control unit **104**. Refer to FIG. 9, FIG. 10, and FIG. 11. The bottom plate **120**, the lower-layer circuit board **160**, and the first shielding case **114a** are sequentially stacked in the third direction Z. In the first direction X, the first side wall **112a** and the first shielding case **114a** are adjacently arranged.

[0228] In this embodiment, the first shielding cover **114a** is fastened and connected to at least a part of the plurality of chips **144** of the vehicle control unit **104**. This helps enhance stability of the vehicle control unit **104** in the power supply apparatus **100**. The first shielding cover **114a** may shield electrical impact of the motor control unit **101** of the lower-layer circuit board **160** on the vehicle control unit **104**, to improve electromagnetic compatibility of the power supply apparatus **100**, so that communication of the vehicle control unit **104** (as shown in FIG. 4) operates smoothly.

[0229] In this embodiment, the bottom plate **120**, the lower-layer circuit board **160**, and the first shielding cover **114a** are sequentially stacked in the third direction Z. In other words, at least a plurality of chips **144** of the vehicle control unit **104** are in contact with the lower-layer circuit board **160**. This facilitates a control signal of the vehicle control unit **104** to be transmitted from the communication connector **178** mounted at the communication connector mounting hole **111g** to the chip **144** of the vehicle control unit **104**, and then transmitted to the lower-layer circuit board **160** to control the power supply apparatus **100**.

[0230] In this embodiment, in the first direction X, the first side wall **112a** and the first shielding cover **114a** are arranged adjacent to each other, so that the communication connector mounting hole **111g** is disposed close to the first side wall **112a**. This helps the communication connector **178** to

be electrically connected to the load on the vehicle.

[0231] In an embodiment, the power supply apparatus **100** further includes the second shielding cover **114b**, and the second shielding cover **114b** is configured to shield the plurality of magnetic components in the alternating current filter **145**. Refer to FIG. 9, FIG. 10, and FIG. 11. The bottom plate **120**, the upper-layer circuit board **150**, and the second shielding case **114b** are sequentially stacked in the third direction Z. In the first direction X, the second side wall **112b**, the second shielding case **114b**, and the third shielding wall **113c** are adjacently arranged.

[0232] In this embodiment, the second shielding case **114b** is fastened and connected to the third shielding wall **113c** and the second side wall **112b**, so that structural stability of the power supply apparatus **100** can be enhanced. In addition, a region enclosed by the third shielding wall **113c**, the second shielding case **114b**, and the second side wall **112b** is used to mount the plurality of magnetic components in the alternating current filter **145**. This helps reduce electrical interference caused by the plurality of capacitors **141c** and the plurality of inductors **141b** in the on-board charger **141** to the plurality of magnetic components in the alternating current filter **145**.

[0233] Refer to FIG. 9, FIG. 10, and FIG. 11. The secondary region **162** is further configured to carry the plurality of magnetic components in the low voltage filter **147**, and the space between the secondary region **162** and the upper-layer circuit board **150** is used to accommodate the plurality of magnetic components in the low voltage filter **147**.

[0234] In this embodiment, the secondary region **162** not only carries at least a part of the power switching transistors **142a** of the direct current converter **142**, but also carries the plurality of magnetic components in the low voltage filter **147**. This helps integrate the direct current converter **142** and the low voltage filter **147** into the lower-layer circuit board **160**, so that the bus capacitor **163** and the power module **164** of the vehicle control unit **104**, the plurality of chips **144** of the vehicle control unit **104**, the direct current converter **142**, and the low voltage filter **147** share one lower-layer circuit board **160**. This helps reduce a quantity of used circuit boards and helps improve integration of the power supply apparatus **100**.

[0235] In this embodiment, the space between the secondary region **162** and the upper-layer circuit board **150** is used to accommodate the plurality of magnetic components in the low voltage filter **147**. This helps improve space utilization inside the power supply apparatus **100** and improve a fusion degree between modules in the power supply apparatus **100**.

[0236] In an embodiment, the power supply apparatus **100** further includes a third shielding cover **114c** and a 12 V copper bar **117**. Refer to FIG. 9, FIG. 10, and FIG. 11. In the first direction X, the primary region **161**, the third shielding cover **114c**, and the secondary region **162** are sequentially arranged adjacent to each other.

[0237] In this embodiment, the third shielding cover **114c** is a 12 V shielding cover, and the third shielding cover **114c** extends in the second direction Y and is vertical to the lower-layer circuit board **160**. This helps provide support for the cover plate **130** of the power supply apparatus **100** and helps improve mounting stability of the power supply apparatus **100**. In the first direction X, the third shielding cover **114c** is located between the primary region **161** and the secondary region **162** of the lower-layer circuit board **160**, so that electrical interference between the primary region **161** and the secondary region **162** can be reduced. The third shielding cover **114c** is configured to shield the plurality of magnetic components in the low voltage filter **147**. The 12 V copper bar **117** is configured to transmit a current in the low voltage filter **147** to the low voltage load. A shielding area of the low voltage filter **147** is formed between the third shielding case **114c** and the third shielding wall **113c**, to facilitate smooth running of the low voltage filter **147**.

[0238] In an embodiment, the power supply apparatus **100** further includes a board-to-board connector **118** that connects the upper-layer circuit board **150** and the lower-layer circuit board **160**. Refer to FIG. 9, FIG. 10, and FIG. 11. The board-to-board connector **118** is used to implement a communication connection between the upper-layer circuit board **150** and the lower-layer circuit board **160**. This helps connect the upper-layer circuit board **150** and the lower-layer circuit board

160 and promotes deep fusion of the power supply apparatus **100**. In addition, the power supply apparatus **100** further has many slotting tool structures and is configured to electrically connect the upper-layer circuit board **150** and the lower-layer circuit board **160**.

[0239] Refer to FIG. 9, FIG. 10, and FIG. 11. Upper surfaces of the third shielding wall **113c**, the fourth shielding wall **113d**, the fifth shielding wall **113e**, and the sixth shielding wall **113f** in the third direction Z are attached to the lower surface of the upper-layer circuit board **150**. This helps implement better shielding effect of the circuit in the upper-layer circuit board **150**.

[0240] In an embodiment, the integrated groove housing **110** further includes the third side wall **112c**, the second shielding wall **113b**, and the fourth side wall **112d**. The upper surface of the bottom plate **120** in the third direction Z is configured to fasten the third side wall **112c**, the second shielding wall **113b**, and the fourth side wall **112d**. Refer to FIG. 9, FIG. 10, and FIG. 11. The third side wall **112c**, the second shielding wall **113b**, and the fourth side wall **112d** are sequentially spaced in the second direction Y. Space between the third side wall **112c** and the second shielding wall **113b** is used to accommodate a part of copper bars of the power distribution unit **103**. Space between the second shielding wall **113b** and the fourth side wall **112d** is used to accommodate the primary region **161**.

[0241] As shown in FIG. 4, the first side wall **112a**, the second side wall **112b**, the third side wall **112c**, the fourth side wall **112d**, the bottom plate **120**, and the cover plate **130** jointly enclose the accommodating cavity **140** of the integrated groove housing **110**. The accommodating cavity **140** is configured to accommodate the upper-layer circuit board **150** and the lower-layer circuit board **160**.

[0242] In this embodiment, the second shielding wall **113b** is fastened to the upper surface of the bottom plate **120** in the third direction Z, and the second shielding wall **113b** has a support function for the power supply apparatus **100**. This helps improve mounting stability of the power supply apparatus **100** and ensures stable running of the power supply apparatus **100**.

[0243] In this embodiment, the power distribution unit **103** converts a high voltage direct current output by the battery **30** into a direct current voltage or an alternating current required by a load when the load operates, to supply power to the load. In the second direction Y, the third side wall **112c**, the second shielding wall **113b**, and the fourth side wall **112d** are sequentially spaced. A mounting region is provided between the third side wall **112c** and the second shielding wall **113b** for a part of copper bars of the power distribution unit **103**. A mounting region is provided between the second shielding wall **113b** and the fourth side wall **112d** for the primary region **161** of the lower-layer circuit board **160**. In addition, the second shielding wall **113b** electrically shields, in the second direction Y, the part of copper bars of the power distribution unit **103** in the power supply apparatus **100** from the bus capacitor **163** and the power module **164** of the motor control unit **101** in the primary region **161**. This helps reduce electrical interference caused when the part of copper bars of the power distribution unit **103**, the bus capacitor **163** of the motor control unit **101**, and the power module **164** operate, and improve electromagnetic compatibility of the power supply apparatus **100**.

[0244] Refer to FIG. 9, FIG. 10, and FIG. 11. The battery connector mounting hole **111a** and the second shielding wall **113b** are arranged opposite to each other in the second direction Y. In this way, the battery connector **171** fastened to the battery connector mounting hole **111a** can be connected to the part of copper bars of the power distribution unit **103** between the second shielding wall **113b** and the third side wall **112c**, so that a connection line between the battery connector **171** and a part of copper bars of the power distribution unit **103** is shortened, and a power loss is reduced.

[0245] As shown in FIG. 7 and FIG. 8, in the first direction X, a length of the secondary region **162** is less than a length of the primary region **161**. In the second direction Y, the length of the secondary region **162** is less than the length of the primary region **161**. In the second direction Y, sides that are of the primary region **161** and the secondary region **162** and that are away from the third side wall **112c** are arranged adjacent to the fourth side wall **112d**.

[0246] In this embodiment, in the first direction X, the length of the secondary region **162** is denoted as **L11**, the length of the primary region **161** is denoted as **L12**, and **L11<L12**. As shown in FIG. 7, in the first direction X, a small length of the secondary region **162** helps the secondary region **162** be arranged below the upper-layer circuit board **150** in the third direction Z, and does not occupy much space in the power supply apparatus **100** in the first direction X. The small secondary region **162** in the first direction X provides sufficient space for mounting the plurality of magnetic components in the alternating current filter **145** between the secondary region **162** and the second side wall **112b**.

[0247] As shown in FIG. 8, in the second direction Y, a length of the secondary region **162** is denoted as **L13**, a length of the primary region **161** is denoted as **L14**, and **L13<L14**. As shown in FIG. 9, the small secondary region **162** in the second direction Y provides sufficient mounting space for the plurality of magnetic components in the direct current filter **146**, the plurality of power switching transistors **141a** and the plurality of inductors **141b** in the on-board charger **141**, a part of the power switching transistors **142a** in the direct current converter **142**, a transformer **141d** in the on-board charger **141**, and the compressor power supply connector **173**.

[0248] In this embodiment, in the second direction Y, sides that are of the primary region **161** and the secondary region **162** and that face from the third side wall **112c** are arranged adjacent to the fourth side wall **112d**. This helps a circuit on the lower-layer circuit board **160** more quickly be transmitted to the three-phase connector mounting hole **111f** close to the fourth side wall **112d**, to transmit a current in the power supply apparatus **100** to the winding of the motor **300** and drive the rotor and the motor shaft of the motor **300** to rotate. This also helps a circuit on the lower-layer circuit board **160** more quickly be transmitted to the low voltage load connector mounting hole **111e** close to the fourth side wall **112d**, to supply power to the low voltage load. In addition, this further helps save a material of the lower-layer circuit board **160** and reduce production costs.

[0249] In an embodiment, the upper-layer circuit board **150** includes a notch **151**, and the notch **151** includes an opening facing the third side wall **112c** in the second direction Y and an opening facing the primary region **161** in the first direction X. As shown in FIG. 5, space between an opening side edge of the notch **151** and the third side wall **112c** is used to accommodate the direct current power supply connector **172** and a part of copper bars of the power distribution unit **103**.

[0250] In this embodiment, the notch **151** of the upper-layer circuit board **150** provides mounting space for the direct current power supply connector **172** at the direct current power connector mounting hole **111b** on the integrated groove housing **110**. The notch **151** includes the opening facing the third side wall **112c** in the second direction Y and the opening facing the primary region **161** in the first direction X. The third side wall **112c** and the opening that is of the notch **151** and that faces the third side wall **112c** in the second direction Y provide sufficient mounting space for the direct current power supply connector **172** in the second direction Y. Sufficient mounting space is provided for the direct current power supply connector **172** in the first direction X between the opening that is in the first direction X and that faces the primary region **161** and the part of copper bars of the power distribution unit **103**.

[0251] In this embodiment, the space between the opening side edge of the notch **151** and the third side wall **112c** is used to accommodate the part of copper bars of the power distribution unit **103** and the direct current power supply connector **172**. This helps mount the direct current power supply connector **172** closer to the direct current power supply connector mounting hole **111b** that penetrates the third side wall **112c** in the second direction Y. This also helps the part of copper bars of the power distribution unit **103** connect the direct current power supply connector **172** to the connector **171** of the battery **30** by using fewer materials and helps the direct current power supply connector **172** more quickly transmit a high voltage current of an external power supply to the battery **30**, to charge the battery **30**.

[0252] In an embodiment, the motor end cover **600** and the fourth side wall **112d** of the integrated groove housing **110** are arranged on a same side. As shown in FIG. 4, the reducer end cover **700**

and the third side wall **112c** of the integrated groove housing **110** are arranged on a same side.

[0253] In this embodiment, the motor end cover **600** and the fourth side wall **112d** of the integrated groove housing **110** are arranged on the same side. This helps the motor control unit **101** close to the fourth side wall **112d** transmit an alternating current to the winding of the motor **300**, to drive the rotor and the motor shaft of the motor **300** to rotate. In addition, this helps the low voltage filter **147** close to the fourth side wall **112d** transmits a low voltage current to the low voltage load of the vehicle through a shorter path, to help reduce a power loss. The reducer end cover **700** is arranged on a same side as the third side wall **112c** of the integrated groove housing **110**, and the battery charge and discharge connector mounting hole **111a**, the direct current power supply connector mounting hole **111b**, and the power supply connector mounting hole **111c** are arranged on the third side wall **112c**. This helps the battery charge and discharge connector **171**, the direct current power supply connector **172**, and the compressor connector **173** that are close to the third side wall **112c** be disposed above the reducer **200** and helps the motor control unit **101** and the low voltage filter **147** that are disposed above the motor **300** be disposed in a distributed manner. In this way, the components in the power supply apparatus **100** are arranged more regularly.

[0254] In an embodiment, the integrated groove housing **110** further includes a support column **128**. As shown in FIG. 5, the support column **128** is configured to be fastened to the two bolts **131** on the cover plate **130**, so that stability of the power supply apparatus **100** can be enhanced, noise radiation can be reduced, and NVH performance of the vehicle can be improved. As shown in FIG. 5, the shielding wall is connected to the support column **128** and is used to enhance structural strength of the shielding wall.

[0255] In an embodiment, the first shielding wall **113a**, the fourth shielding wall **113d**, and the fifth shielding wall **113e** are enclosed to form a high voltage direct current common mode inductor filter region **106**. Refer to FIG. 9, FIG. 10, and FIG. 11. An alternating current common mode inductor filter region **107** is formed between the third shielding wall **113c** and the second side wall **112b**. A 12 V power supply filter region **108** is formed between the third shielding cover **114c** and the third shielding wall **113c**. Electrical interference between regions is effectively reduced, electromagnetic compatibility of the power supply apparatus **100** is improved, and stable running of the power supply apparatus **100** is ensured.

[0256] In an implementation, the electrical component in the power supply apparatus **100** is directly placed into the inner cavity from a groove opening of the integrated groove housing **110** and is mounted from bottom to top of the bottom plate **120**. The upper-layer circuit board **150** and the primary region **161** of the lower-layer circuit board **160** are tiled in the first direction X. The upper-layer circuit board **150** and the secondary region **162** of the lower-layer circuit board **160** are stacked in the third direction Z. In a mounting process, the circuit board does not need to be turned over, assembly is simple, and the mounting process is smooth.

[0257] In an embodiment, the upper-layer circuit board **150** and the secondary region **162** of the lower-layer circuit board **160** are stacked, and the direct current converter **142** is arranged below the upper-layer circuit board **160** by using the secondary region **162** of the lower-layer circuit board **1620** to further improve integration of the circuit board.

[0258] FIG. 13 is a bottom view of the integrated groove housing **110** according to an embodiment. FIG. 14 is an AA cross sectional view of FIG. 13. FIG. 15 is a diagram of a partial structure of the integrated groove housing **110** according to an embodiment. FIG. 16 is a diagram of structures of a first flow channel groove and a second flow channel groove according to an embodiment.

[0259] As shown in FIG. 13, in an embodiment, an internal flow channel of the bottom plate **120** of the integrated groove housing **110** includes the first flow channel **181** and the second flow channel **191**, and the first flow channel **181** is configured to communicate with the second flow channel **191** and the radiator **105**. The first flow channel **181** and the second flow channel **191** are arranged in the first direction X. The first flow channel **181**, the upper-layer circuit board **150**, and the radiator **105** are sequentially stacked in the third direction Z (with reference to FIG. 5). The first flow

channel **181** and the radiator **105** are configured to cool an electrical component in the on-board charger **141** carried by the upper-layer circuit board **150**. The second flow channel **191** and the lower-layer circuit board **160** are stacked in the third direction Z, and the second flow channel **191** is configured to cool the power module **164** of the motor control unit **101** carried on the lower surface of the lower-layer circuit board **160**.

[0260] In this embodiment, the integrated groove housing **110** is configured to fasten and mount the radiator **105**, the upper-layer circuit board **150**, and the lower-layer circuit board **160** (as shown in FIG. 5). The radiator **105**, the upper-layer circuit board **150**, and the lower-layer circuit board **160** are supported by the integrated groove housing **110**, so that the radiator **105**, the upper-layer circuit board **150**, and the lower-layer circuit board **160** are fastened to the integrated groove housing **110** with high stability. In this way overall structural strength of the power supply apparatus **100** is stronger, and an electrical connection is more stable. In an embodiment, the radiator **105** is a brazed radiator **105**. When an external environment exerts external force on the power supply apparatus **100**, the radiator **105**, the upper-layer circuit board **150**, the lower-layer circuit board **160**, and the integrated groove housing **110** are not easily displaced relative to each other. This helps the power supply apparatus **100** operate in a stable state.

[0261] In this embodiment, the power supply apparatus **100** generates a large amount of heat in an operating process, and heat dissipation needs to be performed on the power supply apparatus **100** to ensure that a component in the power supply apparatus **100** operates normally. As shown in FIG. 5 and FIG. 13, the bottom plate **120** includes the first flow channel **181** and the second flow channel **191**. The first flow channel **181** and the second flow channel **191** are configured to the cool electrical components carried by the upper-layer circuit board **150** and the lower-layer circuit board **160** in the power supply apparatus **100**. The first flow channel **181** is configured to communicate the second flow channel **191** and the radiator **105**, to facilitate communication of a coolant in the power supply apparatus **100**. In an embodiment, after entering the power supply apparatus **100**, the coolant sequentially passes through the radiator **105**, the first flow channel **181**, and the second flow channel **191**, to implement series circulation cooling of the coolant in the power supply apparatus **100**. In an embodiment, after the coolant enters the power supply apparatus **100**, a part of the coolant flows through the radiator **105** and the first flow channel **181** to the second flow channel **191**, and the other part of the coolant directly flows from the first flow channel **181** to the second flow channel **191** without passing through the radiator **105**. The two parts of the coolant converge in the second flow channel **191**, to implement parallel circulation of the coolant in the power supply apparatus **100** for cooling.

[0262] As shown in FIG. 13, the first flow channel **181** and the second flow channel **191** are arranged in the first direction X. As shown in FIG. 5, the upper-layer circuit board **150** and the primary region **161** of the lower-layer circuit board **160** are also arranged in the first direction X, to help the first flow channel **181** and the second flow channel **191** cool the lower-layer circuit board **160** and the upper-layer circuit board **150**.

[0263] In this embodiment, the second flow channel **191** is configured to cool the power module **164** of the motor control unit **101** carried on the lower surface of the lower-layer circuit board **160**. The second flow channel **191** and the lower-layer circuit board **160** are stacked in the third direction Z. Therefore, the second flow channel **191** covers a mounting region in which the power module **164** of the motor control unit **101** is mounted on the bottom plate **120**. In this way, the second flow channel **191** cools the power module **164** of the motor control unit **101** as much as possible, thereby improving cooling efficiency.

[0264] In an embodiment, a heat dissipation structure **164a** (as shown in FIG. 15) is disposed on a lower surface of the power module **164** of the motor control unit **101**. The heat dissipation structure **164a** is located in the second flow channel groove **190**, and the heat dissipation structure **164a** may be immersed in a coolant. When the coolant in the first flow channel groove **180** flows through the second flow channel groove **190**, heat of the power module **164** can be taken away more quickly,

thereby improving cooling efficiency of the motor control unit **101**. In an embodiment, the heat dissipation structure **164a** includes a plurality of heat dissipation fins distributed at intervals. [0265] Refer to FIG. **9** and FIG. **13**. The first flow channel **181** is configured to cool at least one of the transformer **141d**, the plurality of inductors **141b**, and the plurality of capacitors **141c** in the on-board charger **141** carried on the lower surface of the upper-layer circuit board **150**. The radiator **105** is configured to cool the plurality of power switching transistors **141a** of the on-board charger **141** carried on the upper surface of the upper-layer circuit board **150**.

[0266] In this embodiment, the first flow channel **181** is located on the bottom plate **120**. The transformer **141d**, the plurality of inductors **141b**, and the plurality of capacitors **141c** in the on-board charger **141** are sequentially arranged on the lower surface of the upper-layer circuit board **150** in a second direction Y. The first flow channel **181** is configured to cool at least one of the transformer **141d**, the plurality of inductors **141b**, and the plurality of capacitors **141c** in the on-board charger **141** carried on the lower surface of the upper-layer circuit board **150**. In this way, at least one of the transformer **141d**, the plurality of inductors **141b**, and the plurality of capacitors **141c** in the on-board charger **141** can be cooled in time when the on-board charger **141** operates. This helps reduce a temperature in the power supply apparatus **100** and ensures normal operating of the power supply apparatus **100**.

[0267] In this embodiment, the radiator **105** is configured to cool the plurality of power switching transistors **141a** of the on-board charger **141** carried on the upper surface of the upper-layer circuit board **150**. The plurality of power switching transistors **141a** of the on-board charger **141** are closer to the radiator **105** than the first flow channel **181**, so that the radiator **105** can cool the plurality of power switching transistors **141a** of the on-board charger **141**. This helps reduce the temperature in the power supply apparatus **100** and ensures normal operating of the power supply apparatus **100**.

[0268] In this embodiment, the first flow channel **181** and the radiator **105** are respectively configured to cool electrical components carried on the lower surface and the lower surface of the upper-layer circuit board **150**. Some electrical components of the upper-layer circuit board **150** are stacked between the upper-layer circuit board **150** and the bottom plate, and some electrical components are stacked between the upper-layer circuit board **150** and the radiator **105**. This not only improves cooling and heat dissipation effect of the electrical components, but also can fully use space of the upper surface and the lower surface of the upper-layer circuit board **150**, so that the components are arranged more compactly, a heat dissipation and cooling region is more centralized, and heat dissipation effect is better. This improves power density and operating efficiency of the power supply apparatus **100**.

[0269] In an embodiment, the lower-layer circuit board **160** includes a primary region **161** and a secondary region **162**. Refer to FIG. **9** and FIG. **13**. A lower surface of the primary region **161** is configured to fasten the power module **164** of the motor control unit **101**, and the secondary region **162** is configured to fasten at least a part of a part of the power switching transistors **142a** of the direct current converter **142**. The primary region **161** and the secondary region **162** are arranged in the first direction X. The first flow channel **181**, the secondary region **162**, and the upper-layer circuit board **150** are stacked in the third direction Z. The second flow channel **191** and the primary region **161** are stacked in the third direction Z.

[0270] In this embodiment, the primary region **161** and the secondary region **162** are arranged in the first direction X, and the first flow channel **181** and the second flow channel **191** are arranged in the first direction X. This makes it possible for the first flow channel **181** and the second flow channel **191** to jointly cool the lower-layer circuit board **160** and helps improve cooling efficiency of the lower-layer circuit board **160**. The first flow channel **181**, the secondary region **162**, and the upper-layer circuit board **150** are stacked in the third direction Z, so that the first flow channel **181** can not only cool the upper-layer circuit board **150**, but also cool the secondary region **162** of the lower-layer circuit board **160**, thereby improving efficiency of cooling the power supply apparatus **100** by the coolant. The second flow channel **191** and the primary region **161** are stacked in the

third direction Z, so that the second flow channel **191** cools the primary region **161** of the lower-layer circuit board **160**, to ensure normal operating of the electrical component in the lower-layer circuit board **160**.

[0271] In an embodiment, the bottom plate **120** includes the first flow channel groove **180** and the second flow channel groove **190**. As shown in FIG. **14** and FIG. **16**, the first flow channel groove **180** is recessed in the third direction Z from a lower surface of the bottom plate **120** to the upper-layer circuit board **150**, the first flow channel groove **180** is configured to form the first flow channel **181**, the second flow channel groove **190** is recessed in the third direction Z from the upper surface of the bottom plate **120** and away from the lower-layer circuit board **160**, and the second flow channel groove **190** is configured to form the second flow channel **191**.

[0272] In this embodiment, the coolant flows in the first flow channel groove **180** and the second flow channel groove **190** of the bottom plate **120**, to dissipate heat in the power supply apparatus **100**. As shown in FIG. **14** and FIG. **16**. The first flow channel groove **180** is recessed from the lower surface of the bottom plate **120** to the upper-layer circuit board **150** in the third direction Z, to help form the first flow channel **181** on the lower surface of the bottom plate **120**. In this way, arrangement of the first flow channel **181** does not affect mounting and arrangement of electrical components in the secondary region **162** of the upper-layer circuit board **150** and the lower-layer circuit board **160** in the power supply apparatus **100**. The second flow channel groove **190** is recessed in the third direction Z from the upper surface of the bottom plate **120** to the direction away from the lower-layer circuit board **160**. This helps form the second flow channel **191** on the upper surface of the bottom plate **120**. The second flow channel **191** is formed on the upper surface of the bottom plate **120** and is closer to the lower-layer circuit board **160**. This helps the second flow channel **191** cool the lower-layer circuit board **160**.

[0273] In an embodiment, the first flow channel groove **180** on the lower surface of the bottom plate **120** of the integrated groove housing **110** seals the first flow channel **181** by using a friction stir welding or glue dispensing process, to implement circulation of the coolant on the lower surface of the bottom plate **120** of the power supply apparatus **100**. In addition, this further helps prevent the coolant from leaking to the motor **300** and the reducer **200** of the powertrain **10**, to affect normal operating of the powertrain **10**. In an embodiment, a sealing plate covers a groove opening of the first flow channel groove **180**, the sealing plate and the first flow channel groove **180** form the first flow channel **181** through enclosure, and the sealing plate may seal and fasten the groove opening of the first flow channel groove **180** by using glue dispensing.

[0274] As shown in FIG. **16**, the power module **164** in the motor control unit **101** covers a groove opening of the second flow channel groove **190**, and a heat dissipation structure **164a** is disposed at the bottom of the power module **164**. The heat dissipation structure **164a** is accommodated in the second flow channel groove **190**, and a bottom wall of the power module **164** and the second flow channel groove **190** are enclosed to form the second flow channel **191**. In an embodiment, the bottom wall of the power module **164** and a bottom plate part on a periphery side of the groove opening of the second flow channel groove **190** may be sealed and fastened through welding.

[0275] As shown in FIG. **16**, in the third direction Z, a spacing between a groove bottom **182** of the first flow channel groove **180** and the radiator **105** is less than a spacing between a groove bottom **192** of the second flow channel groove **190** and the radiator **105**.

[0276] In this embodiment, in the third direction Z, a spacing between the groove bottom **182** of the first flow channel groove **180** and the radiator **105** is denoted as $L15$, in the third direction Z, a spacing between the groove bottom **192** of the second flow channel groove **190** and the radiator **105** is denoted as $L16$, and $L15 < L16$. As shown in FIG. **15**, the first flow channel groove **180** is located on the lower surface of the bottom plate **120**, $L15$ is small, and the coolant in the radiator **105** and the first flow channel **181** is closer to the upper-layer circuit board **150**. This helps cool the upper-layer circuit board **150**. The second flow channel groove **190** is located on the upper surface of the bottom plate **120**, and $L16$ is large, to provide larger space for the second flow channel

groove **190** to form the second flow channel **191**. More coolants flow through the second flow channel **191**, to better cool the lower-layer circuit board **160**. In addition, more space is provided for mounting the electrical component of the lower-layer circuit board **160**. The radiator **105**, the first flow channel groove **180**, and the second flow channel groove **190** in FIG. **15** are all diagrams of simplified structures.

[0277] In this embodiment, the groove bottom **182** of the first flow channel groove **180** and the groove bottom **192** of the second flow channel groove **190** are staggered in the third direction Z. In comparison with a solution in which the groove bottoms are not staggered, in this solution, a length of the first flow channel groove **180** and a length of the second flow channel groove **190** in the third direction Z can be reduced, so that a length of the power supply apparatus **100** in the third direction Z can be reduced, thereby facilitating miniaturization of the power supply apparatus **100**.

[0278] As shown in FIG. **13**, a length of the first flow channel groove **180** in the first direction X is greater than a length of the second flow channel groove **190** in the first direction X, and a length of the first flow channel groove **180** in the second direction Y is greater than a length of the second flow channel groove **190** in the second direction Y.

[0279] In this embodiment, a length of the first flow channel groove **180** in the first direction X is denoted as L**17**, a length of the second flow channel groove **190** in the first direction X is denoted as L**18**, and $L17 > L18$. As shown in FIG. **13**, L**17** is large, a surface area of the first flow channel **181** adjacent to the electrical component in the upper-layer circuit board **150** is larger, and more coolants flow through the first flow channel **181** in the first flow channel groove **180**. This helps improve efficiency of cooling the upper-layer circuit board **150** by the first flow channel **181**. L**18** is small, so that more mounting space is provided for the plurality of chips **144** of the vehicle control unit **104**.

[0280] In this embodiment, a length of the first flow channel groove **180** in the second direction Y is denoted as L**19**, a length of the second flow channel groove **190** in the second direction Y is denoted as L**20**, and $L19 > L20$. As shown in FIG. **13**, L**19** is large. This helps the first flow channel **181** dissipate heat for more electrical components in the upper-layer circuit board **150** in the second direction Y and improves cooling efficiency on the upper-layer circuit board **150**. Because the second flow channel groove **190** is disposed on the upper surface of the bottom plate **120**, L**20** is small, and more mounting space is provided for a bus capacitor **163** and a power distribution unit **103** of the motor control unit **101**.

[0281] In an embodiment, the groove peripheral wall **195** of the second flow channel groove **190** includes a communication hole **193**, and the communication hole **193** is configured to communicate with the first flow channel groove **180**. As shown in FIG. **14**, FIG. **15**, and FIG. **16**, a part of the groove peripheral wall **194** of the second flow channel groove **190** is adjacent to a part of the groove peripheral wall **183** of the first flow channel groove **180** in the first direction X. The communication hole **193** penetrates, in the first direction X, the part of the groove peripheral wall **194** of the second flow channel groove **190** and the part of the groove peripheral wall **183** of the first flow channel groove **180** that are adjacent to each other.

[0282] In this embodiment, the communication hole **193** communicates the first flow channel groove **180** with the second flow channel groove **190**, so that the coolant in the first flow channel **181** can flow into the second flow channel **191** from the communication hole **193**. This facilitates circulation of the coolant in the power supply apparatus **100** and helps improve a fusion degree of the power supply apparatus **100**.

[0283] As shown in FIG. **16**, the part of the groove peripheral wall **194** of the second flow channel groove **190** is adjacent to the part of the groove peripheral wall **183** of the first flow channel groove **180** in the first direction X, so that it is possible that the communication hole **193** is disposed on the groove peripheral wall **195** of the second flow channel groove **190**, so that the second flow channel groove **190** can communicate with the first flow channel groove **180**.

[0284] In this embodiment, the communication hole **193** penetrates, in the first direction X, the part

of the groove peripheral wall **194** of second flow channel groove **190** and the part of the groove peripheral wall **183** of the first flow channel groove **180** that are adjacent to each other. In this way, the first flow channel **181** in the first flow channel groove **180** communicate with the second flow channel **191** in the second flow channel groove **190**, so that the coolant in the first flow channel **181** flows into the second flow channel **191**. A flow path between the first flow channel **181** and the second flow channel **191** is shortened.

[0285] In an embodiment, the groove peripheral wall **195** of the second flow channel groove **190** includes the communication hole **193**, and the communication hole **193** is configured to communicate with the first flow channel groove **180**. As shown in FIG. **14**, FIG. **15**, and FIG. **16**, a part of a groove bottom wall **196** of the second flow channel groove **190** is adjacent to a part of a groove bottom wall **184** of the first flow channel groove **180** in the third direction Z. The communication hole **193** penetrates, in the third direction Z, the part of the groove bottom wall **196** of the second flow channel groove **190** and the part of the groove bottom wall **184** of the first flow channel groove **180** that are adjacent to each other.

[0286] In this embodiment, the communication hole **193** communicates the first flow channel groove **180** with the second flow channel groove **190**, so that the coolant in the first flow channel **181** can flow into the second flow channel **191** from the communication hole **193**. This facilitates circulation of the coolant in the power supply apparatus **100** and helps improve a fusion degree of the power supply apparatus **100**.

[0287] In this embodiment, the groove bottom **192** of the first flow channel groove **180** is located on the lower surface of the bottom plate **120**, the groove bottom **192** of the second flow channel groove **190** is located on the upper surface of the bottom plate **120**, and the part of the groove bottom wall **196** of the second flow channel groove **190** is adjacent to the part of the groove bottom wall **184** of the first flow channel groove **180** in the third direction Z. This provides space for the coolant in the first flow channel **181** in the first flow channel groove **180** to flow into the second flow channel **191** in the second flow channel groove **190**.

[0288] In this embodiment, the communication hole **193** penetrates, in the third direction Z, the part of the groove bottom wall **196** of the second flow channel groove **190** and the part of the groove bottom wall **184** of the first flow channel groove **180** that are adjacent to each other, so that the coolant in the first flow channel **181** can flow into the second flow channel **191** through the communication hole **193**, and a flow path between the first flow channel **181** and the second flow channel **191** is shortened. This helps improve the overall fusion degree in the power supply apparatus **100**.

[0289] In an embodiment, the communication hole **193** includes two parts. As shown in FIG. **14**, FIG. **15**, and FIG. **16**, one part of the communication hole **193** penetrates, in the third direction Z, the part of the groove bottom wall **196** of the second flow channel groove **190** and the part of the groove bottom wall **184** of the first flow channel groove **180** that are adjacent to each other. The other part of the communication hole **193** penetrates, in the first direction X, the part of the groove peripheral wall **194** of second flow channel groove **190** and the part of the groove peripheral wall **183** of the first flow channel groove **180** that are adjacent to each other. In other words, the communication hole **193** enables a cooling medium to flow from the first flow channel groove **190** into the second flow channel groove **180** in the third direction Z, and also enables the cooling medium to flow from the first flow channel groove **190** into the second flow channel groove **180** in the first direction X. A speed at which the cooling medium flows from the first flow channel groove **190** into the second flow channel groove **180** is increased, and heat exchange efficiency is increased.

[0290] In an embodiment, the peripheral side wall **112** of the integrated groove housing **110** includes the liquid inlet **115**, the bottom plate **120** includes the liquid outlet **116**, and the groove peripheral wall **195** of the second flow channel groove **190** includes the communication hole **193**. As shown in FIG. **14**, the liquid inlet **115** is configured to communicate with the radiator **105** and

the first flow channel groove **180**, the liquid outlet **116** is configured to communicate with the second flow channel **191**, and the communication hole **193** is configured to communicate with the first flow channel groove **180** and the second flow channel groove **190**. The liquid outlet **116**, the communication hole **193**, and the liquid inlet **115** are sequentially spaced in the first direction X. The liquid outlet **116** penetrates the groove bottom **192** of the second flow channel groove **190** in the third direction Z. An opening of the liquid inlet **115** in the first direction X faces from an inner cavity of the integrated groove housing **110**.

[0291] In this embodiment, the liquid inlet **115** is located on the peripheral side wall **112** of the integrated groove housing **110**, to facilitate arrangement of an external cooling pipe connected to the liquid inlet **115**. The liquid outlet **116** is located on the bottom plate **120** of the integrated groove housing **110**. This helps the heated coolant flow out of the power supply apparatus **100** in a gravity direction and helps reduce a power loss.

[0292] In this embodiment, the liquid inlet **115** is configured to communicate with the radiator **105** and the first flow channel groove **180**, and the coolant in the vehicle cooling system flows into the radiator **105** and the first flow channel groove **180** from the liquid inlet **115**, so that the coolant in the radiator **105** and the coolant in the first flow channel groove **180** simultaneously cool the upper-layer circuit board **150**. This helps improve cooling efficiency of the power supply apparatus **100**. The liquid outlet **116** is configured to communicate with the second flow channel **191**, so that the coolant in the second flow channel **191** can flow out of the power supply apparatus **100** from the liquid outlet **116**. The coolant from the vehicle cooling system sequentially flows through the liquid inlet **115**, the first flow channel **181**, the communication hole **193**, the second flow channel **191**, and the liquid outlet **116**, or sequentially flows through the liquid inlet **115**, the radiator **105**, the first flow channel **181**, the communication hole **193**, the second flow channel **191**, and the liquid outlet **116**.

[0293] In this embodiment, the liquid outlet **116**, the communication hole **193**, and the liquid inlet **115** are sequentially spaced in the first direction X, so that the first flow channel **181** and the second flow channel **191** are arranged in the first direction X, and the coolant smoothly flows through the liquid inlet **115**, the communication hole **193**, and the liquid outlet **116** in sequence.

[0294] In this embodiment, the liquid outlet **116** penetrates the groove bottom **192** of the second flow channel groove **190** in the third direction Z, so that the external cooling pipe **116a** (as shown in FIG. 3) connected to the liquid outlet **116** is disposed below the power supply apparatus **100** in the third direction Z, and the coolant flow out of the power supply apparatus **100** from the groove bottom **192** of the second flow channel groove **190** in the gravity direction, thereby reducing a power loss. The opening of the liquid inlet **115** faces away from the inner cavity of the integrated groove housing **110** in the first direction X, to facilitate connection and mounting of the external pipe connected to the liquid inlet **115**.

[0295] In an embodiment, the liquid inlet **115** is located on the second side wall **112b** of the integrated groove housing **110**.

[0296] In an embodiment, the first flow channel groove **180** includes a separation rib **187**. As shown in FIG. 13, the separation rib **187** is configured to separate the first flow channel groove **180** into two flow channel sub-grooves **185** and **186**, and the two flow channel sub-grooves **185** and **186** are spaced in the second direction Y. An inlet **185a** of one flow channel sub-groove **185** is configured to communicate with the liquid inlet **115** through an internal oil channel of the integrated groove housing **110**, the other flow channel sub-groove **186** is configured to communicate with the outlet **105b** (as shown in FIG. 6) of the radiator **105** through the internal oil channel of the integrated groove housing **110**, and outlets **185b** and **186b** (as shown in FIG. 13) of the two flow channel sub-grooves **185** and **186** are configured to communicate with the communication hole **193** of the second flow channel groove **190**.

[0297] In this embodiment, the separation rib **187** is fastened to the lower surface of the bottom plate **120** and extends in the third direction Z, and the separation rib **187** separates the first flow

channel groove **180** into two flow channel sub-grooves **185** and **186**, so that the coolant input into the liquid inlet **115** flows through one of the flow channel sub-grooves **185** in a more centralized manner. A flowing speed of the coolant in the one flow channel sub-groove **185** is increased, so that a coolant with a low temperature is continuously input into the flow channel sub-groove **185**. This helps improve cooling efficiency of the power supply apparatus **100**. In addition, when the coolant input from the liquid inlet **115** is input into the radiator **105**, the coolant in the radiator **105** may flow out of the power supply apparatus **100** through the another flow channel sub-groove **186**.

[0298] In this embodiment, the coolant from the vehicle cooling system may flow out of the power supply apparatus **100** through the liquid inlet **115**, the inlet **185a** of the one flow channel sub-groove **185**, the one flow channel sub-groove **185**, the outlet **185b** of the one flow channel sub-groove **186**, the communication hole **193**, the second flow channel groove **190**, and the liquid outlet **116** in sequence. The coolant may flow out of the power supply apparatus **100** through the liquid inlet **115**, the radiator **105**, the outlet **105b** of the radiator **105**, the other flow channel sub-groove **186**, the outlet **186b** of the other flow channel sub-groove **186**, the communication hole **193**, the second flow channel groove **190**, and the liquid outlet **116** in sequence. The first flow channel groove **180** is separated into the two flow channel sub-grooves **185** and **186**. When the coolant flowing in the other flow channel sub-groove **186** is a coolant whose temperature increases in the radiator **105**, it can be ensured that the coolant in the flow channel sub-groove **185** is a coolant with a low temperature that is directly from the vehicle cooling system. This helps ensure cooling effect of the first flow channel groove **180** on the upper-layer circuit board **150**.

[0299] As shown in FIG. 5, the inlet **105a** of the radiator **105** and the outlet **105b** of the radiator **105** respectively communicate with the inlet **185a** (as shown in FIG. 13) of the flow channel sub-groove **185** and the inlet **186a** of the another flow channel sub-groove **186** of the first flow channel groove **180** through a communication structure **129**.

[0300] In an embodiment, the communication structure **129** is located inside the integrated groove housing **110**, and the communication structure **129** is fastened to the bottom plate **120** and the second side wall **112b**. The communication structure **129** is configured to communicate the liquid inlet **115**, the inlet **105a** and the outlet **105b** of the radiator **105**, the inlet **185a** of the one flow channel sub-groove **185**, and the inlet **186a** of the other flow channel sub-groove **186**. The communication structure **129** is sealed and fastened to the radiator **105** by using a sealing ring, to prevent the coolant from leaking, so that operating of the electrical component is not affected.

[0301] Refer to FIG. 12 and FIG. 13. The bottom plate **120** further includes a power distribution groove **121**, a bus capacitor groove **122**, and a three-phase connector mounting hole **111f**. The power distribution groove **121** is configured to accommodate a copper bar of the power distribution unit **103**, the bus capacitor groove **122** is configured to accommodate a bus capacitor **163** of the motor control unit **101**, and the three-phase connector mounting hole **111f** is configured to fasten a connector **177** between the motor control unit **101** and a motor winding. The three-phase connector mounting hole **111f**, the second flow channel groove **190**, the bus capacitor groove **122**, and the power distribution groove **121** are sequentially arranged in the second direction Y.

[0302] In this embodiment, the three-phase connector mounting hole **111f**, the second flow channel groove **190**, the bus capacitor groove **122**, and the power distribution groove **121** are sequentially arranged in the second direction Y. This helps regular arrangement of electrical components on the power supply apparatus **100**. A three-phase copper bar component **177**, the power module **164**, the bus capacitor **163**, and the copper bar of the power distribution unit **103** are sequentially arranged in the second direction Y. This helps cool the power module **164** by using the coolant in the second flow channel groove **190**.

[0303] In this embodiment, the second flow channel groove **190** and the power distribution groove **121** are separated through the bus capacitor groove **122**, to prevent a cooling medium penetrating the second flow channel groove **190** in an extreme case from affecting power transmission of the copper bar in the power distribution groove **121**, and ensure cooling effect and stability of

transmission power of the copper bar.

[0304] In an embodiment, the bottom plate **120** further includes the communication connector mounting hole **111g**, and the communication connector mounting hole **111g** is configured to fasten the connector **178** between the vehicle control unit **104** and the vehicle-mounted load. Refer to FIG. **12** and FIG. **13**. The communication connector mounting hole **111g**, the second flow channel groove **190**, and the first flow channel groove **180** are sequentially arranged in the first direction X.

[0305] In this embodiment, the communication connector mounting hole **111g** is configured to fasten the connector **178** between the vehicle control unit **104** and the vehicle-mounted load. The vehicle control unit **104** is configured to transmit a communication signal of the vehicle-mounted load to the power supply apparatus **100**, to control the power supply apparatus **100**. The communication connector mounting hole **111g**, the second flow channel groove **190**, and the first flow channel groove **180** are sequentially arranged in the first direction X, to facilitate arrangement and normalization of the electrical components on the power supply apparatus **100**. The liquid outlet **116** is located between the second flow channel groove **190** and the communication connector mounting hole **111g**, so that when the coolant in the first flow channel groove **180** and the coolant in the second flow channel groove **190** are discharged from the external cooling pipe **116a** connected to the liquid outlet **116**, the external cooling pipe **116a** connected to the liquid outlet **116** does not occupy too much space of the power supply apparatus **100** in the first direction X. This facilitates a compact layout of the powertrain **10** and optimizes vehicle performance.

[0306] In this embodiment, the communication connector mounting hole **111g** and the three-phase connector mounting hole **111f** are distributed on two adjacent sides of the second flow channel groove **190**, so that the cooling medium of the second flow channel groove **190** can absorb heat of the connectors **178** and **177** in the communication connector mounting hole **111g** and the three-phase connector mounting hole **111f**, to cool the connectors **178** and **177** in the communication connector mounting hole **111g** and the three-phase connector mounting hole **111f**. This helps signal transmission of the communication connector **178** in the communication connector mounting hole **111g** be more stable and helps the connector **177** in the three-phase connector mounting hole **111f** transmit power more quickly, to avoid heat generation.

[0307] In an embodiment, the upper surface of the bottom plate **120** further includes a transformer groove **123**, an inductor groove **124**, and a direct current filter groove **125**. Refer to FIG. **12** and FIG. **13**. At least one of the transformer groove **123**, the inductor groove **124**, and the direct current filter groove **125** in the third direction Z is stacked between the first flow channel groove **180** and the upper-layer circuit board **150**. The transformer groove **123**, the inductor groove **124**, the direct current filter groove **125**, and the first flow channel groove **180** are arranged on a same side of the second flow channel groove **190** in the first direction X.

[0308] In this embodiment, the transformer groove **123** and the inductor groove **124** are arranged in the second direction Y, and the transformer groove **123** and the direct current filter groove **125** are arranged in the first direction X. The transformer groove **123** is configured to accommodate the transformer **141d** of the on-board charger **141**, the inductor groove **124** is configured to accommodate the plurality of inductors **141b** in the on-board charger **141**, and the direct current filter groove **125** is configured to accommodate the magnetic component in the direct current filter **146**. A layout of the transformer groove **123**, the inductor groove **124**, and the direct current filter groove **125** can improve structural firmness of the integrated groove housing **110**. This helps improve stability of the power supply apparatus **100** and reduce electrical impact between module components.

[0309] In this embodiment, at least one of the transformer groove **123**, the inductor groove **124**, and the direct current filter groove **125** is stacked between the first flow channel groove **180** and the upper-layer circuit board **150** in the third direction Z. This helps the coolant in the first flow channel groove **180** cool at least one of the transformer **141d** of the on-board charger **141**, the plurality of inductors **141b** of the on-board charger **141**, and the magnetic component in the direct

current filter **146**.

[0310] In this embodiment, the transformer groove **123**, the inductor groove **124**, the direct current filter groove **125**, and the first flow channel groove **180** are arranged on a same side of the second flow channel groove **190** in the first direction X. This helps arrange the transformer **141d** of the on-board charger **141**, the plurality of inductors **141b** in the on-board charger **141**, and the magnetic component in the direct current filter **146** on the lower surface of the upper-layer circuit board **150**. This helps improve integration and fusion of the power supply apparatus **100**, and further helps the first flow channel groove **180** cool the transformer **141d** of the on-board charger **141** in the transformer groove **123**, the plurality of inductors **141b** in the on-board charger **141** in the inductor groove **124**, and the magnetic component in the direct current filter **146** in the direct current filter groove **125**. In this way, cooling of the power supply apparatus **100** is implemented, and stable running of the power supply apparatus **100** is ensured.

[0311] The foregoing describes in detail the all-in-one power supply apparatus, the all-in-one powertrain, and the electric vehicle that are provided in the embodiments. Specific examples are used to describe principles and embodiments, and the foregoing embodiments are merely used to help understand the methods and core ideas of the embodiments. In addition, based on these methods and ideas, a person of ordinary skill in the art may make modifications to the specific embodiments without departing from their scope. Thus, the content of the embodiments shall not be construed as a limitation on their scope.

Claims

1. A power supply apparatus configured to: charge and discharge a battery, and drive a motor, wherein the power supply apparatus comprises: an integrated groove housing comprising a bottom plate, wherein the bottom plate comprises a first flow channel and a second flow channel arranged in a first direction; a radiator, wherein the first flow channel is configured to communicate with the second flow channel and the radiator; an upper-layer circuit board, wherein the first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in a third direction, and the first flow channel and the radiator are configured to cool an electrical component in an on-board charger carried on the upper-layer circuit board; and a lower-layer circuit board, wherein the second flow channel and the lower-layer circuit board are stacked in the third direction, and the second flow channel is configured to cool a power module of a motor control unit carried on a lower surface of the lower-layer circuit board.
2. The power supply apparatus according to claim 1, wherein the first flow channel is configured to cool at least one of a transformer, a plurality of inductors, and a plurality of capacitors in the on-board charger carried on a lower surface of the upper-layer circuit board, and the radiator is configured to cool a plurality of power switching transistors of the on-board charger carried on an upper surface of the upper-layer circuit board.
3. The power supply apparatus according to claim 1, wherein the lower-layer circuit board further comprises: a primary region, wherein a lower surface of the primary region is configured to fasten the power module of the motor control unit; and a secondary region configured to fasten at least a part of power switching transistors of a direct current converter, wherein; the primary region and the secondary region are arranged in the first direction; the first flow channel, the secondary region, and the upper-layer circuit board are stacked in the third direction; and the second flow channel and the primary region are stacked in the third direction.
4. The power supply apparatus according to claim 1, wherein the bottom plate further comprises: a first flow channel groove recessed in the third direction from a lower surface of the bottom plate to the upper-layer circuit board and configured to form the first flow channel; and a second flow channel groove recessed in the third direction from an upper surface of the bottom plate and away from the lower-layer circuit board, configured to form the second flow channel.

5. The power supply apparatus according to claim 4, wherein, in the third direction, a spacing between a groove bottom of the first flow channel groove and the radiator is less than a spacing between a groove bottom of the second flow channel groove and the radiator.
6. The power supply apparatus according to claim 4, wherein a length of the first flow channel groove in the first direction is greater than a length of the second flow channel groove in the first direction, and a length of the first flow channel groove in the second direction is greater than a length of the second flow channel groove in the second direction.
7. The power supply apparatus according to claim 4, wherein a groove peripheral wall of the second flow channel groove further comprises: a communication hole configured to communicate with the first flow channel groove, a part of the groove peripheral wall of the second flow channel groove is adjacent to a part of a groove peripheral wall of the first flow channel groove in the first direction,; and the communication hole penetrates, in the first direction, the part of the groove peripheral wall of the second flow channel groove and the part of the groove peripheral wall of the first flow channel groove that are adjacent to each other.
8. The power supply apparatus according to claim 4, wherein a groove peripheral wall of the second flow channel groove further comprises: a communication hole configured to communicate with the first flow channel groove, a part of a groove bottom wall of the second flow channel groove is adjacent to a part of a groove bottom wall of the first flow channel groove in the third direction, and the communication hole penetrates, in the third direction, the part of the groove bottom wall of the second flow channel groove and the part of the groove bottom wall of the first flow channel groove that are adjacent to each other.
9. The power supply apparatus according to claim 4, wherein a peripheral side wall of the integrated groove housing further comprises: a liquid inlet, the bottom plate further comprises: a liquid outlet, the groove peripheral wall of the second flow channel groove comprises: a communication hole, the liquid inlet is configured to communicate with the radiator and the first flow channel groove, the liquid outlet is configured to communicate with the second flow channel, the communication hole is configured to communicate with the first flow channel groove and the second flow channel groove,; the liquid outlet, the communication hole, and the liquid inlet are sequentially spaced in the first direction, the liquid outlet penetrates the groove bottom of the second flow channel groove in the third direction, and an opening of the liquid inlet faces away from an inner cavity of the integrated groove housing in the first direction.
10. The power supply apparatus according to claim 9, wherein the first flow channel groove further comprises: a separation rib configured to separate the first flow channel groove into two flow channel sub-grooves spaced in a second direction, an inlet of a first flow channel sub-grooves is configured to communicate with the liquid inlet through an internal oil channel of the integrated groove housing, a second flow channel sub-grooves is configured to communicate with an outlet of the radiator through the internal oil channel of the integrated groove housing, and outlets of the two flow channel sub-grooves are configured to communicate with the communication hole of the second flow channel groove.
11. The power supply apparatus according to claim 4, wherein the bottom plate further comprises: a power distribution groove configured to accommodate a copper bar of a power distribution unit; a bus capacitor groove configured to accommodate a bus capacitor of the motor control unit; and a three-phase connector mounting hole configured to fasten a connector between the motor control unit and a motor winding, wherein; the three-phase connector mounting hole, the second flow channel groove, the bus capacitor groove, and the power distribution groove are sequentially arranged in the second direction.
12. The power supply apparatus according to claim 4, wherein the bottom plate further comprises: a communication connector mounting hole configured to fasten a connector between a vehicle control unit and a vehicle-mounted load, and the communication connector mounting hole, the second flow channel groove, and the first flow channel groove are sequentially arranged in the first

direction.

13. The power supply apparatus according to claim 4, wherein the upper surface of the bottom plate further comprises: a transformer groove configured to accommodate the transformer of the on-board charger; an inductor groove configured to accommodate the plurality of inductors in the on-board charger; and a direct current filter groove configured to accommodate a magnetic component in a direct current filter; at least one of the transformer groove, the inductor groove, the direct current filter groove is stacked between the first flow channel groove and the upper-layer circuit board in the third direction; and the transformer groove, and the inductor groove, the direct current filter groove, and the first flow channel groove are arranged on a same side of the second flow channel groove in the first direction.

14. The power supply apparatus according to claim 13, wherein in the third direction, a spacing between a groove bottom of the first flow channel groove and the radiator is less than a spacing between a groove bottom of the second flow channel groove and the radiator.

15. The power supply apparatus according to claim 13, wherein a length of the first flow channel groove in the first direction is greater than a length of the second flow channel groove in the first direction, and a length of the first flow channel groove in the second direction is greater than a length of the second flow channel groove in the second direction.

16. The power supply apparatus according to claim 13, wherein a groove peripheral wall of the second flow channel groove further comprises: a communication hole configured to communicate with the first flow channel groove, a part of the groove peripheral wall of the second flow channel groove is adjacent to a part of a groove peripheral wall of the first flow channel groove in the first direction; and the communication hole penetrates, in the first direction, the part of the groove peripheral wall of the second flow channel groove and the part of the groove peripheral wall of the first flow channel groove that are adjacent to each other.

17. The power supply apparatus according to claim 13, wherein a groove peripheral wall of the second flow channel groove further comprises: a communication hole, configured to communicate with the first flow channel groove, a part of a groove bottom wall of the second flow channel groove is adjacent to a part of a groove bottom wall of the first flow channel groove in the third direction; and the communication hole penetrates, in the third direction, the part of the groove bottom wall of the second flow channel groove and the part of the groove bottom wall of the first flow channel groove that are adjacent to each other.

18. The power supply apparatus according to claim 13, wherein a peripheral side wall of the integrated groove housing further comprises: a liquid inlet, the bottom plate further comprises: a liquid outlet, the groove peripheral wall of the second flow channel groove further comprises the communication hole, the liquid inlet is configured to communicate with the radiator and the first flow channel groove, the liquid outlet is configured to communicate with the second flow channel, the communication hole is configured to communicate with the first flow channel groove and the second flow channel groove,; the liquid outlet, the communication hole, and the liquid inlet are sequentially spaced in the first direction,; the liquid outlet penetrates the groove bottom of the second flow channel groove in the third direction, and an opening of the liquid inlet faces away from an inner cavity of the integrated groove housing in the first direction.

19. A powertrain comprising: a motor; a reducer, wherein a motor shaft of the motor is in transmission connection to an input shaft of the reducer; and a power supply apparatus connected to a winding of the motor through a motor control unit to drive the motor, wherein the power supply apparatus is configured to: charge and discharge a battery and comprises: an integrated groove housing comprising a bottom plate that comprises a first flow channel and a second flow channel arranged in a first direction; a radiator, wherein the first flow channel is configured to communicate with the second flow channel and the radiator; an upper-layer circuit board, wherein the first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in a third direction and the first flow channel and the radiator are configured to cool an electrical

component in an on-board charger carried on the upper-layer circuit board; and a lower-layer circuit board, wherein the second flow channel and the lower-layer circuit board are stacked in the third direction and the second flow channel is configured to cool a power module of a motor control unit carried on a lower surface of the lower-layer circuit board.

20. An electric vehicle comprising: a vehicle frame; a power battery; and a powertrain, wherein the vehicle frame is configured to fasten the power battery and the powertrain and the powertrain comprises: a motor, a reducer, and a power supply apparatus, the power battery is configured to connect to the power supply apparatus, a motor shaft of the motor is in transmission connection to an input shaft of the reducer, the power supply apparatus is connected to a winding of the motor through a motor control unit to drive the motor, the power supply apparatus is configured to: charge and discharge a battery; and the power supply apparatus comprises: an integrated groove housing comprising, a bottom plate that comprises a first flow channel and a second flow channel arranged in a first direction; a radiator, wherein the first flow channel is configured to communicate with the second flow channel and the radiator and the first flow channel, the upper-layer circuit board, and the radiator are sequentially stacked in a third direction; an upper-layer circuit board, wherein the first flow channel and the radiator are configured to cool an electrical component in an on-board charger carried on the upper-layer circuit board; and a lower-layer circuit board, wherein the second flow channel and the lower-layer circuit board are stacked in the third direction and the second flow channel is configured to cool a power module of a motor control unit carried on a lower surface of the lower-layer circuit board.
