US Patent & Trademark Office Patent Public Search | Text View

United States Patent

Kind Code

B2
Date of Patent

Inventor(s)

12384994

August 12, 2025

Hyland; Callen Elizabeth et al.

Gel tray for bacteria transformation lab

Abstract

A gel tray for a bacterial transformation lab exercise has a plastic body with four parallel gel channels and four filling ports, one for each channel into which unmodified bacteria and heat-shocked bacteria can be injected by students along with appropriate reaction constituents to demonstrate transformation of the bacteria under visualization. A seal may be provided to seal the tops of the gel channels and a lid can cover the gel tray during incubation.

Inventors: Hyland; Callen Elizabeth (La Jolla, CA), Schroeder; Christopher Karl (San

Diego, CA), Wong; Rita Mei Yi (San Diego, CA), Chan; Richard Tat Lee (La

Jolla, CA)

Applicant: C.C. Imex (San Diego, CA)

Family ID: 1000008750791

Assignee: C.C. Imex (San Diego, CA)

Appl. No.: 18/408908

Filed: January 10, 2024

Prior Publication Data

Document IdentifierUS 20240141271 A1

Publication Date
May. 02, 2024

Related U.S. Application Data

continuation parent-doc US 17315290 20210508 US 11879118 child-doc US 18408908 continuation-in-part parent-doc US 17094222 20201110 US 11879117 child-doc US 17315290

Publication Classification

Int. Cl.: C12M1/12 (20060101); C12M1/00 (20060101)

U.S. Cl.:

CPC **C12M23/04** (20130101); **C12M23/26** (20130101); **C12M23/34** (20130101);

C12M23/38 (20130101); C12M37/04 (20130101); C12M45/22 (20130101);

Field of Classification Search

CPC: C12M (23/04); C12M (23/26); C12M (23/34); C12M (23/38); C12M (37/04); C12M

(45/22)

USPC: 435/288.3

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4054490	12/1976	Vesterberg	435/304.2	C12M 23/34
4204045	12/1979	Kjellander et al.	N/A	N/A
4271270	12/1980	Lukacsek	435/305.3	C12M 23/38
6649406	12/2002	Williams	435/39	C12M 23/04
11879118	12/2023	Hyland	N/A	C12M 23/22
2014/0196550	12/2013	Chernomorsky	73/864.91	C12M 23/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204065013	12/2003	CN	N/A
106591127	12/2016	CN	N/A
0402888	12/1989	EP	N/A

Primary Examiner: Hobbs; Michael L

Assistant Examiner: Abel; Lenora A

Background/Summary

FIELD

- (1) This application relates to gel trays for bacterial growth, including genetic transformation labs. BACKGROUND
- (2) The present assignee's U.S. Pat. No. 9,835,587, incorporated herein by reference, discloses a commercially successful electrophoresis running tank assembly for use in the classroom to aid students in learning modern DNA assay techniques.

SUMMARY OF THE INVENTION

(3) Present principles are directed to a plastic tray with plural channels to hold bacterial growth medium for the purpose of viewing bacterial growth or behavior. Current methods of growing bacteria are generally intended for professional laboratory personnel. The protocol and process are time consuming, cumbersome, and unreliable for high school education. Students need a system that allows them to reliably get the intended results while performing steps that mirror everyday

biotech research and development.

- (4) One application is observing the results of bacterial transformation, the introduction of new behavior in bacteria through the introduction of foreign DNA. This behavior can include antibiotic resistance, fluorescence, or production of a desired protein. Introduction of antibiotic resistance into a previously antibiotic sensitive bacteria strain via DNA is a seminal discovery that forms an important foundation of biotechnology. The importance of bacterial transformation in the field of biotechnology makes it a key concept to be taught in high schools and colleges. Control of gene expression is also an important concept in biotechnology.
- (5) Accordingly, a gel tray assembly includes a gel tray body that defines a top surface. Plural gel channels are formed in the gel tray body parallel to each other, with at least first and second of the gel channels being separated from each other by a rib defining a top surface. Also, plural filling ports are provided, each having a fill end for receiving samples and a channel end communicating with an end of a respective one of the gel channels. Each filling port defines an axis from the respective fill end to the respective channel end. A flexible sheet is disposed on the top surface of the gel tray body and on the top surface of the rib and covering the gel channels and filling ports while preventing fluid communication between the gel channels.
- (6) In some examples an oblique angle is established between the axis of at least one of the filling ports and a longitudinal axis of its respective gel channel.
- (7) In example implementations the fill ends are elevated above the channel ends on the body.
- (8) If desired, at least one constituent can be in the gel channels to deter the growth of microbes during storage.
- (9) Respective gels may be disposed in the gel channels.
- (10) In example embodiments a lid covers the flexible sheet and the gel tray body. The gel tray body may be regarded as a first gel tray body and the lid defines a top surface comprising plural parallel ribs for receiving, between adjacent ribs, gel channels of a second gel tray body. The second gel tray body may be part of the assembly, disposed on the top surface of the lid.
- (11) In another aspect, a method includes adding gel to each of plural receptacles in a gel tray and preventing fluid communication between the receptacles regardless of an orientation of the gel tray.
- (12) In another aspect, a gel tray, e.g., for a bacteria transformation observation includes a plastic body with plural (e.g., from two to ten and in specific examples four) parallel gel channels into which unmodified bacteria and genetically modified bacteria can be added along with appropriate reaction constituents to demonstrate transformation of the bacteria under visualization. A seal is placed on top surfaces of the plastic body and gel channels to prevent fluid communication between the gel channels.
- (13) The details of the present application, both as to its structure and operation, can best be understood in reference to the accompanying drawings, in which like reference numerals refer to like parts, and in which:

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. **1** is an isometric view of the gel tray when empty from a top perspective;
- (2) FIG. $\bf 2$ is an isometric view of the gel tray when empty from a bottom perspective;
- (3) FIG. **3** is an isometric view of the gel tray when filled with gel and covered with film;
- (4) FIG. 4 is an isometric view of the gel tray in a viewer;
- (5) FIG. **5** is an isometric view of the gel tray on a viewer base;
- (6) FIG. **6** shows colonies of genetically modified bacteria, transformed with a plasmid containing the gene for eGFP, growing in plastic tubes containing LB medium agar with chloramphenicol, ampicillin, and IPTG;

- (7) FIG. **7** shows colonies of genetically modified bacteria, transformed with a plasmid containing the gene for eGFP, growing on a petri dish containing LB medium agar with chloramphenicol, ampicillin, and IPTG;
- (8) FIG. **8** is an isometric view of an alternate embodiment;
- (9) FIGS. **9** and **10** illustrate an alternate embodiment;
- (10) FIG. 11 is a perspective of yet another embodiment of the gel tray; and
- (11) FIG. **12** is an exploded perspective view of the gel tray shown in FIG. **11**, a seal, a lid, and a second gel tray that can stack on the lid.

DETAILED DESCRIPTION

- (12) Referring initially to FIGS. **1** and **2**, an assembly is shown, generally designated **10**, which can be used for observing bacterial growth, is particularly, although not exclusively suited for academic use by students. The assembly **10** includes a plastic body **12** which in some embodiments may be transparent, with a generally parallelepiped-shaped periphery **14** in an x-y (horizontal) plane indicated by the axes **16** that is established when the body **12** is oriented as operationally intended on a viewing assembly as discussed further below. The body **12** may be a unitary piece of plastic formed by, e.g., injection molding.
- (13) In the example shown, first through fourth gel channels 18, 20, 22, 24 are formed in the body **12** parallel to each other, although in other embodiments a fewer or greater number of gel channels may be used, e.g., any integer number of gel channels from two on up. The gel channels are separated from each other by raised elongated ribs **26** that are parallel to the gel channels and that are elongated in the same dimension as the gel channels are elongated. The outer gel channels 18, **24** are thus bounded by respective vertical sidewalls **28** of the body **12** and on their sides opposite the sidewalls **28** by a respective rib **26**, while the inner gel channels **20**, **22** are bounded on both sides by ribs **26**. The gel channels extend in length from a common end wall **30** to respective channel ends **32**, and the bottom walls **34** of the gel channels **18-24** lie in the horizontal plane. (14) Extending upwardly (in the z-dimension) from the horizontal gel channels at oblique angles to the horizontal plane if desired, are first through fourth filling ports 36, 38, 40, 42, each having a respective fill end 44 that may have a semi-circular circumference if desired as shown. More generally, a filling port may be provided for each gel channel. The fill ends are configured for receiving constituent samples from a dispenser such as a micropipette or multi-channel pipette. Each filling port **36-42** extends from its fill end **44** to a respective channel end **46** that communicates with a respective channel end **32** of a respective one of the gel channels. The fill ends **44** thus may be elevated above the channel ends **46** of the fill ports on the body. (15) The respective channel ends **32**, **46** of a respective gel channel/filling port pair are closely juxtaposed as shown such that constituent deposited in the fill end 44 of a filling port flows down the filling port under gravity through the channel ends **32**, **46** and into the respective gel channel. In the example shown, each filling port is elongated from end **44** to end **46** and defines an axis there between with a component 48 in the horizontal plane. As best shown in FIG. 2, an oblique angle α can be established between the axis component 48 of at least one of the filling ports and a longitudinal axis **50** of its respective gel channel.
- (16) FIG. **3** illustrates that respective gels **52** may be disposed in the first through fourth gel channels **18-24** on the bottoms thereof. The gels **52** may contain a constituent to deter the growth of microbes during storage. In one example, the gels **52** are essentially growth media and may be composed of, e.g., lysogeny broth agar that contains chloramphenicol to deter the growth of wild bacteria, yeast, or other microbes during storage.
- (17) A protective plastic sheet **56**, which may be transparent, may cover the interior of the body **12** as shown and may extend across the periphery **14** from all four sides (FIG. **3** illustrates the sheet **56** by means of shading lines.) The assembly shown in FIG. **3** may be vended to end users who can then add constituents to one or more of the gels **52** as discussed further below. Or the body **12** alone may be vended to end users who can fill the gel channels **18-24** with the gels **52**.

- (18) It may now be appreciated that the gel tray assembly **10** may include four separate pools of growth media (gels), for example, one for a control and three for variations. The body **12** of the tray can be transparent (which include translucent) to allow light to pass through the bottom **34** and into the contents of the gel channels **18-24** tray.
- (19) FIGS. **4** and **5** illustrate that the body **12** of the gel tray is designed to fit onto a base **400** of a viewing assembly such as but not limited to that described in the referenced U.S. patent, to be covered by a hood **402** such as the hood described in the referenced U.S. patent, with the base **400** including lamps to illuminate the tray assembly **10** from below and photograph the tray assembly from above through an optical filter to detect and record presence of bacteria colonies and whether or not they exhibit fluorescence. The base **400** and hood **402** alternatively may be implemented by a simpler design apart from that referenced in the U.S. patent, marketed by the instant assignee under the trade name "The WinstonTM". The body **12** of the tray assembly **10** is designed to be easily filled, sterilized, and sealed to meet storage and shipping requirement, and to be easily unsealed by removing the sheet **56** to allow a student to introduce bacterial samples and subsequently resealed to allow for effective incubation of the experiment. The base **400** or other component may include heaters and/or coolers such as thermoelectric coolers to maintain temperature of constituents in the gel tray. Also, illumination may be from the sides or even top of the gel tray in addition to or in lieu of bottom illumination.
- (20) Unmodified bacteria host cells may be disposed in the first gel channel **18** by an end user. Such cells may be, in one example, a strain (BL21) of *E. coli* bacteria that already has resistance to chloramphenicol.
- (21) In one example implementation, unmodified bacteria and an antibiotic may be added to the second gel channel **20** by an end user. For example, ampicillin may be used to demonstrate that this antibiotic will kill bacteria that have not been transformed with an ampicillin resistance gene. Antibiotics other than ampicillin may be used.
- (22) Added to the third gel channel **22** may be genetically modified bacteria such as bacteria transformed with a plasmid (vector) through heat-shocking or another method. Prior to heat-shocking, bacteria may be made competent by the addition of a chemical, for example, calcium chloride. The plasmid (vector) may include genes for making fluorescent protein molecules like eGFP (enhanced Green Florescent Protein), which glows green under blue light when the bacteria make it. The plasmid may also include an ampicillin resistance gene. That way ampicillin can be used to kill all of the bacteria that do not take up the plasmid.
- (23) Genetically modified bacteria may be added to the fourth gel channel **24** by the end user along with an antibiotic and a chemical, e.g., IPTG, to induce expression of an exogenous constituent, as described above. A plasmid vector may be incorporated which can be a plasmid developed specifically for the purpose of a lab activity that gives the bacteria resistance to ampicillin and, when activated by IPTG, induces the bacteria to produce a protein that is fluorescent (e.g., eGFP). (24) Preferably, the samples added to all gel channels are spread evenly over the surface of the agar to maximize growth. In one ambediment, the tray may be scaled again with the sheet **56** and
- to maximize growth. In one embodiment, the tray may be sealed again with the sheet **56** and incubated. In another embodiment, the user will not seal the tray before incubating. The user will place only the below-described lid over the tray, on which the lid does not create a seal, and then incubate.
- (25) FIGS. **6** and **7** illustrate results.
- (26) FIG. **8** illustrates a gel tray **800** that in all essential respects is identical in configuration and operation to the gel tray(s) shown previously with the following exception. The gel tray **800** in FIG. **8** includes tabbed corners **802** extending down and away from fill ends **804** of fill ports **806** to aid in removing the protective sheet discussed previously.
- (27) FIGS. **9** and **10** illustrate a gel tray **900** in all essential respects is identical in configuration and operation to the gel tray(s) shown previously with the following exception. The gel tray **900** in FIGS. **9** and **10** includes no separate fill ports, and includes plural (e.g., four) gel channels **902**

separated by ribs **904** and terminating in a slanted wall **906** that extends upwardly and outwardly from the ends of bottoms **908** of the gel channels **902** at an oblique angle to the bottoms **908** to terminate in a flat edge flange **910** that is generally parallel to the bottoms **908** of the channels **902**. (28) FIGS. **11** and **12** illustrate a gel tray **1100** in all essential respects identical in configuration and operation to the gel tray(s) shown previously with the following exception. The gel tray **1100** in FIGS. **11** and **12** includes first through fourth gel channels **18**A, **20**A, **22**A, **24**A formed in a body **12**A parallel to each other, although in other embodiments a fewer or greater number of gel channels may be used, e.g., any integer number of gel channels from two on up. The gel channels are separated from each other by raised elongated ribs **26**A that are parallel to the gel channels and that are elongated in the same dimension as the gel channels are elongated. The outer gel channels **18**A, **24**A are thus bounded by respective vertical sidewalls **28**A of the body **12**A and on their sides opposite the sidewalls **28**A by a respective rib **26**A, while the inner gel channels **20**A, **22**A are bounded on both sides by ribs **26**A.

- (29) In the example of FIGS. **11** and **12**, the top edges of the ribs **26**A are co-planar or substantially co-planar with the top edges of the sidewalls **28**A. A flat top load flange **1102** extends from sidewall to sidewall along one end of the body **12**A and the top surface of the flange **1102** likewise is co-planar or substantially co-planar with the top edges of the sidewalls **28**A.
- (30) When a seal **1200** (FIG. **12**) is placed over the gel channels **18**A-**24**A, the seal **1200** contacts the top surfaces of the ribs **26**A, sidewalls **28**A, and flange **1102** to establish isolation of the gel channels from each other. This facilitates incubating material in the gel channels with the body **12**A of the tray **1100** tray upside down as during manufacture and transport, preventing any condensation that might accumulate on the seal **1200** from cross contaminating among the gel channels. Thus, the gel tray may be sold with gel in the channels and the seal covering the gel. When it is desired to use the tray, the lid discussed further below is removed, the seal **1200** also is removed, and the bacteria and reagents added to the channels as described above. The lid may then be replaced onto the tray to cover the tray.
- (31) As was the case with the gel tray **800** in FIG. **8**, the gel tray **1100** in FIGS. **11** and **12** may include tabbed corners **802**A extending down and away from fill ends **804**A of fill ports **806**A to aid in removing the protective seal **1200** to facilitate removal of the seal **1200** from the body **12**A. In an example embodiment, the seal **1200** may be a rectangular plastic sheet that is flexible and that is continuously solid between its rectangular edges to completely cover the gel channels and fill ports. The seal **1200** may be sized as shown to extend completely over the body **12** but not overlap past the periphery of the body **12**.
- (32) As alluded to above, a rigid plastic lid **1202** also may be provided. The lid **1202** may be sized to fit over the gel tray **1100** with the seal **1200** sandwiched between the top edges of the gel tray and the bottom flat surface of the lid **1202**. The lid may snappingly engage the body or fit over the edges of the body in an interference fit. In an example embodiment, the bottom left and right edges of the lid **1202** are formed with respective parallel U-shaped (in transverse cross-section) flanges **1203** that slidably engage respective sidewalls **28**A of the gel tray, such that the lid **1202** can be advanced onto the sidewalls **28**A, e.g., from the rear, and slid over the seal **1200** and gel tray **1100** until a **1212** (described further below) clears the front edge of the gel tray **1100**, at which point the **1212** snaps down under material bias over the front edge of the gel tray.
- (33) The top surface of the lid **1202** may be formed with plural elongated raised ribs **1204** that establish a frame with cavities **1206** to receive the bottoms of respective gel channels **1208** of a second gel tray **1210**, with the bottoms of the gel channels **1208** of the second gel tray **1210** closely fitting in respective cavities **1206** of the frame established by the ribs **1204** of the lid **1202**. In this way, gel trays can be stacked one on top of the other.
- (34) The gel tray **1100** may be configured such that it can fit on the lid in only one direction. As discussed above, the lid **1202** may also include a tab **1212** that extends down in the opposite direction that the ribs **1206** extend up, to prevent accidental sliding out of the tray once the tab

1212 clears the front edge of the gel tray and snaps down over the front edge. Once the lid is completely slid on to the gel tray, a rear wall **1214** of the lid **1202** abuts the rear edge **1216** of the gel tray to trap the gel tray between the tab **1212** and rear wall **1214** of the lid. The seal can be removed from the gel tray and the lid can be re-engaged with the gel tray when the seal is removed. (35) While particular structures and techniques are herein shown and described in detail, it is to be understood that the subject matter which is encompassed by the present invention is limited only by the claims.

Claims

- 1. An apparatus comprising: a body; plural channels formed in the body; plural filling ports each having a fill end for receiving samples and a channel end communicating with an end of a respective one of the channels, each filling port defining an axis from the respective fill end to the respective channel end, bottom walls of the channels lying in a common plane, the filling ports extending upwardly from the channels at oblique angles to the common plane, the fill ends being elevated above the channel ends, each filling port being elongated from end to end; and a lid comprising left and right edges formed with respective flanges that slidably engage respective sidewalls of the body, such that the lid can be advanced onto the sidewalls and slid over the body.
- 2. The apparatus of claim 1, wherein the channels are separated from each other by raised elongated ribs that are parallel to the channels and that are elongated in a same dimension as the channels are elongated such that outer channels are bounded by respective vertical sidewalls of the body and on their sides opposite the sidewalls by a respective rib, while inner channels are bounded on both sides by ribs, the channels extending in length from a common end wall of the body to respective channel ends.
- 3. The apparatus of claim 1, wherein at least one fill end has a curvilinear circumference.
- 4. The apparatus of claim 1, comprising at least one constituent in the channels to deter the growth of microbes during storage.
- 5. The apparatus of claim 1, comprising respective gels in the channels.
- 6. The apparatus of claim 5, comprising unmodified bacteria host cells in a first one of the channels.
- 7. The apparatus of claim 5, comprising unmodified bacteria host cells and an antibiotic in a second one of the channels.
- 8. The apparatus of claim 5, comprising genetically modified bacteria host cells and a plasmid in a third one of the channels.
- 9. The apparatus of claim 5, comprising genetically modified bacteria host cells, an antibiotic, and a chemical to induce exogenous expression in a fourth one of the channels.
- 10. The apparatus of claim 1, wherein an oblique angle is established between the axis of at least one of the filling ports and a longitudinal axis of its respective channel.
- 11. A device comprising: a body; plural channels formed in the body; and plural filling ports each having a fill end for receiving samples and a channel end communicating with an end of a respective one of the channels, each filling port defining an axis from the respective fill end to the respective channel end, bottom walls of the channels lying in a common plane, a continuous oblique angle being established between the axis of at least one of the filling ports and a longitudinal axis of its respective channel, the fill ends being elevated above the channel ends, each filling port being elongated from end to end.
- 12. The device of claim 11, wherein the channels are separated from each other by raised elongated ribs that are parallel to the channels and that are elongated in a same dimension as the channels are elongated such that outer channels are bounded by respective vertical sidewalls of the body and on their sides opposite the sidewalls by a respective rib, while inner channels are bounded on both sides by ribs, the channels extending in length from a common end wall of the body to respective

channel ends.

- 13. The device of claim 11, wherein at least one fill end has a curvilinear circumference.
- 14. The device of claim 11, comprising respective gels in the channels.
- 15. The device of claim 11, wherein the filling ports extend upwardly from the channels at oblique angles to the common plane.
- 16. The device of claim 11, comprising a lid slidably engaged with the body.
- 17. An apparatus, comprising: a body; plural channels formed in the body and configured for receiving gel; plural filling ports each having a fill end for receiving samples and a channel end communicating with an end of a respective one of the channels; and a lid slidably engaged with the body to cover the channels.
- 18. The apparatus of claim 17, wherein the lid is configured such that it can slide onto the body in only one direction.
- 19. The apparatus of claim 17, comprising a seal sandwiched between the lid and body.
- 20. An apparatus, comprising: a body; plural channels formed in the body and configured for receiving gel; plural filling ports each having a fill end for receiving samples and a channel end communicating with an end of a respective one of the channels; and a lid slidably engaged with the body to cover the channels, wherein the lid comprises left and right edges formed with respective flanges that slidably engage respective sidewalls of the body, such that the lid can be advanced onto the sidewalls and slid over the body until a tab of the lid clears a front edge of the body.
- 21. The apparatus of claim 20, wherein tab extends in an opposite direction to a direction in which the ribs of the lid extend to prevent the lid sliding off the body once the tab clears a front edge of the body.
- 22. The apparatus of claim 21, wherein the lid is completely slid on to the body and a rear wall of the lid abuts a rear edge of the body to trap the body between the tab and rear wall of the lid.
- 23. An apparatus, comprising: a body; plural channels formed in the body and configured for receiving gel; plural filling ports each having a fill end for receiving samples and a channel end communicating with an end of a respective one of the channels; and a lid slidably engaged with the body to cover the channels, wherein the body is a first body and a top surface of the lid is formed with plural elongated raised ribs that establish cavities to receive bottoms of respective gel channels of a second body.