

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12383771
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Allan; Jason Edward et al.

---

### Adjustable support frame for a breathing apparatus

---

#### Abstract

Disclosed is an adjustable support frame for a breathing apparatus having an adjustable longitudinal dimension and a user-facing side configured to substantially overlay a user's back in use, the adjustable support frame comprising: a first frame portion and a second frame portion, the first and second frame portions being moveable relative to each other so as to adjust the longitudinal dimension; an adjustment mechanism having a locked configuration which inhibits relative movement of the first and second frame portions and an unlocked configuration which permits relative movement of the first and second frame portions; wherein the adjustment mechanism comprises one or more actuating elements which are operable to actuate the adjustment mechanism from the locked configuration to the unlocked configuration, the one or more actuating elements being provided on a surface which is substantially perpendicular to the user-facing side of the support frame.

---

**Inventors:** Allan; Jason Edward (North Shields, GB), Ferguson; Darin (Ashington, GB)

**Applicant:** DRAEGER SAFETY UK LIMITED (Blyth, GB)

**Family ID:** 1000008748643

**Assignee:** DRAEGER SAFETY UK LIMITED (Blyth, GB)

**Appl. No.:** 18/636699

**Filed:** April 16, 2024

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240252849 A1	Aug. 01, 2024

#### Foreign Application Priority Data

EP	20165380	Mar. 24, 2020
----	----------	---------------

## Related U.S. Application Data

continuation parent-doc US 17179685 20210219 US 11986685 child-doc US 18636699

---

## Publication Classification

**Int. Cl.:** A62B9/04 (20060101)

**U.S. Cl.:**

CPC A62B9/04 (20130101);

## Field of Classification Search

**CPC:** A62B (25/00); A62B (25/005); A62B (9/04); A45F (3/08); A45F (3/10); A45F (3/14)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7198186	12/2006	Kling et al.	N/A	N/A
2003/0140392	12/2002	Kling et al.	N/A	N/A
2003/0192925	12/2002	Boone	N/A	N/A
2004/0045991	12/2003	Kling et al.	N/A	N/A
2018/0117372	12/2017	Mesman	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202802556	12/2012	CN	N/A
206852939	12/2017	CN	N/A
2886621	12/2005	FR	N/A
2572971	12/2018	GB	N/A
0197916	12/2000	WO	N/A
0197917	12/2000	WO	N/A
2014140519	12/2013	WO	N/A

---

*Primary Examiner:* Skurdal; Corey N

*Attorney, Agent or Firm:* Banner & Witcoff, Ltd.

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/179,685, filed on Feb. 19, 2021, which claims priority to European Application No. 20165380.5, filed Mar. 24, 2020, the entire contents of which being fully incorporated herein by reference.

(1) The present disclosure relates to an adjustable support frame for a breathing apparatus and is particularly, although not exclusively, concerned with a length-adjustable back plate for a breathing apparatus, such as a self-contained breathing apparatus (SCBA).

## BACKGROUND

(2) Breathing apparatuses, such as SCBAs, comprise support frames, which may also be known as back plates. These support frames may be adjustable so as to be configured to suit the size of the user using the breathing apparatus.

(3) In prior art systems, adjustment mechanisms for adjusting the dimensions of the support frame are generally configured to make it difficult for the frame to be adjusted in use, to avoid accidental adjustments.

(4) However it will be appreciated that improvements in adjustable support frames for breathing apparatus may be desirable.

## SUMMARY OF INVENTION

(5) According to a first aspect of the present disclosure, there is provided an adjustable support frame for a breathing apparatus having an adjustable longitudinal dimension and a user-facing side configured to substantially overlay a user's back in use, the adjustable support frame comprising: a first frame portion and a second frame portion, the first and second frame portions being moveable relative to each other so as to adjust the longitudinal dimension; an adjustment mechanism having a locked configuration which inhibits relative movement of the first and second frame portions and an unlocked configuration which permits relative movement of the first and second frame portions; wherein the adjustment mechanism comprises one or more actuating elements which are operable to actuate the adjustment mechanism from the locked configuration to the unlocked configuration, the one or more actuating elements being provided on a surface which is substantially perpendicular to the user-facing side of the support frame, wherein the adjustable support frame comprises at least one frame rail which extends in a substantially longitudinal direction and a bridge portion extending in a lateral direction substantially perpendicular to the at least one frame rail, and wherein the one or more actuating elements are provided on a longitudinally-facing surface of the bridge portion.

(6) The support frame may be a back plate for a breathing apparatus.

(7) The adjustment mechanism may be biased into the locked configuration.

(8) The surface on which the actuating element or elements are provided may be referred to as an accessible surface.

(9) The term “longitudinal” may be understood as a direction which is substantially vertical in use of the support frame. The longitudinal direction may be parallel with the direction of extent of the user's spine or body when standing. The term “lateral” may be understood as a direction which is substantially horizontal in use of the support frame and which generally extends sideways relative to (i.e. across) the user. The lateral direction may generally be parallel to the direction of a line extending between the user's shoulders and/or hips.

(10) The adjustable support frame may further comprise first and second laterally-spaced frame rails. The bridge portion may extend laterally between the frame rails.

(11) The one or more actuating elements being provided on a longitudinally-facing surface of the bridge portion may mean the surface on which the actuating elements are provided is a longitudinally-facing surface of the bridge portion.

(12) The adjustable support frame may have the user-facing side and an outer-facing side opposing the user facing side. The support frame may further comprise a relief formed in the user-facing side of the support frame, or an aperture through the support frame between the user-facing side and the outer-facing side. The one or more actuating elements may be arranged on a peripheral wall of the relief or aperture (i.e. the surface on which the actuating elements are provided may be a peripheral wall of the relief or aperture).

- (13) The support frame may comprise two frame rails (first and second frame rails) which define the relief or aperture therebetween. The frame rails may comprise at least a portion of the peripheral wall of the relief or aperture.
- (14) The “peripheral wall” should be understood to be a wall surrounding the relief or aperture which is substantially perpendicular to the user-facing surface of the support frame. The or a bridge portion may define at least a portion of the peripheral wall.
- (15) The wall may be comprised of a plurality or distinct wall portions or surfaces, which may be provided on different parts of the support frame. For example, the support frame could comprise two frame rails and two bridge portions, and the relief or aperture could form a substantially rectangular shape which is bordered on each side by one of the frame rails or bridge portions, which together define the peripheral wall.
- (16) The one or more actuating elements may extend into the relief or aperture from a peripheral wall. In other words, the actuating element or elements may be features which project out or stand proud from the peripheral wall to extend into the relief or aperture.
- (17) The one or more actuating elements may comprise an elongate grippable portion which extends in a direction substantially parallel to the user-facing side of the support frame. Optionally, the elongate grippable portion may extend substantially longitudinally or laterally relative to the support frame.
- (18) The actuating mechanism may comprise first and second actuating elements which, when urged together by a user, actuate the adjustment mechanism into the unlocked position.
- (19) The first and/or second frame elements may be configured such that the one or more actuating elements maintain a substantially static longitudinal position relative to a part of a user's back.
- (20) The first frame portion may be an upper frame portion, and the second frame portion may be a lower frame portion. The upper frame portion may comprise fixing points for an upper end of one or more shoulder straps for supporting the support frame on a user's shoulders. The lower frame portion may comprise a securement apparatus, optionally a waist belt, for securing the lower frame portion at a user's waist or lower torso. The one or more actuating elements are provided: i) on the lower frame portion, such that the one or more actuating elements maintain a substantially static position relative to the user's waist; or ii) on the upper frame portion, such that the one or more actuating elements maintain a substantially fixed position relative to the user's shoulders.
- (21) According to a second aspect of the present disclosure, there is provided an adjustable support frame for a breathing apparatus, the support frame having a user-facing side for facing a user's back and an outer-facing side for facing away from a user's back, the support frame comprising: a first frame portion and a second support portion, the first and second frame portions being moveable relative to each other so as to adjust a dimension of the adjustable support; an adjustment mechanism having a locked configuration which prevents relative movement of the first and second frame portions and an unlocked configuration which permits relative movement of the first and second frame portions, the adjustment mechanism comprising one or more actuating elements which are operable to actuate the adjustment mechanism from the locked configuration to the unlocked configuration, wherein the one or more actuating elements are arranged to be accessible on the outer-facing side of the support frame.
- (22) According to a third aspect of the present disclosure, there is provided a breathing apparatus comprising an adjustable support frame according to the first aspect described above.
- (23) To avoid unnecessary duplication of effort and repetition of text in the specification, certain features are described in relation to only one or several aspects or embodiments of the invention. However, it is to be understood that, where it is technically possible, features described in relation to any aspect or embodiment of the invention may also be used with any other aspect or embodiment of the invention.
-

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a better understanding of the present invention, and to show more clearly how it may be carried into effect, reference will now be made, by way of example, to the accompanying drawings, in which:
- (2) FIG. 1 is a perspective view of a breathing apparatus comprising an adjustable support frame;
- (3) FIG. 2 is a perspective view of an adjustable support frame for a breathing apparatus as shown in FIG. 1;
- (4) FIG. 3 is a plan view of an outer-facing side of the support frame of FIG. 2;
- (5) FIG. 4 is a plan view of a user-facing side of the support frame of FIG. 2;
- (6) FIGS. 5A and 5B show the support frame of FIG. 2 in a first configuration having a first longitudinal dimension and a second configuration having a second longitudinal dimension respectively;
- (7) FIGS. 6A and 6B show the adjustment mechanism of the support frame of FIG. 2 in a locked configuration and an unlocked configuration respectively;
- (8) FIG. 7 shows the support frame of FIG. 2 in use by a user when the user is actuating the actuating elements;
- (9) FIG. 8 shows an alternative adjustable support frame having an alternative arrangement of the actuating elements; and
- (10) FIG. 9 shows a further alternative adjustable support frame having a further alternative arrangement of the actuating elements.

### DETAILED DESCRIPTION OF THE INVENTION

- (11) Referring to FIG. 1, a breathing apparatus **10** is shown. In this example, the breathing apparatus **10** is a self-contained breathing apparatus (SCBA), although it should be understood that the principles of this disclosure could be applied to other types of breathing apparatus which have support frames.
- (12) The breathing apparatus **10** comprises an adjustable support frame **100**, also known as a back plate, which supports a breathing gas cylinder **12**. A valve apparatus **14** is provided for securing the cylinder **12** to the support frame **100** and transferring gas out of the cylinder **12** for a user to breath via hosing and a lung demand valve (not shown). It should be understood that the breathing apparatus is generally provided to provide its user with a supply of clean breathing air in environments where clean breathing air is not available in the ambient environment, such as in fires, chemical leaks, etc.
- (13) The breathing apparatus **10** is configured to be worn by a user on the user's back (see FIG. 9, for example). To achieve this, the breathing apparatus **10** comprises shoulder straps **16**, which are configured to be worn over a user's shoulders and encircling the user's arms, and a waist belt **18**, which is secured around a user's waist.
- (14) Turning now to FIGS. 2, 3 and 4, the adjustable support frame **100** for the breathing apparatus **10** is shown in more detail. FIG. 2 shows the support frame **100** in a perspective view showing an outer-facing side **103** of the support frame **100**. FIG. 3 shows a plan view of the support frame **100** from the outer-facing side **103**. FIG. 4 shows a plan view of the same support frame **100** from a user-facing side **102**.
- (15) The adjustable support frame **100**, as shown in FIGS. 3 and 4 has an adjustable longitudinal dimension L, which will be referred to in this detailed description as a length L. It should be understood that the longitudinal direction is the direction of vertical extent of the support frame **100** in use. The term "longitudinal" may be understood as a direction which is substantially vertical in use of the support frame. The longitudinal direction may be parallel with the direction of extent of the user's spine or body when standing. The term "lateral" herein may be understood as a direction

which is substantially horizontal in use of the support frame and which generally extends sideways relative to (i.e. across) the user. The lateral direction may generally be parallel to the direction of a line extending between the user's shoulders and/or hips.

(16) The length L of the support frame **100** is the total length of the support frame **100** in the longitudinal direction. The length L is adjustable, which will be discussed in more detail with respect to FIGS. 5A and 5B below.

(17) The support frame **100** is formed from a first, lower frame portion **104** and a second frame portion **106**. The first and second frame portions **104**, **106** are moveable relative to each other so as to adjust the length L of the support frame **100**, as will be described in more detail with respect to FIGS. 5A and 5B below.

(18) In order to adjust the length L of the support frame **100**, the support frame **100** comprises an adjustment mechanism **108**. The adjustment mechanism **108** is adjustable between a locked configuration which inhibits relative movement of the first and second frame portions **104**, **106** and an unlocked configuration which permits relative movement of the first and second frame portions **104**, **106**. This will be described in more detail with respect to FIGS. 6A and 6B below.

(19) As shown in FIGS. 2-4, the adjustment mechanism **108** comprises two actuating elements **110** which are operable to actuate the adjustment mechanism **108**. The actuating elements **110** are provided on a surface **112** which is substantially perpendicular to the user-facing side **102** of the support frame **100**. Generally, this should be understood to mean that the surface **112** faces sideways or vertically (or some combination thereof, for example diagonally upwards or downwards) with respect to the user-facing side **102**. The provision of the actuating elements **110** on such a surface provides that the actuating elements **110** are not overlaid by a user's back in use, nor arranged out of reach of the user on the outer-facing side **103**, such that the user can actuate the actuating elements themselves while wearing the support frame **100**. It should be understood that the surface **112** need not be exactly perpendicular to the user-facing side **102** of the support frame **100**. Rather, the surface **112** should be arranged sufficiently out-of-plane with the user-facing side **102** such that the actuating elements **110** thereon are accessible from a sideways or vertical direction (or some combination thereof), so that they are not overlaid by a user's back in use. For brevity in this detailed description, the surface on which the actuating element or elements are provided may be referred to as an accessible surface **112**.

(20) In this example, the accessible surface **112** is a longitudinally facing surface. The accessible surface **112** faces (i.e. is normal to) the longitudinal direction of the support frame **100**. The accessible surface **112** faces downwardly in use.

(21) The support frame **100**, in this example, comprises first and second frame rails **114**. The frame rails **114** are laterally spaced across the support frame **100**. The frame rails **114** are telescopic in this example, with an outer frame rail **116** provided on the lower frame portion **104**, which receives an inner frame rail **118** provided on the upper frame portion **106** (see FIG. 5B for more detail). Thus, the inner frame rails **118** can be withdrawn from the outer frame rails **116** to increase the length of the support frame **100**. The frame rails **114** extend in a substantially longitudinal direction along the support frame **100**.

(22) The support frame **100** comprises a bridge portion **120** which extends in a lateral direction substantially perpendicular to the frame rails **114**. In this example, the bridge portion **120** extends laterally between the two frame rails **114**. Furthermore, in this example, the bridge portion comprises a cylinder cradle **122** for supporting the breathing gas cylinder **12** of the breathing apparatus **10** in use.

(23) The actuating elements **110** are, in this example, provided on the accessible surface **112** which is a longitudinally-facing surface of the bridge portion **120**. In particular, the actuating elements **110** are provide on the lower (in use) surface of the bridge portion **120**. The bridge portion **120** has an opposing upper (in use) longitudinally facing surface **124**, which faces upwards in use.

(24) In this example, the support frame **100** comprises an aperture **126** through the support frame

**100** between the user-facing side **102** and the outer-facing side **103**. In this example, the aperture **126** is substantially rectangular, and is bounded by the frame rails **114** on its lateral sides, by the bridge portion **120** at its upper side, and by a base bridge portion **128** of the support frame **100** at its lower side. It should be understood that the aperture **126** is an open hole or window through the support frame **100**.

(25) The aperture **126** is bounded by a peripheral wall **130**. The peripheral wall **130** is formed, in this example as a substantially rectangular peripheral wall comprising portions formed by the frame rails **114**, by the bridge portion **120**, and by a base bridge portion **128**. Other shapes of aperture can be envisaged, for example a circular or oval aperture, having respective peripheral walls. In this example, the accessible surface **112** on which the actuating elements **110** are provided is a portion of the peripheral wall **130** of the aperture **126**. It should be understood that, by providing the aperture **126** through the support frame **100**, the one or more actuating elements are therefore accessible on the outer-facing side of the support frame **100**. Therefore, they could be conveniently accessed by another person than the user who is stood behind the user. This may provide a more convenient and universally adjustable support frame.

(26) In other examples, instead of an aperture which extends completely through the support frame **100**, a relief (i.e. a relieved space) could be provided. The relief may be bounded, like the aperture **126** describe above, by a peripheral wall. However, the relief may not extend completely through the depth of the support frame so as to form an aperture.

(27) In this example, the actuating elements **110** extend into the aperture **126** from the peripheral wall **130** and, in particular, the accessible surface **112** of the bridge portion **120**. In other words, the actuating elements **110** project out or stand proud from the peripheral wall to extend into the aperture **126**. This projection of the actuating elements **110** may enable them to be more easily grasped by a user. The actuating elements **110** of this example are formed with an elongate grippable portion **132** which extends longitudinally from the accessible surface **112**, i.e. generally parallel to the user-facing side **102**.

(28) Referring now to FIGS. 5A and 5B, the adjustment of the length of the support frame **100** will be described briefly.

(29) FIG. 5A shows the support frame **100** in a first configuration, which in this example is the shortest possible configuration, having a total length **L1**. In FIG. 5A, the inner frame rail **118** is completely received within the outer frame rail **116**.

(30) In FIG. 5B, the support frame **100** is shown in a second configuration, where the total length of the support frame **100** is an extended length **L2**. In this configuration, the inner frame rails **118** have been telescoped out of the outer frame rails **116** by a distance **D**, such that the total length of the support frame **100** is increased. The difference between length **L1** and **L2** is, as should be understood, the distance **D**. By adjusting the distance **D** by withdrawing and inserting different lengths of the inner frame rails **118** into the outer frame rails **116**, the length **L** of the support frame can be adjusted to suit the size of the user.

(31) Of course, it could be undesirable for the length **L** of the support frame to change accidentally, so the adjustment mechanism **108** prevents relative movement of the frame portions **104,106** (i.e. movement of the inner frame rails **118** relative to the outer frame rails **116**) unless it is moved to its unlocked configuration.

(32) The configuration of the adjustment mechanism **108** will now be described in more detail with respect to FIGS. 6A and 6B.

(33) Each of FIGS. 6A and 6B shows a close-up view of the upper portion of the user-facing side **102** of the support frame **100**.

(34) In FIG. 6A, the adjustment mechanism **108** is shown in the locked configuration. It can be seen here that the adjustment mechanism **108** comprises a pair of opposing bolts **134**, each of which extends laterally in an opposing direction into one of the frame rails **114**. The bolts **134** extend through the outer frame rail **116** and into the inner frame rail **118**.

(35) The inner frame rail **118** comprises a plurality of longitudinally spaced pockets **136**, which are separated by walls **138**. The pockets **136** provide a plurality of discrete lengths for the support frame **100**.

(36) In this locked position, the bolts **134** extend into one of the pockets **136**, such that the inner frame rail **118** is prevented from moving longitudinally relative to the outer frame rail **116** by contact between the bolts **134** and the walls **138**. Therefore, in the locked position of the adjustment mechanism **108**, the upper and lower frame portions **104,106** cannot be moved relative to one another, and the length L of the frame support is locked.

(37) FIG. **6B** shows the adjustment mechanism **108** in the unlocked position.

(38) In order to move the adjustment mechanism **108** to the unlocked position, the user can grasp the actuating elements **110**, which are conveniently accessible on the accessible surface **112** even when the support frame **100** is worn, and apply a force F to the actuating elements **110** (see FIG. **6A**) to urge the actuating elements **110** towards one another, to the position shown in FIG. **6B**.

(39) Each of actuating elements **110** are attached to a respective one of the bolts **134**. The bolts **134** are slidably moveable out of the inner frame rail **118**, such that, when the actuating elements **110** are urged together, each of the bolts **134** are withdrawn from the respective inner frame rail **118** and, importantly, the pocket **136** in which they were located. In this position, the bolts **134** no longer prevent the longitudinal movement of the inner frame rail **118** relative to the outer frame rail **116**, so the length of the support frame **100** can be freely adjusted as long as the actuating elements **110** are urged together.

(40) Once the frame support has been adjusted to the desired length, the actuating elements **110** can be released. The bolts **134** are biased (by a spring, or similar) to return to the locked position so, on release of the actuating elements **110**, the bolts **134** slide back into the inner frame rails **118**, and the nearest pocket **136**, and into the locked configuration of FIG. **6A**.

(41) It will be appreciated that the support frame **100** is configured such that the actuating elements **110** maintain a substantially static longitudinal position relative to a part of a user's back. In the example support frame **100**, the lower frame portion **104** comprises the waist belt, for securing the lower frame portion at a fixed position on the user's waist or lower torso. The one or more actuating elements are also provided on the lower frame portion, such that they likewise maintain a substantially fixed position relative to the user's waist once the waist belt has been secured to the user's waist, even when the length L is adjusted.

(42) In an alternative arrangement, the actuating elements may be provided on the upper frame portion **106**, to which the upper ends of shoulder straps are attached. In this alternative example, once the shoulder straps have been donned by the user, the actuating elements will maintain a substantially fixed position relative to the user's shoulders, even when the length L is adjusted

(43) These arrangements may make the actuating elements **110** easier for a user to find and actuate while wearing the support frame **100**, because they are in a reliable static position in use.

(44) Providing actuating elements for the adjustment mechanism as described in this application provides significant advantages in terms of ease of adjustment of the length of the support frame while the breathing apparatus is in use. In prior art support frames, it has generally been a design aim to provide systems which prevent adjustment of the length of the support frame in use, so as to avoid accidental adjustments. However, such systems can prevent quick response to emergencies as, if the support frame is wrongly adjusted, then the breathing apparatus may need to be doffed entirely in order to adjust. In contrast, support frames according to the present disclosure are very convenient to adjust while the breathing apparatus is donned.

(45) FIG. **7** shows a user wearing a breathing apparatus **10** comprising a support frame **100** and actuating the actuating elements **110** provided on an accessible surface as described herein. As will be appreciated, due to the provision of the actuating elements on a substantially perpendicular surface to the user-facing side, the user themselves can reach around and actuate the actuating elements themselves with one hand. Furthermore, in the example shown in FIG. **7**, an aperture **126**



through the support frame **100** provides easy access to the actuating elements **110** for other personnel, without having to reach around the side of the frame **100** into the enclosed space between the user and the frame **100**. Thus, a very convenient adjustment of the length of the support frame **100** can be made while it is being used.

(46) FIGS. **8** and **9** show alternative configurations of support frames incorporating the principles of the present disclosure.

(47) FIG. **8** shows an alternative support frame **200** having actuating elements **210** provided on a laterally-facing accessible surface **212** which is provided on a lateral surface of one of the frame rails **214**. In this example, the user could reach around into the small of their back to actuate the actuating elements **210**.

(48) FIG. **9** shows a yet further alternative support frame **300** having actuating elements **310** provided on the opposing upward-facing accessible surface **312** on the bridge portion **320**. In this example, the user could reach over their head (in a similar manner to a tricep stretch) to access and actuate the actuating elements **310**.

(49) To avoid unnecessary duplication of effort and repetition of text in the specification, certain features are described in relation to only one or several aspects or embodiments of the invention. However, it is to be understood that, where it is technically possible, features described in relation to any aspect or embodiment of the invention may also be used with any other aspect or embodiment of the invention.

(50) It will be appreciated by a skilled person that although the invention has been described by way of example, with reference to exemplary examples, it is not limited to the disclosed examples and that alternative examples could be constructed without departing from the scope of the invention as defined by the appended claims.

(51) For the avoidance of doubt, the disclosure extends to the subject matter recited in the following numbered Paras:

(52) Para 1. An adjustable support frame (**100, 200, 300**) for a breathing apparatus (**10**) having an adjustable longitudinal dimension (L) and a user-facing side (**102**) configured to substantially overlay a user's back in use, the adjustable support frame (**100, 200, 300**) comprising: a first frame portion (**104**) and a second frame portion (**106**), the first and second frame portions (**104, 106**) being moveable relative to each other so as to adjust the longitudinal dimension (L); an adjustment mechanism (**108**) having a locked configuration which inhibits relative movement of the first and second frame portions (**104, 106**) and an unlocked configuration which permits relative movement of the first and second frame portions (**104, 106**); wherein the adjustment mechanism (**108**) comprises one or more actuating elements (**110, 210, 310**) which are operable to actuate the adjustment mechanism (**108**) from the locked configuration to the unlocked configuration, the one or more actuating elements (**110, 210, 310**) being provided on a surface (**112, 212, 312**) which is substantially perpendicular to the user-facing side (**102**) of the support frame (**100, 200, 300**).

(53) Para 2. An adjustable support frame (**100, 200, 300**) for a breathing apparatus (**10**) according to Para 1, wherein the surface (**112, 212, 312**) is a substantially longitudinally-facing surface (**112, 212**) or a laterally-facing surface (**312**).

(54) Para 3. An adjustable support frame (**100, 200, 300**) for a breathing apparatus (**10**) according to Para 1, wherein the adjustable support frame (**100, 200, 300**) comprises at least one frame rail (**114**) which extends in a substantially longitudinal direction.

(55) Para 4. An adjustable support frame (**100, 200, 300**) for a breathing apparatus (**10**) according to Para 3, further comprising a bridge portion (**120, 320**) extending in a lateral direction substantially perpendicular to the at least one frame rail (**114, 314**).

(56) Para 5. An adjustable support frame (**100, 200, 300**) for a breathing apparatus (**10**) according to Para 4, comprising first and second laterally-spaced frame rails (**114**), wherein the bridge portion (**120, 320**) extends laterally between the frame rails (**114**).

(57) Para 6. An adjustable support frame (**100, 300**) according to Para 4, wherein the one or more

actuating elements (110, 310) are provided on a longitudinally-facing surface (112, 312) of the bridge portion (120, 320).

(58) Para 7. An adjustable support frame (100, 200, 300) for a breathing apparatus (10) according to Para 1, wherein the support frame (100, 200, 300) comprises: the user-facing side (102) and an outer-facing side (103) opposing the user facing side; a relief formed in the user-facing side (102) of the support frame (100, 200, 300), or an aperture (126) through the support frame (100, 200, 300) between the user-facing side (102) and the outer-facing side (103); and wherein the one or more actuating elements (110, 210, 310) are arranged on a peripheral wall (130) of the relief or aperture (126).

(59) Para 8. An adjustable support frame (100, 200, 300) according to Para 7, wherein the support frame (100, 200, 300) comprises two frame rails (114, 214) which define the relief or aperture (126) therebetween, and wherein the frame rails (114, 214) comprise at least a portion of the peripheral wall (130) of the relief or aperture (126).

(60) Para 9. An adjustable support frame (100, 200, 300) according to Para 7, wherein a bridge portion (120, 320) defines at least a portion of the peripheral wall (130).

(61) Para 10. An adjustable support frame (100, 200, 300) according to Para 7, wherein the one or more actuating elements (110, 210, 310) extend into the relief or aperture (126) from a peripheral wall (130).

(62) Para 11. An adjustable support frame (100, 200, 300) according to Para 1, wherein the one or more actuating elements (110, 210, 310) comprise an elongate grippable portion (132) which extends in a direction substantially parallel to the user-facing side (102) of the support frame (100, 200, 300), optionally substantially longitudinally or laterally relative to the support frame (100, 200, 300).

(63) Para 12. An adjustable support frame (100, 200, 300) according to Para 7, wherein the adjustment mechanism (108) comprises first and second actuating elements (110, 210, 310) which, when urged together by a user, actuate the adjustment mechanism (108) into the unlocked position.

(64) Para 13. An adjustable support frame (100, 200, 300) according to Para 1, the first and/or second frame portions (104, 106) are configured such that the one or more actuating elements (110, 210, 310) maintain a substantially static longitudinal position relative to a part of a user's back.

(65) Para 14. An adjustable support frame (100, 200, 300) according to Para 1, wherein: the first frame portion is an upper frame portion (106), and the second frame portion is a lower frame portion (104); the upper frame portion (106) comprises fixing points for an upper end of one or more shoulder straps (16) for supporting the support frame (100, 200, 300) on a user's shoulders and the lower frame portion (104) comprises a securement apparatus, optionally a waist belt (18), for securing the lower frame portion (104) at a user's waist or lower torso, and wherein the one or more actuating elements (110, 210, 310) are provided: on the lower frame portion (104), such that the one or more actuating elements (110, 210, 310) maintain a substantially static position relative to the user's waist; or on the upper frame portion (106) such that the one or more actuating elements (110, 210, 310) maintain a substantially fixed position relative to the user's shoulders.

(66) Para 15. A breathing apparatus (10) comprising an adjustable support frame (100, 200, 300) according to Para 1.

## Claims

1. An adjustable support frame for a breathing apparatus having an adjustable longitudinal dimension and a user-facing side configured to substantially overlay a user's back in use, the adjustable support frame comprising: a first frame portion and a second frame portion, the first and second frame portions being moveable relative to each other so as to adjust the longitudinal dimension; an adjustment mechanism having a locked configuration which inhibits relative movement of the first and second frame portions and an unlocked configuration which permits

relative movement of the first and second frame portions; wherein the adjustment mechanism comprises one or more actuating elements which are operable to actuate the adjustment mechanism from the locked configuration to the unlocked configuration, the one or more actuating elements being provided on a surface which is substantially perpendicular to the user-facing side of the support frame, wherein the adjustable support frame comprises at least one frame rail which extends in a substantially longitudinal direction and a bridge portion extending in a lateral direction substantially perpendicular to the at least one frame rail, and wherein the one or more actuating elements are provided on a longitudinally-facing surface of the bridge portion.

2. An adjustable support frame for a breathing apparatus as claimed in claim 1, comprising first and second laterally-spaced frame rails, wherein the bridge portion extends laterally between the frame rails.

3. An adjustable support frame for a breathing apparatus as claimed in claim 1, wherein the support frame comprises: the user-facing side and an outer-facing side opposing the user facing side; a relief formed in the user-facing side of the support frame, or an aperture through the support frame between the user-facing side and the outer-facing side; and wherein the one or more actuating elements are arranged on a peripheral wall of the relief or aperture.

4. An adjustable support frame as claimed in claim 3, wherein the support frame comprises two frame rails which define the relief or aperture therebetween, and wherein the frame rails comprise at least a portion of the peripheral wall of the relief or aperture.

5. An adjustable support frame as claimed in claim 3, wherein the bridge portion defines at least a portion of the peripheral wall.

6. An adjustable support frame as claimed in claim 3, wherein the one or more actuating elements extend into the relief or aperture from the peripheral wall.

7. An adjustable support frame as claimed in claim 1, wherein the one or more actuating elements comprise an elongate grippable portion which extends in a direction substantially parallel to the user-facing side of the support frame.

8. The adjustable support frame as claimed in claim 7, wherein the elongated grippable portion extends in a direction substantially longitudinally to the user-facing side of the support frame.

9. The adjustable support frame as claimed in claim 7, wherein the elongated grippable portion extends in a direction substantially laterally to the user-facing side of the support frame.

10. An adjustable support frame as claimed in claim 1, wherein the adjustment mechanism comprises first and second actuating elements which, when urged together by a user, actuate the adjustment mechanism into the unlocked configuration.

11. An adjustable support frame as claimed in claim 1, the first and/or second frame portions are configured such that the one or more actuating elements maintain a substantially static longitudinal position relative to a part of a user's back.

12. An adjustable support frame as claimed in claim 1, wherein: the first frame portion is an upper frame portion, and the second frame portion is a lower frame portion; the upper frame portion comprises fixing points for an upper end of one or more shoulder straps for supporting the support frame on a user's shoulders and the lower frame portion comprises a securement apparatus for securing the lower frame portion at a user's waist or lower torso, and wherein the one or more actuating elements are provided: on the lower frame portion, such that the one or more actuating elements maintain a substantially static position relative to the user's waist; or on the upper frame portion such that the one or more actuating elements maintain a substantially fixed position relative to the user's shoulders.

13. The adjustable support frame as claimed in claim 12, wherein the securement apparatus comprises a waist belt.

14. A breathing apparatus comprising an adjustable support frame as claimed in claim 1.

---