

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250251004

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

BRENDEL; Stefan

CONNECTION ARRANGEMENTS, DOWEL AND FURNITURE

Abstract

A connection arrangement for connecting a first furniture part (10) to a second furniture part (20) with a further furniture part (70), wherein the first furniture part (10) comprises: a dowel (11) and one or more abutment surfaces (13) extending circumferentially (C) around or being distributed circumferentially (C) around the dowel (11), wherein the second furniture part (20) comprises: a through-going opening (22) extending through a wall (21) and one or more abutment surfaces (23) extending circumferentially (C) around or being distributed circumferentially (C) around the through-going opening (22), wherein the connection arrangement further comprises said further furniture part (70) is a tubular member and wherein a part of the tubular member (70) forms a connection member (30) having a recess (31), the recess (31) having a locking portion (31b) being configured to receive the dowel (11) by a relative motion between the connection member (30) and the first furniture part (10) in a direction transverse (T) to the longitudinal direction (L) and being configured to interact with the neck portion (11b) of the dowel (11) to counteract removal of the dowel (11) from the locking portion (31b) along the longitudinal direction (L).

Inventors: BRENDEL; Stefan (Markaryd, SE)

Applicant: Inter IKEA Systems B.V. (LN DELFT, NL)

Family ID: 69778206

Assignee: Inter IKEA Systems B.V. (LN DELFT, NL)

Appl. No.: 19/053016

Filed: February 13, 2025

Foreign Application Priority Data

SE	1851077-6	Sep. 12, 2018
----	-----------	---------------

Related U.S. Application Data

parent US continuation 18662080 20240513 parent-grant-document US 12258984 child US 19053016
parent US continuation 18141169 20230428 parent-grant-document US 12012982 child US 18662080
parent US continuation 17274472 20210309 parent-grant-document US 11674539 WO continuation PCT/SE2019/050835 20190905 child US 18141169

Publication Classification

Int. Cl.: F16B12/10 (20060101)

U.S. Cl.:

CPC F16B12/10 (20130101); F16B2012/103 (20130101)

Background/Summary

FIELD OF INVENTION

[0001] The invention relates to a connection arrangement for connecting a first furniture part to a second furniture part. The invention also relates to a connection arrangement for connecting a third furniture part to a second furniture part. The invention also relates to a dowel configured to be attached to a tubular furniture part, which may be said second furniture part. The invention also relates to a connection arrangement for connecting the third furniture part to the second furniture part using the dowel. The invention also relates to a furniture comprising a first furniture part, a second furniture part and a third furniture part, the furniture parts being connected to each other using said connection arrangements.

TECHNICAL BACKGROUND

[0002] Within the field of furniture assembly, it is often desired to connect furniture parts to each other. Furniture parts may be connected by fastening means, such as screws or nails. A problem with such fastening means is the need for tools, and sometimes specific tools, in order to apply them. They are often also sensitive to incorrect positioning; for instance, incorrectly hammering a nail may lead to bending of the nail and/or damages to the furniture part, or even personal injury. The tools may also be difficult to use, especially for the disabled or elderly. Furthermore, the fastening means themselves may be prone to be lost, or dangerous for small children. Furniture parts may also be connected with different kinds of locks. However, these may also require many parts, and may not present strong connections when subjected to wear over time.

[0003] For at least the reasons described above, a need exists for better ways to connect furniture parts.

SUMMARY OF INVENTION

[0004] It is an object of the invention to at least mitigate some of the problems mentioned in the background.

[0005] This object has been achieved by a connection arrangement for connecting a first furniture part to a second furniture part, [0006] wherein the first furniture part comprises: [0007] a dowel extending from the first furniture part along a longitudinal direction towards a free end of the dowel, the dowel having at least one neck portion, and [0008] one or more abutment surfaces, [0009] wherein the second furniture part comprises: [0010] a through-going opening extending through a wall of said second furniture part, and [0011] one or more abutment surfaces on a first side of the wall, the first side facing in a direction opposite the longitudinal direction, the one or

more abutment surfaces extending at least partially circumferentially around or being distributed at least partially circumferentially around the through-going opening, [0012] wherein the connection arrangement further comprises a connection member having a recess, the recess having a locking portion being configured to receive the dowel by a relative motion between the connection member and the first furniture part in a direction transverse to the longitudinal direction and being configured to interact with the neck portion of the dowel to counteract removal of the dowel from the locking portion along the longitudinal direction, [0013] wherein the first furniture part and the second furniture part are configured to be connected to each other by [0014] inserting the dowel through the through-going opening from the first side in an insertion direction along the longitudinal direction and bringing said abutment surfaces of the first and second furniture parts into contact with each other, and [0015] positioning the connection member on a second side, opposite the first side, of the wall and moving the connection member relative to the dowel in a travel direction along the transverse direction such that the dowel slides into the locking portion, [0016] wherein abutment surfaces of the first furniture part have an extension in the longitudinal direction along a portion of the dowel and extending at least partially circumferentially around or being distributed at least partially circumferentially around the dowel, [0017] wherein the abutment surfaces of the second furniture part extend from the first side of the wall in a direction opposite the longitudinal direction and extend at least partially circumferentially around or is at least partially circumferentially distributed around the through-going opening, and [0018] wherein the one or more abutment surfaces of the first furniture part and the one or more abutment surfaces of the second furniture part are positioned on the respective furniture part such that, as the dowel is inserted into the through-going opening, the one or more abutment surfaces of the first furniture part abut the one or more abutment surfaces of the second furniture part and counteract relative movement between the first and second furniture parts along a direction transverse to the longitudinal direction, preferably all directions being transverse, to the longitudinal direction. [0019] The second furniture part will thereby be correctly positioned and oriented relative to the first furniture part and the connection member may be moved with ease and still provide a strong and stable connection between the first and second furniture part.

[0020] It may be noted that the wordings first, second and third are merely labels. The same label is used for the same part through-out the description and the claims. This may result in that in a specific part of the description related to a specific connection arrangement there may be referred to a second and a third furniture part although there is in that context no mention of any first furniture part. However, it may be noted that since the wordings first, second and third are merely labels, it is conceivable to relabel the furniture parts in the different parts of the description and in the different claims such that the labels first, second and third are introduced e.g. in the order of appearance of that specific claim and in the associated description. However, since a single furniture may comprise a first, a second and a third furniture part and include two or more of the different connection arrangements disclosed herein, the same label is used for the same part through-out the description and the claims rather than relabelling them in relation to the different connection arrangements.

[0021] It may be noted that the expression furniture part may relate to different kinds of furniture. It may e.g. relate to separate free standing furniture, such as shelves, book shelves, TV-benches, side boards, tables, cupboards, etc. It may also relate to built-in cabinets or shelves, such as wall-hanged kitchen cabinets, wall-hanged kitchen shelves, etc. It may also relate to semi-built-in cabinets or shelves, such as wall hanged TV-benches, etc. Irrespective of it is built-in or free standing it may not only relate to furniture designed for storage, such as cabinets and shelves, but may also relate to furniture parts for furniture for other kinds of use. It may e.g. relate to furniture for sitting, such as sofas, benches, chairs, etc.

[0022] By providing such a connection arrangement with the dowel, the through-going opening, the abutment surfaces of the first and second furniture part, and the connection member formed to

interact with the dowel and the second side of the second furniture part, it is possible to provide a strong connection between the first and second furniture parts with a connection arrangement that may be assembled into a locking engagement without the use of any tools.

[0023] The design with the abutments surfaces and their positioning around the through-going opening and around the dowel provides a strong yet compact design. The design of the connection arrangement is especially useful for connecting tubular furniture parts to each other, where especially the tubular shape of the first furniture part may be used as the abutment surfaces of the first part and may be used to cover the connection arrangement.

[0024] Moreover, the connection member may e.g. be inserted through an open end of the second furniture part and may as such also be used to provide an end cover to the open end.

[0025] The one or more abutment surfaces of the first furniture part may comprise a tubular section extending along the longitudinal direction and extending circumferentially around a base portion of the dowel. Such a design provides a strong abutment surface, makes the abutment surface easy to manufacture and makes it possible to cover the connection arrangement inside the tubular section. There is preferably a circumferentially extending gap between the base portion and the abutment surface formed by the tubular section.

[0026] The one or more abutment surfaces of the second furniture part are configured to be arranged inside and abut one or more abutments surfaces on an inside of the tubular section. Such a design provides a strong abutment surface, makes the abutment surface easy to manufacture and makes it possible to cover the connection arrangement inside the tubular section.

[0027] The one or more abutment surfaces of the second furniture part comprises a tubular section extending from the first side of the wall in the direction opposite the longitudinal direction and extending circumferentially around the through-going opening. Such a design provides a strong abutment surface and makes the abutment surface easy to manufacture.

[0028] The dowel of the first furniture part may comprise a base portion having an abutment surface adapted to, when the dowel is inserted through the through-going opening of the wall, abut an inner surface of said through-going opening. This may be used to provide a strong and distinct positioning of the first furniture part relative to the second furniture part. If the base portion fits snugly into the through-going opening, the first and second furniture parts will be positioned with precision in any direction in the plane of the wall of the second furniture part.

[0029] The recess has an entrance opening in a first surface forming a corner together with a second surface, the first surface being intended to face in the travel direction and the second surface being intended to face the wall of the second furniture part. Such a recess may be said to be an open ended recess. Designing the connection member with such a recess makes it easy to use; the user can position the first and second furniture parts in their intended position and then in a straight-forward motion push the connection member over the dowel such that the first and second furniture parts becomes interconnected. Such a design also facilitates manufacture of the connection member. The connection member may e.g. be injection moulded in a single step process since the entrance opening may be used as an extraction way for a removable core in an injection moulding tool with the core having the shape of the recess.

[0030] The recess has a depth as seen from the second surface along a depth direction extending along the longitudinal direction and may, as seen along the depth direction, be provided with at least one neck section configured to interact with the neck portion of the dowel. The neck section may be formed by two oppositely arranged internal ridges extending along the second surface and facing each other. Such a design provides a strong connection and is easy to manufacture. The design is especially suitable in combination with an open ended recess since the ridges extending along the second surface allows for the extraction of a removable core in an injection moulding tool. In a preferred embodiment, there is provided two neck sections one after the other as seen along the depth direction.

[0031] The first furniture part may be a tubular member having a main extension along the

longitudinal direction, wherein the dowel is positioned partly into an open end of the tubular member such that it partly extends inside the tubular member and partly extends past the tubular member along the longitudinal direction. As mentioned above, there is preferably a circumferentially extending gap between the base portion and the abutment surface formed by the tubular section.

[0032] The dowel may be a separate element being attached to the first furniture part. The dowel may e.g. be attached to the first furniture part by an attachment portion being positioned further into the tubular member than the base portion.

[0033] The second furniture part may be a tubular member having an open end facing in a direction opposite the travel direction of the connection member and having a main extension along the transverse direction. This is advantageous in that the connection member may be inserted into the tubular member and be moved along the travel direction to the locking position in a single straight-forward motion.

[0034] The above mentioned object has also been achieved by a furniture comprising a second furniture part and a third furniture part, wherein the first and second furniture parts are connected to each other by a connection arrangement as introduced above and as disclosed in more detail with reference to the detailed description and the appended drawings, [0035] wherein the third furniture part is tubular, has an open end facing in a longitudinal direction and has a main extension along the longitudinal direction, [0036] wherein the second furniture part comprises or is configured to receive a dowel extending from the second furniture part along a direction opposite the longitudinal direction towards a free end of the dowel, wherein the dowel has at least one ridge followed, as seen along the longitudinal direction, by at least one valley, [0037] wherein the second and third furniture parts are connected to each other by a connection arrangement which comprises: [0038] a connection member having a recess and being configured to be inserted through the open end and into the third furniture part, [0039] wherein the recess has a locking portion being configured to receive the dowel by a relative motion between the third furniture part and the connection member in a direction transverse to the longitudinal direction and being configured to interact with the valley of the dowel to counteract removal of the dowel from the locking portion along the longitudinal direction, [0040] wherein the second furniture part and the third furniture part are configured to be connected to each other by [0041] inserting the connection member at least partly into the third furniture part, and [0042] moving the third furniture part with the connection member relative to the dowel in a travel direction along the transverse direction such that the dowel slides into the locking portion of the connection member.

[0043] By using a connection member with such a designed recess and at least partly inserting it into the third furniture part in combination with the use of such a designed dowel it is possible to provide a strong connection of a tubular furniture part to a second furniture part and it is possible to provide a connection arrangement being covered by the tubular furniture part and a cover plate on the dowel.

[0044] As mentioned above, it may be noted that the wordings first, second and third are merely labels. The same label is used for the same part through-out the description and the claims. This result in that in this specific part of the description related to this specific connection arrangement there is referred to a second and a third furniture part although there is in this context no mention of any first furniture part. However, it may be noted that since the wordings first, second and third are merely labels, it is conceivable to relabel the furniture parts in the different parts of the description and in the different claims such that the labels first, second and third are introduced e.g. in the order of appearance of that specific claim and in the associated description. However, since a single furniture may comprise a first, a second and a third furniture part and include the initially disclosed connection arrangement and also this immediately above disclosed connection arrangement, the same label is used for the same part through-out the description and the claims rather than relabelling them in relation to the different connection arrangements.

[0045] The dowel may be configured to be attached to a tubular furniture part and to provide a part of a connection arrangement between the tubular furniture part and a third furniture part, whereby the dowel may comprise [0046] a connection portion having at least one ridge followed, as seen along a longitudinal direction, by at least one valley, wherein the connection portion is configured to extend from the second furniture part along a direction opposite the longitudinal direction towards a free end of the dowel, and [0047] an attachment portion having a neck portion followed, as seen along the longitudinal direction by a head portion, the head portion having in a first transverse direction an extension being greater than an extension of the neck portion in said first transverse direction and being greater than an extension of the head portion and an extension of the neck portion in a second transverse direction being orthogonal to the first transverse direction, [0048] wherein the dowel is configured to be attached to the tubular furniture part by [0049] inserting the attachment portion in an elongated through-going opening extending through a first wall of the tubular furniture part, wherein the dowel is during the insertion oriented with the first transverse direction being aligned with, or at least having a major component along, a longitudinal direction of the elongated through-going opening such that the head portion passes through the elongated through-going opening, and thereafter [0050] rotating the dowel in a first direction about an axis extending along the longitudinal direction such that the head portion interacts with an inside of the wall such that the head is prevented from being pulled out of the through-going opening.

[0051] A dowel of this kind is easy to attach to a tubular furniture part and it is capable of providing a strong connection arrangement by being securely attached to the tubular furniture part and by presenting a connecting portion capable of providing a strong connection with a recess having internal ridges interacting with the ridge and valley of the connection portion.

[0052] At least one end, preferably both ends, as seen along the first transverse direction, of the neck portion, may have [0053] a rotation blocking corner configured to interact with an edge of the elongated opening to thereby prevent rotation of the dowel in a second direction, opposite the first direction, about the axis, and [0054] a rotation allowing corner configured to pass along an edge of the elongated opening to thereby allowing rotation of the dowel in the first direction about the axis.

[0055] Thereby the dowel may be rotated from the orientation it has when being inserted to an intended orientation in which the dowel is stopped from further rotation.

[0056] Preferably are both ends each provided with a rotation blocking corner and a rotation allowing corner wherein the two rotation blocking corners are arranged diagonally relative to each other and the two rotation allowing corners are arranged diagonally relative to each other.

[0057] The head portion may be asymmetric in its design and the elongated opening may be asymmetric in its design such that the head of the dowel is only insertable with the first transverse direction in one of two opposing orientations in which the first transverse direction is aligned with or has a major component along the longitudinal direction of the elongated through-going hold.

[0058] Thereby it may be controlled that the dowel is only insertable in the orientation that will, in combination with the rotation blocking and rotation allowing corners result in the intended orientation of the dowel.

[0059] In the above disclosed connection arrangement for connecting a third furniture part to a second furniture part, the second furniture part may be a tubular furniture part provided with an elongated through-going opening extending through a first wall of the tubular furniture part, and the dowel may be designed in accordance with the disclosure above in its most generic terms or in the preferred embodiments of the dowel.

[0060] The elongated through-going opening preferably has a width along a transverse direction of the elongated through-going opening being greater than the extension of the head portion and neck portion along the second transverse direction and being smaller than the extension of the head portion along the first transverse direction.

[0061] In one preferred embodiment, the inventive concept is realised in a furniture comprising a first furniture part, a second furniture part and a third furniture part, wherein the first and second

furniture parts are connected to each other by the connection arrangement for connecting a first furniture part to a second furniture part as disclosed above in its most generic terms or in the preferred embodiments, and wherein the first and third furniture parts are connected to each other by the connection arrangement for connecting a second furniture part to a second furniture part as disclosed above in its most generic terms or in the preferred embodiments.

[0062] The above mentioned object has also been achieved by a connection arrangement for connecting a third furniture part to a second furniture part, [0063] wherein the third furniture part is tubular, has an open end facing in a longitudinal direction and has a main extension along the longitudinal direction, [0064] wherein the second furniture part comprises or is configured to receive a dowel extending from the second furniture part along a direction opposite the longitudinal direction towards a free end of the dowel, wherein the dowel has at least one ridge followed, as seen along the longitudinal direction, by at least one valley, [0065] wherein the connection arrangement further comprises: [0066] a connection member having a recess and being configured to be inserted through the open end and into the third furniture part, [0067] wherein the recess has a locking portion being configured to receive the dowel by a relative motion between the third furniture part and the connection member in a direction transverse to the longitudinal direction and being configured to interact with the valley of the dowel to counteract removal of the dowel from the locking portion along the longitudinal direction, [0068] wherein the second furniture part and the third furniture part are configured to be connected to each other by [0069] inserting the connection member at least partly into the third furniture part, and [0070] moving the third furniture part with the connection member relative to the dowel in a travel direction along the transverse direction such that the dowel slides into the locking portion of the connection member. [0071] By using a connection member with such a designed recess and at least partly inserting it into the third furniture part in combination with the use of such a designed dowel it is possible to provide a strong connection of a tubular furniture part to a second furniture part and it is possible to provide a connection arrangement being covered by the tubular furniture part and a cover plate on the dowel.

[0072] As mentioned above, it may be noted that the wordings first, second and third are merely labels. The same label is used for the same part through-out the description and the claims. This result in that in this specific part of the description related to this specific connection arrangement there is referred to a second and a third furniture part although there is in this context no mention of any first furniture part. However, it may be noted that since the wordings first, second and third are merely labels, it is conceivable to relabel the furniture parts in the different parts of the description and in the different claims such that the labels first, second and third are introduced e.g. in the order of appearance of that specific claim and in the associated description. However, since a single furniture may comprise a first, a second and a third furniture part and include the initially disclosed connection arrangement and also this immediately above disclosed connection arrangement, the same label is used for the same part through-out the description and the claims rather than relabelling them in relation to the different connection arrangements.

[0073] The above mentioned object has also been achieved by a dowel configured to be attached to a tubular furniture part and to provide a part of a connection arrangement between the tubular furniture part and a third furniture part, the dowel comprising [0074] a connection portion having at least one ridge followed, as seen along a longitudinal direction, by at least one valley, wherein the connection portion is configured to extend from the second furniture part along a direction opposite the longitudinal direction towards a free end of the dowel, and [0075] an attachment portion having a neck portion followed, as seen along the longitudinal direction by a head portion, the head portion having in a first transverse direction an extension being greater than an extension of the neck portion in said first transverse direction and being greater than an extension of the head portion and an extension of the neck portion in a second transverse direction being orthogonal to the first transverse direction, [0076] wherein the dowel is configured to be attached to the tubular furniture

part by [0077] inserting the attachment portion in an elongated through-going opening extending through a first wall of the tubular furniture part, wherein the dowel is during the insertion oriented with the first transverse direction being aligned with, or at least having a major component along, a longitudinal direction of the elongated through-going opening such that the head portion passes through the elongated through-going opening, and thereafter [0078] rotating the dowel in a first direction about an axis extending along the longitudinal direction such that the head portion interacts with an inside of the wall such that the head is prevented from being pulled out of the through-going opening.

[0079] A dowel of this kind is easy to attach to a tubular furniture part and it is capable of providing a strong connection arrangement by being securely attached to the tubular furniture part and by presenting a connecting portion capable of providing a strong connection with a recess having internal ridges interacting with the ridge and valley of the connection portion.

[0080] At least one end, preferably both ends, as seen along the first transverse direction, of the neck portion, may have [0081] a rotation blocking corner configured to interact with an edge of the elongated opening to thereby prevent rotation of the dowel in a second direction, opposite the first direction, about the axis, and [0082] a rotation allowing corner configured to pass along an edge of the elongated opening to thereby allowing rotation of the dowel in the first direction about the axis.

[0083] Thereby the dowel may be rotated from the orientation it has when being inserted to an intended orientation in which the dowel 51 is stopped from further rotation.

[0084] Preferably are both ends each provided with a rotation blocking corner and a rotation allowing corner wherein the two rotation blocking corners are arranged diagonally relative to each other and the two rotation allowing corners are arranged diagonally relative to each other.

[0085] The head portion may be asymmetric in its design and the elongated opening may be asymmetric in its design such that the head of the dowel is only insertable with the first transverse direction in one of two opposing orientations in which the first transverse direction is aligned with or has a major component along the longitudinal direction of the elongated through-going hold.

[0086] Thereby it may be controlled that the dowel is only insertable in the orientation that will, in combination with the rotation blocking and rotation allowing corners result in the intended orientation of the dowel.

[0087] In the above disclosed connection arrangement for connecting a third furniture part to a second furniture part, the second furniture part may be a tubular furniture part provided with an elongated through-going opening extending through a first wall of the tubular furniture part, and the dowel may be designed in accordance with the disclosure above in its most generic terms or in the preferred embodiments of the dowel.

[0088] The elongated through-going opening preferably has a width along a transverse direction of the elongated through-going opening being greater than the extension of the head portion and neck portion along the second transverse direction and being smaller than the extension of the head portion along the first transverse direction.

[0089] The above mentioned object has also been achieved by a connection arrangement for connecting a third furniture part to a second furniture part, wherein the third furniture part is tubular, has an open end facing in a longitudinal direction and has a main extension along the longitudinal direction, [0090] wherein the second furniture part comprises or is configured to receive a dowel extending from the second furniture part along a direction opposite the longitudinal direction towards a free end of the dowel, wherein the dowel has at least one ridge followed, as seen along the longitudinal direction, by at least one valley, [0091] wherein the connection arrangement further comprises: [0092] a connection member having a recess and being configured to be inserted through the open end and into the third furniture part, [0093] wherein the recess has a locking portion being configured to receive the dowel by a relative motion between the third furniture part and the connection member in a direction transverse to the longitudinal direction and being configured to interact with the valley of the dowel to counteract removal of the dowel from

the locking portion along the longitudinal direction [0094] wherein the second furniture part and the third furniture part are configured to be connected to each other by [0095] inserting the connection member at least partly into the third furniture part, and [0096] moving the third furniture part with the connection member relative to the dowel in a travel direction along the transverse direction such that the dowel slides into the locking portion of the connection member. [0097] By using a connection member with such a designed recess and at least partly inserting it into the third furniture part in combination with the use of such a designed dowel it is possible to provide a strong connection of a tubular furniture part to a second furniture part and it is possible to provide a connection arrangement being covered by the tubular furniture part and a cover plate on the dowel.

[0098] As mentioned above, it may be noted that the wordings first, second and third are merely labels. The same label is used for the same part through-out the description and the claims. This result in that in this specific part of the description related to this specific connection arrangement there is referred to a second and a third furniture part although there is in this context no mention of any first furniture part. However, it may be noted that since the wordings first, second and third are merely labels, it is conceivable to relabel the furniture parts in the different parts of the description and in the different claims such that the labels first, second and third are introduced e.g. in the order of appearance of that specific claim and in the associated description. However, since a single furniture may comprise a first, a second and a third furniture part and include the initially disclosed connection arrangement and also this immediately above disclosed connection arrangement, the same label is used for the same part through-out the description and the claims rather than relabelling them in relation to the different connection arrangements.

[0099] The above mentioned object has also been achieved by a dowel configured to be attached to a tubular furniture part and to provide a part of a connection arrangement between the tubular furniture part and a third furniture part, the dowel comprising [0100] a connection portion having at least one ridge followed, as seen along a longitudinal direction, by at least one valley, wherein the connection portion is configured to extend from the second furniture part along a direction opposite the longitudinal direction towards a free end of the dowel, and [0101] an attachment portion having a neck portion followed, as seen along the longitudinal direction by a head portion, the head portion having in a first transverse direction an extension being greater than an extension of the neck portion in said first transverse direction and being greater than an extension of the head portion and an extension of the neck portion in a second transverse direction being orthogonal to the first transverse direction, [0102] wherein the dowel is configured to be attached to the tubular furniture part by [0103] inserting the attachment portion in an elongated through-going opening extending through a first wall of the tubular furniture part, wherein the dowel is during the insertion oriented with the first transverse direction being aligned with, or at least having a major component along, a longitudinal direction of the elongated through-going opening such that the head portion passes through the elongated through-going opening, and thereafter [0104] rotating the dowel in a first direction about an axis extending along the longitudinal direction such that the head portion interacts with an inside of the wall such that the head is prevented from being pulled out of the through-going opening.

[0105] A dowel of this kind is easy to attach to a tubular furniture part and it is capable of providing a strong connection arrangement by being securely attached to the tubular furniture part and by presenting a connecting portion capable of providing a strong connection with a recess having internal ridges interacting with the ridge and valley of the connection portion.

[0106] At least one end, preferably both ends, as seen along the first transverse direction, of the neck portion, may have [0107] a rotation blocking corner configured to interact with an edge of the elongated opening to thereby prevent rotation of the dowel in a second direction, opposite the first direction, about the axis, and [0108] a rotation allowing corner configured to pass along an edge of the elongated opening to thereby allowing rotation of the dowel in the first direction about the axis.

[0109] Thereby the dowel may be rotated from the orientation it has when being inserted to an intended orientation in which the dowel 51 is stopped from further rotation.

[0110] Preferably are both ends each provided with a rotation blocking corner and a rotation allowing corner wherein the two rotation blocking corners are arranged diagonally relative to each other and the two rotation allowing corners are arranged diagonally relative to each other.

[0111] The head portion may be asymmetric in its design and the elongated opening may be asymmetric in its design such that the head of the dowel is only insertable with the first transverse direction in one of two opposing orientations in which the first transverse direction is aligned with or has a major component along the longitudinal direction of the elongated through-going hold.

[0112] Thereby it may be controlled that the dowel is only insertable in the orientation that will, in combination with the rotation blocking and rotation allowing corners result in the intended orientation of the dowel.

[0113] In the above disclosed connection arrangement for connecting a third furniture part to a second furniture part, the second furniture part may be a tubular furniture part provided with an elongated through-going opening extending through a first wall of the tubular furniture part, and the dowel may be designed in accordance with the disclosure above in its most generic terms or in the preferred embodiments of the dowel.

[0114] The elongated through-going opening preferably has a width along a transverse direction of the elongated through-going opening being greater than the extension of the head portion and neck portion along the second transverse direction and being smaller than the extension of the head portion along the first transverse direction.

[0115] In one preferred embodiment, the inventive concept is realised in a furniture comprising a first furniture part, a second furniture part and a third furniture part, wherein the first and second furniture parts are connected to each other by the connection arrangement for connecting a first furniture part to a second furniture part as disclosed above in its most generic terms or in the preferred embodiments, and wherein the first and third furniture parts are connected to each other by the connection arrangement for connecting a second furniture part to a second furniture part as disclosed above in its most generic terms or in the preferred embodiments.

[0116] The invention may also in short be said to relate to a connection arrangement for connecting a first furniture part to a second furniture part, wherein the first furniture part comprises: a dowel and one or more abutment surfaces extending circumferentially around or being distributed circumferentially around the dowel, wherein the second furniture part comprises: a through-going opening extending through a wall and one or more abutment surfaces extending circumferentially around or being distributed circumferentially around the through-going opening, wherein the connection arrangement further comprises a connection member having a recess, the recess having a locking portion being configured to receive the dowel by a relative motion between the connection member and the first furniture part in a direction transverse to the longitudinal direction and being configured to interact with the neck portion of the dowel to counteract removal of the dowel from the locking portion along the longitudinal direction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0117] The invention will by way of example be described in more detail with reference to the appended schematic drawings, which shows a presently preferred embodiment of the invention.

[0118] FIG. 1 discloses a connection member provided with a recess.

[0119] FIG. 2a discloses a first and a second furniture part.

[0120] FIG. 2b is a partial cross-section of the view of FIG. 2a.

[0121] FIG. 2c discloses the first and second furniture parts being brought together and indicates

the intended position of the connection member.

[0122] FIG. **2d** is a partial cross-section of the view of FIG. **2c**.

[0123] FIG. **2e** is a partial cross-section disclosing the fully assembled connection arrangement.

[0124] FIG. **3a** discloses a dowel intended to be attached to the second furniture part in an elongated opening in the second furniture part.

[0125] FIG. **3b** discloses the dowel having been inserted into the elongated opening and indicates a rotation of the dowel into an attached position.

[0126] FIG. **3c** discloses the dowel being attached to the second furniture part.

[0127] FIG. **3d** discloses a connection member and the third furniture part and indicates the connection member being inserted into the third furniture part.

[0128] FIG. **3e** indicates how the second and third furniture part are moved relative to each other to provide a connection between them.

[0129] FIG. **3f** discloses the second and third furniture parts being connected to each other.

[0130] FIG. **3g** discloses in planar view the elongated opening in the second furniture part.

[0131] FIG. **4a** discloses the components of an alternative embodiment of connecting a first furniture part to a second furniture part using a connection member being insertable into a fourth furniture part extending along the second furniture part.

[0132] FIG. **4b** discloses the first and second parts being brought together and indicates the intended position of the alternative connection member.

[0133] FIG. **4c** discloses the fully assembled connection arrangement of the alternative embodiment.

[0134] FIG. **5a** discloses a first and a second furniture part and a connection member.

[0135] FIG. **5b** discloses the first and second furniture parts being brought together and indicates the intended position of the connection member.

[0136] FIG. **6** discloses a dowel intended to be inserted into the first furniture part.

[0137] FIG. **7a** discloses the orientation and insertion of the dowel into the first furniture part.

[0138] FIG. **7b** discloses the dowel being inserted into the first furniture part.

[0139] FIG. **8** discloses a dowel intended to be attached to the second furniture part in an elongated opening in the second furniture part.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0140] With reference initially to FIG. **1**, FIG. **2a** and FIG. **5a**, there is disclosed a connection arrangement for connecting a first furniture part **10** to a second furniture part **20**.

[0141] As shown in FIGS. **2a-e**, the first furniture part **10** is tubular and has a main extension along a longitudinal direction L. The first furniture part **10** comprises a dowel **11** and a tubular section **10a** forming an abutment surface **13**. The dowel **11** extends from the first furniture part **10** along a longitudinal direction L towards a free end **11c** of the dowel **11**. The dowel **11** has as e.g. indicated in FIG. **2c**, two neck portions **11b**. The abutment surface **13** has an extension in the longitudinal direction L along a base portion **11a** of the dowel **11**. The abutment surface **13** also extends circumferentially C around the dowel **11**. As shown in FIG. **2d**, there is a circumferentially extending gap G**13** between the base portion **11a** and the abutment surface **13** formed by the tubular section **10a**. In the disclosed embodiment, the dowel **11** and the through-going opening **22** have a circular cross-section. However, the dowel **11** and the through-going opening **22** may basically have any desired cross-sectional shape. A circular shape is preferred from a manufacturing perspective. Non-circular shapes may be preferred from the perspective that non-circular shapes may be used to define a specific rotational relative orientation between the first and second furniture parts **10**, **20** about the longitudinal direction L.

[0142] The second furniture part **20** is tubular and comprises a through-going opening **22** and an abutment surface **23**. The through-going opening **22** extends through a wall **21** of said second furniture part **20**. The abutment surfaces **23** is formed of a tubular section **23'** extending from a first side **21a** of the wall **21** in a direction L' opposite the longitudinal direction L. The abutment surface

23 also extends circumferentially **C** around the through-going opening **22**. The second furniture part **20** has a main extension along a transverse direction **T** being transverse to the longitudinal direction **L**.

[0143] It may be noted that in the preferred embodiment, the first furniture part **10** is formed of from a square or rectangular tube and the abutment surface **13** extending around the dowel **11** is a continuous surface formed of the four sides of the cross-section of the square or rectangular tube.

[0144] As shown in FIG. **2c**, the abutment surface **13** of the first furniture part **10** and the abutment surface **23** of the second furniture part **10** are positioned on the respective furniture part **10**, **20** such that, as the dowel **11** is inserted into the through-going opening **22**, the abutment surface **13** of the first furniture part **10** abut the abutment surface **23** of the second furniture part **10** and counteract relative movement between the first and second furniture parts **10**, **20** along all directions **T** transverse to the longitudinal direction **L**.

[0145] As indicated in FIGS. **2a-e**, and disclosed in more detail in FIG. **1**, the connection arrangement further comprises a connection member **30**. The connection member **30** has a recess **31** which has a locking portion **31b** being configured to receive the dowel **11** by a relative motion between the connection member **30** and the first furniture part **10** in a direction transverse **T** to the longitudinal direction **L** and being configured to interact with the neck portion **11b** of the dowel **11** to counteract removal of the dowel **11** from the locking portion **31b** along the longitudinal direction **L**.

[0146] As shown in FIG. **1**, the recess **31** has an entrance opening **31a** in a first surface **32a** forming a corner **32c** together with a second surface **32b**. The first surface **32a** is intended to face in the travel direction **B** and the second surface **32b** is intended to face the wall **21** of the second furniture part **20**. Such a recess **31** may be said to be an open ended recess **31**. As indicated in FIGS. **2b-d**, connection member **30** with such a recess **31** makes is easy to use; the user can position the first and second furniture parts **10**, **20** in their intended position and then in a straight-forward motion push the connection member **30** over the dowel **11** such that the first and second furniture parts **10**, **20** becomes interconnected. Such a design also facilitates manufacture of the connection member **30**. The connection member **30** may e.g. be injection moulded in a single step process since the entrance opening **31a** may be used as an extraction way for a removable core in an injection moulding tool with the core having the shape of the recess **31**.

[0147] The recess **21** has a depth **d31** as seen from the second surface **32b** along a depth direction **D** extending along the longitudinal direction **L**. The recess is, as seen along the depth direction **D**, provided with two neck sections **31c**, **31c'** configured to interact with the respective neck portion **11b** of the dowel **10**. The two neck sections **31c**, **31c'** are arranged one after the other as seen along the depth direction **D**. Alternatively, it may be said that the neck sections **31c**, **31c'** are provided at different depths of the recess **31**. Each neck section **31c**, **31c'** is be formed by two oppositely arranged internal ridges **33a**, **33b** extending along the second surface **32b** and facing each other.

[0148] As shown in FIG. **1** and e.g. also in FIGS. **2c-d**, the connection member **30** has a body part **30'** in which the recess **31** is formed and an end part **30''**. The body par **30'** is configured to be inserted into the tubular member **20**. The end part **30''** has slightly greater dimensions across the insertion direction **B** and is configured to close the end of the tubular member **20**. The interaction between the end part **30''** and the end of the tubular member **20** may also be used to provide a stop for the connection member's **30** movement along the direction **B** as indicated by arrow **K** in FIG. **2d**.

[0149] As indicated in FIGS. **2a-e**, the first furniture part **10** and the second furniture part **20** are configured to be connected to each other by [0150] inserting as shown in FIG. **2a** the dowel **11** through the through-going opening **22** from the first side **21a** in an insertion direction **A** along the longitudinal direction **L** and bringing as shown in FIG. **2b-c** said abutment surfaces **13**, **23** of the first and second furniture parts **10**, **20** into contact with each other, and [0151] positioning the connection member **30** on a second side **21b**, opposite the first side **21a**, of the wall **21** as indicated

in FIG. 2b-c and moving the connection member **30** relative to the dowel **11** in a travel direction B along the transverse direction T such that the dowel **11** slides into the locking portion **31b** to the position indicated in FIG. 2d.

[0152] The connection member **30** is positioned on the second side **21b** by being inserted through an open end **20c** in the second furniture part **20**, the open end **20c** facing in a direction B' opposite the travel direction B of the connection member **30**.

[0153] As shown in FIG. 2d, the abutment surface **23** of the second furniture part **10** is configured to be arranged inside and abut the abutment surface **13** on an inside of the tubular section **10a**. The extension of the tubular section **10a** along the longitudinal direction is such that an open end **10c** of the tubular section **10a** abuts the first side **21a** of the wall **21** thereby covering these parts of the connection arrangement inside the tubular section **10a**.

[0154] As shown in FIGS. 2c-e, the dowel **10** is positioned partly into the open end **10c** of the tubular member **10** such that it partly extends inside the tubular member **10** and partly extends past the open end **10c** of the tubular member **10** along the longitudinal direction L.

[0155] The dowel **11** is a separate element being attached to the first furniture part **10**. The dowel **11** may e.g. as disclosed in FIGS. 2c-e be attached to the first furniture part **10** by an attachment portion **11d** being positioned further into the tubular member **10** than the base portion **11a**.

[0156] In this embodiment, the base portion **11a** may form an abutment surface which, when the dowel **11** is inserted through the through-going opening **22** of the wall **21**, abuts an inner surface **22a** of the through-going opening **22**.

[0157] In FIGS. 5a-b, FIG. 6 and FIGS. 7a-b, there is disclosed an alternative embodiment to the embodiment shown in FIGS. 2a-e. In this embodiment, the abutment surface **13** of the first furniture part **10** is formed of the end surface of the tubular member **10** as indicated e.g. in FIGS. 5a and 7a. The abutment surface **23** of the second part **20** is formed of the outer surface **23** (or alternatively expressed; the first side **21a**) of the wall **21** as indicated in FIG. 5a.

[0158] The dowel **11** is formed of a sheet metal piece being shaped basically into a longitudinally extending member having a U-shaped cross-section. It is oriented with its continuous curved bottom end facing the connection member **30**. The legs of the U-shaped cross-section extend in parallel with the insertion direction B by which the connection member **30** is inserted into the second furniture part **20**. The dowel **11** has as seen along the longitudinal direction L an attachment portion **11d**, a base portion **11a**, and a plurality of alternately arranged ridges **11c** and valleys **11b**. The attachment portion **11d** is inserted into the tubular member **10** and is attached, such as by welding, to the inside of the tubular member **10**.

[0159] As may be noted from FIGS. 5a-b, there are no longitudinally extending abutment surfaces **13**, **23** in this embodiment. However, a locking effect preventing transversal relative movement of the first and second furniture parts **10**, **20**, is in this embodiment provided by the base portion **11a** forming an abutment surface which, when the dowel **11** is inserted through the through-going opening **22** of the wall **21**, abuts an inner surface or edge surface **22a** of the through-going opening **22**. The curved continuous bottom end of the U-shaped cross-section abuts a congruently shaped edge surface **22a**. The free ends of the legs of the U-shaped cross section of the dowel **11** abuts two abutment surfaces formed in the through-going opening **22**, the two abutment surfaces facing in a direction opposite the insertion direction B along which the connection member **30** is inserted into the second furniture part **20**. The shape of the through-going opening may be shaped differently than the cross-sectional shape of the dowel **11** as long as the above mentioned abutment surfaces are provided.

[0160] With reference to FIGS. 3a-g, there is disclosed a connection arrangement for connecting a third furniture part **40** to a second furniture part **20**.

[0161] The third furniture part **40** is tubular and has a main extension along the longitudinal direction L. The third furniture part **40** has an open end **41** facing in the longitudinal direction L as shown in FIG. 3d.

[0162] As shown in FIGS. 3a-c, the second furniture part **20** is configured to receive a dowel **51**. The dowel **51** extends in the attached position from the second furniture part **20** along a direction L' opposite the longitudinal direction L towards a free end **51c** of the dowel **51**. As shown e.g. in FIG. 3a, the dowel **51** has two ridges **51b** each followed, as seen along the longitudinal direction L, by a valley **51c**.

[0163] As shown in FIG. 3d, the connection arrangement further comprises a connection member **60** being configured to be inserted through the open end **41** and into the third furniture part **40**. The connection member **60** has a recess **31** basically designed in the same manner as the recess **31** of the connection member **30**. The recess **31** of the connection member **60** has a locking portion **31b** being configured to receive the dowel **51** by a relative motion between the third furniture part **40** and the connection member **60** in a direction transverse T to the longitudinal direction L and being configured to interact with the valleys **51c** of the dowel **51** to counteract removal of the dowel **51** from the locking portion **31b** along the longitudinal direction L.

[0164] The second furniture part **20** and the third furniture part **40** are configured to be connected to each other by: [0165] inserting the connection member **60** at least partly into the third furniture part **40** as shown in FIG. 3d, and [0166] moving the third furniture part **40** with the connection member **60** relative to the dowel **51** in a travel direction B along the transverse direction T such that the dowel **51** slides into the locking portion **31b** of the connection member **60** as shown in FIG. 3e.

[0167] In FIG. 3f, the second and third furniture parts **20**, **40** are shown in the connected state. It may be noted that the connection arrangement is covered by the tubular furniture part **40** and a cover plate **51d** on the dowel **51**.

[0168] The dowel **51** will in the following be disclosed in more detail with reference mainly to FIGS. 3a-c. As mentioned above, the dowel **51** is configured to be attached to a tubular furniture part **20** and to provide a part of a connection arrangement between the tubular furniture part **20** and a third furniture part **40**. The dowel **51** comprises in short a connection portion **51'** and an attachment portion **51''**.

[0169] The connection portion **51'** has the above mentioned two ridges **51b** each followed, as seen along the longitudinal direction L, by a valley **51c**. The connection portion **51'** is configured to extend from the second furniture part **20** along the direction L' opposite the longitudinal direction L towards the free end **51c** of the dowel **51**.

[0170] The attachment portion **51''** has a neck portion **52** followed, as seen along the longitudinal direction L, by a head portion **53**. The head portion **53** has in a first transverse direction T' an extension being greater than an extension of the neck portion **52** in said first transverse direction T' and being greater than an extension of the head portion **53** and an extension of the neck portion **52** in a second transverse direction T'' being orthogonal to the first transverse direction T'.

[0171] As shown in FIG. 3a, the second furniture part **20** is provided with an elongated through-going opening **25** extending through a first wall **21** of the tubular furniture part **20**. The elongated through-going opening **25** has, along its longitudinal extension, a width W (see FIG. 3g) along a transverse direction T₂₅ of the elongated through-going opening **25** being greater than the extension of the head portion **53** and neck portion **52** along the second transverse direction T'' and being smaller than the extension of the head portion **53** along the first transverse direction T'.

[0172] The dowel **51** is configured to be attached to the tubular furniture part **20** by [0173] inserting the attachment portion **51''** in the elongated through-going opening **25** with the dowel **51**, during the insertion, being oriented with the first transverse direction T' being aligned with, or at least having a major component along, a longitudinal direction L₂₅ of the elongated through-going opening **25** such that the head portion **53** passes through the elongated through-going opening **25**, and thereafter [0174] rotating as shown in FIG. 3b the dowel **51** in a first direction H about an axis G extending along the longitudinal direction L such that the head portion **53** interacts with an inside **21b** of the wall **21** such that the head **53** is prevented from being pulled out of the through-going opening **25**.

[0175] The dowel **51** is shown in its attached position in FIG. 3c.

[0176] As shown in the cross-section A-A of FIG. 3a, both ends **52a**, **52b**, as seen along the first transverse direction T', of the neck portion **52**, has [0177] a rotation blocking corner **52a'** configured to interact with an edge of the elongated opening **25** to thereby prevent rotation of the dowel **51** in a second direction, opposite the first direction H, about the axis G, and [0178] a rotation allowing corner **52a''** configured to pass along an edge of the elongated opening **25** to thereby allowing rotation of the dowel **51** in the first direction H about the axis G.

[0179] Thereby the dowel **51** may be rotated from the orientation it has when being inserted to an intended orientation in which the dowel **51** is stopped from further rotation.

[0180] The two rotation blocking corners **52a'**, **52b'** are arranged diagonally relative to each other and the two rotation allowing corners **52a''**, **52b''** are arranged diagonally relative to each other.

[0181] The head portion **53** may be asymmetric in its design and the elongated opening **25** may be asymmetric in its design such that the head **53** of the dowel **51** is only insertable with the first transverse direction T' in one of two opposing orientations in which the first transverse direction T' is aligned with or has a major component along the longitudinal direction L25 of the elongated through-going hold **25**.

[0182] In FIGS. 3a and 3g, it is shown that the head portion **53** has at one end **53a** thereof relatively sharp corners and at the other end **53b** thereof it has relatively rounded corners. Similarly, elongated opening **25** has at one end **25a** thereof relatively sharp corners and at the other end **25b** thereof it has relatively rounded corners. The radiuses of the corners are chosen such that the head **53** may only be inserted into the elongated opening **25** with the relatively sharp corners at the end **53a** of the head **53** facing the end **25a** of the elongated opening **25** having the relatively sharp corners.

[0183] Thereby it may be controlled that the dowel **51** is only insertable in the orientation that will, in combination with the rotation blocking **52a'**, **52b'** and rotation allowing corners **52a''**, **52b''** result in the intended orientation of the dowel **51**.

[0184] In an alternative embodiment shown in FIG. 8, the elongated through-going opening **125** may be extended along the extension of the second furniture part **20**. In other words, the first transverse direction T' and the second transverse direction T'' described above would switch places. In this alternative embodiment the rotation blocking corners of the neck portion is omitted and instead rotation is blocked using rotation blocking corners **153a''**, **153b''** at the ends **153a**, **153b** of the head portion **153**. The rotation blocking corners **153a''**, **153b''** is cooperating with the inner walls of the second furniture part **20** to prevent further rotation of the dowel **51**. Thereby there is no need for an edge at the elongated opening to prevent rotation. Moreover, the head portion **153** comprises rotation allowing corners **153a'**, **153b'** configured to allow rotation of the dowel **51** in the first direction H in the same manner as described with reference to FIG. 3b.

[0185] In one preferred embodiment, the inventive concept is realised in a furniture comprising a first furniture part **10**, a second furniture part **20** and a third furniture part **40**, wherein the first and second furniture parts **10**, **20** are connected to each other by the connection arrangement for connecting a first furniture part **10** to a second furniture part **20** as disclosed above in its most generic terms or in the preferred embodiments, and wherein the first and third furniture parts **10**, **40** are connected to each other by the connection arrangement for connecting a second furniture part **10** to a second furniture part **20** as disclosed above in its most generic terms or in the preferred embodiments.

[0186] In FIGS. 4a-c, there is shown a connection arrangement between a first furniture part **10** and a second furniture part **20** similar to the connection arrangement of FIGS. 2a-e. However, instead of using a connection member **30** of FIG. 1, there is in this latter connection arrangement used a connection member **80** which is insertable or form part of a tubular member **70**. The tubular member **70** is intended to extend as a continuation of the second furniture part **20**. This design is e.g. suitable to provide a leg **70** at the bottom of the furniture. The connection member **80** is

provided with a recess **31** of the kind disclosed in detail with reference to FIG. **1**.

[0187] It is also conceivable to combine the connection arrangement of FIGS. **1** and **2a-e** with the connection arrangement of FIGS. **4a-c** in a design where the furniture part **70** is provided with or receives a connection member **80** at one end thereof and is provided with a through-going opening **22** and abutment surfaces **23** at the other end thereof. With such a design, a plurality of such furniture parts **70** may be stacked on top of each other and connect with a first furniture part **10** at each such interconnection. At the top of such a stack the connection arrangement could end with a connection arrangement as disclosed in FIGS. **1** and **2a-e** and at the bottom of such a stack the connection arrangement could end with a connection arrangement as disclosed in FIGS. **4a-c**.

[0188] It may be noted that the furniture shown in the various figures as ending with a connection arrangement as shown in FIGS. **4a-c** may alternatively end at both ends of the second furniture part **20** with a connection arrangement of the kind disclosed in FIGS. **1** and **2a-e**.

[0189] It is contemplated that there are numerous modifications of the embodiments described herein, which are still within the scope of the invention as defined by the appended claims.

[0190] The one or more abutment surfaces **13** may for instance be a plurality of separate abutment surfaces each extending from a first side **21a** of the wall **21** in a direction **L'** opposite the longitudinal direction **L** and being distributed relative to each other circumferentially **C** around the dowel **11**.

[0191] The one or more abutment surfaces **23** may for instance be a plurality of separate abutment surfaces each extending from a first side **21a** of the wall **21** in a direction **L'** opposite the longitudinal direction **L** and being distributed relative to each other circumferentially **C** around the through-going opening **22**.

[0192] It may be noted that in the preferred embodiment, the various furniture parts **10**, **20**, **40** are formed of from a square or rectangular tube. However, the furniture parts do not have to be formed from tubes. They may be solid parts provided with recesses or openings providing the spaces or cavities necessary to receive the dowels, connecting members, etc., which spaces or cavities are provided by the interior of the tubes of the preferred embodiments. It may also be noted that the shapes, of the tubular parts or solid parts, need not be square or rectangular. Other shapes, such as other kinds of polygons, circles, ovals, ellipsoids, are also conceivable.

[0193] As mentioned above, it may be noted that the expression furniture part may relate to different kinds of furniture. It may e.g. relate to separate free standing furniture, such as shelves, book shelves, TV-benches, side boards, tables, cupboards, etc. It may also relate to built-in cabinets or shelves, such as wall-hanged kitchen cabinets, wall-hanged kitchen shelves, etc. It may also relate to semi-built-in cabinets or shelves, such as wall hanged TV-benches, etc. Irrespective of it is built-in or free standing it may not only relate to furniture designed for storage, such as cabinets and shelves, but may also relate to furniture parts for furniture for other kinds of use. It may e.g. relate to furniture for sitting, such as sofas, benches, chairs, etc.

Claims

1-15. (canceled)

16. Connection arrangement comprising a first furniture part, a second furniture part, and a connection member, wherein the first furniture part comprises: a first furniture part wall having an opening, and a dowel extending from the first furniture part wall opening in a direction away from the first furniture part wall and toward a free end of the dowel, wherein the second furniture part comprises: an open end facing toward the first furniture part, and wherein the connection member is arranged in the open end of the second furniture part, and wherein the connection member being configured to receive the dowel by a relative motion between the second furniture part with the connection member and the first furniture part in a direction transverse to a direction from the first furniture part wall to the free end and being configured to interact with the dowel to counteract

removal of the dowel from the connection member in a direction from the first furniture part wall to the free end of the dowel, and wherein the first furniture part and the second furniture part are configured to be connected to each other by moving the connection member, located within the second furniture part relative to the dowel in a travel direction transverse to a direction from the first furniture part wall to the free end of the dowel.

17. Connection arrangement according to claim 16, wherein the dowel comprises a head portion configured to be received within the opening in the first furniture part wall.

18. Connection arrangement according to claim 17, wherein the head portion is sized to prevent the head portion from being pulled out of the opening in the first furniture part wall.

19. Connection arrangement according to claim 17, wherein the opening in the first furniture part wall is elongated in a direction selected among the travel direction, and a direction perpendicular to the travel direction.

20. Connection arrangement according to claim 17, wherein the head portion is configured to be received within the opening in the first furniture part wall, and wherein the dowel is configured to be rotated to lock the dowel in place relative to the first furniture part.

21. Connection arrangement according to claim 16, wherein the connection member has a recess, and the recess has a locking portion.

22. Connection arrangement according to claim 21, wherein the recess has a depth provided with at least one neck section configured to interact with a valley of the dowel, wherein the recess has an entrance opening in a first surface forming a corner together with a second surface, and wherein the at least one neck section is formed by two oppositely arranged internal ridges extending along the second surface and facing each other.

23. Connection arrangement according to claim 16, wherein the second furniture part is a tubular member.

24. Connection arrangement according to claim 23, wherein the second furniture part has an opening extending through a wall of the tubular member, and wherein the connection member includes an opening aligned with the opening of the second furniture part.

25. Connection arrangement according to claim 23, wherein the connection member is insertable in the tubular member through the open end.

26. Connection arrangement according to claim 23, wherein the connection member forms part of the tubular member.

27. Connection arrangement according to claim 17, wherein the dowel has a neck portion.

28. Connection arrangement according to claim 27, wherein the head portion is elongated and is connected to the remaining parts of the dowel via the neck portion.

29. Connection arrangement according to claim 17, wherein the head portion has the general shape of a two-bladed propeller.

30. Connection arrangement according to claim 17, wherein the head portion comprises corners, and wherein the corners are shaped to provide a single orientation for the head portion to engage the opening of the first furniture part.

31. Connection arrangement according to claim 17, wherein the head portion is shaped to provide allow the connection member to rotate to an orientation for engaging the second furniture part, and resist further rotation.

32. Connection arrangement comprising a first furniture part, a second furniture part, and a connection member, wherein the first furniture part comprises: a first end, a second end, a wall extending from the first furniture part first end to the first furniture part second end, and a dowel extending from the first furniture part wall in a direction away from the first furniture part wall and toward a free end of the dowel, and wherein the dowel comprises a first locking arrangement, wherein the second furniture part comprises: a first open end and a second end, wherein the first open end faces in a direction away from the second furniture part second end, and wherein the connection member is arranged in the open end of the second furniture part, and wherein the

connection member comprises a second locking arrangement and is configured to receive the dowel, wherein the first locking arrangement and the second locking arrangement are configured to engage each other along a first direction, and resist disengaging from each other in a second direction, wherein the second direction is perpendicular to the first direction, and wherein the first furniture part and the second furniture part are configured to be connected to each other by moving the connection member, located within the second furniture, part relative to the dowel in the first direction so that the dowel having the first locking arrangement is received within the second locking arrangement.
