

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384287
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Pruss; James E. et al.

Enclosed boat trailer

Abstract

An illustrative embodiment of an enclosed boat trailer may be configured to allow loading of a boat in the water for the purpose of removing the boat from the water using the enclosed boat trailer to engage the boat for storage and/or transportation. An illustrative embodiment of an enclosed boat trailer may be comprised of a roller system positioned on the floor and a right and left rear arm adjacent a rear opening in the enclosed boat trailer. In an illustrative method of use, a boat operator may load and/or unload the boat into the water from the enclosed boat trailer without leaving the boat and without additional personnel.

Inventors:	Pruss; James E. (Dodge, NE), Pruss; Matthew J. (Fremont, NE)
Applicant:	Shield Boat Trailers, LLC (Dodge, NE)
Family ID:	1000008748627
Assignee:	SHIELD BOAT TRAILERS, LLC (Dodge, NE)
Appl. No.:	18/493448
Filed:	October 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240051451 A1	Feb. 15, 2024

Related U.S. Application Data

continuation parent-doc US 17713511 20220405 US 11794624 child-doc US 18493448
continuation parent-doc US 17360428 20210628 US 11292380 20220405 child-doc US 17713511
continuation parent-doc US 17157581 20210125 US 11046231 20210629 child-doc US 17360428
us-provisional-application US 63113705 20201113

Publication Classification

Int. Cl.: B60P3/10 (20060101)

U.S. Cl.:

CPC B60P3/1066 (20130101); B60P3/1041 (20130101); B60P3/1083 (20130101);

Field of Classification Search

CPC: B60P (3/1066); B60P (3/1041); B60P (3/1083)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3077277	12/1962	Holzman	D12/101	B60P 3/1066
3837509	12/1973	Gladnick	280/414.1	B60P 3/1075
3892320	12/1974	Moore	D12/101	B60P 3/1066
4268212	12/1980	Weary	414/539	B60P 3/1075
4278388	12/1980	Johnson	280/414.1	B60P 3/1066
4717165	12/1987	Johnson	D34/28	B60P 3/1066
4997332	12/1990	Johnson	403/385	B60P 3/1066
5549438	12/1995	Dwyer	414/559	B60P 3/10
10065551	12/2017	Zanette	N/A	B60P 3/1033
11046231	12/2020	Pruss	N/A	B60P 3/1041
11292380	12/2021	Pruss	N/A	B60P 3/1075
11794624	12/2022	Pruss	N/A	B60P 3/1041
2004/0011273	12/2003	Gorbutt	114/344	B60P 3/1075
2008/0036174	12/2007	Nieman	280/414.1	B60P 3/1041
2018/0281658	12/2017	Thorley	N/A	B60P 3/1075
2020/0039415	12/2019	Bacon	N/A	B60P 3/1066

Primary Examiner: Joerger; Kaitlin S

Attorney, Agent or Firm: HAMILTON IP LAW

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present nonprovisional patent application claim priority from and is a continuation of U.S. patent application Ser. No. 17/713,511 filed on Apr. 5, 2022 (now U.S. Pat. No. 11,794,624), which application claims priority from and is a continuation of U.S. patent application Ser. No. 17/360,428 filed on Jun. 28, 2021 (now U.S. Pat. No. 11,292,380), which application claims priority from and is a continuation of U.S. patent application Ser. No. 17/157,581 filed on Jan. 25, 2021 (now U.S. Pat. No. 11,046,231), which

application claimed priority from provisional U.S. Pat. App. Nos. 62/965,135 filed on Jan. 23, 2020; 63/055,105 filed on Jul. 22, 2020; and 63/113,705 filed on Nov. 13, 2020, all of which patent applications are incorporated by reference herein in their entireties.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT
(1) No federal funds were used to create or develop the invention herein.
REFERENCE TO SEQUENCE LISTING, A TABLE, OR A COMPUTER PROGRAM LISTING
COMPACT DISK APPENDIX
(2) N/A

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments and together with the description, serve to explain and illustrate the principles of the enclosed boat trailer as disclosed herein.
- (2) FIG. 1A is a perspective view of an illustrative embodiment of an enclosed boat trailer with the rear doors in an open position.
- (3) FIG. 1B is a perspective view of the illustrative embodiment of the enclosed boat trailer shown in FIG. 1A with a portion of the wall and roof removed to show the interior of the enclosed boat trailer.
- (4) FIG. 1C is a perspective view of another illustrative embodiment of the enclosed boat trailer with a differently configured roller system.
- (5) FIG. 2A is a rear view of the illustrative embodiment of an enclosed boat trailer shown in FIGS. 1A & 1B with the rear doors open.
- (6) FIG. 2B is another rear view of the illustrative embodiment of an enclosed boat trailer shown in FIGS. 1A & 1B with the rear doors open and a boat positioned in the enclosed boat trailer.
- (7) FIG. 3A is a top view of the illustrative embodiment of an enclosed boat trailer from FIG. 1B showing general layout of an illustrative embodiment of a roller system.
- (8) FIG. 3B is a top view of the illustrative embodiment of an enclosed boat trailer from FIG. 1C showing general layout of an illustrative embodiment of a roller system.
- (9) FIG. 4 is a detailed perspective view of a portion of the illustrative embodiment of a roller system.
- (10) FIG. 5 is another detailed perspective view of a portion of the illustrative embodiment of a roller system toward the rear portion thereof.
- (11) FIG. 6 is another detailed perspective view of a portion of the illustrative embodiment of a roller system toward the front portion thereof.
- (12) FIG. 7 is another detailed perspective view of a portion of the illustrative embodiment of a roller system toward the rear portion thereof showing the rear arms adjacent the rear opening of the enclosed boat trailer.
- (13) FIG. 8 is a perspective view of an illustrative embodiment of a winch that may be used with various embodiments of the enclosed boat trailer.
- (14) FIG. 9 is a detailed perspective view of an illustrative embodiment of a launch assist system that may be used with various embodiments of the enclosed boat trailer.
- (15) FIG. 10 is another detailed perspective view of an illustrative embodiment of a launch assist system that may be used with various embodiments of the enclosed boat trailer.
- (16) FIG. 11A is a perspective view of an illustrative embodiment of rear arms that may be used with various embodiments of the enclosed boat trailer with the rear arms retracted.
- (17) FIGS. 11B & 11C are perspective views of an illustrative embodiment of rear arms shown in FIG. 11A with the rear arms extended in the horizontal dimension, wherein the contact portions are

shown in FIG. 11C.

(18) FIG. 11D is a perspective view of the illustrative embodiment of the illustrative embodiment of rear arms shown in FIGS. 11A-11C with a boat positioned therebetween.

(19) TABLE-US-00001 DETAILED DESCRIPTION Element Description Element Number
Enclosed Boat Trailer 10 Floor 11 Wall 12 Roof 13 Rear opening 14 Wheel 15 Rear door 16
Forward door 17 Boat 18 Boat hull 18a Launch Assist System 20 Arm 21 Biasing member 22
Wheel 24 Motor 26 Roller system 30 Roller pair 31 Roller wheel 31a Roller axle 31b Roller
mounting beam 32 Mounting beam rocker 32a Central roller 33 Lower plate 34 Cross plate 34a
Coupling member 35 First yoke 35a Second yoke 35b Lower support base 36 U-bolt 37 U-bolt
plate 38 Right rear arm 40a Left rear arm 40b Horizontal portion 42 Horizontal extender 42a Upper
portion 44 Upper extender 44a Contact portion 46 Winch 40 Spool 42 Cable 44

(20) Before the present methods and apparatuses are disclosed and described, it is to be understood that the methods and apparatuses are not limited to specific methods, specific components, or to particular implementations. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments/aspects only and is not intended to be limiting. As used in the specification and the appended claims, the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Ranges may be expressed herein as from “about” one particular value, and/or to “about” another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another embodiment. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint.

(21) “Optional” or “optionally” means that the subsequently described event or circumstance may or may not occur, and that the description includes instances where said event or circumstance occurs and instances where it does not.

(22) “Aspect” when referring to a method, apparatus, and/or component thereof does not mean that limitation, functionality, component etc. referred to as an aspect is required, but rather that it is one part of a particular illustrative disclosure and not limiting to the scope of the method, apparatus, and/or component thereof unless so indicated in the following claims.

(23) Throughout the description and claims of this specification, the word “comprise” and variations of the word, such as “comprising” and “comprises,” means “including but not limited to,” and is not intended to exclude, for example, other components, integers or steps. “Exemplary” means “an example of” and is not intended to convey an indication of a preferred or ideal embodiment. “Such as” is not used in a restrictive sense, but for explanatory purposes.

(24) Disclosed are components that can be used to perform the disclosed methods and apparatuses. These and other components are disclosed herein, and it is understood that when combinations, subsets, interactions, groups, etc. of these components are disclosed that while specific reference of each various individual and collective combinations and permutation of these may not be explicitly disclosed, each is specifically contemplated and described herein, for all methods and apparatuses. This applies to all aspects of this application including, but not limited to, steps in disclosed methods. Thus, if there are a variety of additional steps that can be performed it is understood that each of these additional steps can be performed with any specific embodiment or combination of embodiments of the disclosed methods.

(25) The present methods and apparatuses may be understood more readily by reference to the following detailed description of preferred aspects and the examples included therein and to the Figures and their previous and following description. Corresponding terms may be used interchangeably when referring to generalities of configuration and/or corresponding components, aspects, features, functionality, methods and/or materials of construction, etc. those terms.

(26) It is to be understood that the disclosure is not limited in its application to the details of

construction and the arrangements of components set forth in the following description or illustrated in the drawings. The present disclosure is capable of other embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that phraseology and terminology used herein with reference to device or element orientation (such as, for example, terms like “front”, “back”, “up”, “down”, “top”, “bottom”, and the like) are only used to simplify description, and do not alone indicate or imply that the device or element referred to must have a particular orientation. In addition, terms such as “first”, “second”, and “third” are used herein and in the appended claims for purposes of description and are not intended to indicate or imply relative importance or significance.

(27) Referring now to the drawings, FIGS. **1A** & **1B** provide perspective views of an illustrative embodiment of an enclosed boat trailer **10**, which may be configured to be supported by a plurality of wheels **15** for towing by a primary mover. As shown in FIG. **1B**, a portion of the roof and right-side wall are removed to show an interior portion of the enclosed boat trailer **10**. Another illustrative embodiment of an enclosed boat trailer **10** is shown in FIG. **1C**, wherein the illustrative embodiment in FIG. **1B** has a differently configured roller system **30** compared to that shown in FIG. **1C** as described in further detail below.

(28) Generally, the illustrative embodiments of an enclosed boat trailer **10** may be backed into or near a body of water for loading and/or unloading a boat **18** into the enclosed boat trailer **10**. The enclosed boat trailer **10** may be configured with wide-opening, side-hinged rear doors **16** at a rear opening **14** and a roller system **30** (which may be moveable and responsive to contact with the boat hull **18a**) engaged with a portion of the floor **11** of the enclosed boat trailer **10** such that the boat **18** operator may directly drive a boat **18** from the water into the enclosed boat trailer **10** without assistance from another individual. The illustrative embodiment of an enclosed boat trailer **10** may also be configured with a forward door adjacent a front portion of the enclosed boat trailer **10**. It is contemplated that a forward door **17** may allow relatively easy access to an interior portion of the enclosed boat trailer **10** even when a boat **18** positioned therein.

(29) The illustrative embodiments of an enclosed boat trailer **10** may also allow a boat **18** operator to unload a boat **18** from the trailer while inside the boat **18** and without assistance from another individual, and/or in less time and/or with less effort than compared to trailers found in the prior art. The additional time and/or personnel required when using prior art trailers may be at least due to the prior art trailer requiring a single operator to get in and out of the boat **18** various times to properly align the boat **18** with the trailer, engage the cable with the boat **18**, operate the winch, manual move the boat **18** with respect to the trailer, etc. without limitation unless otherwise indicated in the following claims. Although the illustrative embodiments of an enclosed boat trailer **10** may be configured to accommodate a boat **18** that is approximately eight feet wide, other configurations, dimensions, etc. to accommodate differently sized, shaped, and/or configured boats **18** without limitation unless otherwise indicated in the following claims. The scope of the enclosed boat trailer **10** is not limited to any specific advantage over prior art boat trailers and/or shortfall of prior art boat trailers unless otherwise indicated in the following claims.

(30) Generally, the various components of an enclosed boat trailer **10** for the illustrative embodiments thereof described in detail below (e.g., winch **14**, launch assist system **20**, roller system **30**, structures and/or methods for engaging the roller system **30** with the floor **11**, rear arms **40a**, **40b**, etc.) may be modular in nature such that an existing enclosed trailer of the proper dimensions and/or specifications may be converted to an enclosed boat trailer **10**. Alternatively, a trailer may be configured as an enclosed boat trailer **10** initially during the manufacturing of the trailer itself without limitation unless otherwise indicated in the following claims. Accordingly, the scope of the enclosed boat trailer **10** is not limited to retrofit kits, original equipment, etc. unless otherwise indicated by the following claims, and the optimal configuration of the enclosed boat trailer **10** and various components thereof (e.g., winch **14**, launch assist system **20**, roller system **30**, structures and/or methods for engaging the roller system **30** with the floor **11**, rear arms **40a**,

40b, etc.) will vary from one application to the next and may be dependent on whether the enclosed boat trailer **10** is from a retrofit of an existing trailer or configured as such from the factory.

(31) Referring still to FIGS. **1A** & **1B** (and also FIGS. **2A**, **2B**, & **3A**), an illustrative embodiment of a roller system **30** that may be used with various embodiments of an enclosed boat trailer **10** are shown in more detail. A second illustrative embodiment of a roller system **30** is shown in FIGS. **1C** and **3B**, wherein various components of the roller system **30** are shared between the two illustrative embodiments. However, the specific configuration, number, and/or arrangement of certain components of the roller system **30** may vary from one embodiment of an enclosed boat trailer **10** to the next, and are therefore in no way limiting to the scope of the present disclosure unless otherwise indicated in the following claims.

(32) As shown, a portion of the bottom surface of the enclosed boat trailer **10** may be configured with a plurality of roller pairs **31** and central rollers **33** extending from the rear adjacent the rear doors **16** forward such that the roller system **30** covers over half the length of the floor **11** of the enclosed boat trailer **10**. The roller system **30** may be configured with opposing rows or roller pairs **31** such that there is an approximate line of symmetry fore-to-aft along the centerline of the roller system **30** when viewed as shown in FIG. **3** and left-to-right when viewed as shown in FIGS. **2A** & **2B**. It is contemplated that during use, one roller pair **31** in the first row of roller pairs **31** will engage a first side of the boat hull **18a** and a corresponding roller pair **31** in the second row of roller pairs **31** will engage a second side of the boat hull **18a** at the same or approximately the same lengthwise position on the boat hull **18a** as the first roller pair **31**. In other illustrative embodiments of the enclosed boat trailer **10** not pictured herein, the roller system **30** may be configured differently than roller pairs **31** arranged in opposing rows and may instead be configured merely as opposing rollers without limitation unless otherwise indicated in the following claims.

(33) The optimal configuration and/or dimensions of the roller system **30** (e.g., width, length, distance from rear doors **16**, number of roller pairs **31**, number of center rollers **33**, number of roller pairs **31** engaged with a given roller mounting beam **32**, rows, distance from the front of the enclosed boat trailer **10**, etc.) will vary from one application of the enclosed boat trailer **10** to the next, and depend at least in part on the type, size, and configuration of the boat **18** to be positioned in the enclosed boat trailer **10**. Accordingly, the scope of the enclosed boat trailer **10** is not limited by the specific configuration and/or dimensions of the roller system **30** unless otherwise indicated in the following claims.

(34) Referring now to FIGS. **4-6**, the illustrative embodiments of a roller system **30** may be comprised of a plurality of roller pairs **31**, wherein each roller pair **31** may include two roller wheels **31a** on opposite ends of a roller axle **31b**. The roller wheels **31a** may be free to rotate with respect to the roller axle **31b**. The roller axle **31b** may be pivotally engaged with a roller mounting beam **32**, and a single roller mounting beam **32** may provide an engagement point for a plurality of roller axles **31b**. Generally, the roller axle **31b** may pivot with respect to the roller mounting beam **32** in such a manner as to account for a predetermined amount of rolling motion and/or roll misalignment of a boat **18** with respect to the enclosed boat trailer **10**, and it may also account for a predetermined amount of yaw motion and/or yaw misalignment, but the specific configuration, the amount and/or direction of relative motion and/or misalignment between the boat **18** and the enclosed boat trailer **10** accommodated, and/or pivotal limits between the roller axle **31b** and roller mounting beam **32** are in no way limiting unless otherwise indicated in the following claims.

(35) As shown, in an illustrative embodiment the two rearward roller mounting beams **32** may be engaged with six roller pairs **31** (and consequently six roller axles **31b**) generally placed in relatively close proximity to one another along the length of the roller mounting beam **32**. In FIG. **6**, the illustrative embodiment of the two forwardmost roller mounting beams **32** may be engaged with two roller pairs **31** (and consequently two roller axles **31b**), wherein each roller pair **31** is generally placed at either end of the roller mounting beam **32**. The two forwardmost roller mounting beams **32** may also be spaced from one another by a distance less than the corresponding

distance between corresponding roller mounting beams **32** positioned more rearwardly. Such a configuration may allow the roller pairs **31** toward the front of the enclosed boat trailer **10** to better accommodate portions of the boat hull **18a** adjacent the bow and roller pairs **31** toward the rear of the enclosed boat trailer **10** to better accommodate portions of the boat hull **18a** adjacent the stern without limitation unless otherwise indicated in the following claims.

(36) Additionally or alternatively, one or more roller axles **31** may be engaged with a roller mounting beam **32** via a mounting beam rocker, as shown at least in FIG. 5. The mounting beam rocker **32** may be pivotally engaged with the roller mounting beam **32** in a manner to account for a determined amount of pitching motion and/or pitch misalignment of a boat **18** with respect to the enclosed boat trailer **10**. Finally, the roller mounting beam **32** may be engaged with the floor **11** of the enclosed boat trailer **10** such that it is pivotal with respect to the enclosed boat trailer **10** and in such a manner to account for a determined amount of pitching motion and/or pitch misalignment of a boat **18** with respect to the enclosed boat trailer **10**. However, the specific configuration, the amount and/or direction of relative motion and/or misalignment between the boat **18** and the enclosed boat trailer **10** accommodated, and/or pivotal limits between the mounting beam rocker **32a** and roller mounting beam **32** and/or between the roller mounting beam **32** and floor **11** of the enclosed boat trailer **10** are in no way limiting unless otherwise indicated in the following claims.

(37) The roller system **30** may also include one or more central rollers **33**. It is contemplated that a central roller **33** may be configured to engage a keel formed in the boat hull **18a**. A first central roller **33** may be positioned at the rear of the enclosed boat trailer **10** just forward of the rear opening **14** and may be positioned as low to the floor **11** as possible, as the rearward central roller **33** may serve as the first contact point of the boat **18** with any portion of the enclosed boat trailer **10** during loading. That central roller **33** may serve as a guide for the boat **18** when loading the boat **18** onto the enclosed boat trailer **10** and may help to ensure proper positioning between the boat **18** and enclosed boat trailer **10** and/or help to protect the keel or other portions of the boat hull **18a** without limitation unless otherwise indicated in the following claims. Another central roller **33** may be positioned toward the front of the enclosed boat trailer **10** and may be elevated above the floor **11** and may also be configured to engage the keel of the boat hull **18a**. In an illustrative embodiment, the forwardmost central roller **33** may be positioned adjacent a winch **40** positioned toward a forward portion of the enclosed boat trailer **10**. Additional or fewer central rollers **33**, differently configured and/or positioned central rollers **33**, etc. may be used with the roller system **10** without limitation unless otherwise indicated in the following claims.

(38) Although a nearly infinite number of structures and/or methods for engaging a roller system **30** with the floor **11** of the enclosed boat trailer **10** may be used, an illustrative embodiment thereof will now be described in detail with the understanding that the various details and/or components thereof are not to be regarded as limiting unless otherwise indicated in the following claims. It is contemplated that for many applications it may be advantageous to configure the roller system **30** to be as low-profile as possible so as to accommodate a relatively taller boat **18** and/or to reduce the overall height of the enclosed boat trailer **10** without limitation unless otherwise indicated in the following claims. It is further contemplated that an enclosed boat trailer **10** configured as such from the factory may use other structures, methods, and/or components to provide a roller system **30** on the floor **11** of the enclosed boat trailer **10** than those described herein, and such embodiments of an enclosed boat trailer **10** are within the scope of the enclosed boat trailer **10** unless otherwise indicated in the following claims.

(39) Referring specifically to FIGS. 5 & 6, each roller support beam **32** may be pivotally engaged with a lower support base **36**, wherein the pivot point of the roller support beam **32** with respect to the lower support base **36** may be generally at the center of the roller support beam **32** with respect to its length, but which may be differently configured in other embodiments of the enclosed trailer **10** without limitation unless otherwise indicated in the following claims. A coupling member **35** may be configured to accommodate the pivotal engagement between a roller support beam **32** and a

lower support base **36**, wherein the lower support base **36** may be selected engaged with the floor **11** as described in further detail below.

(40) An illustrative embodiment of a coupling member **35** may be comprised of a first yoke **35a** that engages a roller support beam **32** and generally faces upward and a second yoke **35b** that engages the lower support base **36** and generally faces downward. The first yoke **35a** and second yoke **35b** may be formed as one integral unit and may be rotationally offset from one another by 90 degrees. The roller support beam **32** may be pivotally engaged with the first yoke **35a** such that the pivot point between the roller support beam **32** and first yoke **35a** allows for a predetermined amount of angular motion between the roller support beam **32** and coupling member **35** (and consequently between the roller support beam **32** and lower support base **36** and between the roller support beam **32** and floor **11** of the enclosed boat trailer **10**). The optimal amount of allowable relative motion therebetween will vary from one application of enclosed boat trailer **10** to the next and is therefore in no way limiting to the scope thereof unless otherwise indicated in the following claims. Additionally, other structures and/or methods may be used to engage a roller support beam **32** with a lower support base **36** without limitation unless otherwise indicated in the following claims.

(41) One or more lower plates **34** may be positioned on the floor **11** of the enclosed boat trailer **10**, and each lower support base **36** may be positioned on the upper surface of a lower plate **34**. The lower plate **34** may provide added rigidity, structural integrity, ease of use, longevity, or any other suitable purpose without limitation unless otherwise indicated in the following claims. Cross plates **34a** may be engaged with various lower plates **34** along the length thereof for additional support and/or structure integrity without limitation unless otherwise indicated in the following claims. Generally, the lower plates **34** and lower support bases **36** may be configured such that the opposing rows of roller pairs **31** may be adjusted to accommodate boats **18** having different dimensions and/or configurations. Accommodating for different boat **18** and/or boat hull **18a** widths may be accomplished by adjusting the lateral position of the lower support base **36** (i.e., the distance of the lower support base **36** from the centerline of the floor **11**).

(42) A U-bolt **37** may be positioned under the floor **11** with the studs extending through the floor **11** and on either side of the lower support base **36**. A U-bolt plate **38** may be configured with corresponding apertures to accept the studs of the U-bolt **37**, such that the lower support base **36** is effectively clamped to the floor **11** via the U-bolt **37** and U-bolt plate **38**. In the illustrative embodiments pictured herein, the lower support base **36** may be configured as a length of box-iron that may fit between the studs of the U-bolt **37**. By loosening the U-bolt plate **38**, the lower support base **36** (and consequently any roller mounting beam **32**, roller pair **31**, coupling member **35**, etc. engaged therewith) may slide laterally along the floor **11** and with respect to the lower plate **34**, U-bolt **37**, and U-bolt plate **38** to the desired position. When in the desired position, the U-bolt plate **38** may be tightened to the lower support base **36** thereby securing the position of the lower support base **36** on the floor **11**. As shown, an illustrative embodiment of an enclosed boat trailer **10** may employ a plurality of lower support bases **36** and corresponding U-bolts **37** and U-bolt plates **38** (one each, respectively, for each roller mounting beam **32**), but the specific number, position, configuration, etc. of those components is not limiting unless otherwise indicated in the following claims.

(43) Although specific and detailed reference has been made herein to a lower plate **34**, lower support base **36**, U-bolt **37**, U-bolt plate **38**, and coupling member **35** for providing a roller system **30** that allows for adjusting the lateral distance between opposing rows of roller pairs **31**, any suitable structure and/or method for adjusting that distance may be used with various embodiments of the enclosed boat trailer **10** without limitation unless otherwise indicated in the following claims. Indeed, it is contemplated that enclosed boat trailers **10** configured as such from the factory may not require at least the lower plates **34**, lower support base **36**, U-bolt **37**, and/or U-bolt plate **38** depending on the specific configuration, or may utilize other structures providing at least the same

features and/or functionality of those components as disclosed herein. Such embodiments are fully within the scope of the enclosed boat trailer **10** without limitation unless otherwise indicated in the following claims.

(44) As is evident from contrasting the illustrative embodiment of an enclosed boat trailer **10** as shown in FIGS. **1B** & **3A** with the illustrative embodiment shown in FIGS. **1C** & **3B**, various configurations of a roller system **30** may be used. By way of illustration, and without limitation unless otherwise indicated in the following claims, the illustrative embodiment shown in FIGS. **1B** & **3A** may be comprised of three roller mounting beams **32** on each side of the centerline of the enclosed boat trailer **32**. The two rearward-most roller mounting beams **32** on a given side of the centerline (wherein each rearward roller mounting beam **32** may be engaged with six roller pairs **31**) may be horizontally spaced from the corresponding roller mounting beam **32** on the other centerline by substantially the same distance. The forward-most roller mounting beam **32** on a given side of the centerline (wherein each forward roller mounting beam **32** may be engaged with two roller pairs **31**) may also be horizontally spaced from the corresponding roller mounting beam **32** on the other side of the centerline by substantially the same distance. However, the distance between the two corresponding forward-most roller mounting beams **32** may be less than the distance between two corresponding rearward-most roller mounting beams **32** without limitation unless otherwise indicated in the following claims. It is contemplated that such a configuration may accommodate a relatively conventional boat hull **18a** configuration having a relatively narrower width adjacent the bow compared to the width adjacent the stern.

(45) By way of illustration, and without limitation unless otherwise indicated in the following claims, the illustrative embodiment shown in FIGS. **1C** & **3B** may be comprised of four roller mounting beams **32** on each side of the centerline of the enclosed boat trailer **32** and two center rollers **33** positioned adjacent the rear opening **14**. Each rearward-most roller mounting beam **32** on a given side of the centerline (wherein each rearward roller mounting beam **32** may be engaged with six roller pairs **31**) may be horizontally spaced from the corresponding roller mounting beam **32** on the other centerline by substantially the same distance. The two intermediate roller mounting beams **32** on a given side of the centerline (wherein each intermediate roller mounting beam **32** may be engaged with six roller pairs **31**) may be horizontally spaced from the corresponding roller mounting beam **32** on the other centerline by substantially the same distance. However, the distance between the two corresponding rearward-most roller mounting beams **32** may be less than the distance between two corresponding intermediate roller mounting beams **32** without limitation unless otherwise indicated in the following claims. The forward-most roller mounting beam **32** on a given side of the centerline (wherein each forward roller mounting beam **32** may be engaged with two roller pairs **31**) may also be horizontally spaced from the corresponding roller mounting beam **32** on the other side of the centerline by substantially the same distance. However, the distance between the two corresponding forward-most roller mounting beams **32** may be less than the distance between two corresponding intermediate roller mounting beams **32** and may be greater than the distance between the two corresponding rearward-most roller mounting beams **32** without limitation unless otherwise indicated in the following claims. It is contemplated that such a configuration may accommodate a relatively conventional boat hull **18a** configuration having a relatively narrower width adjacent the bow compared to the width adjacent the stern.

(46) Referring now to FIG. **8**, an illustrative embodiment of an enclosed boat trailer **10** may be configured with a winch **40**, wherein the winch **40** may be positioned generally toward the front of the enclosed boat trailer **10** and ahead of the roller system **30**. The winch **40** may be configured with a spool **42** and cable **44**, wherein one end of the cable **44** may be configured with a hook to attach to an eyelet engaged with the front of a boat **18**. The winch **40** may be powered, wherein the power control may be activated and deactivated remotely, and the winch **40** may simultaneously be configured to allow for manual operation of so desired by the user. Generally, the winch **40** may be used and configured to pull the boat **18** into the enclosed boat trailer **10** and over the roller system

30. It is contemplated that remote activation and/or deactivation of the winch **40** may further facilitate safe and efficient loading and/or unloading of a boat **18** from the enclosed boat trailer **10** by a single operator, wherein the prior art would oftentimes require at least two operators to perform the same task or require a single operator to spend considerably more time than compared to using the enclosed boat trailer **10**.

(47) Referring now to FIGS. **9** & **10**, an illustrative embodiment of the enclosed boat trailer **10** pictured herein may be configured with a launch assist system **20**. An illustrative embodiment of a launch assist system **20** may be comprised of a wheel **24**, wherein the wheel **24** may be configured such that it is biased against a portion of the hull of a boat **18** positioned within the enclosed boat trailer **10**. The wheel **24** may be engaged with a rotational power source, such as an electric motor **26**. When the rotational power source is energized, the wheel **24** may turn, thereby urging the boat **18** in one direction or the other (i.e., into or out of the enclosed boat trailer **10**) depending on the direction of rotation of the wheel **24**.

(48) The wheel **24** may be mounted on a pivoting arm **21**, wherein a first end of the pivoting arm **21** may be pivotally engaged with a portion of the enclosed boat trailer **10** and wherein the pivoting arm **21** may be biased in a direction toward the hull of the boat **18** via a biasing member **22** (e.g., mechanical spring, air spring, etc.) acting on the arm **21**. In this manner adequate engagement between the surface of the wheel **24** and the hull of the boat **18** may be ensured while simultaneously allowing the position of the wheel **24** to adapt to the shape of the hull, the position of the boat **18** with respect to the enclosed boat trailer **10**, and/or to different boats **18**. It is contemplated that the launch assist system **20** may aide in initiating motion of the boat **18** out of the enclosed boat trailer **10** (such as when launching the boat **18** in a body of water) and may also aide in ensuring the boat **18** is properly positioned within the enclosed boat trailer **10** when loading the boat **18** (which may be accomplished in or with cooperation with the winch **40** as previously described above). The launch assist system **20** may be used with any suitable embodiment of an enclosed boat trailer **10** as disclosed herein or may be omitted in certain embodiments thereof without limitation unless otherwise indicated in the following claims.

(49) Referring now to FIGS. **11A-11D**, an illustrative embodiment of an enclosed boat trailer **10** may be configured with an extendable rear arm **40a**, **40b** on either side of the enclosed boat trailer **10** at the rear portion thereof. The extendable arms **40a** **40b** may be configured to help guide a boat **18** into and onto the roller system **30** and into the enclosed boat trailer **10** as described in further detail below.

(50) The illustrative embodiment of an extendable arm **40a**, **40b** may be configured with a horizontal portion **42** and an upper portion **44**. Generally, a right rear arm **40a** may be positioned on the right side of the rear opening **14** of the enclosed boat trailer **10** and a left rear arm **40b** may be positioned on the left side thereof. The horizontal portion **42** may be engaged with the floor **11** of the enclosed boat trailer **10** and angled with respect to the longitudinal axis thereof. In an illustrative embodiment the horizontal portions may be engaged with a cross plate **34a** for additional rigidity and/or structural support without limitation unless otherwise indicated in the following claims. Generally, the upper portion **44** may extend upward and at an angle from the horizontal portion **42**. In an illustrative embodiment pictured herein, the upper portion **44** may be engaged with the horizontal portion **42** such that they are generally perpendicular with respect to one another and form an L-shaped member, but other angles and/or configurations may be used without limitation unless otherwise indicated in the following claims. The horizontal and upper portions **42**, **44** may be separately formed and then engaged with one another or integrally formed as one piece without limitation unless otherwise indicated in the following claims.

(51) The horizontal portion **42** may include a horizontal extender **42a**, such that the length of the horizontal portion **42** may be increased and/or decreased within a certain predetermined range. Similarly, the upper portion **44** may include an upper extender **44a** such that the length of the upper portion **44a** may be increased and/or decreased within a certain predetermined range. In an

illustrative embodiment, both the horizontal extender **42a** and upper extender **44a** may be configured as telescoping box irons, but any suitable structure and/or method to vary the length of either the horizontal portion **42** or upper portion **44** may be used without limitation unless otherwise indicated in the following claims.

(52) As best shown in FIGS. **11C** & **11D**, the extendible arms **40a**, **40b** may be configured with a contact portion **46** on an upper of the upper portion **44**, wherein the contact portion **46** may be configured to engage a portion of the boat **18** without damaging the boat **18** and/or any component of the enclosed boat trailer **10**. That is, the contact portion **46** may be configured to allow slideable engagement with the boat hull **18a** or other portions of the boat **18** during the loading and entry process. Accordingly, in an illustrative embodiment the contact portion **46** may be constructed of a polymer and/or plastic material, such as polytetrafluoroethylene, polypropylene, polyester, polyvinyl chloride, other synthetic materials, other natural materials, and/or combinations thereof without limitation unless otherwise indicated in the following claims. Each contact portion **46** may be configured to extend from the upper portion **44** of the respective rear arm **40a**, **40b** forward through the rear opening **14** so as to prevent and/or mitigate damage that may be caused through unwanted contact of the boat **18** with a portion of the enclosed boat trailer **10** adjacent the rear opening **14** thereof without limitation unless otherwise indicated in the following claims.

(53) It is contemplated that during loading of a boat **18**, the horizontal extenders **42a** may be extended away from the rear opening **14** of the enclosed boat trailer **10**, as shown in FIGS. **11B**, **11C**, & **11D**. The angle of the horizontal portions **42** with respect to the centerline of the enclosed boat trailer **10** provides an angled guide for the boat **18** to aide the boat **18** operator in centering the boat **18** with respect to the roller system **30** and/or enclosed boat trailer **10**, wherein the opening between the upper portions **44** and/or contact portions **46** may be wider than the rear opening **14** of the enclosed boat trailer **10** and wherein the upper portions **44** and/or contact portions **46** may extender rearward beyond the rear opening **14**. The horizontal extenders **42a** may be retracted when not in use such that the rear doors **16** may be fully closed without interference from the rear arms **40a**, **40b**. The horizontal extenders **42a** may also be extended during unloading of a boat **18** without limitation unless otherwise indicated in the following claims.

(54) The upper extenders **44a** may be extended and/or retracted for various reasons, including but not limited to account for boats **18** of different configurations (e.g., hull widths, heights, shapes, etc.) and ensure that the contact portion **46** is the only touch point between the boat **18** and the rear arms **40a**, **40b**. The upper extenders **44a** may also be extended and/or retracted to account for the angle of the enclosed boat trailer **10** and roller system **30** (that is, the pitch) with respect to the boat **18**, which may vary at least depending on the terrain on which the enclosed boat trailer **10** is positioned during loading and/or unloading.

(55) Accordingly, via the horizontal extender **42a**, the distance from and relative angle with respect to the enclosed boat trailer **10** to which the extendable arms **40a**, **40b** extend may be adjustable, and the optimal distance and angle thereof may vary from one application of the enclosed boat trailer **10** to the next and may be dependent at least on the configuration of the boat **18** for which the enclosed boat trailer **10** is designed. The height of the extendable arms **40a**, **40b** (and consequently the height of any contact portion **46** and/or other component engaged therewith) may also be adjustable. Accordingly, the specific configuration, dimensions, angles, etc. of the extendable arms **40a**, **40b** in no way limits the scope of the enclosed boat trailer **10** unless otherwise indicated in the following claims.

(56) Although the illustrative apparatuses and processes described and disclosed herein may be configured for use with a specifically configured roller system **30** comprised of two opposing rows of roller pairs **31**, the scope of the present disclosure is not so limited and extends to any beneficial and/or advantageous use and/or configuration thereof without limitation unless so indicated in the following claims.

(57) The materials used to construct the apparatuses and/or components thereof may vary

depending on the specific application thereof, but it is contemplated that polymers, synthetic materials, metals, metal alloys, natural materials, and/or combinations thereof may be especially useful in some applications. Accordingly, the above-referenced elements may be constructed of any material known to those skilled in the art or later developed, which material is appropriate for the specific application of the present disclosure without departing from the spirit and scope of the present disclosure unless so indicated in the following claims.

(58) Having described preferred aspects and embodiments of the various processes and apparatuses disclosed herein, other features of the present disclosure will undoubtedly occur to those versed in the art, as will numerous modifications and alterations in the embodiments and/or aspects as illustrated herein, all of which may be achieved without departing from the spirit and scope of the present disclosure. Accordingly, the apparatuses and methods and/or embodiments thereof as pictured and described herein are for illustrative purposes only, and the scope of the present disclosure extends to all processes, apparatuses, and/or structures for providing the various benefits and/or features of the present disclosure unless so indicated in the following claims, such as all similar apparatuses for allowing modification or improvement of an enclosed boat trailer **10** including using the various elements disclosed herein as part of the enclosed boat trailer **10** as suitable for the application.

(59) While various apparatuses and methods according to the present disclosure have been described in connection with preferred aspects and specific examples, it is not intended that the scope be limited to the particular embodiments and/or aspects set forth, as the embodiments and/or aspects herein are intended in all respects to be illustrative rather than restrictive. Accordingly, the processes and embodiments pictured and described herein are no way limiting to the scope of the present disclosure unless so stated in the following claims.

(60) Although several figures are drawn to accurate scale, any dimensions provided herein are for illustrative purposes only and in no way limit the scope of the present disclosure unless so indicated in the following claims. It should be noted that the apparatuses and methods disclosed herein are not limited to the specific embodiments pictured and described herein, but rather the scope of the inventive features according to the present disclosure is defined by the claims herein. Modifications and alterations from the described embodiments will occur to those skilled in the art without departure from the spirit and scope of the present disclosure.

(61) Any of the various features, components, functionalities, advantages, aspects, configurations, process steps, process parameters, etc. of the apparatuses and methods disclosed herein may be used alone or in combination with one another depending on the compatibility of the features, components, functionalities, advantages, aspects, configurations, process steps, process parameters, etc. Accordingly, a nearly infinite number of variations of the present disclosure exist. Modifications and/or substitutions of one feature, component, functionality, aspect, configuration, process step, process parameter, etc. for another in no way limit the scope of the present disclosure unless so indicated in the following claims.

(62) It is understood that the present disclosure extends to all alternative combinations of one or more of the individual features mentioned, evident from the text and/or drawings, and/or inherently disclosed. All of these different combinations constitute various alternative aspects of the present disclosure and/or components thereof. The embodiments described herein explain the best modes known for practicing the apparatuses, methods, and/or components disclosed herein and will enable others skilled in the art to utilize the same. The claims are to be construed to include alternative embodiments to the extent permitted by the prior art.

(63) Unless otherwise expressly stated in the claims, it is in no way intended that any process or method set forth herein be construed as requiring that its steps be performed in a specific order. Accordingly, where a method claim does not actually recite an order to be followed by its steps or it is not otherwise specifically stated in the claims or descriptions that the steps are to be limited to a specific order, it is no way intended that an order be inferred, in any respect. This holds for any

possible non-express basis for interpretation, including but not limited to: matters of logic with respect to arrangement of steps or operational flow; plain meaning derived from grammatical organization or punctuation; the number or type of embodiments described in the specification.

Claims

1. An enclosed boat trailer comprising: a) a floor having a centerline along a length of said enclosed boat trailer; b) a first wall extending upward from a first edge of said floor; c) a second wall extending upward from a second edge of said floor; d) a roof connecting an upper edge of said first wall with an upper edge of said second wall; e) a rear opening formed at a rear end of said floor, wherein said rear opening is formed from said floor, said first wall, said second wall, and said roof, and wherein said rear opening has a height and a width; f) a right rear arm positioned adjacent to a right side of said rear opening, said right rear arm comprising: i) a horizontal portion engaged with said floor, wherein said horizontal portion is angled with respect to said centerline; ii) an upper portion extending upward from and angled with respect to said horizontal portion; and, g) a left rear arm positioned adjacent to a left side of said rear opening, said left rear arm comprising: i) a horizontal portion engaged with said floor, wherein said horizontal portion is angled with respect to said centerline; ii) an upper portion extending upward from and angled with respect to said horizontal portion.
2. The enclosed boat trailer according to claim 1 further comprising a roller system, said roller system comprising: a) a center roller positioned at a centerline of said floor, wherein said center roller is adjacent said rear opening; b) a first row having a first plurality of roller pairs positioned to a left side of said centerline; and, c) a second row having a first plurality of roller pairs positioned to a right side of said centerline, wherein said first row and said second row are symmetrical with respect to said centerline, and wherein said first row and said second row are spaced from said rear opening by a first distance.
3. The enclosed boat trailer according to claim 1 wherein said horizontal portion of said right rear arm is further defined as having a variable length and further comprises a horizontal extender configured to provide said variable length.
4. The enclosed boat trailer according to claim 3 wherein said upper portion of said right rear arm is further defined as extending beyond said rear opening when said variable length of said horizontal portion is at a maximum.
5. The enclosed boat trailer according to claim 4 wherein said right rear arm further comprises a contact portion engaged with said upper portion of said right rear arm, wherein said contact portion extends from said upper portion of said right rear arm through said rear opening when said variable length of said horizontal portion of said right rear arm is at said maximum.
6. A method of positioning a boat in an enclosed boat trailer, said method comprising the steps of: a) positioning a portion of said enclosed boat trailer adjacent a body of water; b) maneuvering said enclosed boat trailer such that a rear opening of said enclosed boat trailer is at least partially positioned in said body of water, wherein said enclosed boat trailer comprises: i) a right rear arm positioned adjacent to a right side of said rear opening, said right rear arm comprising: 1. A horizontal portion engaged with said floor and having a variable length, wherein said horizontal portion includes a horizontal extender configured to provide said variable length, and wherein said horizontal portion is angled with respect to said centerline; 2. An upper portion extending upward from and angled with respect to said horizontal portion, wherein said upper portion is positioned beyond said rear opening when said variable length of said horizontal portion is at a maximum; ii) a left rear arm positioned adjacent to a left side of said rear opening, said left rear arm comprising: 1. A horizontal portion engaged with said floor, wherein said horizontal portion is angled with respect to said centerline; and, 2. An upper portion extending upward from and angled with respect to said horizontal portion, wherein a distance between said upper portion of said right rear arm and

said upper portion of said left rear arm is greater than said width of said rear opening; c) positioning said boat in said body of water adjacent said enclosed boat trailer; d) positioning a portion of said boat adjacent a bow of said boat between said left rear arm and said right rear arm; and, e) moving said boat forward with respect to enclosed boat trailer.

7. The method according to claim 6 wherein said enclosed boat trailer further comprises a launch assist system, said launch assist system comprising: a) a biasing member; b) an arm pivotally engaged with said floor at a first end of said arm, wherein said biasing member provides a biasing force to said arm in a direction generally upward from said floor; and, c) a wheel pivotally engaged with a second end of said arm.

8. The method according to claim 7 further comprising the step of extending said horizontal portion of said right rear arm to said maximum.

9. The method according to claim 6 wherein said boat trailer is configured with a roller system, said roller system comprising: a) a center roller positioned at a centerline of said floor, wherein said center roller is adjacent said rear opening; b) a first row having a first plurality of roller pairs positioned to a left side of said centerline; and, c) a second row having a first plurality of roller pairs positioned to a right side of said centerline, wherein said first row and said second row are symmetrical with respect to said centerline, and wherein said first row and said second row are spaced from said rear opening by a first distance.

10. The enclosed boat trailer according to claim 1 wherein said left roller mounting beam and said right roller mounting beam are further defined as being pivotal with respect to said floor in a yaw dimension.

11. The enclosed boat trailer according to claim 1 wherein said horizontal portion of said right rear arm is further defined as having a variable length and further comprises a horizontal extender configured to provide said variable length.

12. The enclosed boat trailer according to claim 1 further comprising a roller system, said roller system comprising: a) a center roller positioned at a centerline of said floor, wherein said center roller is adjacent said rear opening; b) a first row having a first plurality of roller pairs positioned to a left side of said centerline; and, c) a second row having a first plurality of roller pairs positioned to a right side of said centerline, wherein said first row and said second are pivotable in relation to said floor, wherein said first row and said second row are symmetrical with respect to said centerline, and wherein said first row and said second row are spaced from said rear opening by a first distance.

13. The enclosed boat trailer according to claim 1 further comprising a launch assist system positioned within said trailer, wherein said launch assist system further comprises: a) a biasing member; b) an arm pivotally engaged with said floor at a first end of said arm, wherein said biasing member provides a biasing force to said arm in a direction generally upward from said floor; and, c) a wheel pivotally engaged with a second end of said arm.
