

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250251605

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

SINAY; Asif et al.

DIFFRACTIVE OPTICAL ELEMENTS WITH OPTICAL POWER

Abstract

A head mounted display system can include a camera, at least one waveguide, at least one coupling optical element that is configured such that light is coupled into said waveguide and guided therein, and at least one out-coupling element. The at least one out-coupling element can be configured to couple light that is guided within said waveguide out of said waveguide and direct said light to said camera. The at least one coupling element may comprise a diffractive optical element having optical power.

Inventors: SINAY; Asif (Tel-Aviv, IL), MEITAV; Nizan (Kiryat Ata, IL), Oh; Chulwoo (SAMMAMISH, WA), FREEDMAN; Barak (Binyamina, IL), Klug; Michael Anthony (Austin, TX), CARLSON; Adam C. (Plantation, FL)

Applicant: Magic Leap, Inc. (Plantation, FL)

Family ID: 69953291

Appl. No.: 19/185982

Filed: April 22, 2025

Related U.S. Application Data

parent US continuation 18344416 20230629 parent-grant-document US 12306409 child US 19185982

parent US continuation 17278629 20210322 parent-grant-document US 11733523 US continuation PCT/US2019/053014 20190925 child US 18344416

us-provisional-application US 62737042 20180926

Publication Classification

Int. Cl.: G02B27/01 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/344,416, filed on Jun. 29, 2023, entitled “DIFFRACTIVE OPTICAL ELEMENTS WITH OPTICAL POWER,” which is a continuation of U.S. application Ser. No. 17/278,629, filed on Mar. 22, 2021, entitled “DIFFRACTIVE OPTICAL ELEMENTS WITH OPTICAL POWER,” now U.S. Pat. No. 11,733,523, which is a national stage application under 35 U.S.C. § 371 of International Application No. PCT/US2019/053014, filed on Sep. 25, 2019, entitled “DIFFRACTIVE OPTICAL ELEMENTS WITH OPTICAL POWER,” which claims the benefit of priority under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 62/737,042, filed on Sep. 26, 2018, entitled “DIFFRACTIVE OPTICAL ELEMENTS WITH OPTICAL POWER,” which are hereby incorporated by reference herein in their entirety.

BACKGROUND

Field

[0002] The present disclosure relates to optical devices, including augmented reality imaging and visualization systems.

Description of the Related Art

[0003] Modern computing and display technologies have facilitated the development of systems for so called “virtual reality” or “augmented reality” experiences, in which digitally reproduced images or portions thereof are presented to a user in a manner wherein they seem to be, or may be perceived as, real. A virtual reality, or “VR”, scenario typically involves the presentation of digital or virtual image information without transparency to other actual real-world visual input; an augmented reality, or “AR”, scenario typically involves presentation of digital or virtual image information as an augmentation to visualization of the actual world around the user. A mixed reality, or “MR”, scenario is a type of AR scenario and typically involves virtual objects that are integrated into, and responsive to, the natural world. For example, an MR scenario may include AR image content that appears to be blocked by or is otherwise perceived to interact with objects in the real world.

[0004] Referring to FIG. 1, an augmented reality scene **10** is depicted. The user of an AR technology sees a real-world park-like setting **20** featuring people, trees, buildings in the background, and a concrete platform **30**. The user also perceives that he/she “sees” “virtual content” such as a robot statue **40** standing upon the real-world platform **30**, and a flying cartoon-like avatar character **50** which seems to be a personification of a bumble bee. These elements **50**, **40** are “virtual” in that they do not exist in the real world. Because the human visual perception system is complex, it is challenging to produce AR technology that facilitates a comfortable, natural-feeling, rich presentation of virtual image elements amongst other virtual or real-world imagery elements.

[0005] Systems and methods disclosed herein address various challenges related to AR and VR technology.

[0006] Polarizing beam splitters may be used in display systems to direct polarized light to light modulators and then to direct this light to a viewer. There is a continuing demand to reduce the sizes of display systems generally and, as a result, there is also a demand to reduce the sizes of the constituent parts of the display systems, including constituent parts utilizing polarizing beam

splitters.

SUMMARY

[0007] Various implementations described herein include display systems configured to provide illumination and/or image projection to the eye. Additionally or alternatively, the display systems can image the eye and/or the environment.

[0008] In some embodiments, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of said user. The head-mounted display system can include a frame that is configured to be supported on a head of the user. The display system can also include an image projector that is configured to project images into the user's eye to display image content in the vision field of the user. The display system can include a camera, at least one waveguide, at least one coupling optical element that is configured such that light is coupled into said waveguide and guided therein, and at least one out-coupling element. The at least one out-coupling element can be configured to couple light that is guided within said waveguide out of said waveguide and direct said light to said camera. The camera can be disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light that is coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said out-coupling coupling element such that images may be captured by said camera.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 illustrates a user's view of augmented reality (AR) through an AR device.

[0010] FIG. 2 illustrates an example of wearable display system.

[0011] FIG. 3 illustrates a conventional display system for simulating three-dimensional imagery for a user.

[0012] FIG. 4 illustrates aspects of an approach for simulating three-dimensional imagery using multiple depth planes.

[0013] FIGS. 5A-5C illustrate relationships between radius of curvature and focal radius.

[0014] FIG. 6 illustrates an example of a waveguide stack for outputting image information to a user.

[0015] FIG. 7 illustrates an example of exit beams outputted by a waveguide.

[0016] FIG. 8 illustrates an example of a stacked waveguide assembly in which each depth plane includes images formed using multiple different component colors.

[0017] FIG. 9A illustrates a cross-sectional side view of an example of a set of stacked waveguides that each includes an incoupling optical element. As discuss herein, the stack of waveguide may comprise an eyepiece.

[0018] FIG. 9B illustrates a perspective view of an example of the plurality of stacked waveguides of FIG. 9A.

[0019] FIG. 9C illustrates a top-down plan view of an example of the plurality of stacked waveguides of FIGS. 9A and 9B.

[0020] FIG. 10 schematically illustrates a cross-sectional side view of an example imaging system comprising an eyepiece, an image projector, a light source for illuminating the eye, and a camera for capturing an image of the eye.

[0021] FIG. 11A schematically illustrates the light source for illuminating the eye and the image projector for injecting images in the eye both emitting light toward an incoupling optical element on a waveguide of the eyepiece.

[0022] FIG. 11B schematically illustrates projected light from the light source and from the image projector coupled into the waveguide.

[0023] FIG. **11C** schematically illustrates how incoupled light may propagate through a waveguide by total internal reflection.

[0024] FIG. **11D** schematically illustrates light from the light source and from the image projector coupled out of the eyepiece.

[0025] FIG. **11E** schematically illustrates the waveguide and coupling optical element configured to propagate incoupled light at least along a full dimension (e.g., along the x-direction) of the coupling optical element. Light entering the eye is shown from an extended source (e.g., the imaging light will capture a region of the retina).

[0026] FIG. **12A** is a cross-sectional view that schematically shows light reflected from the retina exiting the eye and incident on the eyepiece.

[0027] FIG. **12B** schematically illustrates the example light coupled into the waveguide of the eyepiece.

[0028] FIG. **12C** schematically illustrates collimated incoupled light from the eye propagating through a waveguide toward an imaging device.

[0029] FIG. **12D** schematically shows incoupled light from the eye propagating to the one or more outcoupling optical elements.

[0030] FIG. **12E** schematically illustrates light from the eye coupled out of the waveguide by the outcoupling optical element and directed to the camera so that an image of the eye (e.g., the retina) can be captured by the camera.

[0031] FIG. **13A** schematically illustrates how the imaging system can image various portions of the eye, for example, of the retina, which can enable the orientation of the eye to be determined and the eye position tracked.

[0032] FIG. **13B** illustrates a pattern of sequentially displayed fixation targets used to cause the eye to be directed in a variety of different directions during which the retina is imaged. The resultant images correspond to non-identical portions of the retina. For example, when the eye is directed in various directions to view differently located fixation targets on the display, images captured by the camera include different portions of the retina. These images can be assembled to form a larger map or composite image of the retina.

[0033] FIG. **14A** schematically illustrates a cross-sectional view of an imaging system comprising an eyepiece and a camera for collecting light from the environment forward the eyepiece. Light from the environment is shown reflected off or emitted from one or more physical objects in the environment. Collection of light from objects in the environment in front of the eyepiece can enable images of the environment to be captured.

[0034] FIG. **14B** schematically illustrates light from the environment being coupled by the coupling optical element into a waveguide of the eyepiece.

[0035] FIG. **14C** schematically illustrates an imaging system for collecting light from the environment using a powered optical element, such as a refractive optical element (e.g., lens such as a wide field of view lens), forward the eyepiece.

[0036] FIG. **15A** schematically illustrates an example imaging system comprising a polarization selective incoupling optical element for receiving light a illumination source and coupling the light into a waveguide in an eyepiece. The eyepiece further includes a polarization selective light coupling element for coupling light out of the waveguide. A polarizer may be used to polarize the light from the illumination source and a half wave retarder may be used to rotate the orientation of the linearly polarized light so as to be turned into the waveguide by the polarization selective incoupling optical element.

[0037] FIG. **15B** schematically illustrates light from the eye (e.g., from the retina illuminated with infrared light from the illumination source) being coupled back into the waveguide and directed to a camera for image capture.

[0038] FIG. **16** schematically illustrates an imaging system configured for imaging an anterior portion (e.g., cornea) of an eye. The imaging system comprises an eyepiece such as described

above. The imaging system further includes a positive lens for collimating light collect from the anterior portion of the eye for coupling via an optical coupling element into a waveguide and propagation to a camera for image capture. The system further comprises a negative lens to offset the positive power introduced by the positive lens and to prevent inversion of images of the environment in front of the eyepiece that would otherwise be caused by the positive lens.

[0039] FIG. **17** schematically illustrates another example imaging system configured for imaging an anterior portion (e.g., cornea) of an eye. The imaging system comprises a curved wavelength selective reflector that collimates light from the anterior portion of the eye for coupling via an optical coupling element into a waveguide and propagation to a camera for image capture. The wavelength selective reflector may operate in reflection for infrared light reflected from the eye and in transmission for visible light from the environment in front of the user.

[0040] FIG. **18** schematically illustrates an example imaging system that also includes a curved wavelength selective reflector that collimates light from the anterior portion of the eye for coupling via an optical coupling element into a waveguide and propagation to a camera for image capture. Polarization selectivity may be employed to assist in controlling the path of the light reflected from the eye. Illumination of the eye is provided via the waveguide instead of a plurality of light source between the waveguide and the eye as shown in FIG. **18**.

[0041] FIG. **19** schematically illustrates an imaging system that includes a shutter to assist in a procedure for subtracting out noise.

[0042] FIGS. **20A-20E** schematically illustrate an alternative procedure for subtracting out noise using wavelength modulation in conjunction with a curved wavelength selective reflector.

[0043] FIG. **21** shows an example eyepiece that can be used to simultaneously project light into a user's eye to provide image content thereto while receiving image data of the user's eye or of the environment in front of the user.

[0044] FIG. **22** illustrates a cross-sectional side view of an example of a cholesteric liquid crystal diffraction grating (CLCG) having a plurality of uniform chiral structures.

[0045] FIG. **23** illustrates an example of an imaging system comprising a forward-facing camera configured to images a wearer's eye using a cholesteric liquid crystal (CLC) off-axis mirror.

[0046] FIG. **24** shows another example eyepiece that can be used to simultaneously project light into a user's eye to provide image content thereto while receiving image data of the user's eye or of the environment in front of the user. In this example, the coupling optical element configured to receive light in from the user's or from the environment in front of the user is displaced laterally from the image content out-coupling optical element (e.g., exit pupil expander).

[0047] FIG. **25** shows another example eyepiece similar to that shown in FIG. **24**, however, the coupling optical element configured to receive light in from the user's or from the environment in front of the user is not laterally spaced apart from the image content out-coupling optical element (e.g., exit pupil expander).

[0048] FIG. **26** shows an example eyepiece including first and second coupling optical elements configured to couple light received from the user's or from the environment into a waveguide to be guided therein as well as first and second out-coupling optical elements configured to couple light guided within the waveguide out of said waveguide to one or more cameras.

[0049] FIG. **27** is a cross-section through the waveguide, consolidating optical element, and out-coupling optical elements shown in FIG. **26** showing a polarizer in an optical path between one of the out-coupling optical elements and the camera. The polarizer may be used to remove unwanted glint reflections form the cornea when obtaining images of the retina.

[0050] The drawings are provided to illustrate example embodiments and are not intended to limit the scope of the disclosure. Like reference numerals refer to like parts throughout.

DETAILED DESCRIPTION

[0051] Reference will now be made to the figures, in which like reference numerals refer to like parts throughout.

[0052] FIG. 2 illustrates an example of wearable display system **60**. The display system **60** includes a display **70**, and various mechanical and electronic modules and systems to support the functioning of that display **70**. The display **70** may be coupled to a frame **80**, which is wearable by a display system user or viewer **90** and which is configured to position the display **70** in front of the eyes of the user **90**. The display **70** may be considered eyewear in some embodiments. In some embodiments, a speaker **100** is coupled to the frame **80** and configured to be positioned adjacent the ear canal of the user **90** (in some embodiments, another speaker, not shown, may optionally be positioned adjacent the other ear canal of the user to provide stereo/shapeable sound control). The display system may also include one or more microphones **110** or other devices to detect sound. In some embodiments, the microphone is configured to allow the user to provide inputs or commands to the system **60** (e.g., the selection of voice menu commands, natural language questions, etc.), and/or may allow audio communication with other persons (e.g., with other users of similar display systems). The microphone may further be configured as a peripheral sensor to collect audio data (e.g., sounds from the user and/or environment). In some embodiments, the display system may also include a peripheral sensor **120a**, which may be separate from the frame **80** and attached to the body of the user **90** (e.g., on the head, torso, an extremity, etc. of the user **90**). The peripheral sensor **120a** may be configured to acquire data characterizing a physiological state of the user **90** in some embodiments. For example, the sensor **120a** may be an electrode.

[0053] With continued reference to FIG. 2, the display **70** is operatively coupled by communications link **130**, such as by a wired lead or wireless connectivity, to a local data processing module **140** which may be mounted in a variety of configurations, such as fixedly attached to the frame **80**, fixedly attached to a helmet or hat worn by the user, embedded in headphones, or otherwise removably attached to the user **90** (e.g., in a backpack-style configuration, in a belt-coupling style configuration). Similarly, the sensor **120a** may be operatively coupled by communications link **120b**, e.g., a wired lead or wireless connectivity, to the local processor and data module **140**. The local processing and data module **140** may comprise a hardware processor, as well as digital memory, such as non-volatile memory (e.g., flash memory or hard disk drives), both of which may be utilized to assist in the processing, caching, and storage of data. The data include data a) captured from sensors (which may be, e.g., operatively coupled to the frame **80** or otherwise attached to the user **90**), such as image capture devices (such as cameras), microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, gyros, and/or other sensors disclosed herein; and/or b) acquired and/or processed using remote processing module **150** and/or remote data repository **160** (including data relating to virtual content), possibly for passage to the display **70** after such processing or retrieval. The local processing and data module **140** may be operatively coupled by communication links **170**, **180**, such as via a wired or wireless communication links, to the remote processing module **150** and remote data repository **160** such that these remote modules **150**, **160** are operatively coupled to each other and available as resources to the local processing and data module **140**. In some embodiments, the local processing and data module **140** may include one or more of the image capture devices, microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, and/or gyros. In some other embodiments, one or more of these sensors may be attached to the frame **80**, or may be standalone structures that communicate with the local processing and data module **140** by wired or wireless communication pathways.

[0054] With continued reference to FIG. 2, in some embodiments, the remote processing module **150** may comprise one or more processors configured to analyze and process data and/or image information. In some embodiments, the remote data repository **160** may comprise a digital data storage facility, which may be available through the internet or other networking configuration in a "cloud" resource configuration. In some embodiments, the remote data repository **160** may include one or more remote servers, which provide information, e.g., information for generating augmented reality content, to the local processing and data module **140** and/or the remote processing module

150. In some embodiments, all data is stored and all computations are performed in the local processing and data module, allowing fully autonomous use from a remote module.

[0055] With reference now to FIG. 3, the perception of an image as being “three-dimensional” or “3-D” may be achieved by providing slightly different presentations of the image to each eye of the viewer. FIG. 3 illustrates a conventional display system for simulating three-dimensional imagery for a user. Two distinct images **190, 200**—one for each eye **210, 220**—are outputted to the user. The images **190, 200** are spaced from the eyes **210, 220** by a distance **230** along an optical or z-axis that is parallel to the line of sight of the viewer. The images **190, 200** are flat and the eyes **210, 220** may focus on the images by assuming a single accommodated state. Such 3-D display systems rely on the human visual system to combine the images **190, 200** to provide a perception of depth and/or scale for the combined image.

[0056] It will be appreciated, however, that the human visual system is more complicated and providing a realistic perception of depth is more challenging. For example, many viewers of conventional “3-D” display systems find such systems to be uncomfortable or may not perceive a sense of depth at all. Without being limited by theory, it is believed that viewers of an object may perceive the object as being “three-dimensional” due to a combination of vergence and accommodation. Vergence movements (i.e., rotation of the eyes so that the pupils move toward or away from each other to converge the lines of sight of the eyes to fixate upon an object) of the two eyes relative to each other are closely associated with focusing (or “accommodation”) of the lenses and pupils of the eyes. Under normal conditions, changing the focus of the lenses of the eyes, or accommodating the eyes, to change focus from one object to another object at a different distance will automatically cause a matching change in vergence to the same distance, under a relationship known as the “accommodation-vergence reflex,” as well as pupil dilation or constriction. Likewise, a change in vergence will trigger a matching change in accommodation of lens shape and pupil size, under normal conditions. As noted herein, many stereoscopic or “3-D” display systems display a scene using slightly different presentations (and, so, slightly different images) to each eye such that a three-dimensional perspective is perceived by the human visual system. Such systems are uncomfortable for many viewers, however, since they, among other things, simply provide different presentations of a scene, but with the eyes viewing all the image information at a single accommodated state, and work against the “accommodation-vergence reflex.” Display systems that provide a better match between accommodation and vergence may form more realistic and comfortable simulations of three-dimensional imagery.

[0057] FIG. 4 illustrates aspects of an approach for simulating three-dimensional imagery using multiple depth planes. With reference to FIG. 4, objects at various distances from eyes **210, 220** on the z-axis are accommodated by the eyes **210, 220** so that those objects are in focus. The eyes **210, 220** assume particular accommodated states to bring into focus objects at different distances along the z-axis. Consequently, a particular accommodated state may be said to be associated with a particular one of depth planes **240**, with has an associated focal distance, such that objects or parts of objects in a particular depth plane are in focus when the eye is in the accommodated state for that depth plane. In some embodiments, three-dimensional imagery may be simulated by providing different presentations of an image for each of the eyes **210, 220**, and also by providing different presentations of the image corresponding to each of the depth planes. While shown as being separate for clarity of illustration, it will be appreciated that the fields of view of the eyes **210, 220** may overlap, for example, as distance along the z-axis increases. In addition, while shown as flat for ease of illustration, it will be appreciated that the contours of a depth plane may be curved in physical space, such that all features in a depth plane are in focus with the eye in a particular accommodated state.

[0058] The distance between an object and the eye **210** or **220** may also change the amount of divergence of light from that object, as viewed by that eye. FIGS. 5A-5C illustrate relationships between distance and the divergence of light rays. The distance between the object and the eye **210**

is represented by, in order of decreasing distance, R1, R2, and R3. As shown in FIGS. 5A-5C, the light rays become more divergent as distance to the object decreases. As distance increases, the light rays become more collimated. Stated another way, it may be said that the light field produced by a point (the object or a part of the object) has a spherical wavefront curvature, which is a function of how far away the point is from the eye of the user. The curvature increases with decreasing distance between the object and the eye **210**. Consequently, at different depth planes, the degree of divergence of light rays is also different, with the degree of divergence increasing with decreasing distance between depth planes and the viewer's eye **210**. While only a single eye **210** is illustrated for clarity of illustration in FIGS. 5A-5C and other figures herein, it will be appreciated that the discussions regarding eye **210** may be applied to both eyes **210** and **220** of a viewer.

[0059] Without being limited by theory, it is believed that the human eye typically can interpret a finite number of depth planes to provide depth perception. Consequently, a highly believable simulation of perceived depth may be achieved by providing, to the eye, different presentations of an image corresponding to each of these limited number of depth planes. The different presentations may be separately focused by the viewer's eyes, thereby helping to provide the user with depth cues based on the accommodation of the eye required to bring into focus different image features for the scene located on different depth plane and/or based on observing different image features on different depth planes being out of focus.

[0060] FIG. 6 illustrates an example of a waveguide stack for outputting image information to a user. A display system **250** includes a stack of waveguides, or stacked waveguide assembly, **260** that may be utilized to provide three-dimensional perception to the eye/brain using a plurality of waveguides **270, 280, 290, 300, 310**. In some embodiments, the display system **250** is the system **60** of FIG. 2, with FIG. 6 schematically showing some parts of that system **60** in greater detail. For example, the waveguide assembly **260** may be part of the display **70** of FIG. 2. It will be appreciated that the display system **250** may be considered a light field display in some embodiments. In addition, the waveguide assembly **260** may also be referred to as an eyepiece.

[0061] With continued reference to FIG. 6, the waveguide assembly **260** may also include a plurality of features **320, 330, 340, 350** between the waveguides. In some embodiments, the features **320, 330, 340, 350** may be one or more lenses. The waveguides **270, 280, 290, 300, 310** and/or the plurality of lenses **320, 330, 340, 350** may be configured to send image information to the eye with various levels of wavefront curvature or light ray divergence. Each waveguide level may be associated with a particular depth plane and may be configured to output image information corresponding to that depth plane. Image injection devices **360, 370, 380, 390, 400** may function as a source of light for the waveguides and may be utilized to inject image information into the waveguides **270, 280, 290, 300, 310**, each of which may be configured, as described herein, to distribute incoming light across each respective waveguide, for output toward the eye **210**. Light exits an output surface **410, 420, 430, 440, 450** of the image injection devices **360, 370, 380, 390, 400** and is injected into a corresponding input surface **460, 470, 480, 490, 500** of the waveguides **270, 280, 290, 300, 310**. In some embodiments, the each of the input surfaces **460, 470, 480, 490, 500** may be an edge of a corresponding waveguide, or may be part of a major surface of the corresponding waveguide (that is, one of the waveguide surfaces directly facing the world **510** or the viewer's eye **210**). In some embodiments, a single beam of light (e.g. a collimated beam) may be injected into each waveguide to output an entire field of cloned collimated beams that are directed toward the eye **210** at particular angles (and amounts of divergence) corresponding to the depth plane associated with a particular waveguide. In some embodiments, a single one of the image injection devices **360, 370, 380, 390, 400** may be associated with and inject light into a plurality (e.g., three) of the waveguides **270, 280, 290, 300, 310**.

[0062] In some embodiments, the image injection devices **360, 370, 380, 390, 400** are discrete displays that each produce image information for injection into a corresponding waveguide **270, 280, 290, 300, 310**, respectively. In some other embodiments, the image injection devices **360, 370,**

380, 390, 400 are the output ends of a single multiplexed display which may, e.g., pipe image information via one or more optical conduits (such as fiber optic cables) to each of the image injection devices **360, 370, 380, 390, 400**. It will be appreciated that the image information provided by the image injection devices **360, 370, 380, 390, 400** may include light of different wavelengths, or colors (e.g., different component colors, as discussed herein).

[0063] In some embodiments, the light injected into the waveguides **270, 280, 290, 300, 310** is provided by a light projector system **520**, which comprises a light module **540**, which may include a light emitter, such as a light emitting diode (LED). The light from the light module **540** may be directed to and modified by a light modulator **530**, e.g., a spatial light modulator, via a beam splitter **550**. The light modulator **530** may be configured to change the perceived intensity of the light injected into the waveguides **270, 280, 290, 300, 310**. Examples of spatial light modulators include liquid crystal displays (LCD) including a liquid crystal on silicon (LCOS) displays. It will be appreciated that the image injection devices **360, 370, 380, 390, 400** are illustrated schematically and, in some embodiments, these image injection devices may represent different light paths and locations in a common projection system configured to output light into associated ones of the waveguides **270, 280, 290, 300, 310**.

[0064] In some embodiments, the display system **250** may be a scanning fiber display comprising one or more scanning fibers configured to project light in various patterns (e.g., raster scan, spiral scan, Lissajous patterns, etc.) into one or more waveguides **270, 280, 290, 300, 310** and ultimately to the eye **210** of the viewer. In some embodiments, the illustrated image injection devices **360, 370, 380, 390, 400** may schematically represent a single scanning fiber or a bundle of scanning fibers configured to inject light into one or a plurality of the waveguides **270, 280, 290, 300, 310**. In some other embodiments, the illustrated image injection devices **360, 370, 380, 390, 400** may schematically represent a plurality of scanning fibers or a plurality of bundles of scanning fibers, each of which are configured to inject light into an associated one of the waveguides **270, 280, 290, 300, 310**. It will be appreciated that one or more optical fibers may be configured to transmit light from the light module **540** to the one or more waveguides **270, 280, 290, 300, 310**. It will be appreciated that one or more intervening optical structures may be provided between the scanning fiber, or fibers, and the one or more waveguides **270, 280, 290, 300, 310** to, e.g., redirect light exiting the scanning fiber into the one or more waveguides **270, 280, 290, 300, 310**.

[0065] A controller **560** controls the operation of one or more of the stacked waveguide assembly **260**, including operation of the image injection devices **360, 370, 380, 390, 400**, the light source **540**, and the light modulator **530**. In some embodiments, the controller **560** is part of the local data processing module **140**. The controller **560** includes programming (e.g., instructions in a non-transitory medium) that regulates the timing and provision of image information to the waveguides **270, 280, 290, 300, 310** according to, e.g., any of the various schemes disclosed herein. In some embodiments, the controller may be a single integral device, or a distributed system connected by wired or wireless communication channels. The controller **560** may be part of the processing modules **140** or **150** (FIG. 2) in some embodiments.

[0066] With continued reference to FIG. 6, the waveguides **270, 280, 290, 300, 310** may be configured to propagate light within each respective waveguide by total internal reflection (TIR). The waveguides **270, 280, 290, 300, 310** may each be planar or have another shape (e.g., curved), with major top and bottom surfaces and edges extending between those major top and bottom surfaces. In the illustrated configuration, the waveguides **270, 280, 290, 300, 310** may each include out-coupling optical elements **570, 580, 590, 600, 610** that are configured to extract light out of a waveguide by redirecting the light, propagating within each respective waveguide, out of the waveguide to output image information to the eye **210**. Extracted light may also be referred to as out-coupled light and the out-coupling optical elements light may also be referred to light extracting optical elements. An extracted beam of light may be outputted by the waveguide at locations at which the light propagating in the waveguide strikes a light extracting optical element.

The out-coupling optical elements **570, 580, 590, 600, 610** may, for example, be gratings, including diffractive optical features, as discussed further herein. While illustrated disposed at the bottom major surfaces of the waveguides **270, 280, 290, 300, 310**, for ease of description and drawing clarity, in some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** may be disposed at the top and/or bottom major surfaces, and/or may be disposed directly in the volume of the waveguides **270, 280, 290, 300, 310**, as discussed further herein. In some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** may be formed in a layer of material that is attached to a transparent substrate to form the waveguides **270, 280, 290, 300, 310**. In some other embodiments, the waveguides **270, 280, 290, 300, 310** may be a monolithic piece of material and the out-coupling optical elements **570, 580, 590, 600, 610** may be formed on a surface and/or in the interior of that piece of material.

[0067] With continued reference to FIG. **6**, as discussed herein, each waveguide **270, 280, 290, 300, 310** is configured to output light to form an image corresponding to a particular depth plane. For example, the waveguide **270** nearest the eye may be configured to deliver collimated light (which was injected into such waveguide **270**), to the eye **210**. The collimated light may be representative of the optical infinity focal plane. The next waveguide up **280** may be configured to send out collimated light which passes through the first lens **350** (e.g., a negative lens) before it can reach the eye **210**; such first lens **350** may be configured to create a slight convex wavefront curvature so that the eye/brain interprets light coming from that next waveguide up **280** as coming from a first focal plane closer inward toward the eye **210** from optical infinity. Similarly, the third up waveguide **290** passes its output light through both the first **350** and second **340** lenses before reaching the eye **210**; the combined optical power of the first **350** and second **340** lenses may be configured to create another incremental amount of wavefront curvature so that the eye/brain interprets light coming from the third waveguide **290** as coming from a second focal plane that is even closer inward toward the person from optical infinity than was light from the next waveguide up **280**.

[0068] The other waveguide layers **300, 310** and lenses **330, 320** are similarly configured, with the highest waveguide **310** in the stack sending its output through all of the lenses between it and the eye for an aggregate focal power representative of the closest focal plane to the person. To compensate for the stack of lenses **320, 330, 340, 350** when viewing/interpreting light coming from the world **510** on the other side of the stacked waveguide assembly **260**, a compensating lens layer **620** may be disposed at the top of the stack to compensate for the aggregate power of the lens stack **320, 330, 340, 350** below. Such a configuration provides as many perceived focal planes as there are available waveguide/lens pairings. Both the out-coupling optical elements of the waveguides and the focusing aspects of the lenses may be static (i.e., not dynamic or electro-active). In some alternative embodiments, either or both may be dynamic using electro-active features.

[0069] In some embodiments, two or more of the waveguides **270, 280, 290, 300, 310** may have the same associated depth plane. For example, multiple waveguides **270, 280, 290, 300, 310** may be configured to output images set to the same depth plane, or multiple subsets of the waveguides **270, 280, 290, 300, 310** may be configured to output images set to the same plurality of depth planes, with one set for each depth plane. This can provide advantages for forming a tiled image to provide an expanded field of view at those depth planes.

[0070] With continued reference to FIG. **6**, the out-coupling optical elements **570, 580, 590, 600, 610** may be configured to both redirect light out of their respective waveguides and to output this light with the appropriate amount of divergence or collimation for a particular depth plane associated with the waveguide. As a result, waveguides having different associated depth planes may have different configurations of out-coupling optical elements **570, 580, 590, 600, 610**, which output light with a different amount of divergence depending on the associated depth plane. In some embodiments, the light extracting optical elements **570, 580, 590, 600, 610** may be volumetric or surface features, which may be configured to output light at specific angles. For

example, the light extracting optical elements **570, 580, 590, 600, 610** may be volume holograms, surface holograms, and/or diffraction gratings. In some embodiments, the features **320, 330, 340, 350** may not be lenses; rather, they may simply be spacers (e.g., cladding layers and/or structures for forming air gaps).

[0071] In some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** are diffractive features that form a diffraction pattern, or “diffractive optical element” (also referred to herein as a “DOE”). Preferably, the DOE's have a sufficiently low diffraction efficiency so that only a portion of the light of the beam is deflected away toward the eye **210** with each intersection of the DOE, while the rest continues to move through a waveguide via TIR. The light carrying the image information is thus divided into a number of related exit beams that exit the waveguide at a multiplicity of locations and the result is a fairly uniform pattern of exit emission toward the eye **210** for this particular collimated beam bouncing around within a waveguide.

[0072] In some embodiments, one or more DOEs may be switchable between “on” states in which they actively diffract, and “off” states in which they do not significantly diffract. For instance, a switchable DOE may comprise a layer of polymer dispersed liquid crystal, in which microdroplets comprise a diffraction pattern in a host medium, and the refractive index of the microdroplets may be switched to substantially match the refractive index of the host material (in which case the pattern does not appreciably diffract incident light) or the microdroplet may be switched to an index that does not match that of the host medium (in which case the pattern actively diffracts incident light).

[0073] In some embodiments, a camera assembly **630** (e.g., a digital camera, including visible light and infrared light cameras) may be provided to capture images of the eye **210** and/or tissue around the eye **210** to, e.g., detect user inputs and/or to monitor the physiological state of the user. As used herein, a camera may be any image capture device. In some embodiments, the camera assembly **630** may include an image capture device and a light source to project light (e.g., infrared light) to the eye, which may then be reflected by the eye and detected by the image capture device. In some embodiments, the camera assembly **630** may be attached to the frame **80** (FIG. 2) and may be in electrical communication with the processing modules **140** and/or **150**, which may process image information from the camera assembly **630**. In some embodiments, one camera assembly **630** may be utilized for each eye, to separately monitor each eye.

[0074] With reference now to FIG. 7, an example of exit beams outputted by a waveguide is shown. One waveguide is illustrated, but it will be appreciated that other waveguides in the waveguide assembly **260** (FIG. 6) may function similarly, where the waveguide assembly **260** includes multiple waveguides. Light **640** is injected into the waveguide **270** at the input surface **460** of the waveguide **270** and propagates within the waveguide **270** by TIR. At points where the light **640** impinges on the DOE **570**, a portion of the light exits the waveguide as exit beams **650**. The exit beams **650** are illustrated as substantially parallel but, as discussed herein, they may also be redirected to propagate to the eye **210** at an angle (e.g., forming divergent exit beams), depending on the depth plane associated with the waveguide **270**. It will be appreciated that substantially parallel exit beams may be indicative of a waveguide with out-coupling optical elements that out-couple light to form images that appear to be set on a depth plane at a large distance (e.g., optical infinity) from the eye **210**. Other waveguides or other sets of out-coupling optical elements may output an exit beam pattern that is more divergent, which would require the eye **210** to accommodate to a closer distance to bring it into focus on the retina and would be interpreted by the brain as light from a distance closer to the eye **210** than optical infinity.

[0075] In some embodiments, a full color image may be formed at each depth plane by overlaying images in each of the component colors, e.g., three or more component colors. FIG. 8 illustrates an example of a stacked waveguide assembly in which each depth plane includes images formed using multiple different component colors. The illustrated embodiment shows depth planes **240a-240f**, although more or fewer depths are also contemplated. Each depth plane may have three or more

component color images associated with it, including: a first image of a first color, G; a second image of a second color, R; and a third image of a third color, B. Different depth planes are indicated in the figure by different numbers for diopters (dpt) following the letters G, R, and B. Just as examples, the numbers following each of these letters indicate diopters (1/m), or inverse distance of the depth plane from a viewer, and each box in the figures represents an individual component color image. In some embodiments, to account for differences in the eye's focusing of light of different wavelengths, the exact placement of the depth planes for different component colors may vary. For example, different component color images for a given depth plane may be placed on depth planes corresponding to different distances from the user. Such an arrangement may increase visual acuity and user comfort and/or may decrease chromatic aberrations.

[0076] In some embodiments, light of each component color may be outputted by a single dedicated waveguide and, consequently, each depth plane may have multiple waveguides associated with it. In such embodiments, each box in the figures including the letters G, R, or B may be understood to represent an individual waveguide, and three waveguides may be provided per depth plane where three component color images are provided per depth plane. While the waveguides associated with each depth plane are shown adjacent to one another in this drawing for ease of description, it will be appreciated that, in a physical device, the waveguides may all be arranged in a stack with one waveguide per level. In some other embodiments, multiple component colors may be outputted by the same waveguide, such that, e.g., only a single waveguide may be provided per depth plane.

[0077] With continued reference to FIG. 8, in some embodiments, G is the color green, R is the color red, and B is the color blue. In some other embodiments, other colors associated with other wavelengths of light, including magenta and cyan, may be used in addition to or may replace one or more of red, green, or blue.

[0078] It will be appreciated that references to a given color of light throughout this disclosure will be understood to encompass light of one or more wavelengths within a range of wavelengths of light that are perceived by a viewer as being of that given color. For example, red light may include light of one or more wavelengths in the range of about 620-780 nm, green light may include light of one or more wavelengths in the range of about 492-577 nm, and blue light may include light of one or more wavelengths in the range of about 435-493 nm.

[0079] In some embodiments, the light source **540** (FIG. 6) may be configured to emit light of one or more wavelengths outside the visual perception range of the viewer, for example, infrared and/or ultraviolet wavelengths. In addition, the in-coupling, out-coupling, and other light redirecting structures of the waveguides of the display **250** may be configured to direct and emit this light out of the display towards the user's eye **210**, e.g., for imaging and/or user stimulation applications.

[0080] With reference now to FIG. 9A, in some embodiments, light impinging on a waveguide may need to be redirected to in-couple that light into the waveguide. An in-coupling optical element may be used to redirect and in-couple the light into its corresponding waveguide. FIG. 9A illustrates a cross-sectional side view of an example of a plurality or set **660** of stacked waveguides that each includes an in-coupling optical element. The waveguides may each be configured to output light of one or more different wavelengths, or one or more different ranges of wavelengths. It will be appreciated that the stack **660** may correspond to the stack **260** (FIG. 6) and the illustrated waveguides of the stack **660** may correspond to part of the plurality of waveguides **270, 280, 290, 300, 310**, except that light from one or more of the image injection devices **360, 370, 380, 390, 400** is injected into the waveguides from a position that requires light to be redirected for in-coupling.

[0081] The illustrated set **660** of stacked waveguides includes waveguides **670, 680, and 690**. Each waveguide includes an associated in-coupling optical element (which may also be referred to as a light input area on the waveguide), with, e.g., in-coupling optical element **700** disposed on a major surface (e.g., an upper major surface) of waveguide **670**, in-coupling optical element **710** disposed on a major surface (e.g., an upper major surface) of waveguide **680**, and in-coupling optical

element **720** disposed on a major surface (e.g., an upper major surface) of waveguide **690**. In some embodiments, one or more of the in-coupling optical elements **700, 710, 720** may be disposed on the bottom major surface of the respective waveguide **670, 680, 690** (particularly where the one or more in-coupling optical elements are reflective, deflecting optical elements). As illustrated, the in-coupling optical elements **700, 710, 720** may be disposed on the upper major surface of their respective waveguide **670, 680, 690** (or the top of the next lower waveguide), particularly where those in-coupling optical elements are transmissive, deflecting optical elements. In some embodiments, the in-coupling optical elements **700, 710, 720** may be disposed in the body of the respective waveguide **670, 680, 690**. In some embodiments, as discussed herein, the in-coupling optical elements **700, 710, 720** are wavelength selective, such that they selectively redirect one or more wavelengths of light, while transmitting other wavelengths of light. While illustrated on one side or corner of their respective waveguide **670, 680, 690**, it will be appreciated that the in-coupling optical elements **700, 710, 720** may be disposed in other areas of their respective waveguide **670, 680, 690** in some embodiments.

[0082] As illustrated, the in-coupling optical elements **700, 710, 720** may be laterally offset from one another. In some embodiments, each in-coupling optical element may be offset such that it receives light without that light passing through another in-coupling optical element. For example, each in-coupling optical element **700, 710, 720** may be configured to receive light from a different image injection device **360, 370, 380, 390**, and **400** as shown in FIG. 6, and may be separated (e.g., laterally spaced apart) from other in-coupling optical elements **700, 710, 720** such that it substantially does not receive light from the other ones of the in-coupling optical elements **700, 710, 720**.

[0083] Each waveguide also includes associated light distributing elements, with, e.g., light distributing elements **730** disposed on a major surface (e.g., a top major surface) of waveguide **670**, light distributing elements **740** disposed on a major surface (e.g., a top major surface) of waveguide **680**, and light distributing elements **750** disposed on a major surface (e.g., a top major surface) of waveguide **690**. In some other embodiments, the light distributing elements **730, 740, 750**, may be disposed on a bottom major surface of associated waveguides **670, 680, 690**, respectively. In some other embodiments, the light distributing elements **730, 740, 750**, may be disposed on both top and bottom major surface of associated waveguides **670, 680, 690**, respectively; or the light distributing elements **730, 740, 750**, may be disposed on different ones of the top and bottom major surfaces in different associated waveguides **670, 680, 690**, respectively.

[0084] The waveguides **670, 680, 690** may be spaced apart and separated by, e.g., gas, liquid, and/or solid layers of material. For example, as illustrated, layer **760a** may separate waveguides **670** and **680**; and layer **760b** may separate waveguides **680** and **690**. In some embodiments, the layers **760a** and **760b** are formed of low refractive index materials (that is, materials having a lower refractive index than the material forming the immediately adjacent one of waveguides **670, 680, 690**). Preferably, the refractive index of the material forming the layers **760a, 760b** is 0.05 or more, or 0.10 or less than the refractive index of the material forming the waveguides **670, 680, 690**.

Advantageously, the lower refractive index layers **760a, 760b** may function as cladding layers that facilitate total internal reflection (TIR) of light through the waveguides **670, 680, 690** (e.g., TIR between the top and bottom major surfaces of each waveguide). In some embodiments, the layers **760a, 760b** are formed of air. While not illustrated, it will be appreciated that the top and bottom of the illustrated set **660** of waveguides may include immediately neighboring cladding layers.

[0085] Preferably, for ease of manufacturing and other considerations, the material forming the waveguides **670, 680, 690** are similar or the same, and the material forming the layers **760a, 760b** are similar or the same. In some embodiments, the material forming the waveguides **670, 680, 690** may be different between one or more waveguides, and/or the material forming the layers **760a, 760b** may be different, while still holding to the various refractive index relationships noted above.

[0086] With continued reference to FIG. 9A, light rays **770, 780, 790** are incident on the set **660** of

waveguides. It will be appreciated that the light rays **770, 780, 790** may be injected into the waveguides **670, 680, 690** by one or more image injection devices **360, 370, 380, 390, 400** (FIG. 6).

[0087] In some embodiments, the light rays **770, 780, 790** have different properties, e.g., different wavelengths or different ranges of wavelengths, which may correspond to different colors. The in-coupling optical elements **700, 710, 720** each deflect the incident light such that the light propagates through a respective one of the waveguides **670, 680, 690** by TIR. In some embodiments, the in-coupling optical elements **700, 710, 720** each selectively deflect one or more particular wavelengths of light, while transmitting other wavelengths to an underlying waveguide and associated in-coupling optical element.

[0088] For example, in-coupling optical element **700** may be configured to deflect ray **770**, which has a first wavelength or range of wavelengths, while transmitting rays **780** and **790**, which have different second and third wavelengths or ranges of wavelengths, respectively. The transmitted ray **780** impinges on and is deflected by the in-coupling optical element **710**, which is configured to deflect light of a second wavelength or range of wavelengths. The ray **790** is deflected by the in-coupling optical element **720**, which is configured to selectively deflect light of third wavelength or range of wavelengths.

[0089] With continued reference to FIG. 9A, the deflected light rays **770, 780, 790** are deflected so that they propagate through a corresponding waveguide **670, 680, 690**; that is, the in-coupling optical elements **700, 710, 720** of each waveguide deflects light into that corresponding waveguide **670, 680, 690** to in-couple light into that corresponding waveguide. The light rays **770, 780, 790** are deflected at angles that cause the light to propagate through the respective waveguide **670, 680, 690** by TIR. The light rays **770, 780, 790** propagate through the respective waveguide **670, 680, 690** by TIR until impinging on the waveguide's corresponding light distributing elements **730, 740, 750**.

[0090] With reference now to FIG. 9B, a perspective view of an example of the plurality of stacked waveguides of FIG. 9A is illustrated. As noted above, the in-coupled light rays **770, 780, 790**, are deflected by the in-coupling optical elements **700, 710, 720**, respectively, and then propagate by TIR within the waveguides **670, 680, 690**, respectively. The light rays **770, 780, 790** then impinge on the light distributing elements **730, 740, 750**, respectively. The light distributing elements **730, 740, 750** deflect the light rays **770, 780, 790** so that they propagate towards the out-coupling optical elements **800, 810, 820**, respectively.

[0091] In some embodiments, the light distributing elements **730, 740, 750** are orthogonal pupil expanders (OPE's). In some embodiments, the OPE's deflect or distribute light to the out-coupling optical elements **800, 810, 820** and, in some embodiments, may also increase the beam or spot size of this light as it propagates to the out-coupling optical elements. In some embodiments, the light distributing elements **730, 740, 750** may be omitted and the in-coupling optical elements **700, 710, 720** may be configured to deflect light directly to the out-coupling optical elements **800, 810, 820**. For example, with reference to FIG. 9A, the light distributing elements **730, 740, 750** may be replaced with out-coupling optical elements **800, 810, 820**, respectively. In some embodiments, the out-coupling optical elements **800, 810, 820** are exit pupils (EP's) or exit pupil expanders (EPE's) that direct light in a viewer's eye **210** (FIG. 7). It will be appreciated that the OPE's may be configured to increase the dimensions of the eye box in at least one axis and the EPE's may be to increase the eye box in an axis crossing, e.g., orthogonal to, the axis of the OPEs. For example, each OPE may be configured to redirect a portion of the light striking the OPE to an EPE of the same waveguide, while allowing the remaining portion of the light to continue to propagate down the waveguide. Upon impinging on the OPE again, another portion of the remaining light is redirected to the EPE, and the remaining portion of that portion continues to propagate further down the waveguide, and so on. Similarly, upon striking the EPE, a portion of the impinging light is directed out of the waveguide towards the user, and a remaining portion of that light continues to

propagate through the waveguide until it strikes the EP again, at which time another portion of the impinging light is directed out of the waveguide, and so on. Consequently, a single beam of incoupled light may be “replicated” each time a portion of that light is redirected by an OPE or EPE, thereby forming a field of cloned beams of light, as shown in FIG. 6. In some embodiments, the OPE and/or EPE may be configured to modify a size of the beams of light.

[0092] Accordingly, with reference to FIGS. 9A and 9B, in some embodiments, the set **660** of waveguides includes waveguides **670, 680, 690**; in-coupling optical elements **700, 710, 720**; light distributing elements (e.g., OPE's) **730, 740, 750**; and out-coupling optical elements (e.g., EP's) **800, 810, 820** for each component color. The waveguides **670, 680, 690** may be stacked with an air gap/cladding layer between each one. The in-coupling optical elements **700, 710, 720** redirect or deflect incident light (with different in-coupling optical elements receiving light of different wavelengths) into its waveguide. The light then propagates at an angle which will result in TIR within the respective waveguide **670, 680, 690**. In the example shown, light ray **770** (e.g., blue light) is deflected by the first in-coupling optical element **700**, and then continues to bounce down the waveguide, interacting with the light distributing element (e.g., OPE's) **730** and then the out-coupling optical element (e.g., EPs) **800**, in a manner described earlier. The light rays **780** and **790** (e.g., green and red light, respectively) will pass through the waveguide **670**, with light ray **780** impinging on and being deflected by in-coupling optical element **710**. The light ray **780** then bounces down the waveguide **680** via TIR, proceeding on to its light distributing element (e.g., OPEs) **740** and then the out-coupling optical element (e.g., EP's) **810**. Finally, light ray **790** (e.g., red light) passes through the waveguide **690** to impinge on the light in-coupling optical elements **720** of the waveguide **690**. The light in-coupling optical elements **720** deflect the light ray **790** such that the light ray propagates to light distributing element (e.g., OPEs) **750** by TIR, and then to the out-coupling optical element (e.g., EPs) **820** by TIR. The out-coupling optical element **820** then finally out-couples the light ray **790** to the viewer, who also receives the out-coupled light from the other waveguides **670, 680**.

[0093] FIG. 9C illustrates a top-down plan view of an example of the plurality of stacked waveguides of FIGS. 9A and 9B. As illustrated, the waveguides **670, 680, 690**, along with each waveguide's associated light distributing element **730, 740, 750** and associated out-coupling optical element **800, 810, 820**, may be vertically aligned. However, as discussed herein, the in-coupling optical elements **700, 710, 720** are not vertically aligned; rather, the in-coupling optical elements are preferably non-overlapping (e.g., laterally spaced apart as seen in the top-down view). As discussed further herein, this nonoverlapping spatial arrangement facilitates the injection of light from different resources into different waveguides on a one-to-one basis, thereby allowing a specific light source to be uniquely coupled to a specific waveguide. In some embodiments, arrangements including nonoverlapping spatially-separated in-coupling optical elements may be referred to as a shifted pupil system, and the in-coupling optical elements within these arrangements may correspond to sub pupils.

Eye Imaging and Environment Imaging

[0094] As discussed above, head mounted displays can be used to provide image content to a user integrated with, in conjunction with, and/or superimposed over the view of the world in front of the wearer. Such head mounted display systems can be configured to project light into an eye of a user to form augmented reality image content as well as to transmit light from an environment in front of the user to the user. A head mounted display system may include one or more cameras for imaging the environment and/or the user's eye. Outward facing cameras may be used for directly imaging the environment, for example, to determine where to place augmented reality image content with respect to objects in the environment. For example, imaging the environment may provide the location of a table such that the head mounted display may render an image of person standing next to the table instead of on the table or in the table. Inward-facing cameras may be used for directly imaging the eye such as for eye tracking. Disclosed herein are examples of head-

mounted display systems and/or imaging systems that can be configured also to image the eye and/or the environment. In some designs, the systems do not require inward and/or outward facing cameras to directly image the eye and/or environment, respectively. Such systems may employ one or more cameras that are configured to receive light from the eye/environment via the eyepiece such as one or more waveguides in the eyepiece that are in optical communication with the one or more cameras. With the light collected by the waveguide(s), the one or more cameras can generate images of the eye and/or the environment in front of the user. Using the waveguide to collect the light for imaging the eye and/or environment may potentially reduce the form factor of the head mounted display, making the head mounted display possibly more compact and/or aesthetically desirable.

[0095] FIG. 10 illustrates an example imaging system 900 configured to image the eye that is integrated with an eyepiece 950 that can be used on in head mounted display. The eyepiece 950, which can be disposed in front of the user's eye 210 can be used to both inject image content into the eye as well as image the eye. FIG. 10 shows one eyepiece 950 in front of one eye 210. Various head mounted display systems such as shown in FIG. 2, may include a pair of eyepieces 950 and associated components disposed in front of respective left and right eyes 210. A single waveguide 940 is shown in FIG. 10, but the waveguide 940 may include one, two, three, four, six, seven, eight, or more waveguides (e.g., one or more stacks of waveguides).

[0096] The imaging system 900 can include a light source or illumination source 960 illuminating the eye to facilitate image capture, the eyepiece 950 comprising a waveguide 940 configured to propagate light therein, and/or an imaging device 920 such as a camera for image capture. An image projector 930 for producing an image that can be injected into the eye via the eyepiece 950 is also shown. The eyepiece 950 may include one or more waveguides 940 configured to transport light from the illumination source 960 and/or image projector 930 to the eye and to transport light from the eye to the camera 920. The eyepiece 950 may further comprise one or more coupling optical elements 944 for coupling light out of the waveguide 940 and to the eye for illuminating the eye and for image injection and/or from the eye and into the waveguide for image capture. The eyepiece 950 may additionally comprise one or more incoupling optical elements 942 for coupling light from the illumination source 960 and/or image projector 930 into the waveguides 940 as well as one or more outcoupling optical elements 952 for coupling light from the waveguide out to the camera 920.

[0097] The eyepiece 950 may be disposed on a frame wearable on the head. The eyepiece 950 may be disposed in front of the eye 210. The eyepiece 950 may have a medial or nasal side closer to the nose of the wearer and an opposite lateral or temporal side closer to the temples and farther from the nose of the wearer. In FIG. 10, the coupling optical element 944 is medial or nasal with respect to the incoupling 942 and outcoupling 952 optical elements (which are lateral or temporal to the coupling optical elements 944). The illumination source 960 is also more medial or nasal with respect to the image projector 930 (or the image projector is more lateral or temporal than the illumination source.) The relative positions can be different, however. For example, the illumination source 960 may be more lateral or temporal than the image projector 930 in some designs.

[0098] The waveguide 940 may comprise a sheet or layer having two major surfaces (a forward and a rearward surface), having the largest surface areas, disposed opposite one another. The forward surface may be farther from the user's eye 210 (closer to the environment in front of the wearer) and the rearward closer to the user's eye (and farther from the environment in front of the wearer) when the user wears the head mounted display. The waveguide 940 may comprise a transparent material with an index of refraction greater than 1.0 (e.g., glass, plastic) such that light may be guided therein by total internal reflection between the major surfaces. Elements with the same numbers may have the same functionality for one or more of the embodiments described herein.

[0099] A coupling optical element **944** for coupling light to the eye **210** from waveguide **940** and/or from the waveguide to the eye may be disposed on or in the waveguide **940**. As shown in FIG. **10**, the coupling optical element **944** may be disposed in an optical path between the user's eye **210** and the waveguide **940** such that light coupled from the waveguide **940** via the coupling optical element **944** may be incident on the user's eye **210** (for example to illuminate the eye and/or for image injection). The coupling optical element **944** may comprise a plurality of turning features configured to turn light guided within the waveguide out of the waveguide or turn light incident on the coupling optical element **944** at an angle into the waveguide to be guided therein by total internal reflection. The coupling optical element **944** and turning features may be in physical engagement with the waveguide **940**. For example, the coupling optical element **944** may comprise a holographic or diffractive optical element (e.g., surface relief grating) patterned (e.g., etched) in or on the waveguide **940**. The coupling optical element **944** may comprise a layer disposed on the waveguide **940** or may be formed in the waveguide **940**. For example, a volume holographic or other diffractive optical element may be formed by changing the index of refraction of material comprising the waveguide or a layer disposed thereon. Accordingly, the coupling optical element **944** may be disposed in the volume of the waveguide **940** or as a layer disposed thereon.

[0100] Depending on the design, the coupling optical element **944** may be transmissive or reflective and may operate in transmission or reflection. For example, the coupling optical element **944** may include a transmissive or reflective diffractive optical element (e.g., grating) or holographical optical element that operates in transmission or reflection respectively, e.g., turning light via that is transmitted therethrough or that is reflected therefrom. The coupling optical element **944** can include a polarization optical element, such as a polarization selective turning element (e.g., polarizer). The polarization selective turning element may include one or more polarization gratings, diffractive optical elements, and/or holographic optical elements and may comprise liquid crystal structures such as liquid crystal polarization gratings. The coupling optical element **944** may be configured to direct light from the image projector **930** and/or light source **960** guided within the waveguide **940** by total internal reflection (TIR) to the user's eye **210** at an angle less than (e.g., more normal) than the critical angle so as to be ejected out of the waveguide to the eye. Additionally or in the alternative, the coupling optical element **944** may be configured to couple light from the eye **210** into the waveguide **940** at an angle greater (e.g., less normal) than the critical angle so as to be guided therein by total internal reflection to the camera **920**.

[0101] As shown in FIG. **10**, an incoupling optical element **942** for coupling light from the illumination source **960** and/or the image projector **930** into the waveguide **940** may be disposed on or in the waveguide **940**. The incoupling optical element **942** may be disposed in an optical path between the light source **960** and the waveguide **940** such that light coupled from the light source **960** via the incoupling optical element **942** is guided within the waveguide **940**. The incoupling optical element **942** may comprise, for example, a plurality of turning features configured to turn light incident thereon at an angle into the waveguide to be guided therein by total internal reflection. The incoupling optical element **942** may comprise liquid crystal structures such as liquid crystal polarization gratings. Additionally or alternatively, the incoupling optical element **942** may include a blazed grating. The incoupling optical element **942** may comprise a layer disposed on the waveguide **940** or may be formed on or in the waveguide **940** (e.g., patterned) or may be otherwise manufactured therein. For example, a surface holographic or diffractive optical element (e.g., surface relief grating) may be fabricated by patterning (e.g., etching) a surface of the waveguide or a layer thereon. A volume holographic or diffractive optical element may also be formed by changing the index of refraction of material comprising the waveguide or a layer disposed thereon. Accordingly, the incoupling optical element **942** may be disposed in the volume of the waveguide **940** or a layer disposed thereon. Depending on the design, the incoupling optical element **942** may be transmissive or reflective and may operate in transmission or reflection. For example, the incoupling optical element **942** may include a transmissive or reflective diffractive optical element

(e.g., grating) or holographical optical element that operates in transmission or reflection, respectively, e.g., turning light that is transmitted therethrough or that is reflected therefrom.

[0102] The incoupling optical element **942** may comprise a reflective optical element (e.g., mirror). For example, the incoupling optical element **942** may comprise an off-axis reflector. Additionally or alternatively, the incoupling optical element **942** and/or coupling optical element **944** can include a polarization optical element, such as a polarization selective turning element (e.g., polarizer). The polarization selective turning element may include one or more polarization gratings, diffractive optical elements, and/or holographic optical elements and may comprise liquid crystal structures such as liquid crystal polarization gratings. For example, one or both of the incoupling optical element **942** and/or the coupling optical element **944** can include liquid crystal polarization gratings (LCPGs). LCPGs can provide high efficiency diffraction potentially at broad wavelengths. Accordingly, LCPGs may be useful for incoupling optical elements **942** and/or the coupling optical element **944**. The LCPG may be polarization dependent. The LCPG or other type of liquid crystal grating, diffractive optical element, or optical element may include a pattern or arrangement of molecules of liquid crystal configured to provide one or more functions such as turn light into a waveguide or out of a waveguide. Accordingly, incoupling optical element **942** and/or the coupling optical element **944** may comprise polarization gratings. Additionally or alternatively, incoupling optical element **942** and/or the coupling optical element **944** can comprises liquid crystal and thus in some implementations one or both may be liquid crystal gratings or liquid crystal diffractive optical elements. Additionally or alternatively, one or both of the incoupling optical element **942** and/or the coupling optical element **944** can include a blazed grating. In some designs, the incoupling optical element **942** comprises a liquid crystal reflector, such as a cholesteric liquid crystal reflective lens (e.g., reflective liquid crystal diffraction lens, Bragg-reflective structure, reflective liquid crystal diffraction grating, etc.). Some nonlimiting examples of liquid crystal gratings, liquid crystal polarization gratings and other liquid crystal optical elements are discussed in the following published applications, each of which is hereby incorporated by reference herein in its entirety and for all purposes: U.S. Publication No. 2018/0143438, titled “MULTILAYER LIQUID CRYSTAL DIFFRACTIVE GRATINGS FOR REDIRECTING LIGHT OF WIDE INCIDENT ANGLE RANGES,” filed on Nov. 16, 2017; U.S. Publication No. 2018/0143485, titled “SPATIALLY VARIABLE LIQUID CRYSTAL DIFFRACTION GRATINGS,” filed on Nov. 16, 2017; U.S. Publication No. 2018/0143509, titled “WAVEGUIDE LIGHT MULTIPLEXER USING CROSSED GRATINGS,” filed on Nov. 16, 2017; U.S. Publication No. 2018/0239147, titled “DISPLAY SYSTEM WITH VARIABLE POWER REFLECTOR,” filed on Feb. 22, 2018; U.S. Publication No. 2018/0239177, titled “VARIABLE-FOCUS VIRTUAL IMAGE DEVICES BASED ON POLARIZATION CONVERSION,” filed on Feb. 22, 2018; and U.S. Publication No. 2018/0164627, titled “DIFFRACTIVE DEVICES BASED ON CHOLESTERIC LIQUID CRYSTAL,” filed on Dec. 7, 2017. The designs of the incoupling optical element **942** and/or the coupling optical element **944**, however, are not limited to these and may include other types of optical elements, diffractive optical element, liquid crystal optical element, liquid crystal gratings and liquid crystal polarization gratings. Further information on examples of cholesteric liquid crystal structures such as reflectors may also be found below in the section titled “Cholesteric Liquid Crystal Mirror.” As discussed above, other liquid crystal optical elements as well as other non-liquid crystal optical elements may be used. Accordingly, many types of coupling optical elements (e.g. incoupling optical element **942** and/or the coupling optical element **944**), diffractive optical element, gratings, polarization gratings, etc., may be used, both those described herein as well as other types of gratings, diffractive optical elements, liquid crystal elements, and optical elements generally. In various implementations, the incoupling optical element **942** may be configured to couple light from the image projector **930** and/or the light source **960** into the waveguide at an angle greater than the critical angle so as to be guided within the waveguide **940** by total internal reflection to the eye to the user's eye **210**.

[0103] The waveguide **940** may comprise one or more waveguides. In some implementations, the one or more waveguides **940** comprises a stack of waveguides. In some designs, for example, different waveguides of the stack of waveguides are configured to output light with different wavefront divergence as if projected from different distances from the user's eye. For example, a first waveguide or group of waveguides may be configured to output light that is collimated or has a first divergence as if projected from a first depth, and a second waveguide or group of waveguides may be configured to output light that is diverging (not collimated) or is at a second divergence (greater than the first divergence) as if projected from a second depth closer than the first depth. In some designs, the different waveguides may be configured to output light having different associated colors. For example, a first waveguide may be configured to output red light, a second waveguide may be configured to output green light, and a third waveguide may be configured to output blue light. A fourth waveguide may be configured to output and/or input infrared light.

[0104] The outcoupling optical element **952** for coupling light from the waveguide **940** to the camera **920** such as shown in FIG. **10** may comprise, for example, a plurality of turning features configured to turn light incident thereon at an angle such that light is not guided within the waveguide and is turned out of the waveguide to the camera. The outcoupling optical element **952** may be disposed within an interior of the waveguide **940** or may be patterned (e.g., etched) in or on a surface (e.g., major surface) of the waveguide **940**. For example, a surface holographic or diffractive optical element (e.g., surface relief grating) may be fabricated by patterning (e.g., etching) a surface of the waveguide or a layer thereon. A volume holographic or diffractive optical element may also be formed by changing the index of refraction of material comprising the waveguide or a layer disposed thereon. Depending on the design, the outcoupling optical element **952** may be transmissive or reflective and may operate in transmission or reflection. For example, the outcoupling optical element **952** may include a transmissive or reflective diffractive optical element (e.g., grating) or holographical optical element that operates in transmission or reflection, respectively, e.g., turning light that is transmitted therethrough or that is reflected therefrom.

[0105] The outcoupling optical element **942** may comprise a reflective optical element (e.g., mirror). For example, the outcoupling optical element **952** may comprise an off-axis reflector. In some designs, the outcoupling optical element **952** can include a polarization optical element, such as a polarization selective turning element (e.g., polarizer). Accordingly, the polarization selective turning element may include one or more polarization gratings, diffractive optical elements, and/or holographic optical elements and may comprise liquid crystal structures such as liquid crystal polarization gratings. In some implementations, for example, the outcoupling optical element **952** can include liquid crystal polarization gratings (LCPGs). LCPGs can provide high efficiency diffraction potentially at broad wavelengths. Likewise, LCPGs may be useful for outcoupling optical element **952**. The LCPG may be polarization dependent. The LCPG or other types of liquid crystal gratings may include a pattern or arrangement of molecules of liquid crystal configured to provide one or more functions such as turn light into a waveguide or out of a waveguide. Accordingly, outcoupling optical element **952** may comprise polarization gratings. Additionally or alternatively, outcoupling optical element **952** can comprises liquid crystal and thus in some implementations may be liquid crystal gratings or other liquid crystal optical element such as liquid crystal diffractive optical elements. Additionally or alternatively, the outcoupling optical element **952** can include a blazed grating. In some designs, the outcoupling optical element **952** comprises a liquid crystal reflector, such as a cholesteric liquid crystal reflective lens (e.g., reflective liquid crystal diffraction lens, Bragg-reflective structure, reflective liquid crystal diffraction grating, etc.). Some nonlimiting examples of liquid crystal gratings, liquid crystal polarization gratings and other liquid crystal optical elements are discussed in the following published applications, each of which is hereby incorporated by reference herein in its entirety and for all purposes: U.S. Publication No. 2018/0143438, titled "MULTILAYER LIQUID CRYSTAL DIFFRACTIVE GRATINGS FOR

REDIRECTING LIGHT OF WIDE INCIDENT ANGLE RANGES,” filed on Nov. 16, 2017; U.S. Publication No. 2018/0143485, titled “SPATIALLY VARIABLE LIQUID CRYSTAL DIFFRACTION GRATINGS,” filed on Nov. 16, 2017; U.S. Publication No. 2018/0143509, titled “WAVEGUIDE LIGHT MULTIPLEXER USING CROSSED GRATINGS,” filed on Nov. 16, 2017; U.S. Publication No. 2018/0239147, titled “DISPLAY SYSTEM WITH VARIABLE POWER REFLECTOR,” filed on Feb. 22, 2018; U.S. Publication No. 2018/0239177, titled “VARIABLE-FOCUS VIRTUAL IMAGE DEVICES BASED ON POLARIZATION CONVERSION,” filed on Feb. 22, 2018; and U.S. Publication No. 2018/0164627, titled “DIFFRACTIVE DEVICES BASED ON CHOLESTERIC LIQUID CRYSTAL,” filed on Dec. 7, 2017. The designs of the outcoupling optical element **952**, however, are not limited to these and may include other types of optical elements, diffractive optical element, liquid crystal optical element, liquid crystal gratings and liquid crystal polarization gratings. Further information on examples of cholesteric liquid crystal structures such as reflectors may also be found below in the section titled “Cholesteric Liquid Crystal Mirror.” As discussed above, other liquid crystal optical elements as well as other non-liquid crystal optical elements may be used. Accordingly, many types of coupling optical elements (e.g. outcoupling optical element **952**), diffractive optical element, gratings, polarization gratings, etc., may be used, both those described herein as well as other types of gratings, diffractive optical elements, liquid crystal elements, or optical elements generally. As referred to above, the outcoupling optical element **952** may be configured to redirected light guided within the waveguide **940** at an angle less than the critical angle so as not to be guided within the waveguide by total internal reflection but to be ejected out to the camera **920**.

[0106] In various designs, the coupling optical element **944** may be transparent in the visible spectrum such that the user can see through the coupling optical element **944** and the eyepiece **950** to the environment in front of the user. The incoupling optical element **942** may also turn light in the visible spectrum, for example, if the incoupling optical element is used to receive light from the image projector **930** and/or if the illumination source **960** is configured to output visible light to illuminate the eye **210** with visible light. In some embodiments, the incoupling optical element **942** is configured to turn infrared light, for example, if the illumination source **960** is configured to output infrared light to illuminate the eye **210** with infrared light. In some designs such as shown in FIG. **10**, the incoupling optical element **942** may be more medial or nasal than the outcoupling optical element **952**. However, in other designs the incoupling optical element **942** may be more lateral or temporal than the outcoupling optical element **952**. In certain implementations such as shown in FIG. **10**, the outcoupling optical element **952** may be adjacent the incoupling optical element **942** although non-adjacent positioning is possible.

[0107] The illumination source **960** may be disposed on the same side of the eyepiece **950** as the eye **210** (e.g., rearward or proximal side), as shown in FIG. **10**. (Proximal may refer to the side closest to the eye **210**.) Alternatively, the illumination source **960** may be disposed on the side opposite the eye **210** (e.g., forward or distal side). The illumination source **960** may be configured to direct light into at least one of the major surfaces of the waveguide **940** via the incoupling optical element **942**. The light source **960** may be configured to emit invisible light (e.g., infrared). The light source **960** may include one or more LEDs. The LEDs may comprise infrared LEDs. The light source **960** may be configured to emit coherent light. In some designs, the light source **960** comprises a laser (e.g., infrared laser). In some designs, the light source **960** emits pulsed light. For example, the camera **920** can be configured to capture an image periodically. Accordingly, the illumination source **960** can be pulsed to coincide with the period during which the camera obtains images. The intensity output from the illumination source **960** can be reduced when the camera is not obtaining an image. By concentrating the total energy of the illumination on a short time increased signal to noise can be obtained while not exposing the eye **210** to unsafe intensity levels. In some cases, for example, the camera **920** captures one image every 30 milliseconds and the exposure time of the camera is few milliseconds. The illumination source **960** can be configured to

output pulses having similar period and duration to match that of the camera **920**.

[0108] In some implementations, different light sources having different wavelengths are alternately pulsed to provide different wavelength illumination at different times as discussed below.

[0109] The incoupling optical element **942** may be in direct optical communication with the illumination source **960** and/or image projector **930**, for example, so as to guide light from said image projector **930** and/or light source **960** therein. For example, light emitted by the light source **960** may be incident on the incoupling optical element **942** before optically interacting with either the coupling optical element **944** and/or outcoupling optical element **952**.

[0110] As shown in FIGS. **11A-11E**, light **902** projected from the image projector **930** may form an image on the retina. The image projector **930** may include a light source, a modulator, and/or projection optics. The light source for the image projector **930** may comprise one or more LEDs, lasers or other light sources and may comprises one or more visible light sources. The modulator may comprise a spatial light modulator such as a liquid crystal spatial light modulator. Such a spatial light modulator may be configured, for example, to modulate the intensity of light at different spatial locations. The projection optics may comprise one or more lenses. Other types of image projectors **930** capable of projecting and/or forming images may be employed. For example, the image projector **930** may comprise a scanning optical fiber.

[0111] The image projector **930** and the incoupling optical element **942** may be in direct optical communication with each other. The image projector **930** may, for example, be aligned with the incoupling optical element **942** into which light from the image projector **930** is directed. In some cases, image projector **930** is disposed adjacent the corresponding incoupling optical element **942** and/or the waveguide **940**. The image projector **930** may also be disposed in an optical path that includes the incoupling optical element **942**, the coupling optical element **944**, and the eye **210**.

[0112] The image projector **930** may be a separate element than the illumination source **960**, as shown in FIG. **10** as well as in FIGS. **11A-11E**. However, in some cases the image projector **930** may be used as the illumination source. For example, in addition to injecting images into the eye **210**, the image projector **930** may be used to direct visible and/or infrared light into the eye to illuminate the eye for image capture. Alternatively, however, one or more separate light sources **960** may be used to illuminate the eye **210** for image capture.

[0113] The light emitted by the illumination source **960** may comprise a particular wavelength range of light such as, for example, invisible light. The illumination source **960** may be configured to project invisible (e.g., infrared) light onto/into the eye **210** for imaging one or more parts (e.g., cornea, retina) of the eye **210**. In certain example implementations, the light source **960** may be configured to emit light in the range of between about 850 nm and 940 nm. The light source **960** may be configured to emit light extending over a wavelength range of at least about 20 nm. Other ranges are also possible. The wavelength range emitted may be 5 nm, 10 nm, 15 nm, 50 nm, 75 nm, 100 nm, 150 nm, 200 nm, or any range between any of these values. The light source **960** may be configured to emit light across a broad band of wavelengths, such as any range within the infrared spectrum.

[0114] The imaging device **920**, which may comprise a camera, may comprise a detector array and possibly imaging optics. The detector array may comprise, for example, a CCD or CMOS detector array and the imaging optics may comprise one or more lenses. The one or more lenses may have positive optical power and an associated focal length. In certain designs, the camera **920** is focused at infinity. For example, the optics may have a focal length, f , and detector array may be disposed a distance away from the optics corresponding to the focal length such that objects at a large distance are imaged onto the detector array. Similarly, light from the eye or objects in the environment that is collimated will be focus on the detector array to form an image of the eye or object thereon.

[0115] The imaging device **920** may be disposed on the opposite side of the waveguide **940** as the illumination source **960** and/or the eye **210**. In some designs, the imaging device **920** may be

disposed on the same side of the waveguide **940** as the light source **960** and/or eye **210**. As shown in FIG. **10**, the imaging device **920** may be disposed near a lateral or temporal edge of the eyepiece **950** although other locations are possible.

[0116] FIGS. **11A-11E** illustrate the operation of the example imaging system **900** of FIG. **10**. FIG. **11A** shows the illumination source **960** emitting light **902** toward the incoupling optical element **942** on the waveguide **940**. As shown, the light **902** can be directed generally at normal incidence to the eyepiece **950** although other angles are possible. In some designs, the light source **960** is configured to emit collimated light into the eyepiece **950**. As shown in FIG. **11B**, the illumination light **902** can be coupled into the waveguide **940** via the incoupling optical element **942**. In some designs where the incoupling optical element **942** comprises a diffractive optical element (e.g., grating, holographic element) the light incident thereon is diffracted at an angle greater than the critical angle of the waveguide to cause the incoupled light **904** to be guided within the eyepiece **950** by total internal reflection (TIR). In some designs, the incoupling optical element **942** may be configured to direct light toward the coupling optical element **944**. The incoupling optical element **942** may be polarization selective. For example, the incoupling optical element **942** can include a polarization selective turning element such a polarization grating like a liquid crystal polarization grating. FIG. **11C** shows how the incoupled light **904** propagating through the waveguide **940** by TIR.

[0117] FIG. **11D** illustrates an example imaging system **900** coupling light out of the eyepiece **950**. As the incoupled light **904** propagates through the waveguide **940**, some of the light may be incident on the coupling optical element **944**. The coupling optical element **944** can be configured to couple the incoupled light **904** out of the eyepiece **950** and toward the user's eye **210**. The coupling optical element **944** may be configured to couple the light as collimated light toward the eye **210**. The coupling optical element **944** may be tuned to light of a particular wavelength range. For example, the coupling optical element **944** may be configured to couple infrared light (e.g., between about 700 nm and 15000 nm) out of the waveguide **940**. In some designs, the coupling optical element **944** can be configured to couple multiple wavelengths of light out of the eyepiece **950**. For example, the coupling optical element **944** may be tuned for both infrared and visible light. The coupling optical element **944** can also be configured to couple light into the waveguide **940**, as described more fully below.

[0118] The coupling optical element **944** can be configured to increase one or more dimensions of an eyebox for a user. For example, the one or more dimensions may be measured along a first axis (e.g., x axis). The eyepiece **950** may further include an orthogonal pupil expander (OPE). The OPE may have at least one light redirecting element disposed on or in the waveguide (e.g., on one of the major surfaces) or the OPE may be disposed within the waveguide **940**. The OPE may include features similar or identical to those described above for light distributing elements **730**, **740**, **750** above. In some implementations, the light redirecting element may comprise a diffractive optical element. The OPE may be configured to increase a dimension of the eyebox along a second axis (e.g., y axis) orthogonal to the first axis.

[0119] FIG. **11D** shows some of the light exiting the eyepiece **950** toward the user's eye **210**. In some designs, the coupling optical element **944** is configured such that incoupled light **904** that is incident on the coupling optical element **944** at various portions of the coupling optical element **944** along the first axis (e.g., parallel to the x-axis) exits the eyepiece **950** at each portion of the coupling optical element **944** along the first axis. This may provide a user with a light for projecting images or illuminating the eye for different eye positions or locations.

[0120] As shown in FIGS. **11D-11E**, the coupling optical element **944** may be configured to couple the incoupled light **904** out of the eyepiece **950** as collimated light. This light may also be directed in general near normal relative to a major surface of the eyepiece **950** and/or waveguide **940**. The collimated light may be directed into the eye and focus by the eye (e.g., the cornea and natural lens of the eye) onto the retina. This light **908** incident on the retina may be provide illumination for

imaging the retina and/or providing image content to the eye. Some of this light **908**, for example, may be reflected or scatter off the retina, exiting the eye and providing for images of the retina to be captured. The light source **960** may be an extended light source such that the light will illuminate a region of the retina.

[0121] FIGS. **12A-12E** illustrate how the imaging system **900** of FIGS. **11A-11E** may additionally or alternatively be used for image collection of the eye **210**. FIG. **12A** shows light **910** reflected from the retina exiting the eye **210**. As shown, the light **910** scattered or reflected from the retina that passes through the natural lens of the eye, the pupil in the eye and the cornea from may be collimated. This light may also be incident on the eyepiece **950** at normal incidence (e.g., at a right angle to a major surface of the waveguide **940** and/or coupling optical element **944**). The coupling optical element **944** may be configured to couple the light **910** reflected from the retina into the waveguide **940**.

[0122] FIG. **12B** illustrates an example imaging system **900** as it couples light into the eyepiece **950**. The coupling optical element **944** may include a turning feature such as a diffractive optical element, or other structures that redirect the light at an angle greater than the critical angle so as to be guided within the waveguide **940**. The coupling optical element **944** may be configured to direct the incoupled light **914** generally toward the light source **960** and/or the imaging device **920**. The coupling optical element **944** can be configured to couple less than a fraction of this light propagating toward the camera **920** back out of the waveguide **940**. For example, a partially reflective element (e.g., semi-transparent mirror) may be disposed on or in the waveguide **940** such that a portion of the incoupled light **914** continues to propagate within the waveguide **940** by total internal reflection while reducing leakage of the incoupled light **914** out of the waveguide **940** along portions of the waveguide **940** where the coupling optical element **944** is disposed. The portion of light that does not leak out may be any fraction between 0 and 1. For example, the portion may be 0.90, where 90% of the light rays propagating through the waveguide **940** along the coupling optical element **944** are maintained within the waveguide **940** at each reflection of the light rays. Other portions are possible (e.g., 0.10, 0.20, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, or any range between any of these values). Such partially reflective element(s) can similarly be used in implementations described below.

[0123] As shown in FIG. **12C**, collimated incoupled light **914** may continue to propagate through the waveguide **940** toward the imaging device **920**. FIG. **12D** shows how some of the incoupled light **914** can continue to propagate until it is incident on one or more outcoupling optical elements **952**. In order to reduce the amount of leakage of incoupled light **914** out of the incoupling optical element **942**, the incoupling optical element **942** can be configured to couple little of this light propagating toward the camera **920** back out of the waveguide. For example, a partially reflective element (e.g., semi-transparent mirror) may be disposed on or in the waveguide **940** such that a portion of the incoupled light **914** continues to propagate within the waveguide **940** by total internal reflection while reducing leakage of the incoupled light **914** out of the waveguide **940** along portions of the waveguide **940** where the incoupling optical element **942** is disposed. The portion of light that does not leak out may be any fraction between 0 and 1. For example, the portion may be 0.90, where 90% of the light rays propagating through the waveguide **940** along the coupling optical element **944** are maintained within the waveguide **940** at each reflection of the light rays. Other portion may be possible (e.g., 0.10, 0.20, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, or any range between any of these values). Such partially reflective element(s) can similarly be used in implementations described below.

[0124] As shown in FIG. **12E**, the outcoupling optical element **952** can be configured to couple light guided within the waveguide **940** out of the waveguide **940** and to the imaging device **920**. As a result, light propagating in the waveguide **940** that is incident on the outcoupling element **952** may be redirected so as to be ejected out of the waveguide **940**, for example, out of a major surface of the waveguide **940** (e.g., the forward or rearward side of the waveguide **940**) and directed on the

imaging device **920**. The outcoupling optical element **952** may be configured to direct the light **926** to exit the waveguide **940** perpendicular (e.g., normal) to the major surface of waveguide **940**. In some designs, the outcoupling optical element **952** is configured to direct collimated light **924** onto the imaging device **920** at normal incidence to a light sensitive portion of the imaging device **920**. As discussed above, the camera **920** may be infinity focused, for example, the imaging optics may be configured to focus collimated light onto the detector array.

[0125] Accordingly, the waveguide **940** may be configured to guide light coupled from the user's eye **210** into the waveguide **940** to be received by the imaging device **920** (e.g., camera) so as to capture an image of at least a portion of the eye **210** of the user. The same waveguide **940** may be configured to guide light coupled from the image projector **930** such that light from the image projector **930** can be directed to the user's eye **210** such that the image from the image projector **930** is in the vision field of the user. In some implementations, the same waveguide is configured to guide light coupled from the illumination source **960** such that light from the illumination source can be directed to the user's eye **210** to illuminate the eye such that an image of the eye can be captured by the camera **920**.

[0126] In some implementations, the same coupling optical element **944** can be configured to (i) couple light from the user's eye **210** into the waveguide **940** to be received by the imaging device **920** and (ii) couple light from the image projector **930** out from the waveguide **940** to the user's eye **210** to project image content into the user's vision field. In some implementations, the same coupling optical element **944** can be configured to couple light from the illumination source **960** out of the waveguide to the user's eye **210** such that light from the illumination source can illuminate the eye.

[0127] In other designs, different waveguides can be used and/or different coupling optical elements **944** can be used. In some designs for example, a first waveguide **940** may be configured to guide light coupled from the user's eye **210** to be received by the camera **920** so as to capture an image of at least a portion of the eye **210** of the user and a second waveguide may be configured to guide light coupled from the image projector **930** such that light from the image projector **930** can be directed to the user's eye **210**. The first and second waveguides may be stacked on top of one another. Another waveguide may in addition or in the alternative be configured to guide light coupled from the illumination source **960** such that light from the illumination source can be directed to the user's eye **210** to illuminate the eye.

[0128] Also, in some implementations, a first coupling optical element **944** can be configured to (i) couple light from the user's eye **210** into the waveguide **940** to be received by the imaging device **920** and (ii) couple light from the image projector **930** out from the waveguide **940** to the user's eye **210** to project image content into the user's vision field. Another coupling optical element may in addition or in the alternative be configured to couple light from the illumination source **960** out of the waveguide to the user's eye **210** such that light from the illumination source can illuminate the eye.

[0129] In some designs, the coupling optical element **944** can include a plurality of diffractive optical elements (DOEs). For example, a first DOE can be configured to couple light from the user's eye **210** into the waveguide **940** to be received by the imaging device **920**. A second DOE can be configured to couple light from the image projector **930** out of the waveguide **940** to the user's eye **210** to project image content into the user's vision field. Optionally, a third DOE can be configured to couple light from the light source **960** out of the waveguide **940** to the user's eye **210** to illuminate the eye. The first and second (and possibly third) DOEs can be stacked, e.g., in some implementations such that light from the environment in front of the user passes through the first DOE and is then incident on the second DOE and then incident on the third DOE and incident on the user's eye. The order, however, may be different.

[0130] In some designs, the first and second DOEs are integrated in a single element or volume of the waveguide **940**. In some implementations, for example, both the first and second DOEs are

superimposed on each other (e.g., occupy the same or approximately the same volume) within the waveguide **2102**. For example, the first and second DOE may be recorded in the same medium. [0131] As described above, image capture of the eye, e.g., of the retina, can facilitate eye tracking. FIG. **13A**, for example, illustrates the imaging system **900** configured to image various portions of the eye **210** (e.g., retina), for example, at different times when the eye is in different positions. Stages A and B may refer to images of the eye **210** during different orientations of the eye. FIG. **13A** shows imaging of the eye **210** and the results thereof during both stage A and stage B imaging. [0132] In some implementations, the light emission **928** (e.g., from an illumination source **960** such as described above or from one or more illuminations sources configured and/or located differently) can be used to obtain one or more images of the retina **962**, as shown by FIG. **13A**. The image of the retina **962** may comprise one or more regions **964**, **966** that are imaged during different orientations of the eye **210**. FIG. **13A** shows two regions **964**, **966** of the image of the retina **962**. For example, the region **964** of retina imaged in stage A may be imaged while the eye **210** is directed at an angle normal to the waveguide **940**. The image data for the region **966** of retina imaged in stage B may be obtained while the eye **210** is oriented at an acute angle with the waveguide **940**. Using one or more orientations of the eye **210** during one or more stages of imaging, a composite image or map of the retina **962** may be obtained. Processing electronics or a processor, such as data module **140** (see FIG. **2**), may be used to find overlapping image data between two neighboring regions. Using the overlapping regional image data, a composite image or of the retina **962** can be determined. A larger size (e.g., full-size) composite image or map of the user's retina can be stored.

[0133] As described herein, the head mounted display can be used to map a user's eye retina based on the direction that user's eye is directed. To provide a realistic and intuitive interaction with objects in the user's environment using eye gaze and/or to identify a wearer of the head mounted display device, the head mounted display system can use retinal mapping to incorporate a uniqueness of a user's eye features and other conditions that may have some effect on eye measurements. For example, the images may be identified based on positions of blood vessels in the corresponding retinal image.

[0134] Retinal mapping can involve a process for enabling a computing device to learn how to associate a user's eye gaze (e.g., as identified in retinal images) with gaze points in a 2D or 3D space. An eye gaze may be associated with a single point in the 2D or 3D space. An eye gaze can also be associated with multiple points in the space, which can describe a movement of a virtual object (e.g., a series of points, a location of a moving image).

[0135] The head mounted display system can determine a user's eye gaze based on retinal images. The head mounted display system can obtain retinal images using sensors (e.g., eye cameras such as the imaging device **920**). The head mounted display system can image one or both eyes of the user while the user changes his or her eye gazes (such as, e.g., when the user is looking around to follow a moving or shifting calibration target or fixation target). To map a user's retina, the head mounted display system can present a virtual target, e.g., a fixation target, for the user to look at. The virtual target may be associated with one or more known points of gaze in the 2D or 3D space. While the user is looking at the target, the head mounted display system can acquire retinal image(s) and associate the image(s) with gaze point(s). The head mounted display system can calculate and/or generate a mapping matrix based on the associations of respective retinal images and points of gaze associated with the target.

[0136] The retinal mapping result can reflect uniqueness in each person's eyes. For example, the head mounted display system can generate a mapping matrix customized to one or both eyes of a specific individual. For example, the users may have different amounts of eye movements or eye gazes in response to a specific target. Additionally or alternatively, the user may have a different position, size, shape, and/or orientation of blood vessels in the retina. As a result, by generating a calibration result specific to an individual user, the head mounted display system may allow more

accurate user interactions with eye gazes and/or may allow for identification a particular user. [0137] Accordingly, when a user puts on the head mounted display device, the system can detect whether the user is a previous user or a new user. A confusion matrix can be calculated where a score for a particular eye gaze image stored in the system memory is compared to a corresponding image of the current user. The confusion matrix can include a comparison score for a plurality of eye gazes and associated retinal images. Based on the comparison scores, the system may be able to make a determination with regard to an identity of the user (e.g., whether the user is the same as the individual for which the stored retinal images or composite map are associated) and/or a confidence level for the determination. The confidence level may, for example, include an identity coefficient. Stored images, for example, a composite image or map, may be compared with later obtained images referred to as instantaneous or real-time images obtained for a current user. The system may provide an alert if the system detects that the user is a new user or may take other action.

[0138] The system may apply filtering such as digital filtering or image processing to the images of the retina captured by the camera. Such filtering or imaging processing, may for example, enhance features that may be used for identification, stitching, assembling a composite images, eye tracking, etc. Such filtering or image processing may comprise edge enhancement. Such a filter may comprise, for example, a Frangi filter although other types of filters may be used. Such a filter or processing (e.g., edge enhancement or a Frangi filter) can be used to enhance and/or detect images features such as vessels or tubular structures or fibers in retinal images.

[0139] FIG. 13B illustrates a pattern of sequentially displayed fixation targets that can be used in the retinal mapping process. These virtual targets on which a user's eye will direct their gaze can cause the eye's gaze to be redirected to a variety of different directions during which the retina can be imaged. The resultant images associated with the different gaze directions correspond to non-identical portions of the retina. As discussed above, when the eye is gazing in different directions to view differently located fixation targets on the display, images captured by the camera include different portions of the retina. These images can be assembled to form a larger map or composite image of the retina.

[0140] FIG. 13B shows a virtual target at sixteen different location in a user's field of view (FOV) 1200. In various implementations, the virtual target would be presented at a given location at a given time. One or more retinal images would be obtained during a time when the virtual target is presented at that particular location to a user. This image or these images may be associated with that target position and/or a corresponding gaze direction. Greater or fewer target locations may be used. In the example shown in FIG. 13B, the sixteen targets locations 1202a-1202p are shown. More or less target locations may be used. The target locations may also be different. The order at which the targets are presented at the different locations may vary. For example, the target may move in a raster pattern from the left to the right side of the field of view of the user, back to from the right to the left, and again from the left to the right, lowering the position of the target in the field of view with each lateral pass across the field of view. However, other patterns and approaches are possible. Likewise, the target can be rendered identically or differently at the different locations. For example, the target rendered may be different sizes, shapes, colors, etc. The targets can be rendered sequentially to a user during the eye tracking calibration process. For example, as discussed above the head mounted display system may render target in a serpentine pattern. For example, the target 1202a may be followed by 1202b, then 1202c, then 1202d, then 1202h, then 1202g, and so forth. Other patterns are possible. For example, the target could be displayed in more random or non-sequential patterns. In some embodiments, a single target is displayed to the user, and the target moves around the user's field of view (for example, passing or temporarily stopping at the positions 1202a-1202p during the target's movement). The head mounted display system can acquire an image of the user's retina(s) while the user is looking at these targets. For example, the head mounted display system can acquire a first image when the

user is looking at the target at the first location **1202a** while acquiring a second image when the user is looking at the target at a second location **1202b**, and a third image when the user is looking at the target at a third location **1202c**, and so forth. The wearable system can associate the first image to the first position **1202a** and associate the second image with the second position **1202b**, and the third image with the third position **1202c**, and so forth. Neighboring images may be stitched together in a database to create a full or partial retinal map. For example, two image can be stitched together in appropriate registration using features or portions of the feature (e.g., blood vessels or portions thereof) that are common to the multiple images. In various implementations, adjacent target positions would produce overlapping images that can be registered and stitched together. For example, target position **1202a** and target position **1202b** as well as target position **1202b** and target position **1202c** may produce overlapping and adjacent retinal images that can be stitched with each other. Accordingly, a number of different retinal images may be obtained with different eye gazes so as to assemble a larger image (e.g., a composite image or map) of the retina. [0141] As discussed above, eye tracking can be performed using the composite retinal image or map. For example, after the target is no longer displayed, the user may move their eye gaze about as the user looks at different real objects in front of the user and head mounted display or augmented reality (virtual) image content displayed by the head mounted display. One or more retinal images may be obtained at these times. The term “instantaneous” or “real-time” images may be used herein to describe these images obtained subsequent to calibration that can be used for eye tracking (or other purpose such as obtaining biometric data). These “instantaneous” or “real-time” images likely correspond to a portion of the composite retinal image or map. The system may be configured to sufficiently match this “instantaneous” or “real-time” retinal image with a portion of the composite retinal image or retinal map. Such matching may be based on features or portions of features (blood vessels or portions thereof) that are common to both the “instantaneous” or “real-time” retinal image and the portion of the composite retinal image or map. Based on the location the portion of the composite retinal image or map to which this “instantaneous” or “real-time” retinal image coincides, a gaze direction may be deduced. Different gaze directions will result in retinal images that correspond to different portions of the retinal map. Accordingly, identifying the location of the “instantaneous” or “real-time” retinal image on the composite retinal image or map will provide information as to the direction of the user's gaze. Eye tracking, for example, tracking the movement of the eye and the change in eye gaze may be performed using such or similar methods. As discussed above, edge enhancement, edge detection, or other digital filtering and/or processing may be used to enhance and/or correlate features of different images with the composite retinal image or retinal map.

[0142] In various implementations after completion of the initial calibration process where the virtual target or fixation target is displayed (e.g., at a plurality of locations) to assemble a composite retinal image or map, the composite retinal image or map can still be refined. For example, as additional retinal images are obtained, the composite retinal image or map can be further refined or improved using the additional images. Accordingly as additional “instantaneous” or “real-time” retinal images are obtained, for example for the purpose of providing eye tracking, the composite retinal image or map can be further refined or improved using the “instantaneous” or “real-time”. As a user continues to look at various positions in the display (with or without aid of a calibration target), the retinal composite image or map may be further refined using additional images are acquired subsequent to the initial calibration where the virtual target or fixation target was displayed. The quality of the composite retinal image or map may therefore be increased.

[0143] Additional non-limiting examples of how eye tracking may be accomplished and/or a composite retinal image or map may be produced and retinal images used are described in U.S. Publication No. 2017/0205875, titled “EYE IMAGE COLLECTION,” filed on Jan. 17, 2017, the disclosure of which is hereby incorporated herein by reference in its entirety.

[0144] Accordingly, as discussed above larger portions of the retina may be recorded and mapped

by obtaining retinal images and/or other images of the eye using imaging systems such as described herein and such images may facilitate eye tracking. For example, an image of the eye **210** shown in FIG. **13A** may be captured when the eye is in an arbitrary position. The processing electronics or a processor (such as the same or different one described above as forming the composite image) may then compare captured images of the user's retina in real time to the stored composite or larger size (e.g., full-size) image of the user's retina to track eye movement. A given image of the user's retina captured in real time may show a specific portion of the user's retina. As described above, by comparing such a captured image to the stored image of the user's mapping a larger portion of the user's retina, the system can determine which portion of the user's retina is shown in the captured image, and can thereby determine the position/orientation of the eye that would produce such an image. See for example FIG. **13A**, which shows two different images of portions of the retina that are produced when the eye is in two different positions and/or orientations. Accordingly, the position and/or orientation of the eye may be determined by capturing different images of the retina and determining which portion of the retina is visible. Such determination may be performed even if a composite image is not formed but rather multiple images of the retina for different eye positions/orientations are recorded and stored in a database. When a future image of the retina is obtained, that image may be compared to images in the database of stored images to determine which image in the database resembles the image of the eye recently obtained. Matching the recent image to one or more of the images in the database having associated positions and/or orientations associated with them can enable determination of the orientation and/or position of the more recent image. Other approaches to eye tracking may be used based on the images captured using the designs described herein.

[0145] As described herein, the retinal images may be employed for other purposes as well. For example, the retinal images may be used to verify that the user is the same user for which the composite retinal image or map was obtained. An image of the retina that is obtained when a user is wearing the head mounted display system (e.g., during the calibration process and/or during later use) may be compared with a previously obtained composite retinal image or map (e.g., created a prior day or when the head mounted display was previously booted up) that is stored. If the recently obtained retinal image does not match a portion of the composite retinal image or map sufficiently enough, a conclusion may be made that the current user is different than the previous user (e.g., for which the composite virtual image or map was created). Such methods may be used for security, e.g., to verify that the current user of the head mounted display device is the owner or typical user of the device. Accordingly, biometric data obtained via retinal imaging may be used for security purposes.

[0146] The retinal imaging may be used as well to collect biometric data for monitoring the user's health. Medically related data may be obtained from the retinal images. Such medical data may be useful for monitoring the health of the user.

[0147] Although various applications of eye imaging, such as eye tracking, collection of biometric data for health monitoring and for security are discussed herein in the context of retinal imaging, imaging other parts of the user, for example, of the user's eye may be employed for these and other purposes.

[0148] Although the eyepiece **950** is described above as capable of being utilized to facilitate imaging of the eye, the eyepiece can also be used to image the world in front of the user. FIGS. **14A-14B**, for example, illustrate an example imaging system **900** that can be used to image a portion of an environment in front of the user and/or objects in the portion of the environment. The imaging system **900** used may be a similar system as described for FIGS. **11A-11E** and/or for FIGS. **12A-12E** except that light is collected by the eyepiece **950** from the environment forward the eyepiece and the user. FIG. **14A**, for example, illustrates light **970** from the environment that is reflected off and/or emitted by one or more physical objects **972** in the environment forward the user and eyepiece **950**. As shown, the light **970** from the environment may be approximately

collimated (e.g., at infinity), for example because the physical object **972** in the environment may be located at a sufficiently large distance from the imaging system **900** for the light rays reaching the imaging system **900** to be collimated or approximately collimated. In some implementations, the imaging system **900** may be configured to image the environment and/or objects in the environment without the use of any optical elements having optical power (e.g., lenses, mirrors) in the imaging system **900**.

[0149] The imaging system **900** shown in FIGS. **14A** and **14B** is similar to the imaging systems described above. The imaging system includes the eyepiece **950** comprising one or more waveguides **940** including the coupling optical element **944** configured to direct light from an image projector **930** (not shown) into the eye **210** to form images therein. The one or more waveguides may include a plurality of waveguides (e.g., a stack of waveguides) configured to incouple/outcouple a plurality of corresponding colors/wavelengths. Each waveguide in a stack of waveguides may be configured to direct light of a particular color (e.g., red, green, blue). For example, a distalmost waveguide (e.g., stack of waveguides) may be configured for visible light (e.g., red, blue, green) such that the waveguide is configured to incouple and outcouple the same wavelength(s) of visible light. Additionally or alternatively, a waveguide configured to incouple and outcouple invisible (e.g., infrared) light may be disposed proximal the eye **210**. Such a plurality of waveguides corresponding to the waveguide **940** may be used in any other implementation described herein. The imaging system **900** may also include the imaging device (e.g., camera) **920** and outcoupling optical element **952** configured to turn light reflected from the eye **210** that is propagated within the waveguide **940** to the camera. In FIGS. **14A** and **14B**, the illumination source **960** is excluded since an illumination source may not be needed to image the environment in front of the user. However, an illumination source (e.g., the light source **960** described above) may be used in certain designs.

[0150] The eyepiece **950**, waveguide **940**, coupling optical element **944**, outcoupling optical element **952** and camera **920** may be the same or similar to that describe above. For example, the coupling optical element **944** may be in physical engagement with the waveguide **940**. For example, the coupling optical element **944** and/or outcoupling optical element **952** may be disposed in an optical path between the environment in front of the eyepiece **950** and camera **920** such that light from the environment is coupled into the waveguide **940** via the coupling optical element **944** and coupled out of the waveguide via the outcoupling optical element to be incident on the camera **210** (for example to form an image of at least a portion of the environment). The coupling optical element **944** may comprise a plurality of turning features configured to turn light guided within the waveguide out of the waveguide or turn light incident on the coupling optical element **944** at an angle into the waveguide to be guided therein by total internal reflection. The outcoupling optical element **952** may comprise a plurality of turning features configured to turn light (from the environment) that is guided within the waveguide at an angle such that the light is not guided in the waveguide by total internal reflection but is direct out toward the camera. The coupling optical element **944**, outcoupling optical element **952** and the turning features associated with each may be in physical engagement with the waveguide **940**. For example, the coupling optical element **944** and/or outcoupling optical element **952** may comprise one or more holographic or diffractive optical elements (e.g., surface relief gratings) patterned (e.g., etched) in or on the waveguide **940**. The coupling optical element **944** and/or outcoupling optical element **952** may comprise a layer disposed on the waveguide **940** or may be formed in the waveguide **940**. For example, a volume holographic or diffractive optical element may be formed by changing the index of refraction of material comprising the waveguide or a layer disposed thereon. Accordingly, the coupling optical element **944** and/or outcoupling optical element **952** may be disposed in the volume of the waveguide **940** or a layer disposed thereon. Depending on the design, the coupling optical element **944** and/or outcoupling optical element **952** may be transmissive or reflective and may operate in transmission or reflection. For example, the coupling optical element **944** and/or outcoupling

optical element **952** may include a transmissive or reflective diffractive optical element (e.g., grating) or holographical optical element that operates in transmission or reflection respectively, e.g., turning light via that is transmitted therethrough or that is reflected therefrom. The coupling optical element **944** and/or outcoupling optical element **952** can include a polarization optical element, such as a polarization selective turning element (e.g., polarizer). The polarization selective turning element may include one or more polarization gratings, diffractive optical elements, and/or holographic optical elements and may comprise liquid crystal structures such as liquid crystal polarization gratings. In some implementations, the reflective optical element may include a reflector (e.g., mirror). Other elements, such as for example the waveguide **940** may be similar to that described above as well.

[0151] FIG. **14B** illustrates the operation of the imaging system **900** shown in FIG. **14A**. Light **970** from the environment is coupled by the coupling optical element **944** into the waveguide **940**. The coupling optical element **944** may be configured to turn collimated light at an angle that is greater than the critical angle of the waveguide **940** such that at least a portion of this collimated light is guided within the waveguide by total internal reflection toward the camera **920**. The outcoupling optical element **952** can be configured to receive at least a portion of the light from the environment in front of the user that is coupled into the waveguide **940** via the coupling optical element **944** and guided therein. The outcoupling optical element **952** may be configured to couple the incoupled light out from the waveguide **940** to the camera **920** such that images of the environment may be captured by the camera **920**. The images of the environment may be passed to processing electronics, (e.g., one or more processors), such as data module **140** (see FIG. **2**). The data module **140** may be configured to reproduce a modified image of the environment in an augmented reality context. The processing electronics may be in communication with the camera **920** via a wired or wireless electronic signal. Additionally or alternatively, the processing electronics may communicate with the camera **920** using one or more remote receivers. The processing electronics may reside remotely (e.g., cloud computing devices, remote server, etc.).

[0152] This imaging system **900** may therefore be used for directly imaging the environment, which may be useful for a variety of reasons. For example, imaging the environment can be used to determine where to place augmented reality image content with respect to objects in the environment. For example, imaging the environment may provide the location of a table such that the head mounted display may render an image of person standing next to the table instead of on the table or in the table. The imaging system **900** described for imaging the environment may also be used to image the eye **210**, such as is described for FIGS. **10**, **11A-11E**, and/or **12A-12E**.

[0153] It may be desirable to image a wide view of the environment using the imaging system **900**. FIG. **14C** schematically illustrates an imaging system **900** for collecting light from the environment using a powered optical element or lens such as refractive optical element **980** (e.g., a wide field of view lens) forward the eyepiece. The refractive optical element **980** may have a positive optical power. The refractive optical element **980** (e.g., positive lens) converges collimated light **970** from the environment toward the waveguide **940**. Other types of lenses than the lens shown in FIG. **14C** may be employed. Light that is transmitted (not shown) may pass through a powered optical element or lens such as refractive optical element **990** (e.g., negative lens) that is configured for a negative power equal and opposite of the refractive optical element **980**. The negative lens **990** may have a similar or the same optical power as the positive lens **980** to offset or counter the optical power of the positive lens or a portion thereof. In this way, light from the environment (e.g., distal of the waveguide **940**) may pass through the negative lens **990**, the eyepiece **950**, and the positive lens **980** with substantially no net change in optical power introduced by these two lenses to the eye. The negative lens **990** may be configured to offset or counter the optical power of the positive lens **980** such that a user's will not experience the power of the positive lens when viewing the environment in front of the eyepiece **950**. The negative lens **990** will also counter the effect of the positive lens **980** to invert images of object in the environment in front of the wearer. Some light

970 from the environment may be incoupled into the waveguide **940** by the coupling optical element **944**, in spite of some of the rays of light being convergent. The incoupled light incident on the outcoupling optical element **952** may be ejected out of the waveguide **940**.

[0154] Implementations (e.g., those described by FIGS. **14A-14C**) may be used outside an augmented reality context. For example, it is intended that an imaging system **900** configured to image the environment be implemented within a wearable device, such as, for example, eyeglasses (including unpowered glasses) or bifocals. Such an imaging system **900** may not require an image projector **930** and/or light source **960**. Additionally or alternatively, such an imaging system **900** may not require an incoupling optical element configured for a corresponding image projector **930** and/or light source **960**.

[0155] It may be advantageous to implement such an imaging system **900** for imaging the environment on a viewing screen (e.g., television screen, computer screen), such as a handheld device (e.g., cell phone, tablet). The imaging system **900** could improve video chat capabilities. For example, a viewer who is seeing a chat partner look into the screen may appear to be looking directly at the viewer. This would be possible since the light rays captured by the imaging system **900** would be captured in the same region where the user is looking (e.g., as opposed to viewing a screen but having the light rays captured by a separate outward-facing camera positioned at a different location).

[0156] In implementations where the imaging system **900** of FIG. **14C** is also used to image the eye **210**, a light source **960** and/or image projector **930** may be configured to inject light into the waveguide **940**. Because the light reflected from the eye that is incoupled into the waveguide will pass through the refractive optical element **990** (e.g., negative lens), a positive powered refractive optical element may be disposed between the light source **960** and/or image projector **930** and between the waveguide **940**. The positive lens can be configured to offset or counter any optical power provided by the refractive optical element **990** before the incoupled light from the light source and/or light projector is incident on the eye **210**. Other types of lenses than shown in FIG. **14C** may be used as the optical element **990**. Alternatively or additionally, processing electronics in communication with the light source and/or image projector can be configured to alter an image sufficient to present to the user an undistorted image after the light has passed through the refractive optical element **990**. Corresponding incoupling optical element, outcoupling optical element, and/or coupling optical element may be configured to operate on non-collimated light (e.g., divergent, convergent light) in some designs.

[0157] In various implementations, the same waveguide **940** may be used to (i) propagate light from the environment in front of the eyepiece **950** and the user to the camera **940** and (ii) to propagate light from the image projector **930** to the eye **210** to form image content therein. Using the same waveguide **940** may simplify the system and/or the eyepiece and may make the system and/or eyepiece more compact possibly providing a reduced form factor. Reducing the thickness of the eyepiece **950** by reducing the number of waveguide **940** may be advantageous for other reasons as well. Lower cost and a more simplified manufacturing process may be some such advantages.

[0158] Also in various designs, the same or different imaging system may be used in the same head mounted display to image the eye by propagating light from the eye via a waveguide in the eyepiece **950** to the camera **940** such as, for example, described above. Such systems may also use the eyepiece to transfer light from an illumination source to the eye **210** to illuminate the eye. In some designs, the eyepiece may additionally be used to propagate light from the image projector **930** to the eye **210** to form image content therein. Using the eyepiece to assist in imaging the environment and image the eye (and possibly to illuminate the eye) may simplify the system and/or may make the system more compact possibly providing a reduced form factor.

[0159] Moreover, in some implementations, the same waveguide **940** may be used to (i) propagate light from the environment in front of the eyepiece **950** to the camera **940** and (ii) to propagate light from the eye **210** to the camera to capture images of the eye. The same waveguide may be used to

propagate light from the image projector **930** to the eye **210** to form image content therein and/or to propagate light from the illumination source **960** to the eye **210** to illuminate the eye for image capture. Using the same waveguide **940** may simplify the system and/or the eyepiece and may make the system and/or eyepiece more compact possibly providing a reduced form factor. Reducing the thickness of the eyepiece **950** by reducing the number of waveguide **940** may be advantage for other reasons as well. Lower cost and a more simplified manufacturing process may be some such advantages.

[0160] Similarly, in addition to coupling light from the environment into the waveguide **940**, the same coupling optical element **944** may be configured to direct light from the image projector **930** to the eye **210** to form image content therein and/or light from the eye into the waveguide **940** to be guided therein to the camera **920**. Additionally or in the alternative, the same coupling optical element **944** may be configured to couple light from the illumination source **960** guided within the waveguide **940** out of the waveguide to the user's eye **210**.

[0161] As discussed above, one or more of the coupling optical element **944**, the in-coupling optical element **942**, or the out-coupling optical element **952** may comprises polarization selective coupling elements. Accordingly, in various designs, light input into eyepiece **950** or waveguide **940** is polarized so as to acted on appropriately by the polarization selective turning elements.

[0162] Accordingly, in some embodiments the illumination source **960** comprises a polarized light source of suitable polarization to be acted on properly by the polarization selective coupling/turning elements.

[0163] One or more polarization specific optical filters and polarization modifying elements may be included in various imaging systems **900**, such as those where the image projector **930** and/or light source **960** are disposed directly opposite each other through the waveguide **940**. The polarization sensitive elements may be helpful in reducing direction light emission into the imaging device **920** and/or to reduce saturation of the imaging device **920**, for example, in configurations where these elements are aligned on opposite sides of the waveguide **940** at the same lateral position. FIGS. **15A-15B** show such a configuration. The light source **960** such as shown in FIG. **15A** can be configured to direct light through a polarization specific optical filter **982** such as a polarizer (e.g., a linear polarizer) and/or through a polarization modifying element **986** configured to alter a polarization state of incident light, such as a polarization rotator. A retarder such as a half wave retarder may, for example, rotate linear polarization. Accordingly, an appropriately oriented half wave retarder or half wave plate may rotate s-polarized light to p-polarized light or vice versa. Accordingly, in various implementations, the polarization specific optical filter **982** and/or a polarization modifying element **986** are disposed in an optical path between the light source **960** and the in-coupling optical element **942** so as to provide the properly oriented polarization to the in-coupling optical element. In some implementations, the imaging system **900** does not include polarization modifying elements but includes properly oriented polarization optical filters, such as polarizers.

[0164] The light emitted by the light source **960** may pass through an arrangement of optical elements in a particular order. For example, as shown in FIG. **15A**, the light may pass first from the light source **960** through the polarization specific optical filter **982** (e.g., polarizer) and then through the polarization modifying element **986** (e.g. rotator). After the light has passed through the polarization modifying element **986**, the light may be incident on an incoupling optical element **942**, which may direct the light into the waveguide **940** to be guided therein.

[0165] For example, the light source **960** may be configured to emit light of a mixed polarization (e.g., s-polarization and p-polarization). The polarization specific optical filter **982** may be configured to transmit only light of a first polarization state (e.g., p-polarization). As the light continues, the polarization modifying element **986** may be configured to change the polarization state of the light (e.g., from p-polarized to s-polarized). The incoupling optical element may be configured to turn s-polarized light into an angle that is greater than the critical angle of the

waveguide such that the s-polarized light is guided within the waveguide. The incoupled light **904** may be substantially polarized in the second polarization (s-polarization) as it propagates through the waveguide **940**. The coupling optical element **944** may be configured to turn light only of the second polarization state (s-polarization). The coupling optical element **944** may be configured to couple the incoupled light **904** out of the waveguide **940** and to the eye **210** to provide illumination for image capture.

[0166] In order to prevent direct illumination (e.g., saturation) of the imaging device **920**, a polarization modifying element **958** and/or a polarization specific optical filter **984** may be disposed in or on the waveguide **940** such that only light of a certain polarization state (e.g., p-polarized) can pass through the polarization specific optical filter **984** and to the imaging device **920**. The polarization modifying element **958** (e.g., half waveplate) may be configured to change the state of the polarization (e.g., from s-polarized to p-polarized). The polarization specific optical filter **984** may be configured to transmit only light of a certain polarization (e.g., p-polarized light) therethrough. In this way, light passing through the polarization specific optical filter **982** will not be configured to transmit directly through the polarization specific optical filter **984**. In any of the implementations above (e.g., where the image projector **930** and/or the light source **960** are on the same optical axis as shown in FIG. **15A**), such as in FIGS. **10**, **11A-11E**, and **12A-12E**, the configuration of the polarization specific optical filter **982**, the polarization modifying element **986**, the incoupling optical element **942**, the polarization modifying element **958**, and/or the polarization specific optical filter **984** may be implemented according to the design of FIG. **15A**. The polarization specific optical filter **984** may be a transmissive-reflective polarizer (e.g., a polarizer beam splitter) configured to transmit light of a first polarization and to redirect or reflect light of a second polarization different from the first.

[0167] A partially reflective element (e.g., semi-transparent mirror) may be included to turn the incoupled light **904** to the imaging device **920**. The partially reflective element may be disposed between the incoupling optical element **942** and the polarization modifying element **986** such that a portion of the incoupled light **914** is reflected toward the imaging device **920** while reducing leakage of the incoupled light **914** out of the waveguide **940**. The portion of light that does not leak out may be any fraction between 0 and 1. For example, the portion may be 0.90, where 90% of the light rays propagating through the waveguide **940** along the coupling optical element **944** are maintained within the waveguide **940** at each reflection of the light rays. Other portions are possible (e.g., 0.10, 0.20, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, or any value in a range between these values).

[0168] FIG. **15B** illustrates propagation of light reflected or scatter off the retina. Some of the light **910** reflected from the retina that is incident on the coupling optical element **944** having the second polarization (s-polarization) is turned by the coupling optical element **944** at angle greater than the critical angle of the waveguide **940** and thus may be guided therein. Some of the light may not be coupled into the waveguide **940** and will transmit therethrough as non-incoupled light **912**. The incoupled light **904** may propagate through the waveguide **940** toward the camera.

[0169] Other implementations may benefit from use of polarization selective elements proximal the light source and camera. For example, various systems can be configured to provide illumination having a first polarization and capture images with the camera using light having a different polarization. For example, such a configuration may be used to reduce unwanted reflections, such as from the cornea when imaging the retina. Reflection from the cornea will be specular.

Accordingly, if light of a first polarization is incident on the cornea, the light reflected from the cornea will retain that first polarization. In contrast, the retina is diffuse. If light of a first polarization is incident on the retina, the light reflected from the retina does not retain solely the first polarization. The diffuse reflection more likely results in unpolarized light. Accordingly, a second polarization, different from the first polarization will be present in the reflected light. Likewise by illuminating with a first polarization and imaging with a second different polarization,

the retina can be imaged with reduced glare from the cornea.

[0170] Accordingly, in various implementations, the polarization specific optical filters **982**, **984** may be used together to reduce unwanted reflected light from the eye **210** (e.g., from the cornea). For example, unwanted light, glare, or glint may be reflected off the cornea that may saturate an image captured by the imaging device **920**. Light reflected from the cornea may be specular and maintain its polarization. By contrast, light reflected off the retina may be more diffusely reflected and may be less homogeneously polarized. Likewise, a combination of polarizers may be used to remove some or most of the unwanted reflected light. Initially polarized light can be used for illuminating the eye **210**. In some designs, a polarized illumination source (e.g., the light source **960**) may be used. Additionally or alternatively, a first polarizer (e.g., the polarization specific optical filter **982**) may be positioned at the beginning of the optical path of the illumination source to provide initial polarization of the light. A second polarizer (e.g., the polarization specific optical filter **984**) may be positioned at the optical path before the light enters the imaging device **920**. The second polarizer may be rotated at 90° from the first polarizer (e.g. the polarizers **982**, **984** may be “crossed”). As a result, the eye will be illuminated with the first polarization with some light of the first polarization reflected from the cornea. This light will not pass through the polarizer **984** proximal the camera. However, light reflected from the retina will include the second polarization. Likewise light diffusely reflected from the retina will pass through the polarizer **984** proximal the camera and will enable an image of the retina to be captured by the camera. Thus, in such a configuration unwanted light received from the eye (e.g., from cornea) may be entering the imaging device **920** may be reduced or eliminated. Other configurations are possible. For example, a polarization selective incoupling optical element **942** for coupling light from the light source **960** into the waveguide **940** and a polarization selective outcoupling optical element for coupling light out of the waveguide to the camera **920** may be employed having different polarization selectivity properties. For example, the polarization selective incoupling optical element may selectively turn light from the illumination source having a first polarization into the waveguide while the outcoupling optical element may selectively turn light of a second different polarization out of the waveguide to the camera. The effect may again be to reduce or remove unwanted light received from the eye (e.g., from cornea) before entering the imaging device **920**.

[0171] Various imaging systems **900** are discussed herein that are capable of using the eyepiece **950** to collect light to image the retina. The imaging systems **900**, however, can be configured to image other portions of the eye such as anterior portions of the eye. FIG. **16** illustrates how an imaging system **900** can be used for imaging an anterior portion (e.g., cornea) of an eye **210**. The imaging system **900** may include one or more elements of the example imaging systems **900** described above. In addition, an example imaging system **900** may include one or more powered optical elements or lenses such as powered refractive optical elements **980**, **990** having optical power. For example, a positive power lens or positive lens **980** may be disposed on a proximal side (e.g., closer to the eye **210**) of the eyepiece **950** between the eye **210** and the eyepiece. A negative power lens or negative lens **990** may be disposed on a distal side of the eyepiece **950**, between the eyepiece and the environment forward the user. One or both of the lenses **980**, **990** may be variable focus elements (e.g., varifocal lenses) and/or may include a liquid crystal element. In some designs, one or both of the lenses **980**, **990** includes a Fresnel lens. The lenses **980**, **990** may incorporate liquid crystals to produce Fresnel lens functionality. Such functionality may allow for variable focus of one or both of the lenses **980**, **990**. In some designs, one or more of the lenses **980**, **990** may be integrated with and/or manufactured (e.g., formed) on or into the eyepiece **950**.

[0172] In various embodiments, the coupling optical element **944** is configured to turn collimated light reflected from the eye **210** into the light guide to be guided therein. Accordingly, the positive lens **980** may be configured to collimate light reflected from the eye **210**, such as an anterior portion of the eye (e.g., the cornea). The positive lens **980** therefore may have a focal length that is equal or substantially equal to the distance of the lens to the portion of the eye **210** to be imaged,

e.g., the cornea.

[0173] The negative lens **990** may have a similar or the same optical power as the positive lens **980** to offset or counter the optical power of the positive lens. In this way, light from the environment (e.g., distal of the waveguide **940**) may pass through the negative lens **990**, the eyepiece **950**, and the positive lens **980** with substantially no net change in optical power introduced by these two lenses. Thus, the negative lens **990** may be configured to offset or cancel out the optical power of the positive lens **980** such that a user will not experience the power of the positive lens when viewing the environment in front of the eyepiece **950**. The negative lens **990** will also counter the effect of the positive lens **980** to invert images of object in the environment in front of the wearer.

[0174] FIG. **16** illustrates light **928** that is incident on the cornea scattering therefrom. The imaging system **900** may be configured to capture this light **988** reflected from the cornea. For example, the positive lens **980** may collect a portion of the light **988** scattered from the cornea and collimate this light **988**. This light **988**, collimated by the positive lens **980**, is incident on the coupling optical element **944**, which is configured to turn collimated light into the waveguide **940** at an angle larger than the critical angle of the waveguide such that the light is guided therein by TIR. The coupling optical element **944**, the outcoupling optical element **952**, and/or the waveguide **940** may be as described above. Resultant outcoupled light **906** may be directed by the outcoupling optical element **952** out of the waveguide **940** to the camera (not shown).

[0175] FIG. **16** shows light **928**, such as collimated light, which may be from the eyepiece **950** such as describe above. An illumination source **960** may couple light into the waveguide **940** and the coupling element **944** may couple this light from the illumination source **960** out of the waveguide. The coupling element **944** may be configured to couple light out of the waveguide **940** as collimated light. This light illuminates the anterior portion of the eye (e.g., the cornea) and scatters therefrom. As discussed above, this scattered light **988** can be collected by the positive lens **980** and the imaging system **900** to form an image of the anterior portion of the eye **210**. Also as discussed above, this illumination **928** directed onto the eye **210** may be invisible (e.g., infrared) light.

[0176] FIG. **16** also shows an alternative arrangement for illuminating the eye **210**. In some designs, one or more light sources **934** such as LEDs or emitters may be disposed with respect to the eye **210** to direct light thereon without being guided by TIR through the waveguide **940** and directed onto the eye **210**. In some implementations, the eyepiece **950** or waveguide **940** is not in an optical path between the one or more light source **934** and the eye **210**. In some designs, a plurality of such light sources **934** may be arranged in a pattern (e.g., circular or ring-like pattern) near and/or around the eye. In some designs, the pattern of light sources **934** may define an illumination axis parallel (e.g., coaxial) with the optical axis of the one or more lenses **980**, **990**. The one or more light sources **934** may be similar to the one or more light sources **960** described above and may, for example, be pulsed. Similarly, the one or more light sources **934** may comprise infrared light sources such as infrared LEDs or another type of invisible light. Alternatively, the one or more light sources may comprise visible light sources that emit visible light. Or the one or more light sources may emit both visible and invisible (e.g., infrared) light.

[0177] FIG. **17** illustrates another example imaging system **900** configured to image a portion of the eye **210** such as an anterior portion of the eye (e.g., cornea). The imaging system **900** shown in FIG. **17** employs a reflective optical element **996** configured to collimate the light from the eye, in contrast to the transmissive optical element (lens) **980** shown in FIG. **16**. A reflective optical element will have less aberration than a transmissive optical element as chromatic aberration is not generally applicable to reflective optical elements such as the reflector **996** shown in FIG. **17**. Accordingly, by using a reflective surface in collecting light from the eye **210**, less (e.g., chromatic) aberration is introduced in the image captured of the eye.

[0178] FIG. **17** illustrates, for example, an imaging system **900** that includes a curved transmissive optical element **996** having a wavelength dependent reflective coating **998**. The curved

transmissive optical element **996** may be disposed distal the waveguide **940** (on the environment side of the eyepiece **950**). Accordingly, the curved transmissive optical element **996** may be disposed between the environment forward the wearer and the waveguide **940** and/or the coupling optical element **944**. Similarly, the waveguide **940** and/or the coupling optical element **944** may be disposed between the curved transmissive optical element **996** and the eye **210**.

[0179] The wavelength dependent reflective coating **998** may be configured to reflect light of a certain wavelength or range of wavelengths. In some implementations, for example, the wavelength dependent reflective coating **998** may be configured to reflect invisible light (e.g., infrared light) within a certain range of wavelength, while the wavelength dependent reflective coating **998** may be configured to transmit visible light. The wavelength dependent reflective coating **998** may be disposed on a surface of the curved transmissive optical element **996**, in some cases.

[0180] As discussed above, in various designs, the coupling optical element **944** is configured to turn collimated light reflected from the eye **210** into the waveguide **940** to be guided therein. Accordingly, the reflective optical element **996** may be configured to collimate light reflected from the eye **210**, such as an anterior portion of the eye (e.g., the cornea). The curved reflective optical element **996** may therefore have a positive optical power for light that is incident on the proximal side thereof that is reflected from wavelength dependent reflective coating **998**. In particular, in various designs, the reflective optical element **994** may have a focal length that is equal or substantially equal to the distance from the reflective optical element **996** to the portion of the eye **210** to be imaged, e.g., the cornea, iris, etc. Example values of focal lengths may be, for example, 2 cm to 8 cm. In some implementations, the focal length is between 4 cm and 6 cm. In some designs, the focal length is about 5 cm. The focal length may be in any range formed by any of these values or may be outside such ranges in different designs.

[0181] In various implementations, the reflective optical element **996** is disposed on the distal side of the eyepiece **950** forward the eyepiece. Accordingly, the reflective optical element **996** is disposed between the eyepiece **950** and the environment forward the user. Similarly, the eyepiece **950** is disposed between the reflective optical element **996** and the eye **210**.

[0182] The curved transmissive optical element **996** may have a curved reflective surface having a curvature of any shape. In some implementations, the surface is rotationally symmetric. In some implementations, the surface may be spherical or aspheric (e.g., parabolic). Non-rotationally symmetric shapes are also possible. In various designs, however, the reflective surface has positive optical power. The reflective optical element **996** may comprise, for example, a concave mirror at least for some wavelengths and/or polarizations.

[0183] The curved transmissive optical element **996** may be configured to have negligible power in transmission. Likewise, the curved transmissive optical element **996** may be configured to transmit light without introducing convergence or divergence. In one example, the curved transmissive optical element **996** may have a curvature of an inner radius substantially the same as a curvature of an outer radius. A thin optical element **996** may reduce optical aberration, for example, for light transmitted therethrough, may be lighter and/or may be more compact.

[0184] In various designs, the reflective optical element **996** comprises material transmissive to visible light such that the user can see the environment in front of wearer. In some cases, to enhance transmission, the curved transmissive optical element **996** may be coated on an outer surface (e.g., the distal surface) with an anti-reflective coating. The anti-reflective coating may be configured to reduce reflection of, for example, of visible light such as red, green, and/or blue light. The reflective optical element **996**, however, may be configured to reflect a portion of the light scattered from the eye **210** to form an image of the eye. Accordingly, the reflective optical element **996** may operate on different light differently. For example, the reflective optical element **996** may operate on different wavelengths differently. The reflective optical element **996** may be configured to reflect infrared light and transmit visible light.

[0185] As discussed above, one or more light sources **934** may be configured to illuminate the eye **210** with infrared light. Resultant light **988** reflected from the eye **210** (e.g., cornea) may be diverge, as schematically illustrated in FIG. **17**. The curved transmissive optical element **996** may be disposed to receive this light **988** reflected from the eye (e.g., cornea, iris). The wavelength dependent reflective coating **998** may be configured to reflect the light **988** reflected from the eye because the wavelength illumination used to illuminate the eye is the same wavelength that is reflected by the reflective coating on the curved transmissive optical element **996** (e.g., 850 nm). For example the eye may be illuminated with infrared light (e.g., 850 nm) and the curved transmissive optical element **996** may be configured to reflect infrared light (e.g., 850 nm) and to pass visible light. The shape of the curved transmissive optical element **996** may also be configured to collimate the light **988** reflected from the eye and to reflect the light to the coupling optical element **944**, which turns the collimated light into the waveguide **940** to be guided therein by TIR.

[0186] In FIG. **17**, as in some other designs, one or more light sources **934** such as LEDs or emitters may be disposed with respect to the eye **210** to direct light thereon without being guided by TIR through the waveguide **940** and directed onto the eye **210**. In some implementations, the eyepiece **950** or waveguide **940** is not in an optical path between the one or more light source **934** and the eye **210**. In some designs, a plurality of such light sources **934** may be arranged in a pattern (e.g., circular or ring-like pattern) near and/or around the eye. In some designs, the pattern of light sources **934** may define an illumination axis parallel (e.g., coaxial) with the optical axis of the one or more lenses **980**, **990**. The one or more light sources **934** may be similar to the one or more light sources **960** described above and may, for example, be pulsed. Similarly, the one or more light sources **934** may comprise infrared light sources such as infrared LEDs or another type of invisible light. Other types of light sources, however, can be used.

[0187] FIG. **18** illustrates another example imaging system **900** configured to image a portion of the eye **210** such as an anterior portion of the eye (e.g., cornea). In the implementation shown in FIG. **18**, polarization selectivity is employed to assist in controlling the path of the light reflected from the eye. In particular, in various designs, the coupling optical element **944** is polarization selective. Light, for example, having a first polarization is transmitted through the coupling optical element **944** while light of a second different polarization is turned by the coupling optical element **944** into the waveguide **940** to be coupled therein by TIR. Accordingly, in various implementations the eye **210** is illuminated with polarized light or a polarizer (not shown) is disposed between the eye and the waveguide **940** such that the light from the eye incident on the waveguide is polarized. For example, the emitters **934** may emit polarized light or a polarizer may be disposed in front of the emitters **934** such that the eye **210** is illuminated with polarized light. Accordingly, in various designs, the polarization of the polarized light incident and/or reflected from the eye **210** that is received by the optical coupling element **944** may be the first polarization such that said light is directed to the reflector **996**.

[0188] Likewise, in various implementations, the coupling optical element **944** (and/or an outcoupling optical element **952**) is configured to transmit light of a first polarization state such as a first linear, circular, or elliptical polarization state (e.g., p-polarization, left handed circular or elliptical polarization, etc.) and turn light of a second polarization state such as a second linear, circular, or elliptical (e.g., s-polarization, right handed circular or elliptical polarization, etc.) into and/or out of the waveguide, respectively. In some implementations, the eye illuminators **934** may emit only or primarily the first polarization (e.g., p polarization) or further include a polarization modifying element (e.g., polarizer) that is configured to transmit only light of the first polarization state (e.g., p-polarization). Additionally, the coupling optical element **944** and/or outcoupling optical element **952** may be configured to turn light of a second polarization (e.g., s-polarization) into and/or out of the waveguide, respectively.

[0189] Similar to the imaging system **900** shown in FIG. **17**, an imaging system **900** the curved reflector **998** shown in FIG. **17** comprises a curved transmissive optical element **996** having a

wavelength dependent reflective coating **998**. The wavelength dependent reflective coating **998** may be configured to reflect light of a certain wavelength or range of wavelengths. In some implementations, for example, the wavelength dependent reflective coating **998** may be configured to reflect invisible light (e.g., infrared light) within a certain range of wavelength, while the wavelength dependent reflective coating **998** may be configured to transmit visible light. The wavelength dependent reflective coating **998** may be disposed on a surface of the curved transmissive optical element **996**, in some cases.

[0190] In various implementations, the curved transmissive optical element **996** is disposed on the distal side of the eyepiece **950** forward the eyepiece. Accordingly, the reflective optical element **996** is disposed between the eyepiece **950** and the environment forward the user. Similarly, the eyepiece **950** is disposed between the reflective optical element **996** and the eye **210**.

[0191] Accordingly, light having the first polarization (e.g., p-polarization) from the eye **210** is incident on the coupling optical element **944** and passes therethrough to the curved transmissive optical element **996**. The imaging system **900** further included a polarization modifying optical element **978**, such as a retarder (e.g., a quarter-wave retarder). This retarder **978** is transmissive and imparts a quarter wave of retardance on the light transmitted therethrough. This light is incident on and reflected from the curved transmissive optical element **996**. The wavelength dependent reflective coating **998** may be configured to reflect the wavelength of light reflected from the eye. Consequently, this light is reflected from the curved surface of the curved transmissive optical element **996** and is collimated. This collimated light passes again through the retarder **978**, thereby imparting another quarter wave of retardance on the light transmitted therethrough. The retardance introduced on these two passes through the retarder (e.g., a full wave of retardance) causes the polarization to rotate. Accordingly, the first polarization (e.g., p-polarization) transmitted through the polarization selective coupling optical element **944** on the first pass, is transformed into the second polarization (s-polarization) and is turned into the waveguide **940** to be guided to the camera **920** by TIR. As discussed above, in various designs, the coupling optical element **944** is configured to turn collimated light reflected from the eye **210** into the waveguide **940** to be guided therein. Accordingly, the reflective optical element **996** may be configured to collimate light reflected from the eye **210**, such as an anterior portion of the eye (e.g., the cornea). The curved reflective optical element **996** may therefore have a positive optical power. In particular, in various designs, the reflective optical element **994** may have a focal length that is equal or substantially equal to the distance from the reflective optical element **996** to the portion of the eye **210** to be imaged, e.g., the cornea, iris, etc. Example values of focal lengths may be for example, 2 cm to 8 cm. In some implementations, the focal length is between 4 cm and 6 cm. In some designs, the focal length is about 5 cm.

[0192] In various designs, the reflective optical element **996** may comprise a curved surface that is configured to reflect light. The curved surface may be spherical or rotationally symmetric in certain cases. The reflective optical element **996** may comprise, for example, a concave mirror at least for some wavelengths and/or polarizations.

[0193] In various designs, the reflective optical element **996** comprises material transmissive to visible light such that the user can see the environment in front of wearer. The wavelength dependent reflective coating **998** disposed on a surface of the curved transmissive optical element **996** may therefore be transmissive to visible light or at least certain wavelength of visible light. The curved transmissive optical element **996** may also be coated on an outer surface (e.g., the distal surface) with an anti-reflective coating. The anti-reflective coating may be configured to reduce reflection of red, green, and/or blue light. The reflective optical element **994**, however, may be configured to reflect a portion of the light scattered from the eye **210** to form an image of the eye. Accordingly, the reflective optical element **996** may operate on different light differently. For example, the reflective optical element **996** may operate on different polarization states (and/or wavelengths) of light differently. The reflective optical element **996** may be configured to transmit

visible light and reflect infrared light.

[0194] As shown in FIG. 17, the one or more light sources **934** such as LEDs or emitters in FIG. 18 may be disposed with respect to the eye **210** to direct light thereon without being guided by TIR through the waveguide **940** and directed onto the eye **210**. Accordingly, in some implementations, the eyepiece **950** or waveguide **940** is not in an optical path between the one or more light sources **934** and the eye **210**. In some designs, a plurality of such light sources **934** may be arranged in a pattern (e.g., circular or ring-like pattern) near and/or around the eye. The one or more light sources **934** may be similar to the one or more light sources **960** described above and may, for example, be pulsed. Similarly, the one or more light sources **934** may comprise infrared light sources such as infrared LEDs or another type of invisible light. In particular, in various implementations the light sources **934** may emit light that is reflected by the wavelength dependent reflective coating **998** and/or the curved transmissive optical element **996**. Other types of light sources, however, can be used.

[0195] Although the polarization selective coupling optical element **944** is configured to be polarization selective depending on the type of linear polarization incident thereon, other polarization selective coupling optical elements may be polarization selective to other types of polarization states such as different types of circular or elliptical polarization. The polarization selective coupling optical element **944** may, for example, be configured such that the first polarization, such as a first circular or elliptical polarization (e.g., left handed polarization or LHP-polarization), is transmitted through the polarization selective coupling optical element **944** and the second polarization, such as second circular or elliptical polarization (e.g., right handed polarization or RHP), is turned into the light guide, or vice versa. Such a polarization selective coupling optical element **944** may comprise liquid crystal such as cholesteric liquid crystal. Examples of some liquid crystal optical elements are discussed below in the section titled “Cholesteric Liquid Crystal Mirror,” in U.S. Publication No. 2018/0164627, titled “DIFFRACTIVE DEVICES BASED ON CHOLESTERIC LIQUID CRYSTAL,” filed on Dec. 7, 2017; in U.S. Publication No. 2018/0239147, titled “DISPLAY SYSTEM WITH VARIABLE POWER REFLECTOR,” filed on Feb. 22, 2018; in U.S. Publication No. 2018/0239177, titled “VARIABLE-FOCUS VIRTUAL IMAGE DEVICES BASED ON POLARIZATION CONVERSION,” filed on Feb. 22, 2018; each of which is hereby incorporated by reference in its entirety and for all purposes.

[0196] A polarization modification element or retarder such as a circular polarizer may be disposed between the eye and the polarization selective coupling optical element **944** to convert the light reflected from the eye to the first polarization (e.g., LHP). The LHP light will pass through the polarization selective coupling optical element **944**, reflect from the reflector **998**, change polarization into RHP and be turned by the polarization selective coupling optical element **944** into the waveguide to the camera.

[0197] In some implementations, the reflector **996** may be polarization selective in its reflectivity such that only light of a certain polarization state is reflected and/or that light of a different polarization state is transmitted. Such an optical element may comprise liquid crystal such as cholesteric liquid crystal. Examples of such optical elements are discussed below in the section titled “Cholesteric Liquid Crystal Mirror,” in U.S. Publication No. 2018/0164627, titled “DIFFRACTIVE DEVICES BASED ON CHOLESTERIC LIQUID CRYSTAL,” filed on Dec. 7, 2017; in U.S. Publication No. 2018/0239147, titled “DISPLAY SYSTEM WITH VARIABLE POWER REFLECTOR,” filed on Feb. 22, 2018; in U.S. Publication No. 2018/0239177, titled “VARIABLE-FOCUS VIRTUAL IMAGE DEVICES BASED ON POLARIZATION CONVERSION,” filed on Feb. 22, 2018; each of which is hereby incorporated by reference in its entirety and for all purposes. Such optical elements may reflect light of a first polarization state such as a first circular or elliptical polarization state (left handed circular or elliptical polarization) and transmit light of a second polarization state such as a second circular or elliptical polarization

state (e.g. right handed circular or elliptical polarization) or vice versa. In some embodiments, the liquid crystal is disposed on a curved surface of the reflector **996** such that in reflection, the reflector has optical power such as positive optical power. In various other implementations, the liquid crystal optical element may be flat or planar. For example, the liquid crystal may be disposed on a flat or planar substrate or layer. Despite being flat, optical power may be included in the liquid crystal optical element. Such an element may be referred to as a cholesteric liquid crystal reflective lens. Accordingly, light from the eye may be collimated and reflected to the coupling optical element **998**. The reflector, for example, may reflect light of a first polarization state (e.g., left handed circular or elliptical) and transmit light of a second polarization (e.g., right handed circular or elliptical polarization). Accordingly, the eye **210** is illuminated with left handed circular polarized light or the light reflected from the eye is transmitted through a polarizer (e.g., a circular or elliptical polarizer) that transmits light having the first polarization (e.g., left handed circular or elliptical polarized light). The coupling optical element **944** may also be polarization selective and may transmit LHP light and turn RHP light into the waveguide. The LHP light from the eye passes through the coupling optical element **944**. This transmitted LHP light also is incident on the wavelength-selective liquid crystal reflector **996** and reflected therefrom. In certain designs, the wavelength-selective liquid crystal reflector **996** transforms the first polarization state (e.g. LHP) into the second polarization state (e.g. RHP) upon reflection. This light of the second polarization state (e.g., RHP light) is directed to the coupling optical element **944**, which turns light of the second polarization state (RHP) into the waveguide **940** to the camera **920**.

[0198] In some designs, the coupling optical element **944** does not comprise a liquid crystal grating but instead comprises, for example a surface relief diffraction grating or holographic grating. As discussed above, these coupling optical element **944** that do not comprise cholesteric liquid crystal may also comprise a volume diffractive or holographic optical elements or grating.

[0199] Accordingly, light scattered from the eye, is reflected by the reflective optical element **996** back to the waveguide **940** for coupling into the waveguide by the coupling element **944**. In contrast, however, a portion of the unpolarized light from the environment in front of the wearer corresponding to the second polarization state (e.g., RHP) would be transmitted through the reflective optical element **996**. Thus, the wearer could see objects through the reflective optical element **996**.

[0200] In various designs, however, the reflective optical element **996** would have negligible power in transmission. For example, the reflective optical element **996** may have curved surfaces on both sides of the optical element having the same curvature such that the aggregate power of the optical element for light transmitted therethrough would be negligible.

[0201] As discussed above, in various implementations, the reflective optical element **996** comprises a cholesteric liquid crystal reflective lens, a cholesteric liquid crystal reflective element such as discussed below in the section titled “Cholesteric Liquid Crystal Mirror,” in U.S. Publication No. 2018/0164627, titled “DIFFRACTIVE DEVICES BASED ON CHOLESTERIC LIQUID CRYSTAL,” filed on Dec. 7, 2017; in U.S. Publication No. 2018/0239147, titled “DISPLAY SYSTEM WITH VARIABLE POWER REFLECTOR,” filed on Feb. 22, 2018; in U.S. Publication No. 2018/0239177, titled “VARIABLE-FOCUS VIRTUAL IMAGE DEVICES BASED ON POLARIZATION CONVERSION,” filed on Feb. 22, 2018; each of which is hereby incorporated by reference in its entirety and for all purposes. Such optical element may operate on a particular wavelength or wavelength range. Accordingly, light such as infrared light reflected from the eye may be acted on by the cholesteric liquid crystal reflective element. However, light not in that wavelength range such as visible light from the environment may be passed through the cholesteric liquid crystal reflective element without being operated on by the cholesteric liquid crystal reflective element. Accordingly, the cholesteric liquid crystal reflective element may have negligible power for this visible light from the environment passing therethrough

[0202] As discussed above, in certain implementations, the illumination source **960** couples light

into the waveguide **940** that is turned out of the waveguide to illuminate the eye **210**. In such embodiments, the coupling optical element **944** may be polarization selective. For example, the coupling optical element **944** may transmit a first polarization (p-polarization) and transmit a second polarization (s-polarization).

[0203] Accordingly, if light from the illumination source **906** propagates through the waveguide **940** and is turned by the coupling optical element **944**, this illumination will be s-polarization. A polarization modifying optical element (e.g., a quarter wave retarder) may be disposed between the waveguide **940** and the eye **210** so as to cause rotation of the polarized light reflected from the eye. Light from the light source **960** that is reflected from the eye **210** will pass twice through the quarter wave retarder and as a result the s-polarized light ejected from the waveguide by the coupling element **944** to illuminate the eye will be transformed into p-polarized light.

[0204] This p-polarized light will be transmitted through the coupling optical element **944** and the waveguide and be incident on the reflective optical element **996**.

[0205] The imaging system **900** may further comprise a second polarization modifying element **978** which may comprise, for example, a retarder or waveplate as discussed above. This retarder may comprise for example a quarter wave retarder. The second polarization modifying element **978** may be disposed distal of the waveguide **940**, between the waveguide and the reflector **996**. The second polarization modifying element **978** may also be disposed between the coupling element light **944** and the reflector **996**. Light (p-polarized) from the eye **210** that is transmitted through the coupling element light **944** passes through second polarization modifying element **978** is transformed into circular polarization. If the reflector **996** reflects circular polarized light, this light will be reflected back to the waveguide **940** after passing again through the polarization modifying element **978**. Two passes through this polarization modifying element (e.g., quarter wave retarder) **978** will cause the light to be transformed into s-polarized light, which will be turned by the coupling element **944** into the waveguide to be guide therein to the camera (not shown).

[0206] As illustrated in FIG. **18**, the light **988** reflected from the eye **210** is diverging. This light is incident on the reflector **996**, which is curved or otherwise has positive optical power, and may be collimated thereby. The coupling optical element **944**, which is configured to turn collimated into the waveguide **940**, will therefore direct this collimated light from the curved reflective optical element **996** toward the imaging device **920** (not shown). Accordingly, the light reflected from the eye **210** that is collimated by the curved reflective optical element **996** is coupled into the waveguide **940** and guided therein toward the outcoupling optical element **952**. The outcoupling optical element **952** may be configured to direct the light out of the eyepiece **950** to the camera (not shown).

[0207] A wide variety of variations are possible in the configurations of the imaging system. Different types of reflectors **996** and coupling elements **944** may be employed. The reflectors **996** and coupling elements **944** may, for example, be configured to operate on linear polarized light or circular or elliptical polarized light. As discussed, the reflectors **996** have optical power. The reflectors **996** and coupling elements **944** may comprise cholesteric liquid crystal grating reflectors and/or lenses with or without optical power. Polarization modifying elements **978** such as retarders may be included between the coupling elements **944** and the reflector and/or between the coupling elements **944** and the eye. In some embodiments, a polarizer such as a circular polarizer or a linear polarizer may be disposed between the eye and the coupling elements **944**. If for example unpolarized light is reflected from the eye, a polarizer (e.g., circular polarizer or linear polarizer) may be disposed between the eye and the coupling elements **944**. In some such cases the coupling elements **944** are polarization selective.

[0208] In configurations such as shown in FIGS. **17** and **18**, where light reflected from the eye passes through the waveguide **940** to the curved reflective optical element **996** to be collimated and redirected back to the waveguide, background noise is introduced. This background noise results from light passing initially from the eye through the coupling optical element **944**. As discussed

above, the coupling optical element **944** may be configured to turn collimated light into the waveguide **940** to be guided therein to the camera **920** where an image is formed. The coupling optical element **944** will, however, turn some non-collimated light incident thereon. Accordingly, on the initial pass through the coupling optical element **944** and the waveguide **940** to the curved reflective optical element **996**, some of the non-collimated (diverging) light reflected from the eye will be coupled by the coupling optical element **944** into the waveguide and contribute background noise to image of the eye formed at by the camera **920**. This noise will be superimposed on the image formed by the collimated light retro-reflected by the curved reflective optical element **996** that is coupled by the coupling optical element **944** into the waveguide to be guided therein to the camera **920**.

[0209] In certain designs, this noise can be subtracted out from the image. The process for subtracting out the noise from the signal may involve (a) measuring the amount of light coupled by the coupling optical element **944** on the initial pass through the coupling optical element **944** to the curved reflective optical element **996** that is turned and reaches the camera **920** (referred to as N) and (b) measuring the total signal at the camera **920** when light passes through coupling optical element **944** and the waveguide **940** to the curved reflective optical element **996**, is collimated, and reflected back to the coupling optical element and turned to the camera. This total signal will also include some noise, N, as the uncollimated light reflected from the eye will have passed through the coupling optical element **944** to get to the curved reflective optical element **996** and thus some of uncollimated light will be turned by the coupling optical element **944** to the camera **920**. If the noise, N, can be measured separately from the total signal, T, that includes the noise superimposed over the image of the eye, the noise, N, can be subtracted out from the total signal, T, as represented by the formula below:

$$I=T-N$$

[0210] where I represents the image with the noise component, N, removed.

[0211] The two measurements (a) and (b) above can be obtained in various ways. For example, as shown in FIG. **19**, a shutter **936** can be disposed between the curved reflective optical element **996** and the waveguide **940** and coupling optical element **944**. This shutter **936** may be configured to block light when the shutter is in a first state and to transmit light when the shutter is in a second state. This shutter **936** may comprise, for example, a liquid crystal shutter.

[0212] Accordingly, the noise component N can be measured when the shutter **936** is in the first state where light reflected from the eye **210** is incident on the coupling optical element **944**, passes therethrough toward the curved reflective optical element **996**, however, is prevented from reaching the curved reflective optical element by the closed shutter. As discussed above, some of the light reflected from the eye **210**, although mainly uncollimated, does couple into the coupling optical element **944** and is turned into the waveguide and guided therein to the camera **920**. As referenced above, this light does not contribute to formation of an image, but will be background noise. The camera **920** may record this noise, N, when the shutter **936** is closed.

[0213] The total signal, T, including both the noise, N, and the image, can be measured when the shutter **936** is in the second state where the shutter is open. Light reflected from the eye **210** is again incident on the coupling optical element **944**. Some of this light reflected from the eye **210**, although mainly uncollimated, couples into the coupling optical element **944** and is turned into the waveguide and guided therein to the camera **920**. Most of this light reflected from the eye **210**, however, passes through the coupling optical element **944**, through the open shutter **936** and to the curved reflective optical element **996**. The curved reflective optical element **996** collimates and reflects at least a portion of this light back to the coupling optical element **944**, which turns this collimated light into the waveguide **940** to be guided to the camera **920** to form an image of the eye **210**. The camera **920** can capture this image of the eye **210**.

[0214] Processing electronics (such as processing electronics **140**) in communication with the

camera **920** can receive the noise component, N, measured when the shutter **936** was in the first closed state as well as the total signal, T, measured when the shutter was in the second open state and can subtract the two (T-N). In this manner, the noise, N, contributed by the non-collimated light reflected from the eye **210** that is coupled into the coupling optical element **944** on the initial pass therethrough, can be subtracted from the total image signal, T. The processing electronics may be in communication with the camera **920** via a wired electronic signal. Additionally or alternatively, the processing electronics may communicate with the camera **920** using one or more remote receivers. The processing electronics may reside remotely (e.g., cloud computing devices, remote server, etc.).

[0215] Other ways may be employed to perform the measurement of (a) and (b) to obtain N and T and subtract N from T. For example, if the curved reflective optical element **996** is wavelength selective such as shown in FIG. **18**, the eye can be illuminated with light of different wavelength at different times. For example, to perform the measurement (a) and quantify the noise, N, the eye can be illuminated with a wavelength that is not reflected by the curved reflective optical element **996**. However, to perform the measurement (b) and quantify the total signal, T, the eye can be illuminated with a wavelength that is reflected by the curved reflective optical element **996**. The noise, N, can then be subtracted from the total T, as discussed above (e.g., T-N).

[0216] FIGS. **20-20E** illustrate an example imaging system **900** configured to use wavelength modulation to measure and subtract out the noise component, N, as discussed above. The imaging system **900** in FIGS. **20A-20E** includes a curved transmissive optical element **996** that is wavelength selective (such as described with reference to FIGS. **17** and **18** above). For example, the curved transmissive optical element **996** has a wavelength dependent reflective coating **998** on a curved surface thereof. The imaging system **900** may also include one or more light sources or illumination sources (not shown) configured to illuminate the eye **210**. The one or more light sources may be configured to emit infrared light. The one or more light sources, however, can be configured to emit different color or wavelength light at different times. Such wavelength modulation can enable the measurement of N separately so as to be subtracted out from the total signal, T.

[0217] In various implementations, for example, the one or more illumination sources **960**, **934** may be configured in a first state to emit one or more wavelengths that are reflected by the curved reflective optical element, $\lambda_{\text{sub.Reflect}}$, and in a second state one or more wavelengths that are not reflected $\lambda_{\text{sub.Not Reflect}}$. In the second state, no more than negligible amounts of wavelengths that are reflected by the curved reflective optical element, $\lambda_{\text{sub.Reflect}}$, are emitted. Similarly, in the first state, no more than negligible amounts of wavelengths that are not reflected $\lambda_{\text{sub.Not Reflect}}$ are emitted.

[0218] In some examples, the reflected wavelength(s), $\lambda_{\text{sub.Reflect}}$, may be between about 800 nm and 950 nm. The reflected wavelength(s), $\lambda_{\text{sub.Reflect}}$, may be between about 835 nm and 915 nm. The reflected wavelength(s), $\lambda_{\text{sub.Reflect}}$, may be between about 840 nm and 870 nm. In some designs, the reflected wavelength, $\lambda_{\text{sub.Reflect}}$, is about 850 nm. The light emission **928** from the one or more light sources **960** may illuminate the eye.

[0219] As shown in FIG. **20B**, light **988** having the wavelength(s) that are not reflected by the curved reflective optical element **944**, $\lambda_{\text{sub.Not Reflect}}$, (and no more than negligible amounts of light that is reflected by the curved reflective optical element **944**, $\lambda_{\text{sub.Reflect}}$) is reflected off part of the eye **210** (e.g., the cornea). Because this light comprises wavelength(s) that are not reflected by the curved reflective optical element **944**, $\lambda_{\text{sub.Not Reflect}}$, rays of light **916** are shown propagating through the curved reflective optical element **996** to the environment forward the user.

[0220] Although the light **988** incident on the coupling optical element **944** is not collimated, the coupling optical element nevertheless couples at least some light **914** into the waveguide **940** to be guided to the camera **920**. According, the camera **920** may capture an image (Image #1)

corresponding to the noise component, N, that results from uncollimated light that is turned by the coupling optical element **944** on the initial pass to the curved reflective optical element **996**. This image (Image #1) is background noise and does not a recognizable image of the eye. Processing electronics **140** is shown as receiving this first image (Image #1).

[0221] In FIGS. **20C-20E**, the illumination sources (not shown) emit one or more wavelengths that are reflected by the curved reflective optical element, $\lambda_{\text{sub.Reflect}}$, and no more than negligible amounts of wavelengths that are not reflected $\lambda_{\text{sub.Not Reflect}}$. This wavelength, $\lambda_{\text{sub.Reflect}}$, may be, for example, 850 nm.

[0222] As shown in FIG. **20C**, some of the light **988** reflected from the eye **210** that is incident on coupling optical element **944** in the first pass through the coupling optical element **944** is coupled by the coupling optical element **944** into the waveguide **940** (as in FIG. **20B**) and directed toward the camera **920**. Additionally, the curved transmissive optical element **996**, which selectively reflect light of wavelength $\lambda_{\text{sub.Reflect}}$, reflects and collimates the non-incoupled light **918** reflected from the eye **210** that is incident on the curved transmissive optical element. As illustrated in FIG. **20E**, the coupling optical element **944** turns and couples this collimated reflected light into the waveguide **940** toward the camera **920**. FIG. **20E** shows both components reaching the camera **920**, light **988** reflected from the eye **210** that is incident on coupling optical element **944** in the first pass through the coupling optical element **944** is coupled by the coupling optical element into the waveguide **940** and light reflected and collimate by the curved transmissive optical element **996** that is coupled by the coupling optical element into the waveguide. The camera **920** may capture an image (Image #2) corresponding to this total image component, T. Processing electronics **140** is shown as receiving this second image (Image #2).

[0223] As discussed above, the processing electronics may subtract the noise from the image, T-N. In this example, Image #1 can be subtracted from Image #2. Accordingly, the processing electronics **140** may be configured to modify the second image based on the first image. Other approaches, however, are possible. For example, the processing electronics **140** may be configured to create a new image that represents a version of the second image with reduced optical noise. Implementations for subtracting noise from the image may be used in implementations described above. For example, implementations shown in FIGS. **10**, **11A-11E**, and/or FIGS. **12A-12E** can include a shutter **936** and/or a curved transmissive optical element **996** having a wavelength dependent reflective coating **998** configured to selectively reflect non-incoupled light **912** and to direct the light to an imaging device **920**.

[0224] As discussed above, the Image #1 was obtained for the case where the light was illuminated with one or more wavelengths that are not reflected by the curved reflective optical element, $\lambda_{\text{sub.Not Reflect}}$, and no more than negligible amounts of wavelengths that are reflected $\lambda_{\text{sub.Reflect}}$. Image #2 was obtained for the case where the light was illuminated with one or more wavelengths that are reflected by the curved reflective optical element, $\lambda_{\text{sub.Reflect}}$, and no more than negligible amounts of wavelengths that are not reflected $\lambda_{\text{sub.Not Reflect}}$. Accordingly, the one or more illumination sources **960**, **934** may be configured to modulate in wavelength. For example, in certain designs the one or more illumination sources **960**, **934** may comprise a first illumination source configured to output one or more wavelengths not reflected by the curved reflective optical element, $\lambda_{\text{sub.Not Reflect}}$, and no more than negligible amounts of wavelengths that are reflected $\lambda_{\text{sub.Reflect}}$. The one or more illumination sources may further comprise a second illumination source configured to output one or more wavelengths that are reflected by the curved reflective optical element, $\lambda_{\text{sub.Reflect}}$, and no more than negligible amounts of wavelengths that are not reflected $\lambda_{\text{sub.Not Reflect}}$. The intensity of the first and second illumination sources can be alternately increased and decreased, turned on and off, attenuated and not attenuated, passed and blocked to provide modulation in the wavelength of light illuminating the eye. For example, during a first time interval the first illumination source can be blocked while the second illumination source is not blocked. During a subsequent second time interval, the

second illumination source can be blocked while the first illumination source is not blocked. This process can be repeated to provide modulation of the wavelength of light illuminating the eye. In other designs, the wavelength of a light source may be tuned and detuned to shifted the wavelength back and forth between λ_{sub} . Reflect and Not Reflect. Other arrangements are possible.

[0225] As described above, imaging systems **900** may be included in head mounted displays such as augmented reality displays that additionally provide the ability to image the eye by collecting light with the eyepiece **950**. Such imaging systems **900** may be used for eye tracking. Multiple images of the retina or an anterior portion of the eye may be obtained. Movement and/or repositioning of the eye can be ascertained from these images to track the eye position and/or orientation. These imaging system may also be use as for biometric imaging and/or for identifying the user. For example, an image of the user's eye such as of the retina or iris may be obtained and recorded. A subsequent image of the eye (e.g., retina, or iris) of the wearer may be obtained at a later time. The two images may be compared to determine whether the wearer in that later instance was the wearer in the first instance. Other uses for the imaging systems however are possible.

[0226] Although illumination systems may be described above as waveguide based and comprising one or more waveguides, other types of light turning optical elements may be employed instead of a waveguide. Such light turning optical elements may include turning features to eject the light out of the light turning optical element, for example, onto the spatial light modulator. Accordingly, in any of the examples described herein as well as any of the examples below, any reference to waveguide may be replaced with light turning optical element instead of a waveguide. Such a light turning optical element may comprise, for example, a polarizing beam splitter such as a polarizing beam splitting prism.

[0227] As discussed above the systems described herein can allow for collection of biometric data and/or biometric identification. For example, the eye or portions thereof (e.g., the retina) can be imaged to provide such biometric data and/or biometric identification. Images of the eye such as of the retina may be obtained at various times when the head mounted display system is being worn by a user, presumably the same user. A collection of such images can be recorded, for example, in a database. These images may be analyzed to collect biometric data. Such biometric data may be useful for monitoring the user's health or medical status. Different medical parameters can be monitored by imaging the patient, for example, the patient eye (e.g., retina). The medical parameters can be recorded and compared with subsequent measurements obtained when the user is wearing the head mounted display system.

[0228] In addition, if a person begins wearing the head mounted display system and an image of the user's eye is captured that does not match the images stored in the database a conclusion may be drawn that the person currently wearing the head mounted display system is different from the previous user. This can be useful in determining whether the intended user is wearing the headset or if it is being worn by a new user. Such a feature may allow for certain medical, security, and/or convenience-in-use applications or functionality. For example, the head mounted display may be configured to identify a wearer based on characteristics of the wearer's eye. For example, the system can be configured to determine an individual based on features of a wearer's retina (e.g. blood vessels), cornea, or other eye features. In some implementations for example, a series of markers may be determined for a particular wearer. Based on the series of markers, the system may be able to determine that the previous user is wearing the headset or, alternatively, that another user is wearing the headset. The markers may include a shape or center of a user's cornea, a configuration of blood vessels in the user's retina, an intensity and/or position of a reflection of light from the cornea, a shape of an aspect of the eye, and/or any other biometric marker. In certain implementations a confusion matrix can be determined. As discussed above for example in the discussion of developing a retinal map using a virtual/fixation target at a variety of location (see, e.g., FIG. **13B**), the system may have a user look in a set of pre-determined directions or eye poses and develop a matrix of characteristics of the eye or part of the eye (e.g., cornea, retina, etc.)

associated with each direction or eye pose. Using such a matrix, the system can determine an identity of the individual. Other methods are possible.

[0229] Similarly, as discussed above, a wide variety of configurations of the system are possible. For example, FIG. 21 shows an example eyepiece 900 that can be used to simultaneously project light into a user's eye while imaging the user's eye. The eyepiece 900 shown includes an incoupling optical element 2104, a light distributing element 2108, and a light consolidating element 2116, and an outcoupling optical element 2120 on opposite sides of a coupling optical element 2112. Each of these optical elements may be disposed within or on a waveguide 2102. The waveguide 2102 may correspond, for example, to one of the waveguides 670, 680, 690 described herein (see, e.g., FIG. 9A-9C). The incoupling optical element 2104 may correspond to one of incoupling optical elements 700, 710, 720 described herein and/or to the incoupling optical element 942 (see, e.g., FIG. 10) and may be configured to inject image content from a projector into the waveguide and/or illumination from a light source 960. The light distributing element 2108 may correspond to one of the light distributing elements 730, 740, 750 described herein (see, e.g., FIGS. 9A-9C) and may be used to spread light in a given direction and redirect the light from the incoupling optical element 2104 to the coupling optical element 2112. The coupling optical element 2112 may correspond to the coupling optical element 944 described herein (see, e.g., FIG. 10). In some designs, the coupling optical element 2112 includes functionality described herein with respect to the outcoupling optical elements 800, 810, 820 (see FIGS. 9A-9C). The light consolidating element 2116 may be configured to reduce the lateral spatial extent of light received from the coupling optical element 2112 and redirect said light toward the outcoupling optical element 2120. The outcoupling optical element 2120 may correspond to the outcoupling optical element 952 described herein (see, e.g., FIG. 10).

[0230] The incoupling optical element 2104 may be disposed within or on the waveguide 2102 so as to receive light, such as from a projector (e.g., the image projector 930) and/or an illuminator (e.g., the light source 960). The light may be passed via the waveguide 2102 to the associated light distributing optical element 2108. Any of the incoupling optical element 2104, light distributed optical element 2108 or coupling optical element 2112 may be disposed on a major surface of (e.g., on a top or bottom surface) of the waveguide or within the waveguide. Similarly, any one or combination of the light consolidating element 2116, and/or the outcoupling optical element 2120 may be disposed on the major surface (e.g., a top or both major surface) of the waveguide 2102 or within the waveguide.

[0231] The coupling optical element 2112 may receive the light (e.g., via TIR) from the light distributing element 2108 and expand the light to enter the user's eye. Thus, the coupling optical element 2112 may be disposed in front of a user's eye and project image content therein. Additionally or alternatively, the coupling optical element 2112 may be configured to provide illuminating light onto and/or into the user's eye.

[0232] Light that is reflected from the eye (e.g., the illumination light from the illumination source) may be reflected and captured by the coupling optical element 2112. Thus, in some embodiments, the coupling optical element 2112 can serve to both outcouple light received from the light distributing element 2108 and incouple light received from the eye into the waveguide 2102.

[0233] In some embodiments, the coupling optical element 2112 may include one or more diffractive optical elements (DOEs) such that the coupling optical element 2112 has dual functionality. A first DOE (e.g., a grating, holographic region) may be configured to outcouple light as well and a second DOE may be configured to incouple reflected light from the eye into the waveguide 2102. In some embodiments, both the first and second DOEs are superimposed (e.g., occupy the same or approximately the same volume) within the waveguide 2102.

[0234] Alternatively, in some embodiments, the coupling optical element 2112 includes at least two DOEs that are stacked on over or in front of the other. For example, with reference to FIG. 21, the first DOE of the coupling optical element 2112 may be disposed over, whereas the second

diffractive element may be disposed under the first DOE. The order of each DOE may be reversed in other implementations.

Cholesteric Liquid Crystal Mirror

[0235] Some liquid crystals are in a phase referred to as a chiral phase or a cholesteric phase. In a cholesteric phase, the liquid crystals can exhibit a twisting of the molecules along an axis perpendicular to the director, where the molecular axis is parallel to the director. As described herein, a cholesteric liquid crystal (CLC) layer comprises a plurality of liquid crystal molecules in a cholesteric phase that extend in a direction, e.g., a direction perpendicular to the director such as a layer depth direction, and that are successively rotated or twisted in a rotation direction, e.g., clockwise or counterclockwise. The directors of the liquid crystal molecules in a chiral structure can be characterized as a helix having a helical pitch (p), which corresponds to a length in the layer depth direction corresponding to a net rotation angle of the liquid crystal molecules of the chiral structures by one full rotation in the first rotation direction. In other words, the helical pitch refers to the distance over which the liquid crystal molecules undergo a full 360° twist. The liquid crystals displaying chirality can also be described as having a twist angle, or a rotation angle (ϕ), which can refer to, for example, the relative azimuthal angular rotation between successive liquid crystal molecules in the layer normal direction, and as having a net twist angle, or a net rotation angle, which can refer to, for example, the relative azimuthal angular rotation between an uppermost liquid crystal molecule and a lowermost liquid crystal molecule across a specified length, e.g., the length of a chiral structure or the thickness of the liquid crystal layer. As described herein, a chiral structure refers to a plurality of liquid crystal molecules in a cholesteric phase that extend in a direction, e.g., a direction perpendicular to the director such as a layer depth direction, and are successively rotated or twisted in a rotation direction, e.g., clockwise or counterclockwise. In one aspect, the directors of the liquid crystal molecules in a chiral structure can be characterized as a helix having a helical pitch.

[0236] FIG. 22 illustrates a cross-sectional side view of a cholesteric liquid crystal (CLC) layer **1004** comprising a plurality of uniform chiral structures, according to embodiments. In the CLC layer **1004**, the chiral structures that are adjacent in a lateral direction, e.g., x-direction, have similarly arranged liquid crystal molecules. In the illustrated embodiment, the chiral structures **1012-1**, **1012-2**, . . . **1012-i** are similarly configured such that liquid crystal molecules of the different chiral structures that are at about the same depth, e.g., the liquid crystal molecules closest to the light-incident surface **1004S**, have the same rotation angle, as well as successive rotation angles of successive liquid crystal molecules at about the same depth, as well as the net rotation angle of the liquid crystal molecules of each chiral structure.

[0237] The CLC **1004** comprises a CLC layer **1008** comprising liquid crystal molecules arranged as a plurality of chiral structures **1012-1**, **1012-2**, . . . **1012-i**, wherein each chiral structure comprises a plurality of liquid crystal molecules, where i is any suitable integer greater than 2. In operation, when incident light having a combination of light beams having left-handed circular polarization and light beams having right-handed circular polarization are incident on the surface **1004S** of the CLC layer **1008**, by Bragg-reflection, light with one of the circular polarization handedness is reflected by the CLC layer **1004**, while light with the opposite polarization handedness is transmitted through the CLC layer **1008** without substantial interference. As described herein and throughout the disclosure, the handedness is defined as viewed in the direction of propagation. According to embodiments, when the direction of polarization, or handedness of the polarization, of the light beams **1016-L**, **1016-R** is matched such that it and has the same direction of rotation as the liquid crystal molecules of the chiral structures **1012-1**, **1012-2**, . . . **1012-i**, the incident light is reflected. As illustrated, incident on the surface **1004S** are light beams **1016-L** having left-handed circular polarization and light beams **1016-R** having a right-handed circular polarization. In the illustrated embodiment, the liquid crystal molecules of the chiral structures **1012-1**, **1012-2**, . . . **1012-i** are rotated in a clockwise direction successively in the

direction in which incident light beams **1016-L**, **1016-R** travel, i.e., positive x-direction, which is the same rotation direction as the light teams **1016-R** having right-handed circular polarization. As a result, the light beams **1016-R** having right-handed circular polarization are substantially reflected, whereas the light beams **1016-L** having left-handed circular polarization are substantially transmitted through the CLC layer **1004**.

[0238] As described supra, by matching the handedness of polarization of incident elliptically or circularly polarized light with the direction of rotation as the liquid crystal molecules of the chiral structures of a CLC layer, the CLC layer can be configured as a Bragg reflector. Furthermore, one or more CLC layers having different helical pitches can be configured as a wave-length selective Bragg reflector with high bandwidth. Based on the concepts described herein with respect to various embodiments, the CLC layers can be configured as an off-axis or on-axis mirror configured to selectively reflect a first range of wavelengths, for example, infrared wavelengths (e.g., the near infrared), while transmitting another range of wavelengths, e.g., visible wavelengths.

[0239] FIG. **23** illustrates an example of an eye-tracking system **2300** employing a cholesteric liquid crystal reflector (CLCR), e.g., a wavelength-selective CLCR **1150** configured to image an eye **302** of a viewer, according to various embodiments. Unlike the CLC layer **1004** described above with respect to FIG. **22**, the chiral structures in the wavelength-selective CLCR **1150** that are adjacent in a lateral direction, e.g., x-direction, have differently arranged liquid crystal molecules. That is, the chiral structures are configured such that liquid crystal molecules of the different chiral structures that are at about the same depth, e.g., the liquid crystal molecules closest to the light-incident surface **1004S**, have different rotation angle. As a result, light incident on the CLCR **1150** is reflected at an angle ($\theta_{\text{sub.R}}$) relative to the layer depth direction, as described further below in the context of the eye-tracking system **2300**.

[0240] Eye tracking can be a useful feature in interactive vision or control systems including wearable display systems described elsewhere in the specification, for virtual/augmented/mixed reality display applications, among other applications. To achieve effective eye tracking, it may be desirable to obtain images of the eye **302** at low perspective angles, for which it may in turn be desirable to dispose an eye-tracking camera **702b** near a central position of viewer's eyes. However, such position of the camera **702b** may interfere with user's view. Alternatively, the eye-tracking camera **702b** may be disposed to a lower position or a side. However, such position of the camera may increase the difficulty of obtaining robust and accurate eye tracking since the eye images are captured at a steeper angle. By configuring the CLCR **1150** to selectively reflect infrared (IR) light **2308** (e.g., having a wavelength of 850 nm) from the eye **302** while transmitting visible light **2304** from the world, the camera **702b** can be placed away from the user's view while capturing eye images at normal or low perspective angles. Such configuration does not interfere with user's view since visible light is not reflected. The same CLCR **1150** can also be configured as an IR illumination source **2320** by reflecting IR light from an IR source, e.g., IR LED, into the eye **302**, as illustrated. A low perspective angle of IR illuminator can result in less occlusions, e.g., from eye lashes, which configuration allows more robust detection of specular reflections, which can be a useful feature in modern eye-tracking systems.

[0241] Still referring to FIG. **23**, according to various embodiments, the CLCR **1150** comprises one or more cholesteric liquid crystal (CLC) layers each comprising a plurality of chiral structures, wherein each chiral structure comprises a plurality of liquid crystal molecules that extend in a layer depth direction (e.g., z-direction) and are successively rotated in a first rotation direction, as described supra. The arrangements of the liquid crystal molecules of the chiral structures vary periodically in a lateral direction perpendicular to the layer depth direction such that the one or more CLC layers are configured to substantially Bragg-reflect a first incident light having a first wavelength ($\lambda_{\text{sub.1}}$) while substantially transmitting a second incident light having a second wavelength ($\lambda_{\text{sub.2}}$). As described above, each of the one or more CLC layers are configured to substantially Bragg-reflect elliptically or circularly polarized first and second incident light having

a handedness of polarization that is matched to the first rotation direction, when viewed in the layer depth direction, while being configured to substantially transmit elliptically or circularly polarized first and second incident light having a handedness of polarization that is opposite to the first rotation direction, when viewed in the layer depth direction. According to embodiments, the arrangements of the liquid crystal molecules varying periodically in the lateral direction are arranged to have a period in the lateral direction such that a ratio between the first wavelength and the period is between about 0.5 and about 2.0. According to embodiments, the first wavelength is in the near infrared range between about 600 nm and about 1.4 μm , for instance about 850 nm and the second wavelength is in the visible range having one or more colors as described elsewhere in the specification. According to various embodiments, the liquid crystal molecules of the chiral structures are pre-tilted relative to a direction normal to the layer depth direction. As configured, the one or more CLC layers are configured such that the first incident light is reflected at an angle ($\theta_{\text{sub.R}}$) relative to the layer depth direction (z-direction) exceeding about 50°, about 60°, about 70° or about 80° degrees relative to the layer depth direction.

[0242] Thus configured, the wavelength-selective CLCR **1150** comprises one or more cholesteric liquid crystal (CLC) layers each comprising a plurality of liquid crystal molecules that extend in a layer depth direction and are successively rotated in a first rotation direction, wherein arrangements of the liquid crystal molecules of the chiral structures vary periodically in a lateral direction perpendicular to the layer depth direction such that the one or more CLC layers are configured to substantially Bragg-reflect a first incident light having a first wavelength, e.g., an IR wavelength, while substantially transmitting a second incident light having a second wavelength, e.g., a visible wavelength.

[0243] Similar liquid crystal layers and structures may be used for the reflector **996** and coating **998** described above in connection with FIGS. 17-20E. The coating **998** may for example comprise a liquid crystal coating and may be wavelength and/or polarization selective in certain implementations. Other types of coatings **998** and reflectors **996**, however, may be employed.

[0244] As discussed above, for example, in connection with FIG. 16, a lens **980** may be used to alter the propagation of (e.g., collimate) light directed to the coupling optical element **944**. This light may be light reflected from, for example, the user's eye such as an anterior surface (e.g., corneal surface) of the user's eye. The distance from the eye, e.g., the anterior surface (e.g., corneal surface) to the coupling optical element **944** may be for example about 20 mm. A positive lens **980** such as a lens having a focal length of about 20 mm may be configured to collimate light reflected from the eye **210**, such as an anterior portion of the eye (e.g., the cornea). Light reflected from the anterior surface eye may be coupled into the waveguide **940** and guided therein to a camera. With the focal length set at the distance to the anterior surface of the eye, the camera can image such surfaces. Accordingly, in various implementations the positive lens **980** therefore may have a focal length that is equal or substantially equal to the distance of the lens to the portion of the eye **210** to be imaged, e.g., the cornea.

[0245] Although a refractive optical element is shown, other types of lenses or optical elements with optical power such as positive optical power may be used. For example, the lens may comprise a diffractive optical element such as a diffractive lens or hologram. Such a lens may be disposed between the eye and the coupling optical element **944** in some implementations.

[0246] In various implementations, the coupling optical element **944** may include optical power. The coupling optical element **944** may, for example, comprise a diffractive optical element having optical power. The diffractive optical element may comprise, for example, a diffractive grating. The diffractive optical element may comprise a holographic optical element or a hologram. The diffractive optical element may have diffractive features such as for example surface features that are configured to both turn light into the waveguide and to provide optical power. Other types of diffractive optical elements are possible. In various implementations, the diffractive optical elements may comprise liquid crystal and may comprise liquid crystal gratings. The diffractive

optical elements may also comprise polarization grating. Additionally, the diffractive optical elements may comprise liquid crystal polarization gratings. Some nonlimiting examples of liquid crystal gratings, liquid crystal polarization gratings and other liquid crystal optical elements are discussed in the following published applications, each of which is hereby incorporated by reference herein in its entirety and for all purposes: U.S. Publication No. 2018/0143438, titled "MULTILAYER LIQUID CRYSTAL DIFFRACTIVE GRATINGS FOR REDIRECTING LIGHT OF WIDE INCIDENT ANGLE RANGES," filed on Nov. 16, 2017; U.S. Publication No. 2018/0143485, titled "SPATIALLY VARIABLE LIQUID CRYSTAL DIFFRACTION GRATINGS," filed on Nov. 16, 2017; U.S. Publication No. 2018/0143509, titled "WAVEGUIDE LIGHT MULTIPLEXER USING CROSSED GRATINGS," filed on Nov. 16, 2017; U.S. Publication No. 2018/0239177, titled "VARIABLE-FOCUS VIRTUAL IMAGE DEVICES BASED ON POLARIZATION CONVERSION," filed on Feb. 22, 2018; and U.S. Publication No. 2018/0164627, titled "DIFFRACTIVE DEVICES BASED ON CHOLESTERIC LIQUID CRYSTAL," filed on Dec. 7, 2017.

[0247] This diffractive optical element may have optical power that alters on the propagation of light incident thereon. The diffractive optical element, may for example, collimate light reflected from a surface having a distance from said diffractive optical element corresponding to the focal length of the diffractive optical element. Such distance may be for example from about 15 to 20 mm (e.g., 20 mm or thereabouts). Such a focal length may provide for collimating light reflected from an anterior surface of the eye such as a corneal surface (e.g., cornea).

[0248] FIG. 24 shows an example, of a coupling optical element (e.g., coupling grating) **2111** disposed on a waveguide **2102** of an eyepiece **950**. The coupling optical element **2111** comprises a diffractive optical element configured to couple light incident thereon into the waveguide **2102**. The diffractive optical element also includes optical power. For example, the diffractive optical element includes diffractive features such as surface diffractive features that are configured to provide optical power, for example, to collimate light incident thereon from an anterior surface of the eye (e.g., corneal surface). A light consolidating element **2116**, and an outcoupling optical element **2120** are also shown disposed on the waveguide **2102**. The light consolidating element **2116** is disposed to receive light coupled into the waveguide **2102** by the coupling element **2111**. The light consolidating element **2116** is configured to redirect light incident thereon from the coupling optical element **2111** to the out-coupling optical element **2120**. The light consolidating element **2116** is configured to reduce lateral spatial extent of light (e.g., the light beam) from said at least one coupling element prior to reaching said at least one out-coupling optical element, and an outcoupling optical element **2120**. In certain configurations, fewer optical elements may be used, possibly, for example, to reduce cost and/or optical losses or for other reasons. For example, the light consolidating element **2116** may be omitted in certain embodiments. In such embodiments, light may be incoupled from the input coupling element **2111** (e.g., after being reflected from the eye **210**) and directly coupled to the outcoupling optical element **2120**. The light may propagate through the eyepiece **950** between the input coupling element **2111** and the outcoupling optical element **2120**. Other configurations are possible. A camera is disposed with respect to the out-coupling optical element **2120** to receive light therefrom. The out-coupling optical element **2120** is configured to direct light received from the light consolidating element **2116** to the camera for capturing an image.

[0249] FIG. 24 also shows incoupling optical element **2104**, a light distributing element **2108**, and an image content out-coupling optical element **2110** disposed on the waveguide **2102**. The incoupling optical element **2104** may be configured to couple light received from an image projector into the waveguide **2102**. The light distribution element **2108** may be configured to redirect light received from the incoupling optical element **2104** to the out-coupling optical element **2110**, additionally increasing the spatial extent of the light as discussed above. The out-coupling optical element **2110** may be configured to couple light guided within the waveguide **2102** out of

the waveguide and direct such light to the eye for viewing image content from the projector.

[0250] In various implementations one or more of these optical elements **2111**, **2116**, **2120**, **2110**, **2108**, **2104** may be disposed within or on a waveguide **2102**. Similarly, as discussed above, one or more of these optical elements **2111**, **2116**, **2120**, **2110**, **2108**, **2104** may comprise diffractive optical elements.

[0251] In the implementation illustrated in FIG. **24**, the coupling optical element (e.g., coupling grating) **2111** may be displaced lateral from the out-coupling optical element **2110** on the waveguide **2102**. In the implementation shown, a space laterally separates the coupling optical element **2111** from the out-coupling optical element **2110**.

[0252] FIG. **25** shows another similar implementations wherein the coupling optical element (e.g., coupling grating) **2111** is displaced lateral from the out-coupling optical element **2110** on the waveguide **2102**. In the implementation shown in FIG. **25**, however, a space does not laterally separate the coupling optical element **2111** from the out-coupling optical element **2110**.

[0253] Having the coupling optical element (e.g., coupling grating) **2111** is displaced lateral from the out-coupling optical element **2110** on the waveguide **2102** can enable the coupling optical element to include optical power, for example, that collimates light received from an anterior surface of the eye (e.g., corneal surface) such that this optical power does not affect the propagation of light from and/or through the out-coupling optical element **2110** to the eye. Images presented to the eye from the image projector as well as the view of the environment in front of the user and the head mounted display, need not therefore be affected (e.g., distorted or defocused, etc.) by the optical power of the coupling optical element **2111**.

[0254] FIG. **26** illustrates an implementation of an imaging system **900** configured to image multiple portions of the eye. For example, an imaging system **900** such as shown in FIG. **26** may be configured to image both anterior surfaces of the eye (e.g., corneal surfaces) as well as the retina. The imaging system **900** includes a pair of incoupling optical elements, a first incoupling optical element **2111a** and a second incoupling optical element disposed on the waveguide **2102** of the eyepiece. The imaging system **900** additionally includes a pair of light consolidating elements, a first light consolidating optical element **2116a** and a second light consolidating element **2116b** disposed on the waveguide **2102**. In certain configurations, fewer optical elements may be used, possibly, for example, to reduce cost and/or optical losses or for other reasons. For example, the light consolidating elements **2116a**, **2116b** may be omitted in certain embodiments. In such embodiments, light may be incoupled from the first and second input coupling elements **2111a**, **2111b** (e.g., after being reflected from portions the eye **210** such as the retina and/or cornea) and directly coupled to corresponding first and second outcoupling optical elements **2120a**, **2120b**. The light may propagate through the eyepiece **950** (e.g., via a waveguide such as the waveguide **2102**) between the first and second input coupling elements **2111a**, **2111b** and the corresponding outcoupling optical elements **2120a**, **2120b**. Other configurations are possible. In addition, the imaging system **900** additionally includes a pair of light out-coupling optical elements, a first out-coupling optical element **2120a** and a second out-coupling optical element **2120b** disposed on the waveguide **2102**.

[0255] The first coupling optical element **2111a** is configured to couple light incident thereon into the waveguide **2102**. The first light consolidating element **2116a** is disposed to receive light coupled into the waveguide **2102** by the first coupling element **2111a**. The first light consolidating element **2116a** is configured to redirect light incident thereon from the first coupling optical element **2111a** to the first out-coupling optical element **2120a**. The first light consolidating element **2116a** is also configured to reduce the lateral spatial extent of light (e.g., the light beam) from the first coupling element **2111a** prior to reaching the first out-coupling optical element **2120a**. A camera is disposed with respect to the first out-coupling optical element **2120a** to receive light therefrom. Although the camera is not shown in FIG. **26**, an area corresponding to the detection area **2130** of the camera is shown. The first out-coupling optical element **2120a** is configured to

direct light received from the first light consolidating element **2116a** to the camera and, in particular, to the detection area **2130** shown in FIG. **26** for capturing an image.

[0256] Likewise, the second coupling optical element **2111b** is configured to couple light incident thereon into the waveguide **2102**. The second light consolidating element **2116b** is disposed to receive light coupled into the waveguide **2102** by the second coupling element **2111b**. The second light consolidating element **2116b** is configured to redirect light incident thereon from the second coupling optical element **2111b** to the second out-coupling optical element **2120b**. The second light consolidating element **2116b** is also configured to reduce the lateral spatial extent of light (e.g., the light beam) from the second coupling element **2111a** prior to reaching the second out-coupling optical element **2120a**. A camera is disposed with respect to the second out-coupling optical element **2120b** to receive light therefrom. Although the camera is not shown in FIG. **26**, an area corresponding to the detection area **2130** of the camera is shown. The second out-coupling optical element **2120b** is configured to direct light received from the second light consolidating element **2116b** to the camera and, in particular, to the detection area **2130** shown in FIG. **26** for capturing an image.

[0257] FIG. **26** also shows incoupling optical element **2104**, a light distributing element **2108**, and an image content out-coupling optical element **2110** disposed on the waveguide **2102**. The incoupling optical element **2104** may be configured to couple light received from an image projector into the waveguide **2102**. The light distribution element **2108** may be configured to redirect light received from the incoupling optical element **2104** to the out-coupling optical element **2110**, additionally increasing the spatial extent of the light as discussed above. The out-coupling optical element **2110** may be configured to couple light guided within the waveguide **2102** out of the waveguide and direct such light to the eye for viewing image content from the projector.

[0258] In the implementation illustrated in FIG. **26**, the first and second coupling optical elements (e.g., coupling gratings) **2111a**, **2111b** are displaced lateral from the out-coupling optical element **2110** on the waveguide **2102**. In the implementation shown, a space laterally separates the first and second coupling optical elements **2111a**, **2111b** from the out-coupling optical element **2110**.

Furthermore, in the example of FIG. **26**, the first and second coupling optical elements **2111a**, **2111b** are displaced lateral from each other on the waveguide **2102**. In other implementations, two or more of the first coupling optical element (e.g., coupling grating) **2111a**, the second coupling optical element **2111b**, and the out-coupling optical element **2110** need not be displaced laterally from each other on the waveguide **2102**.

[0259] In various implementations one or more of these optical elements **2111a**, **2111b**, **2116a**, **2116b**, **2120a**, **2120b**, **2110**, **2108**, **2104** may be disposed within or on a waveguide **2102**. Similarly, as discussed above, one or more of these optical elements **2111a**, **2111b**, **2116a**, **2116b**, **2120a**, **2120b**, **2110**, **2108**, **2104** may comprise diffractive optical elements.

[0260] The imaging system **900** of FIG. **26** can be configured to image multiple portions of the eye. For example, an imaging system **900** may be configured to image both anterior surfaces of the eye (e.g., corneal surfaces) as well as the retina. The first incoupling optical element **2111a**, may for example have optical power or have a lens disposed in front thereof with optical power. The first coupling optical element **2111a**, may for example comprise a diffractive optical element configured to couple light into the waveguide **2102** but also configured to impart optical power thereto.

Additionally or alternatively, a lens having optical power may be disposed in front of the first coupling optical element **2111a**. The optical power may be configured to alter the propagation of light received by the first incoupling optical element **2111a** such that a particular portion of the eye may be imaged. In some examples, the optical power may be positive optical power. Moreover, the optical power may be such that an anterior surface of the eye may be imaged. The optical power may, for example, correspond to a focal length of between about 15 to 25 mm (e.g., about 20 mm). As a result, light reflected from an anterior surface of the eye, which may be about 15 to 25 mm (e.g., about 20 mm) from the first coupling optical element **2111a** may be collimated and coupled

into the waveguide.

[0261] In contrast, in various implementations, the second coupling optical element **2111b** may neither have optical power nor include a lens disposed in front thereof. The lack of optical power associated with the second coupling optical element **2111b** will result in light from the anterior portion of the eye (e.g., corneal surfaces) not being collimated and not being imaged by the camera. However, light reflected from the retina may upon passing through the natural lens of the eye of the user be collimated. This light collimated by the natural lens of the eye may be coupled into the waveguide **2102** by the second coupling optical element **2111b** and imaged by the camera. In this manner, light collected by the first coupling optical element **2111a** may image an anterior surface of the eye (e.g., a corneal surface of the eye) and the second coupling optical element **2111b** may image the retina of the eye of the user. In some implementations, such a configuration enables light collected by the first coupling optical element **2111a** to form images of glint on the eye, for example, on image an anterior surface of the eye (e.g., a corneal surface of the eye). The second coupling optical element **2111b** may image the retina of the eye of the user as discussed above. In some examples, the second coupling optical element **2111b** and/or a lens disposed in front thereof may have some amount of net optical power (e.g., a non-zero amount of net optical power) that is weaker than that of the first coupling optical element **2111a** and/or a lens disposed in front of the first coupling optical element **2111a**.

[0262] In some implementations, the images formed by light collected by the first coupling optical element **2111a** are next to (e.g., not superimposed over) images formed by light collected by the second coupling optical element **2111b**. For example, images of the anterior surface(s) of the user's eye (e.g., cornea) may be formed next to (e.g., not superimposed over) images of the retina.

[0263] Polarization techniques can be used to attenuate or remove light from the anterior surfaces (e.g., corneal surfaces) from affecting images formed by light collected by the second coupling optical element **2111b**. For example, the eye can be illuminated with polarized light having a first polarization and the camera can form an image using light from second out-coupling optical element **2120b** using light of a second different polarization. For example, the second out-coupling optical element **2111b** may be a polarization selective coupling element that selectively couple out light of the second polarization different than the first polarization. Additionally or alternatively, a polarizer **2140** that filters out the first polarization (e.g., selectively transmits the second polarization) may be included between the second out-coupling optical element **2120b** and the camera **920** as illustrated in FIG. 27, which is a cross-section through the waveguide **950**, **2102**, consolidating optical elements **2116a**, **2116b**, and out-coupling optical elements **2120a**, **2120b** shown in FIG. 26.

[0264] Such a configuration may be used to reduce unwanted reflections (e.g., glint), such as from the cornea when imaging the retina. Reflection from the cornea will be specular. Accordingly, if light of the first polarization is incident on the cornea, the light reflected from the cornea will retain that first polarization. In contrast, the retina is diffuse. If light of the first polarization is incident on the retina, the light reflected from the retina does not retain solely the first polarization. The diffuse reflection more likely results in unpolarized light. Accordingly, the second polarization, different from the first polarization will be present in the light reflected from the retina. As a result, by forming images with light coupled out of the second out-coupling optical element **2120b** using light of the second polarization, images of the retina will be obtained while images of the cornea or glint will be suppressed. Likewise, by illuminating with a first polarization and imaging with a second different polarization, the retina can be image with reduced glare from the cornea.

[0265] Accordingly, in various implementations, polarization specific optical filters or polarization selective optical element (e.g. coupling gratings) may be used to reduce unwanted reflected light from the eye **210** (e.g., from the cornea). For example, unwanted light, glare, or glint may be reflected off the cornea that may saturate an image captured by the camera. As discussed above, light reflected from the cornea may be specular and maintain its polarization. By contrast, light

reflected off the retina may be more diffusely reflected and may be less homogeneously polarized. Likewise, a combination of polarizers may be used to remove some or most of the unwanted light reflected from the cornea. Initially polarized light can be used for illuminating the eye of the user. In some designs, a polarized illumination source (e.g., the light source) may be used. Additionally or alternatively, a first polarizer (e.g., a polarization specific optical filter or a polarization selective optical coupling element coupling illumination light into an illumination waveguide) may be positioned at the beginning of the optical path of the illumination source to provide initial polarization of the light to the eye. A second polarizer (e.g., a polarization specific optical filter or polarization selective coupling element) may be positioned at the optical path before the light enters the camera. The second polarizer may be rotated at 90° from the first polarizer (e.g. the polarizers may be “crossed”). As a result, the eye will be illuminated with the first polarization with some light of the first polarization reflected from the cornea. This light will not pass through the crossed polarizer (that preferentially passes light of the second polarization) located proximal the camera. However, light reflected from the retina will include the second polarization. Likewise, light diffusely reflected from the retina will pass through the polarizer **2140** proximal the camera and will enable an image of the retina to be captured by the camera. Thus, in such configurations, unwanted light received from the eye (e.g., from cornea) and entering the camera may be reduced or eliminated from the image captures using light from the second coupling optical element **2111b**. Other configurations are possible. For example, a polarization selective coupling elements **2111b** and/or a polarization selective out-coupling optical elements **2120b** may be used in addition or in alternative to polarizers such as the polarizer **2140** proximal the camera. The effect may again be to reduce or remove unwanted light received from the eye (e.g., from cornea) before entering the imaging device **920**.

[0266] As illustrated in FIG. **27**, in various implementations, such polarizers are not used in an optical path from the first coupling optical element **2111a** and the camera or between the first out-coupling optical element **2120a** and the camera. As a result, images of the cornea and glint may be obtained from light coupled by the first coupling optical element **2111a** into the waveguide and/or light coupled out of the waveguide from the first out-coupling optical element **2120a**. As discussed above, this first coupling optical element **2111a** may have optical power or a lens associated therewith that is specifically used to image the cornea and/or glint. Likewise, polarization selective coupling optical elements **2111a** or polarization selective out-coupling optical element **2120a** that filter out light of the first polarization would not be used as the first coupling optical element **2111a** and out-coupling optical element **2120a**, respectively. Additionally, polarizers **2140** between the coupling optical element **2111a** and the camera **920** or between the out-coupling optical element **2111a** and the camera **920** that filter out light of the first polarization would not be used.

[0267] A wide variety of variations are possible. For example, although the first and second out-coupling optical elements **2120a**, **2120b** are described above as coupling light and forming images on a single camera (e.g., a single detection area **2130**), in other implementations, the first and second out-coupling optical elements **2120a**, **2120b** can coupling light and forming images on respective first and second cameras. Other variations are possible.

[0268] In some implementations, one or more of the eyepieces described above (e.g., the eyepiece **950**) with reference to FIGS. **24-27** may be dedicated imaging eyepiece layer (e.g., omitting the incoupling optical element **2104**, the light distributing element **2108**, and/or the output coupling element **2110**). In such implementations, the imaging eyepiece layer may be included as a layer in a stack of waveguides. The one or more other layers in the stack of waveguides may include the incoupling optical element **2104**, the light distributing element **2108**, and/or the output coupling element **2110**.

[0269] In some embodiments, the dedicated imaging eyepiece layer can be configured to capture images of the environment. In some such embodiments, the imaging eyepiece layer may be disposed most proximal to the environment when installed in the head-mounted display. In some

such configurations, the dedicated imaging eyepiece layer may be the outermost layer in the waveguide stack such that it is positioned between the other layers (e.g., waveguides) and the environment. In some embodiments, the dedicated imaging eyepiece layer can be configured to capture images of the user's eye **210**. In some such embodiments, the imaging eyepiece layer may be disposed most proximal to the user when installed in the head-mounted display. In some implementations, the dedicated imaging eyepiece layer may be the innermost layer in the waveguide stack such that it is positioned between the other layers (e.g., waveguides) and the user. Other configurations are possible.

[0270] In certain embodiments, the first and second coupling elements **211a**, **211b** may be laterally aligned but displaced in depth (e.g., along the z-axis or into the page of FIG. **26**). For example, in such embodiments, the first and second coupling elements **211a**, **211b** may be positioned on opposite sides of the same waveguide. In certain embodiments, the first input coupling element **211a** may be disposed on or within a first waveguide and the second input coupling element **211b**. Additionally or alternatively, the first and second light consolidating elements **2116a**, **2116b** and/or the first and second outcoupling optical elements **2120a**, **2120b** may be disposed on opposite sides of the same waveguide and/or may be disposed on or in corresponding separate waveguides.

[0271] One or more of the coupling optical elements **211**, **211a**, **211b** described above with reference to FIGS. **24-27** may be wavelength-selective such that the optical elements are configured to interact only with a certain wavelength or band of wavelengths. The wavelength or band of wavelengths may include invisible light (e.g., infrared light, or a specific band thereof). In some implementations, the first input coupling element **211a** may be configured to operate on a wavelength lower than that for the second input coupling element **211b** (or vice versa). For example, the first coupling optical element **211a** may be configured to interact with about 800 nm light, and/or the second coupling optical element **211b** may be configured to interact with about 950 nm light (or vice versa). Optical filters may also be used to effectuate similar wavelength selection. In various implementations, therefore, light coupled into the waveguide by the first coupling optical element that reaches the at least one can be of a different wavelength than light coupled into the waveguide by the second optical element that reaches the at least one camera. Other configurations are possible.

[0272] In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than restrictive sense.

[0273] Indeed, it will be appreciated that the systems and methods of the disclosure each have several innovative aspects, no single one of which is solely responsible or required for the desirable attributes disclosed herein. The various features and processes described above may be used independently of one another, or may be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this disclosure.

[0274] Certain features that are described in this specification in the context of separate embodiments also may be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment also may be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially exemplified as such, one or more features from an exemplified combination may in some cases be excised from the combination, and the exemplified combination may be directed to a subcombination or variation of a subcombination. No single feature or group of features is necessary or indispensable to each and every embodiment.

[0275] It will be appreciated that conditional language used herein, such as, among others, “can,”

“could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. In addition, the articles “a,” “an,” and “the” as used in this application and the appended examples are to be construed to mean “one or more” or “at least one” unless specified otherwise. Similarly, while operations may be depicted in the drawings in a particular order, it is to be recognized that such operations need not be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Further, the drawings may schematically depict one more example processes in the form of a flowchart. However, other operations that are not depicted may be incorporated in the example methods and processes that are schematically illustrated. For example, one or more additional operations may be performed before, after, simultaneously, or between any of the illustrated operations. Additionally, the operations may be rearranged or reordered in other embodiments. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products. Additionally, other embodiments are within the scope of the following examples. In some cases, the actions recited in the examples may be performed in a different order and still achieve desirable results.

[0276] Accordingly, the disclosure are not intended to be limited to the embodiments shown herein, but are to be accorded the widest scope consistent with this disclosure, the principles and the novel features disclosed herein. A variety of example systems and methods are provided below.

EXAMPLES

Example Section I

[0277] 1. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user, said head-mounted display system comprising: [0278] a frame configured to be supported on a head of the user; [0279] an image projector configured to project images into the user's eye to display image content in the vision field of the user; [0280] a camera; [0281] at least one waveguide; [0282] at least one coupling optical element configured such that light is coupled into said waveguide and guided therein; and [0283] at least one out-coupling element configured to couple light guided within said waveguide out of said waveguide and direct said light to said camera, [0284] wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light that is coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element such that images may be captured by said camera.

[0285] 2. The system of Example 1, wherein said at least one coupling optical element is configured such that light from the environment in front of the user wearing the head mounted display system is coupled into said at least one waveguide and guided therein such that images of said environment may be captured by said camera.

[0286] 3. The system of any of the Examples above, wherein said at least one coupling optical

element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said at least one waveguide and guided therein such that images of said eye may be captured by said camera.

[0287] 4. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera, said system configured to image an anterior portion of said eye.

[0288] 5. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera, said system configured to image a corneal surface of said eye.

[0289] 6. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera, said system configured to image the retina of said user's eye.

[0290] 7. The system of any of the Examples above, further comprising an eyepiece disposed on the frame, said eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from an environment in front of the user to the user's eye to provide a view of the environment in front of the user.

[0291] 8. The system of Example 7, wherein said eyepiece is configured to receive light from said image projector and to direct said light into said user's eye to display augmented reality image content to the user's vision field.

[0292] 9. The system of any of Examples 7-8, wherein said eyepiece comprises said at least one waveguide.

[0293] 10. The system of any of Examples 7-9, wherein said image projector is configured to direct light into an edge of said eyepiece.

[0294] 11. The system of Examples 9 or 10, wherein said image projector is configured to direct light into an edge of said at least one waveguide.

[0295] 12. The system of any of the Examples above, further comprising at least one in-coupling optical element configured to in-couple light from said image projector into said at least one waveguide so as to guide light from said image projector for providing said image content to said user's eye.

[0296] 13. The system of any of the Examples above, wherein said at least one coupling optical element is also configured to couple light from said image projector guided within said waveguide out of said at least one waveguide such that image content can be viewed by the user's eye.

[0297] 14. The system of any of the Examples above, wherein the same coupling optical element is configured to couple light from said image projector guided within said waveguide out of said waveguide such that image content can be viewed by the user's eye and to couple light into said at least one waveguide to be guided therein to said camera.

[0298] 15. The system of any of Examples 1 to 12, further comprising at least one image content out-coupling optical element configured to couple light from said image projector guided within said waveguide out of said at least one waveguide such that image content can be viewed by the user's eye.

[0299] 16. The system of any of the Examples above, wherein said at least one coupling optical element faces the eye of the user wearing the head mounted imaging system to receive light from said eye.

[0300] 17. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light from the environment in front of the user wearing the head

mounted imaging system is coupled into said at least one waveguide and guided therein such that images of said environment may be captured by said camera.

[0301] 18. The system of any of the Examples above, wherein said at least one coupling optical element faces the environment in front of the user wearing the head mounted imaging system to receive light from said environment.

[0302] 19. The system of Example 15, wherein said at least one image content out-coupling optical element configured to couple light from said image projector guided within said waveguide out of said at least one waveguide and said at least one coupling optical element configured such that light is coupled into said waveguide and guided therein to said camera are superimposed on each other.

[0303] 20. The system of Example 15, wherein said at least one image content out-coupling optical element configured to couple light from said image projector guided within said waveguide out of said at least one waveguide and said at least one coupling optical element configured such that light is coupled into said waveguide and guided therein to said camera are stacked over the other.

[0304] 21. The system of Example 15, wherein said at least one image content out-coupling optical element configured to couple light from said image projector guided within said waveguide out of said at least one waveguide and said at least one coupling optical element configured such that light is coupled into said waveguide and guided therein to said camera are integrated in the same diffractive optical element.

[0305] 22. The system of Example 15, wherein said at least one coupling optical element is configured such that light is coupled into a first waveguide and guided therein to said camera and said at least one image content out-coupling optical element is configured to couple light from said image projector guided within a second waveguide out of said second waveguide.

[0306] 23. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light is coupled into a first waveguide and guided therein to said camera and said image projector is configured to couple light into a second waveguide to provide image content to said eye.

[0307] 24. The system of any of the Examples above, wherein said image projector comprises a light source, a modulator, and projection optics.

[0308] 25. The system of any of the Examples above, wherein the image projector comprises scanning optical fiber.

[0309] 26. The system of any of Examples 24 or 25, wherein the modulator comprises a light modulator.

[0310] 27. The system of Example 26, wherein the light modulator comprises a spatial light modulator.

[0311] 28. The system of any of the Examples above, wherein said camera comprises a detector array and imaging optics.

[0312] 29. The system of Example 28, wherein said imaging optics is configured to focus collimated light onto said detector array.

[0313] 30. The system of any of the Examples above, wherein said at least one waveguide comprises material that is transparent to visible light having a refractive index sufficient to guide light in said waveguide by total internal reflection.

[0314] 31. The system of any of the Examples above, wherein said at least one waveguide comprises a stack of waveguides.

[0315] 32. The system of Example 31, wherein different waveguides of the stack of waveguides are configured to output light with different wavefront divergence as if projected from different distances from the user's eye.

[0316] 33. The system of Example 31 or 32, wherein different waveguides of the stack of waveguides are configured to output light with different colors.

[0317] 34. The system of any of Examples 31, 32, or 33, wherein different waveguides comprise first, second, and third waveguides, said system is configured such that the first is for red color

light, the second for is green color light, and the third is for blue color light.

[0318] 35. The system of any of the Examples 12 to 34, wherein the in-coupling optical element comprises a diffractive optical element or reflector.

[0319] 36. The system of any of the Examples 12 to 34, wherein the in-coupling optical element comprises a diffractive optical element.

[0320] 37. The system of any of the Examples above, wherein the coupling optical element comprises a diffractive optical element.

[0321] 38. The system of any of the Examples above, wherein the coupling optical element comprises liquid crystal.

[0322] 39. The system of any of the Examples above, wherein the coupling optical element comprises a liquid crystal polarization grating.

[0323] 40. The system of any of the Examples above, wherein the out-coupling optical element comprises a diffractive optical element.

[0324] 41. The system of any of the Examples above, wherein the coupling optical element comprises liquid crystal.

[0325] 42. The system of any of the Examples above, wherein the coupling optical element comprises a liquid crystal polarization grating.

[0326] 43. The system of any of the Examples above, wherein the coupling element is configured to increase a dimension of the eyepiece along at least one axis.

[0327] 44. The system of Example 43, further comprising an orthogonal pupil expander comprising at least one light redirecting element in or on said at least one waveguide that is configured to increase a dimension of an eyepiece along an axis that is orthogonal to the at least one axis.

[0328] 45. The system of Example 44, wherein said at least one light redirecting element comprises a diffractive optical element.

[0329] 46. The system of any of the Examples above, wherein the same coupling element is configured to (a) couple light into said at least one waveguide to be received by said camera and to (b) couple light from said image projector out from said at least one waveguide to said user's eye.

[0330] 47. The system of any of the Examples above, wherein the same coupling element is configured to (a) couple light from said environment into said at least one waveguide to be received by said camera and to (b) couple light from said image projector out from said at least one waveguide to said user's eye.

[0331] 48. The system of any of the Examples above, wherein the same coupling element is configured to (a) couple light from said eye into said at least one waveguide to be received by said camera and to (b) couple light from said image projector out from said at least one waveguide to said user's eye.

[0332] 49. The system of any of the above Examples, further comprising a reflective surface having optical power disposed to receive light reflected from the user's eye that passes through said eyepiece and to direct said light back to said eyepiece.

[0333] 50. The system of Example 49, wherein said at least one coupling element is configured such that light from the user's eye that passes through the at least one waveguide and is reflected from the reflective surface back to the at least one waveguide is coupled into said at least one waveguide and guided therein.

[0334] 51. The system of any of Examples 49 to 50, wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the user's eye that is reflected from the reflective surface and coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element.

[0335] 52. The system of any of Examples 49 to 51, wherein the reflective surface reflects infrared light but transmits visible light.

[0336] 53. The system of any of Examples 49 to 52, wherein the reflective surface is curved.

[0337] 54. The system of any of Examples 49 to 53, wherein the reflective surface is disposed on a curved optical element.

[0338] 55. The system of any of Examples 49 to 54, wherein the reflective surface is disposed on a concave mirror.

[0339] 56. The system of any of Examples 49 to 55, wherein the reflective surface has positive optical power in reflection and negligible optical power in transmission.

[0340] 57. The system any of Examples 49 to 56, wherein the reflective surface is configured to collimated light from the user's eye.

[0341] 58. The system of any of Examples 49 to 57, wherein the reflective surface is configured to collimate light from the retina of the user's eye.

[0342] 59. The system of any of Examples 49 to 58, wherein the reflective surface is configured to collimate light from an anterior region of the user's eye.

[0343] 60. The system of any of Examples 49 to 59, wherein the reflective surface is configured to collimate light from the cornea of the user's eye.

[0344] 61. The system of any of Examples 49 to 60, wherein the reflective surface is formed on a curved optical element and comprises an infrared reflective coating.

[0345] 62. The system of Example 61, wherein the curved optical element has negligible power for light transmitted therethrough.

[0346] 63. The system of Example 61 or 62, wherein the curved optical element has first and second curved surfaces on opposite sides of the curved optical element, said first and second curved surfaces having the same curvature.

[0347] 64. The system of any of Examples 49 to 63, further comprising a retarder disposed with respect to the reflective surface and the coupling optical element so as to rotate the polarization of light passing through the at least one waveguide and reflected from the reflective surface back to the at least one waveguide and the coupling optical element.

[0348] 65. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization selective turning element.

[0349] 66 The system of any of the Examples above, wherein the at least one coupling element comprises a polarization grating.

[0350] 67. The system of any of the Examples above, wherein the at least one coupling element is configured to turn light guided within the at least one waveguide out of the waveguide to the eye as collimated light directed to the eye of the user.

[0351] 68. The system of any of the Examples above, wherein the at least one coupling element is configured to turn collimated light from the reflective surface into the at least one waveguide.

[0352] 69. The system of any of the Examples above, wherein the at least one out-coupling element comprises an off-axis reflector.

[0353] 70. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization selective turning element.

[0354] 71. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization grating.

[0355] 72. The system of any of the Examples above, wherein the at least one out-coupling element comprises liquid crystal.

[0356] 73. The system of any of the Examples above, wherein the at least one out-coupling element comprises a liquid crystal polarization grating.

[0357] 74. The system of any of the Examples above, further comprising a circular polarizer.

[0358] 75. The system of any of the Examples above, wherein the in-coupling element comprises a polarization selective turning element.

[0359] 76. The system of any of the Examples above, wherein the in-coupling element comprises a polarization grating.

[0360] 77. The system of any of the Examples above, wherein the at least one in-coupling element

comprises a diffractive optical element.

[0361] 78. The system of any of the Examples above, wherein the at least one in-coupling element comprises a diffraction grating.

[0362] 79. The system of any of the Examples above, wherein the in-coupling element comprises an off-axis reflector.

[0363] 80. The system of any of Examples 49 to 79, wherein the reflective surface comprises a liquid crystal reflector.

[0364] 81. The system of any of Examples 49 to 80, wherein the reflective surface comprises a cholesteric liquid crystal reflective lens.

[0365] 82. The system of any of the Examples above, wherein the same waveguide (a) guides light coupled from the user's eye into said at least one waveguide to be received by said camera so as to capture an image of at least a portion of the eye of the user, and (b) guides light coupled from said image projector such that light from said projector can be directed to said user's eye such that said image from said image projector is in the vision field of said the user.

[0366] 83. The system of any of the Examples above, wherein the same coupling element (a) couples light from said user's eye into said at least one waveguide to be received by said camera and (b) couples light from said image projector out from said at least one waveguide to said user's eye.

[0367] 84. The system of any of Examples 49 to 83, further comprising electronics configured to cause the camera to capture a first image when light reflected from the reflective surface is blocked.

[0368] 85. The system of Example 84, wherein said electronics is configured to cause the camera to capture a second image when light reflected from the reflective surface is not blocked.

[0369] 86. The system of Example 85, wherein said electronics is configured to use the first image to modify the second image.

[0370] 87. The system of Examples 85 or 86, wherein said electronics is configured to subtract from the second image based on the first image.

[0371] 88. The system of any of the Examples above, wherein said system is configured to perform eye tracking based images of said eye.

[0372] 89. The system of Example 88, wherein performing eye tracking based on said images of said eye comprises storing an image of the retina of said eye.

[0373] 90. The system of any of any of the Examples above, wherein said system is configured to:

[0374] obtain an image of a portion of said retina of said eye using said camera; [0375] compare one or more stored images of said retina with the image of said portion of said retina; and [0376] determine a gaze of the user based on the comparison of the one or more stored images and the image of the portion of the retina obtained from the camera.

[0377] 91. The system of Example 90, wherein determining a gaze of the user comprises determining to which portion of the retina corresponds to the image of said portion of the retina.

[0378] 92. The system of any of Examples 90 to 91, wherein determining a gaze of the user comprises determining an orientation of the eye.

[0379] 93. The system of any of the Examples above, wherein said system is configured to obtain biometric data based on one or more images of the user's eye obtained with said camera.

[0380] 94. The system of any of the Examples above, wherein said system is configured to identify the user via biometric sensing based on one or more images of said eye obtained with said camera.

[0381] 95. The system of any of the above Examples, wherein said system is configured to provide illumination of a first polarization and to preferentially capture images with said camera using light of a second polarization different than said first polarization.

[0382] 96. The system of any of the above Examples, wherein said system is configured to illuminate said user's eye with light of a first polarization and to preferentially capture images of said user's eye with said camera using light of a second polarization different than said first

polarization.

[0383] 97. The system of Examples 95 or 96, wherein said first and second polarizations are orthogonal.

[0384] 98. The system of any of the above Examples, further comprising a light source disposed so as to provide illumination so as to capture images with said camera.

[0385] 99. The system of any of the above Examples, further comprising a light source disposed so as to illuminate of the user's eye.

[0386] 100. The system of Examples 98 or 99, wherein said light source comprises one or more infrared light sources.

[0387] 101. The system of any of Examples 98 to 100, wherein said light source comprises one or more infrared light emitting diodes (LEDs).

[0388] 102. The system of any of Examples 98 to 101, wherein said light source is pulsed.

[0389] 103. The system of any of Examples 98 to 102 further comprising an off-axis reflector disposed to receive light from said light source and illuminate said user's eye with said light.

[0390] 104. The system of any of Examples 98 to 103, wherein said light source is configured to input light into a waveguide to provide said illumination.

[0391] 105. The system of any of Examples 98 to 104, wherein said light source is configured to input light into a waveguide disposed with respect to said eye to provide illumination to said eye.

[0392] 106. The system of Examples 104 or 105, further comprising an illumination in-coupling optical element configured to couple light from said light source into said waveguide.

[0393] 107. The system of any of Examples 98 to 103, wherein said light source is configured to input light into said at least one waveguide to provide illumination.

[0394] 108. The system of Example 107, further comprising an illumination in-coupling optical element configured to couple light from said light source into said at least one waveguide to provide illumination.

[0395] 109. The system of any of Examples 98 to 103, wherein said light source is configured to input light into the same waveguide as used to project image content to the user's eye.

[0396] 110. The system of any of Examples 98 to 104, wherein said light source is configured, to provide illumination to the user's eye, to input light into the same waveguide as used to guide light to the camera.

[0397] 111. The system of any of Examples 98 to 105, wherein said light source is configured to input light into the same waveguide as used to guide light from the user's eye to the camera.

[0398] 112. The system of any of Examples 109 to 111, further comprising an illumination in-coupling optical element configured to couple light from said light source into said waveguide.

[0399] 113. The system of any of Examples 106, 108, or 112, wherein said illumination in-coupling optical element is polarization selective, in-coupling light of a first polarization.

[0400] 114. The system of Example 98 to 113, wherein said light source is a polarized light source configured to output polarized light having a first polarization.

[0401] 115. The system of any of Examples 98 to 114, wherein said light source is configured to direct polarized light having a first polarization onto said eye.

[0402] 116. The system of Example 98 to 115, further comprising an illumination polarizer having a first polarization disposed in the optical path between said light source and said eye to polarize light directed to said eye.

[0403] 117. The system of Example 116, wherein the illumination polarizer is disposed in the optical path between said light source and said waveguide configured to provide illumination.

[0404] 118. The system of any of Examples 98 to 117, further comprising an image acquisition polarizer in an optical path between said eye and said camera.

[0405] 119. The system of Example 118, wherein said image acquisition polarizer is proximal said camera.

[0406] 120. The system of Examples 118 or 119, wherein said image acquisition polarizer is

disposed in an optical path between (a) said at least one waveguide configured guide light to said camera and (b) said camera.

[0407] 121. The system of any of Examples 118 to 120, wherein said image acquisition polarizer reduces the amount of light said first polarization that reaches said camera.

[0408] 122. The system of Examples 118 to 121, wherein said image acquisition polarizer comprises a polarizer configured to selectively coupling light of a second polarization different than said first polarization to said camera.

[0409] 123. The system of any of the Examples above, further comprising at least one light consolidating element disposed in an optical path between said at least one coupling element and said at least one out-coupling optical element to reduce lateral spatial extent of light from said at least one coupling element prior to reaching said at least one out-coupling optical element.

[0410] 124. The system of any of the Examples above, wherein said at least one light consolidating element comprises a diffractive optical element.

[0411] 125. The system of any of the Examples above, wherein said at least one light consolidating element comprises a hologram or diffraction grating.

[0412] 126. The system of any of the Examples above, wherein said at least one waveguide comprises material that is transparent to infrared light having a refractive index sufficient to guide infrared light in said waveguide by total internal reflection.

[0413] 127. The system of any of the Examples above, wherein said at least one coupling optical element comprises an exit pupil expander.

[0414] 128. The system of any of the Examples above, wherein the system includes optical power to increase collimation of light reflected from the eye that is coupled into the waveguide to be guided to the camera.

[0415] 129. The system of any of the Examples above, wherein the system includes optical power to increase collimation of light reflected from an anterior portion of the eye that is coupled into the waveguide to be guided to the camera.

[0416] 130. The system of any of the Examples above, wherein the system includes optical power to increase collimation of light reflected from the cornea of the eye that is coupled into the waveguide to be guided to the camera.

[0417] 131. The system of any of Examples 128 to 130, wherein the optical power comprises positive optical power.

[0418] 132. The system of any of Examples 128 to 131, wherein the optical power is provided by a lens.

[0419] 133. The system of any of Examples 88 to 132, wherein the one or more stored images of the retina of the eye comprise a composite image of the retina of the eye generated using a plurality of images of different portions of the retina of the eye.

[0420] 134. The system of any of Examples 88 to 133, wherein the composite image of the retina comprises a plurality of images of the retina stitched together.

[0421] 135. The system of any of Examples 88 to 134, wherein the plurality of images of the retina stitched together comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0422] 136. The system of any of Examples 88 to 135, wherein the one or more stored images of the retina comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0423] 137. The system of any of Examples 88 to 136, wherein the system is further configured to use the obtained image of the portion of the retina of the eye to update the composite image.

[0424] 138. The system of any of Examples 88 to 137, wherein using the obtained image of the portion of the retina to update the composite image of the retina comprises stitching the obtained image into a section of the composite image corresponding to the portion of the retina shown in the obtained image.

[0425] 139. The system of any of Examples 88 to 138, wherein the system is further configured to apply a digital filter to the obtained image of the portion of the retina of the eye to obtain a filtered image of the portion of the retina.

[0426] 140. The system of Examples 139, wherein the system is further configured to compare one or more stored images of the retina with the filtered image of the portion of the retina.

[0427] 141. The system of any of Examples 139 to 140, wherein the digital filter comprises a Frangi Filter.

[0428] 142. The system of any of Examples 88 to 139, wherein the system is configured to apply edge enhance the obtained image of the portion of the retina.

[0429] 143. The system of any of the Examples above, wherein said system is configured to perform user identification verification using images of the retina.

[0430] 144. The system of any of the Examples above, wherein said system is configured to:

[0431] obtain an image of a portion of said retina of said eye using said camera; [0432] compare one or more stored images of said retina with the image of said portion of said retina.

[0433] 145. The system of Example 144, wherein the one or more stored images of the retina of the eye comprise a composite image of the retina of the eye generated using a plurality of images of different portions of the retina of the eye.

[0434] 146. The system of any of Examples 144 to 145, wherein the composite image of the retina comprises a plurality of images of the retina stitched together.

[0435] 147. The system of any of Examples 144 to 146, wherein the plurality of images of the retina stitched together comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0436] 148. The system of any of Examples 144 to 146, wherein the one or more stored images of the retina comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0437] 149. The system of any of Examples 144 to 148, wherein the system is further configured to use the obtained image of the portion of the retina of the eye to update the composite image.

[0438] 150. The system of any of Examples 144 to 149, wherein using the obtained image of the portion of the retina to update the composite image of the retina comprises stitching the obtained image into a section of the composite image corresponding to the portion of the retina shown in the obtained image.

[0439] 151. The system of any of Examples 144 to 150, wherein the system is further configured to apply a digital filter to the obtained image of the portion of the retina of the eye to obtain a filtered image of the portion of the retina.

[0440] 152. The system of Examples 151, wherein the system is further configured to compare one or more stored images of the retina with the filtered image of the portion of the retina.

[0441] 153. The system of any of Examples 144 to 152, wherein the digital filter comprises a Frangi Filter.

[0442] 154. The system of any of Examples 144 to 153, wherein the system is configured to apply edge enhance the obtained image of the portion of the retina.

Example Section II

[0443] 1. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user and to image at least a portion of an environment in front of the user wearing the head mounted display system, said head-mounted display system comprising: [0444] a frame configured to be supported on a head of the user; [0445] an image projector configured to project an image; [0446] a camera; and [0447] an eyepiece disposed on the frame, said eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from the environment in front of

the user to the user's eye to provide a view of the environment in front of the user, said eyepiece comprising: [0448] (a) at least one waveguide; [0449] (b) at least one in-coupling optical element configured to in-couple light from said image projector into said at least one waveguide so as to guide light from said image projector therein; [0450] (c) at least one coupling optical element configured to couple light from said image projector guided within said waveguide out of said waveguide and direct said light to the user's eye; and [0451] (d) at least one out-coupling element configured to couple light within said waveguide out of said waveguide and direct said light to said camera, [0452] wherein the image projector is disposed in an optical path with respect to said at least one in-coupling optical element to couple light from said image projector into said waveguide to be guided therein such that said light is coupled out from said waveguide by said at least one coupling element to said user's eye such that said image from said projector is in the vision field of said the user, [0453] wherein said coupling element is configured such that light from the environment in front of the user wearing the head mounted display is coupled into said waveguide and guided therein, [0454] wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the environment in front of the user that is coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element such that images of said environment may be captured by said camera, and [0455] wherein the same waveguide (a) guides light coupled from said environment into said waveguide to be received by said camera so as to capture an image of at least a portion of the environment in front of the user, and (b) guides light coupled from said projector such that light from said projector can be directed to said user's eye so that said image from said projector is in the vision field of said the user.

[0456] 2. The system of Example 1, wherein said image projector comprises a light source, a modulator, and projection optics.

[0457] 3. The system of Example 1 or 2, wherein the image projector comprises scanning optical fiber.

[0458] 4. The system of any of Examples 2 or 3, wherein the modulator comprises a light modulator.

[0459] 5. The system of Example 4, wherein the light modulator comprises a spatial light modulator.

[0460] 6. The system of any of the Examples above, wherein said camera comprises a detector array and imaging optics.

[0461] 7. The system of Example 6, wherein said imaging optics is configured to focus collimated light onto said detector array.

[0462] 8. The system of any of the Examples above, wherein said at least one waveguide comprises material that is transparent to visible light having a refractive index sufficient to guide light in said waveguide by total internal reflection.

[0463] 9 The system of any of the Examples above, wherein said at least one waveguide comprises a stack of waveguides.

[0464] 10. The system of Example 9, wherein different waveguides of the stack of waveguides are configured to output light with different wavefront divergence as if projected from different distances from the user's eye.

[0465] 11. The system of Example 9 or 10, wherein different waveguides of the stack of waveguides are configured to output light with different colors.

[0466] 12. The system of any of Examples 9, 10, or 11, wherein different waveguides comprise first, second, and third waveguides, said system is configured such that the first is for red color light, the second for is green color light, and the third is for blue color light.

[0467] 13. The system of any of the Examples above, wherein the in-coupling optical element comprises a diffractive optical element or reflector.

[0468] 14. The system of any of the Examples above, wherein the coupling optical element

comprises a diffractive optical element.

[0469] 15. The system of any of the Examples above, wherein the out-coupling optical element comprises a diffractive optical element.

[0470] 16. The system of any of the Examples above, wherein the coupling element is configured to increase a dimension of the eyebox along at least one axis.

[0471] 17. The system of Example 16, further comprising an orthogonal pupil expander comprising at least one light redirecting element in or on said at least one waveguide that is configured to increase a dimension of an eyebox along an axis that is orthogonal to the at least one axis.

[0472] 18. The system of Example 17, wherein said at least one light redirecting element comprises a diffractive optical element.

[0473] 19. The system of any of the Examples above, wherein the same coupling element (a) couples light from said environment into said at least one waveguide to be received by said camera and (b) couples light from said image projector out from said at least one waveguide to said user's eye.

[0474] 20. The system of any of the above Examples, further comprising a reflective surface having optical power disposed to receive light reflected from the user's eye that passes through said eyepiece and to direct said light back to said eyepiece.

[0475] 21. The system of Example 20, wherein said at least one coupling element is configured such that light from the user's eye that passes through the eyepiece and is reflected from the reflective surface back to the eyepiece is coupled into said waveguide and guided therein.

[0476] 22. The system of any of Examples 20 to 21, wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the user's eye that is reflected from the reflective surface and coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element.

[0477] 23 The system of any of Examples 20 to 22, wherein the reflective surface reflects infrared light but transmits visible light.

[0478] 24. The system of any of Examples 20 to 23, wherein the reflective surface is curved.

[0479] 25. The system of any of Examples 20 to 24, wherein the reflective surface is disposed on a curved optical element.

[0480] 26. The system of any of Examples 20 to 25, wherein the reflective surface is disposed on a concave mirror.

[0481] 27. The system of any of Examples 20 to 26, wherein the reflective surface has positive optical power in reflection and negligible optical power in transmission.

[0482] 28. The system any of Examples 20 to 27, wherein the reflective surface is configured to collimated light from the user's eye.

[0483] 29. The system of any of Examples 20 to 28, wherein the reflective surface is configured to collimate light from the retina of the user's eye.

[0484] 30. The system of any of Examples 20 to 29, wherein the reflective surface is configured to collimate light from an anterior region of the user's eye.

[0485] 31. The system of any of Examples 20 to 30, wherein the reflective surface is configured to collimate light from the cornea of the user's eye.

[0486] 32. The system of any of Examples 20 to 31, wherein the reflective surface is formed on a curved optical element having an infrared reflective coating on said reflective surface.

[0487] 33. The system of Example 33, wherein the curved optical element has negligible power for light transmitted therethrough.

[0488] 34. The system of Example 32 or 33, wherein the curved optical element has first and second curved surface on opposite sides of the curved optical element, said first and second curved surfaces having the same curvature.

[0489] 35. The system of any of the Examples above, further comprising a retarder disposed with

respect to the reflective surface and the coupling optical element so as to rotate the polarization of light passing through the eye piece and reflected from the reflective surface back to the eye piece and the coupling optical element.

[0490] 36. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization selective turning element.

[0491] 37. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization grating.

[0492] 38. The system of any of the Examples above, wherein the at least one coupling element is configured to turn light guided within the at least one waveguide out of the waveguide to the eye as collimated light directed to the eye of the user.

[0493] 39. The system of any of the Examples above, wherein the at least one coupling element is configured to turn collimated light from the reflective surface into the at least one waveguide.

[0494] 40. The system of any of the Examples above, wherein the at least one out-coupling element comprises an off-axis reflector.

[0495] 41. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization selective turning element.

[0496] 42. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization grating.

[0497] 43. The system of any of the Examples above, further comprising a circular polarizer.

[0498] 44. The system of any of the Examples above, wherein the in-coupling element comprises a polarization selective turning element.

[0499] 45. The system of any of the Examples above, wherein the in-coupling element comprises a polarization grating.

[0500] 46. The system of any of the Examples above, wherein the in-coupling element comprises an off-axis reflector.

[0501] 47. The system of any of Examples 20 to 34, wherein the reflective surface comprises a liquid crystal reflector.

[0502] 48. The system of any of Examples 20 to 34 or 47, wherein the reflective surface comprises a cholesteric liquid crystal reflective lens.

[0503] 49. The system of any of the Examples above, wherein the same waveguide (a) guides light coupled from the user's eye into said at least one waveguide to be received by said camera so as to capture an image of at least a portion of the eye of the user, and (b) guides light coupled from said image projector such that light from said projector can be directed to said user's eye such that said image from said image projector is in the vision field of said the user.

[0504] 50. The system of any of the Examples above, wherein the same coupling element (a) couples light from said user's eye into said at least one waveguide to be received by said camera and (b) couples light from said image projector out from said at least one waveguide to said user's eye.

[0505] 51. The system of any of the Examples above, further comprising electronics configured to cause the camera to capture a first image when light reflected from the reflective surface is blocked.

[0506] 52. The system of Example 51, wherein said electronics is configured to cause the camera to capture a second image when light reflected from the reflective surface is not blocked.

[0507] 53. The system of Example 52, wherein said electronics is configured to use the first image to modify the second image.

[0508] 54. The system of Example 53, wherein said electronics is configured to subtract from the second image based on the first image.

[0509] 55. The system of any of the Examples above, wherein said system is configured to perform eye tracking based on said image of said eye.

[0510] 56. The system of Example 55, wherein performing eye tracking based on said image of

said eye comprises storing an image of the retina of said eye.

[0511] 57. The system of any of any of the Examples above, wherein said system is configured to: [0512] store an image of the retina of said eye; [0513] capture an image of a portion of said retina of said eye; [0514] compare the stored image of said retina with the image of said portion of said retina; and [0515] determine a gaze of the user based on the comparison of the stored image and image of the portion of the retina.

[0516] 58. The system of Example 57, wherein determining a gaze of the user comprises determining to which portion of the retina corresponds to the image of said portion of the retina.

[0517] 59. The system of any of Examples 57 to 58, wherein determining a gaze of the user comprises determining an orientation of the eye.

[0518] 60. The system of any of the above Examples, further comprising a light source disposed so as to illuminate of the user's eye.

[0519] 61. The system of Example 60, wherein said light source comprises one or more infrared light sources configured to direct infrared light to the user's eye.

[0520] 62. The system of Examples 60 or 61, wherein said light source comprises one or more infrared light emitting diodes (LEDs).

[0521] 63. The system of any of Examples 60 to 62, wherein said light source is pulsed.

[0522] 64. The system of any of the Examples above, further comprising an off-axis reflector disposed to receive light from said light source and illuminate said eye with said light.

[0523] 65. A head mounted imaging system configured to image at least a portion of an environment in front of a user wearing the head mounted imaging system, said head-mounted imaging system comprising: [0524] a frame configured to be supported on a head of the user; [0525] a camera; and [0526] an eyepiece disposed on the frame, at least a portion of said eyepiece being transparent and disposed at a location in front of the user's eye when the user wears said head-mounted imaging system such that said transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user, said eyepiece comprising: [0527] (a) at least one waveguide; [0528] (b) at least one coupling optical element configured such that light from the environment in front of the user wearing the head mounted imaging system is coupled into said waveguide and guided therein; and [0529] (c) at least one out-coupling element configured to couple light within said waveguide out of said waveguide and direct said light to said camera, [0530] wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the environment in front of the user that is coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element such that images of said environment may be captured by said camera.

[0531] 66. The system of Example 65, wherein said camera comprises a detector array and imaging optics.

[0532] 67. The system of Example 66, wherein said imaging optics is configured to focus collimated light onto said detector array.

[0533] 68. The system of any of Examples 65 to 67, wherein said at least one waveguide comprises material that is transparent to visible light having a refractive index sufficient to guide light in said waveguide by total internal reflection.

[0534] 69. The system of any of Examples 65 to 68, wherein said at least one waveguide comprises a stack of waveguides.

[0535] 70. The system of Example 69, wherein different waveguides of the stack of waveguides are configured to output light with different wavefront divergence as if projected from different distances from the user's eye.

[0536] 71. The system of Example 69 or 70, wherein different waveguides of the stack of waveguides are configured to output light with different colors.

- [0537] 72. The system of any of Examples 69 to 71, wherein different waveguides comprise first, second, and third waveguides, said system is configured such that the first is for red color light, the second for is green color light, and the third is for blue color light.
- [0538] 73. The system of any of Examples 65 to 72, wherein the coupling optical element comprises a diffractive optical element.
- [0539] 74. The system of any of Examples 65 to 73, wherein the out-coupling optical element comprises a diffractive optical element.
- [0540] 75. The system of any of Examples 65 to 74, wherein the coupling element is configured to increase a dimension of the eyebox along at least one axis.
- [0541] 76. The system of Example 75, further comprising an orthogonal pupil expander comprising at least one light redirecting element in or on said at least one waveguide that is configured to increase a dimension of an eyebox along an axis that is orthogonal to the at least one axis.
- [0542] 77. The system of Example 76, wherein said at least one light redirecting element comprises a diffractive optical element.

Example Section III

- [0543] 1. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user and to image at least a portion of the eye of the user wearing the head mounted display system, said head-mounted display system comprising: [0544] a frame configured to be supported on a head of the user; [0545] an image projector configured to project an image; [0546] a camera; [0547] an eyepiece disposed on the frame, said eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user, said eyepiece comprising: [0548] (a) at least one waveguide; [0549] (b) at least one in-coupling optical element configured to in-couple light from said image projector into said at least one waveguide so as to guide light from said image projector therein; [0550] (c) at least one coupling optical element configured to couple light from said image projector guided within said waveguide out of said waveguide and direct said light to the user's eye; and [0551] (d) at least one out-coupling element configured to couple said light guided within said waveguide out of said waveguide and direct said light to said camera; and [0552] a reflective surface having optical power disposed to receive light reflected from the user's eye that passes through said eyepiece and to direct said light back to said eyepiece; [0553] wherein the image projector is disposed in an optical path with respect to said at least one in-coupling optical element to in-couple light from said image projector into said waveguide to be guided therein such that said light is coupled out from said waveguide by said at least one coupling element to said user's eye such that said image from said projector is in the vision field of said the user, [0554] wherein said at least one coupling element is configured such that light from the user's eye that passes through the eyepiece and is reflected from the reflective surface back to the eyepiece is coupled into said waveguide and guided therein, and [0555] wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the user's eye that is reflected from the reflective surface and coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element.
- [0556] 2. The system of Example 1, further comprising a light source disposed so as to illuminate of the user's eye.
- [0557] 3. The system of Example 2, wherein said light source comprises one or more infrared light sources configured to direct infrared light to the user's eye.
- [0558] 4. The system of Examples 2 or 3, wherein said light source comprises one or more infrared light emitting diodes (LEDs).

- [0559] 5. The system of any of Examples 2 to 4, wherein said light source is pulsed.
- [0560] 6. The system of any of the Examples above, further comprising an off-axis reflector disposed to receive light from said light source and illuminate said eye with said light.
- [0561] 7. The system of any of the Examples above, wherein the reflective surface reflects infrared light but transmits visible light.
- [0562] 8. The system of any of the Examples above, wherein the reflective surface is curved.
- [0563] 9. The system of any of the Examples above, wherein the reflective surface is disposed on a curved optical element.
- [0564] 10. The system of any of the Examples above, wherein the reflective surface is disposed on a concave mirror.
- [0565] 11. The system of any of the Examples above, wherein the reflective surface has positive optical power in reflection and negligible optical power in transmission.
- [0566] 12. The system of any of the Examples above, wherein the reflective surface is configured to collimated light from the user's eye.
- [0567] 13. The system of any of the Examples above, wherein the reflective surface is configured to collimate light from the retina of the user's eye.
- [0568] 14. The system of any of the Examples above, wherein the reflective surface is configured to collimate light from an anterior region of the user's eye.
- [0569] 15. The system of any of the Examples above, wherein the reflective surface is configured to collimate light from the cornea of the user's eye.
- [0570] 16. The system of any of the Examples above, wherein the reflective surface is formed on a curved optical element having an infrared reflective coating on said reflective surface.
- [0571] 17. The system of Example 9 or 16, wherein the curved optical element has negligible power for light transmitted therethrough.
- [0572] 18. The system of any of Examples 9 or 16 or 17, wherein the curved optical element has first and second curved surface on opposite sides of the curved optical element, said first and second curved surfaces having the same curvature.
- [0573] 19. The system of any of the Examples above, further comprising a retarder disposed with respect to the reflective surface and the coupling optical element so as to rotate the polarization of light passing through the eye piece and reflected from the reflective surface back to the eye piece and the coupling optical element.
- [0574] 20. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization selective turning element.
- [0575] 21. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization grating.
- [0576] 22. The system of any of the Examples above, wherein the at least one coupling element is configured to turn light guided within the at least one waveguide out of the waveguide to the eye as collimated light directed to the eye of the user.
- [0577] 23. The system of any of the Examples above, wherein the at least one coupling element is configured to turn collimated light from the reflective surface into the at least one waveguide.
- [0578] 24. The system of any of the Examples above, wherein the at least one out-coupling element comprises an off-axis reflector.
- [0579] 25. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization selective turning element.
- [0580] 26. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization grating.
- [0581] 27. The system of any of the Examples above, further comprising a circular polarizer.
- [0582] 28. The system of any of the Examples above, wherein the in-coupling element comprises a polarization selective turning element.
- [0583] 29. The system of any of the Examples above, wherein the in-coupling element comprises a

polarization grating.

[0584] 30. The system of any of the Examples above, wherein the in-coupling element comprises an off-axis reflector.

[0585] 31. The system of any of the Examples above, wherein the reflective surface comprises a liquid crystal reflector.

[0586] 32. The system of any of the Examples above, wherein the reflective surface comprises a cholesteric liquid crystal reflective lens.

[0587] 33. The system of any of the Examples above, wherein said image projector comprises a light source, a modulator, and projection optics.

[0588] 34. The system of any of the Examples above, wherein the image projector comprises scanning optical fiber.

[0589] 35. The system of any of the Examples above, wherein the modulator comprises a light modulator.

[0590] 36. The system of Example 34, wherein the light modulator comprises a spatial light modulator.

[0591] 37. The system of any of the Examples above, wherein said camera comprises a detector array and imaging optics.

[0592] 38. The system of Example 36, wherein said imaging optics is configured to focus collimated light onto a detector array.

[0593] 39. The system of any of the Examples above, wherein said at least one waveguide comprises material transparent to visible light having a refractive index sufficient to guide light in said waveguide by total internal reflection.

[0594] 40. The system of any of the Examples above, wherein said at least one waveguide comprises a stack of waveguides.

[0595] 41. The system of Example 40, wherein different waveguides of the stack of waveguides are configured to output light with different wavefront divergence as if projected from different distances from the user's eye.

[0596] 42. The system of Example 40 or 41, wherein different waveguides of the stack of waveguides are configured to output light with different colors.

[0597] 43. The system of any of Examples 40, 41, or 42, wherein different waveguides comprise first, second, and third waveguides, said system is configured such that said first is for red color light, the second for is green color light, and the third is for blue color light.

[0598] 44. The system of any of the Examples above, wherein the in-coupling optical element comprises a diffractive optical element or reflector.

[0599] 45. The system of any of the Examples above, wherein the coupling optical element comprises a diffractive optical element.

[0600] 46. The system of any of the Examples above, wherein the out-coupling optical element comprises a diffractive optical element.

[0601] 47. The system of any of the Examples above, wherein the coupling element is configured to increase dimensions of the eyebox along at least one axis.

[0602] 48. The system of Example 47, further comprising an orthogonal pupil expander comprising at least one light redirecting element in or on said at least one waveguide that is configured to increase a dimension of an eyebox along an axis that is orthogonal to the at least one axis.

[0603] 49. The system of Example 48, wherein said at least one light redirecting element comprises a diffractive optical element.

[0604] 50. The system of any of the Examples above, wherein the same waveguide (a) guides light coupled from the user's eye into said at least one waveguide to be received by said camera so as to capture an image of at least a portion of the eye of the user, and (b) guides light coupled from said image projector such that light from said projector can be directed to said user's eye such that said image from said image projector is in the vision field of said the user

[0605] 51. The system of any of the Examples above, wherein the same coupling element (a) couples light from said user's eye into said at least one waveguide to be received by said camera and (b) couples light from said image projector out from said at least one waveguide to said user's eye.

[0606] 52. The system of any of the Examples above, further comprising electronics configured to cause the camera to capture a first image when light reflected from the reflective surface is blocked.

[0607] 53. The system of Example 52, wherein said electronics is configured to cause the camera to capture a second image when light reflected from the reflective surface is not blocked.

[0608] 54. The system of Example 53, wherein said electronics is configured to use the first image to modify the second image.

[0609] 55. The system of Example 54, wherein said electronics is configured to subtract from the second image based on the first image.

[0610] 56. The system of any of the Examples above, wherein said system is configured to perform eye tracking based on said image of said eye.

[0611] 57. The system of Example 56, wherein performing eye tracking based on said image of said eye comprises storing an image of the retina of said eye.

[0612] 58. The system of any of any of the Examples above, wherein said system is configured to:

[0613] store an image of the retina of said eye; [0614] capture an image of a portion of said retina of said eye; [0615] compare the stored image of said retina with the image of said portion of said retina; and [0616] determine a gaze of the user based on the comparison of the stored image and image of the portion of the retina.

[0617] 59. The system of Example 58, wherein determining a gaze of the user comprises determining to which portion of the retina corresponds to the image of said portion of the retina.

[0618] 60. The system of any of Examples 58 to 59, wherein determining a gaze of the user comprises determining an orientation of the eye.

[0619] 61. The system of any of the above Examples, wherein said coupling element is configured such that light from the environment in front of the user wearing the head mounted display is coupled into said waveguide and guided therein.

[0620] 62. The system of any of the above Examples, wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the environment in front of the user that is coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said outcoupling coupling element such that images of said environment may be captured by said camera.

[0621] 63. The system of any of the above Examples, wherein the same waveguide (a) guides light coupled from said environment into said waveguide to be received by said camera so as to capture an image of at least a portion of the environment in front of the user, and (b) guides light coupled from said projector such that light from said projector can be directed to said user's eye so that said image from said projector is in the vision field of said the user.

[0622] 64. The system of any of the above Examples, wherein the same coupling element (a) couples light from said environment into said at least one waveguide to be received by said camera and (b) couples light from said image projector out from said at least one waveguide to said user's eye.

[0623] 65. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user and to image at least a portion of the eye of the user wearing the head mounted display system, said head-mounted display system comprising: [0624] a frame configured to be supported on a head of the user; [0625] an image projector configured to project an image; [0626] a camera; [0627] an eyepiece disposed on the frame, said eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and

disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from an environment in front of the user to the user's eye to provide a view of the environment in front of the user, said eyepiece comprising: [0628] (a) at least one waveguide; [0629] (b) at least one in-coupling optical element configured to in-couple light from said image projector into said at least one waveguide so as to guide light from said image projector therein; [0630] (c) at least one coupling optical element configured to couple light from said image projector guided within said waveguide out of said waveguide and direct said light to the user's eye; and [0631] (d) at least one out-coupling element configured to couple said light guided within said waveguide out of said waveguide and direct said light to said camera; and [0632] a positive lens having positive optical power disposed in an optical path between the user's eye and said eyepiece such that light reflected from the user's eye is transmitted through said lens to said eyepiece; and [0633] a negative lens having negative optical power disposed on the other side of the eyepiece as the positive lens to offset the power of said positive lens for light from the environment in front of the user, [0634] wherein the image projector is disposed in an optical path with respect to said at least one in-coupling optical element to couple light from said image projector into said waveguide to be guided therein such that said light is coupled out from said waveguide by said at least one coupling element to said user's eye such that said image from said image projector is in the vision field of said the user, [0635] wherein said at least one coupling element is configured such that light from the user's eye that passes through the lens to the eyepiece is coupled into said waveguide and guided therein, and [0636] wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light from the user's eye that is reflected from the reflective surface and coupled into said waveguide via the coupling element and guided therein and that is coupled out from said waveguide by said out-coupling coupling element.

[0637] 66. The system of Example 65, wherein said positive lens comprises a Fresnel lens.

[0638] 67. The system of Example 65 or 66, wherein said positive lens is configured to collimate light from an anterior region of said user's eye.

[0639] 68. The system of any of Examples 65, 66, or 67 above, wherein said positive lens is configured to collimate light from the cornea of said user's eye.

[0640] 69. The system of any of Examples 65 to 68, wherein said system is configured to perform eye tracking based on said image of said eye.

[0641] 70. The system of any of Examples 65 to 69, further comprising a light source disposed so as to illuminate of the user's eye.

[0642] 71. The system of Example 70, wherein said light source comprises one or more infrared light sources configured to direct infrared light to the user's eye.

[0643] 72. The system of Examples 70 or 71, wherein said light source comprises one or more infrared light emitting diodes (LEDs).

[0644] 73. The system of any of the Examples above, wherein said system is configured to identify the user via biometric sensing based on said image of said eye.

Example Section IV

[0645] 1. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user, said head-mounted display system comprising: [0646] a frame configured to be supported on a head of the user; [0647] an image projector configured to project images into the user's eye to display image content in the vision field of the user; [0648] at least one camera; [0649] at least one waveguide; [0650] at least one coupling optical element configured such that light is coupled into said waveguide and guided therein, said at least one coupling optical element comprising a diffractive optical element having optical power; and [0651] at least one out-coupling element configured to couple light guided within said waveguide out of said waveguide and direct said light to said camera, [0652] wherein the camera is disposed in an optical path with respect to said at least one out-coupling optical

element to receive at least a portion of the light that is coupled into said waveguide via the coupling optical element and guided therein and that is coupled out from said waveguide by said out-coupling coupling element such that images may be captured by said camera.

[0653] 2. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said at least one waveguide and guided therein such that images of said eye may be captured by said at least one camera.

[0654] 3. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from an anterior portion of the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera such that said at least one camera can capture images of said anterior portion of said eye.

[0655] 4. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from a corneal surface of said eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera such that said at least one camera can capture images of said corneal surface of said eye.

[0656] 5. The system of any of the Examples above, wherein the optical power of said coupling optical element is configured to increase collimation of light reflected from the eye that is coupled into the waveguide to be guided to the camera.

[0657] 6. The system of any of the Examples above, wherein the optical power of said coupling optical element is configured to increase collimation of light reflected from an anterior portion of the eye that is coupled into the waveguide to be guided to the camera.

[0658] 7. The system of any of the Examples above, wherein the optical power of said coupling optical element is configured increase collimation of light reflected from the cornea of the eye that is coupled into the waveguide to be guided to the camera.

[0659] 8. The system of any of Examples 1 or 7, wherein the optical power comprises positive optical power.

[0660] 9. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light reflected from the retina of the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said retina may be captured by said camera.

[0661] 10. The system of any of the Examples above, further comprising an eyepiece disposed on the frame, said eyepiece configured to direct light into said user's eye to display augmented reality image content to the user's vision field, at least a portion of said eyepiece being transparent and disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from an environment in front of the user to the user's eye to provide a view of the environment in front of the user.

[0662] 11. The system of Example 10, wherein said eyepiece is configured to receive light from said image projector and to direct said light into said user's eye to display augmented reality image content to the user's vision field.

[0663] 12. The system of any of Examples 10-11, wherein said eyepiece comprises said at least one waveguide.

[0664] 13. The system of any of Examples 10-12, wherein said image projector is configured to direct light into an edge of said eyepiece.

[0665] 14. The system of Examples 12 or 13, wherein said image projector is configured to direct light into an edge of said at least one waveguide.

[0666] 15. The system of any of the Examples above, further comprising at least one in-coupling optical element configured to in-couple light from said image projector into said at least one waveguide so as to guide light from said image projector for providing said image content to said

user's eye.

[0667] 16. The system of any of Examples 1 to 15, further comprising at least one image content out-coupling optical element configured to couple light from said image projector guided within said waveguide out of said at least one waveguide such that image content can be viewed by the user's eye.

[0668] 17. The system of any of the Examples above, wherein said at least one coupling optical element faces the eye of the user wearing the head mounted imaging system to receive light from said eye.

[0669] 18. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light from the environment in front of the user wearing the head mounted imaging system is coupled into said at least one waveguide and guided therein such that images of said environment may be captured by said camera.

[0670] 19. The system of any of the Examples above, wherein said at least one coupling optical element faces the environment in front of the user wearing the head mounted imaging system to receive light from said environment.

[0671] 20. The system of Example 16, wherein said at least one coupling optical element is configured such that light is coupled into a first waveguide and guided therein to said camera and said at least one image content out-coupling optical element is configured to couple light from said image projector guided within a second waveguide out of said second waveguide.

[0672] 21. The system of any of the Examples above, wherein said at least one coupling optical element is configured such that light is coupled into a first waveguide and guided therein to said camera and said image projector is configured to couple light into a second waveguide to provide image content to said eye.

[0673] 22. The system of any of the Examples above, wherein said image projector comprises a light source, a modulator, and projection optics.

[0674] 23. The system of any of the Examples above, wherein the image projector comprises scanning optical fiber.

[0675] 24. The system of any of Examples 22, wherein the modulator comprises a light modulator.

[0676] 25. The system of Example 24, wherein the light modulator comprises a spatial light modulator.

[0677] 26. The system of any of the Examples above, wherein said camera comprises a detector array and imaging optics.

[0678] 27. The system of Example 26, wherein said imaging optics is configured to focus collimated light onto said detector array.

[0679] 28. The system of any of the Examples above, wherein said at least one waveguide comprises material that is transparent to visible light having a refractive index sufficient to guide light in said waveguide by total internal reflection.

[0680] 29. The system of any of the Examples above, wherein said at least one waveguide comprises material that is transparent to infrared light having a refractive index sufficient to guide light in said waveguide by total internal reflection.

[0681] 30. The system of any of the Examples above, wherein said at least one waveguide comprises a stack of waveguides.

[0682] 31. The system of Example 30, wherein different waveguides of the stack of waveguides are configured to output light with different wavefront divergence as if projected from different distances from the user's eye.

[0683] 32. The system of Example 30 or 31, wherein different waveguides of the stack of waveguides are configured to output light with different colors.

[0684] 33. The system of any of Examples 30, 31, or 32, wherein different waveguides comprise first, second, and third waveguides, said system is configured such that the first is for red color light, the second for is green color light, and the third is for blue color light.

[0685] 34. The system of any of the Examples 15 to 33, wherein the at least one in-coupling optical element comprises a diffractive optical element.

[0686] 35. The system of any of the Examples 15 to 33, wherein the at least one in-coupling optical element comprises a diffraction grating.

[0687] 36. The system of any of the Examples above, wherein the in-coupling element comprises a polarization selective turning element.

[0688] 37. The system of any of the Examples above, wherein the in-coupling element comprises a polarization grating.

[0689] 38. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization selective turning element.

[0690] 39. The system of any of the Examples above, wherein the at least one coupling element comprises a polarization grating.

[0691] 40. The system of any of the Examples above, wherein the coupling optical element comprises liquid crystal.

[0692] 41. The system of any of the Examples above, wherein the coupling optical element comprises a liquid crystal polarization grating.

[0693] 42. The system of any of the Examples above, wherein the out-coupling optical element comprises a diffractive optical element.

[0694] 43. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization selective turning element.

[0695] 44. The system of any of the Examples above, wherein the at least one out-coupling element comprises a polarization grating.

[0696] 45. The system of any of the Examples above, wherein the at least one out-coupling element comprises liquid crystal.

[0697] 46. The system of any of the Examples above, wherein the at least one out-coupling element comprises a liquid crystal polarization grating.

[0698] 47. The system of any of the Examples above, wherein the at least one out-coupling element comprises an off-axis reflector.

[0699] 48. The system of any of the Examples above, wherein the same waveguide (a) guides light coupled from the user's eye into said at least one waveguide to be received by said camera so as to capture an image of at least a portion of the eye of the user, and (b) guides light coupled from said image projector such that light from said projector can be directed to said user's eye such that said image from said image projector is in the vision field of said the user.

[0700] 49. The system of any of the Examples above, wherein said system is configured to perform eye tracking based images of said eye.

[0701] 50. The system of Example 49, wherein performing eye tracking based on said images of said eye comprises storing an image of the retina of said eye.

[0702] 51. The system of any of any of the Examples above, wherein said system is configured to:

[0703] obtain an image of a portion of said retina of said eye using said camera; [0704] compare one or more stored images of said retina with the image of said portion of said retina; and [0705] determine a gaze of the user based on the comparison of the one or more stored images and the image of the portion of the retina obtained from the camera.

[0706] 52. The system of Example 51, wherein determining a gaze of the user comprises determining to which portion of the retina corresponds to the image of said portion of the retina.

[0707] 53. The system of any of Examples 51 to 52, wherein determining a gaze of the user comprises determining an orientation of the eye.

[0708] 54. The system of any of the Examples above, wherein said system is configured to obtain biometric data based on one or more images of the user's eye obtained with said camera.

[0709] 55. The system of any of the Examples above, wherein said system is configured to identify the user via biometric sensing based on one or more images of said eye obtained with said camera.

[0710] 56. The system of any of the above Examples, wherein said system is configured to provide illumination of a first polarization and to preferentially capture images with said camera using light of a second polarization different than said first polarization.

[0711] 57. The system of any of the above Examples, wherein said system is configured to illuminate said user's eye with light of a first polarization and to preferentially capture images of said user's eye with said camera using light of a second polarization different than said first polarization.

[0712] 58. The system of Examples 60 or 61, wherein said first and second polarizations are orthogonal.

[0713] 59. The system of any of the above Examples, further comprising a light source disposed so as to provide illumination so as to capture images with said camera.

[0714] 60. The system of any of the above Examples, further comprising a light source disposed so as to illuminate of the user's eye.

[0715] 61. The system of Examples 59 or 60, wherein said light source comprises one or more infrared light sources.

[0716] 62. The system of any of Examples 59 to 61, wherein said light source comprises one or more infrared light emitting diodes (LEDs).

[0717] 63. The system of any of Examples 59 to 63, wherein said light source is pulsed.

[0718] 64. The system of any of Examples 59 to 63, wherein said light source is configured to input light into a waveguide to provide said illumination.

[0719] 65. The system of any of Examples 59 to 64, wherein said light source is configured to input light into a waveguide disposed with respect to said eye to provide illumination to said eye.

[0720] 66. The system of Examples 64 or 65, further comprising an illumination in-coupling optical element configured to couple light from said light source into said waveguide.

[0721] 67. The system of any of Examples 60 to 66, wherein said light source is configured to input light into said at least one waveguide to provide illumination.

[0722] 68. The system of any of Examples 59 to 68, wherein said light source is configured to input light into the same waveguide as used to project image content to the user's eye.

[0723] 69. The system of any of Examples 59 to 69, wherein said light source is configured, to provide illumination to the user's eye, to input light into the same waveguide as used to guide light to the camera.

[0724] 70. The system of any of Examples 59 to 70, wherein said light source is configured to input light into the same waveguide as used to guide light from the user's eye to the camera.

[0725] 71. The system of any of Examples 64 to 70, further comprising an illumination in-coupling optical element configured to couple light from said light source into said waveguide to provide illumination.

[0726] 72. The system of Example 71, wherein said illumination in-coupling optical element is polarization selective, in-coupling light of a first polarization.

[0727] 73. The system of Example 59 to 77, wherein said light source is a polarized light source configured to output polarized light having a first polarization.

[0728] 74. The system of any of Examples 59 to 78, wherein said light source is configured to direct polarized light having a first polarization onto said eye.

[0729] 75. The system of Example 59 to 79, further comprising an illumination polarizer having a first polarization disposed in the optical path between said light source and said eye to polarize light directed to said eye.

[0730] 76. The system of Example 75, wherein the illumination polarizer is disposed in the optical path between said light source and said waveguide configured to provide illumination.

[0731] 77. The system of any of Examples 59 to 76, further comprising an image acquisition polarizer in an optical path between said eye and said camera.

[0732] 78. The system of Example 77, wherein said image acquisition polarizer is proximal said

camera.

[0733] 79. The system of Examples 77 or 78, wherein said image acquisition polarizer is disposed in an optical path between (a) said at least one waveguide configured guide light to said camera and (b) said camera.

[0734] 80. The system of any of Examples 77 to 79, wherein said image acquisition polarizer reduces the amount of light of said first polarization that reaches said camera.

[0735] 81. The system of Examples 77 to 80, wherein said image acquisition polarizer comprises a polarizer configured to selectively coupling light of a second polarization different than said first polarization to said camera.

[0736] 82. The system of any of the Examples above, further comprising at least one light consolidating element disposed in an optical path between said at least one coupling element and said at least one out-coupling optical element to reduce lateral spatial extent of light from said at least one coupling element prior to reaching said at least one out-coupling optical element.

[0737] 83. The system of any of the Examples above, wherein said at least one light consolidating element comprises a diffractive optical element.

[0738] 84. The system of any of the Examples above, wherein said at least one light consolidating element comprises a hologram or diffraction grating.

[0739] 85. The system of any of Examples 51, wherein the one or more stored images of the retina of the eye comprise a composite image of the retina of the eye generated using a plurality of images of different portions of the retina of the eye.

[0740] 86. The system of any of Examples 51 to 85, wherein the composite image of the retina comprises a plurality of images of the retina stitched together.

[0741] 87. The system of any of Examples 51 to 86, wherein the plurality of images of the retina stitched together comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0742] 88. The system of any of Examples 51 to 87, wherein the one or more stored images of the retina comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0743] 89. The system of any of Examples 51 to 88, wherein the system is further configured to use the obtained image of the portion of the retina of the eye to update the composite image.

[0744] 90. The system of any of Examples 51 to 89, wherein using the obtained image of the portion of the retina to update the composite image of the retina comprises stitching the obtained image into a section of the composite image corresponding to the portion of the retina shown in the obtained image.

[0745] 91. The system of any of Examples 51 to 90, wherein the system is further configured to apply a digital filter to the obtained image of the portion of the retina of the eye to obtain a filtered image of the portion of the retina.

[0746] 92. The system of Examples 91, wherein the system is further configured to compare one or more stored images of the retina with the filtered image of the portion of the retina.

[0747] 93. The system of any of Examples 91 to 92, wherein the digital filter comprises a Frangi Filter.

[0748] 94. The system of any of Examples 51 to 93, wherein the system is configured to apply edge enhance the obtained image of the portion of the retina.

[0749] 95. The system of any of the Examples above, wherein said system is configured to perform user identification verification using images of the retina.

[0750] 96. The system of any of the Examples above, wherein said system is configured to: [0751] obtain an image of a portion of said retina of said eye using said camera; [0752] compare one or more stored images of said retina with the image of said portion of said retina.

[0753] 97. The system of Example 96, wherein the one or more stored images of the retina of the eye comprise a composite image of the retina of the eye generated using a plurality of images of

different portions of the retina of the eye.

[0754] 98. The system of any of Examples 96 to 97, wherein the composite image of the retina comprises a plurality of images of the retina stitched together.

[0755] 99. The system of any of Examples 96 to 98, wherein the plurality of images of the retina stitched together comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0756] 100. The system of any of Examples 96 to 99, wherein the one or more stored images of the retina comprises images obtained when a fixation target was displayed in the vision field of the user at various locations, respectively.

[0757] 101. The system of any of Examples 96 to 100, wherein the system is further configured to use the obtained image of the portion of the retina of the eye to update the composite image.

[0758] 102. The system of any of Examples 96 to 101, wherein using the obtained image of the portion of the retina to update the composite image of the retina comprises stitching the obtained image into a section of the composite image corresponding to the portion of the retina shown in the obtained image.

[0759] 103. The system of any of Examples 96 to 102, wherein the system is further configured to apply a digital filter to the obtained image of the portion of the retina of the eye to obtain a filtered image of the portion of the retina.

[0760] 104. The system of Examples 103, wherein the system is further configured to compare one or more stored images of the retina with the filtered image of the portion of the retina.

[0761] 105. The system of any of Examples 96 to 104, wherein the digital filter comprises a Frangi Filter.

[0762] 106. The system of any of Examples 96 to 105, wherein the system is configured to apply edge enhancement the obtained image of the portion of the retina.

[0763] 107. The system of any of Examples above, wherein the optical power corresponds to a focal length about the distance of the eye to the coupling optical element.

[0764] 108. The system of any of Examples above, wherein the optical power corresponds to a focal length of between 15 mm and 25 mm.

[0765] 109. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user, said head-mounted display system comprising: [0766] a frame configured to be supported on a head of the user; [0767] at least one waveguide, [0768] an image projector for projecting images into the user's eye to display image content in the vision field of the user, said image projector configured to input light into at least one of said at least one waveguide to be guided therein; [0769] at least one image content out-coupling optical element configured to couple light from said image projector guided within said at least one of said at least one waveguide out thereof such that image content can be viewed by the user's eye. [0770] a camera; [0771] at least one coupling optical element configured such that light is coupled into at least one of said at least one waveguide and guided therein to said camera; and [0772] at least one out-coupling element configured to couple light guided within said at least one of said at least one waveguide out thereof and direct said light to said camera, said camera disposed in an optical path with respect to said at least one out-coupling optical element to receive at least a portion of the light that is coupled into said at least one of said at least one waveguide via the coupling optical element and guided therein and that is coupled out from said at least one of said at least one waveguide by said out-coupling coupling element such that images may be captured by said camera, [0773] wherein said at least one image content out-coupling optical element and said at least one coupling optical element are disposed laterally with respect to each other.

[0774] 110. The system of any of Example 109, wherein said at least one image content out-coupling optical element is disposed more nasally than said at least one out-coupling element.

[0775] 111. The system of any of Example 110, wherein said at least one image content out-coupling optical element is disposed more temporally than said at least one out-coupling element.

[0776] 112. The system of any of the Examples above, further comprising at least one light consolidating element disposed in an optical path between said at least one coupling element and said at least one out-coupling optical element to reduce lateral spatial extent of light from said at least one coupling element prior to reaching said at least one out-coupling optical element.

[0777] 113. The system of any of the Examples above, wherein said at least one light consolidating element comprises a diffractive optical element.

[0778] 114. The system of any of the Examples above, wherein said at least one light consolidating element comprises a hologram or diffraction grating.

[0779] 115. The system of any of the Examples above, wherein said coupling optical element comprises a diffractive optical element having optical power.

[0780] 116. The system of any of the Examples above, further comprising a lens disposed with respect to said coupling optical element to provide optical power to light received by said coupling optical element.

[0781] 117. The system of any of the Examples above, wherein the optical power is configured to increase collimation of light reflected from the eye that is coupled into the waveguide to be guided to the camera.

[0782] 118. The system of any of the Examples above, wherein the optical power is configured to increase collimation of light reflected from an anterior portion of the eye that is coupled into the waveguide to be guided to the camera.

[0783] 119. The system of any of the Examples above, wherein the optical power is configured increase collimation of light reflected from the cornea of the eye that is coupled into the waveguide to be guided to the camera.

[0784] 120. The system of any of Examples above, wherein the optical power comprises positive optical power.

[0785] 121. The system of any of Examples above, wherein the optical power corresponds to a focal length about the distance of the eye to the coupling optical element.

[0786] 122. The system of any of Examples above, wherein the optical power corresponds to a focal length of between 15 mm and 25 mm.

[0787] 123. The system of any of the Examples above, wherein said coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera, said system configured to image an anterior portion of said eye.

[0788] 124. The system of any of the Examples above, wherein said coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera, said system configured to image a corneal surface of said eye.

[0789] 125. The system of any of the Examples above, wherein said second coupling optical element is configured such that light reflected from the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said eye may be captured by said camera, said system configured to image the retina of said user's eye.

[0790] 126. The system of any of the above Examples, wherein said system is configured to provide illumination of a first polarization and to preferentially capture images with said camera using light of a second polarization different than said first polarization.

[0791] 127. The system of any of the above Examples, wherein said system is configured to illuminate said user's eye with light of a first polarization and to preferentially capture images of said user's eye with said camera using light of a second polarization different than said first polarization.

[0792] 128. The system of Examples 126 or 127, wherein said first and second polarizations are orthogonal.

[0793] 129. The system of any of Examples 126 to 128, further comprising an illumination in-

coupling optical element configured to couple light from a light source into said waveguide to provide illumination.

[0794] 130. The system of Example 129, wherein said illumination in-coupling optical element is polarization selective, in-coupling light of a first polarization.

[0795] 131. The system of any of the Examples above, further comprising a light source that is a polarized light source configured to output polarized light having a first polarization. **132.** The system of any of Example above, wherein said light source is configured to direct polarized light having a first polarization onto said eye.

[0796] 133. The system of any of the Examples above, further comprising an illumination polarizer having a first polarization disposed in the optical path between said light source and said eye to polarize light directed to said eye.

[0797] 134. The system of Example 133, wherein the illumination polarizer is disposed in the optical path between said light source and said waveguide configured to provide illumination.

[0798] 135. The system of any of the Example above, further comprising an image acquisition polarizer in an optical path between said eye and said camera.

[0799] 136. The system of Example 135, wherein said image acquisition polarizer is proximal said camera.

[0800] 137. The system of Examples 135 or 136, wherein said image acquisition polarizer is disposed in an optical path between (a) said at least one waveguide configured guide light to said camera and (b) said camera.

[0801] 138. The system of any of Examples 135 to 137, wherein said image acquisition polarizer reduces the amount of light of said first polarization that reaches said camera.

[0802] 139. The system of Examples 135 to 138, wherein said image acquisition polarizer comprises a polarizer configured to selectively coupling light of a second polarization different than said first polarization to said camera.

[0803] 140. A head mounted display system configured to project light to an eye of a user to display augmented reality image content in a vision field of said user, said head-mounted display system comprising: [0804] a frame configured to be supported on a head of the user; [0805] an image projector configured to project images into the user's eye to display image content in the vision field of the user; [0806] at least one camera; [0807] at least one waveguide; [0808] a first coupling optical element configured such that light is coupled into said at least one waveguide and guided therein to at least one of said at least one cameras; [0809] a second coupling optical element configured such that light is coupled into said at least one waveguide and guided therein to at least one of said at least one cameras; and [0810] at least one out-coupling element configured to couple light coupled into said at least one waveguide by said first and second coupling optical elements and guided within said at least one waveguide out of said at least one waveguide and direct said light to said at least one said camera, [0811] wherein first coupling optical element and said second coupling optical element are disposed laterally with respect to each other.

[0812] 141. The system of any of Example 140, wherein said first coupling optical element comprising a diffractive optical element having optical power.

[0813] 142. The system of any of the Examples above, further comprising a lens disposed with respect to said first coupling optical element to provide optical power to light received by said first coupling optical element.

[0814] 143. The system of any of the Examples above, wherein said optical power is configured to increase collimation of light reflected from the eye that is coupled into the waveguide to be guided to the camera.

[0815] 144. The system of any of the Examples above, wherein said optical power is configured to increase collimation of light reflected from an anterior portion of the eye that is coupled into the waveguide to be guided to the camera.

[0816] 145. The system of any of the Examples above, wherein said optical power is configured

increase collimation of light reflected from the cornea of the eye that is coupled into the waveguide to be guided to the camera.

[0817] 146. The system of any of the Examples above, wherein the optical power comprises positive optical power.

[0818] 147. The system of any of the Examples above, wherein the optical power corresponds to a focal length about the distance of the eye to first coupling optical element.

[0819] 148. The system of any of any the Examples above, wherein the optical power corresponds to a focal length of between 15 mm and 25 mm.

[0820] 149. The system of any of the Examples above, wherein said first coupling optical element is configured such that light reflected from an anterior portion of the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of said anterior portion of said eye may be captured by said camera.

[0821] 150. The system of any of the Examples above, wherein said first coupling optical element is configured such that light reflected from a corneal surface of the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of the corneal surface said eye may be captured by said camera.

[0822] 151. The system of any of the Examples above, wherein said second coupling optical element is configured such that light reflected from the retina of the eye of the user wearing the head mounted display system is coupled into said waveguide and guided therein such that images of the retina of said eye may be captured by said camera.

[0823] 152. The system of any of the Examples above, wherein said second coupling optical element does not include optical power.

[0824] 153. The system of any of the Examples above, wherein said second coupling optical element does not include a lens in an optical path between the eye and said second coupling optical element.

[0825] 154. The system of any of the Examples above, wherein said first and second coupling optical elements couple light into said waveguide that is guided therein to a single camera.

[0826] 155. The system of any of the Examples above, wherein said at least one camera comprises first and second cameras, said first coupling optical element configured to couple light into said waveguide that is guided therein to said first camera and said second coupling optical element configured to couple light into said waveguide that is guided therein to the second camera.

[0827] 156. The system of any of the Examples above, wherein said at least one camera comprises a single camera, said first and second coupling optical element configured to couple light into said waveguide that is guided therein to said single camera.

[0828] 157. The system of any of the Examples above, wherein at least one out-coupling element comprises a first out-coupling element for out-coupling light that is input into said at least one waveguide through said first coupling optical element and a second out-coupling element for out-coupling light guided that is input into said at least one waveguide through said second coupling optical element.

[0829] 158. The system of any of the above Examples, wherein said system is configured to provide illumination of a first polarization.

[0830] 159. The system of Example 158, said system is configured such that light received by said second coupling optical element is preferentially used to capture images with light having a second polarization different than said first polarization.

[0831] 160. The system of any of the above Examples, wherein said system is configured to illuminate said user's eye with light of a first polarization.

[0832] 161. The system of Example 160, wherein said system is configured such that light received by said second coupling optical element is preferentially used to capture images of said eye with light having a second polarization different than said first polarization.

[0833] 162. The system of any of Examples 158 to 161, wherein said system is configured such

that light received by said first coupling optical element enables capture of images of said eye with light having either said first or second polarizations.

[0834] 163. The system of any of Examples 158 to 162, wherein said first and second polarizations are orthogonal.

[0835] 164. The system of any of Examples 158 to 163, further comprising an illumination in-coupling optical element configured to couple light from a light source into said waveguide to provide illumination.

[0836] 165. The system of Example 164, wherein said illumination in-coupling optical element is polarization selective, in-coupling light of a first polarization.

[0837] 166. The system of any of Examples 158 to 165, further comprising a light source that is a polarized light source configured to output polarized light having a first polarization.

[0838] 167. The system of any of Examples 158 to 166, wherein said light source is configured to direct polarized light having a first polarization onto said eye.

[0839] 168. The system of any of Examples 158 to 167, further comprising an illumination polarizer having a first polarization disposed in the optical path between said light source and said eye to polarize light directed to said eye.

[0840] 169. The system of Example 168, wherein the illumination polarizer is disposed in the optical path between said light source and said waveguide configured to provide illumination.

[0841] 170. The system of any of Examples 158 to 169, further comprising an image acquisition polarizer in an optical path between said eye and said camera.

[0842] 171. The system of any of Examples 158 to 169, wherein said image acquisition polarizer is disposed in an optical path between said second coupling optical element and said at least one camera that receives light from said second coupling optical element.

[0843] 172. The system of any of the Examples above, wherein at least one out-coupling element comprises a first out-coupling element for out-coupling light that is input into said at least one waveguide through said first coupling optical element and a second out-coupling element for out-coupling light guided that is input into said at least one waveguide through said second coupling optical element.

[0844] 173. The system of any of Examples 158 to 169, wherein said image acquisition polarizer is disposed in an optical path between a second out-coupling coupling optical element and said camera.

[0845] 174. The system of Example 170, wherein said image acquisition polarizer is proximal said camera.

[0846] 175. The system of Examples 170 or 171, wherein said image acquisition polarizer is disposed in an optical path between (a) said at least one waveguide configured guide light to said camera and (b) said camera.

[0847] 176. The system of any of Examples 170 to 172, wherein said image acquisition polarizer reduces the amount of light of said first polarization that reaches said camera.

[0848] 177. The system of Examples 170 to 173, wherein said image acquisition polarizer comprises a polarizer configured to selectively coupling light of a second polarization different than said first polarization to said camera.

[0849] 178. The system of any of Examples 158 to 169, wherein said second out-coupling optical element is polarization selective, selectively outcoupling light of said second polarization from said at least one waveguide.

[0850] 179. The system of any of the Examples above, wherein no polarization selective optical elements that selectively direct said second polarization in comparison to said first polarization to said at least one camera are not included in the path between the first coupling optical element and said at least one camera receiving light therefrom.

[0851] 180. The system of any of the Examples above, wherein said first coupling optical element is not a polarization selective coupler that selectively couples said second polarization in

comparison to said first polarization into said at least one waveguide.

[0852] 181. The system of any of the Examples above, wherein the first out-coupling optical element polarization is not a selective coupling optical elements that selectively couples said second polarization in comparison to said first polarization to said at least one camera.

[0853] 182. The system of any of the Examples above, wherein no polarization selective optical elements that selectively direct said second polarization in comparison to said first polarization to said at least one camera are included in the path between the first out-coupling optical element and said at least one camera receiving light therefrom.

[0854] 183. The system of any of the Examples above, wherein no polarization selective optical elements that selectively direct said second polarization in comparison to said first polarization to said at least one camera are included in the path between the first coupling optical element and said first out-coupling optical element.

[0855] 184. The system of any of the Examples above, wherein and an optical element having optical power is disposed with respect to said first coupling optical element such that propagation of light coupled into said first coupling optical element is altered by said optical power or said first coupling optical element has optical power.

[0856] 185. The system of any of Examples above, wherein an optical element having optical power is disposed in an optical path to said first coupling optical element such that light coupled into said waveguide passes through said optical element having optical power or said first coupling optical element has optical power.

[0857] 186. The system of any of Examples above, wherein an optical element having optical power is disposed in an optical path from said eye to said first coupling optical element such that light from said eye coupled into said waveguide passes through said optical element having optical power or said first coupling optical element has optical power.

[0858] 187. The system of any of the Examples above, wherein an optical element having optical power is not disposed in an optical path from the eye to said second coupling optical element.

[0859] 188. The system of any of the Examples above, wherein an optical element having optical power is not disposed with respect to said second coupling optical element such that the propagation of light to said second coupling optical element is not altered by an optical element having optical power.

[0860] 189. The system of any of Examples above, wherein said second coupling optical element does not have optical power.

[0861] 190. The system of any of the Examples above, wherein said system is configured such that said light from said first coupling element forms an image of an anterior surface of the eye on said at least one camera thereby enabling images of said anterior surface to be captured.

[0862] 191. The system of any of the Examples above, wherein said system is configured such that said light from said first coupling optical element forms an image of glint on said at least one camera thereby enabling images of said glint to be captured.

[0863] 192. The system of any of the Examples above, wherein said system is configured such that said light from said second coupling optical element forms an image of the retina on said at least one camera thereby enabling images of said retina to be captured.

[0864] 193. The system of any of the Examples above, wherein said system is configured such that light from said first coupling optical element preferentially enabling images of glint to be captured by said at least one camera and light from said second coupling optical element preferentially enables images of the retina to be captured by said at least one camera.

[0865] 194. The system of any of the Examples above, wherein said system is configured such that light from said first coupling optical element preferentially enabling images of an anterior surface of the eye to be captured by said at least one camera and light from said second coupling optical element preferentially enables images of the retina to be captured by said at least one camera.

[0866] 195. The system of any of the Examples above, wherein said system is configured such that

light from said first coupling optical element preferentially enabling images of a corneal surface to be captured by said at least one camera and light from said second coupling optical element preferentially enables images of the retina to be captured by said at least one camera.

[0867] 196. The system of any of the Examples above, wherein said first and second coupling optical elements are in contact with each other.

Claims

1.-19. (canceled)

20. A head-mounted display system comprising: an image projector; a camera; an eyepiece configured, during operation of the system, to receive light from the image projector and direct the light along a first optical path to a user's eye, and to direct light reflected from the user's eye along a second optical path to the camera located on a world side of the eyepiece; wherein the eyepiece comprises: (i) a waveguide having a first surface facing the user's eye, (ii) a first in-coupling optical element on the first surface in the first optical path configured to in-couple light from the image projector into the waveguide, (iii) a second in-coupling optical element on the first surface in the second optical path configured to in-couple light reflected from the user's eye into the waveguide such that the in-coupled infrared light that reflected from the user's eye travels via total internal reflection within the waveguide, and (iv) an out-coupling optical element on the first surface in the second optical path configured to out-couple the light reflected from the user's eye and guided within the waveguide out of the waveguide and direct the out-coupled light to the camera; a light source located on a user side of the eyepiece opposite the camera and arranged to illuminate the user's eye with infrared light, the user side being opposite the world side; and a reflector configured to direct the infrared light reflected from the user's eye toward the second in-coupling optical element.

21. The head-mounted display system of claim 20, wherein the reflector is a curved reflector configured to collimate the infrared light reflected from the user's eye.

22. The head-mounted display system of claim 21, wherein the reflector comprises a curved transmissive optical element and a reflective coating.

23. The head-mounted display system of claim 22, wherein the reflective coating is wavelength-dependent.

24. The head-mounted display system of claim 23, wherein the reflective coating reflects optical signals in the infrared range and transmits optical signals in a visible light range.

25. The head-mounted display system of claim 22, wherein the transmissive optical element is disposed between the reflective coating and the waveguide.

26. The head-mounted display system of claim 20, wherein the reflector is positioned on the world side of the waveguide.

27. The head-mounted display system of claim 20, wherein the light source comprises a plurality of individual light sources.

28. The head-mounted display system of claim 27, wherein the plurality of individual light sources are arranged in a circular pattern in front of the user's eye.

29. The head-mounted display system of claim 27, wherein the plurality of individual light sources comprise a plurality of light-emitting diodes.

30. The head-mounted display system of claim 20, wherein the light source is configured to emit light in pulses.

31. The system of claim 20, wherein the camera comprises a detector array and imaging optics.

32. The head-mounted display system of claim 31, wherein the imaging optics are configured to image the user's eye onto the detector array.

33. The head-mounted display system of claim 32, wherein the imaging optics are configured to image an anterior portion of the user's eye onto the detector array.

34. The head-mounted display system of claim 20, wherein the waveguide comprises a material that is transparent to visible light having a refractive index sufficient for the waveguide to guide light in the waveguide by total internal reflection.

35. The head-mounted display system of claim 20, further comprising additional waveguides, wherein the waveguide and the additional waveguides form a stack of waveguides.

36. The head-mounted display system of claim 20, wherein the second in-coupling optical element comprises a diffractive optical element.

37. The head-mounted display system of claim 20, wherein the out-coupling optical element comprises a diffractive optical element.

38. The head-mounted display system of claim 20, wherein the first in-coupling optical element is configured to increase a dimension of an eyebox along at least one axis relative to a dimension of the in-coupled light.

39. The head-mounted display system of claim 38, further comprising an orthogonal pupil expander comprising at least one light redirecting element in or on the waveguide that is configured to increase a dimension of the eyebox along an axis that is orthogonal to the at least one axis relative to the dimension of the in-coupled light.
