

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12384312
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Shah; Anish et al.

---

### Structure for managing loads during an impact event

---

#### Abstract

A system for managing wheel kinematics during a small overlap collision event includes a deflector apparatus. The deflector is configured to direct a wheel away from an occupant compartment of a vehicle. The deflector includes a first section arranged at an inside wall of a wheel well facing a wheel, near the base of a hinge-pillar. The first section includes a hollow structure configured to absorb energy from the collision event by plastically deforming. The deflector also includes a second section arranged at an angle to the wheel and configured to deflect the wheel laterally outwards from the vehicle away from an occupant compartment during the small overlap collision event. The deflector may be formed of extruded aluminum. The system may include an absorber arranged behind the first section and configured to further absorb energy from the collision event by plastically deforming.

---

<b>Inventors:</b>	<b>Shah; Anish (Ann Arbor, MI), Chauhan; Akshat (Livonia, MI)</b>
<b>Applicant:</b>	<b>Rivian IP Holdings, LLC (Irvine, CA)</b>
<b>Family ID:</b>	<b>1000008749148</b>
<b>Assignee:</b>	<b>Rivian IP Holdings, LLC (Irvine, CA)</b>
<b>Appl. No.:</b>	<b>18/516566</b>
<b>Filed:</b>	<b>November 21, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240083377 A1	Mar. 14, 2024

#### Related U.S. Application Data

continuation parent-doc US 16911714 20200625 US 11827167 child-doc US 18516566

---

## Publication Classification

**Int. Cl.:** **B60R19/00** (20060101); **B60R19/34** (20060101); **B62D21/02** (20060101); **B62D21/15** (20060101)

**U.S. Cl.:**

**CPC** **B60R19/00** (20130101); **B60R19/34** (20130101); **B62D21/02** (20130101); **B62D21/15** (20130101); **B62D21/152** (20130101); B60R2019/002 (20130101); B60R2019/005 (20130101)

## Field of Classification Search

**CPC:** B60R (19/00); B60R (2019/002); B60R (19/34); B60R (2019/247); B62D (21/02); B62D (21/15); B62D (21/152); B62D (29/008)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3486764	12/1968	Beyer et al.	N/A	N/A
3881742	12/1974	Felzer	N/A	N/A
4334693	12/1981	Huber	N/A	N/A
5275436	12/1993	Pomero	N/A	N/A
5601304	12/1996	Tilly et al.	N/A	N/A
5607177	12/1996	Kato	N/A	N/A
6196621	12/2000	Vanassche et al.	N/A	N/A
6296298	12/2000	Barz	N/A	N/A
6311996	12/2000	Kato et al.	N/A	N/A
6364358	12/2001	Miller	N/A	N/A
6474722	12/2001	Barz	N/A	N/A
6631942	12/2002	Kitagawa	N/A	N/A
6705627	12/2003	Hasebe et al.	N/A	N/A
6729425	12/2003	Schneider et al.	N/A	N/A
6777049	12/2003	Sheldon et al.	N/A	N/A
6866115	12/2004	Miyasaka	N/A	N/A
6880657	12/2004	Schneider et al.	N/A	N/A
6892621	12/2004	Grosch	N/A	N/A
7198139	12/2006	Wilson et al.	N/A	N/A
7374219	12/2007	Brennecke	296/187.02	B62D 29/002
7479246	12/2008	Muteau et al.	N/A	N/A
7540550	12/2008	Huber	296/29	B60R 19/24
7641264	12/2009	Niezur et al.	N/A	N/A
7819218	12/2009	Eichberger	180/274	B60R 19/00
7900964	12/2010	Chretien	180/274	B62D 21/155
7931318	12/2010	Matsumura	N/A	N/A
8033557	12/2010	Dundon	N/A	N/A
8353380	12/2012	Schoenberger et al.	N/A	N/A
8430448	12/2012	Richardson et al.	N/A	N/A

8469442	12/2012	Pencak et al.	N/A	N/A
8480130	12/2012	Dandekar	280/784	B62D 21/155
8544589	12/2012	Rupp et al.	N/A	N/A
8733823	12/2013	Brockhoff et al.	N/A	N/A
8801083	12/2013	Miyashita	N/A	N/A
8857555	12/2013	Paintmayer et al.	N/A	N/A
8985258	12/2014	Midoun	180/274	B62D 21/152
9010843	12/2014	Lewis et al.	N/A	N/A
9067549	12/2014	Baccouche et al.	N/A	N/A
9067627	12/2014	Hara	N/A	B62D 21/152
9073503	12/2014	Ookubo	N/A	B60R 19/18
9156418	12/2014	Ramoutar	N/A	B60R 19/24
9168958	12/2014	Kim	N/A	B60G 7/001
9187133	12/2014	Rangaswamaiah et al.	N/A	N/A
9233716	12/2015	Midoun	N/A	B62D 21/152
9242673	12/2015	Okamoto	N/A	N/A
9296427	12/2015	Kim et al.	N/A	N/A
9340230	12/2015	Murray	N/A	N/A
9365245	12/2015	Donabedian et al.	N/A	N/A
9376144	12/2015	Shaner	N/A	B62D 21/152
9394005	12/2015	Enders	N/A	N/A
9415805	12/2015	Fujikawa	N/A	B62D 21/152
9421927	12/2015	Basappa	N/A	B60R 19/04
9533712	12/2016	Panganiban et al.	N/A	N/A
9550463	12/2016	Hara	N/A	B62D 21/152
9561824	12/2016	Tamaoki	N/A	B60R 19/34
9567010	12/2016	Volz	N/A	B62D 25/2081
9663050	12/2016	Nishida et al.	N/A	N/A
9669784	12/2016	Jensen et al.	N/A	N/A
9669785	12/2016	Holmstrom et al.	N/A	N/A
9676416	12/2016	Kitakata	N/A	B62D 21/152
9688311	12/2016	Yamamoto et al.	N/A	N/A
9701345	12/2016	Kanemori et al.	N/A	N/A
9821853	12/2016	Torikawa et al.	N/A	N/A
9884648	12/2017	Grattan	N/A	B62D 21/152
9926012	12/2017	Makowski	N/A	B62D 21/152
9944142	12/2017	Mohrlock	N/A	N/A
10077014	12/2017	Chiang et al.	N/A	N/A
10118644	12/2017	Grattan	N/A	B62D 21/05
10150507	12/2017	Grattan	N/A	B62D 21/02
10173728	12/2018	Munjurulimana et al.	N/A	N/A
10315700	12/2018	Coppuck	N/A	B60G 3/20
10421505	12/2018	Tjoelker et al.	N/A	N/A
10479409	12/2018	Fujiwara	N/A	B62D 21/155
10486628	12/2018	Grattan	N/A	B60R 19/24
10526017	12/2019	Grattan	N/A	B62D 21/02
10654525	12/2019	Komiya	N/A	B62D 21/11
10661833	12/2019	McGory	N/A	B62D 27/023

10730461	12/2019	Yoshida	N/A	B60R 19/34
10766326	12/2019	Hata	N/A	B62D 21/15
10822027	12/2019	Karlsson	N/A	B62D 7/18
10829157	12/2019	Kato	N/A	B60G 3/18
10913499	12/2020	Alwan et al.	N/A	N/A
10926803	12/2020	Moss	N/A	B62D 21/04
10926806	12/2020	Alwan et al.	N/A	N/A
11220296	12/2021	Hammer	N/A	B62D 21/03
11286001	12/2021	O'Bannon	N/A	B62D 21/155
11292523	12/2021	Shah	N/A	B62D 21/152
11299206	12/2021	Matsumoto	N/A	B62D 21/03
11312420	12/2021	Yoshida	N/A	B62D 25/08
11377156	12/2021	Esber et al.	N/A	N/A
11396331	12/2021	Park	N/A	B62D 21/155
11505251	12/2021	Shah	N/A	B60R 19/24
2002/0008375	12/2001	Iyanagi et al.	N/A	N/A
2002/0180171	12/2001	Hasebe et al.	N/A	N/A
2003/0090099	12/2002	Miyasaka	280/784	B62D 21/15
2006/0151970	12/2005	Kaminski et al.	N/A	N/A
2009/0146462	12/2008	Sato et al.	N/A	N/A
2012/0248820	12/2011	Yasui	296/193.09	B62D 21/152
2012/0313360	12/2011	Akaki	280/784	B62D 21/02
2013/0241166	12/2012	Paintmayer et al.	N/A	N/A
2014/0062106	12/2013	Han	293/133	F16F 7/12
2014/0062129	12/2013	Syed	296/187.1	B62D 21/152
2014/0091595	12/2013	Ramoutar	293/150	B60R 19/24
2014/0125030	12/2013	Hara	280/124.134	B62D 21/152
2014/0361559	12/2013	Sakakibara	293/133	B60R 19/34
2015/0021935	12/2014	Baccouche et al.	N/A	N/A
2015/0021936	12/2014	Nusier et al.	N/A	N/A
2015/0246691	12/2014	Volz et al.	N/A	N/A
2015/0274209	12/2014	Basappa	296/187.1	B60R 19/04
2015/0298634	12/2014	Hara	293/133	B60R 19/04
2015/0314742	12/2014	Kato	293/155	B60R 19/34
2019/0023323	12/2018	Uehata	N/A	B62D 25/025
2019/0161037	12/2018	Yoshida	N/A	B62D 21/152
2021/0403089	12/2020	Shah	N/A	B60G 7/02
2021/0403090	12/2020	Shah et al.	N/A	N/A
2021/0403092	12/2020	Shah et al.	N/A	N/A

#### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204488697	12/2014	CN	N/A
204567534	12/2014	CN	N/A
204641888	12/2014	CN	N/A
105270307	12/2015	CN	N/A
210149273	12/2019	CN	N/A
111038425	12/2019	CN	N/A
102015116836	12/2015	DE	N/A

102015007453	12/2015	DE	N/A
102018105803	12/2017	DE	N/A
2018/078226	12/2017	WO	N/A

---

*Primary Examiner:* Wilhelm; Timothy

*Attorney, Agent or Firm:* Haley Guiliano LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/911,714, filed Jun. 25, 2020, now U.S. Pat. No. 11,827,167, the entire contents of which is hereby incorporated by reference herein in its entirety.

### **INTRODUCTION**

(1) The present disclosure is directed towards an apparatus for deflecting a wheel away from an occupant compartment during small overlap front crash events.

### **SUMMARY**

(2) Structures of the present disclosure are configured to provide sufficient lateral push to a vehicle so that a head-on collision can be mitigated. In some embodiments, the present disclosure is directed to a system for managing lateral loads in a vehicle. The system includes a crossmember and a load-transmitting structure, which may be deformable. The crossmember is arranged laterally spanning a first longitudinal frame member and a second longitudinal frame member of the vehicle. The first longitudinal frame member is arranged on a first side of the vehicle, and the second longitudinal frame member is arranged on a second side of the vehicle. The deformable structure is affixed to one lateral side of the vehicle, arranged longitudinally forward of the crossmember, arranged laterally outside of the first frame member, and configured to deform during a small overlap collision. While deforming, the structure applies a lateral force on a first end of the crossmember to cause lateral displacement of the vehicle. For example, the structure applies the lateral force directed towards the second side of the vehicle from the first side of the vehicle.

(3) In some embodiments, the crossmember is rigidly affixed to the first longitudinal frame member and to the second longitudinal frame member. For example, in some embodiments, the crossmember is welded to both longitudinal frame members to form structurally rigid connections.

(4) In some embodiments, the structure includes a wedge. The wedge includes a first face arranged along a laterally outer edge of the first frame member, and a second face arranged along a bumper system. For example, the first face and the second face are arranged at approximately 90° to each other. In some embodiments, the second face is configured to deflect towards the first face under the small overlap collision. For example, the wedge may deform to form a substantially sharper wedge angle, thus elongating in the longitudinal direction.

(5) In some embodiments, the crossmember extends through a first opening in the first longitudinal frame member and a through a second opening in the second longitudinal frame member. For example, the cross member may have a substantially tubular cross section, of any suitable shape (e.g., circular, rectangular, rounded rectangular, or other suitable shape), which extends through each respective longitudinal frame member. In the further example, the ends of the crossmember may extend outboard of the respective longitudinal frame members. In some embodiments, the end of the crossmember is angled such that the front length of the crossmember is shorter than the rear length.

(6) In some embodiments, the present disclosure is directed to a frame system that includes the system for managing lateral loads in a vehicle. For example, the frame system may include the

crossmember, the structure, the longitudinal frame members, any other suitable components, or any suitable combination thereof. In some embodiments, the present disclosure is directed to a vehicle that includes the frame system.

(7) In some embodiments, the frame system includes a second structure affixed to the second side of the vehicle. The second structure is arranged longitudinally forward of the crossmember, arranged laterally outside of the second frame member, and configured to deform during a small overlap collision to the second side. The second structure is configured to apply a lateral force on a second end of the crossmember to cause lateral displacement of the vehicle towards the first side.

(8) In some embodiments, the present disclosure is directed to a structure for generating side loads in a vehicle during a small-offset collision that is configured to be arranged laterally outside of a longitudinal frame element of the vehicle, and wherein a crossmember is connected to the longitudinal frame member. The structure includes a sidewall (e.g., forming a wedge-shaped structure). The sidewall includes a first wall longitudinally oriented, a second wall laterally oriented, and a first spine angled to connect the first wall and the second wall. The structure also includes a second spine substantially parallel to the first spine, arranged inside of the sidewall. The structure also includes a plurality of ribs connecting the first spine and the second spine, connecting the second spine to the first wall and the second wall, or both. The structure is configured to deform when a load is applied to the second wall such that the first spine and the second spine align with an end of the crossmember to impart a lateral force on the crossmember. For example, in some embodiments, a profile of the sidewall, the second spine, and the plurality of ribs is made from extruded aluminum.

(9) In some embodiments, the structure includes a plurality of holes arranged in the second face for coupling the structure to a bumper assembly of the vehicle. In some embodiments, the first wall is configured to be arranged along the longitudinal frame element, and the first wall does not include holes for affixing to the longitudinal frame element.

(10) In some embodiments, the structure is configured to define when the load is applied to the second wall such that the first spine and the second spine are configured to align with respective walls of the crossmember.

(11) In some embodiments, the structure includes a cover affixed on a top of the sidewall, the second spine, and the plurality of ribs. The cover is configured to be coupled to a body element of the vehicle.

(12) In some embodiments, the first spine meets the first wall at a first curved interface, and the first spine meets the second wall at a second curved interface. For example, the structure may be substantially wedge shaped and include curved or segmented regions where walls meet. In a further example, in some embodiments, the structure includes a third wall longitudinally oriented to connect the second wall to the first spine.

(13) In some embodiments, the first spine and the second spine include respective stiffnesses sufficient to transfer load to the crossmember. The plurality of ribs include respective stiffnesses to substantially maintain a distance between the first spine and the second spine, maintain alignment of the first spine and the second spine with the crossmember during the small offset collision, or both.

(14) In some embodiments, the structure is made using a method that includes extruding aluminum along an axis, and then cutting the extrusion to form the structure. A billet is extruded along the axis to form a first extrusion having a first length and a cross-section. The cross-section (e.g., the profile) includes a sidewall having a first wall longitudinally oriented, a second wall laterally oriented, and a first spine angled to connect the first wall and the second wall. The cross-section also includes a second spine and a plurality of ribs. The second spine is substantially parallel to the first spine and arranged inside of the sidewall. The plurality of ribs connect the first spine and the second spine, connect the second spine to the first wall and the second wall, or both. The structure is configured to deform when a load is applied to the second wall such that the first spine and the

second spine align with an end of the crossmember to impart a lateral force on the crossmember. The method includes cutting the extrusion at a first position along the axis, and then cutting the extrusion at a second position along the axis a predetermined length from the first position to form the structure. For example, the predetermined length defines the height of the structure when installed in a vehicle (e.g., from top to bottom). In some embodiments, the method includes forming a plurality of through features in the second wall for securing the structure to a vehicle. For example, the through features may include drilled holes or slots, machined holes or slots, any other suitable opening, or any combination thereof. In some embodiments, the method includes welding or otherwise securing (e.g., fastening) a top plate to a top side of the structure, a bottom plate to a bottom side of the structure, or both. For example, the top side and the bottom side are separated by the predetermined length.

(15) In some embodiments, the present disclosure is directed to a structure that includes a sidewall (e.g., forming a wedge-shaped structure) including a first wall longitudinally oriented, a second wall laterally oriented, and a third wall angled to connect the first wall and the second wall. The structure includes a top plate arranged on top of and affixed to the sidewall, a bottom plate arranged below and affixed to the sidewall, and an intermediate plate arranged between the top plate and the bottom plate. The structure is configured to deform when a load is applied to the second wall such that the intermediate plate aligns with an end of the crossmember to impart a lateral force on the crossmember. For example, in some embodiments, the sidewall, the top plate, the bottom plate, and the intermediate plate are made of sheet steel. In a further example, the sidewall, the top plate, the bottom plate, and the intermediate plate are spot welded to form the structure. In some embodiments, the intermediate plate has a stiffness sufficient to transfer load to the crossmember.

(16) In some embodiments, the structure includes a plurality of holes arranged in the second face for coupling the structure to a bumper assembly of the vehicle.

(17) In some embodiments, the structure is configured to define when the load is applied to the second wall such that the intermediate plate is configured to align with respective walls of the crossmember.

(18) In some embodiments, the present disclosure is directed to a system for managing wheel kinematics during a collision event. In some embodiments, the system includes a recess arranged in a frame member, a pin, a top plate, and a bottom plate. The pin is arranged vertically in the recess and configured to couple a lower control arm to the frame member. The top plate defines a top of the recess and includes a first through feature configured to accommodate the pin and constrain lateral motion of the pin, and a first break-away region including a reduced stiffness. The first break-away region is configured to fail under the collision event to allow the pin to move laterally out of the first through feature. The bottom plate defines a bottom of the recess and includes a second through feature configured to accommodate the pin and constrain lateral motion of the pin, and a second break-away region including a reduced stiffness. The second break-away region is configured to fail under the collision event to allow the pin to move laterally out of the second through feature.

(19) In an illustrative example, in some embodiments, the first break-away region, the second break-away region, or both include one or more notches such as a first notch and a second notch. In a further illustrative example, the first break-away region includes a first region of the top plate arranged between a first notch and the first through feature, and a second region of the top plate arranged between a second notch and the first through feature. The first region and the second region are configured to fail during the collision event. In some embodiments, the first through feature, the second through feature, or both include a circular hole or a slot. In some embodiments, the first break-away region, the second break-away region, or both are configured to fail under the collision event by fracturing.

(20) In some embodiments, a system for managing wheel kinematics during a collision event includes a lower control arm, a front mount, and a rear mount. The lower control arm is configured

to couple a wheel to a frame member and includes a front portion and a rear portion. The front mount couples the front portion of the lower control arm to the frame member to form a first joint. The front mount includes a break-away region configured to fail under the collision event to allow the front portion to move laterally away from the front mount. The rear mount couples the rear portion of the lower control arm to the frame member forming a second joint configured to constrain lateral displacement of the second portion during the collision event.

(21) In some embodiments, the front mount includes a through feature configured to accommodate a pin and constrain lateral motion of the pin. The pin couples the front portion of the lower control arm to the first mount. The break-away region is configured to fail during the collision event to allow the pin to move laterally out of the through feature. In an illustrative example, in some embodiments, the break-away region includes one or more notches such as a first notch and a second notch. In some embodiments, the break-away region includes a first region arranged between a first notch and the through feature, and a second region arranged between a second notch and the through feature. The first region and the second region are configured to fail during the collision event. For example, in some embodiments, the break-away region is configured to fail during the collision event by fracturing. In an illustrative example, the break-away region may be configured to fail under a load of 100 kN.

(22) In some embodiments, the front mount includes a top through feature, a bottom through feature vertically aligned with the top feature, and a pin extending vertically through the top through feature and the bottom through feature. In some such embodiments, the front portion of the lower control arm is coupled to the pin, and the pin constrains lateral motion of the front portion of the lower control arm.

(23) In some embodiments, the present disclosure is directed to a mount configured to constrain and release a front portion of a lower control arm. The mount includes a top through feature, a bottom through feature vertically aligned with the top feature, a pin extending vertically through the top through feature and the bottom through feature, and a break-away region. The front portion of the lower control arm is coupled to the pin, and the pin constrains lateral motion of the front portion of the lower control arm. The break-away region is configured to fail during a collision event to allow the front portion to move laterally away from the first through feature. In some embodiments, the break-away region includes one or more notches such as a first notch and a second notch. For example, in some embodiments, a first notch and a second notch reduce a stiffness of the first mount to fail under the collision event.

(24) In some embodiments, the mount includes a top plate in which the top through feature is arranged, and a bottom plate in which the bottom through feature is arranged. In some such embodiments, the break-away region includes a first break-away region of the top plate and a second break-away region of the bottom plate.

(25) In some embodiments, the mount includes a top section in which the top through feature is arranged, and a bottom section in which the bottom through feature is arranged. For example, the top section and the bottom section may be two sections of a single component such as a C-shaped bracket.

(26) In some embodiments, the present disclosure is directed to a deflector apparatus for managing wheel kinematics during a small overlap collision event. The deflector apparatus includes a first section and a second section. The first section is arranged at an inside wall of a wheel well and substantially facing a wheel positioned in the wheel well. The first section comprises a hollow structure configured to absorb energy from the collision event by plastically deforming. The second section is arranged at an angle to the wheel and is configured to deflect the wheel laterally outwards from the vehicle away from an occupant compartment during the small overlap collision event. In an illustrative example, in some embodiments, the deflector apparatus is extruded from aluminum. For example, the first section and the second section may include extruded aluminum.

(27) In some embodiments, the deflector apparatus is configured to be arranged at the base of a



hinge-pillar. In some such embodiments, the deflector apparatus includes a set of through features configured to accommodate a corresponding set of fasteners affixed to the hinge-pillar. The hinge pillar provides support for a door hinge, for example.

(28) In some embodiments, the deflector apparatus includes a set of through features configured to accommodate a corresponding set of fasteners affixed to a rear of the wheel well.

(29) In some embodiments, the deflector apparatus includes an absorber arranged behind the first section and configured to further absorb energy from the collision event by plastically deforming. In some embodiments, the deflector apparatus includes an absorber arranged behind the frame coupler and configured to further absorb energy from the collision event by plastically deforming.

(30) In some embodiments, the deflector apparatus includes a frame coupler configured to affix a frame system and a body system. The occupant compartment is formed by the body system, and the frame coupler is arranged behind the first section.

(31) In some embodiments, the present disclosure is directed to a vehicle configured for managing wheel kinematics during a small overlap collision event. The vehicle includes a first wheel, a first wheel mount, a first wheel well configured to accommodate the first wheel, a frame system, an occupant compartment, and a deflector. The frame system includes a first pillar arranged at a first position, which is arranged at a rear and laterally outside portion of the first wheel well. The deflector is affixed in the first wheel well at the first position. The deflector includes a first section having a hollow structure configured to absorb energy from the collision event by plastically deforming, and a second section arranged at an angle to the first wheel and configured to deflect the first wheel laterally outwards from the vehicle to prevent intrusion of the first wheel into the occupant compartment during the collision event. In an illustrative example, in some embodiments, the deflector is extruded from aluminum.

(32) In some embodiments, the deflector is configured to be arranged at the base of a hinge-pillar. In some such embodiments, the deflector includes a set of through features configured to accommodate a corresponding set of fasteners affixed to the hinge-pillar. In some embodiments, the deflector includes a set of through features configured to accommodate a corresponding set of fasteners affixed to a rear of the wheel well.

(33) In some embodiments, the vehicle includes an absorber arranged behind the first section and configured to further absorb energy from the collision event by plastically deforming. In some embodiments, the vehicle includes an absorber arranged behind the frame coupler and configured to further absorb energy from the collision event by plastically deforming.

(34) In some embodiments, the vehicle includes a frame coupler configured to affix a frame system and a body system. The occupant compartment is formed by the body system, and the frame coupler is arranged behind the first section.

(35) In some embodiments, the wheel includes a plurality of radial spokes, and the deflector is configured to deflect the plurality of spokes away from the occupant compartment during the collision event. For example, in some embodiments, the wheel mount includes a lower control arm configured to direct the plurality of radial spokes to the deflector during the collision event.

(36) In some embodiments, the present disclosure is directed to a system for managing wheel kinematics during a small overlap collision event of a vehicle. The system includes a frame system, a body system, a frame coupler, and a deflector. The frame system includes a first pillar arranged at first position at a laterally outside portion of a rear of the first wheel well. The body system includes an occupant compartment. The frame coupler at least partially affixes the frame system to the body system. The deflector is affixed to the frame coupler and faces a wheel in the first wheel well. The deflector includes a first section having a hollow structure configured to absorb energy from the collision event by plastically deforming, and a second section arranged at an angle to the wheel and configured to deflect the wheel laterally outwards from the vehicle to prevent intrusion of the wheel into the occupant compartment during the small overlap collision event. In some embodiments, the system includes an absorber arranged behind the frame coupler and that is

configured to further absorb energy from the collision event by plastically deforming.

(37) In some embodiments, a vehicle includes a crossmember and structure for generating lateral loads, a lower control arm configured to break-away, and a deflector, or any combination thereof, to manage loads during a collision event such as a small offset crash.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present disclosure, in accordance with one or more various embodiments, is described in detail with reference to the following figures. The drawings are provided for purposes of illustration only and merely depict typical or example embodiments. These drawings are provided to facilitate an understanding of the concepts disclosed herein and shall not be considered limiting of the breadth, scope, or applicability of these concepts. It should be noted that for clarity and ease of illustration these drawings are not necessarily made to scale.
- (2) FIG. 1 shows several arrangements of vehicles during a small overlap collision, in accordance with some embodiments of the present disclosure;
- (3) FIG. 2 shows several bottom views of an illustrative system for managing lateral loads during a small overlap collision and a system having a break-away region, in accordance with some embodiments of the present disclosure;
- (4) FIG. 3 shows a perspective view, from above, of an illustrative structure for managing lateral loads in a front crash, in accordance with some embodiments of the present disclosure;
- (5) FIG. 4 shows two bottom views of an illustrative structure for managing lateral loads in a front crash, before and during an impact, in accordance with some embodiments of the present disclosure;
- (6) FIG. 5 shows illustrative structures for managing lateral loads in a front crash, in accordance with some embodiments of the present disclosure;
- (7) FIG. 6 shows a top view of an illustrative mount having a break-away region, before and after failure of the break-away region, in accordance with some embodiments of the present disclosure;
- (8) FIG. 7 shows a perspective view of an illustrative system including part of a lower control arm, and a mount having a break-away region, in accordance with some embodiments of the present disclosure;
- (9) FIG. 8 shows a bottom view of a portion of an illustrative vehicle having a wheel deflector, in accordance with some embodiments of the present disclosure;
- (10) FIG. 9 shows a bottom view of a portion of the illustrative vehicle of FIG. 8 with the frame coupling removed, in accordance with some embodiments of the present disclosure;
- (11) FIG. 10 shows a perspective view of a portion of the illustrative vehicle of FIG. 8, with the wheel removed, in accordance with some embodiments of the present disclosure; and
- (12) FIG. 11 shows a perspective view of the deflector of FIG. 8, in accordance with some embodiments of the present disclosure.

### DETAILED DESCRIPTION

- (13) In some embodiments, the present disclosure is directed to structures arranged in the front of the vehicle, configured to affect the crashworthiness of a vehicle, particularly in small offset front collisions. The structures of the present disclosure may be designed to meet the most common mode of accidents, which are well-defined by the Insurance for Institute of Highway Safety (IIHS) and its test protocol on Small Overlap Rigid Barrier (commonly known as SORB). A vehicle may include structures and systems for managing loads, deformation, and kinematics during such a crash. For example, a vehicle may include a crossmember and structure for generating lateral loads to move the vehicle away from the barrier, a lower control arm configured to break-away to direct the wheel away from an occupant compartment, a deflector to aid in directing the wheel away from

the occupant compartment, any other suitable features or components, or any combination thereof, to manage loads during a collision event such as a small offset crash.

(14) The systems and structures of FIGS. **2-11** may be combined or otherwise modified to provide reduced intrusion into an occupant compartment from a small offset collision.

(15) In some embodiments, the structures of the present disclosure address the issue of creating a cross-car load-path, which plays a role in deflection of the vehicle off of a barrier. In an illustrative example, the structures of the present disclosure include one or more wedges and a cross member. For example, the structure may include two wedges, one on either side of the vehicle, and a crossmember extending laterally across the frame of the vehicle.

(16) FIG. **1** shows several arrangements of vehicles **101** and **102** during a small overlap collision, in accordance with some embodiments of the present disclosure. Vehicle **101** includes a structure in accordance with the present disclosure. Arrangement **100** corresponds to a pre-event arrangement, wherein vehicle **101** is approaching vehicle **102** with a small overlap (e.g., designated as “L” in the figure). Arrangement **150** corresponds to an arrangement during the event, wherein the structure of vehicle **101** is reacting to loads from the collision, thus generating lateral displacement (e.g., along the “Y” axis). Arrangement **170** corresponds to an arrangement substantially after the event, wherein vehicle **101** is laterally offset from vehicle **102** (e.g., offset along the “Y” axis). It will be understood that while the description of FIG. **1** is in the context of the structure of vehicle **101**, vehicle **102** may also have a similar structure to generate lateral loads (e.g., both vehicles **101** and **102** may include structure in accordance with the present disclosure).

(17) Referencing arrangement **100**, vehicle **101** and vehicle **102** may be approaching head-on, one vehicle may be stationary and the other approaching, or alternatively (not shown), vehicle **102** may be replaced by a substantially rigid barrier. In any of these scenarios, vehicle **101** is configured to transfer some of the kinetic energy along the “X” axis into kinetic energy along the “Y” axis, thus causing lateral displacement. A small overlap collision can cause significant damage to a vehicle, including intrusion into the passenger cabin. Without some lateral displacement, the full energy of impact is experienced by the vehicle. By deflecting the collision by imparting lateral displacement, vehicle **101** may undergo less damage, experience less energy dissipation, and expose the occupant compartment to less force or impact.

(18) Referencing arrangement **150**, the structure of vehicle **101** generates lateral forces that cause lateral displacement. Effectively, the lateral forces decrease the value of “L” as the event proceeds, thus moving vehicle **101** and vehicle **102** laterally away from each other.

(19) Referencing arrangement **170**, vehicle **101** has been displaced laterally a distance of “L” or even greater such that vehicle **101** and vehicle **102** do not overlap and thus can continue moving substantially past each other. By generating lateral forces, the structure of vehicle **101** causes vehicle **101** to move away from vehicle **102** along the “Y” axis.

(20) FIG. **2** shows several bottom views (e.g., panels **200**, **201**, and **202**) of an illustrative system for managing lateral loads during a small overlap collision and a system having a break-away region, in accordance with some embodiments of the present disclosure. Panels **200**, **201**, and **202** illustrate bottom views of a corner of an illustrative vehicle undergoing a small overlap collision event.

(21) As illustrated in FIG. **2**, the vehicle includes element **211**, which is configured to engage crossmember **215** during a small overlap collision. For example, element **211** may be referred to herein as a “wedge,” and is configured to transmit force to cross member **215** to cause lateral displacement of the vehicle during the small overlap collision (e.g., as described in the context of FIGS. **3-4**).

(22) Lower control arm **230** is secured to mount **221**, which includes a break-away region, by pin **299**, and also to mount **233** (e.g., a rear mount). Mount **221**, as illustrated includes a top section (e.g., the top of a C-shaped mount as illustrated) and a bottom section (e.g., the bottom of the C-shaped mount). Mount **221** couples control arm **230** to frame member **231**. For example, as

illustrated, pin **299** constrains lateral displacement of the front portion of control arm **230**. In a further example, pin **299** and the end of lower control arm **230** may form a ball joint or other suitable joint for connecting control arm **230** to mount **221**. In some embodiments, pin **299** may be considered part of mount **221** (e.g., a mount may include a bracket and joint structure). Mount **221** is rigidly affixed to frame member **231**, and thus mount **221** is constrained from displacement relative to frame member **231**.

(23) Panel **200** corresponds to a pre-collision configuration. Panel **201** corresponds to a configuration during a small overlap collision. Panel **202** corresponds to a configuration during a small overlap collision at a later time than that illustrated in panel **201**. Upon colliding with a rigid barrier (e.g., a structure, another vehicle, any other suitable rigid object having a suitable mass and stiffness) during a small overlap collision, element **211** is configured to be loaded by the barrier laterally into crossmember **215** thus imparting a lateral force on crossmember **215**. The lateral force causes a lateral displacement such that the vehicle moves laterally away from the rigid barrier. Further, during the small overlap collision, as wheel **250** is loaded in the longitudinal direction (e.g., front to back), lower control arm **230** is loaded. Mount **221** is configured to break away during the collision, and thus stop constraining the front end of lower control arm **230**. For example, pin **299** is configured to be loaded by lower control arm **230** and break-away from mount **221**. After breaking away from mount **221**, lower control arm **230** is constrained by rear mount **233**, and it may pivot about rear mount **233**. By breaking away from mount **221**, the pivot point is shifted to rear mount **233**, thus preventing wheel **250** from following a trajectory more directly into an occupant compartment (e.g., towards the center of the vehicle).

(24) Although not shown in FIG. 2, in some embodiments, a deflector is included at the rear of the wheel well of wheel **250**. For example, as illustrated in FIGS. 7-10, a deflector may be configured to further direct wheel **250** away from the occupant compartment to prevent intrusion. In a further example, a vehicle may include element **211** and crossmember **215**, mount **221**, and the deflector, on one or both sides of the vehicle, to mitigate intrusion during a small overlap collision.

(25) FIGS. 3-4 illustrate structures for managing loads in a front crash. For example, FIG. 3 illustrates an illustrative wedge and crossmember assembly that may correspond to panel **550** of FIG. 5 (e.g., a welded steel wedge). In a further example, FIG. 4 illustrates deformation of a wedge and crossmember assembly that may correspond to panel **500** of FIG. 5 (e.g., an extruded wedge). Any suitable structure (e.g., wedge and crossmember), having any suitable construction, may be used in accordance with the present disclosure.

(26) FIG. 3 shows a perspective view, from above, of an illustrative structure for managing lateral loads in a front crash, in accordance with some embodiments of the present disclosure. For example, the structure of FIG. 3 may be included in vehicle **101** of FIG. 1 to generate lateral forces and displacement.

(27) Vehicle portion **300** includes bumper assembly **305**, plates **303** and **304**, frame members **301** and **302**, and a structure that includes wedges **311** and **312** and crossmember **315**. Bumper system **305** interfaces to plates **303** and **304**, which may be part of, or are otherwise affixed to, respective frame members **301** and **302**. Frame members **301** and **302** extend substantially longitudinally along vehicle portion **300**, although frame members **301** and **302** may exhibit some curvature or other non-linear shape. In an illustrative example, and as illustrated, frame members **301** and **302** may include tubing having a cross-sectional shape indicative of a rounded rectangle.

(28) In some embodiments, each of wedges **311** and **312** includes a composition of three stamped pieces affixed together. For example, to illustrate, the wedge may include steel stampings of cold stamped dual-phase DP980 grade (e.g., having a yield strength of approximately 700 MPa and an ultimate tensile strength of approximately 1000 MPa) spot-welded to each other at multiple locations to form the wedge. In some embodiments, each of wedges **311** and **312** is connected to plates **303** and **304**, respectively (e.g., Steel HSLA 500 plates) joining bumper system **305** and the front rail assembly (e.g., frame members **301** and **302** running longitudinally along the vehicle,

front to back).

(29) In an illustrative example, crossmember **315** extends between the front rails (e.g., frame members **301** and **302**, as illustrated) which is secured (e.g., MIG welded, otherwise welded, or otherwise affixed) to both frame members **301** and **302**. In some embodiments, for example, crossmember **315** may include martensite steel with the nomenclature MS 1500, a yield strength of approximately 1100 MPa, and an ultimate tensile strength of approximately 1500 MPa.

(30) In an illustrative example, during the event of a 25% overlap crash on the same side of the vehicle as wedge **311**, the bumper beam (of bumper system **305**) rotates onto wedge **311** in order to provide the required moment to rotate wedge **311** and line up against crossmember **315**. This allows the vehicle structure to provide a lateral push to the vehicle with sufficient lateral forces acting against it. In some embodiments, the middle reinforcement in wedge **311** lines up against crossmember **315** (e.g., in the center of crossmember **315** vertical-wise) so that the stack-up is near perfect in terms of a push along the “Y” axis. The middle reinforcement may include a horizontal plate (e.g., spot-welded to the lateral sides of wedge), a set of ribs and spines, any other suitable features, or any combination thereof. As illustrated, the ends of the crossmember are angled such that the front length of the crossmember is shorter than the rear length. For example, the side of crossmember **315** nearest bumper system **305** is shorter than the rear side. This tapering may improve, for example, engagement of either of wedges **311** or **312** with the respective end of crossmember **315** (e.g., prevent glancing contact).

(31) Wedges **311** and **312** each include a first face arranged along a laterally outer edge of the respective frame member (e.g., of frame members **301** and **302**) and a second face affixed to the respective bumper plate (e.g., of plates **303** and **304**), which are arranged along bumper system **305** (e.g., bolted against bumper system **305**). The first face and the second face are arranged at approximately 90° to each other, forming a wedge angle of approximately 90°. In an illustrative example, the wedge angle is configured to decrease when the wedge is loaded (e.g., the second face deflects towards the first face during the small overlap collision), thus elongating the wedge longitudinally via deformation, causing the wedge to engage with crossmember **315**.

(32) FIG. 4 shows two bottom views (e.g., panels **400** and **401**) of an illustrative structure for managing lateral loads in a front crash, before and during an impact, in accordance with some embodiments of the present disclosure. Panel **400** shows a configuration just before a small overlap collision, and panel **401** shows a configuration during the small overlap collision. As illustrated in panels **400** and **401**, the structure (e.g., which may be similar to the structure illustrated in FIG. 3) includes bumper assembly **405**, frame member **402** (e.g., which interfaces to bumper assembly **405**), element **411** (e.g., a “wedge”), and crossmember **415**. Frame member **402** extends substantially longitudinally along the vehicle and may exhibit some curvature or other non-linear shape. The structure may allow for improved energy absorption in an event of crash and an initial lateral push of the vehicle in the “Y” direction. To illustrate, the rigid barrier (e.g., a building, vehicle, or other substantially rigid barrier) impacts the vehicle, and bumper system **405** loads frame member **402** and element **411**. During the collision event, element **411**, which may deform under loading, engages and applies lateral force to cross member **415** in the “Y” direction. The lateral force causes the vehicle to move in the “Y” direction, away from the rigid barrier. Element **411** is illustrated and annotated in further detail in FIG. 5.

(33) FIG. 5 shows illustrative structures for managing lateral loads in a front crash, in accordance with some embodiments of the present disclosure. Panel **500** shows a configuration, without deformation, of illustrative element **511** (e.g., a “wedge”), frame member **502**, bumper interface **501**, and cross-member **515**. Spines **521** and **531** of element **511** are configured and arranged to, upon loading in direction **510** during a small overlap collision, align with the forward and rear edges of the near end of crossmember **515**, thus imparting lateral loading on the end of crossmember **515** (e.g., to cause lateral displacement). Because spines **521** and **531** are relatively stiff (e.g., further stiffened by ribs **541**, of which several are indicated in panel **500**), they are able

to impart load onto crossmember **515** rather than deforming significantly themselves. In an illustrative example, element **511** may be formed by extruding aluminum (e.g., and any suitable subsequent processing or machining). For example, a single length of extruded aluminum having a profile as shown on the top of element **511** can be cut into multiple wedges that can be used on both lateral sides of the vehicle. Using an extrusion technique provides a low cost and simple process for manufacturing the wedges. In addition, using extruded aluminum provides a weight savings compared to a wedge made out of steel. In a further illustrative example, element **511** may be secured to bumper interface **501** (e.g., using fasteners, bonding, mechanical locking, or any other suitable technique). In a further illustrative example, element **511** is not secured to frame member **502** to allow avoid longitudinal constraint of element **511** by frame member **502** (e.g., which might impact alignment of spines **521** and **531** with the end of crossmember **515**). In some embodiments, a top plate, a bottom plate, or both may be affixed to (e.g., welded to or otherwise fastened to) element **511** (e.g., or a top of a sidewall, spine, and/or ribs thereof). For example, the top plate or bottom plate may include features for securing to body elements (e.g., a hood support, fender bracket, or other component).

(34) Fasteners **503** secure element **511** to bumper interface **501**, and may include, for example, threaded nuts and bolts, threaded studs and nuts, screws, rivets, mechanical interlocks, welds, any other suitable affixment, or any combination thereof. Features **504** are configured to affix other components (e.g., a fender bracket or other body element). In some embodiments, element **511** includes a plurality of holes arranged in wall adjacent bumper interface **501** for coupling element **511** to bumper interface **501** of the vehicle. In some embodiments, the wall of element **511** arranged along frame element **502** and does not include holes for affixing to the frame element **502**.

(35) Element **511** is configured for generating side loads in a vehicle during a small-offset collision and is configured to be arranged laterally outside of a longitudinal frame element of the vehicle. In some embodiments, element **511** includes a sidewall (e.g., forming a wedge-shaped structure). The sidewall includes a first wall longitudinally oriented (e.g., along frame member **502**), a second wall laterally oriented (e.g., along bumper interface **501**), and a first spine (e.g., spine **521**) angled to connect the first wall and the second wall. The structure also includes a second spine (e.g., spine **531**) substantially parallel to the first spine, arranged inside of the sidewall. The structure also includes a plurality of ribs (e.g., ribs **541**) connecting the first spine and the second spine, connecting the second spine to the first wall and the second wall, or both. The structure is configured to deform when a load is applied to the second wall such that the first spine and the second spine align with an end of the crossmember to impart a lateral force on the crossmember. For example, in some embodiments, a profile of the sidewall, the second spine, and the plurality of ribs is made from extruded aluminum. Element **511**, as illustrated, is configured to define when the load is applied to the wall adjacent bumper interface **501** such that spines **521** and **531** are configured to align with respective walls of crossmember **515**.

(36) In some embodiments, spine **521** meets the wall of element **511** adjacent frame member **502** at a curved interface. In some embodiments, spine **521** meets the wall of element **511** adjacent bumper interface **501** at a curved interface. For example, element **511** may be substantially wedge shaped and include curved or segmented regions where walls meet. In a further example, in some embodiments, element **511** includes third wall longitudinally oriented to connect spine **521** and the wall of element **511** adjacent bumper interface **501**.

(37) In some embodiments, spines **521** and **531** have stiffnesses sufficient to transfer load to crossmember **515**. Ribs **541** have stiffnesses to substantially maintain a distance between spines **521** and **531**, maintain alignment of spines **521** and **531** with crossmember **515** during the small offset collision, or both.

(38) In some embodiments, element **511** is formed by extruding aluminum along an axis, and then cutting the extrusion to form the structure. A billet is extruded along the axis to form a first extrusion having a first length and a cross-section. The cross-section (e.g., the profile) includes a

sidewall having a first wall longitudinally oriented (e.g., configured to be arranged along frame member **502**), a second wall laterally oriented (e.g., configured to be arranged along bumper interface **501**), and a first spine (e.g., spine **521**) angled to connect the first wall and the second wall. The cross-section also includes a second spine (e.g., spine **531**) and a plurality of ribs (e.g., ribs **541**). The second spine is substantially parallel to the first spine and arranged inside of the sidewall. The plurality of ribs connect the first spine and the second spine, connect the second spine to the first wall and the second wall, or both. The structure is configured to deform when a load is applied to the second wall such that the first spine and the second spine align with an end of a crossmember (e.g., crossmember **515**) to impart a lateral force on the crossmember. The method includes cutting the extrusion at a first position along the axis, and then cutting the extrusion at a second position along the axis a predetermined length from the first position to form the structure. For example, the predetermined length defines the height of the structure when installed in a vehicle (e.g., from top to bottom, as illustrated). In some embodiments, the technique includes forming a plurality of through features in the second wall for securing the structure to a vehicle (e.g., to accommodate fasteners **503**). For example, the through features may include drilled holes or slots, machined holes or slots, any other suitable opening, or any combination thereof. In some embodiments, the method includes welding or otherwise securing (e.g., fastening) a top plate to a top side of the structure (not shown), a bottom plate to a bottom side of the structure (not shown), or both. For example, the top side and the bottom side are separated by the predetermined length.

(39) Panel **550** shows element **560** made of sheet metal. Element **560** includes top sheet **551**, middle sheet **552**, and bottom sheet **553**, with lateral sheet **554** extending around the sides of element **560**. For example, to contrast, element **560** does not include a rib-spine structure such as element **511** of panel **500**. In some embodiments, element **560** is made of steel sheet, cut and/or bent to a suitable shape and secured (e.g., spot welded). Middle sheet **552** provides stiffness to transfer to load to an end of a crossmember without undergoing significant deformation (e.g., element **560** is sufficiently stiff to impart a lateral load onto an end of the crossmember).

(40) In some embodiments, the present disclosure is directed to a structure (e.g., element **560**) that includes a sidewall (e.g., forming a wedge-shaped structure) including a first wall longitudinally oriented, a second wall laterally oriented, and a third wall angled to connect the first wall and the second wall. The structure includes a top plate (e.g., top sheet **551**) arranged on top of and affixed to the sidewall, a bottom plate (e.g., bottom sheet **553**) arranged below and affixed to the sidewall, and an intermediate plate (e.g., middle sheet **552**) arranged between the top plate and the bottom plate. The structure is configured to deform when a load is applied to the second wall such that the intermediate plate aligns with an end of the crossmember to impart a lateral force on the crossmember. For example, in some embodiments, the sidewall, the top plate, the bottom plate, and the intermediate plate are made of sheet steel. In a further example, the sidewall, the top plate, the bottom plate, and the intermediate plate are spot welded to form the structure. In some embodiments, the intermediate plate (e.g., middle sheet **552**) has a stiffness sufficient to transfer load to the crossmember.

(41) In some embodiments, element **560** is formed by stamping, pressing, laser-cutting, plasma-cutting, water-jet cutting, or otherwise cutting sheet steel to form one or more cutouts. The one or more cutouts are folded, bent, or otherwise formed to generate a structure, and the one or more cutouts are welded at one or more locations to secure the structure.

(42) As shown in FIGS. **1-5**, a lateral load may be imparted to a vehicle to reduce intrusion into an occupant compartment. During the collision event, the wheel may be loaded rearward, and thus may approach an occupant compartment. In some embodiments, the present disclosure is directed to systems and structures for managing the kinematics of the wheel to direct the wheel away from the occupant compartment as least partially. FIGS. **6-7** illustrate a control arm mount configured to break-away to manage kinematics of the wheel.

(43) FIG. **6** shows a top view of illustrative mount **601** having break-away region **605**, before (e.g.,

arrangement **600**) and after (e.g., arrangement **650**) failure of break-away region **605**, in accordance with some embodiments of the present disclosure. Mount **601** (e.g., which may be similar to mount **221** of FIG. 2) includes through feature **602** (e.g., a slot as illustrated, although any suitable through feature may be included), and break-away region **605** (e.g., defined at least in part by notch **604** and notch **603**, as illustrated). As illustrated, pin **699**, which is coupled to a lower control arm, is arranged in through feature **602**. For example, in arrangement **600** (e.g., a pre-collision arrangement), pin **699** is constrained to lateral displacement within through feature **602** (e.g., pin **699** can move within the slot under loading). Notches **603** and **604** introduce relatively weakened regions (e.g., the regions between each notch and through feature **602**) in terms of tensile strength as compared to a mount not having the notches. For example, notch **603**, notch **604**, and through feature **602** define break-away region **605**.

(44) Break-away region **605** exhibits a reduced tensile strength at its boundary and is configured to fail under a collision event to allow pin **699** to move laterally out of through feature **602**, as illustrated in arrangement **650**. In some embodiments, break-away region **605** is configured to fail and release pin **699** during the collision event by fracturing. In some embodiments, break-away region **605** is configured to fail and release pin **699** during the collision event by plastically deforming and opening through feature **602** to a boundary of mount **601**. In an illustrative example, referencing arrangement **600**, pin **699** may be loaded by a force in direction **610** (e.g., or other suitable direction). Pin **699** transmits the load to mount **610**, and the resultant load causes break-away region **605** to fail, as illustrated in arrangement **650**. In arrangement **650**, for example, pin **699** is no longer constrained laterally by through feature **602**. In an illustrative example, break-away region **605** may be configured to fail under a loading of 100 kN, 150 kN, or any other suitable loading in accordance with the present disclosure. It will be understood that notch **603** and **604** may include any suitable cross-sectional shape, having any suitable geometric properties, to define a break-away region of a mount, in accordance with the present disclosure.

(45) FIG. 7 shows a perspective view of an illustrative system including part of lower control arm **730** (e.g., which may be the same as or similar to lower control arm **230** of FIG. 2), and mount **701** (e.g., which may be similar to mount **221** of FIG. 2) having a break-away region (e.g., defined by through feature **713** and **714**), in accordance with some embodiments of the present disclosure. Mount **701**, as illustrated includes a top section (e.g., section **710**, which is the top of a C-shaped mount as illustrated) and a bottom section (e.g., section **720**, which is the bottom of a C-shaped mount as illustrated). In some embodiments (not illustrated in FIG. 7), the top and bottom sections may be separate components such as separate plates (e.g., rather than plates/sections of a C-shaped structure). Mount **701** couples control arm **730** to frame member **740**. For example, as illustrated, pin **799** constrains lateral displacement of the front portion of control arm **730**. In a further example, pin **799** and the end of lower control arm **730** may form a ball joint or other suitable joint for connecting control arm **730** to mount **701**. In some embodiments, pin **799** may be considered part of mount **701** (e.g., a mount may include a bracket and joint structure). Mount **701** is rigidly affixed to frame member **740**, and thus mount **701** is constrained from displacement relative to frame member **740**.

(46) Section **710** includes a through feature that is configured to accommodate pin **799** and constrain lateral displacement of pin **799** during normal operation. Section **710** also includes features **713** and **714**, illustrated as notches in FIG. 7, which define a break-away region (e.g., similar to break-away region **605** of FIG. 6). The break-away region exhibits a reduced tensile strength at its boundary and is configured to fail under a collision event to allow pin **799** to move laterally out of the through feature of section **710**. Section **720** also includes a through feature (not visible in FIG. 7) that is configured to accommodate pin **799** and constrain lateral displacement of pin **799** during normal operation. Section **720** also includes features for defining a break-away region (e.g., similar to the break-away region of section **710**), but the features are not visible in FIG. 7 (e.g., hidden by control arm **730**).



(47) In an illustrative example, a system for managing wheel kinematics during a collision event may include a recess arranged in a frame member, a pin arranged vertically in the recess, a top plate, and a bottom plate. The pin (e.g., pin **799**) may be configured to couple a lower control arm (e.g., lower control arm **730**) to the frame member and constrain vertical displacement of the lower control arm relative to the frame member. For example, the frame member may include one or more beams, mounts, any other suitable structural components, or any combination thereof (e.g., frame member **740** and mount **701** may be combined and referred to as a frame member). The top plate, the bottom plate, or both may include respective through features configured to accommodate the pin and constrain lateral motion of the pin. Further, the top plate, the bottom plate, or both may include a respective break-away region having a reduced stiffness configured to fail under the collision event to allow the pin to move laterally out of the through feature.

(48) As illustrated, features **713** and **714** are notches. Any suitable through or recess feature may be included to define a break-away region of section **710**, section **720**, or both. For example, features include blind or through holes, blind or through slots, blind or through notches, and other suitable blind or through features, or any combination thereof that define a break-away region. To illustrate, the break-away region is configured to fail (e.g., plastically deform, fracture, or otherwise fail) during a small overlap collision (e.g., under loading experienced during the collision). To further illustrate, in some embodiments, the break-away region is configured to fail under a load of 100 kN (or any other suitable threshold).

(49) In an illustrative example, a lower control arm (e.g., lower control arm **230** of FIG. 2, or lower control arm **730** of FIG. 7) or “A-arm” may be designed to pull out of a mount at about 40 ms into the collision event such that the wheel follows a trajectory based on kinematics. For example, other joints (e.g., rear mount **233** of FIG. 2, a lower control arm-to-knuckle joint, an upper control arm-to-knuckle joint, a tie-rod-to-knuckle joint, any other suitable joint, or any combination thereof) may be included to couple lower control arm **230** to the frame member and govern the kinematics after pull out.

(50) In some embodiments, a lower control arm (e.g., lower control arm **230** of FIG. 2, lower control arm **730** of FIG. 7) may be constructed of an aluminum material (e.g., forged aluminum 6110 T6). The lower control arm may be configured to pull out of a subframe clevis (e.g., of mount **221** of FIG. 2, mount **601** of FIG. 6, or mount **701** of FIG. 7). For example, the mount may be constructed of aluminum (e.g., 6008 T79 grade aluminum), and may be configured to fracture at about 40 ms into the collision event (e.g., with suitable strain values). In an illustrative example, the clevis (e.g., which includes the features defining the break-away region) may include a 3 mm slot, both at the top and bottom. When loaded by the collision event in tension with 150 kN of force in the cross-car direction, the clevis fractures the slot constraining the pin to pull the lower control arm out of the slot, thus assisting kinematics of the wheel. To further illustrate, the clevis (e.g., mount **221** of FIG. 2, mount **601** of FIG. 6, or mount **701** of FIG. 7) may be MIG-welded to the rest of an aluminum 6008 T79 subframe. In some embodiments, the lower control arm is secured against the subframe clevis by a fastener, optionally with a preload. For example, the lower control arm may be secured against the subframe clevis with an M16 bolt, under a preload of 80 kN, with a bushing arranged around the bolt to improve, maintain, or otherwise impact vehicle suspension performance. To illustrate, the subframe clevis may be configured to exhibit material fracture in order to release the pin and release the lower control arm at a suitable loading under collision (e.g., at 150 kN of crash loads in the lateral direction).

(51) To illustrate, the break-away region allows management of wheel kinematics to avoid the wheel stacking up against a hinge pillar and rocker of the vehicle. The reduction in loading against the hinge pillar provides for reduced intrusion into the occupant compartment, the battery pack structure (e.g., of an electric vehicle), or both. For example, referencing FIG. 2, if lower control arm **230** rotated about pin **299** (e.g., did not break-away), wheel **250** would be directed inward. By breaking away, lower control arm **230** causes wheel **250** to take a path that stays further outside

(laterally) than a path wheel **250** would take if lower control arm **230** did not break-away.

(52) As shown in FIGS. **1-5**, a lateral load may be imparted to a vehicle to reduce intrusion into an occupant compartment. During the collision event, the wheel may be loaded rearward, and thus may approach an occupant compartment. As shown in FIGS. **6-7**, in some embodiments, the present disclosure is directed to systems and structures for managing the kinematics of the wheel to direct the wheel away from the occupant compartment as least partially. FIGS. **8-11** illustrate a deflector configured to further manage kinematics of the wheel by deflecting it away from the occupant compartment.

(53) FIG. **8** shows a bottom view of a portion of illustrative vehicle **800** having wheel deflector **860**, in accordance with some embodiments of the present disclosure. FIG. **9** shows a bottom view of a portion of illustrative vehicle **800** of FIG. **8** with frame coupling **804** removed, in accordance with some embodiments of the present disclosure. FIG. **10** shows a perspective view of a portion of illustrative vehicle **800** of FIG. **8**, with wheel **850** removed, in accordance with some embodiments of the present disclosure. Vehicle **800** includes wheel **850** affixed to mounting system **852**, wheel well **851**, body system **802**, frame system **803**, frame coupling **804**, and deflector **860**. For example, mounting system **852** may include a spindle, control arms, suspension components, braking components, steering components, structural components, any other suitable components, or any suitable combination thereof. In a further example, wheel **850** and at least some of mounting system **852** are arranged in wheel well **851**. In a further example, body system **802** may include an occupant compartment. In a further example, frame system **803** may include a structural frame and a battery system, suspension system, steering system, electrical system, any other suitable system, or any suitable combination thereof.

(54) During a small offset collision event, wheel **850** may be loaded in direction **810** (e.g., as illustrated in FIGS. **8** and **10**). As wheel **850** is displaced relative to wheel well **851** during a collision event, wheel **850** approaches deflector **860**. Deflector **860** is configured to absorb some energy from wheel **850** (e.g., by plastically deforming). For example, the structure of deflector **801** may be designed with ribs and hollow portions (e.g., to result in a stiffness) to buckle or deform under loading. Further, section **861** (e.g., an angled portion) of deflector **860** is configured to cause wheel **850** to deflect away from frame system **803**, an occupant compartment of body system **802**, or both.

(55) Referencing FIG. **9**, wherein frame coupling **804** is removed, absorber **870** is shown arranged between deflector **860** and frame system **803**. Absorber **870** is arranged behind frame coupler **804**, as illustrated, and configured to further absorb energy from deflector **860** that arises from wheel **850**. In some embodiments, absorber **870** need not be included or may otherwise be included as part of deflector **860**. Components such as wheel **850** that may impact deflector **860** may have sufficient energy to otherwise intrude into the occupant compartment of body system **802** if (i) that energy is not partially absorbed by deflector **860**, absorber **870**, or both, or if (ii) the component is not otherwise deflected away from frame system **803**, body system **802**, or both. In an illustrative example, absorber **870** is arranged behind section **862** and is configured to further absorb energy from the collision event by plastically deforming.

(56) Referencing FIG. **10**, wherein wheel **850** is removed, hinge pillar **805** of body system **802** is shown more clearly. Further, occupant compartment **840** is illustrated in FIG. **10** (e.g., occupant compartment **840** is not visible in FIGS. **8-9**, both of which include bottom views). Mounting system **852** remains in place in FIG. **10** (e.g., and includes a rotor, caliper assembly, spindle, suspension arms, etc.).

(57) FIG. **11** shows a perspective view of deflector **860** of FIG. **8**, in accordance with some embodiments of the present disclosure. Deflector **860** includes holes **864** and **865** for mounting to body system **802** or a member thereof, holes **866** and **867** for accessing mounting holes (not visible in FIG. **6**) for mounting deflector **860** to frame coupler **804**, feature **868** (e.g., for attaching a wheel well liner or inner fender), section **861**, section **862**, and section **863**. In some embodiments, for

example, deflector **860** is an aluminum extrusion (e.g., with at least some recess features and through features machined after extrusion).

(58) In some embodiments, deflector **860** is configured to allow spokes or other features of wheel **850** to move away from occupant compartment **840** such that wheel **850** does not get caught up between the barrier and occupant compartment **840**, which might cause large intrusions in the footrest and toe-pan region.

(59) In some embodiments, deflector **860**, absorber **870**, and frame coupler **804** form a system for deflecting wheel **850**. In some such embodiments, the system is affixed to four structures: a portion of wheel well **851**, frame member **803**, a portion of body system **802**, and hinge pillar **805**. In an illustrative example, deflector **860**, absorber **870**, or both may be constructed of (e.g., extruded from) aluminum. To further illustrate, deflector **860**, absorber **870**, or both may be constructed of aluminum of grade 6008 T74 temper with a yield strength of 275 MPa, an ultimate tensile strength of 320 MPa, and a total elongation of 12%. In some embodiments, for example, frame coupler **804** is configured (e.g., hot stamped) to achieve a Yield strength of 1000 MPa and an Ultimate tensile strength of 1500 MPa with total elongation of about 7% (e.g., frame coupler **804** may be a steel-press-hardened stamping). To illustrate, deflector **860** and absorber **870** may be extrusions of multiple thicknesses ranging from 2.5 mm to 6.5 mm, while frame coupler **804** may include a steel stamped part (e.g., having a thickness of 2.4 mm or any other suitable thickness).

(60) In an illustrative example, deflector **860** is arranged between wheel well **851** and hinge pillar **805**, and is capable of transferring up to 500 kN loads in a crash event to hinge pillar **805** and frame coupling **804**, body system **802**, and frame system **803** so that intrusion into occupant compartment **840** may be mitigated.

(61) Deflector **860** includes tapered surface (e.g., section **861**) for engaging the wheel spokes and pushing them away from occupant compartment **840** during a small overlap offset crash. For example, in the context of an electric vehicle, a battery pack may be arranged underneath the floor of the vehicle (e.g., below occupant compartment **840**). Deflector **860**, absorber **870**, and frame coupler **804** enable wheel **850** to move away from the battery pack in the event of a small overlap crash. Further, deflector **860**, absorber **870**, and frame coupler **804** protect flanges or other features of hinge pillar **805** (e.g., where the spot welds may be prone to fracture). In some embodiments, deflector **860**, absorber **870**, and frame coupler **804** cause kinematics that prevent wheel **850** from stacking up against hinge pillar **805** and a rocker of body system **802** thus allowing for lessened intrusion into occupant compartment **840**, a battery pack structure, or both.

(62) In some embodiments, deflector **860** includes section **862** arranged at an inside wall of wheel well **851** and substantially facing wheel **850**. Section **862** includes, for example, a hollow structure configured to absorb energy from the collision event by plastically deforming. In some embodiments, deflector **260** includes section **861** arranged at an angle to wheel **850** (e.g., and section **862**) and configured to deflect wheel **850** laterally outwards from the vehicle to prevent intrusion of the wheel into occupant compartment **840** during the collision event.

(63) In an illustrative example, deflector **860** includes a set of through features (e.g., holes **864** and **865**) configured to accommodate a corresponding set of fasteners affixed to the hinge-pillar. In some embodiments, deflector **860** includes a set of through features (e.g., holes **866** and **867**) configured to accommodate a corresponding set of fasteners affixed to a rear of wheel well **851**.

(64) In an illustrative example, frame coupler **804** is arranged behind section **862** and is configured to affix a frame system (e.g., frame member **803**) and body system **802**, which forms occupant compartment **840**. Absorber **870** may be arranged behind frame coupler **804** and may be configured to further absorb energy from the collision event by plastically deforming.

(65) In an illustrative example, wheel **850** may include a plurality of radial spokes, and deflector **860** may be configured to deflect the plurality of spokes away from occupant compartment **840** during the collision event. In a further example, wheel mount **852** may include a lower control arm (e.g., similar to lower control arm **230** of FIG. 2 or lower control arm **730** of FIG. 7) configured to

direct the plurality of radial spokes to deflector **860** during the collision event.

(66) In an illustrative example, a system for managing wheel kinematics during a collision event of a vehicle may include a frame system (e.g., including frame member **802**), a body system (e.g., body system **803**), a frame coupler (e.g., frame coupler **804**), and a deflector (e.g., deflector **860**). The frame system may include a first pillar (e.g., hinge pillar **805**) arranged at first position at a rear and laterally outside portion of a wheel well (e.g., wheel well **851**). The body system includes an occupant compartment (e.g., occupant compartment **840**). The frame coupler (e.g., frame coupler **804**) at least partially affixes the frame system to the body system. The deflector is affixed to the frame coupler and faces the wheel (e.g., wheel **850**). The deflector includes a first section (section **862**) having a hollow structure configured to absorb energy from the collision event by plastically deforming, and a second section (e.g., section **861**) arranged at an angle to the wheel and configured to deflect the wheel laterally outwards from the vehicle to prevent intrusion of the wheel into the occupant compartment during the collision event.

(67) The foregoing is merely illustrative of the principles of this disclosure, and various modifications may be made by those skilled in the art without departing from the scope of this disclosure. The above described embodiments are presented for purposes of illustration and not of limitation. The present disclosure also can take many forms other than those explicitly described herein. Accordingly, it is emphasized that this disclosure is not limited to the explicitly disclosed methods, systems, and apparatuses, but is intended to include variations to and modifications thereof, which are within the spirit of the following claims.

## Claims

1. An apparatus comprising: a crossmember having an end that extends outboard through a frame member of a vehicle; and a structure comprising a rear portion spaced away from the end of the crossmember and further comprising a sidewall oriented longitudinally, wherein: the structure is arranged outboard of the frame member and forward of the end of the crossmember such that the sidewall faces an outbound side of the frame member and such that a forward end of the sidewall is spaced closer to the outbound side of the frame member than the rear portion; and the structure is configured to deform during an impact event such that the rear portion engages the end of the crossmember to apply a force on the end of the crossmember.
2. The apparatus of claim 1, wherein the force comprises a lateral force, and wherein the rear portion comprises a rear curved corner configured to deform towards the end of the crossmember during the impact event to apply the lateral force on the end of the crossmember.
3. The apparatus of claim 2, wherein the rear curved corner is spaced away from the frame member.
4. The apparatus of claim 1, wherein the rear portion comprises a rear curved corner configured to deform towards and engage a forward edge of the end of the crossmember during the impact event.
5. The apparatus of claim 1, wherein the impact event comprises a small overlap collision.
6. The apparatus of claim 1, wherein the structure comprises an internal spine and a plurality of ribs.
7. The apparatus of claim 6, wherein the internal spine extends between a front sidewall and a side sidewall of the structure.
8. The apparatus of claim 6, wherein the structure is configured to deform such that the internal spine aligns with the end of the crossmember to impart a lateral force on the crossmember.
9. The apparatus of claim 1, wherein the end of the crossmember comprises a forward edge and a rear edge.
10. The apparatus of claim 1, wherein the end of the crossmember is angled such that a front length of the crossmember is shorter than a rear length.
11. The apparatus of claim 1, wherein the structure comprises a wedge shape comprising a width that decreases towards the rear portion.

12. The apparatus of claim 1, wherein the crossmember is rigidly affixed to the frame member.

13. The apparatus of claim 1, wherein the crossmember extends through an opening in the frame member.

14. A frame system of a vehicle, comprising: a crossmember comprising: a first end that extends outboard through a first frame member of the vehicle; and a second end that extends outboard through a second frame member of the vehicle; and a structure comprising a rear portion spaced away from the first end of the crossmember and further comprising a sidewall oriented longitudinally, wherein: the structure is arranged outboard of the first frame member and forward of the first end of the crossmember such that the sidewall faces an outbound side of the first frame member and such that a forward end of the sidewall is spaced closer to the outbound side of the first frame member than the rear portion; and the structure is configured to deform during an impact event such that the rear portion engages the first end of the crossmember to apply a force on the first end of the crossmember.

15. The frame system of claim 14, wherein the structure comprises a first structure, the frame system further comprising: a second structure arranged outboard of the second frame member and forward of the second end of the crossmember, wherein: the second structure is configured to deform during an impact event and apply a force on the second end of the crossmember.

16. The frame system of claim 14, wherein the force comprises a lateral force, and wherein the rear portion comprises a rear curved corner configured to deform towards the first end of the crossmember during the impact event to apply the lateral force on the first end.

17. A vehicle comprising: a first frame member arranged on a first side of the vehicle; a second frame member arranged on a second side of the vehicle; a bumper system affixed to the first frame member and the second frame member, wherein the bumper system is configured to receive a small overlap impact; a crossmember laterally spanning the first frame member and the second frame member, wherein an end of the crossmember extends outboard through the first frame member; and a structure having a rear portion spaced away from the end of the crossmember, wherein the structure is arranged outboard of the first frame member and forward of the end of the crossmember, wherein: the structure is configured to deform during the small overlap impact such that the rear portion engages the end of the crossmember to apply a force on the end of the crossmember.

18. The vehicle of claim 17, wherein the structure comprises a first structure and the end of the crossmember comprises a first end and wherein a second end of the crossmember extends outboard through the second frame member, the vehicle further comprising: a second structure arranged outboard of the second frame member and forward of the second end of the crossmember, wherein: the second structure is configured to deform during the small overlap impact and apply a force on the second end of the crossmember.

---