United States Patent	12384335
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Ando; Yusuke

Vehicle control system

Abstract

A vehicle control system performs a first determination process to determine whether a first condition is satisfied, a second determination process to determine whether a second condition is satisfied, and a precedence process to gradually decrease a braking force of the vehicle by decreasing a braking force applied to a rear wheel preferentially over a braking force applied to a front wheel. The first condition includes at least a braking force condition that the braking force of the vehicle is greater than or equal to a predetermined braking force, and a turning condition that a turning degree of the vehicle is greater than or equal to a predetermined turning degree. The second condition is a condition that the vehicle is brought into a state where braking is to be cancelled while the first condition is being satisfied. The precedence process is performed when the second condition is satisfied.

Inventors:	**Ando; Yusuke (Tokyo, JP)**
Applicant:	**SUBARU CORPORATION** (Tokyo, JP)
Family ID:	**1000008747669**
Assignee:	**SUBARU CORPORATION (Tokyo, JP)**
Appl. No.:	**18/535017**
Filed:	**December 11, 2023**

Prior Publication Data

Document Identifier	Publication Date
US 20240208469 A1	Jun. 27, 2024

Foreign Application Priority Data

JP	2022-208400	Dec. 26, 2022

Publication Classification

Int. Cl.: B60W30/09 (20120101); **B60T7/12** (20060101); **B60T8/1755** (20060101); **B60W10/18** (20120101); B60W30/04 (20060101)

U.S. Cl.:

CPC **B60T7/12** (20130101); **B60T8/17554** (20130101); **B60T8/17558** (20130101); **B60W10/18** (20130101); **B60W30/09** (20130101); B60T2201/022 (20130101); B60W2030/043 (20130101)

Field of Classification Search

CPC: B60T (7/12); B60T (8/1755); B60T (8/17551); B60T (8/17554); B60T (8/17558); B60T (2201/022); B60W (30/09); B60W (2030/043)

USPC: 701/70; 701/72; 701/80

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2022/0105809	12/2021	Yamamoto	N/A	N/A
2022/0144229	12/2021	Yamamoto	N/A	B60T 8/1766
2022/0289157	12/2021	Leibbrand	N/A	B60T 17/221
2024/0017718	12/2023	Matsuo	N/A	B60W 30/045
2024/0067143	12/2023	Cameron	N/A	B60T 8/17552
2024/0308585	12/2023	Cho	N/A	B60T 7/12
2024/0343246	12/2023	Goetz	N/A	B60W 30/09

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2020-117216	12/2019	JP	N/A
2021-146808	12/2020	JP	N/A

Primary Examiner: Solis; Erick R

Attorney, Agent or Firm: TROUTMAN PEPPER LOCKE LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION
(1) The present application claims priority from Japanese Patent Application No. 2022-208400 filed on Dec. 26, 2022, the entire contents of which are hereby incorporated by reference.
BACKGROUND
(2) The disclosure relates to a vehicle control system to be applied to a vehicle including a braking unit that brakes the vehicle.
(3) Japanese Unexamined Patent Application Publication (JP-A) No. 2020-117216 discloses a

technique that controls a rolling motion of a vehicle by adjusting the distribution ratio of a braking force to a target wheel including at least one of a rear wheel on an inside during turning of the vehicle and a front wheel on an outside during turning of the vehicle when the braking force is applied to the vehicle under a situation where the vehicle is turning.

(4) Further, JP-A No. 2021-146808 discloses a technique that controls a posture of a vehicle by a torque vectoring control unit that adjusts a driving force or braking force of the left and right wheels to control turning driving, and a damping force control unit that corrects and controls damping force of a buffer (suspension) according to the roll of the vehicle body added by adjusting the driving force or the braking force by the torque vectoring control unit.

SUMMARY

(5) An aspect of the disclosure provides a vehicle control system to be applied to a vehicle. The vehicle including a braking unit configured to brake a vehicle. The vehicle control system includes one or more processors and one or more memories in which a program to be executed by the one or more processors is stored. The program includes one or more commands adapted to cause the one or more processors to perform a first determination process to determine whether a first condition is satisfied, perform a second determination process to determine whether the second condition is satisfied, and perform a precedence process to gradually decrease the braking force by decreasing a braking force applied to a rear wheel of the vehicle preferentially over a braking force applied to a front wheel of the vehicle. The first condition includes at least a braking force condition that a braking force of the vehicle is greater than or equal to a predetermined braking force, and a turning condition that a turning degree of the vehicle is greater than or equal to a predetermined turning degree. The second condition is a condition that the vehicle is brought into a state where braking by the braking unit is to be cancelled while the first condition is being satisfied. The precedence process is performed when the second condition is satisfied.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments and, together with the specification, serve to explain the principles of the disclosure.

(2) FIG. **1** is a diagram illustrating a schematic configuration of a vehicle including a vehicle control system according to one example embodiment of the disclosure.

(3) FIG. **2** is an explanatory diagram of an exemplary configuration of the vehicle control system according to one example embodiment of the disclosure.

(4) FIG. **3** is a flowchart of an exemplary procedure of contact avoidance control according to one example embodiment of the disclosure.

(5) FIG. **4** is a block diagram for describing an exemplary operation of the vehicle control system according to one example embodiment of the disclosure.

(6) FIG. **5** is a diagram illustrating a braking force decreasing process according to a comparative example.

(7) FIG. **6** is a diagram illustrating a braking force decreasing process according to one example embodiment of the disclosure.

(8) FIG. **7** is a diagram illustrating an exemplary method of determining whether a turning condition is satisfied, according to one example embodiment of the disclosure.

(9) FIG. **8** is a flowchart of an exemplary procedure adapted to achieve traveling stability control according to one example embodiment of the disclosure.

(10) FIG. **9** is a flowchart of an exemplary procedure adapted to achieve traveling stability control according to a modification example of the disclosure.

DETAILED DESCRIPTION

(11) It is desirable to provide a vehicle control system that makes it possible to improve vehicle traveling stability.

(12) In the following, some example embodiments of the disclosure are described in detail with reference to the accompanying drawings. Note that the following description is directed to illustrative examples of the disclosure and not to be construed as limiting to the disclosure. Factors including, without limitation, numerical values, shapes, materials, components, positions of the components, and how the components are coupled to each other are illustrative only and not to be construed as limiting to the disclosure. Further, elements in the following example embodiments which are not recited in a most-generic independent claim of the disclosure are optional and may be provided on an as-needed basis. The drawings are schematic and are not intended to be drawn to scale. Throughout the present specification and the drawings, elements having substantially the same function and configuration are denoted with the same reference numerals to avoid any redundant description. In addition, elements that are not directly related to any embodiment of the disclosure are unillustrated in the drawings. As used herein, the term "collision" may be used interchangeably with the term "contact".

(13) FIG. **1** illustrates a schematic configuration of a vehicle **100** including a vehicle control system **1** according to an example embodiment of the disclosure. FIG. **2** illustrates an exemplary configuration of the vehicle control system **1** according to the example embodiment. FIG. **2** further illustrates an exemplary configuration of a steering mechanism **30** included in the vehicle **100** as well as the exemplary configuration of the vehicle control system **1**.

(14) In the example embodiment, the vehicle **100** may be a four-wheeled vehicle, for example. The vehicle **100** may include one or both of an engine and a traveling motor as a drive source or drive sources of the wheels. That is, the vehicle **100** may be an electric vehicle (EV) including only a traveling motor as a drive source of the wheels, a hybrid electric vehicle (HEV) including both of an engine and a traveling motor as drive sources of the wheels, or an engine vehicle including only an engine as a drive source of the wheels.

(15) The vehicle **100** may include a non-illustrated braking unit that brakes the vehicle **100**, and a steering unit (the steering mechanism **30** to be described later) that causes the vehicle **100** to turn in a desired direction.

(16) The term "braking unit" used herein may refer to not only a brake mechanism such as a disk brake or a drum brake and also a configuration that performs brake control of the vehicle **100** using regenerative braking of the traveling motor in a case where the vehicle **100** is an EV or a HEV, in a broad sense.

(17) The term "steering unit" used herein may refer to a configuration (e.g., the steering mechanism **30**) that causes the vehicle **100** to turn in any desired direction of right and left directions, in a broad sense.

(18) The vehicle **100** may include a device that recognizes an external environment of the vehicle **100**. In the example embodiment, the vehicle **100** may include an imaging device **10** that recognizes the external environment of the vehicle **100**, for example. The imaging device **10** will be described later.

(19) As illustrated in FIG. **1**, the vehicle control system **1** of the vehicle **100** includes a brake control unit **20** that performs control according to the example embodiment of the disclosure.

(20) The vehicle control system **1** may further include a driver assistance control processor **13** that performs various kinds of driver assistance control. The driver assistance control processor **13** may include a contact avoidance control unit **14**. As to be described later, the contact avoidance control unit **14** may conduct contact avoidance brake control on the vehicle **100**. The term "contact avoidance brake control" used herein may refer to control to avid contact of the vehicle **100** using the braking unit such as the brake mechanism. The contact avoidance brake control may encompass various kinds of brake control that involve a braking operation to avoid contact of the vehicle **100**,

such as autonomous emergency braking (AEB), and various kinds of brake control that involve a steering operation to avoid contact of the vehicle **100**, such as automatic emergency steering (AES).

(21) The vehicle control system **1** may further include an electronic stability control (ESC) unit **25**. The term "ESC" used herein may refer to control in which the braking unit and an engine output (including a motor output in a case of the vehicle **100** including a traveling motor) are controlled to maintain the vehicle **100** in a stable attitude without causing a skid of the vehicle **100**.

(22) As illustrated in FIG. **2**, the vehicle control system **1** may include a vehicle speed sensor **16**, a motion sensor **17**, an actual steering angle sensor **18**, and a steering torque sensor **19** as sensors relating to the contact avoidance control.

(23) The vehicle control system **1** may further include a display **23** and a sound generator **24** as devices relating to the contact avoidance control.

(24) The vehicle speed sensor **16** may detect an own vehicle speed v which is a speed of the vehicle **100**.

(25) The motion sensor **17** may collectively refer to sensors, including a yaw rate (angular velocity) sensor and an acceleration sensor, that detect motions of the vehicle **100**.

(26) The actual steering angle sensor **18** may detect actual cutting angles of steered wheels **40** (e.g., a right steered wheel **40**R and a left steered wheel **40**L to be described later) with respect to a longitudinal axis of the vehicle **100** as actual steering angles.

(27) The steering torque sensor **19** may detect input torque to a steering shaft **32** to thereby detect a steering force (steering input torque) inputted by a driver who drives the vehicle **100** via a steering wheel **34**, for example.

(28) The imaging device **10** may include imaging units **11**R and **11**L, an image processing unit **12**, and the driver assistance control processor **13**. The imaging units **11**R and **11**L may be disposed so as to capture an image of an environment in front of the vehicle **100** in a traveling direction.

(29) To the imaging device **10**, the vehicle speed sensor **16**, the motion sensor **17**, and the actual steering angle sensor **18** may be coupled. The image processing unit **12** and the driver assistance control processor **13** that are included in the imaging device **10** may be configured to receive detection signals from these sensors.

(30) To the imaging device **10**, an operation unit **26** may be coupled. The operation unit **26** may receive an operational input from the driver who drives the vehicle **100**, for example. This enables the image processing unit **12** and the driver assistance control processor **13** to execute a process in accordance with data on the operational input inputted by the driver with the operation unit **26**, for example.

(31) The imaging units **11**R and **11**L may be disposed in the vicinity of an upper portion of a windshield of the vehicle **100** at a predetermined interval in a vehicle width direction such that stereoscopic ranging is enabled, for example. The imaging units **11**R and **11**L may have respective optical axes parallel to each other, and respective focal lengths equal to each other. The imaging units **11**R and **11**L may further have respective frame periods synchronized with each other, and respective frame rates equal to each other.

(32) Electric signals (captured image signals) acquired by imaging elements of the imaging units **11**R and **11**L may be each converted by an analog-to-digital (A/D) conversion into a digital image signal (captured image data) indicating a luminance value based on a predetermined grayscale and on a pixel unit basis. The captured image data may be color image data, for example.

(33) The image processing unit **12** may include a microcomputer that includes a central processing unit (CPU), a read only memory (ROM), and a random access memory (RAM) serving as a work area, for example. The CPU may execute various processes according to programs stored in the ROM.

(34) The image processing unit **12** may store each frame of the captured image data on the environment in front of the vehicle **100** acquired by the imaging units **11**R and **11**L in an internal

memory. Thereafter, based on two frames of the captured image data, the image processing unit **12** may execute various processes to recognize the external environment of the vehicle **100**. For example, the image processing unit **12** may perform a process adapted to recognize objects present in front of the vehicle **100**, such as regulation lines (e.g., white lines or orange lines) on a road, preceding vehicles, pedestrians, obstacles, and various three-dimensional objects such as guardrails, curbs, or sidewalls that extend along a road.

(35) The term "regulation lines" used herein may refer to lines that divide a traveling lane of the vehicle **100**. Based on data on the recognized regulation lines, the image processing unit **12** may recognize the traveling lane of the vehicle **100** (hereinafter also referred to as an own vehicle traveling lane).

(36) To recognize a three-dimensional object present in front of the vehicle **100**, the image processing unit **12** may perform a process adapted to acquire distance data from a positional shift of an identical position (i.e., parallax) between a pair of the captured image data (i.e., a stereo image) acquired by the imaging units **11**R and **11**L based on a triangular ranging method. Based on the distance data, the image processing unit **12** may generate data indicating three-dimensional distance distribution (hereinafter referred to as distance image). Based on the distance image, the image processing unit **12** may perform a known grouping process to recognize regulation lines and three-dimensional objects such as guardrails, curbs, sidewalls, pedestrians, or vehicles, as described above.

(37) The image processing unit **12** may store the position of the recognized three-dimensional object as three-dimensional object position data. The three-dimensional object position data may indicate the position of the recognized three-dimensional object as position coordinates on an x-z coordinate system having a z-axis in the longitudinal direction of the vehicle **100** and an x-axis in the lateral direction (vehicle width direction) of the vehicle **100**. For example, the image processing unit **12** according to the example embodiment may store data on positions of right and left end points of a rear face of a three-dimensional object such as a preceding vehicle, a pedestrian, or an obstacle. The image processing unit **12** may further store a central position between the right and left end points of the rear face as data on a central position of the three-dimensional object.

(38) Further, the image processing unit **12** may calculate and store data on a longitudinal distance dz, a longitudinal relative speed vrz, a longitudinal speed vz, and a longitudinal acceleration rate az of the recognized three-dimensional object. The longitudinal distance dz may be a distance to the three-dimensional object in the z-axis direction. The longitudinal relative speed vrz may be an amount of change in the longitudinal distance dz per unit time. The longitudinal speed vz may be calculated by adding the own vehicle speed v to the longitudinal relative speed vrz. The longitudinal acceleration rate az may be a differential value of the longitudinal speed vz.

(39) Further, the image processing unit **12** may calculate and store data on a lateral distance dx, a lateral relative speed vrx, a lateral speed vx, and a lateral acceleration rate ax of the recognized three-dimensional object. The lateral distance dx may be a distance to the three-dimensional object in the x-axis direction. The lateral relative speed vrx may be an amount of change in the lateral distance dz per unit time. The lateral speed vx may be calculated by adding a lateral moving speed of the vehicle **100** to the lateral relative speed vrx. The lateral acceleration rate ax may be a differential value of the lateral speed vx.

(40) Among the three-dimensional objects recognized as vehicles, the image processing unit **12** may recognize a vehicle traveling closest to the vehicle **100** on the own vehicle traveling lane in substantially the same direction as the vehicle **100** as a preceding vehicle. If a traveling speed of the preceding vehicle is about zero kilometers per hour, the image processing unit **12** may recognize the preceding vehicle as being stopped.

(41) The information on the results of the image recognition, including the data on the position, speed, and acceleration rate of the three-dimensional object and the data on the own vehicle traveling lane, that are acquired by the image processing unit **12** as described above may be used in

various kinds of driver assistance control.

(42) Based on the information on the results of the image recognition by the image processing unit **12**, the driver assistance control processor **13** may perform various kinds of driver assistance control.

(43) The driver assistance control processor **13** may include the contact avoidance control unit **14**. The contact avoidance control unit **14** may include a microcomputer that includes a CPU, a ROM, and a RAM, for example. The contact avoidance control unit **14** may execute various kinds of processes according to programs stored in the ROM.

(44) In one example, the contact avoidance control unit **14** may perform processes relating to autonomous emergency braking (AEB) and automatic emergency steering (AES).

(45) In the contact avoidance control as the AEB or the AES, the contact avoidance control unit **14** may calculate a risk evaluation value representing the degree of a risk of contact with an object based on the results of recognition of the external environment of the vehicle **100** and determine a timing of braking intervention or a timing of steering intervention based on the degree of the risk of contact represented by the risk evaluation value.

(46) For example, the contact avoidance control unit **14** according to the example embodiment may calculate, as the risk evaluation value, time-to-contact (TTC) based on the longitudinal distance dz and the longitudinal relative speed vrz described above for each three-dimensional object recognized by the image processing unit **12**. The TTC may be an index indicating how many seconds remain for contact if the current longitudinal relative speed vrz is maintained. For example, the TTC may be calculated by the following expression:

(47) $TTC = dz / vrz$.

(48) As the value of the TTC serving as the risk evaluation value decreases, the degree of the risk of contact may increase.

(49) Based on the value of the TTC described above, the contact avoidance control unit **14** may determine whether there is a possible contact object in specific three-dimensional objects of interest among the three-dimensional objects recognized by the image processing unit **12**. The term "possible contact object" used herein may refer to an object estimated to come into contact with the vehicle **100**.

(50) The term "specific three-dimensional objects of interest" used herein may refer to three-dimensional objects including movable creatures such as people and animals (hereinafter collectively referred to as movable objects). In this example, the term "specific three-dimensional objects of interest" may refer to three-dimensional objects including movable objects except the three-dimensional object recognized as the preceding vehicle. Accordingly, the three-dimensional objects subjected to the contact avoidance control may therefore include guardrails, curbs, and sidewalls as described above.

(51) In one example, the determination regarding the presence of the possible contact object may be performed based on the TTC according to the following procedure.

(52) For example, the contact avoidance control unit **14** may determine whether the specific three-dimensional objects of interest include a three-dimensional object whose rate of overlapping with the vehicle **100** in the lateral direction is greater than or equal to a predetermined value and whose TTC is less than or equal to a predetermined threshold. If no appropriate three-dimensional object is present, the contact avoidance control unit **14** may determine that there is no possible contact object.

(53) If only one appropriate three-dimensional object is found in the determination described above, the contact avoidance control unit **14** may determine the three-dimensional object to be the possible contact object. If multiple appropriate three-dimensional objects are found, the contact avoidance control unit **14** may determine a three-dimensional object having the smallest TTC value among the multiple three-dimensional objects to be the possible contact object, for example.

(54) When the possible contact object is present, the contact avoidance control unit **14** may perform

the AEB and, if needed, the AES with respect to the possible contact object. For example, the contact avoidance control unit **14** may start only the AEB first, and may perform, when it is determined that contact is unavoidable only by the AEB, the steering intervention by conducting the AES to avoid the contact while maintaining the braking by the AEB.

(55) Upon the start of the AEB, the contact avoidance control unit **14** may send a brake command to the brake control unit **20** to brake the vehicle **100**.

(56) Upon the start of the AES, the contact avoidance control unit **14** may determine a target steering angle based on the results of the image recognition by the image processing unit **12**. Thereafter, the contact avoidance control unit **14** may output a steering command current value determined based on the target steering angle to an electric power steering (EPS) control unit **22** to be described later.

(57) The driver assistance control processor **13** may further make various notifications relating the driver assistance to the driver who drives the vehicle **100**. For example, the driver assistance control processor **13** may supply display information and sound generation command information to the display **23** and the sound generator **24**.

(58) The display **23** may collectively refer to a display control unit including a microprocessor, and a display device, for example. Examples of the display device may include various meters such as a speedometer or a tachometer provided in a meter panel disposed in front of the driver, a multi-function display (MFD), and other devices that present information to the driver. In the contact avoidance control, the display **23** may display a warning about danger of contact with an object or a visual indication that notifies the driver of a start or a stop of the AEB or AES.

(59) Further, the display **23** may display one or both of a notification that the electronic stability control by the ESC unit **25** has been enabled and a notification that the electronic stability control by the ESC unit **25** has been disabled.

(60) The term "enabling" control used herein may refer to making the control executable (allowable to execute). The term "disabling" control used herein may refer to making the control inexecutable (unallowable to execute).

(61) The sound generator **24** may collectively refer to a sound control unit including a microcomputer, and a sound generation device such as an amplifier or a speaker, for example. In the contact avoidance control, the sound generator **24** may output a warning sound that notifies the driver of a start or a stop of the AEB or AES, for example.

(62) The vehicle control system **1** may include a brake control unit **20** and a brake-related actuator **21** to achieve brake control of the vehicle **100**.

(63) The brake control unit **20** may include a microcomputer that includes a CPU, a ROM and a RAM, for example. The brake control unit **20** may control various actuators provided as the brake-related actuator **21**. Examples of the brake-related actuator **21** may include various kinds of brake-related actuators including a hydraulic control actuator that controls the hydraulic pressure of an output from a brake booster to a master cylinder and a hydraulic pressure inside a brake liquid pipe.

(64) In the example embodiment, the vehicle speed sensor **16**, the motion sensor **17**, and the actual steering angle sensor **18** may be coupled to the brake control unit **20**. The brake control unit **20** may receive detection signals from these sensors.

(65) The brake control unit **20** may include an anti-lock brake system (ABS) processor **20***a*. During braking the vehicle **100**, the ABS processor **20***a* may control the above-described hydraulic control actuator based on slip ratios of the steered wheels **40**R and **40**L so that the steered wheels **40**R and **40**L are prevented from idling.

(66) The slip ratio to be used in the ABS control may be calculated by a known method, and the method of calculating the slip ratio is not limited to a particular calculation method. The slip ratio may be calculated based on a wheel speed detected by a wheel speed sensor and a vehicle speed, for example.

(67) The brake control unit **20** may perform brake control of the vehicle **100** by controlling the

above-described hydraulic control actuator based on a command from the driver assistance control processor **13** (including the contact avoidance control unit **14**). The brake control as the AEB described above may be thereby achieved.

(68) Further, the brake control unit **20** may perform a braking force decreasing process based on various determination processes according to the example embodiment and results of the determination processes. Details of the process according to the example embodiment will be described later.

(69) The ESC unit **25** may be a control unit that achieves the electronic stability control. For example, the ESC unit **25** may include a microcomputer that includes a CPU, a ROM, and a RAM, and may achieve the electronic stability control by executing various kinds of processes according to programs stored in the ROM.

(70) In this example, the ESC unit **25** may include various sensors, such as a wheel speed sensor and a yaw rate sensor, to be used in the electronic stability control. The CPU of the ESC unit **25** may achieve the electronic stability control by controlling the brake control unit **20** described above based on detection data acquired by these sensors.

(71) To the ESC unit **25**, the operation unit **26** may be coupled. In this example, an operation to enable the electronic stability control by the ESC unit **25** and an operation to disable the electronic stability control by the ESC unit **25** may be conducted on the vehicle **100** using the operation unit **26**.

(72) The ESC unit **25** may enable or disable the electronic stability control based on the operation of the operation unit **26**.

(73) The EPS control unit **22** may include a microcomputer, for example. The EPS control unit **22** may control an EPS motor **42** in the steering mechanism **30** based on the steering command current value sent from the contact avoidance control unit **14** in the driver assistance control processor **13** and the detection signal sent from the steering torque sensor **19**.

(74) Based on the data on the steering input torque inputted by the driver and acquired from the detection signal sent from the steering torque sensor **19**, the EPS control unit **22** may determine a steering command current value to acquire steering assistance torque corresponding to the steering input torque. Based on the steering command current value, the EPS control unit **22** may drive the EPS motor **42**. This achieves power steering control that assists the driver in performing a steering operation.

(75) Note that the driver may be allowed to perform a steering operation during the execution of the steering control by the contact avoidance control unit **14**. When a manual steering operation is performed during the steering control, the EPS control unit **22** may calculate the sum of the steering command current value sent from the contact avoidance control unit **14** and the steering command current value for the power steering control calculated as described above. Based on the sum of the current values, the EPS control unit **22** may drive the EPS motor **42**.

(76) The steering mechanism **30** to be subjected to the steering control may be configured as follows.

(77) The steering mechanism **30** may have the steering shaft **32** rotatably supported by a non-illustrated vehicle body frame via a steering column **33**. One end of the steering shaft **32** may extend toward a driver seat, and the steering wheel **34** may be attached to the end of the steering shaft **32**. A pinion shaft **35** may be joined to the other end of the steering shaft **32**.

(78) The pinion shaft **35** may have a non-illustrated pinion engaged with a rack of a rack shaft **37** extending in a steering gear box **36** and supported by the steering gear box **36** in a reciprocally movable manner. A rack-and-pinion steering gear mechanism may be thereby configured.

(79) Right and left ends of the rack shaft **37** may each project from the steering gear box **36**. Respective tie rods **38** may be joined to the right and left ends of the rack shaft **37**. A front knuckle **39** may be coupled to one end of each of the tie rods **38** opposite to the other end joined to the rack shaft **37**. The front knuckles **39** may support the respective steered wheels **40** (the right steered

wheel **40**R and the left steered wheel **40**L) and may be supported by the vehicle body frame via non-illustrated kingpins. The front knuckles **39** may be each coupled to an end of a corresponding one of the tie rods **38** so as to be rotatable about the kingpin.

(80) Accordingly, when the steering shaft **32** and the pinion shaft **35** are rotated by operating the steering wheel **34**, the rotation of the pinion shaft **35** may move the rack shaft **37** in a lateral direction. The lateral movement of the rack shaft **37** may rotate the front knuckle **39** about the kingpin, which steers the steered wheel **40**R or **40**L in the lateral direction.

(81) The EPS motor **42** may be attached to the pinion shaft **35** via an assisting transmission mechanism **41**. The EPS motor **42** may assist steering torque applied to the steering wheel **34** or may apply such steering torque that achieves a target steering angle.

(82) According to the vehicle control system **1** of the example embodiment described above, the AEB control may be performed when the possible contact object is detected, and the steering intervention may be performed by the AES when it is determined that the contact is unavoidable only by the AEB that brakes the vehicle **100**.

(83) An exemplary procedure for the contact avoidance control described above will now be described with reference to the flowchart illustrated in FIG. **3**, for confirmation.

(84) As illustrated in FIG. **3**, the contact avoidance control unit **14** may first determine whether the possible contact object has been detected (Step S**11**). For example, using the method described above, the contact avoidance control unit **14** may determine whether there is a three-dimensional object satisfying the above-described conditions regarding the lap rate and the TTC in the three-dimensional objects recognized by the image processing unit **12**. If it is determined that there is the three-dimensional object satisfying the conditions, the contact avoidance control unit **14** may determine that the possible contact object has been detected (Step S**11**: Yes). As described above, if there are multiple three-dimensional objects satisfying the conditions, the contact avoidance control unit **14** may select one of the three-dimensional objects as the possible contact object based on the values of the TTC.

(85) Thereafter, in Step S**12**, the contact avoidance control unit **14** may start brake intervention. That is, the contact avoidance control unit **14** may start the AEB control. For example, the contact avoidance control unit **14** may send the brake control unit **20** a command to thereby start braking the vehicle **100** by the AEB.

(86) Thereafter, in Step S**13**, the contact avoidance control unit **14** may determine whether the contact is avoidable only by braking the vehicle **100**. The determination may be made by a known method, for example. In one example, the determination may be made based on the current longitudinal relative speed vrz of the possible contact object and map data indicating the TTC values adapted to avoid the contact and set for respective values of the longitudinal relative speed vrz.

(87) If it is determined that the contact is avoidable only by braking the vehicle **100** (Step S**13**: Yes), the contact avoidance control unit **14** may end a series of processes illustrated in FIG. **3**. That is, in that case, the contact may be avoided only by the AEB.

(88) In contrast, it is determined that the contact is unavoidable only by braking the vehicle **100** (Step S**13**: No), the procedure may proceed to Step S**14**. In Step S**14**, the contact avoidance control unit **14** may calculate a target steering angle adapted to avoid the contact. That is, the contact avoidance control unit **14** may calculate a target steering angle adapted to avoid contact with the object recognized as the possible contact object.

(89) After calculating the target steering angle in Step S**14**, the contact avoidance control unit **14** may start steering intervention in Step S**15**. That is, the contact avoidance control unit **14** may start the AES control. For example, the contact avoidance control unit **14** may send the target steering angle adapted to avoid the contact to the EPS control unit **22** to thereby start the steering intervention to avoid the contact.

(90) After performing the steering intervention in Step S**15**, the contact avoidance control unit **14**

may end the series of processes illustrated in FIG. **3**.

(91) In the following, an example is described in which a sudden braking state is eliminated while the vehicle **100** is traveling in a state where the braking force of the vehicle **100** is greater than or equal to a predetermined braking force (i.e., where the vehicle **100** is in the sudden braking state) and where the turning degree of the vehicle **100** is greater than or equal to a predetermined turning degree.

(92) As used herein, the term "turning degree" may refer to the degree of turning of the vehicle **100**, that is, the degree of load biased to an outer wheel during turning of the vehicle **100**.

(93) In this example, while the sudden braking state is being eliminated and the braking force is being gradually decreased, a load may be applied to the front wheels, and grip of the front wheels may be gradually recovered. Thus, if the vehicle **100** keeps turning, the vehicle **100** is likely to cause oversteering, resulting in a spinning behavior of the vehicle **100**. In particular, spinning is likely to occur while the vehicle **100** is traveling on a road having a low frictional coefficient μ (hereinafter referred to as a low friction road), such as a snow road or an ice road.

(94) According to the example embodiment, the vehicle **100** is configured to perform the electronic stability control (ESC), and the ESC may be activated in the situation described above. This prevents the vehicle **100** from exhibiting the spinning behavior.

(95) However, when the ESC is disabled or when a vehicle is not configured to perform the ESC, the spinning behavior of the vehicle **100** is to be prevented by an operation of the driver who drives the vehicle **100**. If the driver is an unskilled driver, it may be difficult for the driver to avoid the spinning behavior of the vehicle **100**.

(96) In view of such circumstances, the vehicle control system **1** according to the example embodiment is provided for the following purpose.

(97) That is, the vehicle control system **1** according to the example embodiment prevents the vehicle **100** from exhibiting the spinning behavior when the sudden braking state is eliminated while the vehicle **100** is traveling in a state where the braking force of the vehicle **100** is greater than or equal to the predetermined braking force and where the turning degree of the vehicle **100** is greater than or equal to the predetermined turning degree. This makes it possible to improve the traveling stability of the vehicle **100**.

(98) For the purpose, the brake control unit **20** of the vehicle control system **1** may include some operational units as illustrated in FIG. **4**.

(99) FIG. **4** is a block diagram for describing exemplary operations of the brake control unit **20** according to the example embodiment.

(100) The brake control unit **20** may include a precondition determination processor F**1**, an execution condition determination processor F**2**, and a rear-wheel precedence force decreasing processor F**3** as well as the ABS processor **20***a* described above.

(101) The precondition determination processor F**1** performs a precondition determination process to determine whether a processing precondition is satisfied. The processing precondition includes at least a braking force condition that the braking force of the vehicle **100** is greater than or equal to the predetermined braking force and a turning condition that the turning degree of the vehicle **100** is greater than or equal to the predetermined turning degree. In one embodiment, the precondition determination process may serve as a "first determination process". In one embodiment, the processing precondition may serve as a "first condition".

(102) The execution condition determination processor F**2** performs an execution condition determination process to determine whether a processing execution condition is satisfied. The processing execution condition is a condition that the vehicle **100** is brought into a state where braking is to be cancelled while the processing precondition is being satisfied. In one embodiment, the execution condition determination process may serve as a "second determination process". In one embodiment, the processing execution condition may serve as a "second condition".

(103) When the processing execution condition is satisfied, the rear-wheel precedence force

decreasing processor F**3** performs a rear-wheel precedence force decreasing process as the braking force decreasing process to gradually decrease the braking force. In the rear-wheel precedence force decreasing process, the braking force applied to the rear wheels of the vehicle **100** is decreased preferentially over the braking force applied to the front wheels of the vehicle **100**.

(104) In other words, in the rear-wheel precedence force decreasing process, the braking force applied to the front wheels is remained to be greater than the braking force applied to the rear wheels.

(105) In one embodiment, the rear-wheel precedence force decreasing process may serve as a "precedence process".

(106) If the braking force applied to each wheel is uniformly decreased when the vehicle **100** is brought from the state where the braking force of the vehicle **100** is greater than or equal to the predetermined braking force and the turning degree of the vehicle **100** is greater than or equal to the predetermined turning degree (i.e., the state where the processing precondition is satisfied) into the state where braking of the vehicle **100** is to be cancelled (i.e., when the processing execution condition is satisfied), a load is biased to the front wheels, and grip of the front wheels is recovered. This can cause oversteering of the vehicle **100**, resulting in the spinning behavior of the vehicle **100**.

(107) To address such a concern, according to the example embodiment, the rear-wheel precedence force decreasing process is performed as the process adapted to gradually decrease the braking force when the processing execution condition is satisfied. In the rear-wheel precedence force decreasing process, the braking force applied to the rear wheels is decreased preferentially over the braking force applied to the front wheels.

(108) Accordingly, when the vehicle **100** is brought from the state where the braking force of the vehicle **100** is greater than or equal to the predetermined braking force (i.e., where sudden braking is applied to the vehicle **100**) and where the turning degree of the vehicle **100** is greater than or equal to the predetermined turning degree into the state where braking of the vehicle **100** is to be cancelled, the sudden braking is cancelled so that the vehicle **100** is prevented from occurring oversteering. This makes it possible to prevent the vehicle **100** from exhibiting the spinning behavior.

(109) The change from the state where the vehicle **100** is traveling in the state where the braking force is greater than or equal to the predetermined braking force and the turning degree of the vehicle **100** is greater than or equal to the predetermined turning degree to the state where braking of the vehicle **100** is to be cancelled is caused when the contact avoidance brake control is started once and thereafter terminated, for example.

(110) In that case, since the sudden braking is not cancelled according to a driver's intention, it is difficult to prevent the vehicle **100** from exhibiting the spinning behavior by a driver's operation.

(111) If the ESC is being enabled, the spinning behavior of the vehicle **100** can be avoided by the ESC. However, if the ESC is being disabled, it is difficult to avoid the spinning behavior of the vehicle **100**.

(112) To address such a concern, according to the example embodiment of the disclosure, the processing precondition for the rear-wheel precedence force decreasing process may further include a condition that the contact avoidance brake control is being activated and a condition that ESC is being disabled in addition to the braking force condition and the turning condition that are described above. In that case, the processing execution condition may be a condition that the vehicle **100** is brought into a state where the contact avoidance brake control is to be terminated while the processing precondition is being satisfied.

(113) In this example, whether the braking force condition is satisfied may be estimated by determining whether the ABS is being activated.

(114) In this example, the precondition determination processor F**1** and the execution condition determination processor F**2** may perform the following determination processes to determine

whether the above-described conditions are satisfied.

(115) For example, the precondition determination processor F**1** may determine whether the braking force condition is satisfied by determining whether the ABS control is being activated. Further, the precondition determination processor F**1** may determine whether the processing precondition is satisfied by determining whether at least four conditions are satisfied. The at least four conditions may include the condition that the contact avoidance brake control is being activated, the braking force condition, the turning condition, and the condition that the ESC is being disabled.

(116) The execution condition determination processor F**2** may determine whether the processing execution condition is satisfied by determining whether the vehicle **100** is in the state where the contact avoidance brake control is to be terminated.

(117) In this example, the processing precondition may further include a condition that the vehicle **100** is traveling on a low friction road.

(118) In that case, the precondition determination processor F**1** may determine whether the processing precondition is satisfied by determining whether the contact avoidance brake control is being activated, whether the ESC is being disabled, whether the vehicle **100** is traveling on the low friction road, whether the ABS is being activated (whether the braking force condition is satisfied), and whether the turning degree is greater than or equal to the predetermined turning degree (whether the turning condition is satisfied).

(119) Now, an example of the rear-wheel precedence force decreasing process is described with reference to FIGS. **5** and **6**.

(120) First, a braking force decreasing process according to a comparative example is described with reference to FIG. **5**.

(121) In FIG. **5**, time t**1** represents a timing at which the contact avoidance brake control is activated, time t**2** represents a timing at which the ABS is activated, and time t**3** represents a timing at which the processing execution condition is satisfied, that is, in this example, a timing at which the vehicle **100** is brought into a state where the contact avoidance brake control is to be terminated.

(122) A solid line in FIG. **5** represents a change in brake fluid pressure of the front wheels, and a dotted line represents a change in brake fluid pressure of the rear wheels.

(123) When the processing execution condition is satisfied at the time t**3**, the brake fluid pressure to the front wheels and the brake fluid pressure to the rear wheels are decreased at the same decreasing rate in the comparative example illustrated in FIG. **5**.

(124) In contrast, according to the example embodiment of the disclosure illustrated in FIG. **6**, when the processing execution condition is satisfied at the time t**3**, the process adapted to gradually decrease the braking force is performed so that the brake fluid pressure to the rear wheels is decreased preferentially over the brake fluid pressure to the front wheels. For example, the brake fluid pressure to the front wheels and the brake fluid pressure to the rear wheels may be gradually decreased so that a decreasing rate of the brake fluid pressure to the rear wheels becomes greater than a decreasing rate of the brake fluid pressure to the front wheels.

(125) In the example embodiment of the disclosure, the rear-wheel precedence force decreasing processor F**3** may determine a difference in the decrease rate (hereinafter referred to as a decreasing rate difference) between the braking force applied to the front wheels and the braking force applied to the rear wheels in the braking force decreasing process based on one or both of the vehicle speed and the turning degree of the vehicle **100** that are measure in a processing stand-by time from the timing at which the braking force condition is satisfied to the timing at which the rear-wheel precedence force decreasing process is started.

(126) In this example, an inclination θf, which is the inclination of decrease in the brake fluid pressure to the front wheels, and an inclination θr, which is the inclination of decrease in the brake fluid pressure to the rear wheels may be determined as data corresponding to the decreasing rate

difference described above.

(127) If the vehicle speed or the turning degree is high at the timing at which the processing execution condition is satisfied (i.e., the timing at which the sudden braking state is eliminated), the vehicle **100** is likely to spin. To address such a concern, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels in the braking force decreasing process may be determined based on one or both of the vehicle speed and the turning degree in the processing stand-by time as described above. In this example, the vehicle speed and the turning degree in the processing stand-by time may be the vehicle speed and the turning degree at the timing at which the processing execution condition is satisfied, for example.

(128) If it is determined that the vehicle **100** is likely to spin when the sudden braking state is eliminated because the vehicle speed or the turning degree is high, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels may be increased by increasing the decreasing rate of the braking force to the rear wheels, for example. This helps to further prevent the vehicle **100** from spinning.

(129) In contrast, if it is determined that the vehicle **100** is unlikely to spin when the sudden braking state is eliminated because the vehicle speed or the turning degree is low, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels may be decreased by decreasing the decreasing rate of the braking force to the rear wheels, for example. This helps to prevent the vehicle **100** from being unnecessarily understeered. It is therefore possible to improve drivability.

(130) Whether the vehicle speed is high may be determined by determining whether the own vehicle speed v is greater than or equal to a predetermined value, for example. Whether the turning degree is high may be determined by determining whether the value of an actual steering angle detected by the actual steering angle sensor **18** is greater than or equal to a predetermined value, for example.

(131) When the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels is determined based on both of the vehicle speed and the turning degree, map data may be used in which each combination of a vehicle speed and a turning degree is associated with the data on a corresponding decreasing rate difference. In that case, the map data may have a map characteristic that the decreasing rate difference increases as the vehicle speed and the turning degree increase.

(132) The vehicle speed and the turning degree in the processing stand-by time may be those detected at any timing in the processing stand-by time, or may be each an average value of those detected in the processing stand-by time.

(133) In either case, the vehicle speed and the turning degree used in the example embodiment may be those based on which likelihood of spinning of the vehicle **100** at the time when the sudden braking state is eliminated may be estimated. In that sense, the vehicle speed and the turning degree may be those measured in the processing stand-by time.

(134) In the example embodiment illustrated in FIG. **6**, the inclination of the decreasing rate of the brake fluid pressure to the front wheels may be changed from the initial inclination θf to the same inclination as the inclination θr of the decreasing rate of the brake fluid pressure to the rear wheels during the rear-wheel precedence force decreasing process. However, the inclination of the decreasing rate of the brake fluid pressure to the front wheels may not be necessarily changed to the same inclination as the inclination θr of the decreasing rate of the brake fluid pressure to the rear wheels, and may be changed to any inclination other than the inclination θr. Alternatively, the inclination of the decreasing rate of the brake fluid pressure to the front wheels may not be changed during the rear-wheel precedence force decreasing process.

(135) In either case, the braking force applied to the rear wheels is preferentially over the braking force applied to the front wheel in the rear-wheel precedence force decreasing process according to the example embodiment.

(136) FIG. **7** is a diagram illustrating an exemplary method of determining whether the turning condition is satisfied.

(137) In FIG. **7**, the time t**2** represents the timing at which the braking force condition is satisfied, that is, in this example, the timing at which the ABS control is activated, as in FIGS. **5** and **6**.

(138) In this example, the precondition determination processor F**1** may determine whether the turning condition is satisfied based on a turning threshold. The turning threshold may be determined based on a braking force measured while the braking force condition is being satisfied.

(139) For example, after the ABS control is activated at the time t**2**, the precondition determination processor F**1** may sequentially execute a process adapted to calculate an average value of the braking forces detected during the ABS control, and calculate a turning limit steering angle based on the average value. The process may be repeated in a predetermined processing cycle.

(140) The turning limit steering angle may be a steering angle at which the vehicle **100** is estimated to exhibit a spinning behavior when the application of a braking force to the vehicle **100** is stopped. In other words, if the steering angle of the vehicle **100** is greater than or equal to the turning limit steering angle when the application of the braking force to the vehicle **100** is stopped, it may be estimated that the vehicle **100** will exhibit the spinning behavior.

(141) In this example, a correspondence relation between the braking force and the turning limit steering angle may be determined through experiments or simulations in advance, and the turning limit steering angle may be calculated based on the braking force measured during the ABS control referring to the data (e.g., map data or arithmetic function data) on the correspondence relation between the braking force and the turning limit steering angle.

(142) Note that the turning limit steering angle may tend to decrease as the braking force increases.

(143) Using the turning limit steering angle calculated as described above, the precondition determination processor F**1** may determine whether the turning condition is satisfied. For example, whether the turning condition is satisfied may be determined by determining whether an actual current steering angle detected by the actual steering angle sensor **18** is greater than or equal to the turning limit steering angle.

(144) As described above, the determination as to whether the turning condition is satisfied may be made based on the turning limit steering angle determined based on the braking force measured while the braking force condition is being satisfied. This makes it possible to accurately determine whether the processing precondition is satisfied (i.e., whether the vehicle **100** exhibits the spinning behavior when the sudden braking state is eliminated) depending on the degree of the braking force.

(145) An exemplary procedure for implementing the traveling stability control according to the example embodiment described above will now be described with reference to a flowchart illustrated in FIG. **8**.

(146) In this example, the procedure illustrated in FIG. **8** may be executed by the CPU of the brake control unit **20** according to a program stored in the memory such as the ROM in the brake control unit **20**, for example.

(147) First, in Step S**101**, the brake control unit **20** may wait for activation of the AEB. That is, the brake control unit **20** may wait until the contact avoidance control unit **14** starts the AEB (refer to Step S**12** in FIG. **3**).

(148) Thereafter, in Step S**102**, the brake control unit **20** may determine whether the vehicle **100** is traveling on a low friction road. That is, the brake control unit **20** may determine whether the frictional coefficient μ of the road surface of the traveling road of the vehicle **100** is less than or equal to a predetermined value.

(149) The frictional coefficient μ of the low friction road may be estimated by a known method, and the method of estimating the frictional coefficient μ is not limited to a particular method. For example, the frictional coefficient μ of the low friction road may be estimated in the image processing at the image processing unit **12**. Alternatively, the frictional coefficient μ of the low

friction road may be estimated based on the slip ratio of the wheels.

(150) In this example, the low friction road may be a wet road due to rainfall, a snow road, an ice road, or a mud road, for example. The term "low friction road" used herein may refer to a road determined to have a frictional coefficient μ less than or equal to the predetermined value. The predetermined value may vary depending on turning performance of the vehicle **100**, for example, and is not limited to a particular value.

(151) If it is determined that the frictional coefficient μ of the low friction road is not less than or equal to the predetermined value and that the vehicle is not traveling on the low friction road (Step S**102**: No), the brake control unit **20** may end a series of processes illustrated in FIG. **8**.

(152) That is, because the processing precondition for the rear-wheel precedence force decreasing process according to the example embodiment includes the condition that the vehicle is traveling on the low friction road, the rear-wheel precedence force decreasing process may not be performed when the vehicle **100** is not traveling on the low friction road.

(153) In contrast, if it is determined that the vehicle is traveling on the low friction road (Step S**102**: Yes), the procedure may proceed to Step S**103**. In Step S**103**, the brake control unit **20** may determine whether the ESC is being disabled.

(154) If it is determined that the ESC is not being disabled (Step S**103**: No), the brake control unit **20** may end the series of processes illustrated in FIG. **8**.

(155) That is, because the processing precondition for the rear-wheel precedence force decreasing process according to the example embodiment includes the condition that the ESC is being disabled, the rear-wheel precedence force decreasing process may not be performed when the ESC is not being disabled.

(156) If it is determined that the ESC is being disabled (Step S**103**: Yes), the procedure may proceed to Step S**104**. In Step S**104**, the brake control unit **20** may determine whether the ABS is being activated. That is, the brake control unit **20** may determine whether the ABS processor **20**a described above is performing the ABS control. In this example, the determination process at Step S**104** may correspond to a process adapted to determine whether the braking force condition is satisfied.

(157) If it is determined that the ABS is being activated (Step S**104**: Yes), the procedure may proceed to Step S**105**. In Step S**105**, the brake control unit **20** may calculate the turning limit steering angle. In this example, the brake control unit **20** may calculate an average value of the braking forces (brake fluid pressures in this example) measured while the ABS control is being activated, and may calculate the turning limit steering angle based on the average value. Since the method of calculating the turning limit steering angle based on the braking forces has been already described above, the description thereof is omitted herein to avoid redundancy.

(158) Thereafter, in Step S**106**, the brake control unit **20** may determine whether the steering angle is greater than or equal to the turning limit steering angle. For example, the brake control unit **20** may determine whether the actual steering angle acquired from the actual steering angle sensor **18** is greater than or equal to the turning limit steering angle calculated in Step S**105**.

(159) If it is determined that the steering angle is greater than or equal to the turning limit steering angle (Step S**106**: Yes), the procedure may proceed to Step S**107**. In Step S**107**, the brake control unit **20** may determine whether the AEB is to be terminated. The determination as to whether the ABS is to be terminated may correspond to the determination as to whether the processing execution condition is satisfied.

(160) Examples of the case where the AEB is to be terminated may include a case where the contact avoidance control is no longer to be performed due to a movement of the possible contact object, and a case where it is determined that the possible contact object has been erroneously recognized.

(161) If it is determined that the AEB is to be terminated (Step S**107**: Yes), the procedure may proceed to Step S**109**. In Step S**109**, the brake control unit **20** may execute the rear-wheel

precedence force decreasing process, following which the series of processes illustrated in FIG. **8** may end. In the rear-wheel precedence force decreasing process according to the example embodiment, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels to be used in the braking force decreasing process may be determined based on one or both of the own vehicle speed v and the steering rate (e.g., the actual steering angle) that are measured in the processing stand-by time from the timing at which the braking force condition is satisfied to the timing at which the rear-wheel precedence force decreasing process is started, as described above (refer to FIG. **6**). In the rear-wheel precedence force decreasing process according to the example embodiment, the brake fluid pressure to the rear wheels and the brake fluid pressure to the front wheels may be gradually decreased so that the decreasing rate difference in the braking force determined as described above is achieved.

(162) As illustrated in FIG. **8**, if it is determined that the ABS is not being activated (Step S**104**: No), if it is determined that the steering angle is not greater than or equal to the turning limit steering angle (Step S**106**: No), or if it is determined that the AEB is not to be terminated (Step S**107**: No), the brake control unit **20** may cause the procedure to proceed to Step S**108**.

(163) In Step S**108**, the brake control unit **20** may determine whether the procedure is to be terminated. For example, the brake control unit **20** may determine whether a predetermined condition for terminating the series of processes illustrated in FIG. **8** is satisfied. Examples of the predetermined condition may include a condition that the elapsed time from the determination in Step S**101** that the AEB is being activated is longer than or equal to a predetermined time.

(164) If it is determined that the predetermined condition for terminating the procedure is not satisfied and thus that the procedure is not to be terminated (Step S**108**: No), the brake control unit **20** may return the procedure to Step S**104**.

(165) Accordingly, after it is determined that the AEB is being activated (Step S**101**: Yes), that the vehicle **100** is traveling on the low friction road (Step S**102**: Yes), and that the ESC is being disabled (Step S**103**: Yes), the procedure may enter a loop process to wait until it is determined that the ABS is being activated (Step S**104**: Yes), that the steering angle is greater than or equal to the turning limit steering angle (Step S**106**: Yes), and that the AEB is to be terminated (Step S**107**: Yes), or until it is determined that the procedure is to be terminated (Step S**108**: Yes).

(166) If it is determined that the procedure is to be terminated because the above-described conditions for terminating the procedure are satisfied (Step S**108**: Yes), the brake control unit **20** may end the series of processes illustrated in FIG. **8**.

(167) Although some of the example embodiments of the disclosure have been described above, the disclosure is not limited to the example embodiments described above, and various modification examples may be made.

(168) For example, in the example embodiment described above, the processing precondition may include the condition that the AEB is being activated, and the processing execution condition may include the condition that the AEB has been terminated, assuming that the vehicle **100** will exhibit the spinning behavior when the AEB is switched from the enabled state to the disabled state. However, the spinning behavior of the vehicle **100** can be caused by a braking operation performed by the driver rather than braking by the AEB.

(169) An exemplary procedure to be performed in that case by the brake control unit **20** will now be described with reference to a flowchart illustrated in FIG. **9**.

(170) Note that, in FIG. **9**, the same processes as those described above are denoted by the same reference numerals to omit the description thereof.

(171) First, in Step S**201**, the brake control unit **20** may wait until a sudden braking operation is performed by the driver. For example, the brake control unit **20** may wait until a braking operation (brake pedal operation) to apply a braking force greater than or equal to a predetermined braking force is performed by the driver. That is, the determination process at Step S**201** may be a process in which the brake control unit **20** waits until the amount of depression of the brake pedal reaches a

predetermined amount or greater, for example.

(172) If it is determined that the sudden braking operation has been performed (Step S**201**: Yes), the brake control unit **20** may cause the procedure to proceed to Step S**102**. In Step S**102**, the brake control unit **20** may determine whether the vehicle **100** is traveling on a low friction road. If it is determined that the vehicle **100** is traveling on the low friction road (Step S**102**: Yes), the brake control unit **20** may cause the procedure to proceed to Step S**104**. In Step S**104**, the brake control unit **20** may determine whether the ABS is being activated.

(173) If it is determined that the ABS is being activated (Step S**104**: Yes), the brake control unit **20** may execute the process at Step S**105**, and thereafter determine whether the steering angle is greater than or equal to the turning limit steering angle in Step S**106**.

(174) If it is determined that the steering angle is greater than or equal to the turning limit steering angle (Step S**106**: Yes), the brake control unit **20** may determine in Step S**202** whether the sudden braking operation has been cancelled. Whether the sudden braking operation has been cancelled may be determined by determining whether the amount of depression of the brake pedal is less than a predetermined amount (e.g., whether the amount of depression of the brake pedal is zero (0)), for example.

(175) If it is determined that the sudden braking operation has been cancelled (Step S**202**: Yes), the brake control unit **20** may execute the rear-wheel precedence force decreasing process in Step S**109**, following which a series of processes illustrated in FIG. **9** may end.

(176) If it is determined that the ABS is not being activated (Step S**104**: No), if it is determined that the steering angle is not greater than or equal to the turning limit steering angle (Step S**106**: No), or if it is determined that the sudden braking operation has not been cancelled (Step S**202**: No), the procedure may proceed to Step S**108**. In Step S**108**, the brake control unit **20** may determine whether the procedure is to be terminated. If it is determined that the procedure is not to be terminated (Step S**108**: No), the brake control unit **20** may return the procedure to Step S**104**. Accordingly, after it is determined that the sudden braking operation is performed (Step S**201**: Yes) and that the vehicle **100** is traveling on the low friction road (Step S**102**: Yes), the procedure may enter a loop process to wait until it is determined that the ABS is being activated (Step S**104**: Yes), that the steering angles is greater than or equal to the turning limit steering angle (Step S**106**: Yes), and that the sudden braking operation has been cancelled (Step S**202**), or until it is determined whether the procedure is to be terminated (Step S**108**: Yes).

(177) If it is determined that the procedure is to be terminated (Step S**108**: Yes), the brake control unit **20** may end the series of processes illustrated in FIG. **9**.

(178) In the procedure illustrated in FIG. **9**, Step S**103** may be omitted, and the processing precondition may not include the condition that the ESC is being disabled. However, in this example, the process at Step S**103** may be executed and the processing precondition may include the condition that the ESC is being disabled.

(179) The traveling stability process illustrated in FIG. **9**, which is based on a sudden braking operation performed by the driver, may be executed as a process in one of the modes of the ESC (e.g., a process in a stability-focused mode). In that case, the process at Step S**103** may be omitted as illustrated in FIG. **9**.

(180) In the example embodiments described above, whether the braking force condition is satisfied may be determined by determining whether the ABS is being activated. Alternatively, whether the braking force condition is satisfied may be determined by determining whether the brake fluid pressure is greater than or equal to a predetermined pressure. Still alternatively, whether the braking force condition is satisfied may be determined based on the amount of depression of the brake pedal or a longitudinal acceleration. The method of determining whether the braking force condition is satisfied is not limited to a particular method.

(181) In the example embodiments described above, the brake fluid pressure may be gradually decreased in the rear-wheel precedence force decreasing process. However, when the vehicle **100** is

a HEV or an EV, the braking force may include a braking force derived from regenerative power of a motor generator, and in such a case, the braking force derived from both of the brake fluid pressure and the regenerative power may be gradually decreased in the rear-wheel precedence force decreasing process.

(182) Further, the determination regarding the braking force described above may be performed based on not only the brake fluid pressure and also the regenerative power.

(183) In the example embodiments described above, whether the turning condition is satisfied may be determined based on the actual steering angle. Alternatively, whether the turning condition is satisfied may be determined based on a steering torque detected by the steering torque sensor **19**, the amount of a steering operation, a yaw rate, or a lateral G, for example. The method of determining whether the turning condition is satisfied is not limited to a particular method.

(184) The turning condition may include a condition regarding the AES intervention.

(185) In the example embodiments described above, the process adapted to recognize the external environment of the vehicle **100** in the AEB may be performed based on images captured by the camera. However, the process adapted to recognize the external environment of the vehicle **100** may be performed by another method. For example, the process adapted to recognize the external environment of the vehicle **100** may be performed using a radar or a map locator. In that case, an object which is present near the vehicle **100** may be recognized based on a position of the vehicle **100** detected by a position sensor and a high-resolution map data.

(186) In the example embodiments described above, the precondition determination process, the execution condition determination process, and the rear-wheel precedence force decreasing process may be performed by the brake control unit **20**. However, these processes may be performed by another device, such as another control unit of the vehicle control system **1**, instead of the brake control unit **20**.

(187) Alternatively, these processes may be performed by multiple control units. For example, some of the processes may be performed by a first control unit, and the other processes may be performed by a second control unit.

(188) The vehicle control system (vehicle control system **1**) according to the example embodiments described above is applied to the vehicle (vehicle **100**) including the braking unit configured to brake the vehicle (vehicle **100**). The vehicle control system includes one or more processors (the CPU(s) of the brake control unit **20**) and the one or more memories (the ROM(s) of the brake control unit **20**) in which a program to be executed by the one or more processors. The program includes one or more commands adapted to cause the one or more processors to perform the precondition determination process, the execution condition determination process, and the rear-wheel precedence force decreasing process. The precondition determination process is a process adapted to determine whether the processing precondition is satisfied. The processing precondition includes at least the braking force condition that the braking force of the vehicle is greater than or equal to the predetermined braking force, and the turning condition that the turning degree of the vehicle is greater than or equal to the predetermined turning degree. The execution condition determination process is a process adapted to determine whether the processing execution condition is satisfied. The processing execution condition includes the condition that the vehicle is brought into the state where braking by the braking unit is to be cancelled while the processing precondition is being satisfied. The rear-wheel precedence force decreasing process is a process adapted to gradually decrease the braking force by decreasing a braking force applied to the rear wheel of the vehicle preferentially over a braking force applied to the front wheel of the vehicle. The rear-wheel precedence force decreasing process is performed when the second condition is satisfied.

(189) If the braking force applied to each wheel is uniformly decreased when the vehicle **100** is brought from the state where the braking force of the vehicle is greater than or equal to the predetermined braking force and the turning degree of the vehicle is greater than or equal to the predetermined turning degree (i.e., the state where the processing precondition is satisfied) into the

state where braking of the vehicle **100** is to be cancelled (i.e., when the processing execution condition is satisfied), a load is biased to the front wheels, and grip of the front wheels is recovered. This can cause oversteering of the vehicle, resulting in the spinning behavior of the vehicle. To address such a concern, according to the example embodiments described above, the rear-wheel precedence force decreasing process is performed as the process adapted to gradually decrease the braking force when the processing execution conditions described above is satisfied. In the rear-wheel precedence force decreasing process, the braking force applied to the rear wheels is decreased preferentially over the braking force applied to the front wheels.

(190) Accordingly, when the vehicle is brought from the state where the braking force of the vehicle is greater than or equal to the predetermined braking force (i.e., where sudden braking is applied to the vehicle) and the turning degree of the vehicle is greater than or equal to the predetermined turning degree into the state where braking of the vehicle is to be cancelled, the sudden braking is cancelled so that the vehicle is prevented from occurring oversteering. This makes it possible to prevent the vehicle from exhibiting the spinning behavior.

(191) It is therefore possible to improve the traveling stability of the vehicle.

(192) Further, according to the vehicle control system of the example embodiments described above, the vehicle may be configured to execute, with the braking unit, the contact avoidance control (AEB or AEB+AES), the electronic stability control (ESC), and the anti-lock brake system (ABS) control. In the precondition determination process, the one or more processors may determine whether the braking force condition is satisfied by determining whether the ABS control is being activated (refer to Step S**104**), and whether the processing precondition is satisfied by determining whether at least four conditions are satisfied. The at least four conditions may include the condition that the contact avoidance brake control is being activated (refer to Step S**101**), the braking force condition, the turning condition (refer to Step S**106**), and the condition that the electronic stability control is being disabled (refer to Step S**103**). In the execution condition determination process, the one or more processors may determine whether the processing execution condition is satisfied by determining whether the vehicle has been brought into a state where the contact avoidance brake control is to be terminated (refer to Step S**107**).

(193) That is, the determination as to whether the processing precondition is satisfied may be performed as the determination as to whether the at least four conditions, including the condition that the contact avoidance brake control is being activated, the condition that the ABS control is being activated, the condition that the turning degree is greater than or equal to the predetermined turning degree, and the condition that the electronic stability control is being disabled, are satisfied. Further, the determination as to whether the processing execution condition is satisfied may be performed as the determination as to whether the vehicle has been brought into the state where the contact avoidance brake control is to be switched from the enabled state to the disabled state.

(194) The vehicle is likely to exhibit the spinning behavior when the contact avoidance control is terminated (i.e., the sudden braking state generated by the contact avoidance brake control is eliminated) in the state where the contact avoidance brake control is activated while the electronic stability control is being disabled, where the ABS control is activated in conjunction with the activation of the contact avoidance brake control, and where the turning degree is greater than or equal to the predetermined turning degree. To address such a concern, the rear-wheel precedence force decreasing process is performed in the example embodiments described above. This makes it possible to prevent the vehicle from spinning when the sudden braking state is eliminated in accordance with the termination of the contact avoidance brake control. It is therefore possible to improve the vehicle traveling stability.

(195) JP-A No. 2015-048006 discloses a technique in which the electronic stability control is enabled when the contact avoidance brake control is activated while the electronic stability control is being disabled. The technique helps to secure vehicle behavior stability in the contact avoidance brake control.

(196) According to the technique disclosed in JP-A No. 2015-048006, the electronic stability control is being enabled when the vehicle is brought from the state where the vehicle is in the sudden braking state due to the activation of the contact avoidance brake control and the turning degree is greater than or equal to the predetermined turning degree into the state where the contact avoidance brake control is terminated and the sudden braking state is eliminated. If the driver performs a spin avoidance driving operation to address a situation where the spinning behavior is likely to occur in the same way as in the case where the electronic stability control is disabled, the spin avoidance driving operation performed by the driver can overlap with spin prevention control performed by the electronic stability control. This can cause spinning (drifting) of the vehicle in the reverse direction. In contrast, according to the example embodiments, the electronic stability control in the disabled state is not automatically enabled in response to the activation of the contact avoidance brake control. This helps to prevent the vehicle from occurring such drifting. In this respect, it is possible to improve the vehicle traveling stability.

(197) Further, according to the vehicle control system of the example embodiments described above, the one or more processors may determine, in the processing precondition determination process, whether the turning condition is satisfied based on the turning threshold. The turning threshold may be determined based on the braking force measured while the braking force condition is being satisfied (refer to Steps S**105** and S**106** in FIG. **7**).

(198) When the sudden braking state is eliminated, the vehicle is more likely to exhibit the spinning behavior as the turning degree is higher. The turning threshold for determining whether the vehicle will exhibit the spinning behavior may vary depending on the braking force at the time when the sudden braking state is eliminated. That is, the turning threshold may tend to decrease as the braking force increases. Therefore, the determination as to whether the turning condition is satisfied may be made based on the turning threshold determined based on the braking force measured while the braking force condition is satisfied, as described above.

(199) Accordingly, it is possible to accurately determine whether the processing precondition is satisfied, that is, whether there is a possibility that the vehicle exhibits the spinning behavior when the sudden braking state is eliminated, based on the magnitude of the braking force.

(200) Further, according to the vehicle control system of the example embodiments described above, the one or more processors may determine, in the rear-wheel precedence force decreasing process, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels, based on one or both of the vehicle speed of the vehicle and the turning degree of the vehicle that are measured in the time period from the timing at which the braking force condition is satisfied to the timing at which the rear-wheel precedence force decreasing process is started (refer to Step S**109**).

(201) The vehicle is more likely to exhibit the spinning behavior when the vehicle speed or the turning degree is high at the timing at which the processing execution condition is satisfied, that is, at the timing at which the sudden braking state is eliminated. Thus, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels may be determined based on one or both of the vehicle speed and the turning degree that are measured when the processing execution condition is satisfied, as described above. Accordingly, if the vehicle is likely to exhibit the spinning behavior in association with the elimination of the sudden braking state because the vehicle speed or the turning degree is high, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels may be increased (i.e., the braking force decreasing rate at the rear wheel side may be increased) to prevent the vehicle from exhibiting the spinning behavior. In contrast, if the vehicle is unlikely to exhibit the spinning behavior in association with the elimination of the sudden braking state because the vehicle speed or the turning degree is low, the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels may be decreased (i.e., the braking force decreasing rate at the rear wheel side may

be decreased) to prevent the vehicle from being unnecessarily understeered. This helps to improve drivability, for example. That is, it is possible to appropriately determine the decreasing rate difference between the braking force applied to the front wheels and the braking force applied to the rear wheels depending on the likelihood of spinning of the vehicle at the time of the elimination of the sudden braking state.

(202) Further, according to the vehicle control system of the example embodiments described above, the processing precondition includes the condition that the vehicle is traveling on a low friction road (refer to Step S**102**).

(203) For example, the vehicle traveling on the low friction road such as a wet road due to rainfall, a snow road, an ice road, or a mud road is more likely to exhibit the spinning behavior when the vehicle is brought from the state where the vehicle is in the sudden braking state (i.e., where the braking force is greater than or equal to the predetermined braking force) and the turning degree is greater than or equal to the predetermined turning degree into the state where the sudden braking state is eliminated.

(204) Therefore, the rear-wheel precedence force decreasing process according to the example embodiments described above may be performed when the vehicle is traveling on the low friction road.

(205) The brake control unit **20** illustrated in FIG. **1** is implementable by circuitry including at least one semiconductor integrated circuit such as at least one processor (e.g., a central processing unit (CPU)), at least one application specific integrated circuit (ASIC), and/or at least one field programmable gate array (FPGA). At least one processor is configurable, by reading instructions from at least one machine readable non-transitory tangible medium, to perform all or a part of functions of the brake control unit **20** illustrated in FIG. **1**. Such a medium may take many forms, including, but not limited to, any type of magnetic medium such as a hard disk, any type of optical medium such as a CD and a DVD, any type of semiconductor memory (i.e., semiconductor circuit) such as a volatile memory and a non-volatile memory. The volatile memory may include a DRAM and a SRAM, and the nonvolatile memory may include a ROM and a NVRAM. The ASIC is an integrated circuit (IC) customized to perform, and the FPGA is an integrated circuit designed to be configured after manufacturing in order to perform, all or a part of the functions of the brake control unit **20** illustrated in FIG. **1**.

Claims

1. A vehicle control system to be applied to a vehicle, the vehicle comprising a braking unit configured to brake the vehicle, the vehicle control system comprising: one or more processors; and one or more memories in which a program to be executed by the one or more processors is stored, wherein the program comprises one or more commands adapted to cause the one or more processors to perform a first determination process to determine whether a first condition is satisfied, the first condition comprising at least a braking force condition that a braking force of the vehicle is greater than or equal to a predetermined braking force, and a turning condition that a turning degree of the vehicle is greater than or equal to a predetermined turning degree, perform a second determination process to determine whether a second condition is satisfied, the second condition comprising a condition that the vehicle is brought into a state where braking by the braking unit is to be cancelled while the first condition is being satisfied, and perform, when the second condition is satisfied, a precedence process to gradually decrease the braking force by decreasing a braking force applied to a rear wheel of the vehicle preferentially over a braking force applied to a front wheel of the vehicle.

2. The vehicle control system according to claim 1, wherein the vehicle is configured to execute, with the braking unit, contact avoidance brake control, electronic stability control, and anti-lock brake system control, the one or more processors are configured to determine, in the first

determination process, whether the braking force condition is satisfied by determining whether the anti-lock brake system control is being activated, and whether the first condition is satisfied by determining whether at least four conditions are satisfied, the at least four conditions comprising a condition that the contact avoidance brake control is being activated, the braking force condition, the turning condition, and a condition that the electronic stability control is being disabled, and the one or more processors are configured to determine, in the second determination process, whether the second condition is satisfied by determining whether the vehicle has been brought into a state where the contact avoidance brake control is to be terminated.

3. The vehicle control system according to claim 1, wherein the one or more processors are configured to determine, in the first determination process, whether the turning condition is satisfied based on a turning threshold, the turning threshold being determined based on the braking force measured while the braking force condition is being satisfied.

4. The vehicle control system according to claim 1, wherein the one or more processors are configured to determine, in the precedence process, a decreasing rate difference between the braking force applied to the front wheel and the braking force applied to the rear wheel, based on one or both of a vehicle speed of the vehicle and the turning degree of the vehicle that are measured in a time period from a timing at which the braking force condition is satisfied to a timing at which the precedence process is started.

5. The vehicle control system according to claim 1, wherein the first condition comprises a condition that the vehicle is traveling on a low friction road.

6. The vehicle control system according to claim 2, wherein the first condition comprises a condition that the vehicle is traveling on a low friction road.

7. The vehicle control system according to claim 3, wherein the first condition comprises a condition that the vehicle is traveling on a low friction road.

8. The vehicle control system according to claim 4, wherein the first condition comprises a condition that the vehicle is traveling on a low friction road.