

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383114
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Park; Kitae et al.

Dish washer

Abstract

A dishwasher is disclosed. The dishwasher includes a main body provided a washing tub inside, a first basket disposed inside the washing tub and configured to accommodate an object to be washed, and a second basket configured to accommodate the object to be washed, and move in a vertical direction between a first position disposed in a partial area inside the first basket, and a second position disposed above the partial area spaced apart from the first basket.

Inventors: Park; Kitae (Suwon-si, KR), Kim; Jusik (Suwon-si, KR), Yeom; Daeseon (Suwon-si, KR), Lee; Junho (Suwon-si, KR), Jung; Minhoo (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008748236

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/819974

Filed: August 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220386847 A1	Dec. 08, 2022

Foreign Application Priority Data

KR	10-2020-0140973	Oct. 28, 2020
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2021/095087 20211025 PENDING child-doc US 17819974

Publication Classification

Int. Cl.: A47L15/50 (20060101); A47L15/42 (20060101)

U.S. Cl.:

CPC A47L15/503 (20130101); A47L15/4278 (20130101); A47L15/504 (20130101);

Field of Classification Search

CPC: A47L (15/503); A47L (15/4278); A47L (15/504)

USPC: 134/199

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4998678	12/1990	Durr	N/A	N/A
5244129	12/1992	Poussin et al.	N/A	N/A
5984826	12/1998	Nakano	N/A	N/A
6113119	12/1999	Laurent et al.	N/A	N/A
6409456	12/2001	Horejsi et al.	N/A	N/A
6938627	12/2004	Jung et al.	N/A	N/A
6990828	12/2005	Kim et al.	N/A	N/A
7228817	12/2006	Busse	N/A	N/A
7644826	12/2009	Koch et al.	N/A	N/A
8671712	12/2013	Noel et al.	N/A	N/A
8783170	12/2013	Mathey et al.	N/A	N/A
8876984	12/2013	Hong et al.	N/A	N/A
8926232	12/2014	Sjoo	N/A	N/A
9420882	12/2015	Garcia et al.	N/A	N/A
9895018	12/2017	Lin	N/A	N/A
9936851	12/2017	Kim et al.	N/A	N/A
10413947	12/2018	Borghi et al.	N/A	N/A
10512359	12/2018	Xu et al.	N/A	N/A
11419479	12/2021	Kim et al.	N/A	N/A
2005/0133072	12/2004	Yoon et al.	N/A	N/A
2020/0281441	12/2019	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1042670	12/1989	CN	N/A
1061940	12/1991	CN	N/A
1100195	12/1994	CN	N/A
1122892	12/1995	CN	N/A
1161481	12/1996	CN	N/A
1197506	12/1997	CN	N/A
1466931	12/2003	CN	N/A
1492208	12/2003	CN	N/A

1541060	12/2003	CN	N/A
1628597	12/2004	CN	N/A
101006833	12/2006	CN	N/A
102697436	12/2011	CN	N/A
102730189	12/2011	CN	N/A
102756625	12/2011	CN	N/A
102783307	12/2011	CN	N/A
102837078	12/2011	CN	N/A
103126515	12/2012	CN	N/A
103168606	12/2012	CN	N/A
103174310	12/2012	CN	N/A
103315525	12/2012	CN	N/A
103330337	12/2012	CN	N/A
103462574	12/2012	CN	N/A
103519568	12/2013	CN	N/A
103548632	12/2013	CN	N/A
103598807	12/2013	CN	N/A
103625869	12/2013	CN	N/A
103653838	12/2013	CN	N/A
103654205	12/2013	CN	N/A
103654666	12/2013	CN	N/A
103654673	12/2013	CN	N/A
103654677	12/2013	CN	N/A
103696845	12/2013	CN	N/A
103758184	12/2013	CN	N/A
104033324	12/2013	CN	N/A
104096673	12/2013	CN	N/A
104188054	12/2013	CN	N/A
104264749	12/2014	CN	N/A
104274064	12/2014	CN	N/A
104444014	12/2014	CN	N/A
104464086	12/2014	CN	N/A
104608415	12/2014	CN	N/A
104719096	12/2014	CN	N/A
104719097	12/2014	CN	N/A
104739139	12/2014	CN	N/A
104739223	12/2014	CN	N/A
104757922	12/2014	CN	N/A
104782257	12/2014	CN	N/A
104791793	12/2014	CN	N/A
104798471	12/2014	CN	N/A
104858643	12/2014	CN	N/A
104889691	12/2014	CN	N/A
104889729	12/2014	CN	N/A
105011734	12/2014	CN	N/A
105052330	12/2014	CN	N/A
105054885	12/2014	CN	N/A
105057731	12/2014	CN	N/A
105147050	12/2014	CN	N/A
105193569	12/2014	CN	N/A

105340438	12/2015	CN	N/A
105496177	12/2015	CN	N/A
105534462	12/2015	CN	N/A
105615808	12/2015	CN	N/A
105691779	12/2015	CN	N/A
105794354	12/2015	CN	N/A
105855896	12/2015	CN	N/A
105904147	12/2015	CN	N/A
105909834	12/2015	CN	N/A
105942951	12/2015	CN	N/A
105996951	12/2015	CN	N/A
106002162	12/2015	CN	N/A
106090807	12/2015	CN	N/A
106100564	12/2015	CN	N/A
106108821	12/2015	CN	N/A
106333591	12/2016	CN	N/A
106377214	12/2016	CN	N/A
106495055	12/2016	CN	N/A
106736510	12/2016	CN	N/A
106742533	12/2016	CN	N/A
106799575	12/2016	CN	N/A
106877539	12/2016	CN	N/A
106964552	12/2016	CN	N/A
106965838	12/2016	CN	N/A
107028346	12/2016	CN	N/A
107088639	12/2016	CN	N/A
107095531	12/2016	CN	N/A
107198355	12/2016	CN	N/A
107338709	12/2016	CN	N/A
107351296	12/2016	CN	N/A
107363175	12/2016	CN	N/A
107393744	12/2016	CN	N/A
107440532	12/2016	CN	N/A
107554840	12/2017	CN	N/A
107745254	12/2017	CN	N/A
107822480	12/2017	CN	N/A
108245109	12/2017	CN	N/A
108354317	12/2017	CN	N/A
208693222	12/2018	CN	N/A
209285437	12/2018	CN	N/A
209404716	12/2018	CN	N/A
0688147	12/2001	EP	N/A
0878332	12/2001	EP	N/A
1152681	12/2002	EP	N/A
1488730	12/2008	EP	N/A
2074925	12/2008	EP	N/A
2671494	12/2015	EP	N/A
2890271	12/2015	EP	N/A
1922965	12/2017	EP	N/A
3137587	12/2017	EP	N/A

2282216	12/1994	GB	N/A
H11-342098	12/1998	JP	N/A
2004-351082	12/2003	JP	N/A
2006-000189	12/2005	JP	N/A
2008-125702	12/2007	JP	N/A
10-0165042	12/1998	KR	N/A
20-0386333	12/2004	KR	N/A
10-0707556	12/2006	KR	N/A
10-2010-0037460	12/2009	KR	N/A
10-1088313	12/2010	KR	N/A
10-2020-0107102	12/2019	KR	N/A
10-2022-0005346	12/2021	KR	N/A
2017176286	12/2016	WO	N/A

OTHER PUBLICATIONS

CN108245109A—machine translation (Year: 2018). cited by examiner

KR0165042B1—machine translation (Year: 1999). cited by examiner

JP2008125702A—machine translation (Year: 2008). cited by examiner

International Search Report and Written Opinion of the International Searching Authority dated Jan. 26, 2022, in connection with International Application No. PCT/KR2021/095087, 21 pages. cited by applicant

Supplementary European Search Report dated Nov. 28, 2023, in connection with European Patent Application No. 21886989.9, 10 pages. cited by applicant

Primary Examiner: Ayalew; Tinsae B

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a bypass continuation of International Application No. PCT/KR2021/095087, filed Oct. 25, 2021, which claims priority to Korean Patent Application No. 10-2020-0140973, filed Oct. 28, 2020, the disclosures of which are herein incorporated by reference in their entirety.

BACKGROUND

1. Field

(1) The disclosure relates to a dishwasher. More particularly, the disclosure relates to a dishwasher including a basket movable in a vertical direction to form an accommodation space.

2. Description of Related Art

(2) A dishwasher is a device for washing dishes by spraying high-pressure washing water onto the dishes. A general configuration of a dishwasher includes a machine room including a sump and a washing pump, a washing tub for washing, a basket for accommodating dishes, and a spray nozzle for spraying washing water, or the like, and the washing water sprayed from the spray nozzle by the washing pump washes an object to be washed.

(3) Objects to be washed in the dishwasher include bulky kitchen utensils such as pots and frying pans in addition to cutlery including bowls, cups, spoons, forks, knives, or the like, and these objects to be washed are mounted at appropriate positions in a basket. Therefore, the basket of the dishwasher had to be able to efficiently accommodate various volumes of washing objects, and the basket had to have a structure in which the objects to be washed could be stably sprayed with washing water.

(4) Since the height and width of the dishwasher are limited, there is a limit to the objects to be washed that can be accommodated. Accordingly, in a situation where there are many objects to be washed or a situation where a bulky object to be washed is required to be washed, there was inconvenience of operating the dishwasher multiple times. Therefore, there has been a technical need to accommodate a large amount and a bulky object to be washed in a limited space and to improve washing performance at the same time.

(5) An object of the disclosure is to solve the problem described above, and it is an object of the disclosure to provide a dishwasher including a basket that is movable in a vertical direction to form an accommodation space.

SUMMARY

(6) According to an embodiment of the disclosure, a dishwasher includes a main body provided with a washing tub inside, a first basket disposed inside the washing tub and configured to accommodate an object to be washed, and a second basket configured to accommodate the object to be washed, and move in a vertical direction between a first position disposed in a partial area inside the first basket, and a second position disposed above the partial area spaced apart from the first basket.

(7) The first basket is composed of a plurality of wires at different intervals.

(8) The plurality of wires include: a plurality of first wires disposed in the partial area where the second basket is disposed at a first interval, and a plurality of second wires disposed outside of the partial area and disposed at a second interval that is narrower than the first interval, wherein the plurality of first wires interferences less with a flow of washing water than the plurality of second wires.

(9) The first basket is configured to, based on the second basket positioned in the first position, accommodate the object to be washed in another area, and based on the second basket being in the second position, accommodate the object to be washed in both the partial area and the another area, thereby accommodating an object to be washed with a relatively large washing area.

(10) The first basket includes a plurality of tines formed on the plurality of second wires, among the plurality of wires, to support the object to be washed.

(11) The second basket includes a plurality of ribs having an inclined shape to support the object to be washed.

(12) The second basket includes a guide member coupled to the first basket and extending in the vertical direction, and the guide member includes a guide portion configured to guide a movement of the second basket, and a fixing unit configured to fix the second basket to the second position.

(13) The second basket is configured to include a roller coupled to the guide member, and the guide member is formed in a shape of a rail for guiding the movement of the roller.

(14) The guide member includes: a front guide member configured to support a front of the second basket, and a rear guide member configured to support a rear of the second basket.

(15) The front guide member further includes a pivot guide portion configured to guide the second basket to be pivotable in an upper direction from the fixing portion at the second position.

(16) The second basket includes a support wire disposed on one side of the second basket to support the object to be washed and prevent separation.

(17) The support wire includes: a first support wire positioned on a rear side of the second basket, and a second support wire positioned on left and right sides of the second basket.

(18) The support wire fixed to the first basket and extends in the vertical direction.

(19) The dishwasher further comprises: a main spray nozzle configured to spray washing water into the first basket, a duct configured to supply washing water to the main spray nozzle and an additional spray nozzle configured to spray washing water to a position where the second basket is fixed on an upper portion.

(20) The duct is configured to include a docking hole that is opened and closed by a docking of the additional spray nozzle, and the additional spray nozzle is fixed to the second basket and docked in

the docking hole based on the second basket moving to the second position.

(21) Before undertaking the DETAILED DESCRIPTION below, it may be advantageous to set forth definitions of certain words and phrases used throughout this patent document: the terms “include” and “comprise,” as well as derivatives thereof, mean inclusion without limitation; the term “or,” is inclusive, meaning and/or; the phrases “associated with” and “associated therewith,” as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, or the like.

(22) Definitions for certain words and phrases are provided throughout this patent document, those of ordinary skill in the art should understand that in many, if not most instances, such definitions apply to prior, as well as future uses of such defined words and phrases.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a more complete understanding of the present disclosure and its advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which like reference numerals represent like parts:

(2) FIG. 1 is a perspective view illustrating a dishwasher according to an embodiment;

(3) FIG. 2 is a side cross-sectional view illustrating a dishwasher according to an embodiment;

(4) FIGS. 3A and 3B are perspective views illustrating a first basket and a second basket according to an embodiment;

(5) FIGS. 4A to 4D are side views illustrating a movement of a second basket according to an embodiment;

(6) FIG. 5 is a perspective view illustrating a first basket and a second basket according to an embodiment; and

(7) FIGS. 6A and 6B are exploded perspective views illustrating a coupling structure of an additional spray nozzle according to an embodiment.

DETAILED DESCRIPTION

(8) FIGS. 1 through 6B, discussed below, and the various embodiments used to describe the principles of the present disclosure in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the disclosure. Those skilled in the art will understand that the principles of the present disclosure may be implemented in any suitably arranged system or device.

(9) In the following description, same drawing reference numerals are used for the same elements even in different drawings. In the following description, well-known functions or constructions are not described in detail since they would obscure the invention in unnecessary detail. Further, dimensions of various elements in the accompanying drawings may be arbitrarily increased or decreased for assisting in a comprehensive understanding.

(10) The terms used in the disclosure and the claims are general terms selected in consideration of the functions of the various example embodiments of the disclosure. However, such terms may be varied depending on an intention of those skilled in the art, a legal or technical interpretation, an emergence of a new technology, and the like. Also, there may be some terms arbitrarily selected by an applicant. Such terms may be construed according to meanings defined in the present specification and may also be construed based on general contents of the present specification and a typical technical concept in the art unless the terms are not specifically defined.

(11) In the description of the disclosure, the order of each operation should be understood as non-limiting unless a preceding operation must be logically and temporally performed before a subsequent operation. In other words, except for the exceptional cases described above, even if the

process described as the subsequent operation is performed before the process described as the preceding operation, an essence of the disclosure is not affected, and the scope of rights should also be defined regardless of the order of the operations.

(12) As used herein, the terms such as “have”, “may have”, “include”, “may include”, or the like may indicate the presence of the corresponding characteristic (e.g., a numerical value, function, operation, or component such as a part), and does not exclude the presence of an additional characteristic.

(13) The terms such as “first,” “second,” and so on may be used to describe a variety of elements, but the elements should not be limited by these terms. The terms are only used to differentiate one component from other components. For example, the ‘first’ component may be named the ‘second’ component, and vice versa, without departing from the scope of the disclosure.

(14) In addition, the terms such as “outer peripheral surface”, “inner peripheral surface”, “top surface”, “bottom surface”, “side surface”, “left”, “right”, “top”, “bottom”, “area”, or the like used in the disclosure are defined based on figures, and the shape and position of each component are not limited by this term.

(15) In addition, since the disclosure describes components necessary for a description of each embodiment of the disclosure, the disclosure is not necessarily limited thereto. Accordingly, some components may be changed or omitted, and other components may be added. In addition, they may be distributed and arranged in different independent devices.

(16) Furthermore, although embodiments of the disclosure will be described in detail below with reference to the accompanying drawings and the contents described in the accompanying drawings, the disclosure is not restricted or limited by the embodiments.

(17) Hereinafter, the disclosure will be described in more detail with reference to FIGS. **1** to **6B**.

(18) FIG. **1** is a perspective view illustrating a dishwasher **10** according to an embodiment of the disclosure.

(19) Referring to FIG. **1**, the dishwasher **10** may include a main body **15** forming an exterior and a door **12** for opening and closing the inside of the body **15**.

(20) The dishwasher **10** is a device for washing by spraying washing water on an object to be washed such as dishes, or the like, and may be classified into various types according to the structure and arrangement method of the main body **15**. Types of the dishwasher **10** may include a built-in method in which a part of a furniture cabinet, which is an external support, is separated and installed in an empty space, a free-standing method that can be independently disposed, a counter top method placed on top counters such as furniture cabinets, an in-sink method that is manufactured and installed integrally with the dishwasher **10**, or the like.

(21) The dishwasher **10** shown in FIG. is a built-in type dishwasher **10** generally used for home use, but the dishwasher **10** including a basket **100** of the disclosure is not limited thereto, and may be applied to the basket **100** of the other types of dishwashers **10**.

(22) The door **12** has a structure that is rotatably installed on a front side of the main body **15**, and a control device for the user to control the dishwasher **10** may be provided on the upper portion of the door **12**, and the user may easily open and close the door **12** and operate the dishwasher **10**. A washing tub **20** may be provided inside the door **12**.

(23) FIG. **2** is a side cross-sectional view of the dishwasher **10** according to an embodiment of the disclosure.

(24) Referring to FIG. **2**, the dishwasher **10** may include a washing tub **20**, a machine room **40**, and baskets **50** and **100**.

(25) The baskets **50** and **100** may be respectively disposed at the upper end and lower end of the washing tub **20**. The baskets **50** and **100** is to support and accommodate objects to be washed, and may be composed of a frame, a plurality of racks, a plurality of wires, or the like, and may be referred to as a rack assembly according to a structure.

(26) According to an arrangement position of the baskets **50** and **100**, it may be divided into an

upper basket **50** and a lower basket **100**. Since an injection pressure of a spray nozzle **26** located close to the machine room **40** is stronger, a washing performance of the lower end of the washing tub **20** may be relatively good in the structure in which the machine room **40** is formed at the lower end of the washing tub **20**. Accordingly, a space of the lower end of the dishwasher **10** is often larger than that of the upper end. Hereinafter, in consideration of an effect of an expansion of an accommodating space, the lower basket **100** will be described as the basis for convenience, but the upper basket **50** may have the same structure as the lower basket **100**.

(27) The washing tub **20** is a space provided inside the main body **15**, and the washing tub **20** may include a plurality of baskets **50** and **100** in which dishes to be washed are mounted, and a plurality of spray nozzles **26**.

(28) The spray nozzle **26** may be provided on an upper portion of the upper basket **50** located at the uppermost side and be disposed between the upper spray nozzle **26** for spraying washing water, a middle spray nozzle **26** disposed between the upper basket **50** and the lower basket **100** to spray the washing water into each of the baskets **50** and **100**, and the lower spray nozzle **26** for spraying washing water from the lower portion to the lower basket **100**. In addition, although not shown in FIG. 2, as will be described in detail below with reference to FIG. 5, the dishwasher **10** of the disclosure may further include an additional spray nozzle **140**, and the spray nozzle **26** described above may be referred to as a main spray nozzle **26** in order to distinguish the nozzles.

(29) The spray nozzle **26** may be connected to a sump **42** by a duct **28** to receive washing water. The spray nozzle **26** may have a structure for spraying the washing water in various directions at a fixed position, or may rotate and evenly spray the washing water into the plurality of baskets **50** and **100**.

(30) A heater **30** for heating the washing water may be provided on a bottom surface of the washing tub **20**, and a machine room **40** may be provided under the washing tub **20**.

(31) The sump **42** may be provided in the machine room **40** to collect and pump the washing water supplied into the washing tub **20** to move the washing water to the spray nozzle **26**.

(32) In addition, a plurality of passages and a circulation pump **46** for pumping water to the plurality of passages are provided in the sump **42**, and a drain pump **48** for discharging contaminated washing water to the outside through a drain pipe may be provided on one side of the sump **42**.

(33) Hereinafter, an operation process of the dishwasher **10** configured as described above will be described.

(34) When power is applied while an object to be washed is stored in the baskets **50** and **100** inside the washing tub **20**, washing water required for washing may start to be supplied into the washing tub **20** through a washing water supply hole.

(35) After the washing water supplied into the washing tub **20** may be collected into the sump **42** provided at the bottom of the washing tub **20**, a washing process may be proceeded by supplying the washing water collected by a pumping action of an internal circulation pump **46** of the sump **42** to the spray nozzle **26** through the duct **28**, and spraying the washing water at high pressure to the objects to be washed stored in the respective baskets **50** and **100**.

(36) When the washing process is completed, not only the washing water but also the contaminants on the objects to be washed are washed by the washing water and collected in the sump **42**, such that the washing water containing the contaminants may be discharged to the outside through a drain pipe according to an operation of the drain pump **48**.

(37) When the washing water containing contaminants is discharged to the outside, clean washing water may be collected again into the sump **42** through a washing water supply hole, and the washing water may be sprayed to the objects to be washed at high pressure through each spray nozzle **26** in the same manner as the washing process, thereby processing a rinsing cycle.

(38) When the rinsing cycle is completed, a drying cycle may be performed, and in the drying cycle, a heater **30** may be driven such that a high-temperature washing water may be sprayed on the

objects to be washed and the washing water may be evaporated and dried together with the washing water remaining in the process of vaporizing the high-temperature washing water. Alternatively, high-pressure hot air may be sprayed in the drying cycle. When drying is completed, the washing process may be terminated.

(39) FIGS. 3A and 3B are perspective views of a first basket **110** and a second basket **120** according to an embodiment of the disclosure.

(40) Referring to FIG. 3A, the basket **100** of the dishwasher **10** may include a first basket **110** and a second basket **120**.

(41) The first basket **110** may be disposed inside the washing tub **20** to accommodate an object to be washed. The first basket **110** may accommodate the object to be washed therein and may support the object to be washed such that the washing water sprayed from the spray nozzle **26** is well aimed at the object to be washed. Since a plurality of wheels are included on both sides of the first basket **110**, the user may easily move the first basket **110** from a guide rail of the washing tub **20**.

(42) The first basket **110** may be formed of a frame in which at least a portion of the bottom surface is open, forming an outer periphery, and the frame may have a structure in which a plurality of wires **111** are spaced apart and combined. Particularly, on a bottom surface of the first basket **110**, the plurality of wires **111** are spaced apart from each other in parallel to support the object to be washed and to pass washing water into the spaced space.

(43) The main spray nozzle **26** located at the bottom and/or top of the first basket **110** may spray washing water toward the object to be washed accommodated in the first basket **110**, and the sprayed washing water may be discharged downward through the bottom surface of the first basket **110**. Therefore, since the plurality of wires **111** on the bottom surface of the first basket **110** may become obstacles for spraying and discharging the washing water, the smaller an area occupied by the plurality of wires **111** is, the more advantageous a movement of the washing water is, and thus cleaning performance may be improved. Therefore, the lower end of the first basket **110** may be formed of a minimum number of wires **111** for supporting the object to be washed.

(44) The second basket **120** may be movable in a vertical direction and may accommodate an object to be washed. The second basket **120** may be disposed in a partial area of an interior of the first basket **110**, may have a smaller volume than the first basket **110**, and may be placed parallel to the first basket **110** on the bottom surface of the first basket **110**.

(45) The second basket **120**, like the first basket **110**, may accommodate an object to be washed therein and introduce and discharge washing water, such that the second basket **120** may be made of the same or similar structure and material as the first basket **110**, and may be composed of a plurality of wires **111**.

(46) The second basket **120** may be composed of a plurality of ribs **121** having an inclined shape to support the object to be washed. The plurality of ribs **121** may be formed of the plurality of wires **111**. The plurality of ribs **121** may be fixed so as not to be shaken or moved during washing by mounting the object to be washed at an angle. The plurality of ribs **121** may be effective in supporting an object to be washed such as a bowl having a concave shape. An angle of an inclination may be formed to correspond to a spraying direction of the additional spray nozzle **140** to be described below with reference to FIGS. 6A and 6B.

(47) Although not shown in the figures, the second basket **120** may include a plurality of tines and may support dishes such as plates in an upright state. In this case, a support wire **125** may also have a structure for supporting an object to be mounted, and a spraying direction of the additional spray nozzle **140** may be changed to correspond to the mounting structure of the mounting target.

(48) The second basket **120** may include the support wire **125** disposed on one side of the second basket **120** to support an object to be washed and prevent separation. The support wire **125** may include a plurality of first support wires **126** positioned on a rear side of the second basket **120** and a second support wire **127** positioned on both left and right sides of the second basket **120**.

(49) As shown in FIG. 3A, the support wire **127** may be fixed to the first basket **110** and may have a shape extending in a vertical direction, or, although not shown in the figures, a side frame of the second basket **120** may have a shape extending in the vertical direction.

(50) An extended height of the support wire **125** may be higher than a height at which the second basket **120** moves in the vertical direction. The support wire **125** may prevent the object to be washed of the second basket **120** from falling downward when the second basket **120** is located on the upper portion and is being washed. As the support wire **125** is formed on both sides and the rear side, a front portion of the second basket **120** may include a bump structure of the frame to prevent separation of the object to be washed.

(51) Referring to FIG. 3B, the second basket **120** may move up and down inside the first basket **110**.

(52) The second basket **120** may be movable in the vertical direction between a first position and a second position by a guide member **130** located on a side frame of the first basket **110** and may be fixed at the second position. The movement in the vertical direction may include not only movement of 90 degrees from a horizontal direction, but all movement moving upward from the horizontal direction. In other words, the movement of inclined straight line, curved line, or broken line shape may also be included in the movement in the vertical direction. A movement of the guide member **130** and the second basket **120** will be described below in detail with reference to FIGS. 4A to 4B.

(53) Due to the movement of the second basket **120**, the first basket **110** may have a variable accommodation space. For convenience of description, the first basket **110** may be divided into a partial area A in which the second basket **120** is disposed and the other area B which is an external area excluding this area. In addition, the plurality of wires **111** may include a plurality of first wires **112** disposed in the partial area A, and a plurality of wires **111** disposed in the other area B may include a plurality of second wires **113**.

(54) In a state in which the second basket **120** is positioned at the first position, which is a partial area inside the first basket, an object to be washed may be mounted on the second basket **120** corresponding to the partial area of the first basket **110**. Therefore, in this state, the object to be washed may be accommodated in the other area B of the first basket **110** and the second basket **120**.

(55) In a state in which the second basket **120** is spaced apart from the first basket **110** and positioned at the second position disposed above the partial area A, the first basket **110** and the second basket **120** may be spaced apart from each other, and a space for accommodating dishes may be formed between the partial area A of the first basket **110** and the second basket **120**. Therefore, in this state, the object to be washed may be accommodated in both the partial area A and the other area B of the first basket **110** and the second basket **120**. Therefore, the first basket **110** may have a relatively large washing area and accommodate a bulky object to be washed.

(56) The dishwasher **10** of the disclosure may increase an efficiency of space utilization by moving the second basket **120**. Particularly, as shown in FIG. 3B, when the first basket **110** accommodates a relatively large pan **60**, a pot **65**, etc. among the objects to be washed, the first basket **110** may have a limit in accommodating other cleaning objects. However, in the dishwasher **10** of the disclosure, the second basket **120** may move upward and be fixed at the second position, such that the second basket **120** may additionally accommodate dishes and the like.

(57) Some of the plurality of wires **111** may be spaced apart from the other plurality of wires **111** at different intervals. Specifically, a spacing between the plurality of first wires **112** and the plurality of second wires **113** may be different, and the plurality of second wires **113** may be disposed at a narrower interval than the plurality of first wires **112**.

(58) In the dishwasher **10**, if the object to be washed moves away or moves during washing, washing water may not be properly delivered to the object to be washed and may interfere with washing away foreign substances in the washing water. Therefore, the first basket **110** should

include fixing portions such as a plurality of wires **111** and a plurality of tines in order to fix the object to be washed, but if a volume occupied by the fixing portion increases, it may become an obstacle to the movement of washing water as described above, it may improve, by minimizing this, washing performance and efficiency.

(59) In the first basket **110**, in some areas where the plurality of first wires **112** are located, when the second basket **120** is at the lower portion, the object to be washed may be accommodated and supported in the second basket **120**, and when the second basket **120** is located at the upper portion, the pan **60**, the pot **65**, etc. may mainly accommodate and support a bulky object to be washed. Therefore, the plurality of first wire **112** may be formed wider at the arrangement intervals than the plurality of second wire **113**, and the partial area A has less interference with a flow of washing water than other area B, and thus it may be possible to accommodate a relatively bulky object to be washed in the accommodation space, while at the same time effectively delivering washing water and improving washing performance.

(60) The first basket **110** may include the plurality of tines supporting the object to be washed, and the plurality of tines may be selectively formed only on the plurality of second wires **113** among the plurality of wires **111**. By partially forming the plurality of tines, the other area B may effectively support the object to be washed by the plurality of tines, and the partial area A may reduce obstacles in passing the washing water.

(61) Through the structure of the first basket **110** and the second basket **120** described above, the second basket **120** may accommodate dishes having a concave shape, and the other area B may accommodate a plate, cutlery, etc. by the plurality of tines, and the partial area A may accommodate the pan **60**, the pot **65**, etc., and thus the first basket **110** has an advantage that it can accommodate various types and shapes of dishes.

(62) Therefore, the dishwasher **10** of the disclosure may accommodate a bulky object to be washed, increase space efficiency by moving the second basket **120** and by the structure of the first basket **110** and the second basket **120**, and increase space efficiency. Also, as the spacing between the plurality of wires **111** of the first basket **110** is changed, the washing performance of the bulky object to be washed may be improved.

(63) FIGS. **4A** to **4D** are side views illustrating a movement of the second basket **120** according to an embodiment of the disclosure.

(64) Referring to FIG. **4A**, the second basket **120** may include a guide member **130**.

(65) The guide member **130** may be coupled to the first basket **110** and have a shape extending in the vertical direction. The second basket **120** may include a coupling member coupled to the guide member **130** to be guided along a predetermined movement path. The coupling member of the second basket **120** may be formed as a protrusion or a receiving portion corresponding to the structure of the guide member **130**, or the guide member **130** may be formed in a rail shape, such that the second basket **120** may include a roller coupled to the guide member **130** to be guided by the guide member **130**. The second basket **120** may be moved smoothly by the roller, and the user may move the second basket **120** intuitively and easily.

(66) The guide member **130** may be coupled to a side surface of the first basket **110** to position the second basket **120** inside the first basket **110**. The guide member **130** may form a single body, or the second basket **120** may include a plurality of guide members **130**. A front guide member **137** supporting the front of the second basket **120** and a rear guide member **139** supporting the rear of the second basket **120** may each be coupled to the first basket **110**.

(67) Referring to FIG. **4B**, the guide member **130** may include a guide portion **131**.

(68) The guide portion **131** may guide a movement of the second basket **120**. A starting point of the guide portion **131** may be set to a position where at least a portion of the bottom surface of the first basket **110** and the bottom surface of the second basket **120** contact each other. The second basket **120** may be in contact with the upper surface of the partial area A of the first basket **110** to accommodate and support the object to be washed. At the starting point of the guide portion **131**,

since the second basket **120** is fixed to the lower end by its own weight, a separate fixing portion may be omitted, or the second basket **120** may be fixed so as not to be pushed by the washing water by including a separate locking structure.

(69) The guide portion **131** may have a linear shape to guide the second basket **120** in a straight direction, but is not limited thereto, and may have an oblique, curved, or broken line shape.

(70) An end point of the guide portion **131** may be formed adjacent to a height at which the second basket **120** is fixed thereto. There is no limit to a movement range of the second basket **120** between the starting point and the ending point of the guide portion **131**, but it may have a height equal to or higher than the upper surface of the first basket **110** by considering that a spatial range of the washing tub **20** is limited, the upper surface of the first basket **110** and the same or may have a high degree of height, or it may be designed to be higher than the height of the pan **60** or the pot **65** generally used at home by considering the space between the first basket **110** and the second basket **120**.

(71) Referring to FIG. 4C, the guide member **130** may include a fixing portion **133**.

(72) The fixing portion **133** may fix the second basket **120** at the second position. The fixing portion **133** may be connected to an end point of the guide portion **131** such that the second basket **120** may be separated from the guide portion **131** to be fixed. A method of fixing may be various. For example, the second basket **120** may further include a separate fixing portion, the second basket **120** may include a fixing groove, or the fixing portion **133** of the guide member **130** may include a magnet to attract and fix the fixing portion of the second basket **120** having magnetism.

(73) The fixing portion **133** may have a shape extending in the horizontal direction from the guide portion **131** as shown in FIG. 4C or may have a structure inclined downward from the horizontal direction. In this case, the second basket **120** may be pushed back to escape from the guide portion **131** and be fixed to the fixing portion **133**.

(74) Referring to FIG. 4D, the guide member **130** may include a pivot guide portion **135**.

(75) The pivot guide portion **135** may guide the second basket **120** to be pivotable from the fixing portion **133** in the upper direction. The pivot guide portion **135** may have a shape in which the guide portion **131** extends upward from the fixing portion **133** within a predetermined angle and range.

(76) The pivot guide portion **135** may be formed on a front guide member **137** of the guide member **130**. In this case, the front side of the second basket **120** may be pivoted by the pivot guide portion **135** while the rear side may be fixed to the fixing portion **133**. When the first basket **110** and the second basket **120** are spaced apart and a bulky pan **60** or pot **65** is put on a partial area A of the first basket **110**, the front of the second basket **120** may be pivoted, and the object to be washed may be easily mounted on the accommodation space without being caught in the second basket **120**.

(77) FIG. 5 is a perspective view illustrating the first basket **110** and the second basket **120** according to an embodiment of the disclosure.

(78) Referring to FIG. 5, the dishwasher **10** may include an additional spray nozzle **140**.

(79) The additional spray nozzle **140** may have the second basket **120** positioned on the rear surface to spray the washing water to the object to be washed of the second basket **120**. For example, when the second basket **120** is located at the upper portion, the additional spray nozzle **140** may spray the washing water to the second basket **120**, and when the second basket **120** is located at the lower portion, the main spray nozzle **26** located on the upper or lower portion of the first basket **110** may spray the washing water into the second basket **120**. The duct **28** may be connected to the main spray nozzle **26** and the additional spray nozzle **140** to supply washing water.

(80) The additional spray nozzle **140** may have a structure fixed to the duct **28**, or the additional spray nozzle **140** may include a docking member **141** to be detachable from a docking hole **147** of the duct **28**.

(81) The additional spray nozzle **140** may spray the washing water to the object to be washed of the second basket **120** only when the second basket **120** is located on the upper portion. When the second basket **120** is positioned at the lower portion, the supply of washing water may be interrupted by interlocking with the movement of the second basket **120**, or the additional spray nozzle **140** may be separated from the docking hole **147**.

(82) The docking hole **147** may be opened and closed by docking of the additional spray nozzle **140**. The docking hole **147**, by including a door, may maintain the door closed in a state in which the additional spray nozzle **140** is not docked, such that the washing water does not pass, and when the additional spray nozzle **140** is docked, the door is opened and the docking hole **147** may transmit the washing water to the additional spray nozzle **140**.

(83) The opening and closing structure of the docking hole **147** may be implemented in various ways. The door of the docking hole **147** has a structure divided into a plurality of zones, the additional spray nozzle **140** is docked, the docking member **141** pushes the door to open the door, and the washing water may be transmitted through the docking hole **147**. Alternatively, the docking hole **147** may include a plurality of elastic protrusions therein, and the plurality of elastic protrusions may serve to prevent the washing water from flowing into the docking hole **147**, and when the additional spray nozzle **140** is docked, the docking member **141** may form a space through which the washing water can pass by pushing the plurality of elastic protrusions.

(84) The additional spray nozzle **140** may be coupled to the second basket **120** and move together with the second basket **120**. The fixing portion **133** of the guide member **130** has a structure for guiding the second basket **120** in a horizontal direction, and the additional spray nozzle **140** may move to the rear side together with the second basket **120**, and when the second basket **120** is located at the end of the fixing portion **133**, the docking member **141** of the additional spray nozzle **140** may be in contact with and connected to the docking portion. Even when the second basket **120** moves to the front and is separated from the fixing portion **133**, the docking member **141** of the additional spray nozzle **140** may be separated from the docking hole **147** and the docking hole **147** may be closed. In this case, the user may dock or separate the additional spray nozzle **140** by only moving the second basket **120** without docking and releasing the additional spray nozzle **140**.

(85) When the second basket **120** is located at the upper portion, the bulky pan **60**, pot **65**, etc. may be accommodated in a space spaced apart between the first basket **110** and the second basket **120**, and thus the lower main spray nozzle **26** may have a limitation in spraying the washing water to the object to be washed of the second basket **120**. The additional spray nozzle **140** may be selectively docked only when the second basket **120** is positioned on the upper portion to spray the washing water, thereby improving washing performance.

(86) The docking hole **147** may supply washing water to the additional spray nozzle **140** as needed, such that when the additional spray nozzle **140** is not docked, it may be possible to prevent a problem in which the washing water is lost and a spray pressure of the washing water is lowered, and the amount of water used may be reduced, thereby increasing washing efficiency and reducing water consumption by the docking hole **147** selectively opened and closed according to the position of the second basket **120**.

(87) FIGS. **6A** and **6B** are exploded perspective views illustrating a coupling structure of the additional spray nozzle **140** according to an embodiment of the disclosure.

(88) Referring to FIG. **6A**, the additional spray nozzle **143** may spray the washing water in a direction inclined upward with respect to a horizontal direction.

(89) The additional spray nozzle **143** may be docked in the docking hole **147** through the docking member **141** located at the rear side. The additional spray nozzle **143** may have a bar shape extending in a horizontal direction, and may spray washing water through a plurality of spray holes formed on the front surface.

(90) In consideration of the angle at which the plurality of ribs **121** of the second basket **120** are inclined, the plurality of spray holes of the additional spray nozzle **143** may be inclined in a

spraying direction of the nozzle to spray the washing water to an internal washing area of the object to be washed. When the object to be washed of the second basket **120** is supported to be inclined upward with respect to the horizontal direction, the additional spray nozzle **143** may spray the washing water in a direction inclined upward with respect to the horizontal direction, and the object to be washed mounted on the second basket **120** may be washed.

(91) Referring to FIG. **6B**, the additional spray nozzle **145** may spray the washing water in a vertical direction.

(92) The additional spray nozzle **145** may have a structure including a plurality of rods in which a plurality of spray holes is formed. The plurality of rods may be disposed parallel to each other and may spray the washing water in the vertical direction, respectively. Through this structure, washing water may be sprayed with a strong spray pressure even to an object to be washed from a relatively long distance, and as the plurality of spray holes of the additional spray nozzle **145** are widely distributed, a wider range may be washed.

(93) Although not shown in the figures, the dishwasher **10** may include a lever for moving the second basket **120** and the additional spray nozzle **140**, and the user may push and pull the lever with the second basket **120** to move the second basket **120** and the additional spray nozzle **140**. Alternatively, a driving device may be controlled by a processor (not shown) of the dishwasher **10**, including a driving device for moving the guide member **130** or opening and closing the docking hole **147**.

(94) Although the preferred exemplary embodiments of the disclosure have been disclosed for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the disclosure as disclosed in the accompanying claims. Accordingly, such modifications, additions and substitutions should also be understood to fall within the scope of the disclosure.

(95) Although the present disclosure has been described with various embodiments, various changes and modifications may be suggested to one skilled in the art. It is intended that the present disclosure encompass such changes and modifications as fall within the scope of the appended claims.

Claims

1. A dishwasher comprising: a main body; a washing tub provided inside the main body; a first basket disposed inside the washing tub; and a second basket configured to: move in a vertical direction between a first position disposed in a partial area inside the first basket, and a second position disposed above the partial area spaced apart from the first basket, wherein the second basket includes a guide member that is coupled to a side frame of the first basket and extends in the vertical direction, wherein, when the second basket is positioned at the first position, the second basket is parallel to the first basket and touches the bottom surface of the first basket, wherein, when the second basket is positioned at the first position, the first basket and the second basket are able to accommodate objects to be washed in another area, wherein, in a state in which the second basket is positioned at the second position, the second basket is spaced apart from a bottom surface of the first basket, the first basket and the second basket are parallel to each other, and the first basket and the second basket are able to accommodate objects to be washed in both the partial area and the another area, wherein the guide member includes: a guide portion configured to guide a movement of the second basket, and a fixing unit configured to fix the second basket to the second position.

2. The dishwasher of claim 1, wherein the first basket is composed of a plurality of wires spaced apart at different intervals.

3. The dishwasher of claim 2, wherein: the plurality of wires include: a plurality of first wires disposed in the partial area where the second basket is disposed at a first interval, and a plurality of

second wires disposed outside of the partial area and disposed at a second interval that is narrower than the first interval, and the plurality of first wires interferes less with a flow of washing water than the plurality of second wires.

4. The dishwasher of claim 3, wherein the first basket is configured to: based on positioning the second basket in the second position, support an object to be washed in both the partial area and outside the partial area.

5. The dishwasher of claim 3, wherein the first basket includes a plurality of tines formed on the plurality of second wires, among the plurality of wires, to support the object to be washed.

6. The dishwasher of claim 1, wherein the second basket includes a plurality of ribs having an inclined shape to support the object to be washed.

7. The dishwasher of claim 1, wherein: the second basket is configured to include a roller coupled to the guide member, and the guide member is formed in a shape of a rail for guiding the movement of the roller.

8. The dishwasher of claim 1, wherein the guide member includes: a front guide member configured to support a front of the second basket, and a rear guide member configured to support a rear of the second basket.

9. The dishwasher of claim 8, wherein the front guide member further includes a pivot guide portion configured to guide the second basket to be pivotable in an upper direction from a fixing portion at the second position.

10. The dishwasher of claim 1, wherein the second basket includes a support wire disposed on one side of the second basket to support the object to be washed and prevent separation.

11. The dishwasher of claim 10, wherein the support wire includes: a first support wire positioned on a rear side of the second basket, and a second support wire positioned on left and right sides of the second basket.

12. The dishwasher of claim 10, wherein the support wire is fixed to the first basket and extends in the vertical direction.

13. The dishwasher of claim 1, further comprising: a main spray nozzle configured to spray washing water into the first basket; a duct configured to supply washing water to the main spray nozzle; and an additional spray nozzle configured to spray washing water to a position where the second basket is fixed on an upper portion.

14. The dishwasher of claim 13, wherein: the duct is configured to include a docking hole that is opened and closed by a docking of the additional spray nozzle, and the additional spray nozzle is fixed to the second basket and docked in the docking hole based on the second basket moving to the second position.

15. A dishwasher basket assembly, comprising: a first basket, the first basket comprising: a horizontal portion having four sides; a vertical portion extending upwards from the four sides of the horizontal portion to define a perimeter of the first basket; a pair of front guide members disposed on opposing sides of the perimeter of the first basket, and wherein each front guide member is disposed toward a front of the first basket; and a pair of rear guide members disposed on opposing sides of the perimeter of the first basket, wherein each rear guide member is disposed towards a rear of the first basket, and a second basket, the second basket comprising: a horizontal portion, having a front end and a rear end, wherein the front end of the horizontal portion of the second basket is configured to move vertically within the front guide members between a first position and a second position, wherein the rear end of the horizontal portion of the second basket is configured to move vertically within the rear guide members between the first position and the second position, and wherein the horizontal portion of the second basket is parallel with the horizontal portion of the first basket in the first position.

16. The dishwasher basket assembly of claim 15, wherein front guide members of the pair of front guide members each comprise a pivot portion, and wherein rear guide members of the pair of rear guide members each comprise a rear fixing portion.

17. The dishwasher basket assembly of claim 16, wherein the front guide members of the pair of front guide members each comprise a front fixing portion.

18. The dishwasher basket assembly of claim 17, wherein the front end of the horizontal portion is configured to move upwards within the pivot portion of each front guide member of the pair of front guide members to a third position, and wherein in the third position, the horizontal portion of the second basket is angled relative to the horizontal portion of the first basket.

19. The dishwasher basket assembly of claim 15, wherein the second basket includes a plurality of ribs having an inclined shape to support an object to be washed.
