

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250249320

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Bamber; Jeffrey V

---

### Golf Clubs Having Weighting System With Movable Weights

---

#### Abstract

Golf clubs having weighting systems with movable weights are disclosed. In one embodiment, the golf club head includes: a main body having a periphery; and a weighting system including a movable weight, wherein the weighting system is configured to allow the weight to move between: a first position inward of the periphery of the main body; and a second position wherein at least a portion of the weight is located outward of the periphery of the main body. In other cases, the movable weight need not be movable to a position that is outward of the periphery of the main body.

---

**Inventors:** Bamber; Jeffrey V (Cincinnati, OH)

**Applicant:** Bamber; Jeffrey V (Cincinnati, OH)

**Family ID:** 74066227

**Appl. No.:** 18/432010

**Filed:** February 04, 2024

#### Related U.S. Application Data

parent US continuation 17672587 20220215 parent-grant-document US 11918870 child US 18432010

parent US continuation 16920704 20200704 parent-grant-document US 11266889 child US 17672587

us-provisional-application US 62871129 20190706

---

#### Publication Classification

**Int. Cl.:** A63B53/06 (20150101); A63B53/02 (20150101); A63B53/04 (20150101); A63B53/08 (20150101)

## U.S. Cl.:

CPC     **A63B53/06** (20130101); **A63B53/02** (20130101); **A63B53/08** (20130101); **A63B60/04** (20151001); **A63B53/0466** (20130101); **A63B53/047** (20130101); **A63B2053/0491** (20130101); **A63B53/065** (20130101)

---

## Background/Summary

[0001] This application is a continuation of pending U.S. patent application Ser. No. 17/672,587 filed Feb. 15, 2022, which is a continuation of U.S. patent application Ser. No. 16/920,704 filed Jul. 4, 2020, now U.S. Pat. No. 11,266,889 B2, which claims priority to U.S. Provisional Patent Application No. 62/871,129 filed Jul. 6, 2019, the entire disclosure of such applications being incorporated herein by reference.

### FIELD OF THE INVENTION

[0002] The present invention relates to golf clubs, and more particularly to golf clubs having a weighting system with movable weights.

### BACKGROUND OF THE INVENTION

[0003] Patents relating to golf clubs include U.S. Pat. Nos. 5,419,560; 5,540,437; 6,702,693 B2; and 7,815,524 B2, and the references listed on the face and any subsequent pages thereof.

[0004] A number of patents and patent publications are directed to golf club heads with an adjustable center of gravity. Such patents include U.S. Patent Application Publication No. US 2019/0009143 A1, Myers (Callaway Golf Company). Some of these patents disclose metal wood club heads having a channel and a slidable weight assembly disposed in their soles or skirt portion. The adjustability of the moment of inertia and center of gravity of such club heads is, however, limited due to the fact that the slidable weight assembly is confined to locations within the periphery of the club head.

[0005] There remains a need for weighting mechanisms that allow for adjusting the moment of inertia and center of gravity of such club heads to an even greater degree.

### SUMMARY OF THE INVENTION

[0006] The present invention relates to golf clubs, and more particularly to golf clubs having a weighting system with movable weights. This can allow the moment of inertia and center of gravity to be adjusted.

[0007] There are numerous, non-limiting embodiments of the invention. All embodiments, even if they are only described as being “embodiments” of the invention, are intended to be non-limiting (that is, there may be other embodiments in addition to these), unless they are expressly described as limiting the scope of the invention. Any of the embodiments described herein can also be combined with any other embodiments in any manner to form still other embodiments.

[0008] The golf clubs may comprise metal woods, hybrids, irons, “crossover irons”, or putters. The golf clubs may comprise movable features, such as a weighting system, that have one or more weights that are movable from a first position to a second position. In some cases, the movable weight may be movable from a position inward of the periphery of the main body of the club head to a position that is outward of the periphery of the main body. In other cases, the movable weight need not be movable to a position that is outward of the periphery of the main body.

[0009] In one embodiment, the golf club head comprises: [0010] a main body having a periphery; and [0011] a weighting system joined to said main body, said weighting system comprising a movable weight, wherein said weighting system is configured to allow the weight to move between: [0012] a first position that is located inward of the periphery of the main body; and [0013] a second position wherein at least a portion of said weight is located outward of the

periphery of said main body.

[0014] The weighting system can take several different forms. In some cases, the weighting system can comprise a track and at least one weight that is movable between different positions along the track. In some cases, the weighting system can comprise at least one weighted element that is movable from a retracted position to an extended position. In some cases, the latter type of weighted element may be biased to move in a particular direction, such as by one or more springs. In some cases, the weighting system can comprise at least one weighted element that is rotatable from a first angle to a second angle. Such a weighted element (or “rotatable weight element”) may provide rotation by being pivotable.

[0015] Other embodiments are also contemplated. A shaft and a grip can be further provided to form a golf club. The shaft has two ends, where one end is inserted into the club head, or into a hosel joined to the club head. The grip can be positioned on top of the other end of the shaft.

[0016] Any of the adjustable elements described herein can be adjustable in a manner that makes the golf club legal for tournament play according to the rules of the USGA. For instance, such clubs would typically not be adjustable during a round of golf.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0017] While the specification concludes with claims particularly pointing out and distinctly claiming the present invention, it is believed the invention will be better understood from the following description taken in conjunction with the accompanying drawings.

[0018] FIG. 1 is a front elevation view of one embodiment of a golf club head in a Cartesian coordinate system.

[0019] FIG. 1A is a perspective view of the Cartesian coordinate system shown in FIG. 1.

[0020] FIG. 2 is a top view of the golf club head shown in FIG. 1.

[0021] FIG. 3 is a rear elevation view of one embodiment of the golf club head shown in FIG. 1.

[0022] FIG. 4 is a rear elevation view of another embodiment of a golf club head which has a weighted perimeter portion.

[0023] FIG. 5 is an end view of an embodiment of an iron golf club head.

[0024] FIG. 6 is a rear elevation view of an alternative variation of the golf club head shown in FIG. 3.

[0025] FIG. 7 is a front elevation view of one embodiment of a metal wood golf club head.

[0026] FIG. 7A is a perspective view of the Cartesian coordinate system shown in FIG. 7.

[0027] FIG. 8 is a top view of the metal wood golf club head shown in FIG. 7.

[0028] FIG. 9 is a rear elevation view of one variation of the metal wood golf club head shown in FIG. 7.

[0029] FIG. 10 is a bottom view of a metal wood having an alternative type of weighting system.

[0030] FIG. 11 is a rear elevation view of an iron golf club head having an alternative type of weighting system.

[0031] FIG. 12 is an enlarged, partially fragmented rear elevation view showing a portion of a variation of the golf club head shown in FIG. 11.

[0032] FIG. 13 is a perspective view of an iron golf club head looking down the clubface, where the club head has another alternative type of weighting system.

[0033] FIG. 14 is a bottom view of a metal wood having an alternative type of weighting system.

### DETAILED DESCRIPTION OF THE INVENTION

[0034] The present invention relates to golf clubs, and more particularly to golf clubs having a weighting system with movable weights.

[0035] FIG. 1 shows one embodiment of the lower portion of a golf club 20. The golf club 20

comprises a club head **22** and a shaft **24**. The grip is conventional and is not shown. The club head **22** shown in FIG. **1** is of the “iron” type. It should be understood, however, that the weighting systems described herein are also applicable to: “wood” or “metal wood” club heads; “crossover irons” (player's irons with additional forgiveness); “hybrid” club heads which combine the features of irons and metal woods; and putters.

[0036] The club head **22** shown in FIG. **1** comprises a club face **28**, a back surface **30** (shown in FIG. **3**), a heel or heel portion **32**, a toe or toe portion **34**, a top edge **36**, and a sole **38**. The club face **28** has a leading edge **28A**, which may have a slight convex curvature. The club face **28** has a centerline, CL, which on irons will typically pass through the middle of the grooved portion **40** of the club face. Several representative grooves **42** are shown. The club face **28** may have additional grooves **42** in the region located vertically above the representative grooves shown. The club head **22** may comprise a hosel **26** joined adjacent to the heel portion **32** into which the lower end of the shaft **24** is inserted. The hosel **26** is integrally formed with the club head in this embodiment. In other embodiments, the hosel **26** may be a separate component. In other embodiments, the hosel **26** may be optional.

[0037] FIG. **1** shows the golf club head **22** in a Cartesian coordinate system. The Cartesian coordinate system has X, Y, and Z axes. (These axes are shown in a perspective view to the right of FIG. **1A**.) For the purposes of describing the present invention, the golf club head **22** is placed with its sole **38** on a flat surface S as at address. The origin, O, of the coordinate system will be at a point on the leading edge **28A** of the club face **28** that is aligned with the centerline, CL, of the club face **28**.

[0038] The X axis runs tangent to the point on the leading edge **28A** of the club head **22** at the origin O in a direction between the heel **32** and the toe **34**. The term “X-direction” refers to a direction parallel to the X axis. The positive X direction along the X axis runs from the origin, O, toward the heel **32**. The negative X direction along the X axis runs from the origin, O, toward the toe **34**. The X direction may be referred to herein as the “lateral” direction. The Y axis is perpendicular to the X axis and intersects the X axis. The Y axis runs from the origin O where it intersects the X axis in a direction vertically upward from the origin O. The Y axis can define positions (in the “Y-direction”) that are disposed above the bottom of the sole **38** of the club head **22**. The Y direction refers to a direction parallel to the Y axis, and may be referred to herein as the “vertical” direction. The third axis, the Z axis, passes through the origin O, and is perpendicular to X and Y axes (and goes into the plane of the paper). The Z axis can define positions (in the “Z-direction”) that are either on the club face **28**, or in front of the club face, or to the rear of the club face **28**. The Z direction refers to a direction parallel to the Z axis, and may be referred to as the forward or rearward (or front or rear) direction. The X and Z axes define an X-Z plane that contains surface S.

[0039] The terms “inward” (“inside” or “inboard”) IW and “outward” (“outside” or “outboard”) OW may be used herein to define the relative positions of various elements on the club head **22**. These directions may be shown with arrows in the drawings. For example, as shown in FIG. **3**, if a first element is described as being “laterally inward” of a second element, it is meant that the first element is closer to the center of the club head **22** (that is, the centerline CL) in the X direction than the second element. If a first element is described as being “laterally outward” of a second element, it is meant that the first element is spaced further away from the center of the club head **22** in the X direction than the second element.

[0040] The center of gravity (and other properties) of the club head are defined in the conventional manner which is further described in the book entitled “Golf Club Fitting & Performance” by Ralph Maltby, The GolfWorks, Newark, Ohio, U.S.A., 2011. The club head **22** can be balanced on its face, its sole, or other surfaces of the club head. The club head has a center of gravity CG that is located within the periphery of the club head **22** where lines drawn through all the balance points intersect. The center of gravity CG of the club head **22** can be: above; at; or, below the center of

gravity of a golf ball when the golf club is at address position behind the golf ball. (A center of gravity that is above the center of gravity of a golf ball, however, may be less desirable, and in some cases, undesirable.) The moment of inertia, MOI, of a golf club head can be calculated, or it may be measured using a testing machine at The GolfWorks, Newark, Ohio.

[0041] Certain types of golf clubs are commonly used (at least part of the time) to hit golf balls at rest on the ground (rather than being teed up on a golf tee as with drivers). These include irons, crossover irons, fairway woods, hybrids, and the like. In the case of these types of clubs, it may be desirable for the golf club head to have a vertical center of gravity that is less than or equal to the center of gravity of a golf ball at rest on the ground. The term “vertical center of gravity” refers to the vertical (Y direction) distance that the center of gravity is from the sole **38** of the club head **22**. Thus, the golf club head's vertical center of gravity may be at or below the center of gravity of a golf ball at rest on the ground. Since a golf ball has a diameter of 1.680 inches (42.67 mm), it may be desirable for these types of golf clubs to have a vertical center of gravity that is less than or equal to 0.84 inches.

[0042] The club head **22** comprises a main body **44** and a weighting system. The term “main body”, as used herein, refers to the portion of the club head **22** that does not include the weighting system. The main body **44** has a periphery **46**. The periphery **46** of the main body **44** may comprise portions on the club face **28**, the back surface **30**, the heel portion **32**, the toe portion **34**, the top edge **36**, and the sole **38** of the club head **22**. In some cases, the main body can be at least partially hollow for any suitable purpose, such as to allow for the elimination of weight and/or redistribution of weight (such as by the weighting systems described herein).

[0043] The main body **44** of the club head **22** can comprise one or more materials. The main body **44** of the club head **22** can be made of any suitable material or materials. Suitable materials include, but are not limited to stainless steel, titanium, graphite, carbon fiber, aluminum, polymeric material, plastic, or combinations thereof. The main body **44** of the club head **22** can be made in any suitable manner including, but not limited to forging, casting, molding, or joining one or more forged, cast, molded, or otherwise formed, pieces together in any suitable manner. Suitable manners for joining such pieces together include, but are not limited to using mechanical fasteners, adhesives, brazing, welds, friction fitting, or any other known manners of attachment.

[0044] The golf club head **22** shown in FIG. 3 is of a “blade” type and has a thicker lower portion **48** on its back surface **30**. FIG. 4 shows that in other cases, the club head **22** may be a cavity back perimeter weighted club head. Metal woods, crossover irons, and hybrid clubs also may, but need not, be perimeter weighted. If these types of clubs are perimeter weighted, they may, but need not, have a cavity in their back surface.

[0045] The club head **22** shown in FIGS. 1-3 comprises a weighting system (or “movable weighting system”) **50** that is joined to the main body **44** of the club head **22** in a particular location. The weighting system **50** can be joined to any suitable portion of the main body **44** of the club head including one or more of: the hosel **26**, the back surface **30**, the heel portion **32**, the toe portion **34**, the top edge **36**, the sole **38**, and the crown and/or the skirt portion in the case of metal woods and the like.

[0046] The weighting system **50**, in the embodiment shown in FIGS. 1-3, comprises a track weighting system (or “track system”) comprising a track **52** and at least one movable weight **54**. At least a portion of the track **52** may comprise a channel. The track **52** (in any of the embodiments described herein) can be rectilinear, curvilinear, or comprise some segments that are rectilinear and some segments that are curvilinear. The movable weight(s) **54** may be slidable on the track and in the channel. The weight(s) are designated generally by reference number **54**. The club head **22** in any of the embodiments described herein can have any suitable number of weights **54**. Suitable numbers of weights **54** include, but are not limited to: 1, 2, 3, 4, 5, 6, 7, 8, . . . , etc. If there is more than one weight, they may be designated as **54A**, **54B**, **54C**, etc. It should be understood that only the weight(s) **54** of the weighting system **50** need be movable. One or more portions of the

weighting system (such as a track **52**) may not be movable (that is, the track and other portions may be fixed).

[0047] In FIGS. **1-3**, the weighting system **50** is joined to the back **30** of the club head **22**. The term “joined”, as used herein, encompasses configurations in which an element is directly secured to another element by affixing the element directly to the other element; configurations in which the element is indirectly secured to the other element by affixing the element to intermediate member(s) which in turn are affixed to the other element; and configurations in which one element is integral with another element, i.e., one element is essentially part of the other element. The term “joined” includes both those configurations in which an element is temporarily joined to another element, or in which an element is permanently joined to another element.

[0048] In the embodiment shown in FIG. **3**, the track **52** may be formed as part of the thicker lower portion **48** on the back surface **30** of the club head **22**, or it may comprise one or more pieces of material having a channel therein that are joined to the thicker lower portion **48**. The pieces of material, if present, can be made of any suitable material, including any of the materials described herein as being suitable for the main body of the club head **22**. In cases in which there is no thicker lower portion **48** on the back surface **30** of the club head **22**, the track **52** may be joined to a suitable position on the back surface **30** of the club head **22**. As discussed above, the track **52** can define a path for the weights **54** that is rectilinear, curvilinear, or it can comprise some portions that are rectilinear and some portions that are curvilinear.

[0049] The track **52** may, in some cases, be oriented generally horizontally on the back surface **30** of the club head **22** so that the weight(s) **54** are movable in the X direction. The track **52** may extend between the heel **32** of the club head and the toe **34** of the club head **22**. In some cases, the track **52** may be configured so that it terminates laterally inward of the portions on the periphery **46** of the club head at the heel **32** and/or the toe **34**. In other cases, the track **52** may extend to one or more of the portions on the periphery **46** of the club head at the heel **32** and/or the toe **34**, or beyond the same. In some cases, the track **52** may be configured so that at least a portion of the weight **54**, (and in some cases, all of the weight **54**) extends laterally outward beyond the heel and/or toe of the club head. FIG. **3** shows an example of a track **52** that comprises extensions **52Y** and **52Z** that extend beyond the heel **32** and toe **34**, respectively, of the club head **22**. Such extensions **52Y** and **52Z** can be of a length that allows some or all of the weight **54** to extend laterally outward beyond the heel and/or toe of the club head.

[0050] The weights **54** are comprised of a material (or more than one different material) of higher specific gravity than at least a portion of the main body **44** of the club head **22**. The phrase “higher specific gravity”, as used herein, means higher specific gravity than at least some portion of the main body **44** of the club head **22**. The weights **54** may have a higher specific gravity than the portion(s) of the main body of the club head **22** with the highest specific gravity. In other embodiments, the weights **54** may have a higher specific gravity than at least some other portion of the main body **44** of the club head **22**. Non-limiting examples of materials with higher specific gravity include: lead, brass, and tungsten. Such materials would have a higher specific gravity than stainless steel or titanium, for example, which may form at least a portion of the main body **44** of the club head **22**.

[0051] The weights **54** described herein refer to higher specific gravity material that is supplied by the manufacturer either as part of the club head **22**, or together with, or for the club head **22** as a component for the club head **22** which is intended to be added to the club head **22**. That is, the weights **54** described herein are those that are intended to be offered for use as part of the club head, as manufactured. The weights **54** referred to herein are intended to be distinguished from higher specific gravity material, such as lead tape, which may be obtained and subsequently cut and applied to the club head by a golfer, but is not a part of a pre-fabricated weighting system for a particular club head.

[0052] The weights **54** can be of any suitable configuration and size. It is not necessary that all of

the weights **54** have the same configuration, or be of the same size. If there is more than one weight **54**, any two or more weights **54** may differ in configuration and/or size.

[0053] The weights **54** may have a regular-shaped, or an irregularly shaped configuration. The weights **54** may also comprise structures that have one or more regularly shaped sides and one or more irregularly shaped sides. The weights **54** may be symmetrical, or asymmetrical about one or more axis. The weights **54** can have sides or portions with rectilinear shapes, curvilinear shapes, or they can comprise portions having both types of shapes. The aforementioned shapes can be seen when the weights **54** are viewed from a given direction (including, but not limited to the back surface **30** of the club head **22**). Examples of regular shaped configurations include, but are not limited to: cubes, parallelepipeds, any other known polygon shapes, spheres, hemi-spheres, cylinders, and certain other geometric shapes. In some embodiments, however, it may be desirable for the weights **54** to exclude certain of these configurations (e.g., spherical or cylindrical).

[0054] In the embodiment shown in FIG. **3**, the weights **54** may have a generally cylindrical configuration, or alternatively, a ring-shaped configuration with a central opening that fits around a slider **64** that moves along the track **52**. The sliders **64** may be made of the same material as the weights **54**, or of a different material, such as a lighter, lower coefficient of friction material. Alternatively, the weights **54** can be configured similarly to a combination of the weight and slider, wherein a portion of the weight comprises a stem that replaces the slider and slides within the track **52**.

[0055] The weights **54** can have any suitable dimensions (e.g., length, width, diameter, or thickness). The weights **54** can have any suitable dimensions relative to the adjacent portion (or portions) of the main body **44**. As used herein in reference to the weights **54**, the terms “length”, L, and “width”, W, refer generally to the longer and shorter dimensions of the weights, respectively, as measured along the surface to which they are joined or positioned (e.g., the back surface, or the sole of the club head). If the weights do not have longer and shorter dimensions (e.g., the weights are square or circular), their length and width may be the same. The thickness of the weights **54** is their dimension measured in the direction perpendicular to the surface of the club head **22** to which the weights are joined. Thus, if the weights **54** are joined to the back surface **30** of the club head **22**, the thickness will be measured in a direction from the front of the club head **22** to the back **30** of the club head **22** (that is, in the Z direction). If the weights **54** are joined to the sole **38** of the club head **22**, the thickness of the weights **54** will be measured in a direction perpendicular to the portion of the sole **38** (that is, generally in the Y direction).

[0056] FIG. **4** shows an alternative embodiment of the club head shown in FIGS. **1-3**. The club head **22** shown in FIG. **4** is a cavity back perimeter weighted club head. In such a case, the back surface **30** of the club head may have a central region **56** with a cavity **58** therein, wherein the club head has a first thickness measured between the club face and the back surface of the club head. The cavity **58** may be at least partially surrounded by thicker perimeter weighted portions **60** extending rearward on the back surface **30** of the club head **22** that provide the club head **22** with increased weight around at least part of its perimeter. The perimeter weighted portions **60** may include perimeter weighted portions along the heel **32**, the toe **34**, the top edge **36**, and the sole **38** of the club head. In one version of such an embodiment, the back surface **30** of the club head **22** can be provided with a track system **52**, or some other element, that forms a bridge **62** across the cavity **58**, and the weight(s) **54** can be movable along this bridge **62**.

[0057] FIG. **5** is an end view of an iron club head **22** that can be similar to the club head shown in either FIGS. **1-3** or FIG. **4**. FIG. **5** shows that the weight(s) **54** may extend rearward in the Z direction from the back surface **30** of the club head.

[0058] FIG. **6** shows that in other cases, the weighting system **50** can comprise a plurality of track portions (such as **52A** to **52G**). The track portions may extend in any suitable direction. For example, a first track portion **52A** for the slidable weights may extend toward, or to the heel **32** of the club head and toward, or to the toe **34** of the club head **22** (and optionally beyond the heel

and/or toe). The other track portions can extend in other directions, and may be referred to as second, third, fourth, etc. track portions. The other track portions may (optionally) be connected (or “joined”) to any of the other track portions such as the first track portion **52A** so that a weight can be moved (e.g., by sliding) between any connected track portions. Some of the track portions may extend vertically, or substantially vertically, upward or downward (that is, in the Y direction) from track portion **52A**. Such track portions including track portions **52B**, **52C**, and **52D** may extend toward, to, or beyond the top edge **36** of the club head **22**. Other track portions including track portions **52E**, **52F**, and **52G** may extend toward or to the sole **38** of the club head **22**.

[0059] In addition, as shown in FIG. **6**, some of the track portions may extend toward, to, or beyond the corners of the club head, such as: (1) track portion **52B** that extends toward, to, or beyond the corner where the heel portion **32** merges into the top edge **36**; (2) track portion **52D** that extends toward, to, or beyond the corner where the top edge **36** merges into the toe portion **34**; (3) track portion **52E** that extends toward, to, or beyond the corner where the toe portion **34** merges into the sole **38**; and, (4) track portion **52G** that extends toward, to, or beyond the corner where the heel portion **32** merges into the sole **38**.

[0060] When the embodiments of the weighting system **50** are described herein as comprising a plurality of track portions, any suitable number of track portions greater than or equal to two may be present. The weighting system **50** on a club head also need not have all the track portions shown in a particular drawing figure. In some cases, the weighting system **50** may comprise any two, or more, of the track portions shown in the drawings. In other cases, the track portions can be in other configurations that are not specifically shown in the drawings but are within the scope of the subject matter disclosed herein. For instance, the track portions can be oriented in any suitable orientation that is consistent with the present disclosure. In addition, it should be understood that any of the individual track portions shown and/or described herein can be provided on a club head as the sole track, without providing any of the other track portions that are shown in a particular drawing figure (of an embodiment with a plurality of track portions).

[0061] FIGS. **7-9** show one example of a track weighting system **50** with movable weights provided on a metal wood, such as a driver. The metal wood club head **22** may also comprise a crown **70** and a skirt (or skirt portion) **72** around its sides and back surface. The weighting system **50** can have any of the features and properties described above in conjunction with the irons.

[0062] For example, FIG. **9** shows that the weighting system **50** can comprise a plurality of track portions (such as **52A** to **52G**). The track portions may extend in any suitable direction. For example, a first track portion **52A** for the slidable weights may extend toward, or to the heel **32** of the club head **22** and toward, or to the toe **34** of the club head **22** (and optionally beyond the heel and/or toe). Other track portions may (optionally) be connected (or “joined”) to track portion **52A** and extend in other directions so that a weight can be moved (e.g., by sliding) between any connected track portions. For example, some track portions may extend vertically, or substantially vertically, upward or downward (that is, in the Y direction) from track portion **52A**. Such track portions including track portions **52B**, **52C**, and **52D** may extend toward, to, or beyond the top edge **36** of the club head **22**. Other track portions including track portions **52E**, **52F**, and **52G** may extend toward or to the sole **38** of the club head **22**.

[0063] The first track portion **52A** may extend toward, to, or beyond, the heel **32** of the club head and toward, to, or beyond the toe **34** of the club head **22**. For example, as shown in FIG. **9**, the track portion **52A** may be configured so that at least a portion of the weight **54**, (and in some cases, all of the weight **54**) extends laterally outward beyond the heel **32** and/or toe **34** of the club head. The feature of FIG. **3** where the track **52** comprises extensions **52Y** and **52Z** that extend beyond the heel **32** and toe **34**, respectively, of the club head **22** can also be applied to the club head **22** shown in FIG. **9**. Such extensions **52Y** and **52Z** can be of a length that allows some or all of the weight **54** to extend laterally outward beyond the heel and/or toe of the club head.

[0064] FIG. **10** shows a track weighting system **50** that is joined to sole **38** of the main body **44** of a



metal wood, such as a driver or fairway metal wood. The track weighting system **50** can be provided in one or more recesses in the sole **38** of the club head so that it does not interfere with placing the club on the ground. FIG. **10** shows that the weighting system **50** on the sole **38** of the club head **22** can comprise a plurality of track portions (such as **52A** to **52H** similar to the embodiments shown in FIGS. **6** and **9**). The track portions may (optionally) be connected (or “joined”) so that a weight **54** can be moved (e.g., by sliding) between any connected track portions. [0065] The track portions on the sole **38** may be oriented in any suitable direction. The track portions can be oriented in the X direction, the Z direction, or any direction in the X-Z plane. The different track portions can be parallel to each other, or they can form an angle or other suitable relationship with one another. In the embodiment shown in FIG. **10**, the track portions can form a grid on the sole **38** of the club head to allow a high degree of flexibility in locating the weight(s) **54**.

[0066] As shown in FIG. **10**, some track portions, such as **52A**, **52B**, and **52C** may extend in the X direction and be generally parallel. The track portions **52A**, **52B**, and **52C** may extend toward, to, or beyond, the heel **32** of the club head and toward, to, or beyond the toe **34** of the club head **22**. For example, as shown in FIG. **10**, the track portion **52B** may be configured so that at least a portion of the weight **54**, (and in some cases, all of the weight **54**) extends laterally outward beyond the heel and/or toe of the club head. The feature of FIG. **3** where the track **52** comprises extensions **52Y** and **52Z** that extend beyond the heel **32** and toe **34**, respectively, of the club head **22** can also be applied to the club head **22** shown in FIG. **10**. Such extensions **52Y** and **52Z** can be of a length that allows some or all of the weight(s) **54** to extend laterally outward beyond the heel and/or toe of the club head.

[0067] FIG. **10** shows that track portion **52E** is oriented in the Z direction and is disposed along the centerline of the club head **22**. Track portions **52D**, **52F**, **52G**, and **52H** may be perpendicular to track portion **52E**. Alternatively, as shown in FIG. **10**, one or more of track portions **52D**, **52F**, **52G**, and **52H** may be generally oriented in the Z direction, but form an angle with track portion **52E**.

[0068] FIGS. **11** and **12** show examples of an alternative weighting system that comprises at least one weight element (or weight) **80** that may be, at least initially, at least partially located in a recess **82** in a portion of the periphery **46** of the main body **44**. The weight(s) **80** may, in certain embodiments, be sized and configured to fit into a mating recess in one or more particular regions of the main body **44** of the club head **22**. The club head **22** can have any suitable number of weight elements **80** located in recesses **82**. The recesses **82** and weight elements **80** can be in any portion of the club head **22**. G

[0069] The weight element(s) **80** may be movable from a retracted position inside the recess **82** to one or more extended positions. That is, in the retracted position, the weights are located at least partially in the recess. In the extended position, the weight element(s) **80** further protrude from the recess **82**. In some cases, this weight element **80** may be movable outward from the heel **32** and/or toe **34** in the X direction as shown by the upper set of double-headed arrows in FIG. **11**.

Alternatively, one or more of these weight elements **80** may be inserted into recesses that are oriented at an angle to the X direction, such as a slight downwardly oriented angle, as shown by the lower set of double-headed arrows in FIG. **11**. The weight elements **80** may be biased to move in a particular direction, such as by one or more springs **84**. The spring **84** may have a first portion (or first end) thereof adjacent to the surface of the main body **44** that defines the recess **82**, and a second portion (or second end) thereof which is adjacent to the inner surface of the weight element **80**. The first portion of the spring **84** may be joined to the surface of the main body **44** that defines the recess **82**, and/or the second portion of the spring **84** may be joined to the inner surface of the weight element **80**.

[0070] FIG. **12** shows that the weight element **80** and the recess **82** can be provided with one or more pre-established positions for the weight elements **80** with respect to the periphery **46** of the club head. As shown in FIG. **12**, these locations can be created by providing the one or more of the

surface defining the recess **82** and a portion of the surface of the weight element **80** with engageable features, such as **86** and **88**. These engageable features **86** and **88** on at least one of the weight elements **80** and the surface that defines the recess **82** may comprise a flexible material that is joined thereto to allow the weight element **80** to move between positions.

[0071] The weight elements **80** have an inner surface **76** and an outer surface **78**. The outer surface **78** of the weight element shown in FIGS. **11** and **12** can have any suitable configuration. In some cases, at least some of the weight elements **80** can have an exterior configuration that forms a part of, or is a continuation of, the curvature of the periphery **46** of the main body **44** of the club head **22**. In other embodiments, at least some of the weight elements **80** may create a discontinuity or change in the curvature of the periphery **46** of the main body **44** of the club head **22**. Non-limiting examples of discontinuities in the curvature of the periphery **46** of the main body **44** are breaks in the curvature, or changes in the direction of the curvature (e.g., a change from a convex curved surface to a concave curved surface or a planar surface). The description of the configuration of the weight elements **80** in this paragraph can also apply to the weights **54** in any of the previous embodiments.

[0072] FIGS. **13** and **14** show examples of golf club heads **22** with an alternative weighting system that comprises at least one weight **90** that is rotatable from a first angle to at least a second angle. In some cases, the weight **90** may be rotatable through and/or to a plurality of different angles. Such a weight **90** (or “rotatable weight element” or “rotatable weight”) **90** may provide rotation by being pivotable (and may, in such cases, be referred to as a “pivoting” or “pivotable” weight element).

[0073] FIG. **13** shows the rotatable weight element **90** on an iron club head **22**. The rotatable weight element **90** can be of any suitable size and shape. The rotatable weight elements **90** described herein are distinguishable from threaded cylindrical weight elements that are screwed into a club head and unscrewed to remove the same and, thus, need not be cylindrical or threaded. At least a portion of the rotatable weight element **90** can be made of a higher specific gravity material (as described above). There can be any suitable number of rotatable weight elements **90** joined to any portion of the main body of the club head **22**.

[0074] In this case, there are two rotatable elements—one joined adjacent to the heel **32** of the club head, and one joined adjacent to the toe **34** of the club head. Several non-limiting examples of positions for the rotatable weight elements **90** are shown in dashed lines. These positions include at least one in which at least a portion of the weighting element **90** extends outward beyond the periphery **46** of the club head **22** in the X direction from the heel **32** and/or toe **34**. In the embodiment shown, the rotatable elements **90** comprise a rectangular weight that has a proximal end **92** and a distal end **94**. The rotatable elements **90** are rotatably joined at a location on the back surface **30** of the club head **22**. The back surface **30** of the club head **22** may optionally have a recessed area **96** to make room for rotation of the rotatable weight elements **90**. Rotation can be provided by joining the rotatable weight element **90** adjacent its proximal end **92** with a pin **98**. The pin **98** can be oriented in any suitable direction. In the embodiment shown, the pin **98** can be oriented generally, or substantially, in the Y direction.

[0075] FIG. **14** shows a metal wood club head **22**. The metal wood club head **22** can be provided with rotatable weights **90** having the same characteristics described above for the iron club head shown in FIG. **13**. In the embodiment shown in FIG. **14**, the rotatable element weighting system is provided on the sole **38** of the club head **22**. In this embodiment, the sole **38** of the club head **22** may have one or more recessed areas **96**. Several non-limiting examples of positions for the rotatable weight elements **90** are shown in dashed lines. These positions include at least one in which at least a portion of the weighting element **90** extends outward beyond the periphery **46** of the club head **22** in the X direction from the heel **32** and/or toe **34**. As shown in FIG. **14**, the weight elements **90** can rotate forward (toward the club face **28**) as well. The surface of the club head **22** to which the rotatable weight elements **90** are attached can also be provided with detents between the positions to keep the rotatable elements **90** from moving once their positions are set. Providing a

weighting system that comprises at least one weight element that is rotatable between different angles allows the location of the weight (and the center of gravity of the club head) to be simultaneously adjusted in the X and Z directions.

[0076] The weighting systems described herein may have several additional features. The weights can be removable and replaceable with lighter or heavier weights in any of the embodiments described herein. The leading edge of the weights can be aerodynamically shaped, particularly when all or a portion of the weights may extend outward from the periphery of the main body **44**. For instance, the leading edge of the weights **54** may be rounded and provided with a convex configuration as shown in FIG. **10**, for example. The “leading edge” is the portion of the weights that is furthest forward in the Z direction. The leading edge of any extensions of the track can also be similarly aerodynamically shaped.

[0077] In some cases, the weighting systems **50** described herein may not be visible to a golfer when the golf club **20** is held in the usual manner with the club head **22** placed on the ground in the address position. In other cases, one or more portions of the weighting systems **50** may be visible to a golfer when the golf club **20** is held with the club head **22** in the address position.

[0078] In addition, any of the weights described herein can be adjustable before play so that the golfer can pre-select a desired shape for the golf shots that they will hit with such clubs and/or to compensate for swing faults that they may have on any given day.

[0079] Numerous other embodiments of the golf clubs described herein are possible. For example, in other embodiments, the club head can be provided with more, or fewer, higher specific gravity weights, or weights having different configurations than those shown in each of the drawing figures. In other embodiments, any of the features of the golf clubs described herein can be combined in any suitable manner to produce still other embodiments. The features of the golf clubs described herein may also be combined with the features of the golf clubs described in U.S. Pat. Nos. 5,419,560; 5,540,437; 6,702,693 B2; and 7,815,524 B2, and the references listed on the face and any subsequent pages thereof, as well as in U.S. Patent Application Publication No. US 2019/0009143 A1, Myers.

[0080] The golf clubs described herein may provide a number of advantages. It should be understood, however, that such advantages are not required to be provided unless specifically set forth in the appended claims. Golfer's swings vary from day-to-day, and shot trajectories (draw or fade; high or low) can vary from club to club. The weighting systems described herein provide a golfer with the ability to adjust any of these things before a round. The weighting system can provide greater adjustability in the moment of inertia than in current club heads having weights that are located in tracks on the underside or the back of the club head that are confined to movement within the periphery of the club head. The weighting system can, in some cases, provide the ability to adjust the center of gravity of the club head upward or downward. This may provide a golfer with the ability to hit a ball lower (for example, when it is windy), or higher (for example, when it is not windy). The weighting system may be adjusted faster than adjustable weighting systems that require removing and screwing in weights.

[0081] The disclosure of all patents, patent applications (and any patents which issue thereon, as well as any corresponding published foreign patent applications), and publications mentioned throughout this description are hereby incorporated by reference herein. It is expressly not admitted, however, that any of the documents incorporated by reference herein teach or disclose the present invention.

[0082] It should be understood that every maximum numerical limitation given throughout this specification includes every lower numerical limitation, as if such lower numerical limitations were expressly written herein. Every minimum numerical limitation given throughout this specification includes every higher numerical limitation, as if such higher numerical limitations were expressly written herein. Every numerical range given throughout this specification includes every narrower numerical range that falls within such broader numerical range, as if such narrower numerical

ranges were all expressly written herein.

[0083] While particular embodiments of the subject invention have been described, it will be obvious to those skilled in the art that various changes and modifications of the subject invention can be made without departing from the spirit and scope of the invention. In addition, while the present invention has been described in connection with certain specific embodiments thereof, it is to be understood that this is by way of illustration and not by way of limitation.

## Claims

**1-8.** (canceled)

**9.** A golf club head comprising a club face, a back surface on the opposite side of said club head from said club face, a heel portion, a toe portion, a top, and a sole extending generally between the heel portion and the toe portion, wherein said golf club head comprises: a main body having a periphery, wherein said main body is configured to receive a shaft adjacent said heel portion; and a weighting system joined to said main body, said weighting system comprising a movable weight, wherein said weighting system is configured to allow the weight to move between: a first position that is located inward of the periphery of the main body; and a second position wherein at least a portion of said weight is located outward of the periphery of said main body, wherein the weighting system comprises a track and said movable weight is movably joined to said track and is movable between different positions along the track, wherein said track extends beyond at least one of the heel portion and the toe portion of said club head.

**10.** A golf club head of claim 9 wherein said golf club head is an iron club head.

**11.** A golf club head of claim 9 wherein said golf club head is a wood or metal wood club head.

**12.** A golf club head of claim 9 wherein said golf club head is a putter club head.

**13-14.** (canceled)

**15.** The golf club head of claim 9 wherein the track is joined to the back surface of said club head.

**16.** The golf club head of claim 9 wherein the track is joined to the sole of said club head.

**17.** A golf club comprising the golf club head of claim 9 further comprising a shaft having a first end and a second end, wherein said first end of said shaft is joined to said golf club head, and the second end of said shaft has a grip thereon.

**18.** A golf club comprising the golf club head of claim 10 further comprising a shaft having a first end and a second end, wherein said first end of said shaft is joined to said golf club head, and the second end of said shaft has a grip thereon.

**19.** A golf club comprising the golf club head of claim 11 further comprising a shaft having a first end and a second end, wherein said first end of said shaft is joined to said golf club head, and the second end of said shaft has a grip thereon.

**20.** A golf club comprising the golf club head of claim 12 further comprising a shaft having a first end and a second end, wherein said first end of said shaft is joined to said golf club head, and the second end of said shaft has a grip thereon.

**21.** A golf club comprising the golf club head of claim 15 further comprising a shaft having a first end and a second end, wherein said first end of said shaft is joined to said golf club head, and the second end of said shaft has a grip thereon.

**22.** A golf club comprising the golf club head of claim 16 further comprising a shaft having a first end and a second end, wherein said first end of said shaft is joined to said golf club head, and the second end of said shaft has a grip thereon.

**23.** The golf club of claim 21 wherein said golf club head is an iron club head.

**24.** The golf club of claim 21 wherein said golf club head is a wood or metal wood club head.

**25.** The golf club of claim 21 wherein said golf club head is a putter club head.

**26.** The golf club of claim 22 wherein said golf club head is an iron club head.

27. The golf club of claim 22 wherein said golf club head is a wood or metal wood club head.
28. The golf club of claim 22 wherein said golf club head is a putter club head.
-