

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250253714

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Peralta; Alberto et al.

WIRELESS POWER TRANSMITTERS UTILIZING REPEATER TRANSMITTER ANTENNAS

Abstract

A modular wireless power transfer system includes a first wireless transmission system and one or more secondary wireless transmission systems. The first wireless transmission system is configured to receive input power from an input power source, generate AC wireless signals, and couple with one or more other antennas. Each of the one or more secondary wireless transmission systems includes a secondary transmission antenna, the secondary transmission antenna configured to couple with one or more of another secondary transmission antenna, the first transmission antenna, one or more receiver antennas, or combinations thereof. The one or more secondary wireless transmission systems are configured to receive the AC wireless signals from one or more of the first wireless transmission system, another secondary wireless transmission system, or combinations thereof and repeat the AC wireless signals to one or more of the secondary transmission antennas, the one or more receiver antennas, or combinations thereof.

Inventors: Peralta; Alberto (Chicago, IL), Alam; Md. Nazmul (Glendale Heights, IL)

Applicant: NuCurrent, Inc. (Chicago, IL)

Family ID: 79688717

Appl. No.: 19/043138

Filed: January 31, 2025

Related U.S. Application Data

parent US continuation 17878569 20220801 parent-grant-document US 12218523 child US 19043138

parent US continuation 16938613 20200724 parent-grant-document US 11404919 child US 17878569

Publication Classification

Int. Cl.: H02J50/50 (20160101); H02J50/12 (20160101); H02J50/40 (20160101)

U.S. Cl.:

CPC H02J50/502 (20200101); H02J50/12 (20160201); H02J50/402 (20200101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of, and claims priority to, U.S. Non-Provisional application Ser. No. 17/878,569, filed on Aug. 1, 2022, and entitled “Modular Wireless Power Transmitters for Powering Multiple Devices,” which is a continuation of U.S. Non-Provisional application Ser. No. 16/938,613, filed on Jul. 24, 2020, and entitled “Modular Wireless Power Transmitters for Powering Multiple Devices,” the contents of each of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

[0002] The present disclosure generally relates to systems and methods for wireless transfer of electrical power and/or electrical data signals, and, more particularly, to modular wireless power transmitters capable of repeating a power signal to other associated wireless power transmitters and associated receivers.

BACKGROUND

[0003] Wireless connection systems are used in a variety of applications for the wireless transfer of electrical energy, electrical power, electromagnetic energy, electrical data signals, among other known wirelessly transmittable signals. Such systems often use inductive and/or resonant inductive wireless power transfer, which occurs when magnetic fields created by a transmitting element induce an electric field and, hence, an electric current, in a receiving element. These transmitting and receiving elements will often take the form of coiled wires and/or antennas.

[0004] Transmission of one or more of electrical energy, electrical power, electromagnetic energy and/or electronic data signals from one of such coiled antennas to another, generally, operates at an operating frequency and/or an operating frequency range. The operating frequency may be selected for a variety of reasons, such as, but not limited to, power transfer characteristics, power level characteristics, self-resonant frequency restraints, design requirements, adherence to standards bodies' required characteristics (e.g. electromagnetic interference (EMI) requirements, specific absorption rate (SAR) requirements, among other things), bill of materials (BOM), and/or form factor constraints, among other things. It is to be noted that, “self-resonating frequency,” as known to those having skill in the art, generally refers to the resonant frequency of a passive component (e.g., an inductor) due to the parasitic characteristics of the component.

[0005] When such systems operate to wirelessly transfer power from a transmission system to a receiver system, via the coils and/or antennas, it is often desired to simultaneously or intermittently communicate electronic data from one system to the other. To that end, a variety of communications systems, methods, and/or apparatus have been utilized for combined wireless power and wireless data transfer. In some example systems, wireless power transfer related communications (e.g., validation procedures, electronic characteristics data communications, voltage data, current data, device type data, among other contemplated data communications) are performed using other circuitry, such as an optional Near Field Communications (NFC) antenna utilized to compliment the wireless power system and/or additional Bluetooth chipsets for data communications, among other known communications circuits and/or antennas.

[0006] However, using additional antennas and/or circuitry can give rise to several disadvantages. For instance, using additional antennas and/or circuitry can be inefficient and/or can increase the BOM of a wireless power system, which raises the cost for putting wireless power into an electronic device. Further, in some such systems, out of band communications provided by such additional antennas may result in interference, such as cross-talk between the antennas; such cross talk may present challenges in. Further yet, inclusion of such additional antennas and/or circuitry can result in worsened EMI, as introduction of the additional system will cause greater harmonic distortion, in comparison to a system wherein both a wireless power signal and a data signal are within the same channel. Still further, inclusion of additional antennas and/or circuitry hardware, for communications or increased charging or powering area, may increase the area within a device, for which the wireless power systems and/or components thereof reside, complicating a build of an end product.

SUMMARY

[0007] In some example applications for wireless power transfer, it is desired to power and/or charge multiple electronic devices simultaneously. Currently, systems and/or products exist, employing multiple transmitter coils and associated driver circuits, wherein each system couples with an individual receiving device. However, such systems are expensive, as the BOM is increased greatly for every additional system. Further, systems with multiple antennas and/or driving circuitry may be prone to interference, between one another, leading to potential inefficiencies and/or complications in communications capability or causing degradation to communications capabilities. Additionally, if a user were to desire to increase the charging and/or powering area of the transmitter, the user would be limited to the area provided by the original device or would be required to provide an additional wireless transmitter, having a separate connector to a power source.

[0008] Additionally, using the systems, methods, and apparatus disclosed herein may allow for greater variety in form factor selection and/or configuration. Thus, a designer and/or user may configure a powering area modularly, in manners that are nearly infinitely customizable, on either the design or consumer-user level. Such variety of form factor selection/configuration may include multiple antenna designs that provide a transmitting device with multiple “sub-areas” that either provide the benefit of a wider power transmission area or allow for multiple devices to be powered by a single transmission system.

[0009] To that end, modular wireless power transmitters, which are capable of repeating a wireless power signal to an associated, additional wireless power transmitter, are desired. Such systems may include communications systems and/or circuitry that provide stable and efficient in band communications, eliminating the aforementioned need for additional wireless data transmission antennas and/or circuitry. The systems and methods disclosed herein provide for a nearly unlimited combination of wireless power transmission areas, made possible by the inclusion of a plurality of modular wireless power transmitters in connection via use of the transmission antenna(s) as repeaters of the wireless power signal.

[0010] In addition to providing a greater charging area, utilizing multiple modular wireless power transmitters, as disclosed herein, may provide for further enhancement and/or fidelity of one or both of wireless power signals and/or wireless data signals, upon such signals' ultimate transmission to a receiver. While the transmitter connected wireless power transmitters may omit active elements in their signal path when coupled with, at least, the input source connected wireless power transmitter, the electronic signals will still travel through any tuning system(s) and/or inactive filters of the unsourced wireless power transmitters. Such exposure of the signal to additional filtering and/or tuning will further process the signal, in addition to the filtering/tuning performed by the input source connected wireless power transmitter. Thus, the additional filtering can increase fidelity of the electronic signals.

[0011] Additionally, the inclusion of multiple, repeater-connected wireless transmission systems, in

separate modules, may allow for supply chain, retail stocking, and/or manufacturing benefits. As large and wide charging areas may be desired (to, for example, cover, in whole or in part, a desktop or tabletop), packaging and/or storing such a large sized wireless power transmission system may be burdensome to the supply chain, retail stocking, and/or manufacturing of such transmission systems. Therefore, by utilizing the modular wireless transmission systems disclosed herein, such burdens may be resolved, as the desired large wireless power transmission areas can be subdivided into the disclosed modular transmission systems, to be packaged, singularly or as a plurality, with far smaller surface areas than a packaged large area, non-modular transmitter. Additionally or alternatively, the modular wireless power transmission systems disclosed herein may be utilized, as sold separately from one another, to upgrade or expand a wireless transmission area of a surface, as the modularity allows for a user to acquire additional transmitters to expand the wirelessly powered space.

[0012] The communications systems of the wireless power transmitters disclosed herein is a relatively inexpensive and/or simplified circuit utilized to, at least partially, decode or demodulate ASK signals down to alerts for rising and falling edges of a data signal. So long as the transmission controller **28** is programmed to understand the coding schema of the ASK modulation, the transmission controller will expend far less computational resources than it would if it had to decode the leading and falling edges directly from an input current or voltage sense signal from the sensing system. To that end, as the computational resources required by the transmission controller to decode the wireless data signals are significantly decreased due to the inclusion of the demodulation circuit. Thus, it follows, that the demodulation circuit may significantly reduce BOM of the wireless transmission system, by allowing usage of cheaper, less computationally capable processor(s) for or with the transmission controller **28**.

[0013] In some embodiments of the disclosure, the wireless transmission antenna is configured to generate a greater powering or charging area, with respect to legacy transmission antennas. Further, by utilizing the transmission antennas and the intelligent placement of the crossovers, the antenna may effectively function as multiple antennas capable of transmission to multiple receivers. Further, due to the spacing of the inner and outer turns, a more uniform charge envelope may be achieved, leading to greater spatial freedom for the receiver when placed relative to the transmission antenna. Thus, having a higher density of turns on the outer edges of the antenna may prevent dead spots or inconsistent coupling, when a receiver is positioned proximate to an outer edge of the wireless transmission system **120**.

[0014] In accordance with one aspect of the disclosure, a modular wireless power transfer system is disclosed. The system includes a first wireless transmission system and one or more secondary wireless transmission systems. The first wireless transmission system is configured to receive input power from an input power source and generate AC wireless signals based, at least in part, on the input power, the AC wireless signals including wireless power signals and wireless data signals, the first wireless transmission system including a first transmission antenna configured to couple with one or more other antennas. Each of the one or more secondary wireless transmission systems includes a secondary transmission antenna, the secondary transmission antenna configured to couple with one or more of another secondary transmission antenna, the first transmission antenna, one or more receiver antennas, or combinations thereof. The one or more secondary wireless transmission systems are configured to receive the AC wireless signals from one or more of the first wireless transmission system, another secondary wireless transmission system, or combinations thereof and repeat the AC wireless signals to one or more of the secondary transmission antennas, the one or more receiver antennas, or combinations thereof.

[0015] In a refinement, the system further includes a wireless receiver system configured to receive the AC wireless signals to provide electrical power to a load operatively associated with the wireless receiver system, the wireless receiver system including one of the one or more receiver antennas, the one or more receiver antennas each configured to couple with one or more of the first

wireless transmission system, the one or more secondary wireless transmission systems, or combinations thereof.

[0016] In a further refinement, one or more of the first wireless transmission system, the one or more secondary wireless transmission systems, or combinations thereof are configured to directly power an electronic device operatively associated with the wireless receiver system.

[0017] In another further refinement, one or more of the first wireless transmission system, the one or more secondary wireless transmission systems, or combinations thereof are configured to provide electrical power to a load of an electronic device operatively associated with the wireless receiver system, wherein the load is an electrical energy storage device.

[0018] In a refinement, the first wireless transmission system further includes a first transmission controller configured to provide first driving signals for driving the first transmission antenna, a first power conditioning system configured to receive the driving signals and generate the AC wireless signals based, at least in part, on the first driving signal. In such a refinement, a first power conditioning system configured to receive the driving signals and generate the AC wireless signals based, at least in part, on the first driving signal and a first power conditioning system configured to receive the driving signals and generate the AC wireless signals based, at least in part, on the first driving signal.

[0019] In a further refinement, when the at least one of the one or more secondary wireless transmission systems is configured to repeat the AC wireless signals, the second transmission controller and the second power conditioning system are bypassed in a signal path for the AC wireless signals.

[0020] In a refinement, the first wireless transmission system further includes a first transmission controller configured to provide first driving signals for driving the first transmission antenna, a first power conditioning system configured to receive the driving signals and generate the AC wireless signals based, at least in part, on the first driving signal, and a first transmission tuning system operatively associated with the first transmission antenna. In such a refinement, at least one of the one or more secondary wireless transmission systems further includes a second transmission tuning system operatively associated with the secondary transmission antenna.

[0021] In a further refinement, the first transmission tuning system is configured to filter the AC wireless signals to generate filtered AC wireless signals and the second transmission tuning system is configured to further filter the filtered AC wireless signals to generate twice-filtered AC wireless signals.

[0022] In a refinement, the system further includes a demodulation circuit configured to receive communications signals from a wireless receiver system and decode the communications signals by determining a rate of change in electrical characteristics of the communications signals.

[0023] In a refinement, the first wireless transmission system further includes a repeater tuning system configured to tune a portion of the first antenna to function as a repeater for the AC wireless signals.

[0024] In a refinement, at least one of the one or more secondary wireless transmission systems further includes a repeater tuning system configured to tune the secondary transmission antenna to function as a repeater for the AC wireless signals.

[0025] In a further refinement, the secondary transmission antenna includes a first antenna portion and a second antenna portion and the repeater tuning system is configured to tune the secondary transmission antenna such that the first antenna portion is configured to receive the AC wireless signals from the transmission antenna and one or more of the first antenna portion, the second antenna portion, or combinations thereof are configured to repeat the AC wireless signals.

[0026] In a refinement, each of the first transmission antenna and the second transmission antenna are configured to operate based on an operating frequency of about 6.78 MHz.

[0027] In accordance with another aspect of the disclosure, a modular wireless transmission system for transmitting AC wireless signals is disclosed. The AC wireless signals including wireless power

signals and wireless data signals. The system includes a transmission controller, a power conditioning system, and a first transmission antenna. The transmission controller is configured to provide first driving signals for driving the first transmission antenna. The power conditioning system is configured to receive the driving signals, receive input power from an input power source, and generate the AC wireless signals based, at least in part, on the first driving signal and the input power source. The first transmission antenna is configured for coupling with one or more other antennas and is configured to transmit the AC wireless signals to the one or more antennas, receive the AC wireless signals from one or more other antennas, and repeat the AC wireless signals to the one or more other antennas.

[0028] In a refinement, the transmission antenna includes a first antenna portion and a second antenna portion, the second antenna portion is configured to receive the AC wireless signals from one or more other antennas.

[0029] In a further refinement, one or more of the first antenna portion, the second antenna portion, or combinations thereof are configured to repeat the AC wireless signals to the one or more other antennas.

[0030] In another further refinement, the system further includes a repeater tuning system configured to tune one or more portion of the transmission antenna to repeat the AC wireless signals.

[0031] In another further refinement, when the wireless transmission system is configured to repeat the AC wireless signals, the transmission controller and the power conditioning system are bypassed in a signal path for the AC wireless signals.

[0032] In a refinement, the first transmission antenna is configured to operate based on an operating frequency of about 6.78 MHz.

[0033] In accordance with one aspect of the disclosure, a modular wireless power transfer system is disclosed. The system is configured to operate based on an operating frequency of about 6.78 MHz. The system includes a first wireless transmission system, one or more secondary wireless transmission systems, and a wireless receiver system. The first wireless transmission system is configured to receive input power from an input power source and generate AC wireless signals based, at least in part, on the input power, the AC wireless signals including wireless power signals and wireless data signals, the first wireless transmission system including a first transmission antenna configured to couple with one or more other antennas and operate based on the operating frequency. Each of the one or more secondary wireless transmission systems includes a secondary transmission antenna, the secondary transmission antenna configured to couple with one or more of another secondary transmission antenna, the first transmission antenna, one or more receiver antennas, or combinations thereof. The one or more secondary wireless transmission systems are configured to operate based on the operating frequency, receive the AC wireless signals from one or more of the first wireless transmission system, another secondary wireless transmission system, or combinations thereof, and repeat the AC wireless signals to one or more of the secondary transmission antennas, the one or more receiver antennas, or combinations thereof. The wireless receiver system is configured to receive the AC wireless signals to provide electrical power to a load operatively associated with the wireless receiver system, the wireless receiver system including one of the one or more receiver antennas, the one or more receiver antennas each configured to couple with one or more of the first wireless transmission system, the one or more secondary wireless transmission systems, or combinations thereof.

[0034] These and other aspects and features of the present disclosure will be better understood when read in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] FIG. 1 is a block diagram of an embodiment of a system for wirelessly transferring one or more of electrical energy, electrical power signals, electrical power, electromagnetic energy, electronic data, and combinations thereof, in accordance with the present disclosure.

[0036] FIG. 2A is a block diagram illustrating components of a plurality of modular wireless transmission systems of the system of FIG. 1 and a plurality of wireless receiver systems of the system of FIG. 1, in accordance with FIG. 1 and the present disclosure.

[0037] FIG. 2B is another block diagram illustrating components of a plurality of modular wireless transmission systems of the system of FIG. 1 and a plurality of wireless receiver systems of the system of FIG. 1, in accordance with FIG. 1 and the present disclosure.

[0038] FIG. 3 is a block diagram illustrating components of a transmission control system of the wireless transmission system of FIGS. 2, in accordance with FIG. 1, FIG. 2, and the present disclosure.

[0039] FIG. 4 is a block diagram illustrating components of a sensing system of the transmission control system of FIG. 3, in accordance with FIGS. 1-3 and the present disclosure.

[0040] FIG. 5 is a block diagram for an example low pass filter of the sensing system of FIG. 4, in accordance with FIGS. 1-4 and the present disclosure.

[0041] FIG. 6 is a block diagram illustrating components of a demodulation circuit for the wireless transmission system of FIGS. 2, in accordance with FIGS. 1-4 and the present disclosure.

[0042] FIG. 7 is an electrical schematic diagram for the demodulation circuit of FIG. 6, in accordance with FIGS. 1-6 and the present disclosure.

[0043] FIG. 8 is a timing diagram for voltages of an electrical signal, as it travels through the demodulation circuit, in accordance with FIGS. 1-7 and the present disclosure.

[0044] FIG. 9 is a block diagram illustrating components of a power conditioning system of the wireless transmission system of FIG. 2, in accordance with FIG. 1, FIG. 2, and the present disclosure.

[0045] FIG. 10 is a block diagram illustrating components of a receiver control system and a receiver power conditioning system of the wireless receiver system of FIGS. 2, in accordance with FIG. 1, FIG. 2, and the present disclosure.

[0046] FIG. 11 is a block diagram of another wireless power transfer system, including modular wireless transmission system(s) and at least one wireless receiver system, including like or similar elements to those of the system(s) of FIGS. 1-10, in accordance with FIGS. 1-10 and the present disclosure.

[0047] FIG. 12A is a simplified electrical schematic diagram of a wireless power transmitter of FIG. 11, in accordance with FIGS. 1-11 and the present disclosure.

[0048] FIG. 12B is another simplified electrical schematic diagram of the wireless power transmitter of FIG. 12A, in accordance with FIGS. 1-12A and the present disclosure.

[0049] FIG. 13A is a top perspective view of a modular wireless power transmitter of FIGS. 11-12, residing in a housing, in accordance with FIGS. 1-12 and the present disclosure.

[0050] FIG. 13B is another top perspective view of the modular wireless power transmitter of FIG. 13A, but with a top of the housing removed from view, in accordance with FIGS. 1-13A and the present disclosure.

[0051] FIG. 14A is an illustration of a configuration of the wireless power transfer system of FIGS. 1-13 and associated host device(s), in accordance with FIGS. 1-13B and the present disclosure.

[0052] FIG. 14B is a block diagram of the wireless power transfer system of FIG. 11, but illustrating components utilized in the configuration of FIG. 14A, in accordance with FIGS. 1-13B, 14A, and the present disclosure.

[0053] FIG. 15A is an illustration of a configuration of the wireless power transfer system of FIGS. 1-13 and associated host device(s), in accordance with FIGS. 1-13B and the present disclosure.

[0054] FIG. **15B** is a block diagram of the wireless power transfer system of FIG. **11**, but illustrating components utilized in the configuration of FIG. **15A**, in accordance with FIGS. **1-13B**, **15A**, and the present disclosure.

[0055] FIG. **16A** is an illustration of a configuration of the wireless power transfer system of FIGS. **1-13** and associated host device(s), in accordance with FIGS. **1-13B** and the present disclosure.

[0056] FIG. **16B** is a block diagram of the wireless power transfer system of FIG. **11**, but illustrating components utilized in the configuration of FIG. **16A**, in accordance with FIGS. **1-13B**, **16A**, and the present disclosure.

[0057] FIG. **17** is a top view of a transmission antenna including two portions which may operate as virtual independent antennas, for use with the system(s) of FIGS. **1-16B**, in accordance with FIGS. **1-16B** and the present disclosure

[0058] FIG. **18** is a top view of a non-limiting, exemplary antenna, for use as one or both of a transmission antenna and a receiver antenna of the system of FIGS. **1-8**, **10-12** and/or any other systems, methods, or apparatus disclosed herein, in accordance with the present disclosure.

[0059] FIG. **19** is an exemplary method for designing a system for wireless transmission of one or more of electrical energy, electrical power signals, electrical power, electrical electromagnetic energy, electronic data, and combinations thereof, in accordance with FIGS. **1-16**, and the present disclosure.

[0060] FIG. **20** is a flow chart for an exemplary method for designing a wireless transmission system for the system of FIG. **19**, in accordance with FIGS. **1-19** and the present disclosure.

[0061] FIG. **21** is a flow chart for an exemplary method for designing a wireless receiver system for the system of FIG. **20**, in accordance with FIGS. **1-19** and the present disclosure.

[0062] FIG. **22** is a flow chart for an exemplary method for manufacturing a system for wireless transmission of one or more of electrical energy, electrical power signals, electrical power, electrical electromagnetic energy, electronic data, and combinations thereof, in accordance with FIGS. **1-16**, **21** and the present disclosure.

[0063] FIG. **23** is a flow chart for an exemplary method for manufacturing a wireless transmission system for the system of FIG. **22**, in accordance with FIGS. **1-16**, **22** and the present disclosure.

[0064] FIG. **24** is a flow chart for an exemplary method for designing a wireless receiver system for the system of FIG. **22**, in accordance with FIGS. **1-16**, **22**, and the present disclosure.

[0065] While the following detailed description will be given with respect to certain illustrative embodiments, it should be understood that the drawings are not necessarily to scale and the disclosed embodiments are sometimes illustrated diagrammatically and in partial views. In addition, in certain instances, details which are not necessary for an understanding of the disclosed subject matter or which render other details too difficult to perceive may have been omitted. It should therefore be understood that this disclosure is not limited to the particular embodiments disclosed and illustrated herein, but rather to a fair reading of the entire disclosure and claims, as well as any equivalents thereto. Additional, different, or fewer components and methods may be included in the systems and methods.

DETAILED DESCRIPTION

[0066] In the following description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant teachings. However, it should be apparent to those skilled in the art that the present teachings may be practiced without such details. In other instances, well known methods, procedures, components, and/or circuitry have been described at a relatively high-level, without detail, in order to avoid unnecessarily obscuring aspects of the present teachings.

[0067] Referring now to the drawings and with specific reference to FIG. **1**, a wireless power transfer system **10** is illustrated. The wireless power transfer system **10** provides for the wireless transmission of electrical signals, such as, but not limited to, electrical energy, electrical power, electrical power signals, electromagnetic energy, and electronically transmittable data (“electronic

data”). As used herein, the term “electrical power signal” refers to an electrical signal transmitted specifically to provide meaningful electrical energy for charging and/or directly powering a load, whereas the term “electronic data signal” refers to an electrical signal that is utilized to convey data across a medium.

[0068] The wireless power transfer system **10** provides for the wireless transmission of electrical signals via near field magnetic coupling. As shown in the embodiment of FIG. **1**, the wireless power transfer system **10** includes one or more wireless transmission systems **20** and one or more wireless receiver systems **30**. A wireless receiver system **30** is configured to receive electrical signals from, at least, a wireless transmission system **20**. As illustrated, the system **10** may include any number of wireless transmission systems **20**, up to “N” number of wireless transmission systems **20N**. Similarly, the system **10** may include any number of wireless receiver systems **30**, up to “N” number of wireless receiver systems **30N**.

[0069] As illustrated, the wireless transmission system(s) **20** and wireless receiver system(s) **30** may be configured to transmit electrical signals across, at least, a separation distance or gap **17**. A separation distance or gap, such as the gap **17**, in the context of a wireless power transfer system, such as the system **10**, does not include a physical connection, such as a wired connection. There may be intermediary objects located in a separation distance or gap, such as, but not limited to, air, a counter top, a casing for an electronic device, a plastic filament, an insulator, a mechanical wall, among other things; however, there is no physical, electrical connection at such a separation distance or gap.

[0070] Thus, the combination of two or more wireless transmission systems **20** and wireless receiver system **30** create an electrical connection without the need for a physical connection. As used herein, the term “electrical connection” refers to any facilitation of a transfer of an electrical current, voltage, and/or power from a first location, device, component, and/or source to a second location, device, component, and/or destination. An “electrical connection” may be a physical connection, such as, but not limited to, a wire, a trace, a via, among other physical electrical connections, connecting a first location, device, component, and/or source to a second location, device, component, and/or destination. Additionally or alternatively, an “electrical connection” may be a wireless power and/or data transfer, such as, but not limited to, magnetic, electromagnetic, resonant, and/or inductive field, among other wireless power and/or data transfers, connecting a first location, device, component, and/or source to a second location, device, component, and/or destination.

[0071] As illustrated in FIG. **1**, one or more transmission antennas **21** of the wireless transmission system(s) **20** may operate as a repeater of a wireless power signal. As defined herein, a “repeater” is an antenna that is configured to relay magnetic fields emanating between a transmission antenna **21** and one or both of a receiver antenna **31** and one or more other transmission antennas **21**, when such subsequent transmission antennas **21** are configured as repeaters. Thus, the one or more transmission antennas **21** and/or systems **20** thereof may be configured to relay electrical energy and/or data via NMFC from the transmission antenna **21** to a receiver antenna **31** or to another transmission antenna **21**. In one or more embodiments, such repeating transmission antennas **20B**, **20N** comprise an inductor coil capable of resonating at a frequency that is about the same as the resonating frequency of the transmission antenna **21** and the receiver antenna **31**.

[0072] Further, while FIGS. **1-2B** may depict wireless power signals and wireless data signals transferring only from one antenna (e.g., a transmission antenna **21**) to another antenna (e.g., a receiver antenna **31** and/or a transmission antenna **21**), it is certainly possible that a transmitting antenna **21** may transfer electrical signals and/or couple with one or more other antennas and transfer, at least in part, components of the output signals or magnetic fields of the transmitting antenna **21**. Such transmission may include secondary and/or stray coupling or signal transfer to multiple antennas of the system **10**.

[0073] In some cases, the gap **17** may also be referenced as a “Z-Distance,” because, if one

considers an antenna **21**, **31** each to be disposed substantially along respective common X-Y planes, then the distance separating the antennas **21**, **31** is the gap in a “Z” or “depth” direction. However, flexible and/or non-planar coils are certainly contemplated by embodiments of the present disclosure and, thus, it is contemplated that the gap **17** may not be uniform, across an envelope of connection distances between the antennas **21**, **31**. It is contemplated that various tunings, configurations, and/or other parameters may alter the possible maximum distance of the gap **17**, such that electrical transmission from the wireless transmission system **20** to the wireless receiver system **30** remains possible.

[0074] The wireless power transfer system **10** operates when the wireless transmission system **20** and the wireless receiver system **30** are coupled. As used herein, the terms “couples,” “coupled,” and “coupling” generally refer to magnetic field coupling, which occurs when a transmitter and/or any components thereof and a receiver and/or any components thereof are coupled to each other through a magnetic field. Such coupling may include coupling, represented by a coupling coefficient (k), that is at least sufficient for an induced electrical power signal, from a transmitter, to be harnessed by a receiver. Coupling of the wireless transmission system **20** and the wireless receiver system **30**, in the system **10**, may be represented by a resonant coupling coefficient of the system **10** and, for the purposes of wireless power transfer, the coupling coefficient for the system **10** may be in the range of about 0.01 and 0.9.

[0075] As illustrated, at least one wireless transmission system **20A** is associated with an input power source **12**. The input power source **12** may be operatively associated with a host device, which may be any electrically operated device, circuit board, electronic assembly, dedicated charging device, or any other contemplated electronic device. Example host devices, with which the wireless transmission system **20A** may be associated therewith, include, but are not limited to including, a device that includes an integrated circuit, a portable computing device, storage medium for electronic devices, charging apparatus for one or multiple electronic devices, dedicated electrical charging devices, among other contemplated electronic devices.

[0076] The input power source **12** may be or may include one or more electrical storage devices, such as an electrochemical cell, a battery pack, and/or a capacitor, among other storage devices. Additionally or alternatively, the input power source **12** may be any electrical input source (e.g., any alternating current (AC) or direct current (DC) delivery port) and may include connection apparatus from said electrical input source to the wireless transmission system **20** (e.g., transformers, regulators, conductive conduits, traces, wires, or equipment, goods, computer, camera, mobile phone, and/or other electrical device connection ports and/or adaptors, such as but not limited to USB ports and/or adaptors, among other contemplated electrical components).

[0077] In FIG. **1**, the only wireless transmission system **20** that is physically in electrical connection with the input power source **12** is the first wireless transmission system **20A**. A wireless transmission system **20** that is in physical electrical connection with the input power source **12**, for the purposes of this disclosure, is referred to as a “input source connected wireless power transmitter.” The additional wireless power transmission systems **20B**, **20N** both are capable of repeating and transmitting wireless signals and may include like or identical components to those of the input source connected wireless power transmitter **20A**; however, the systems **20B**, **20N** are not in physical electrical connection with the input power source **12** and repeat wireless power signals and wireless data signals from one or more of the input source connected wireless power transmitter **20A**, another transmitter connected wireless power transmitter **20B**, **20N**, or combinations thereof. A wireless transmission system **20** that is not in physical electrical connection with the input power source **12**, for the purposes of this disclosure, is referred to as a “transmitter connected wireless power transmitter.”

[0078] Electrical energy received by the wireless transmission system(s) **20** is then used for at least two purposes: to provide electrical power to internal components of the wireless transmission system **20** and to provide electrical power to the transmission antenna **21**. The transmission antenna

21 is configured to wirelessly transmit the electrical signals conditioned and modified for wireless transmission by the wireless transmission system **20** via near-field magnetic coupling (NFMC). Near-field magnetic coupling enables the transfer of signals wirelessly through magnetic induction between the transmission antenna **21** and one or more of receiving antenna **31** of, or associated with, the wireless receiver system **30**, another transmission antenna **21**, or combinations thereof. Near-field magnetic coupling may be and/or be referred to as “inductive coupling,” which, as used herein, is a wireless power transmission technique that utilizes an alternating electromagnetic field to transfer electrical energy between two antennas. Such inductive coupling is the near field wireless transmission of magnetic energy between two magnetically coupled coils that are tuned to resonate at a similar frequency. Accordingly, such near-field magnetic coupling may enable efficient wireless power transmission via resonant transmission of confined magnetic fields. Further, such near-field magnetic coupling may provide connection via “mutual inductance,” which, as defined herein is the production of an electromotive force in a circuit by a change in current in a second circuit magnetically coupled to the first.

[0079] In one or more embodiments, the inductor coils of either the transmission antenna **21** or the receiver antenna **31** are strategically positioned to facilitate reception and/or transmission of wirelessly transferred electrical signals through near field magnetic induction. Antenna operating frequencies may comprise relatively high operating frequency ranges, examples of which may include, but are not limited to, 6.78 MHz (e.g., in accordance with the Rezence and/or Airfuel interface standard and/or any other proprietary interface standard operating at a frequency of 6.78 MHz), 13.56 MHz (e.g., in accordance with the NFC standard, defined by ISO/IEC standard 18092), 27 MHz, and/or an operating frequency of another proprietary operating mode. The operating frequencies of the antennas **21**, **31** may be operating frequencies designated by the International Telecommunications Union (ITU) in the Industrial, Scientific, and Medical (ISM) frequency bands, including not limited to 6.78 MHz, 13.56 MHz, and 27 MHz, which are designated for use in wireless power transfer.

[0080] The transmitting antenna and the receiving antenna of the present disclosure may be configured to transmit and/or receive electrical power having a magnitude that ranges from about 10 milliwatts (mW) to about 500 watts (W). In one or more embodiments the inductor coil of the transmitting antenna **21** is configured to resonate at a transmitting antenna resonant frequency or within a transmitting antenna resonant frequency band.

[0081] As known to those skilled in the art, a “resonant frequency” or “resonant frequency band” refers a frequency or frequencies wherein amplitude response of the antenna is at a relative maximum, or, additionally or alternatively, the frequency or frequency band where the capacitive reactance has a magnitude substantially similar to the magnitude of the inductive reactance. In one or more embodiments, the transmitting antenna resonant frequency is at a high frequency, as known to those in the art of wireless power transfer.

[0082] The wireless receiver system **30** may be associated with at least one electronic device **14**, wherein the electronic device **14** may be any device that requires electrical power for any function and/or for power storage (e.g., via a battery and/or capacitor). Additionally, the electronic device **14** may be any device capable of receipt of electronically transmissible data. For example, the device may be, but is not limited to being, a handheld computing device, a mobile device, a portable appliance, a computer peripheral, an integrated circuit, an identifiable tag, a kitchen utility device, an electronic tool, an electric vehicle, a game console, a robotic device, a wearable electronic device (e.g., an electronic watch, electronically modified glasses, altered-reality (AR) glasses, virtual reality (VR) glasses, among other things), a portable scanning device, a portable identifying device, a sporting good, an embedded sensor, an Internet of Things (IoT) sensor, IoT enabled clothing, IoT enabled recreational equipment, industrial equipment, medical equipment, a medical device a tablet computing device, a portable control device, a remote controller for an electronic device, a gaming controller, among other things.

[0083] For the purposes of illustrating the features and characteristics of the disclosed embodiments, arrow-ended lines are utilized to illustrate transferrable and/or communicative signals and various patterns are used to illustrate electrical signals that are intended for power transmission and electrical signals that are intended for the transmission of data and/or control instructions. Solid lines indicate signal transmission of electrical energy over a physical and/or wireless power transfer, in the form of power signals that are, ultimately, utilized in wireless power transmission from the wireless transmission system **20** to the wireless receiver system **30**. Further, dotted lines are utilized to illustrate electronically transmittable data signals, which ultimately may be wirelessly transmitted from the wireless transmission system **20** to the wireless receiver system **30**.

[0084] While the systems and methods herein illustrate the transmission of wirelessly transmitted energy, wireless power signals, wirelessly transmitted power, wirelessly transmitted electromagnetic energy, and/or electronically transmittable data, it is certainly contemplated that the systems, methods, and apparatus disclosed herein may be utilized in the transmission of only one signal, various combinations of two signals, or more than two signals and, further, it is contemplated that the systems, method, and apparatus disclosed herein may be utilized for wireless transmission of other electrical signals in addition to or uniquely in combination with one or more of the above mentioned signals. In some examples, the signal paths of solid or dotted lines may represent a functional signal path, whereas, in practical application, the actual signal is routed through additional components en route to its indicated destination. For example, it may be indicated that a data signal routes from a communications apparatus to another communications apparatus; however, in practical application, the data signal may be routed through an amplifier, then through a transmission antenna, to a receiver antenna, where, on the receiver end, the data signal is decoded by a respective communications device of the receiver.

[0085] Turning now to FIG. 2, the wireless power transfer system **10** is illustrated as a block diagram including example sub-systems of both the wireless transmission systems **20** and the wireless receiver systems **30**. The wireless transmission systems **20** may include, at least, a power conditioning system **40**, a transmission control system **26**, a transmission tuning system **24**, and the transmission antenna **21**. A first portion of the electrical energy input from the input power source **12** may be configured to electrically power components of the wireless transmission system **20** such as, but not limited to, the transmission control system **26**. A second portion of the electrical energy input from the input power source **12** is conditioned and/or modified for wireless power transmission, to the wireless receiver system **30**, via the transmission antenna **21**. Accordingly, the second portion of the input energy is modified and/or conditioned by the power conditioning system **40**. While not illustrated, it is certainly contemplated that one or both of the first and second portions of the input electrical energy may be modified, conditioned, altered, and/or otherwise changed prior to receipt by the power conditioning system **40** and/or transmission control system **26**, by further contemplated subsystems (e.g., a voltage regulator, a current regulator, switching systems, fault systems, safety regulators, among other things).

[0086] In some examples including transmitter connected wireless transmission systems **20B**, **20N**, active or externally powered components of the wireless transmission system **20** may be shorted or bypassed, when the electrical signals pass through circuitry of the transmitter connected wireless transmission systems **20B**, **20N**. Such shorting or bypassing of the active electronics may be achieved when the transmission antennas **21B**, **21N** are properly impedance matched for repeating the wireless signals. Such signal travel through, for example, the transmission tuning systems **20B**, **20N** may provide for greater filtering and/or signal fidelity, as another instance of filtering and/or tuning is provided to the travelling signal, prior to transmission by the transmission antennas **21B**, **21N**. As illustrated best in the system of FIG. 2B, some example transmitter connected wireless transmission systems **20B**, **20N** may omit one or more of the active circuits and/or active circuit components of the wireless transmission system **20A**.

[0087] “Active components,” as defined herein, refer to components of the wireless transmission system(s) **20** that require an input power (e.g., from an input power source **12**) to perform their intended functions within the wireless transmission system(s) **20** and/or any sub-components thereof. Active components include, but are not limited to including, processors, controllers, amplifiers, transistors, or combinations thereof, among other active components known to those having skill in the art. “Passive components,” as defined herein, refer to components of the wireless transmission system(s) **20** that perform their intended functions, within the wireless transmission system(s) **20** and/or any sub-components thereof, whether or not the passive components are in a signal path of an input power source. Example passive components include, but are not limited to including, resistors, capacitors, inductors, diodes, transformers, or combinations thereof, among other passive components known to those having skill in the art.

[0088] By omitting the active components in the signal path, modular, additional transmitter connected wireless transmission systems **20** may be provided to a user at lower cost than an input source connected wireless transmission system **20A**. Thus, if the user desires to increase the charging area for the electronic device(s) **14**, transmitter connected wireless transmission systems **20** may be provided at a lower cost, due to the omission of active components that would otherwise be necessary if the system **20** was drawing power from an input power source. Additionally, by omitting the active components from the signal path, transmission of the wireless signals, via the wireless transmission system **10** including one or more transmission systems **20B**, **20N** configured as repeating systems, power or efficiency losses caused by the active components may be removed from the signal transfer.

[0089] The term “modular,” as defined herein, is an adjective referring to systems that may be constructed utilizing standardized units or components, such that user flexibility and/or reconfigurability with such standardized units or components allows for a variety uses or permutations of the system.

[0090] Additionally or alternatively, the wireless transmission systems disclosed herein may be reconfigurable. A “reconfigurable” wireless power transfer or transmission system, as defined herein, refers to a wireless power transfer or transmission system having a plurality of secondary transmission systems (e.g., the wireless transmission systems **20B**, **20N**) capable of being moved relative to a primary transmission system (e.g., the wireless transmission system **20A**), while, during such movement, the secondary transmission system(s) are still capable of receiving wireless power signals from the primary transmission system. A primary transmission system, as defined herein, refers to a powered and/or “active” wireless power transmission system receiving electrical energy or power directly from an input power source, which conditions the electrical energy or power for wireless transmission. The primary transmission system generates a primary or active powering/charging zone proximate to the primary transmission system. A secondary transmission system, as defined herein, refers to a wirelessly powered or “passive” wireless transmission system configured to receive wireless power signals from a primary transmission system and transmit or repeat the wireless power signals to one or more of additional secondary transmission systems, wireless receiver systems, or combinations thereof. Secondary wireless transmission systems generate a secondary or passive powering/charging zone proximate to the secondary wireless transmission system(s).

[0091] Referring now to FIG. **3**, with continued reference to FIGS. **1** and **2**, subcomponents and/or systems of the transmission control system **26** are illustrated. The transmission control system **26** may include a sensing system **50**, a transmission controller **28**, a communications system **29**, a driver **48**, and a memory **27**.

[0092] The transmission controller **28** may be any electronic controller or computing system that includes, at least, a processor which performs operations, executes control algorithms, stores data, retrieves data, gathers data, controls and/or provides communication with other components and/or subsystems associated with the wireless transmission system **20**, and/or performs any other

computing or controlling task desired. The transmission controller **28** may be a single controller or may include more than one controller disposed to control various functions and/or features of the wireless transmission system **20**. Functionality of the transmission controller **28** may be implemented in hardware and/or software and may rely on one or more data maps relating to the operation of the wireless transmission system **20**. To that end, the transmission controller **28** may be operatively associated with the memory **27**. The memory may include one or more of internal memory, external memory, and/or remote memory (e.g., a database and/or server operatively connected to the transmission controller **28** via a network, such as, but not limited to, the Internet). The internal memory and/or external memory may include, but are not limited to including, one or more of a read only memory (ROM), including programmable read-only memory (PROM), erasable programmable read-only memory (EPROM or sometimes but rarely labelled EROM), electrically erasable programmable read-only memory (EEPROM), random access memory (RAM), including dynamic RAM (DRAM), static RAM (SRAM), synchronous dynamic RAM (SDRAM), single data rate synchronous dynamic RAM (SDR SDRAM), double data rate synchronous dynamic RAM (DDR SDRAM, DDR2, DDR3, DDR4), and graphics double data rate synchronous dynamic RAM (GDDR SDRAM, GDDR2, GDDR3, GDDR4, GDDR5, a flash memory, a portable memory, and the like. Such memory media are examples of nontransitory machine readable and/or computer readable memory media.

[0093] While particular elements of the transmission control system **26** are illustrated as independent components and/or circuits (e.g., the driver **48**, the memory **27**, the communications system **29**, the sensing system **50**, among other contemplated elements) of the transmission control system **26**, such components may be integrated with the transmission controller **28**. In some examples, the transmission controller **28** may be an integrated circuit configured to include functional elements of one or both of the transmission controller **28** and the wireless transmission system **20**, generally.

[0094] As illustrated, the transmission controller **28** is in operative association, for the purposes of data transmission, receipt, and/or communication, with, at least, the memory **27**, the communications system **29**, the power conditioning system **40**, the driver **48**, and the sensing system **50**. The driver **48** may be implemented to control, at least in part, the operation of the power conditioning system **40**. In some examples, the driver **48** may receive instructions from the transmission controller **28** to generate and/or output a generated pulse width modulation (PWM) signal to the power conditioning system **40**. In some such examples, the PWM signal may be configured to drive the power conditioning system **40** to output electrical power as an alternating current signal, having an operating frequency defined by the PWM signal. In some examples, PWM signal may be configured to generate a duty cycle for the AC power signal output by the power conditioning system **40**. In some such examples, the duty cycle may be configured to be about 50% of a given period of the AC power signal.

[0095] The sensing system may include one or more sensors, wherein each sensor may be operatively associated with one or more components of the wireless transmission system **20** and configured to provide information and/or data. The term “sensor” is used in its broadest interpretation to define one or more components operatively associated with the wireless transmission system **20** that operate to sense functions, conditions, electrical characteristics, operations, and/or operating characteristics of one or more of the wireless transmission system **20**, the wireless receiving system **30**, the input power source **12**, the host device **11**, the transmission antenna **21**, the receiver antenna **31**, along with any other components and/or subcomponents thereof.

[0096] As illustrated in the embodiment of FIG. **4**, the sensing system **50** may include, but is not limited to including, a thermal sensing system **52**, an object sensing system **54**, a receiver sensing system **56**, a current sensor **57**, and/or any other sensor(s) **58**. Within these systems, there may exist even more specific optional additional or alternative sensing systems addressing particular sensing

aspects required by an application, such as, but not limited to: a condition-based maintenance sensing system, a performance optimization sensing system, a state-of-charge sensing system, a temperature management sensing system, a component heating sensing system, an IoT sensing system, an energy and/or power management sensing system, an impact detection sensing system, an electrical status sensing system, a speed detection sensing system, a device health sensing system, among others. The object sensing system **54**, may be a foreign object detection (FOD) system.

[0097] Each of the thermal sensing system **52**, the object sensing system **54**, the receiver sensing system **56**, the current sensor **57**, and/or the other sensor(s) **58**, including the optional additional or alternative systems, are operatively and/or communicatively connected to the transmission controller **28**. The thermal sensing system **52** is configured to monitor ambient and/or component temperatures within the wireless transmission system **20** or other elements nearby the wireless transmission system **20**. The thermal sensing system **52** may be configured to detect a temperature within the wireless transmission system **20** and, if the detected temperature exceeds a threshold temperature, the transmission controller **28** prevents the wireless transmission system **20** from operating. Such a threshold temperature may be configured for safety considerations, operational considerations, efficiency considerations, and/or any combinations thereof. In a non-limiting example, if, via input from the thermal sensing system **52**, the transmission controller **28** determines that the temperature within the wireless transmission system **20** has increased from an acceptable operating temperature to an undesired operating temperature (e.g., in a non-limiting example, the internal temperature increasing from about 20° Celsius (C) to about 50° C., the transmission controller **28** prevents the operation of the wireless transmission system **20** and/or reduces levels of power output from the wireless transmission system **20**. In some non-limiting examples, the thermal sensing system **52** may include one or more of a thermocouple, a thermistor, a negative temperature coefficient (NTC) resistor, a resistance temperature detector (RTD), and/or any combinations thereof.

[0098] As depicted in FIG. **4**, the transmission sensing system **50** may include the object sensing system **54**. The object sensing system **54** may be configured to detect one or more of the wireless receiver system **30** and/or the receiver antenna **31**, thus indicating to the transmission controller **28** that the receiver system **30** is proximate to the wireless transmission system **20**. Additionally or alternatively, the object sensing system **54** may be configured to detect presence of unwanted objects in contact with or proximate to the wireless transmission system **20**. In some examples, the object sensing system **54** is configured to detect the presence of an undesired object. In some such examples, if the transmission controller **28**, via information provided by the object sensing system **54**, detects the presence of an undesired object, then the transmission controller **28** prevents or otherwise modifies operation of the wireless transmission system **20**. In some examples, the object sensing system **54** utilizes an impedance change detection scheme, in which the transmission controller **28** analyzes a change in electrical impedance observed by the transmission antenna **20** against a known, acceptable electrical impedance value or range of electrical impedance values.

[0099] Additionally or alternatively, the object sensing system **54** may utilize a quality factor (Q) change detection scheme, in which the transmission controller **28** analyzes a change from a known quality factor value or range of quality factor values of the object being detected, such as the receiver antenna **31**. The “quality factor” or “Q” of an inductor can be defined as $(\text{frequency (Hz)} \times \text{inductance (H)}) / \text{resistance (ohms)}$, where frequency is the operational frequency of the circuit, inductance is the inductance output of the inductor and resistance is the combination of the radiative and reactive resistances that are internal to the inductor. “Quality factor,” as defined herein, is generally accepted as an index (figure of measure) that measures the efficiency of an apparatus like an antenna, a circuit, or a resonator. In some examples, the object sensing system **54** may include one or more of an optical sensor, an electro-optical sensor, a Hall effect sensor, a proximity sensor, and/or any combinations thereof. In some examples, the quality factor

measurements, described above, may be performed when the wireless power transfer system **10** is performing in band communications.

[0100] The receiver sensing system **56** is any sensor, circuit, and/or combinations thereof configured to detect presence of any wireless receiving system that may be couplable with the wireless transmission system **20**. In some examples, the receiver sensing system **56** and the object sensing system **54** may be combined, may share components, and/or may be embodied by one or more common components. In some examples, if the presence of any such wireless receiving system is detected, wireless transmission of electrical energy, electrical power, electromagnetic energy, and/or data by the wireless transmission system **20** to said wireless receiving system is enabled. In some examples, if the presence of a wireless receiver system is not detected, continued wireless transmission of electrical energy, electrical power, electromagnetic energy, and/or data is prevented from occurring. Accordingly, the receiver sensing system **56** may include one or more sensors and/or may be operatively associated with one or more sensors that are configured to analyze electrical characteristics within an environment of or proximate to the wireless transmission system **20** and, based on the electrical characteristics, determine presence of a wireless receiver system **30**.

[0101] The current sensor **57** may be any sensor configured to determine electrical information from an electrical signal, such as a voltage or a current, based on a current reading at the current sensor **57**. Components of an example current sensor **57** are further illustrated in FIG. 5, which is a block diagram for the current sensor **57**. The current sensor **57** may include a transformer **51**, a rectifier **53**, and/or a low pass filter **55**, to process the AC wireless signals, transferred via coupling between the wireless receiver system(s) **20** and wireless transmission system(s) **30**, to determine or provide information to derive a current ($I_{\text{sub.Tx}}$) or voltage ($V_{\text{sub.Tx}}$) at the transmission antenna **21**. The transformer **51** may receive the AC wireless signals and either step up or step down the voltage of the AC wireless signal, such that it can properly be processed by the current sensor. The rectifier **53** may receive the transformed AC wireless signal and rectify the signal, such that any negative remaining in the transformed AC wireless signal are either eliminated or converted to opposite positive voltages, to generate a rectified AC wireless signal. The low pass filter **55** is configured to receive the rectified AC wireless signal and filter out AC components (e.g., the operating or carrier frequency of the AC wireless signal) of the rectified AC wireless signal, such that a DC voltage is output for the current ($I_{\text{sub.Tx}}$) and/or voltage ($V_{\text{sub.Tx}}$) at the transmission antenna **21**.

[0102] FIG. 6 is a block diagram for a demodulation circuit **70** for the wireless transmission system(s) **20**, which is used by the wireless transmission system **20** to simplify or decode components of wireless data signals of an alternating current (AC) wireless signal, prior to transmission of the wireless data signal to the transmission controller **28**. The demodulation circuit includes, at least, a slope detector **72** and a comparator **74**. In some examples, the demodulation circuit **70** includes a set/reset (SR) latch **76**. In some examples, the demodulation circuit **70** may be an analog circuit comprised of one or more passive components (e.g., resistors, capacitors, inductors, diodes, among other passive components) and/or one or more active components (e.g., operational amplifiers, logic gates, among other active components). Alternatively, it is contemplated that the demodulation circuit **70** and some or all of its components may be implemented as an integrated circuit (IC). In either an analog circuit or IC, it is contemplated that the demodulation circuit may be external of the transmission controller **28** and is configured to provide information associated with wireless data signals transmitted from the wireless receiver system **30** to the wireless transmission system **20**.

[0103] The demodulation circuit **70** is configured to receive electrical information (e.g., $I_{\text{sub.Tx}}$, $V_{\text{sub.Tx}}$) from at least one sensor (e.g., a sensor of the sensing system **50**), detect a change in such electrical information, determine if the change in the electrical information meets or exceeds one of a rise threshold or a fall threshold. If the change exceeds one of the rise threshold or the fall

threshold, the demodulation circuit **70** generates an alert, and, output a plurality of data alerts. Such data alerts are received by the transmitter controller **28** and decoded by the transmitter controller **28** to determine the wireless data signals. In other words, the demodulation circuit **70** is configured to monitor the slope of an electrical signal (e.g., slope of a voltage at the power conditioning system **32** of a wireless receiver system **30**) and output an alert if said slope exceeds a maximum slope threshold or undershoots a minimum slope threshold.

[0104] Such slope monitoring and/or slope detection by the communications system **70** is particularly useful when detecting or decoding an amplitude shift keying (ASK) signal that encodes the wireless data signals in-band of the wireless power signal at the operating frequency. In an ASK signal, the wireless data signals are encoded by damping the voltage of the magnetic field between the wireless transmission system **20** and the wireless receiver system **30**. Such damping and subsequent re-rising of the voltage in the field is performed based on an encoding scheme for the wireless data signals (e.g., binary coding, Manchester coding, pulse-width modulated coding, among other known or novel coding systems and methods). The receiver of the wireless data signals (e.g., the wireless transmission system **20**) must then detect rising and falling edges of the voltage of the field and decode said rising and falling edges to receive the wireless data signals.

[0105] While in a theoretical, ideal scenario, an ASK signal will rise and fall instantaneously, with no slope between the high voltage and the low voltage for ASK modulation; however, in physical reality, there is some time that passes when the ASK signal transitions from the “high” voltage to the “low” voltage. Thus, the voltage or current signal sensed by the demodulation circuit **70** will have some, knowable slope or rate of change in voltage when transitioning from the high ASK voltage to the low ASK voltage. By configuring the demodulation circuit **70** to determine when said slope meets, overshoots and/or undershoots such rise and fall thresholds, known for the slope when operating in the system **10**, the demodulation circuit can accurately detect rising and falling edges of the ASK signal.

[0106] Thus, a relatively inexpensive and/or simplified circuit may be utilized to, at least partially, decode ASK signals down to alerts for rising and falling instances. So long as the transmission controller **28** is programmed to understand the coding schema of the ASK modulation, the transmission controller **28** will expend far less computational resources than it would if it had to decode the leading and falling edges directly from an input current or voltage sense signal from the sensing system **50**. To that end, as the computational resources required by the transmission controller **28** to decode the wireless data signals are significantly decreased due to the inclusion of the demodulation circuit **70**, the demodulation circuit **70** may significantly reduce BOM of the wireless transmission system **20**, by allowing usage of cheaper, less computationally capable processor(s) for or with the transmission controller **28**.

[0107] The demodulation circuit **70** may be particularly useful in reducing the computational burden for decoding data signals, at the transmitter controller **28**, when the ASK wireless data signals are encoded/decoded utilizing a pulse-width encoded ASK signals, in-band of the wireless power signals. A pulse-width encoded ASK signal refers to a signal wherein the data is encoded as a percentage of a period of a signal. For example, a two-bit pulse width encoded signal may encode a start bit as 20% of a period between high edges of the signal, encode “1” as 40% of a period between high edges of the signal, and encode “0” as 60% of a period between high edges of the signal, to generate a binary encoding format in the pulse width encoding scheme. Thus, as the pulse width encoding relies solely on monitoring rising and falling edges of the ASK signal, the periods between rising times need not be constant and the data signals may be asynchronous or “unclocked.” Examples of pulse width encoding and systems and methods to perform such pulse width encoding are explained in greater detail in U.S. patent application Ser. No. 16/735,342 titled “Systems and Methods for Wireless Power Transfer Including Pulse Width Encoded Data Communications,” to Michael Katz, which is commonly owned by the owner of the instant application and is hereby incorporated by reference.

[0108] Turning now to FIG. 7, with continued reference to FIG. 6, an electrical schematic diagram for the demodulation circuit 70 is illustrated. Additionally, reference will be made to FIG. 8, which is an exemplary timing diagram illustrating signal shape or waveform at various stages or sub-circuits of the demodulation circuit 70. The input signal to the demodulation circuit 70 is illustrated in FIG. 7 as Plot A, showing rising and falling edges from a “high” voltage (V.sub.High) on the transmission antenna 21 to a “low” voltage (V.sub.Low) on the transmission antenna 21. The voltage signal of Plot A may be derived from, for example, a current (I.sub.TX) sensed at the transmission antenna 21 by one or more sensors of the sensing system 50. Such rises and falls from V.sub.High to V.sub.Low may be caused by load modulation, performed at the wireless receiver system(s) 30, to modulate the wireless power signals to include the wireless data signals via ASK modulation. As illustrated, the voltage of Plot A does not cleanly rise and fall when the ASK modulation is performed; rather, a slope or slopes, indicating rate(s) of change, occur during the transitions from V.sub.High to V.sub.Low and vice versa.

[0109] As illustrated in FIG. 7, the slope detector 72 includes a high pass filter 71, an operation amplifier (OpAmp) OP.sub.SD, and an optional stabilizing circuit 73. The high pass filter 71 is configured to monitor for higher frequency components of the AC wireless signals and may include, at least, a filter capacitor (C.sub.HF) and a filter resistor (R.sub.HF). The values for C.sub.HF and R.sub.HF are selected and/or tuned for a desired cutoff frequency for the high pass filter 71. In some examples, the cutoff frequency for the high pass filter 71 may be selected as a value greater than or equal to about 1-2 kHz, to ensure adequately fast slope detection by the slope detector 72, when the operating frequency of the system 10 is on the order of MHz (e.g., an operating frequency of about 6.78 MHz). In some examples, the high pass filter 71 is configured such that harmonic components of the detected slope are unfiltered. In view of the current sensor 57 of FIG. 5, the high pass filter 71 and the low pass filter 55, in combination, may function as a bandpass filter for the demodulation circuit 70.

[0110] OP.sub.SD is any operational amplifier having an adequate bandwidth for proper signal response, for outputting the slope of V.sub.Tx, but low enough to attenuate components of the signal that are based on the operating frequency and/or harmonics of the operating frequency. Additionally or alternatively, OP.sub.SD may be selected to have a small input voltage range for V.sub.Tx, such that OP.sub.SD may avoid unnecessary error or clipping during large changes in voltage at V.sub.Tx. Further, an input bias voltage (V.sub.Bias) for OP.sub.SD may be selected based on values that ensure OP.sub.SD will not saturate under boundary conditions (e.g., steepest slopes, largest changes in V.sub.Tx). It is to be noted, and is illustrated in Plot B of FIG. 8, that when no slope is detected, the output of the slope detector 72 will be V.sub.Bias.

[0111] As the passive components of the slope detector 72 will set the terminals and zeroes for a transfer function of the slope detector 72, such passive components must be selected to ensure stability. To that end, if the desired and/or available components selected for C.sub.HF and R.sub.HF do not adequately set the terminals and zeros for the transfer function, additional, optional stability capacitor(s) C.sub.ST may be placed in parallel with R.sub.HF and stability resistor R.sub.ST may be placed in the input path to OP.sub.SD.

[0112] Output of the slope detector 72 (Plot B representing V.sub.SD) may approximate the following equation:

$$[00001] V_{SD} = -R_{HF} C_{HF} \frac{dV}{dt} + V_{Bias}$$

[0113] Thus, V.sub.SD will approximate to V.sub.Bias, when no change in voltage (slope) is detected, and V.sub.SD will output the change in voltage (dV/dt), as scaled by the high pass filter 71, when V.sub.Tx rises and falls between the high voltage and the low voltage of the ASK modulation. The output of the slope detector 72, as illustrated in Plot B, may be a pulse, showing slope of V.sub.Tx rise and fall.

[0114] V.sub.SD is output to the comparator circuit(s) 74, which is configured to receive V.sub.SD, compare V.sub.SD to a rising rate of change for the voltage (V.sub.SUp) and a falling rate of

change for the voltage (V.sub.SLo). If V.sub.SD exceeds or meets V.sub.SUp, then the comparator circuit will determine that the change in V.sub.Tx meets the rise threshold and indicates a rising edge in the ASK modulation. If V.sub.SD goes below or meets V.sub.SLo, then the comparator circuit will determine that the change in V.sub.Tx meets the fall threshold and indicates a falling edge of the ASK modulation. It is to be noted that V.sub.SUp and V.sub.SLo may be selected to ensure a symmetrical triggering.

[0115] In some examples, such as the comparator circuit **74** illustrated in FIG. **6**, the comparator circuit **74** may comprise a window comparator circuit. In such examples, the V.sub.SUp and V.sub.SLo may be set as a fraction of the power supply determined by resistor values of the comparator circuit **74**. In some such examples, resistor values in the comparator circuit may be configured such that

$$[00002] \quad V_{Sup} = V_{in} \left[\frac{R_{U2}}{R_{U1} + R_{U2}} \right]$$

$$V_{SLo} = V_{in} \left[\frac{R_{L2}}{R_{L1} + R_{L2}} \right]$$

where Vin is a power supply determined by the comparator circuit **74**. When V.sub.SD exceeds the set limits for V.sub.SUp or V.sub.SLo, the comparator circuit **74** triggers and pulls the output (V.sub.Cout) low.

[0116] Further, while the output of the comparator circuit **74** could be output to the transmission controller **28** and utilized to decode the wireless data signals by signaling the rising and falling edges of the ASK modulation, in some examples, the SR latch **76** may be included to add noise reduction and/or a filtering mechanism for the slope detector **72**. The SR latch **76** may be configured to latch the signal (Plot C) in a steady state to be read by the transmitter controller **28**, until a reset is performed. In some examples, the SR latch **76** may perform functions of latching the comparator signal and serve as an inverter to create an active high alert out signal. Accordingly, the SR latch **76** may be any SR latch known in the art configured to sequentially excite when the system detects a slope or other modulation excitation. As illustrated, the SR latch **76** may include NOR gates, wherein such NOR gates may be configured to have an adequate propagation delay for the signal. For example, the SR latch **76** may include two NOR gates (NOR.sub.Up, NOR.sub.Lo), each NOR gate operatively associated with the upper voltage output **78** of the comparator **74** and the lower voltage output **79** of the comparator **74**.

[0117] In some examples, such as those illustrated in Plot C, a reset of the SR latch **76** is triggered when the comparator circuit **74** outputs detection of V.sub.SUp (solid plot on Plot C) and a set of the SR latch **76** is triggered when the comparator circuit **74** outputs V.sub.SLo (dashed plot on Plot C). Thus, the reset of the SR latch **76** indicates a falling edge of the ASK modulation and the set of the SR latch **76** indicates a rising edge of the ASK modulation. Accordingly, as illustrated in Plot D, the rising and falling edges, indicated by the demodulation circuit **70**, are input to the transmission controller **28** as alerts, which are decoded to determine the received wireless data signal transmitted, via the ASK modulation, from the wireless receiver system(s) **30**.

[0118] Referring now to FIG. **9**, and with continued reference to FIGS. **1-5**, a block diagram illustrating an embodiment of the power conditioning system **40** is illustrated. At the power conditioning system **40**, electrical power is received, generally, as a DC power source, via the input power source **12** itself or an intervening power converter, converting an AC source to a DC source (not shown). A voltage regulator **46** receives the electrical power from the input power source **12** and is configured to provide electrical power for transmission by the antenna **21** and provide electrical power for powering components of the wireless transmission system **21**. Accordingly, the voltage regulator **46** is configured to convert the received electrical power into at least two electrical power signals, each at a proper voltage for operation of the respective downstream components: a first electrical power signal to electrically power any components of the wireless transmission system **20** and a second portion conditioned and modified for wireless transmission to the wireless receiver system **30**. As illustrated in FIG. **3**, such a first portion is transmitted to, at

least, the sensing system **50**, the transmission controller **28**, and the communications system **29**; however, the first portion is not limited to transmission to just these components and can be transmitted to any electrical components of the wireless transmission system **20**.

[0119] The second portion of the electrical power is provided to an amplifier **42** of the power conditioning system **40**, which is configured to condition the electrical power for wireless transmission by the antenna **21**. The amplifier may function as an inverter, which receives an input DC power signal from the voltage regulator **46** and generates an AC as output, based, at least in part, on PWM input from the transmission control system **26**. The amplifier **42** may be or include, for example, a power stage inverter, such as a single field effect transistor (FET), a dual field effect transistor power stage inverter or a quadruple field effect transistor power stage inverter. The use of the amplifier **42** within the power conditioning system **40** and, in turn, the wireless transmission system **20** enables wireless transmission of electrical signals having much greater amplitudes than if transmitted without such an amplifier. For example, the addition of the amplifier **42** may enable the wireless transmission system **20** to transmit electrical energy as an electrical power signal having electrical power from about 10 mW to about 500 W. In some examples, the amplifier **42** may be or may include one or more class-E power amplifiers. Class-E power amplifiers are efficiently tuned switching power amplifiers designed for use at high frequencies (e.g., frequencies from about 1 MHz to about 1 GHz). Generally, a single-ended class-E amplifier employs a single-terminal switching element and a tuned reactive network between the switch and an output load (e.g., the antenna **21**). Class E amplifiers may achieve high efficiency at high frequencies by only operating the switching element at points of zero current (e.g., on-to-off switching) or zero voltage (off to on switching). Such switching characteristics may minimize power lost in the switch, even when the switching time of the device is long compared to the frequency of operation. However, the amplifier **42** is certainly not limited to being a class-E power amplifier and may be or may include one or more of a class D amplifier, a class EF amplifier, an H inverter amplifier, and/or a push-pull inverter, among other amplifiers that could be included as part of the amplifier **42**.

[0120] Turning now to FIG. **10** and with continued reference to, at least, FIGS. **1** and **2**, the wireless receiver system **30** is illustrated in further detail. The wireless receiver system **30** is configured to receive, at least, electrical energy, electrical power, electromagnetic energy, and/or electrically transmittable data via near field magnetic coupling from the wireless transmission system **20**, via the transmission antenna **21**. As illustrated in FIG. **9**, the wireless receiver system **30** includes, at least, the receiver antenna **31**, a receiver tuning and filtering system **34**, a power conditioning system **32**, a receiver control system **36**, and a voltage isolation circuit **70**. The receiver tuning and filtering system **34** may be configured to substantially match the electrical impedance of the wireless transmission system **20**. In some examples, the receiver tuning and filtering system **34** may be configured to dynamically adjust and substantially match the electrical impedance of the receiver antenna **31** to a characteristic impedance of the power generator or the load at a driving frequency of the transmission antenna **20**.

[0121] As illustrated, the power conditioning system **32** includes a rectifier **33** and a voltage regulator **35**. In some examples, the rectifier **33** is in electrical connection with the receiver tuning and filtering system **34**. The rectifier **33** is configured to modify the received electrical energy from an alternating current electrical energy signal to a direct current electrical energy signal. In some examples, the rectifier **33** is comprised of at least one diode. Some non-limiting example configurations for the rectifier **33** include, but are not limited to including, a full wave rectifier, including a center tapped full wave rectifier and a full wave rectifier with filter, a half wave rectifier, including a half wave rectifier with filter, a bridge rectifier, including a bridge rectifier with filter, a split supply rectifier, a single phase rectifier, a three phase rectifier, a voltage doubler, a synchronous voltage rectifier, a controlled rectifier, an uncontrolled rectifier, and a half controlled rectifier. As electronic devices may be sensitive to voltage, additional protection of the electronic device may be provided by clipper circuits or devices. In this respect, the rectifier **33** may further

include a clipper circuit or a clipper device, which is a circuit or device that removes either the positive half (top half), the negative half (bottom half), or both the positive and the negative halves of an input AC signal. In other words, a clipper is a circuit or device that limits the positive amplitude, the negative amplitude, or both the positive and the negative amplitudes of the input AC signal.

[0122] Some non-limiting examples of a voltage regulator **35** include, but are not limited to, including a series linear voltage regulator, a buck convertor, a low dropout (LDO) regulator, a shunt linear voltage regulator, a step up switching voltage regulator, a step down switching voltage regulator, an inverter voltage regulator, a Zener controlled transistor series voltage regulator, a charge pump regulator, and an emitter follower voltage regulator. The voltage regulator **35** may further include a voltage multiplier, which is as an electronic circuit or device that delivers an output voltage having an amplitude (peak value) that is two, three, or more times greater than the amplitude (peak value) of the input voltage. The voltage regulator **35** is in electrical connection with the rectifier **33** and configured to adjust the amplitude of the electrical voltage of the wirelessly received electrical energy signal, after conversion to AC by the rectifier **33**. In some examples, the voltage regulator **35** may an LDO linear voltage regulator; however, other voltage regulation circuits and/or systems are contemplated. As illustrated, the direct current electrical energy signal output by the voltage regulator **35** is received at the load **16** of the electronic device **14**. In some examples, a portion of the direct current electrical power signal may be utilized to power the receiver control system **36** and any components thereof; however, it is certainly possible that the receiver control system **36**, and any components thereof, may be powered and/or receive signals from the load **16** (e.g., when the load **16** is a battery and/or other power source) and/or other components of the electronic device **14**.

[0123] The receiver control system **36** may include, but is not limited to including, a receiver controller **38**, a communications system **39** and a memory **37**. The receiver controller **38** may be any electronic controller or computing system that includes, at least, a processor which performs operations, executes control algorithms, stores data, retrieves data, gathers data, controls and/or provides communication with other components and/or subsystems associated with the wireless receiver system **30**. The receiver controller **38** may be a single controller or may include more than one controller disposed to control various functions and/or features of the wireless receiver system **30**. Functionality of the receiver controller **38** may be implemented in hardware and/or software and may rely on one or more data maps relating to the operation of the wireless receiver system **30**. To that end, the receiver controller **38** may be operatively associated with the memory **37**. The memory may include one or both of internal memory, external memory, and/or remote memory (e.g., a database and/or server operatively connected to the receiver controller **38** via a network, such as, but not limited to, the Internet). The internal memory and/or external memory may include, but are not limited to including, one or more of a read only memory (ROM), including programmable read-only memory (PROM), erasable programmable read-only memory (EPROM or sometimes but rarely labelled EROM), electrically erasable programmable read-only memory (EEPROM), random access memory (RAM), including dynamic RAM (DRAM), static RAM (SRAM), synchronous dynamic RAM (SDRAM), single data rate synchronous dynamic RAM (SDR SDRAM), double data rate synchronous dynamic RAM (DDR SDRAM, DDR2, DDR3, DDR4), and graphics double data rate synchronous dynamic RAM (GDDR SDRAM, GDDR2, GDDR3, GDDR4, GDDR5), a flash memory, a portable memory, and the like. Such memory media are examples of nontransitory computer readable memory media.

[0124] Further, while particular elements of the receiver control system **36** are illustrated as subcomponents and/or circuits (e.g., the memory **37**, the communications system **39**, among other contemplated elements) of the receiver control system **36**, such components may be external of the receiver controller **38**. In some examples, the receiver controller **38** may be and/or include one or more integrated circuits configured to include functional elements of one or both of the receiver

controller **38** and the wireless receiver system **30**, generally. As used herein, the term “integrated circuits” generally refers to a circuit in which all or some of the circuit elements are inseparably associated and electrically interconnected so that it is considered to be indivisible for the purposes of construction and commerce. Such integrated circuits may include, but are not limited to including, thin-film transistors, thick-film technologies, and/or hybrid integrated circuits.

[0125] In some examples, the receiver controller **38** may be a dedicated circuit configured to send and receive data at a given operating frequency. For example, the receiver controller **38** may be a tagging or identifier integrated circuit, such as, but not limited to, an NFC tag and/or labelling integrated circuit. Examples of such NFC tags and/or labelling integrated circuits include the NTAG® family of integrated circuits manufactured by NXP Semiconductors N.V. However, the communications system **39** is certainly not limited to these example components and, in some examples, the communications system **39** may be implemented with another integrated circuit (e.g., integrated with the receiver controller **38**), and/or may be another transceiver of or operatively associated with one or both of the electronic device **14** and the wireless receiver system **30**, among other contemplated communication systems and/or apparatus. Further, in some examples, functions of the communications system **39** may be integrated with the receiver controller **38**, such that the controller modifies the inductive field between the antennas **21**, **31** to communicate in the frequency band of wireless power transfer operating frequency.

[0126] FIG. **11** is a block diagram for another wireless power transfer system **110A**, which may utilize one or more wireless transmission systems **120** and one or more wireless receiver systems **30**, each wireless receiver system **30** associated with an electronic device **14**. Similar to the systems **10** described above, one or more antenna **121**, **221** of each wireless transmission system **120** may be configured to function as a repeater antenna and/or a transmission antenna. The transmission antenna **121** of the transmission system(s) **120** may comprise or function as multiple transmission antennas, capable of transmitting wireless power to two or more wireless receiver systems **30**, transmitter connected wireless transmission systems **120**, or combinations thereof.

[0127] In wireless power transfer systems, wherein a high resonant frequency is required (e.g. on the order of about 1 MHz to about 1 GHz), the size of an antenna may be, relatively, limited when compared to lower frequency solutions, due to self-resonant frequency, coil sensitivity, amplifier driving capabilities, and/or low coupling efficiency concerns. In some applications, such as, but not limited to, wireless power transfer systems in which a resonant frequency is above about 5 MHz, these issues may make it difficult for antenna designers to create proper coils having a two-dimensional area greater than, about 200 mm by 200 mm. However, using similarly sized antennas, but coupling each of these similar antennas to a common power amplifier/power system (e.g., the power conditioning system **40**) may allow for larger power transfer areas and/or power transfer areas for multiple devices, coupled at higher resonant frequencies. Such designs allow for a system having two or more transmission antennas or antenna portions that are driven by the same transmitter power amplifier in a uniform and efficient way that enables efficient, single and/or simultaneous power transfer in a lower-cost manner that may limit a bill of materials.

[0128] In view of the system **110** of FIG. **11**, such multiple antenna designs may provide a transmitting device with multiple “sub-areas” that either provide the benefit of a wider power transmission area or allow for multiple devices to be powered by a single transmission system. Further, one or more of such sub-areas may be configured as repeaters to receive wireless power from another wireless power transmitter **120**, for subsequent transmission to one or more of a wireless receiver system, another wireless transmission system **120**, or combinations thereof.

[0129] Turning now to FIGS. **12A-B** and with continued reference to FIG. **11**, a simplified schematic diagram of the wireless transmission system **120A** is illustrated. The transmission antenna **121** may include multiple antenna portions **221A**, **221B**, which functionally behave as individual antennas **21**, while connected to a common power conditioning system **40**. As illustrated in FIGS. **12A-B**, the transmission antenna **121A** includes the first antenna portion **221A**, which

includes a first terminal **161** and the second terminal **162**, and the second antenna portion **221B**, which includes a third terminal **163** and a fourth terminal **164**. The amplifier **42** includes a first power terminal **171** and a second power terminal **172**. As illustrated, to achieve the series antenna-to-amplifier connection, the first terminal **61** of the first antenna portion **221A** is in electrical connection with the first power terminal **171**, the fourth terminal of the second antenna portion **221B** is in electrical connection with the second power terminal **72**, and the second terminal **62** of the first antenna portion **221A** is in electrical connection with the third terminal **63** of the second antenna portion **221B**, thereby establishing the series connection between the transmission antenna portions **221A**, **221B**, with respect to the amplifier **42**.

[0130] As discussed above, any of the transmission antennas **21**, **121** and/or antenna portions **221** may be configured to function as one or more of a transmission antenna for transmission to a wireless receiver system **30**, a repeater antenna for repeating AC wireless signals to another wireless transmission system **20**, **120**, or combinations thereof. Accordingly, in some examples, the antenna portions **221** may be configured such that one or both of the antenna portions **221A**, **221B** are configured or tuned to function as a repeater antenna. To that end, the wireless transmission system **120** may include a repeater tuning system **224**, which may be part of or independent from the transmission tuning system **24** of the wireless transmission system **120**. In some examples, the repeater tuning system **224** may include one or more passive components (e.g., capacitors) configured and/or tuned to isolate the magnetic fields generated by each of the antenna portions **221**, **221B** from one another. Such tuning is performed to limit interference or crosstalk between the two antenna portions **221A**, **221B**.

[0131] To isolate the magnetic fields, the repeater tuning system **224** may be configured to phase shift the AC wireless signal when it passes, in series, from the first antenna portion **221A** to the second antenna portion **221B**. Such a phase shift may be configured to shift the waveform of an AC wireless signal of first antenna portion **221A** about 90 degrees from the phase of the waveform of an AC wireless signal of the second antenna portion **221B**. By phase shifting the two respective AC wireless signals of the first and second antenna portions **221A**, **221B** by about 90 degrees, the repeater tuning system **224** may prevent loss or interference between transmitted signals or fields from either antenna portion **221A**, **221B**. Further, such phase shifting may aid in functionally isolating the first antenna portion **221A** and the second antenna portion **221B**, such that each portion **221A**, **221B** may functionally act as an independent transmitter and/or repeater antenna **21**. Additionally or alternatively, the repeater tuning system **224** and/or components thereof may be utilized to filter out high frequency harmonics from the AC wireless signals.

[0132] FIG. **13A** illustrates a top perspective view of an example wireless transmission system **120**, in view of FIGS. **11**=**12**, wherein the wireless transmission system **120** is housed by a transmitter housing **114**. The transmitter housing **114** may be any mechanical body capable of supporting, enclosing, and/or otherwise positioning the wireless transmission system **120**, for use in transmitting AC wireless signals to one or more of a wireless receiver system **30**, a wireless transmission system **20**, **120**, or combinations thereof. As illustrated, the particular wireless transmission system **120** of FIG. **13A** is an input connected wireless transmission system **120**, as it is connected to the input power source **12**.

[0133] FIG. **13B** illustrates the housed wireless transmission system **120**, but with a top surface of the transmitter housing **114** removed or made invisible. Thus, FIG. **12B** shows the transmitter housing **114** supporting the transmission antenna **121** and providing space and enclosure for circuit elements of the wireless transmission system **120**, such as, but not limited to, the transmission tuning system **24**, the repeater tuning system **24**, the sensing system **50**, the transmission control system **26**, and the power conditioning system **40**.

[0134] The wireless transmission systems **120** are configured to be modular wireless power transmitters, reconfigurable wireless power transmitters and/or modular power transmitting pads for powering and/or charging electronic devices. Any number of wireless transmission systems **120**

may be modularly configured, with one another, to produce any size or scale of wireless power networks, for powering and/or charging any number of electronic devices **14** via wireless receiver systems **30**. The wireless transmission systems **120** may utilize their capabilities to function as repeaters, wherein the repeater functionality enables modularity by extending the power or charging area, without need for additional connections to an input power source **12**. FIGS. **14-16**, below, represent non-limiting examples of modularly configured configurations of the wireless power transfer system **110**.

[0135] FIGS. **14A** and **14B** are representative of a first configuration **110B** of the wireless power transfer system **110**. FIG. **14A** is a perspective view of the wireless power transfer system **110B** having multiple electronic devices **14**, configured with wireless receiver systems **30**, positioned such that they are capable of receiving AC wireless signals from the wireless transmission system **120**. In the first configuration **110B**, a wireless power transmission system **120** includes first and second antenna portions **221A**, **221B** and each are functioning as wireless transmission antennas, thus, coupling and transmitting AC wireless signals to wireless receiver systems **30A**, **30B**, each associated, respectively, with electronic devices **14A**, **14B**. The wireless transmission system **120** is capable of functioning to power or charge at least two wireless receiver systems, utilizing a single transmission system **120**.

[0136] FIGS. **15A** and **15B** are representative of a second configuration **110C** of the wireless power transfer system **110**, wherein FIG. **15A** is a top perspective view of the wireless transmission systems **120** and the electronic devices **14** and FIG. **15B** is a schematic illustration of electronic components of the same. The configuration **110C** includes a network of multiple wireless transmission systems **120A**, **120B**, **120C**, **120D** all functioning, in connection, as a common wireless power transmission system for powering the wireless receiver systems **30** of the electronic devices **14**. As illustrated, the first wireless transmission system **120A** is connected to the input power source **12** and, thus, is an input source connected wireless transmission system **120**, while all of the remaining wireless transmission systems **120B**, **120C**, **120D** are not connected to the input power source **12** and, thus, are transmitter connected wireless transmission systems **120B**, **120C**, **120D**.

[0137] As best illustrated in the schematic diagram of FIG. **15B**, the wireless transmission systems **120B**, **120C**, **120D** are configured as a network of transmitter/repeater systems, receiving input power from the input source connected wireless transmission system **120A** and repeating the AC wireless signal throughout, for ultimate transmission to a wireless receiver system **30**. More specifically, as illustrated, a signal path of the AC wireless signals begins at the circuitry of the first wireless transmission system, travels to the first and second antenna portions **221A**, **221B**, wherein the second portion **221B** transmits the AC wireless signals to a first wireless receiver system **30A**. The first antenna portion **221A** is configured to transmit the AC wireless signals, by coupling with a fourth antenna portion **221D** of the second wireless transmission system **120B**. The fourth antenna portion **221D** receives the AC wireless signals, processes the AC wireless signals in its transmission tuning system **24** and/or repeater tuning system **224**, and provides AC wireless power signals to the third antenna portion **221C** of the second wireless transmission system **120C**.

[0138] The third antenna portion **221C** transmits the AC wireless signals to a sixth antenna portion **221F** of the third wireless transmission system **120C**. The sixth antenna portion **221F** receives the AC wireless signals, processes the AC wireless signals in its transmission tuning system **24** and/or repeater tuning system **224**, and provides AC wireless power signals to the fifth antenna portion **221E** of the third wireless transmission system **120C**. The fifth antenna portion **221E**, as illustrated in the configuration **110C**, may both repeat the AC wireless signals to the fourth wireless transmission system **120D** and provide the AC wireless signals to a second wireless receiver system **30C**, with which the fifth antenna portion **221E** is coupled. While illustrated as coupled with the fifth antenna portion **221E**, it is certainly possible that the second wireless receiver system **30C** may couple with any of the antenna portions **221B-G**.

[0139] The repeated AC wireless signal from the fifth portion **221E** may be received by an eighth antenna portion **221H** of the fourth wireless transmission system **120D**. As illustrated, because there are no additional wireless transmission systems **120** in the signal path of the fourth wireless transmission system **120D**, the signal path may end/loop back at the seventh antenna portion **221G**; however, if a receiver system **30** or additional wireless transmission system **120** were placed within coupling range of one or both of the seventh and eighth antenna portions **221G**, **221H**, the portions **221G**, **221H** would be capable of transmitting the AC wireless signals further.

[0140] While the individual wireless transmission systems **120** are illustrated without any visible mechanical connections, to, for example, hold the wireless transmission systems **120** in place to form a larger powering or charging area, it is certainly contemplated that one or more mechanical features may be integrated with the housing(s) **114** to enable positioning features and/or to maintain positioning of the wireless transmission systems **120**, to facilitate proper wireless power transmission and/or wireless power repetition. Such mechanical features may include, but are not limited to including, “male” and “female” mechanical indents configured to hold the wireless transmission systems **120** in place, latches and/or locks configured to connect two or more wireless transmission systems **120**, magnetic connectors to attract a first wireless transmission system **120** to a second wireless transmission system **120**, mechanical connectors for affixing a wireless transmission system **120** to an external surface (e.g., a desktop, a table top, a counter top, and the like), among other contemplated mechanical connection features utilized to position one or more wireless transmission systems **120** in place to facilitate proper wireless power transfer and/or repetition.

[0141] FIGS. **16A** and **16B** are representative of a third configuration **110D** of the wireless power transfer system **110**, wherein FIG. **16A** is a top perspective view of the wireless transmission systems **120** and the electronic devices **14** and FIG. **16B** is a schematic illustration of electronic components of the same. The configuration **110D** includes a network of multiple wireless transmission systems **120A**, **120B**, **120C**, **120D** all functioning, in connection, as a common wireless power transmission system for powering the wireless receiver systems **30** of the electronic devices **14**. As illustrated, the first wireless transmission system **120A** is connected to the input power source **12** and, thus, is an input source connected wireless transmission system **120**, while all of the remaining wireless transmission systems **120B**, **120C**, **120D** are not connected to the input power source **12** and, thus, are transmitter connected wireless transmission systems **120B**, **120C**, **120D**.

[0142] In FIGS. **16A**, **B**, the wireless transmission systems **120B**, **120C**, **120D** are configured as a network of transmitter/repeater systems, receiving input power from the input source connected wireless transmission system **120A** and repeating the AC wireless signal throughout, for ultimate transmission to a wireless receiver system **30**. More specifically, as illustrated, a signal path of the AC wireless signals begins at the circuitry of the first wireless transmission system **120A**, travels to the first and second antenna portions **221A**, **221B**, wherein the second portion **221B** repeats the AC wireless signals to a fourth antenna portion **221D** of the second wireless receiver system **120B**. The fourth antenna portion **221D** receives the AC wireless signals, transmits the AC wireless signals to a receiver antenna **31A** of a wireless receiver system **30A**, processes the AC wireless signals in its transmission tuning system **24** and/or repeater tuning system **24**, and provides AC wireless power signals to the third antenna portion **221C** of the second wireless transmission system **120B**.

[0143] The third antenna portion **221C** is configured to receive the processed AC wireless signals from the fourth antenna portion **221D**, transmit the AC wireless signals to a second wireless receiver system **30B**, and repeat the AC wireless signals to a sixth antenna portion **221F**. The AC wireless signals, received by the sixth antenna portion **221F**, are processed by a tuning system **24** or repeater tuning system **224** associated with the sixth antenna portion **221F** and received by a fifth antenna portion **221E**. The fifth antenna portion **221** repeats the AC wireless signals to an eighth antenna portion **221H**. The AC wireless signals, received by the eighth antenna portion **221H**, are

processed by a tuning system **24** and/or repeater tuning system **224** associated with the eighth antenna portion **221H** and received by a seventh antenna portion **221G**.

[0144] The AC wireless signals received by the seventh antenna portion **221G** are transmitted to a third wireless receiver system **30C**. As illustrated, because there are no additional wireless transmission systems **120** in the signal path of the fourth wireless transmission system **120D**, the signal path may end/loop back at the seventh antenna portion **221G**; however, if a receiver system **30** or additional wireless transmission system **120** were placed within coupling range of one or both of the seventh and eighth antenna portions **221G**, **221H**, the portions **221G**, **221H** would be capable of transmitting the AC wireless signals further.

[0145] It is to be noted that, while the wireless transmission systems **120** are illustrated in a positioning such that electronic devices **14** are located proximate to a top face of the wireless transmission systems(s) **120**, for the purposes of wireless power transfer to the devices **16**, the electronic devices **14** need not, solely, be positioned atop the wireless transmission system(s) **120** to receive electrical signals from one or more wireless transmission system(s) **120**. Alternatively, the wireless transmission system(s) **120** may be configured such that an electronic device **14** receives wireless signals from one or more wireless transmission system(s) **120** when the electronic device(s) **14** are positioned at one or more of a top surface of one or more wireless transmission system(s) **120**, adjacent to one or more wireless transmission system(s) **120**, beneath one or more wireless transmission system(s) **120**, or combinations thereof, among other contemplated proximate positionings of one or more electronic device(s) **16**, with respect to one or more wireless transmission system(s) **120**.

[0146] While the electronic devices **14** in FIGS. **14-16**, as illustrated, resemble computer peripherals, such as input devices like a mouse or keyboard, the electronic devices **14** that are capable of being powered and/or charged by the modular wireless transmission systems **120** are certainly not limited to computer peripherals. Accordingly, the modular wireless transmission systems **120** may be configured to power other devices, such as audio devices, video devices, mobile devices, game controllers, conference equipment, among other electronic devices mentioned above with reference to FIG. **1**.

[0147] FIG. **17** is a top view of an embodiment of the transmission antenna **121**, which may be utilized as the transmission antenna **21** and may include first and second antenna or coil portions **221A**, **221B**. As discussed above, the transmission antenna **121** may be configured such that each of the antenna portions **221A**, **221B** function as separate antennas; alternatively, the antenna portions **221A**, **221B** may be configured to extend a charging and/or powering envelope/or improve uniformity of magnetic field distribution, relative to the surface area of the transmission antenna **121**. Further, as discussed above, one or more components may, electrically, intersect the signal path between the first and second antenna portions **221A**, **221B**, at, for example, a location between the second and third terminals **162**, **163**. Such components may include, for example, the repeater tuning system **224**.

[0148] While the transmission antenna **121** of FIG. **17** is referenced as a “transmission antenna,” it is certainly possible that a like or similar antenna to the transmission antenna **121**, having a common and/or similar geometry to the transmission antenna **121**, may be utilized as a wireless receiver antenna **31**. Such use of the antenna **121** as a receiver antenna may be useful in a wireless power transfer scenario in which a large wireless power receiving area is desired, such receiving area having a substantially uniform coupling area for power receipt from one or more wireless transmission systems **20**, **120**.

[0149] Each of the first and second antenna portions **221A**, **221B** include a plurality of turns **80A**, **80B**, respectively. Each of the plurality of turns **80** includes at least one inner turn **84** and at least one outer turn **82**. At least one of the inner turns has an inner turn width **85**, and at least one outer turn **82** has an outer turn width **83**. While the inner turn width **85** and the outer turn width **83** may vary along the circumferential locations of any of the turns **80**, generally, inner turn widths **85** are

less than outer turn widths **83** at similar and/or parallel points on substantially concentric turns of the antenna portion **221**. While the first and second coil portions **221A**, **221B** are illustrated with multiple turns **80**, it is certainly possible for either of the first and second coil portions **221A**, **221B** to function, for the purposes of the transmission antenna **121** and/or the system **120**, while having only a single turn.

[0150] To create the coil geometry for one or both of the antenna **121** and the antenna portions **221**, wherein each antenna portion **221** may be functionally independent, the antenna **121** includes one or more wire crossovers, which electrically connect two turns of the antenna **121**, while insulating said turns from one or more proximal turns. For example, the at least one inner turn **84** may be electrically connected to the at least one outer turn via a crossover **86**. Additionally or alternatively, current in the at least one outer turn **82** may flow from a first outer turn **82** to a second turn **82** via a crossover **86**. The crossovers **86** allow for the current path in the antenna **121** to fully traverse each of the antenna portions **221**, prior to entering the opposing antenna portion **221**.

[0151] To illustrate and describe the current path in the transmission antenna **121**, locations A-G are marked on the first antenna portion **221A**. The electrical current enters the first antenna portion **221** at or proximate to the first terminal **161**, as denoted by the location A on the transmission antenna **121**. The current flows through the outermost turn of the outer turns **82A**, until it reaches a first crossover **86A**, wherein the wire crosses over into a second turn of the outer turns **82A** that is inward of the outermost turn **82A**, as depicted at location B. The current continues to flow in the middle turn **82A** until it reaches another crossover **86**, wherein the wire and, thus, current crosses over into the innermost turn of the outer turns **82A**, as depicted at location C. The current continues to flow through to location D, wherein it encounters another crossover and enters the inner turn **84A**. The current then flows entirely through the inner turn **84A** and exits back at the crossover it enters, travelling into the innermost turn of the outer turns **82A**, as depicted at location E. The current then will reverse the travel it made inward, flowing from point E to point F, crossing over into the middle outer turn **82A**, to the location G, crossing over into the outermost outer turn **82A**, and eventually arriving at the second terminal **162**. Then, in some examples, the current may flows to one or more of a transmission tuning system **24**, a repeater tuning system **224**, the second antenna portion **221B**, or combinations thereof, as the current travels from the second terminal **162** to the third terminal **163**. The current enters the second antenna portion **221B** at the third terminal **63** and similarly will flow outward to inward then back outward to the fourth terminal **64**, in reverse but like manner to the current flow of the current flow through the first antenna portion **221A**, as described herein.

[0152] In some examples, the transmission antenna **121** may be a wire wound antenna comprising a conductive wire formed in a shape with the characteristics disclosed herein. In some such examples, the conductive wire may be a continuous conductive wire, extending from the first terminal **161** to the fourth terminal **164**. It is to be contemplated that a continuous wire includes wires that have a tap or exterior connector at any location, such as, but not limited to, between the second and third terminals **62**, **63**. However, the antenna **121** is not limited to being formed as a wire wound antenna and the transmission antenna **121** may be implemented as a printed circuit board (PCB), flexible printed circuit board (FPC), and/or any other printed or non-printed antenna implementation.

[0153] As illustrated, the crossovers **86** are positioned at portions where a first portion of the conductive wire has to cross over a second portion of the conductive wire, without forming an electrical connection between the first and second portions of the conductive wire. Therefore, an insulator **88** may be positioned between the first and second portions of the conductive wire, such that when a crossover **86** occurs, there is no conduction or interruption of the aforementioned signal path at a crossover **86**.

[0154] By utilizing the transmission antenna of FIG. **17** and the intelligent placement of the crossovers **86**, the antenna **121** may effectively function as multiple antennas capable of

transmission to multiple receivers. Further, due to the spacing of the inner and outer turns **84, 82**, a more uniform charge envelope may be achieved, leading to greater spatial freedom for the receiver when placed relative to the transmission antenna **121**. Thus, having a higher density of turns on the outer edges of the antenna **121** may prevent dead spots or inconsistent coupling, when a receiver is positioned proximate to an outer edge of the wireless transmission system **120**.

[0155] FIG. **18** illustrates an example, non-limiting embodiment of the receiver antenna **31** that may be used with any of the systems, methods, and/or apparatus disclosed herein. In the illustrated embodiment, the antenna **31**, is a flat spiral coil configuration. Non-limiting examples can be found in U.S. Pat. Nos. 9,941,743, 9,960,628, 9,941,743 all to Peralta et al.; 9,948,129, 10,063,100 to Singh et al.; U.S. Pat. No. 9,941,590 to Luzinski; U.S. Pat. No. 9,960,629 to Rajagopalan et al.; and U.S. Patent App. Nos. 2017/0040107, 2017/0040105, 2017/0040688 to Peralta et al.; all of which are assigned to the assignee of the present application and incorporated fully herein by reference.

[0156] In addition, the antenna **31** may be constructed having a multi-layer-multi-turn (MLMT) construction in which at least one insulator is positioned between a plurality of conductors. Non-limiting examples of antennas having an MLMT construction that may be incorporated within the wireless transmission system(s) **20** and/or the wireless receiver system(s) **30** may be found in U.S. Pat. Nos. 8,610,530, 8,653,927, 8,680,960, 8,692,641, 8,692,642, 8,698,590, 8,698,591, 8,707,546, 8,710,948, 8,803,649, 8,823,481, 8,823,482, 8,855,786, 8,898,885, 9,208,942, 9,232,893, and 9,300,046 to Singh et al., all of which are assigned to the assignee of the present application are incorporated fully herein. These are merely exemplary antenna examples; however, it is contemplated that the antennas **21, 31** may be any antenna capable of the aforementioned higher power, high frequency wireless power transfer.

[0157] FIG. **19** is an example block diagram for a method **1000** of designing a system for wirelessly transferring one or more of electrical energy, electrical power, electromagnetic energy, and electronic data, in accordance with the systems, methods, and apparatus of the present disclosure. To that end, the method **1000** may be utilized to design a system in accordance with any disclosed embodiments of the system **10, 110** and any components thereof.

[0158] At block **1200**, the method **1000** includes designing a wireless transmission system for use in the system **10, 110**. The wireless transmission system designed at block **1200** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless transmission system **20, 120**, in whole or in part and, optionally, including any components thereof. Block **1200** may be implemented as a method **1200** for designing a wireless transmission system.

[0159] Turning now to FIG. **20** and with continued reference to the method **1000** of FIG. **18**, an example block diagram for the method **1200** for designing a wireless transmission system is illustrated. The wireless transmission system designed by the method **1200** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless transmission system **20, 120** in whole or in part and, optionally, including any components thereof. The method **1200** includes designing and/or selecting a transmission antenna for the wireless transmission system, as illustrated in block **1210**. The designed and/or selected transmission antenna may be designed and/or selected in accordance with one or more of the aforementioned and disclosed embodiments of the transmission antenna **21, 121, 221**, in whole or in part and including any components thereof. The method **1200** also includes designing and/or tuning a transmission tuning system for the wireless transmission system, as illustrated in block **1220**. Such designing and/or tuning may be utilized for, but not limited to being utilized for, impedance matching, as discussed in more detail above. The designed and/or tuned transmission tuning system may be designed and/or tuned in accordance with one or more of the aforementioned and disclosed embodiments of wireless transmission system **20, 120**, in whole or in part and, optionally, including any components thereof.

[0160] The method **1200** further includes designing a power conditioning system for the wireless transmission system **20, 120**, as illustrated in block **1230**. The power conditioning system designed

may be designed with any of a plurality of power output characteristic considerations, such as, but not limited to, power transfer efficiency, maximizing a transmission gap (e.g., the gap **17**), increasing output voltage to a receiver, mitigating power losses during wireless power transfer, increasing power output without degrading fidelity for data communications, optimizing power output for multiple coils receiving power from a common circuit and/or amplifier, among other contemplated power output characteristic considerations. The power conditioning system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the power conditioning system **40**, in whole or in part and, optionally, including any components thereof. Further, at block **1240**, the method **1200** may involve determining and/or optimizing a connection, and any associated connection components, between the input power source **12** and the power conditioning system that is designed at block **1230**. Such determining and/or optimizing may include selecting and implementing protection mechanisms and/or apparatus, selecting and/or implementing voltage protection mechanisms, among other things.

[0161] The method **1200** further includes designing and/or programing a transmission control system of the wireless transmission system of the method **1000**, as illustrated in block **1250**. The designed transmission control system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the transmission control system **26**, in whole or in part and, optionally, including any components thereof. Such components thereof include, but are not limited to including, the sensing system **50**, the driver **41**, the transmission controller **28**, the memory **27**, the communications system **29**, the thermal sensing system **52**, the object sensing system **54**, the receiver sensing system **56**, the other sensor(s) **58**, the gate voltage regulator **43**, the PWM generator **41**, the frequency generator **348**, in whole or in part and, optionally, including any components thereof.

[0162] Returning now to FIG. **20**, at block **1300**, the method **1000** includes designing a wireless receiver system for use in the system **10**, **110**. The wireless transmission system designed at block **1300** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless receiver system **30** in whole or in part and, optionally, including any components thereof. Block **1300** may be implemented as a method **1300** for designing a wireless receiver system.

[0163] Turning now to FIG. **21** and with continued reference to the method **1000** of FIG. **19**, an example block diagram for the method **1300** for designing a wireless receiver system is illustrated. The wireless receiver system designed by the method **1300** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless receiver system **30** in whole or in part and, optionally, including any components thereof. The method **1300** includes designing and/or selecting a receiver antenna for the wireless receiver system, as illustrated in block **1310**. The designed and/or selected receiver antenna may be designed and/or selected in accordance with one or more of the aforementioned and disclosed embodiments of the receiver antenna **31**, in whole or in part and including any components thereof. The method **1300** includes designing and/or tuning a receiver tuning system for the wireless receiver system, as illustrated in block **1320**. Such designing and/or tuning may be utilized for, but not limited to being utilized for, impedance matching, as discussed in more detail above. The designed and/or tuned receiver tuning system may be designed and/or tuned in accordance with one or more of the aforementioned and disclosed embodiments of the receiver tuning and filtering system **34** in whole or in part and/or, optionally, including any components thereof.

[0164] The method **1300** further includes designing a power conditioning system for the wireless receiver system, as illustrated in block **1330**. The power conditioning system may be designed with any of a plurality of power output characteristic considerations, such as, but not limited to, power transfer efficiency, maximizing a transmission gap (e.g., the gap **17**), increasing output voltage to a receiver, mitigating power losses during wireless power transfer, increasing power output without degrading fidelity for data communications, optimizing power output for multiple coils receiving

power from a common circuit and/or amplifier, among other contemplated power output characteristic considerations. The power conditioning system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the power conditioning system **32** in whole or in part and, optionally, including any components thereof. Further, at block **1340**, the method **1300** may involve determining and/or optimizing a connection, and any associated connection components, between the load **16** and the power conditioning system of block **1330**. Such determining may include selecting and implementing protection mechanisms and/or apparatus, selecting and/or implementing voltage protection mechanisms, among other things. [0165] The method **1300** further includes designing and/or programing a receiver control system of the wireless receiver system of the method **1300**, as illustrated in block **1350**. The designed receiver control system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the receiver control system **36** in whole or in part and, optionally, including any components thereof. Such components thereof include, but are not limited to including, the receiver controller **38**, the memory **37**, and the communications system **39**, in whole or in part and, optionally, including any components thereof.

[0166] Returning now to the method **1000** of FIG. **19**, the method **1000** further includes, at block **1400**, optimizing and/or tuning both the wireless transmission system and the wireless receiver system for wireless power transfer. Such optimizing and/or tuning includes, but is not limited to including, controlling and/or tuning parameters of system components to match impedance, optimize and/or set voltage and/or power levels of an output power signal, among other things and in accordance with any of the disclosed systems, methods, and apparatus herein. Further, the method **1000** includes optimizing and/or tuning one or both of the wireless transmission system and the wireless receiver system for data communications, in view of system characteristics necessary for wireless power transfer. Such optimizing and/or tuning includes, but is not limited to including, optimizing power characteristics for concurrent transmission of electrical power signals and electrical data signals, tuning quality factors of antennas for different transmission schemes, among other things and in accordance with any of the disclosed systems, methods, and apparatus herein.

[0167] FIG. **22** is an example block diagram for a method **2000** for manufacturing a system for wirelessly transferring one or both of electrical power signals and electrical data signals, in accordance with the systems, methods, and apparatus of the present disclosure. To that end, the method **2000** may be utilized to manufacture a system in accordance with any disclosed embodiments of the system **10**, **110** and any components thereof.

[0168] At block **2200**, the method **2000** includes manufacturing a wireless transmission system for use in the system **10**, **110**. The wireless transmission system manufactured at block **2200** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless transmission system **20**, **120** in whole or in part and, optionally, including any components thereof. Block **2200** may be implemented as a method **2200** for manufacturing a wireless transmission system.

[0169] Turning now to FIG. **23** and with continued reference to the method **2000** of FIG. **21**, an example block diagram for the method **2200** for manufacturing a wireless transmission system is illustrated. The wireless transmission system manufactured by the method **2200** may be manufactured in accordance with one or more of the aforementioned and disclosed embodiments of the wireless transmission system **20**, **120** in whole or in part and, optionally, including any components thereof. The method **2200** includes manufacturing a transmission antenna for the wireless transmission system, as illustrated in block **2210**. The manufactured transmission system may be built and/or tuned in accordance with one or more of the aforementioned and disclosed embodiments of the transmission antenna **21**, in whole or in part and including any components thereof. The method **2200** also includes building and/or tuning a transmission tuning system for the wireless transmission system, as illustrated in block **2220**. Such building and/or tuning may be

utilized for, but not limited to being utilized for, impedance matching, as discussed in more detail above. The built and/or tuned transmission tuning system may be designed and/or tuned in accordance with one or more of the aforementioned and disclosed embodiments of the transmission tuning system **24**, in whole or in part and, optionally, including any components thereof.

[0170] The method **2200** further includes selecting and/or connecting a power conditioning system for the wireless transmission system, as illustrated in block **2230**. The power conditioning system manufactured may be designed with any of a plurality of power output characteristic considerations, such as, but not limited to, power transfer efficiency, maximizing a transmission gap (e.g., the gap **17**), increasing output voltage to a receiver, mitigating power losses during wireless power transfer, increasing power output without degrading fidelity for data communications, optimizing power output for multiple coils receiving power from a common circuit and/or amplifier, among other contemplated power output characteristic considerations. The power conditioning system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the power conditioning system **40** in whole or in part and, optionally, including any components thereof. Further, at block **2240**, the method **2200** involve determining and/or optimizing a connection, and any associated connection components, between the input power source **12** and the power conditioning system of block **2230**. Such determining may include selecting and implementing protection mechanisms and/or apparatus, selecting and/or implementing voltage protection mechanisms, among other things.

[0171] The method **2200** further includes assembling and/or programing a transmission control system of the wireless transmission system of the method **2000**, as illustrated in block **2250**. The assembled transmission control system may be assembled and/or programmed in accordance with one or more of the aforementioned and disclosed embodiments of the transmission control system **26** in whole or in part and, optionally, including any components thereof. Such components thereof include, but are not limited to including, the sensing system **50**, the driver **41**, the transmission controller **28**, the memory **27**, the communications system **29**, the thermal sensing system **52**, the object sensing system **54**, the receiver sensing system **56**, the other sensor(s) **58**, the gate voltage regulator **43**, the PWM generator **41**, the frequency generator **348**, in whole or in part and, optionally, including any components thereof.

[0172] Returning now to FIG. **22**, at block **2300**, the method **2000** includes manufacturing a wireless receiver system for use in the system **10**. The wireless transmission system manufactured at block **2300** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless receiver system **30** in whole or in part and, optionally, including any components thereof. Block **2300** may be implemented as a method **2300** for manufacturing a wireless receiver system.

[0173] Turning now to FIG. **24** and with continued reference to the method **2000** of FIG. **13**, an example block diagram for the method **2300** for manufacturing a wireless receiver system is illustrated. The wireless receiver system manufactured by the method **2300** may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the wireless receiver system **30** in whole or in part and, optionally, including any components thereof. The method **2300** includes manufacturing a receiver antenna for the wireless receiver system, as illustrated in block **2310**. The manufactured receiver antenna may be manufactured, designed, and/or selected in accordance with one or more of the aforementioned and disclosed embodiments of the receiver antenna **31** in whole or in part and including any components thereof. The method **2300** includes building and/or tuning a receiver tuning system for the wireless receiver system, as illustrated in block **2320**. Such building and/or tuning may be utilized for, but not limited to being utilized for, impedance matching, as discussed in more detail above. The built and/or tuned receiver tuning system may be designed and/or tuned in accordance with one or more of the aforementioned and disclosed embodiments of the receiver tuning and filtering system **34** in whole or in part and, optionally, including any components thereof.

[0174] The method **2300** further includes selecting and/or connecting a power conditioning system for the wireless receiver system, as illustrated in block **2330**. The power conditioning system designed may be designed with any of a plurality of power output characteristic considerations, such as, but not limited to, power transfer efficiency, maximizing a transmission gap (e.g., the gap **17**), increasing output voltage to a receiver, mitigating power losses during wireless power transfer, increasing power output without degrading fidelity for data communications, optimizing power output for multiple coils receiving power from a common circuit and/or amplifier, among other contemplated power output characteristic considerations. The power conditioning system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the power conditioning system **32** in whole or in part and, optionally, including any components thereof. Further, at block **2340**, the method **2300** may involve determining and/or optimizing a connection, and any associated connection components, between the load **16** and the power conditioning system of block **2330**. Such determining may include selecting and implementing protection mechanisms and/or apparatus, selecting and/or implementing voltage protection mechanisms, among other things.

[0175] The method **2300** further includes assembling and/or programing a receiver control system of the wireless receiver system of the method **2300**, as illustrated in block **2350**. The assembled receiver control system may be designed in accordance with one or more of the aforementioned and disclosed embodiments of the receiver control system **36** in whole or in part and, optionally, including any components thereof. Such components thereof include, but are not limited to including, the receiver controller **38**, the memory **37**, and the communications system **39**, in whole or in part and, optionally, including any components thereof.

[0176] Returning now to the method **2000** of FIG. **22**, the method **2000** further includes, at block **2400**, optimizing and/or tuning both the wireless transmission system and the wireless receiver system for wireless power transfer. Such optimizing and/or tuning includes, but is not limited to including, controlling and/or tuning parameters of system components to match impedance, optimize and/or configure voltage and/or power levels of an output power signal, among other things and in accordance with any of the disclosed systems, methods, and apparatus herein. Further, the method **2000** includes optimizing and/or tuning one or both of the wireless transmission system and the wireless receiver system for data communications, in view of system characteristics necessary for wireless power transfer, as illustrated at block **2500**. Such optimizing and/or tuning includes, but is not limited to including, optimizing power characteristics for concurrent transmission of electrical power signals and electrical data signals, tuning quality factors of antennas for different transmission schemes, among other things and in accordance with any of the disclosed systems, methods, and apparatus herein.

[0177] The systems, methods, and apparatus disclosed herein are designed to operate in an efficient, stable and reliable manner to satisfy a variety of operating and environmental conditions. The systems, methods, and/or apparatus disclosed herein are designed to operate in a wide range of thermal and mechanical stress environments so that data and/or electrical energy is transmitted efficiently and with minimal loss. In addition, the system **10**, **110** may be designed with a small form factor using a fabrication technology that allows for scalability, and at a cost that is amenable to developers and adopters. In addition, the systems, methods, and apparatus disclosed herein may be designed to operate over a wide range of frequencies to meet the requirements of a wide range of applications.

[0178] In an embodiment, a ferrite shield may be incorporated within the antenna structure to improve antenna performance. Selection of the ferrite shield material may be dependent on the operating frequency as the complex magnetic permeability ($\mu=\mu'-j*\mu''$) is frequency dependent. The material may be a polymer, a sintered flexible ferrite sheet, a rigid shield, or a hybrid shield, wherein the hybrid shield comprises a rigid portion and a flexible portion. Additionally, the magnetic shield may be composed of varying material compositions. Examples of materials may

include, but are not limited to, zinc comprising ferrite materials such as manganese-zinc, nickel-zinc, copper-zinc, magnesium-zinc, and combinations thereof.

[0179] As used herein, the phrase “at least one of” preceding a series of items, with the term “and” or “or” to separate any of the items, modifies the list as a whole, rather than each member of the list (i.e., each item). The phrase “at least one of” does not require selection of at least one of each item listed; rather, the phrase allows a meaning that includes at least one of any one of the items, and/or at least one of any combination of the items, and/or at least one of each of the items. By way of example, the phrases “at least one of A, B, and C” or “at least one of A, B, or C” each refer to only A, only B, or only C; any combination of A, B, and C; and/or at least one of each of A, B, and C.

[0180] The predicate words “configured to”, “operable to”, and “programmed to” do not imply any particular tangible or intangible modification of a subject, but, rather, are intended to be used interchangeably. In one or more embodiments, a processor configured to monitor and control an operation or a component may also mean the processor being programmed to monitor and control the operation or the processor being operable to monitor and control the operation. Likewise, a processor configured to execute code can be construed as a processor programmed to execute code or operable to execute code.

[0181] A phrase such as “an aspect” does not imply that such aspect is essential to the subject technology or that such aspect applies to all configurations of the subject technology. A disclosure relating to an aspect may apply to all configurations, or one or more configurations. An aspect may provide one or more examples of the disclosure. A phrase such as an “aspect” may refer to one or more aspects and vice versa. A phrase such as an “embodiment” does not imply that such embodiment is essential to the subject technology or that such embodiment applies to all configurations of the subject technology. A disclosure relating to an embodiment may apply to all embodiments, or one or more embodiments. An embodiment may provide one or more examples of the disclosure. A phrase such as an “embodiment” may refer to one or more embodiments and vice versa. A phrase such as a “configuration” does not imply that such configuration is essential to the subject technology or that such configuration applies to all configurations of the subject technology. A disclosure relating to a configuration may apply to all configurations, or one or more configurations. A configuration may provide one or more examples of the disclosure. A phrase such as a “configuration” may refer to one or more configurations and vice versa.

[0182] The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any embodiment described herein as “exemplary” or as an “example” is not necessarily to be construed as preferred or advantageous over other embodiments. Furthermore, to the extent that the term “include,” “have,” or the like is used in the description or the claims, such term is intended to be inclusive in a manner similar to the term “comprise” as “comprise” is interpreted when employed as a transitional word in a claim. Furthermore, to the extent that the term “include,” “have,” or the like is used in the description or the claims, such term is intended to be inclusive in a manner similar to the term “comprise” as “comprise” is interpreted when employed as a transitional word in a claim.

[0183] All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. No claim element is to be construed under the provisions of 35 U.S.C. § 112, sixth paragraph, unless the element is expressly recited using the phrase “means for” or, in the case of a method claim, the element is recited using the phrase “step for.”

[0184] Reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” Unless specifically stated otherwise, the term “some” refers to one or more. Pronouns in the masculine (e.g., his) include the feminine and neuter

gender (e.g., her and its) and vice versa. Headings and subheadings, if any, are used for convenience only and do not limit the subject disclosure.

[0185] While this specification contains many specifics, these should not be construed as limitations on the scope of what may be claimed, but rather as descriptions of particular implementations of the subject matter. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub combination or variation of a sub combination.

Claims

1. A wireless power transmitter comprising: a power conditioning system that (i) receives input power from an input power source, (ii) receives a driving signal that is based on an operating frequency for a wireless power transmission, and (iii) generates alternating current (AC) signals for the wireless power transmission; a first transmitter antenna that (i) is in wired electrical connection with the power conditioning system, (ii) receives the AC signals for the wireless power transmission, and (iii) transmits the wireless power transmission to one or more other transmitter antennas, receiver antennas, or combinations thereof; and a second transmitter antenna that (i) is not in wired electrical connection with the power conditioning system, (ii) receives the wireless power transmission from the first transmitter antenna, and (iii) repeats the wireless power transmission to one or more receiver antennas.
2. The wireless power transmitter of claim 1, further comprising a transmitter housing that houses one or more of the first transmitter antenna, the second transmitter antenna, or combinations thereof.
3. The wireless power transmitter of claim 1, further comprising: a first transmitter tuning system that is in electrical connection with both the power conditioning system and the first transmitter antenna; and a second transmitter tuning system that is (i) in electrical connection with first and second terminals of the second transmitter antenna and (ii) not in electrical connection with the power conditioning system.
4. The wireless power transmitter of claim 3, wherein the first transmitter tuning system is configured to (i) receive the AC wireless signals and (ii) tune the AC wireless signals for transmission as the wireless power transmission via the first transmitter antenna, and wherein the second transmitter tuning system is configured to (i) receive the wireless power transmission and (ii) tune the wireless power transmission for repeating, via the second transmitter antenna, to one or more receiver antennas.
5. The wireless power transmitter of claim 1, wherein the first transmitter antenna comprises: a first antenna portion; and a second antenna portion, and wherein the second transmitter antenna comprises: a third antenna portion; and a fourth antenna portion.
6. The wireless power transmitter of claim 5, wherein the first antenna portion comprises one or more first outer turns, wherein the second antenna portion comprises one or more first inner turns that are radially inward from the one or more first outer turns, wherein the third antenna portion comprises one or more second outer turns, and wherein the fourth antenna portion comprises one or more second inner turns that are radially inward from the one or more second outer turns.
7. The wireless power transmitter of claim 6, wherein the first antenna portion is in wired electrical connection with (i) the second antenna portion and (ii) the power conditioning system, and wherein the third antenna portion is (i) in wireless electrical connection with one or both of the first or

second antenna portions and (ii) is in wired electrical connection with the fourth antenna portion.

8. The wireless power transmitter of claim 5, wherein the first antenna portion includes a first terminal and a second terminal, wherein the second antenna portion includes a third terminal and a fourth terminal, wherein the second terminal is in electrical connection with the third terminal of the second antenna portion, wherein each of the first antenna portion and the second antenna portion is configured to couple with one or more other transmitter antennas, receiver antennas, or combinations thereof, wherein the third antenna portion includes a fifth terminal and a sixth terminal, wherein the fourth antenna portion includes a seventh terminal and an eighth terminal, wherein the sixth terminal of the third antenna portion is in electrical connection with the seventh terminal of the fourth antenna portion, wherein each of the third antenna portion and the fourth antenna portion is configured to couple with one or more receiver antennas.

9. A wireless power transfer system comprising: a wireless power receiver comprising: a receiver antenna; and a rectifier for receiving a wireless power transmission from the receiver antenna and converts the wireless power transmission to usable power for a load associated with wireless power receiver; and a wireless power transmitter comprising: a power conditioning system that (i) receives input power from an input power source, (ii) receives a driving signal that is based on an operating frequency for the wireless power transmission, and (iii) generates alternating current (AC) signals for the wireless power transmission; a first transmitter antenna that (i) is in wired electrical connection with the power conditioning system, (ii) receives the AC signals for the wireless power transmission, and (iii) transmits the wireless power transmission to one or more of a second transmitter antenna, the receiver antenna, or combinations thereof; and the second transmitter antenna that (i) is not in wired electrical connection with the power conditioning system, (ii) receives the wireless power transmission from the first transmitter antenna, and (iii) repeats the wireless power transmission to one or more receiver antennas.

10. The wireless power transfer system of claim 9, wherein the wireless power receiver is configured to (i) electrically connect with a computer peripheral and (ii) provide power to the load associated with the wireless power receiver, and wherein the load is a load of the computer peripheral.

11. The wireless power transfer system of claim 10, wherein the computer peripheral is a computer mouse.

12. The wireless power transfer system of claim 11, wherein one or both of the first or second transmitter antennas are positioned under a surface, upon which the computer mouse is used.

13. The wireless power transfer system of claim 9, further comprising a transmitter housing that houses one or more of the first transmitter antenna, the second transmitter antenna, or combinations thereof.

14. The wireless power transfer system of claim 9, wherein the wireless power transmitter further comprises: a first transmitter tuning system that is in electrical connection with both the power conditioning system and the first transmitter antenna; and a second transmitter tuning system that is (i) in electrical connection with first and second terminals of the second transmitter antenna and (ii) not in electrical connection with the power conditioning system.

15. The wireless power transfer system of claim 14, wherein the first transmitter tuning system is configured to (i) receive the AC wireless signals and (ii) tune the AC wireless signals for transmission as the wireless power transmission via the first transmitter antenna, and wherein the second transmitter tuning system is configured to (i) receive the wireless power transmission and (ii) tune the wireless power transmission for repeating, via the second transmitter antenna, to one or more receiver antennas.

16. An antenna for a wireless power transmitter, the antenna comprising: a first transmitter antenna that (i) is in wired electrical connection with a power conditioning system of the wireless power transmitter, (ii) receives alternating current (AC) signals for a wireless power transmission, and (iii) transmits the wireless power transmission to one or more of other transmitter antennas, receiver

antennas, or combinations thereof; and a second transmitter antenna that (i) is not in wired electrical connection with the power conditioning system, (ii) receives the wireless power transmission from the first transmitter antenna, and (iii) repeats the wireless power transmission to one or more receiver antennas.

17. The antenna of claim 16, wherein the first transmitter antenna comprises: a first antenna portion; and a second antenna portion, and wherein the second transmitter antenna comprises: a third antenna portion; and a fourth antenna portion.

18. The antenna of claim 17, wherein the first antenna portion comprises one or more first outer turns, wherein the second antenna portion comprises one or more first inner turns that are radially inward from the one or more first outer turns, wherein the third antenna portion comprises one or more second outer turns, and wherein the fourth antenna portion comprises one or more second inner turns that are radially inward from the one or more second outer turns.

19. The antenna of claim 18, wherein the first antenna portion is (i) in wired electrical connection with the second antenna portion and (ii) is configured for wired connection electrical connection with the power conditioning system, and wherein the third antenna portion is (i) in wireless electrical connection with one or both of the first or second antenna portions and (ii) is in wired electrical connection with the fourth antenna portion.

20. The antenna of claim 1, further comprising transmitter tuning system that is (i) in electrical connection with first and second terminals of the second transmitter antenna and (ii) not in electrical connection with the power conditioning system.
