

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12385776
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Oda; Hisanori

---

### Windshield for balance

---

#### Abstract

The windshield includes an outer windshield defining a weighing chamber, and an inner windshield disposed inside the outer windshield and covering the weighing pan, the outer windshield includes a pair of left and right sliding doors openable and closable in side surfaces, and the inner windshield is provided with an opening in a surface facing one of the sliding doors, and a shielding wall is provided at a lower portion of the opening. An air flow generated when the sliding door of the outer windshield is opened or closed moves along a floor surface of the outer windshield toward the weighing pan, but is blocked by the shielding wall and does not flow into the inside of the inner windshield.

---

<b>Inventors:</b>	<b>Oda; Hisanori (Saitama, JP)</b>
<b>Applicant:</b>	<b>A&amp;D COMPANY, LIMITED (Tokyo, JP)</b>
<b>Family ID:</b>	<b>1000008752119</b>
<b>Assignee:</b>	<b>A&amp;D COMPANY, LIMITED (Tokyo, JP)</b>
<b>Appl. No.:</b>	<b>18/012197</b>
<b>Filed (or PCT Filed):</b>	<b>July 06, 2020</b>
<b>PCT No.:</b>	<b>PCT/JP2020/026409</b>
<b>PCT Pub. No.:</b>	<b>WO2022/009266</b>
<b>PCT Pub. Date:</b>	<b>January 13, 2022</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230304848 A1	Sep. 28, 2023

---

Publication Classification

Int. Cl.: G01G21/28 (20060101); G01G21/22 (20060101)

U.S. Cl.:

CPC G01G21/286 (20130101); G01G21/22 (20130101);

Field of Classification Search

CPC: G01G (21/286); G01G (21/22)

USPC: 177/181

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9612151	12/2016	Tachibana	N/A	G01G 21/286
10119854	12/2017	Kuhlmann	N/A	G01G 21/286
11002591	12/2020	Buchmann	N/A	G01G 21/23
12140471	12/2023	Oda	N/A	G01G 21/286
12146783	12/2023	Oda	N/A	G01G 21/286
2018/0106665	12/2017	Feldotte et al.	N/A	N/A
2024/0271989	12/2023	Oda	N/A	G01G 21/286

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
S62-179615	12/1986	JP	N/A
H04-221720	12/1991	JP	N/A
H05-62825	12/1992	JP	N/A
05322638	12/1992	JP	N/A
H05-322638	12/1992	JP	N/A
H07-83744	12/1994	JP	N/A
2000-162028	12/1999	JP	N/A
2009-36583	12/2008	JP	N/A
WO-2015074734	12/2014	WO	G01G 21/286

Primary Examiner: Saint Surin; Jacques M

Attorney, Agent or Firm: Studebaker Brackett PLLC

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a windshield to be used for a balance, particularly for a high-resolution balance.

BACKGROUND ART

(2) Conventionally, a balance is provided with a windshield to prevent air flows around a weighing pan, for example, wind from an air conditioner, breath of a person at the time of weighing, air flow generated when a person walks, etc., from acting as a wind pressure on a load-applied portion centered on the weighing pan and adversely influencing weighing. The windshield is provided with an opening and closing door for placing a specimen to be weighed on the weighing pan, and when this opening and closing door is opened and closed, an air flow is generated. This air flow is attenuated as it moves inside the windshield after the opening and closing door is closed, however, in the course of this movement, when the air flow hits the weighing pan, it adversely influences weighing. This adverse influence is particularly pronounced with a high-resolution balance, for example, a balance having a resolution as high as 1/10,000,000.

(3) As a measure to avoid this adverse influence, conventionally, there is known a balance (Patent Literature 1) configured so that, inside the windshield, another windshield is provided to cover the weighing pan. For example, inside an outer windshield formed into a ceilinged cylindrical shape and having an opening in a side wall, a bottomed cylindrical inner windshield is provided which has an opening in a side wall and a bottom plate positioned below the opening and turnably supported by three rollers, and a weighing pan is disposed inside this inner windshield.

#### CITATION LIST

##### Patent Literature

(4) [Patent Literature 1] Japanese Unexamined Patent Application Publication No. H05-322638

#### SUMMARY OF INVENTION

##### Technical Problem

(5) In the balance described in Patent Literature 1, the inner windshield turns without being in contact with the outer windshield, and when the openings of both windshields match, the windshields are made into an open state, and when the openings do not match, the windshields are made into a closed state. Further, the inner windshield turns in a state where the bottom plate is supported by the rollers, and the rollers are thus positioned lower than the opening of the inner windshield, so that dust generated during this turning falls due to its own weight, and does not flow in the direction toward the weighing pan. Further, when there is a down flow flowing downward from above, air that has flowed in from the opening of the outer windshield flows down so as to pass by the rollers through a gap between the outer windshield and the inner windshield, and does not flow in the direction toward the weighing pan.

(6) However, in a case where air flows horizontally, when the windshields are in an open state, air that has flowed into the inside of the inner windshield through the respective openings flows mainly along the bottom plate of the inner windshield in the direction toward the weighing pan. Further, even when the windshields are in a closed state, air that has flowed into the space defined by the respective side walls of the outer windshield and the inner windshield from the opening of the outer windshield flows into the inside of the inner windshield along the bottom plate from the opening of the inner windshield, and flows in the direction toward the weighing pan. As just described, in the balance described in Patent Literature 1, there is a problem in which the inner windshield only functions as a shutter to open and close the opening of the outer windshield, and cannot block inflow of air flowing horizontally toward the inside of the inner windshield, so that air hits the weighing pan, and adverse influence of the air flow during weighing cannot be avoided.

(7) An object of the present invention is to provide a windshield for a balance which solves this problem.

##### Solution to Problem

(8) In order to solve the problem described above, a windshield for a balance according to the present invention includes an outer windshield defining a weighing chamber, and an inner windshield disposed inside the outer windshield and covering a weighing pan, wherein the outer windshield has an openable and closable sliding door in a side surface, and the inner windshield is provided with an opening in a surface facing the sliding door, and a shielding wall is provided at a

lower portion of the opening of the inner windshield.

(9) Since a shielding wall is provided at a lower portion of the opening of the inner windshield, air that has flowed in from an opening portion that is formed by opening the sliding door of the outer windshield moves along a floor surface of the outer windshield toward the inner windshield, but is blocked by the shielding wall and does not flow into the inside of the inner windshield. Moreover, placement of a specimen on a weighing pan before weighing and taking-out of a specimen after weighing can be performed through an opening portion formed in the outer windshield and the opening of the inner windshield.

(10) When an upper end of the shielding wall is set at substantially the same height position as a height position of the weighing pan, inflow of air to the inside of the inner windshield can be reliably blocked, and a sufficient opening area necessary for performing a work to place a specimen on the weighing pan or take out a specimen can be secured.

(11) Further, when the sliding door is provided in each of a pair of side surfaces of the outer windshield, and the inner windshield is provided detachably or rotatably, and is configured to be installed so that the opening of the inner windshield faces the desired one of the sliding doors, a work to place or take out a specimen through the desired side surface of the outer windshield is enabled.

#### Advantageous Effects of Invention

(12) According to the present invention, the windshield is configured as a double structure by being provided with an outer windshield and an inner windshield, and a shielding wall is provided at a lower portion of an opening of the inner windshield, and accordingly, adverse influences of air flows on the weighing pan provided inside the inner windshield are prevented, so that smooth and reliable weighing can be performed, and accurate weighing of a particularly high-resolution balance can be realized.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view illustrating an embodiment of a balance according to the present invention, omitting illustration of the inside of an outer windshield.

(2) FIG. 2 is a side view illustrating a state where a sliding door of an outer windshield is opened.

(3) FIG. 3 is a perspective view, omitting the outer windshield and cylinder boxes.

(4) FIG. 4 is a front view illustrating a height relationship between a shielding wall and a weighing pan, partially omitting the outer windshield and the inner windshield.

### DESCRIPTION OF EMBODIMENT

(5) Hereinafter, a preferred embodiment of the present invention will be described based on the accompanying drawings. For the sake of convenience, the respective accompanying drawings illustrate components of the outer windshield and the inner windshield as components that are not see-through, and illustration of the inside is omitted.

(6) As illustrated in FIGS. 1 to 4, a balance 1 includes a housing 50 in which an electromagnetic balance type or load-cell type mass sensor (illustration omitted) is housed, and a weighing pan 51 which is joined to the mass sensor and on which a specimen is placed. Further, an annular wall 52 is provided so as to surround the weighing pan 51. A windshield 10 is provided on an upper surface of the housing 50. The windshield 10 consists of an outer windshield 11 defining a weighing chamber S, and an inner windshield 21 disposed inside the outer windshield 11 and covering the weighing pan 51. The windshield 10 prevents air flows around a weighing chamber S, for example, wind from an air conditioner, breath of a person at the time of weighing, air flow generated when a person walks, etc., from acting as a wind pressure on a load-applied portion centered on the weighing pan 51 and influencing weighing.

(7) The outer windshield **11** includes a front plate **12**, a pair of left and right sliding doors **13** and **13** for respectively opening and closing side surfaces, an upper surface door **14** for opening and closing an upper surface, and a back plate **16** forming one of the surfaces of a box-shaped case **15** closing a back surface, and defines a weighing chamber **S** having a substantially rectangular parallelepiped shape. The front plate **12**, the pair of sliding doors **13** and **13**, and the upper surface door **14** are preferably made of glass or resin, and transparent so that an internal state can be observed. Further, to prevent generation of static electricity, the glass is preferably a conductive glass having a conductive film provided on the surface, and the resin is desirably a conductive resin with conductivity. Note that the outer windshield **11** may be provided to be attachable to and detachable from the housing **50** by a publicly known attaching and detaching mechanism, or may be fixed to the housing in an undetachable manner.

(8) Next, the pair of left and right sliding doors **13** and **13** will be described. The sliding doors **13** and **13** have the same configuration, so that only one will be described. As illustrated in FIGS. **1** and **2**, the sliding door **13** has a quadrilateral outer frame **13a**, and an upper portion of the outer frame **13a** is slidably supported and suspended by an upper frame **31** and a cylinder box **32** provided along one side portion of the upper surface door **14**. The sliding door **13** is configured to reciprocate by a driving force of an air cylinder (not illustrated) disposed inside the cylinder box **32**. This reciprocation is caused when a lower portion of the outer frame **13a** is guided by a guide rail **34** that is L-shaped in section and formed of a horizontal portion **33a** and a rise portion **33b** of a lower frame **33**. A lower end of the outer frame **13a** of the sliding door **13** is preferably in a non-contact state where the lower end is separated from the horizontal portion **33a** of the lower frame **33**. Note that the sliding door **13** can be reciprocated manually as well as by a driving force of the air cylinder, and for manual movement, a handle **13b** is provided at the front plate **12** side.

(9) As can be best understood in FIG. **1**, the upper surface door **14** is configured to be capable of reciprocal movement in a front-rear direction along guide grooves not illustrated that are provided in the cylinder boxes **32** and **32**. The upper surface door **14** is provided with a handle **14a** at a case **15** side so as to be manually moved.

(10) As illustrated in FIGS. **1** to **4**, on the horizontal portions **33a** of the lower frames **33**, at positions along movement paths of the respective sliding doors **13** and **13**, restricting projections **35** and **35** that restrict displacements of the lower ends of the respective sliding doors **13** and **13** in separating directions from the rise portions **33b** of the lower frames **33**, that is, vertical portions of the guide rails **34** are provided for the sliding doors **13** and **13**, respectively. The shapes of the restricting projections **35** and **35** are octagonal prisms although not clearly illustrated in the figures. The restricting projections **35** and **35** are always at positions where their side surfaces can come into contact with the lower end portions of the corresponding sliding doors **13** and **13** regardless of whether the sliding doors **13** and **13** are in closed states or in open states. These restricting projections **35** and **35** prevent wobbling of lower portions of the sliding doors **13** and **13** that are not in contact with the horizontal portions **33a** of the guide rails **34**, thereby securing smooth movements of the sliding doors **13** and **13**. Further, the restricting projections **35** and **35** are always at positions where they can come into contact with lower end portions of the corresponding sliding doors **13** and **13**, so that the wobbling prevention described above is reliably realized in the entire ranges of the movements of the sliding doors **13** and **13**. Note that the shapes of the restricting projections **35** and **35** may be polygonal prisms other than octagonal prisms, or may be columns.

(11) As illustrated in FIGS. **2** to **4**, the inner windshield **21** includes a front plate **22**, an upper surface plate **23**, side surface plates **24**, a back plate **25**, and an opening **26** formed by opening one of the side surfaces. Respective upper end corner portions of the front plate **22**, the side surface plates **24**, and the back plate **25** are joined and fixed to four corner portions of the upper surface plate **23** by resin-made fixtures **27**, **27**, **27**, and **27**. Respective lower end corner portions of the front plate **22**, the side surface plates **24**, and the back plate **25** are fixed by a resin-made quadrilateral fixing frame **28**. The inner windshield **21** is thus formed in a rectangular

parallelepiped shape having an opening in one surface.

(12) The inner windshield **21** is disposed on an upper surface plate **36** of the lower frame **33** by the fixing frame **28** so that the inner windshield covers the weighing pan **51**, and the opening **26** faces the sliding door **13** of the right side surface, and is detachably attached by a publicly known attaching and detaching mechanism (not illustrated). Therefore, it is also possible that the inner windshield **21** is disposed so that the opening **26** faces the other sliding door **13** (refer to FIG. 2). A portion of the fixing frame **28** positioned corresponding to a lower portion of the opening **26** constitutes a shielding wall **28a**. A height position of an upper end of this shielding wall **28a** is substantially the same as a height position of the weighing pan **51**. Normally, the height position of the upper end of the shielding wall **28a** is the same as or slightly higher than the height position of the weighing pan **51**, which more reliably blocks inflow of air to the inside of the inner windshield **21**. On the other hand, when the height position of the upper end of the shielding wall **28a** is slightly lower than the height position of the weighing pan **51**, the inflow blocking function can be maintained although the reliability decreases. Moreover, in this case, when an aluminum-foil-made, ceramic-made, or platinum-made boat-shaped shallow container called a boat that contains a liquid or powder specimen mainly for element analysis, is picked up with tweezers, moved horizontally, and placed on the weighing pan **51** without spilling the specimen, the work can be easily and reliably performed without being obstructed by the shielding wall **28a**.

(13) Preferably, the front plate **22**, the upper surface plate **23**, the side surface plates **24**, and the back plate **25** of the inner windshield **21** are made of glass or resin, and are transparent so that an internal state can be observed. Further, to prevent generation of static electricity, preferably, the glass is conductive glass having a conductive film provided on the surface, and the resin is a conductive resin with conductivity.

(14) In the configuration described above, when performing weighing, as illustrated in FIG. 2, the sliding door **13** of the right side surface of the outer windshield **11** is opened, and from the opened side surface, a specimen is placed on the weighing pan **51** through the opening **26** of the inner windshield **21**, and the sliding door **13** is then closed to bring the weighing chamber S into a closed state. During this weighing, the weighing chamber S is in the closed state, so that the weighing chamber S is not influenced from the outside.

(15) At the time of weighing of the specimen, when an operation to open and close the sliding door **13** is performed to place the specimen on the weighing pan **51**, air may flow into the inside of the windshield **10** along the upper surface plate **36** of the lower frame **33**. However, even when the air flows from the outer windshield **11** to the inner windshield **21** in the direction toward the weighing pan **51**, the air is blocked by the shielding wall **28a** of the inner windshield **21** and flows along the fixing frame **28** in the direction toward the side surface plates **24**, so that the air does not flow into the inside of the inner windshield **21**, and does not reach the weighing pan **51**. Therefore, with the weighing pan **51** on which the specimen has been placed, accurate weighing is always performed without being influenced by air flows. Even when dust flows in together with the air flow, similar to the air flow, dust does not flow into the inside of the inner windshield **21**.

(16) On the other hand, when it is desired to perform a weighing work by opening the sliding door **13** of the left side surface (refer to FIG. 2), the opening **26** of the inner windshield **21** needs to be arranged to face this sliding door. Therefore, the inner windshield **21** is detached once from the upper surface plate **36**, and the inner windshield **21** is attached to the upper surface plate **36** so that the opening **26** faces the opposite side. Then, the sliding door **13** of the left side surface of the outer windshield **10** is opened, and from the opened side surface, a specimen is placed on the weighing pan **51** through the opening **26** of the inner windshield **21**, and the sliding door **13** is then closed to bring the weighing chamber S into a closed state, and weighing can thus be performed.

(17) It should be noted that the present invention is not limited to the above-described embodiment, and for example, the shapes of the outer windshield **11** and the inner windshield **21** are not limited to rectangular parallelepiped shapes, and may be cylindrical shapes whose upper surfaces are

closed. Further, it is also possible that the outer windshield **11** is formed into a rectangular parallelepiped shape, and the inner windshield **21** is formed into a box body that is U-shaped in a planar view. As with the rectangular parallelepiped shape, this inner windshield **21** formed as a box body that is U-shaped in a planar view is preferred since a sufficient opening can be secured as compared with a cylindrical shape. When the inner windshield **21** is configured to be rotatable, by rotating the inner windshield in a predetermined direction, the opening **26** of the inner windshield **21** can be caused to face the sliding door **13** on a desired side of the outer windshield **11**. This rotatable configuration can be realized by using a conventionally publicly known method.

(18) The annular wall **52** also has a function to block an air flow and accompanying dust from reaching the weighing pan **51**, however, in the present invention, inflow of air to the inside of the inner windshield **21** is blocked by the shielding wall **28a**, so that the annular wall **52** does not necessarily have to be provided.

#### REFERENCE SIGNS LIST

(19) **1** Balance **10** Windshield **11** Outer windshield **12** Front plate **13** Sliding door **14** Upper surface door **16** Back plate **21** Inner windshield **22** Front plate **23** Upper surface plate **24** Side surface plate **25** Back plate **26** Opening **27** Fixture **28** Fixing frame **28a** Shielding wall **34** Guide rail **50** Housing **51** Weighing pan **S** Weighing chamber

## Claims

1. A windshield for a balance, comprising: an outer windshield defining a weighing chamber; and an inner windshield disposed inside the outer windshield and covering a weighing pan, wherein the outer windshield has an openable and closable sliding door in a side surface, and the inner windshield is provided with an opening opened in a surface facing the sliding door, and a shielding wall that blocks inflow of air to the inner windshield is provided at a lower portion of the opening of the inner windshield.
  2. The windshield for a balance according to claim 1, wherein an upper end of the shielding wall is at substantially the same height position as a height position of the weighing pan.
  3. The windshield for a balance according to claim 1, wherein the sliding door is provided in each of a pair of side surfaces of the outer windshield, and the inner windshield is provided detachably, and configured to be installed so that the opening of the inner windshield faces one of the sliding doors.
  4. The windshield for a balance according to claim 2, wherein the sliding door is provided in each of a pair of side surfaces of the outer windshield, and the inner windshield is provided detachably, and configured to be installed so that the opening of the inner windshield faces one of the sliding doors.
  5. The windshield for a balance according to claim 1, wherein the sliding door is provided in each of a pair of side surfaces of the outer windshield, and the inner windshield is provided rotatably, and configured to be installed so that the opening of the inner windshield faces one of the sliding doors.
  6. The windshield for a balance according to claim 2, wherein the sliding door is provided in each of a pair of side surfaces of the outer windshield, and the inner windshield is provided rotatably, and configured to be installed so that the opening of the inner windshield faces one of the sliding doors.
-