

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260205

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

PATIL; Bipin et al.

ELECTRONIC VAPING DEVICE AND CONNECTOR ASSEMBLY

Abstract

A connector assembly of a cartridge of an electronic vaping device may be formed by metal in-molding. The connector assembly may include a connector body that is integrally formed. The connector body may include a base portion that is generally cylindrical, a nose portion extending from a first end of the base portion, and at least two slots extending longitudinally through the base portion and on opposing sides of the nose portion. An electrical lead extends through each of the at least two slots.

Inventors: PATIL; Bipin (Richmond, VA), SUNDBERG; Sean (Richmond, VA), MCKENNA; Kelli (Richmond, VA), SUNDAR; Rangaraj (Richmond, VA), NELSON; Greg (Richmond, VA), BENNETT; David (Richmond, VA)

Applicant: Altria Client Services LLC (Richmond, VA)

Family ID: 1000008563391

Assignee: Altria Client Services LLC (Richmond, VA)

Appl. No.: 19/193295

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 18612194 20240321 parent-grant-document US 12316052 child US 19193295

parent US continuation 17403274 20210816 parent-grant-document US 11962113 child US 18612194

parent US division 15349377 20161111 parent-grant-document US 11245235 child US 17403274

Publication Classification

Int. Cl.: H01R24/38 (20110101); **A24F40/40** (20200101); **A24F40/42** (20200101); **A24F40/46** (20200101); **A24F40/70** (20200101); **A61M15/06** (20060101); **H01R13/03** (20060101); **H05B1/02** (20060101)

U.S. Cl.:

CPC H01R24/38 (20130101); **A24F40/40** (20200101); **A24F40/42** (20200101); **A24F40/46** (20200101); **A24F40/70** (20200101); **A61M15/06** (20130101); **H05B1/0244** (20130101); **H01R13/03** (20130101); **H05B2203/021** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. application Ser. No. 18/612,194, filed Mar. 21, 2024, which is a continuation application of U.S. application Ser. No. 17/403,274 filed on Aug. 16, 2021, which is a divisional application of U.S. application Ser. No. 15/349,377 filed on Nov. 11, 2016, the entire contents of each of which are hereby incorporated by reference.

BACKGROUND

Field

[0002] The present disclosure relates to a connector assembly of an electronic vaping or e-vaping device and methods of forming the connector assembly.

Description of Related Art

[0003] Electronic vaping devices may include a power supply section and a cartridge. The power supply section and the cartridge may be connected by a connector, such as a threaded connector.

SUMMARY

[0004] At least one example embodiment relates to a connector assembly of a cartridge of an electronic vaping device.

[0005] In at least one example embodiment, a connector assembly of a cartridge of an electronic vaping device includes: a first connector body, a second connector body, and at least two electrical leads, each including a first end and a second end. The first connector body includes a first base portion that is generally cylindrical, a nose portion extending from a first end of the first base portion, at least two slots extending longitudinally through the first base portion and on opposing sides of the nose portion; and a first orifice extending longitudinally through the first base portion and the nose portion. The nose portion is generally cylindrical. The nose portion has a smaller diameter than the first base portion. The first end of each of the electrical leads extends through a respective one of the at least two slots. The second connector body includes a second base portion that is generally cylindrical, a tubular portion extending longitudinally from a second end of the second base portion; and a second orifice extending through the second base portion and the tubular portion. The second orifice is configured to receive a portion of the first base portion of the first connector body and the second end of each of the at least two electrical leads, such that the second end of each of the at least two electrical leads abuts an inner surface of the second orifice.

[0006] In at least one example embodiment, the at least two electrical leads are formed of stainless steel. The at least two electrical leads may have a cross-sectional area sufficient to reduce an electrical resistance of the leads.

[0007] In at least one example embodiment, the connector assembly may also include a third slot extending longitudinally through the base portion, a third electrical lead extending through the third slot, a fourth slot extending longitudinally through the base portion, and a fourth electrical lead extending through the fourth slot.

[0008] In at least one example embodiment, each of the first the connector body and the second connector body is formed of at least one polymer.

[0009] In at least one example embodiment, the at least two electrical leads include a generally U-shaped notch at the second end thereof.

[0010] In at least one example embodiment, the connector assembly may also include an air inlet in the second base portion of the second connector body. The air inlet may be in fluid communication with the first orifice in the first connector piece.

[0011] At least one example embodiment relates to a cartridge of an electronic vaping device.

[0012] In at least one example embodiment, a cartridge of an electronic vaping device includes a housing extending in a longitudinal direction, the housing having a first end and a second end, an inner tube coaxially positioned in the housing, a heating element in the housing, and a connector assembly. The connector assembly may include a first connector body, a second connector body, and at least two electrical leads each including a first end and a second end. The first connector body includes a first base portion that is generally cylindrical, a nose portion extending from a first end of the first base portion, at least two slots extending longitudinally through the first base portion and on opposing sides of the nose portion; and a first orifice extending longitudinally through the first base portion and the nose portion. The nose portion is generally cylindrical. The nose portion has a smaller diameter than the first base portion. The first end of each of the electrical leads extends through a respective one of the at least two slots. The second connector body includes a second base portion that is generally cylindrical, a tubular portion extending longitudinally from a second end of the second base portion; and a second orifice extending through the second base portion and the tubular portion. The second orifice is configured to receive a portion of the first base portion of the first connector body and the second end of each of the at least two electrical leads, such that the second end of each of the at least two electrical leads abuts an inner surface of the second orifice.

[0013] In at least one example embodiment, the at least two electrical leads are formed of stainless steel. The at least two electrical leads may have a cross-sectional area sufficient to reduce an electrical resistance of the leads.

[0014] In at least one example embodiment, the connector assembly may also include a third slot extending longitudinally through the base portion, a third electrical lead extending through the third slot, a fourth slot extending longitudinally through the base portion, and a fourth electrical lead extending through the fourth slot.

[0015] In at least one example embodiment, each of the first the connector body and the second connector body is formed of at least one polymer.

[0016] In at least one example embodiment, the at least two electrical leads include a generally U-shaped notch at the second end thereof.

[0017] In at least one example embodiment, the connector assembly may also include an air inlet in the second base portion of the second connector body. The air inlet may be in fluid communication with the first orifice in the first connector piece.

[0018] In at least one example embodiment, the cartridge may also include a microprocessor configured to control temperature of a heater. The microprocessor may be in the housing.

[0019] At least one example embodiment relates to an electronic vaping device.

[0020] In at least one example embodiment, an electronic vaping device includes a cartridge and a power supply section. In at least one example embodiment, the cartridge includes a housing extending in a longitudinal direction, the housing having a first end and a second end, an inner tube coaxially positioned in the housing, a heating element in the housing, and a connector assembly. The connector assembly may include a first connector body, a second connector body, and at least two electrical leads each including a first end and a second end. The first connector body includes a first base portion that is generally cylindrical, a nose portion extending from a first end of the first base portion, at least two slots extending longitudinally through the first base portion and on

opposing sides of the nose portion; and a first orifice extending longitudinally through the first base portion and the nose portion. The nose portion is generally cylindrical. The nose portion has a smaller diameter than the first base portion. The first end of each of the electrical leads extends through a respective one of the at least two slots. The second connector body includes a second base portion that is generally cylindrical, a tubular portion extending longitudinally from a second end of the second base portion; and a second orifice extending through the second base portion and the tubular portion. The second orifice is configured to receive a portion of the first base portion of the first connector body and the second end of each of the at least two electrical leads, such that the second end of each of the at least two electrical leads abuts an inner surface of the second orifice. The power supply section may include a second housing, a battery in the housing, and electrical contacts configured to electrically connect the battery to the heater when the cartridge is connected to the power supply section.

[0021] In at least one example embodiment, the electrical contacts are formed of at least one of copper coated with tin and brass alloys.

[0022] In at least one example embodiment, the electronic vaping device may include a second connector assembly arranged in a first end of the second housing. The second connector assembly may include a generally cup-shaped connector piece and a metal lining, the connector piece and the metal lining configured to receive the tubular portion of the second connector body.

[0023] In at least one example embodiment, the second connector body may include a post extending through a bottom of the connector piece, the electrical leads configured to be received between the metal lining and the post.

[0024] At least one example embodiment relates to a method of making a connector assembly.

[0025] In at least one example embodiment, a method of making a connector assembly of a cartridge of an electronic vaping device may include metal insert molding the connector assembly.

[0026] In at least one example embodiment, the connector assembly may include a first connector body, a second connector body, and at least two electrical leads each including a first end and a second end. The first connector body includes a first base portion that is generally cylindrical, a nose portion extending from a first end of the first base portion, at least two slots extending longitudinally through the first base portion and on opposing sides of the nose portion; and a first orifice extending longitudinally through the first base portion and the nose portion. The nose portion is generally cylindrical. The nose portion has a smaller diameter than the first base portion. The first end of each of the electrical leads extends through a respective one of the at least two slots. The second connector body includes a second base portion that is generally cylindrical, a tubular portion extending longitudinally from a second end of the second base portion; and a second orifice extending through the second base portion and the tubular portion. The second orifice is configured to receive a portion of the first base portion of the first connector body and the second end of each of the at least two electrical leads, such that the second end of each of the at least two electrical leads abuts an inner surface of the second orifice.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] The various features and advantages of the non-limiting embodiments herein may become more apparent upon review of the detailed description in conjunction with the accompanying drawings. The accompanying drawings are merely provided for illustrative purposes and should not be interpreted to limit the scope of the claims. The accompanying drawings are not to be considered as drawn to scale unless explicitly noted. For purposes of clarity, various dimensions of the drawings may have been exaggerated.

[0028] FIG. 1 is a side view of an electronic vaping device including a connector according to at

least one example embodiment.

[0029] FIG. 2 is a cross-sectional view along line II-II of the electronic vaping device and the connector of FIG. 1 according to at least one example embodiment.

[0030] FIG. 3A is an enlarged view of the connector and a portion of the electronic vaping of FIGS. 1 and 2 according to at least one example embodiment.

[0031] FIG. 3B is an enlarged cross-sectional view of the connector and a portion of the electronic vaping device of FIG. 3A with the cross-section rotated 45° with respect to the cross-section in FIG. 3A.

[0032] FIGS. 3C and 3D are enlarged perspective views of the electrical leads of the connector of FIGS. 3A and 3B.

[0033] FIG. 4 is an exploded view of the connector of FIGS. 1-3 according to at least one example embodiment.

[0034] FIG. 5 is a first end view of a second connector body of the connector of FIGS. 1-4 according to at least one example embodiment.

[0035] FIG. 6 is a flow chart illustrating a method of making a first connector assembly according to at least one example embodiment.

[0036] FIG. 7 is a flow chart illustrating the cleaning operation of FIG. 6 according to at least one example embodiment.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

[0037] Some detailed example embodiments are disclosed herein. However, specific structural and functional details disclosed herein are merely representative for purposes of describing example embodiments. Example embodiments may, however, be embodied in many alternate forms and should not be construed as limited to only the example embodiments set forth herein.

[0038] Accordingly, while example embodiments are capable of various modifications and alternative forms, example embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit example embodiments to the particular forms disclosed, but to the contrary, example embodiments are to cover all modifications, equivalents, and alternatives falling within the scope of example embodiments. Like numbers refer to like elements throughout the description of the figures.

[0039] It should be understood that when an element or layer is referred to as being “on,” “connected to,” “coupled to,” or “covering” another element or layer, it may be directly on, connected to, coupled to, or covering the other element or layer or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. Like numbers refer to like elements throughout the specification. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0040] It should be understood that, although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers, and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer, or section from another region, layer, or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from the teachings of example embodiments.

[0041] Spatially relative terms (e.g., “beneath,” “below,” “lower,” “above,” “upper,” and the like) may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It should be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the term “below” may

encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[0042] The terminology used herein is for the purpose of describing various example embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0043] Example embodiments are described herein with reference to cross-sectional illustrations that are schematic illustrations of idealized embodiments (and intermediate structures) of example embodiments. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, example embodiments should not be construed as limited to the shapes of regions illustrated herein but are to include deviations in shapes that result, for example, from manufacturing.

[0044] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which example embodiments belong. It will be further understood that terms, including those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0045] At least one example embodiment relates to an electronic vaping device.

[0046] In at least one example embodiment, as shown in FIG. 1, an electronic vaping device **60** may include a first section (or cartridge) **70** and a second section (or battery section) **72**, which may be coupled together at a connector **74**. The connector **74** may include a first connector assembly **250** (shown in FIG. 3) associated with the first section **70** and a second connector assembly **450** (shown in FIG. 3) associated with the second section. At least some portions of the first connector assembly may be formed by a metal in-molding process as described herein.

[0047] In at least one example embodiment, at least one air inlet **404** may extend through a portion of the connector **74**. In at least one example embodiment, the air inlets **404** may be sized and configured such that the e-vaping device **60** has a resistance-to-draw (RTD) in the range of from about 60 mm H.sub.2O to about 150 mm H.sub.2O.

[0048] In at least one example embodiment, the first section **70** may include a first housing **22'** extending in a longitudinal direction, and the second section **72** may include a second housing **22** extending in the longitudinal direction. The electronic vaping device **60** includes a mouth-end insert **180** at a first end **4**.

[0049] In at least one example embodiment, the first housing **22'** and the second housing **22** may have a generally cylindrical cross-section. In other example embodiments, the housings **22, 22'** may have a generally triangular cross-section along one or more of the first section **70** and the second section **72**. Furthermore, the housings **22, 22'** may have the same or different cross-section shape, or the same or different size. As discussed herein, the housings **22, 22'** may also be referred to as outer or main housings.

[0050] In at least one example embodiment, the electronic vaping device **60** may include an end cap **700** at a second end **10** of the electronic vaping device **60**.

[0051] FIG. 2 is a cross-sectional view along line II-II of the electronic vaping device and connector of FIG. 1 according to at least one example embodiment.

[0052] In at least one example embodiment, as shown in FIG. 2, the electronic vaping device **60** may include a connector **74**, which is shown in greater detail in FIGS. 3-6, which are described

below.

[0053] In at least one example embodiment, as shown in FIG. 2, the first section **70** includes a reservoir **6** configured to store a pre-vapor formulation and a heater **14** that may vaporize the pre-vapor formulation to form a vapor. The e-vaping device **60** may also include the features set forth in U.S. Patent Application Publication No. 2013/0192623 to Tucker et al. filed Jan. 31, 2013 and/or features set forth in U.S. patent application Ser. No. 15/135,930 to Holtz et al. filed Apr. 22, 2016, the entire contents of each of which are incorporated herein by reference thereto. In other example embodiments, the e-vaping device may include the features set forth in U.S. patent application Ser. No. 15/135,923 filed Apr. 22, 2016, and/or U.S. Pat. No. 9,289,014 issued Mar. 22, 2016, the entire contents of each of which is incorporated herein by this reference thereto.

[0054] In at least one example embodiment, the reservoir **6** is established between the first housing **22'** and an inner tube **62** of the first section **70**. The inner tube **62** is positioned coaxially within the first housing **22'**.

[0055] In at least one example embodiment, the reservoir **6** may at least partially surround a central inner passage **21** extending through the inner tube **62**. The heater **14** may extend generally transversely across the inner passage **21** between opposing portions of the reservoir **6**. In some example embodiments, the heater **14** may extend generally parallel to a longitudinal axis of the inner passage **21**.

[0056] In at least one example embodiment, the reservoir **6** may be sized and configured to hold enough pre-vapor formulation such that the electronic vaping device **60** may be configured for vaping for at least about 200 seconds.

[0057] In at least one example embodiment, the pre-vapor formulation may be a material or combination of materials that may be transformed into a vapor. For example, the pre-vapor formulation may be a liquid, solid and/or gel formulation including, but not limited to, water, beads, solvents, active ingredients, ethanol, plant extracts, natural or artificial flavors, tobacco material, and/or vapor formers such as glycerin and propylene glycol. The pre-vapor formulation may include those described in U.S. Patent Application Publication No. 2015/0020823 to Lipowicz et al. filed Jul. 16, 2014 and U.S. Patent Application Publication No. 2015/0313275 to Anderson et al. filed Jan. 21, 2015, the entire contents of each of which is incorporated herein by reference thereto.

[0058] In at least one example embodiment, a storage medium **210** may be in the reservoir **6** between the first housing **22'** and the inner tube **62**. The storage medium **210** is configured to store the pre-vapor formulation therein. The storage medium **210** may include a winding of cotton gauze or other fibrous material about the inner tube **62**.

[0059] In at least one example embodiment, the use of storage medium **210** negates a need for a gasket between the reservoir **6** and the first connector assembly **250**. Gaskets may be formed of silicon or other materials, which may leach flavor from pre-vapor formulations. Thus, the removal of a second gasket from an electronic vaping device **60** aids in maintaining flavor and/or prolonging shelf-life of the pre-vapor formulation stored in the reservoir **6**.

[0060] In at least one example embodiment, the storage medium **210** may be any porous and/or fibrous material that may hold the pre-vapor formulation therein. The storage medium **210** may be a fibrous material including at least one of cotton, polyethylene, polyester, rayon and combinations thereof. The fibers may have a diameter ranging in size from about 6 microns to about 15 microns (e.g., about 8 microns to about 12 microns or about 9 microns to about 11 microns). The storage medium **210** may be a sintered, porous or foamed material. Also, the fibers may be sized to be irrespirable and may have a cross-section which has a Y-shape, cross shape, clover shape or any other suitable shape.

[0061] In at least one example embodiment, as shown in FIG. 2, the first section **70** also includes the heating element **14** that may vaporize the pre-vapor formulation, which may be drawn from the reservoir **6** by a wick **28**. Ends of the heating element **14** and the wick **28** may extend through holes

or slots in the inner tube **62**, and into the reservoir **6**.

[0062] In at least one example embodiment, as shown in FIG. 2, a gasket **11** is fitted into a first end portion **81** of the inner tube **62** so as to reduce leakage from the reservoir via the first end **4** of the electronic vaping device **60**. The gasket **11** includes a nose portion **93** that may be fitted into the first end portion **81** of the inner tube **62**. An outer perimeter of the gasket **11** provides a substantially liquid-tight seal with an interior surface **97** of the first housing **22'**. The gasket **11** includes a central channel **163** disposed between the inner passage **21** of the inner tube **62** and the mouth-end insert **180**, which may transport the vapor from the inner passage **21** to the mouth-end insert **180**.

[0063] During vaping, pre-vapor formulation is transferred from the reservoir **6** to the proximity of the heating element **14** by the wick **28**. The wick **28** may include a first end portion and a second end portion, which may extend into opposite sides of the reservoir **6**. The heating element **14** may at least partially surround a central portion of the wick **28** such that when the heating element **14** is activated, the pre-vapor formulation in the central portion of the wick **28** is vaporized by the heating element **14** to form a vapor.

[0064] In at least one example embodiment, the wick **28** includes filaments (or threads) having a capacity to draw the pre-vapor formulation. For example, the wick **28** may be a bundle of glass (or ceramic) filaments, a bundle including a group of windings of glass filaments, etc., all of which arrangements may be capable of drawing pre-vapor formulation via capillary action by interstitial spacings between the filaments. The filaments may be generally aligned in a direction perpendicular (transverse) to the longitudinal direction of the electronic vaping device **60**. In at least one example embodiment, the wick **28** may include one to eight filament strands, each strand comprising a plurality of glass filaments twisted together. The end portions of the wick **28** may be flexible and foldable into the confines of the reservoir **6**. The filaments may have a cross-section that is generally cross-shaped, clover-shaped, Y-shaped, or in any other suitable shape.

[0065] In at least one example embodiment, the wick **28** may include any suitable material or combination of materials. Examples of suitable materials may be, but not limited to, glass, ceramic- or graphite-based materials. The wick **28** may have any suitable capillarity drawing action to accommodate pre-vapor formulations having different physical properties such as density, viscosity, surface tension and vapor pressure.

[0066] In at least one example embodiment, as shown in FIG. 2, the heating element **14** may include a wire coil which at least partially surrounds the wick **28**. The wire may be a metal wire and/or the heating element coil may extend fully or partially along the length of the wick **28**. The heating element coil may further extend fully or partially around the circumference of the wick **28**. In some example embodiments, the heating element coil **14** may or may not be in contact with the wick **28**.

[0067] The heating element **14** may be formed of any suitable electrically resistive materials. Examples of suitable electrically resistive materials may include, but not limited to, titanium, zirconium, tantalum and metals from the platinum group. Examples of suitable metal alloys include, but not limited to, stainless steel, nickel, cobalt, chromium, aluminum-titanium-zirconium, hafnium, niobium, molybdenum, tantalum, tungsten, tin, gallium, manganese and iron-containing alloys, and super-alloys based on nickel, iron, cobalt, stainless steel. For example, the heating element **14** may be formed of nickel aluminide, a material with a layer of alumina on the surface, iron aluminide and other composite materials, the electrically resistive material may optionally be embedded in, encapsulated or coated with an insulating material or vice-versa, depending on the kinetics of energy transfer and the external physicochemical properties required. The heating element **14** may include at least one material selected from the group consisting of stainless steel, copper, copper alloys, nickel-chromium alloys, super alloys and combinations thereof. In an example embodiment, the heating element **14** may be formed of nickel-chromium alloys or iron-chromium alloys. In another example embodiment, the heating element **14** may be a ceramic

heating element having an electrically resistive layer on an outside surface thereof.

[0068] In at least one example embodiment, the heating element **14** may heat pre-vapor formulation in the wick **28** by thermal conduction. Alternatively, heat from the heating element **14** may be conducted to the pre-vapor formulation by means of a heat conductive element or the heating element **14** may transfer heat to the incoming ambient air that is drawn through the electronic vaping device **60** during vaping, which in turn heats the pre-vapor formulation by convection.

[0069] In at least one example embodiment, as shown in FIG. 3A, electrical leads **325**, **327** may extend from the heating element **14** and through the reservoir **6**. The electrical leads **325**, **327** may be welded to ends of the heating element **14** or attached to ends of the heating element **14** by crimping. In other example embodiments, the electrical leads **325**, **327** may include a notch and/or be sized and configured to receive and hold ends of the heating element **14** in place without the need for welding and/or crimping. Thus, when the first section **70** first connector assembly **250** is connected with the second connector assembly **400** of the second section **72**, an electrical connection may be formed between the power supply **1** in the second section **72** and the heating element **14** in the first section **70** as described herein. In at least one example embodiment, the electrical leads **325**, **327** may be integrally formed with the heating element **14**.

[0070] In at least one example embodiment, the electrical leads **325**, **327** may be formed of copper or stainless steel. Stainless steel may be used to reduce reactions with the pre-vapor formulation when the electrical leads **325**, **327** pass through the reservoir **6** or are otherwise in contact with the pre-vapor formulation.

[0071] It should be appreciated that, instead of using a wick **28**, the heating element **14** may be a porous material which incorporates a resistance heating element formed of a material having a high electrical resistance capable of generating heat quickly.

[0072] In at least one example embodiment, the mouth-end insert **180** may be received in the first housing **22'** at the first end **4**. The mouth-end insert **180** may include two or more outlets **9**, which may be diverging outlets. The outlets **9** may be angled outwardly in relation to the longitudinal axis of the electronic vaping device **60**. The outlets **9** may be substantially uniformly distributed about the perimeter of an end surface of the mouth-end insert **8**.

[0073] In at least one example embodiment, as shown in FIG. 2, the second section **72** includes a power supply **1**, a control circuit **212**, and a sensor **16** configured to sense negative pressure and/or air being drawn into the electronic vaping device **60**.

[0074] In at least one example embodiment, the power supply **1** includes a battery arranged in the electronic vaping device **60**. The battery may be a Lithium-ion battery or one of its variants, for example a Lithium-ion polymer battery. Alternatively, the battery may be a nickel-metal hydride battery, a nickel cadmium battery, a lithium-manganese battery, a lithium-cobalt battery or a fuel cell. The electronic vaping device **60** may be vapable by an adult vaper until the energy in the power supply **1** is depleted or in the case of lithium polymer battery, a minimum voltage cut-off level is achieved.

[0075] In at least one example embodiment, the power supply **1** may be rechargeable and may include circuitry configured to allow the battery to be chargeable by an external charging device. To recharge the electronic vaping device **60**, an USB charger or other suitable charger assembly may be used.

[0076] In at least one example embodiment, the sensor **16** is configured to generate an output indicative of a magnitude and direction of airflow in the electronic vaping device **60**. The control circuit **212** receives the output of the sensor **16**, and determines if (1) the direction of the airflow indicates a draw on the mouth-end insert **180** (versus blowing) and (2) the magnitude of the draw exceeds a threshold level. If these vaping conditions are met, the control circuit **212** electrically connects the power supply **1** to the heating element **14**; thus, activating the heating element **14**. Namely, the control circuit **12** electrically connects to the first and second leads **325**, **327** (e.g., by

activating a heating element power control transistor forming part of the control circuit **212**) such that the heating element **14** becomes electrically connected to the power supply **1**. In an alternative embodiment, the sensor **16** may indicate a pressure drop, and the control circuit **212** activates the heating element **14** in response thereto.

[0077] In at least one example embodiment, the control circuit **212** may also include a light **48**, which the control circuit **212** activates to glow when the heating element **14** is activated and/or the battery **1** is recharged. The light **48** may include one or more light-emitting diodes (LEDs). The LEDs may include one or more colors (e.g., white, yellow, red, green, blue, etc.). Moreover, the light **48** may be arranged to be visible to an adult vaper during vaping, and may be positioned between the first end **4** and the second end **10** of the electronic vaping device **60**. In addition, the light **48** may be utilized for e-vaping system diagnostics or to indicate that recharging is in progress. The light **48** may also be configured such that the adult vaper may activate and/or deactivate the activation light **48** for privacy.

[0078] In at least one example embodiment, the control circuit **212** may include a time-period limiter. In another example embodiment, the control circuit **12** may include a manually operable switch for an adult vaper to initiate heating. The time-period of the electric current supply to the heating element **14** may be set or pre-set depending on the amount of pre-vapor formulation desired to be vaporized.

[0079] Next, operation of the electronic vaping device **60** to create a vapor will be described. For example, air is drawn primarily into the first section **70** through the at least one air inlet **404** in response to a draw on the mouth-end insert **180**. The air passes through the air inlet **404**, into the central channel **21** of inner tube **62**, and through the outlet **9** of the mouth-end insert **180**. If the control circuit **212** detects the vaping conditions discussed above, the control circuit **212** initiates power supply to the heating element **14**, such that the heating element **14** heats pre-vapor formulation in the wick **28**. The vapor and air flowing through the inner passage **21** combine and exit the electronic vaping device **60** via the outlet **9** of the mouth-end insert **180**.

[0080] When activated, the heating element **14** may heat a portion of the wick **28** for less than about 10 seconds.

[0081] In at least one example embodiment, the first section **70** may be replaceable. In other words, once the pre-vapor formulation of the cartridge is depleted, only the first section **70** may be replaced. An alternate arrangement may include an example embodiment where the entire electronic vaping device **60** may be disposed once the reservoir **6** is depleted. In at least one example embodiment, the electronic vaping device **60** may be a one-piece e-vaping device having a single outer housing.

[0082] In at least one example embodiment, the electronic vaping device **60** may be about 80 mm to about 110 mm long and about 7 mm to about 8 mm in diameter. For example, in one example embodiment, the electronic vaping device **60** may be about 84 mm long and may have a diameter of about 7.8 mm.

[0083] FIG. 3A is an enlarged view of the connector and a portion of the electronic vaping of FIGS. 1 and 2 according to at least one example embodiment.

[0084] In at least one example embodiment, as shown in FIG. 3A, the connector **74** includes a first connector assembly **250** and a second connector assembly **450**. The first connector assembly **250** is arranged in the first section **70** and the second connector assembly **450** is arranged in the second section **72**. The first connector assembly **250** is removably connectable to the second connector assembly **450** to join the first section **70** with the second section **72**.

[0085] In at least one example embodiment, the first connector assembly **250** includes a first connector body **300** and a second connector body **400**.

[0086] In at least one example embodiment, as shown in FIG. 3A, the first connector body **300** includes a first base portion **305** and a nose portion **310** extending from the first base portion **305**. The nose portion **310** may be sized and configured to fit snugly within a second end of an inner

tube **62**. A first orifice **320** extends through the first base portion **305** and the nose portion **310** of the first connector body **300**. The first orifice **320** establishes a flow passage **145** through which air may flow. The flow passage **145** is in fluid communication with the central air passage **21** in the inner tube **62**.

[0087] In at least one example embodiment, the first orifice **320** has an inner diameter ranging from about 1.40 mm to about 1.80 mm (e.g., about 1.45 mm to about 1.75 mm or about 1.50 mm to about 1.70 mm). For example, the inner diameter may be about 1.60 mm, and the inner diameter may aid in establishing a desired resistance-to-draw (RTD) ranging from about 90 mm H.sub.2O to about 120 mm H.sub.2O. The inner diameter of the first orifice **320** may be altered to adjust the RTD of the electronic vaping device **60**.

[0088] In at least one example embodiment, the second connector body **400** includes a second base portion **405** and a tubular portion **410**.

[0089] In at least one example embodiment, the tubular portion **410** extends longitudinally from the second base portion **405** towards the second end **10** of the electronic vaping device **60**. A second orifice **415** extends through the tubular portion **410** and the second base portion **405**. The second orifice **415** may have a generally cylindrical cross-section. The second connector body **400** is generally T-shaped when viewed from a side.

[0090] In at least one example embodiment, the first base portion **305** of the first connector body **300** includes a collar portion **303** extending from the first base portion **305** in the longitudinal direction towards the second end **10** of the electronic vaping device **60**. The collar portion **303** may be generally cylindrical and may have a smaller outer diameter than the first base portion **305**. The collar portion **303** may be received within the second base portion **405** of the second connector body **400**, such that the second base portion **405** abuts the larger portion of the first base portion **305**.

[0091] In at least one example embodiment, the second base portion **405** may have an outer diameter that is substantially the same as an outer diameter of the first housing **22'**, and an inner diameter that is substantially the same as an outer diameter of the portion of the first base portion **305** that is received in the second base portion **405**.

[0092] In at least one example embodiment, the electrical leads **325**, **327** extend through the slots **315** in the first base portion **305** such that one of the electrical leads **325**, **327** is on each side of the nose portion **310** of the first connector body **300**. A first end of each of the electrical leads **325**, **327** is configured to contact and/or attach to opposing ends of the heating element **14**. A second end of each of the electrical leads **325**, **327** may be received in the tubular portion **410** of the second connector body **400**. The electrical leads **325**, **327** may be biased so that the second end of each of the electrical leads **325**, **327** abuts an inner surface of the tubular portion **410**. Central portions of the electrical leads **325**, **327** are in-molded within the first connector body **300**, such that the electrical lead **325** is electrically insulated from the electrical lead **327**. The slots **315** may vary in shape, such that the leads **325**, **327** extend longitudinally and transversely through the first connector body **300**.

[0093] The at least two electrical leads **325**, **327** may be formed of stainless steel. The stainless steel may be subjected to a passivation treatment and/or may be coated with a chemical vapor deposited poly (p-xylylene) polymer coating, such as a Parylene coating, which is a chemical vapor deposited poly (p-xylylene) polymer. The electrical leads **325**, **327** pass through the first connector body **300** and have portions extending therefrom. The electrical lead **325** has a longer portion extending from the first connector body **300** than the electrical lead **327**.

[0094] In at least one example embodiment, the first connector body **300** and the second connector body **400** may be formed of a polymer. The polymer may include at least one of: cyclic olefin copolymer, such as TOPAS® 6013M-07, cyclo-olefin polymer, such as Zeon Chemical ZEONEX® 480R (Pharma Grade), copolyester, such as Eastman Tritan MX731, Eastman Tritan Tx1501HF (FDA Grade), Eastman Tritan Tx1501HF with colorant/UV additive package, or Eastman Tritan

TX2001 (FDA Grade), high density polyethylene, polycarbonate, such as Bayer Makrolon® 2858, or polypropylene.

[0095] In at least one example embodiment, as shown in FIG. 3A, the first base portion **305** is generally cylindrical. In at least one example embodiment, the first base portion **305** has an outer diameter that is substantially the same as or less than an inner diameter of the first housing **22'**, such that the first base portion **305** aids in sealing the reservoir **6** established between the first housing **22'** and the inner tube **62** without the need for an additional gasket, adhesive, or seal. The first base portion **305** may be held within the first housing **22'** by friction fit.

[0096] In at least one example embodiment, when the first connector assembly **250** is arranged in the first section **70**, the second connector body **400** abuts an edge of the first housing **22'** and the tubular portion **410** of the second connector body **400** extends from the second end of the first housing **22'**.

[0097] In at least one example embodiment, the second connector assembly **450** is arranged in the second section **72**. The second connector assembly **450** may include a connector piece **460** that is generally cup-shaped. A lining **470** may be arranged on an inner surface of the connector piece **460**. The lining **470** may be formed of metal. A post **480** may extend through a bottom portion of the connector piece **460**. The post **480** is sized and configured to be received in the tubular portion **410** of the second connector body **400** of the first connector assembly **250**. The connector piece **460** has an inner diameter that is about the same or larger than an outer diameter of the tubular portion **410**, such that the tubular portion **410** is held within the connector piece **460** by friction fit. A pin **610** extends from the post **480** and through the connector piece **460**.

[0098] In at least one example embodiment, additional electrical leads may also extend through the first connector assembly **250** so as to establish a connection between the power supply **1** and a microprocessor **800** (shown in FIG. 2) arranged in the first section **70**. For example, the electronic vaping device **60** may include three contacts, which are configured to contact a conductive cylinder **620**, the lining **407**, and the post **480**.

[0099] When the first connector assembly **250** and the second connector assembly **450** are joined, the electrical lead **325** contacts the conductive cylinder **620** that circumscribes the post **480** and the electrical lead **327** contacts the post **480** to establish an electrical connection between the heater **14** in the first section **70** and the a power supply **1** in the second section **72**.

[0100] In at least one example embodiment, as shown in FIG. 3A, electrically conductive tabs **510** extend from the conductive cylinder **620**, through the connector piece **460**, and into the second section **72**.

[0101] As shown in FIG. 3A, when the first connector assembly **250** is attached to the first section **70**, at least a portion of the second base portion **405** and the tubular portion **410** protrude from the second end of the first housing **22'**. In at least one example embodiment, the second connector assembly **450**, when inserted in the outer housing **22** of the second section **72**, may be flush with an edge of the second housing **22**.

[0102] FIG. 3B is an enlarged cross-sectional view of the connector and a portion of the electronic vaping device of FIG. 3A with the cross-section rotated 45° with respect to the cross-section in FIG. 3A.

[0103] In at least one example embodiment, as shown in FIG. 3B, the connector is the same as in FIG. 3A, but is shown including at least one air inlet **404** that extends through the second base portion **405** in a direction that is substantially transverse to the longitudinal direction. The at least one air inlet **404** is in fluid communication with the flow passage **145**.

[0104] Referring to FIGS. 2, 3A, and 3B, as shown, a first lead **720** electrically connects the electrically conductive tab **510** to the control circuit **212**. A second lead **730** electrically connects the control circuit **212** to a first terminal **113** of the power supply **1**. A third lead **725** electrically connects a second terminal **114** of the power supply **1** to the power terminal of the control circuit **212** to provide power to the control circuit **212**. The second terminal **114** of the power supply **1** is

also physically and electrically connected to the conductive pin **610**. The conductive pin **610** may be formed of a conductive material (e.g., stainless steel, copper, etc). The conductive pin **610** nests within the insulator **630**, and is electrically insulated from the conductive cylinder **620**. When the first and second connector assemblies **250**, **450** are mated, the lead **327** physically and electrically connects to the pin **610** via the lead portion **327'**, which contacts the post **480** (and lead portion **327''**, shown in FIG. 4). The lead **325** physically and electrically connects to the cylinder **620** and tab **510** via the lead portions **325'**, **325''**.

[0105] FIGS. 3C and 3D are enlarged perspective views of the electrical leads of the connector of FIGS. 3A and 3B.

[0106] In at least one example embodiment, as shown in FIG. 3C, the electrical lead **327** includes a first straight portion **327a**, a first perpendicular portion **327b**, a second perpendicular portion **327c**, a second straight portion **327d**, and a third straight portion **327e**. The perpendicular portions **327b**, **327c** are in molded within the first connector body **300**. The first straight portion **327a** extends out of the first connector body **300** opposite the second straight portion **327d** and the third straight portion **327e**. The second straight portion **327d** is positioned about 180° from the third straight portion **327e**.

[0107] In other example embodiments, the electrical lead **327** may have other configurations including at least a portion that is in molded within the first connector body **300**.

[0108] In at least one example embodiment, as shown in FIG. 3D, the electrical lead **325** includes a first straight portion **325a**, a perpendicular portion **325b**, and two leg portions **325c**, **325d**. The perpendicular portion **325b** is in molded within the first connector body **300**. The first straight portion and the two leg portions extend from the first connector body **300**. The first straight portion extends out of a first end of the first connector body **300**, while the two leg portions extend from a second end of the first connector body **300**.

[0109] In other example embodiments, the electrical lead **325** may have other configurations including at least a portion that is in molded within the first connector body **300**.

[0110] FIG. 4 is an exploded view of the connector of FIGS. 1-3B according to at least one example embodiment.

[0111] In at least one example embodiment, as shown in FIG. 4, the first connector assembly **250** and the second connector assembly **450** are the same as in FIGS. 1-3B. As shown in FIG. 4, the electrical lead **325** includes two portions **325'**, **325''**, and the electrical lead **327** includes two portions **327'**, **327''**. The portions **325'**, **325''** are longer than the portions **327'**, **327''**. In other example embodiments, the electrical lead **325** may include only one portion **325'** and/or the electrical lead **327** may include only one portion **327'**. More than one portion **325'**, **327'** may be used to provide greater structural stability between the first connector body **300** and the second connector body **400**. The lead portions **325'**, **325''**, **327'**, **327''** may be substantially uniformly spaced about the first connector body **300** or non-uniformly spaced.

[0112] FIG. 5 is a first end view of a second connector body of the connector of FIGS. 1-4 according to at least one example embodiment.

[0113] In at least one example embodiment, as shown in FIG. 5, the second connector body **400** is the same as in FIGS. 1-4. As shown in FIG. 5, the second orifice **415** may have a generally cross-shaped cross-section such that each of the electrical lead portions **325'**, **325''**, **327'**, **327''** may be held within respective arms of the cross-shaped second orifice **415**.

[0114] FIG. 6 is a flow chart illustrating a method of making a first connector assembly according to at least one example embodiment.

[0115] In at least one example embodiment, as shown in FIG. 6, a method of making the first and/or second connector assembly may include metal in-molding **S500** electrical leads in a connector body. The electrical leads may be formed of stainless steel. The electrical leads and/or the connector assembly may be cleaned **S550** before or after the in-molding operation. Following the cleaning **S550**, the leads and/or other metal components may undergo a passivation operation

S560. The passivation operation **S560** may occur after the cleaning operation **S550**, but before the metal in-molding operation **S500** if desired.

[0116] In at least one example embodiment, as shown in FIG. 6, after in-molding, the electrical leads may be subjected to a cleaning and/or passivation operation to improve corrosion resistance of the post.

[0117] In at least one example embodiment, the passivation operation **S650** may include a nitric acid treatment according to ASTM A 967 as set forth in Table 1 below.

TABLE-US-00001 TABLE 1 Solution Time Temperature 20-25% nitric acid and about 20 minutes 120° F. to 130° F. 2.5% sodium dichromate 20-40% nitric acid about 30 minutes 70° F. to 90° F. 20-25% nitric acid about 20 minutes 120° F. to 140° F. 45-55% nitric acid about 30 minutes 120° F. to 130° F.

[0118] In at least one example embodiment, the passivation operation **S650** may include a citric acid treatment according to ASTM A967 as set forth in Table 2 below.

TABLE-US-00002 TABLE 2 Solution Time Temperature 4-10% citric acid about 4 minutes 140° F. to 160° F. 4-10% citric acid about 10 minutes 120° F. to 140° F. 4-1% citric acid about 20 minutes 70° F. to 120° F.

[0119] FIG. 7 is a flow chart illustrating the cleaning operation of FIG. 6 according to at least one example embodiment.

[0120] In at least one example embodiment, as shown in FIG. 7, the cleaning operation **S560** may include a pre-cleaning operation **S570**, which may include cleaning the post with a solution and/or scrubbing the leads. The pre-cleaning may be done so that any passivation operations are uniformly applied to the leads. The pre-cleaning operation **S570** may include any suitable cleaning process including an alkaline process, an emulsion process, a vapor degreasing process, an ultrasonic process, a detergent process, a chelate solution process, a mechanical process including one or more of abrasive blast, grinding, and/or wire brushing, a steam process, and/or a water jet process.

[0121] In at least one example embodiment, the cleaning operation **S560** may include acid pickling and/or a mechanical descaling process. The cleaning operation **S560** may also include acid cleaning to remove iron, light oxide films, and/or dirt from the post. Once the cleaning operation **S560** is complete, the leads may be inspected **S600**.

[0122] In at least one example embodiment, is a descaling operation **S580** and/or pickling process is performed, the process may be that described in ASTM A 380 Table A1, Part 1 titled “Acid Descaling.” Before pickling, the surface must be pre-cleaned. Then, the descaling solution for an annealed austenitic stainless steel may be applied. The descaling solution may include about 8% to about 11% sulfuric acid. The descaling solution may be applied for about 5 minutes to about 45 minutes at a temperature of about 150° F. to about 180° F. Alternatively, the descaling solution may include about 15 to about 25% nitric acid and about 1 to about 8% hydrofluoric acid. This descaling solution may be applied to the post for about 5 minutes to about 30 minutes at a temperature ranging from about 70° F. to about 140° F. After the descaling and/or pickling process, the leads may be brushed with hot water and/or a high-pressure water jet until the wash water has a pH ranging from about 6 to about 8. Surfaces of the leads should then be inspected to ensure proper cleaning.

[0123] In at least one example embodiment, if the leads are formed of annealed 300 series stainless steel, the cleaning operation **S560** may include acid cleaning, and the leads may be cleaned with a nitric-hydrofluoric acid according to ASTM A 380 Table A2, Part I: Cleaning with Nitric-hydrofluoric acid. The cleaning solution may include a solution including 6 to 25% nitric acid and 0.5 to 8% hydrofluoric acid. The cleaning may be done at a temperature ranging from about 70° F. to about 140° F. The acid cleaning may be done for as long as necessary to clean the leads.

[0124] In another example embodiment, the cleaning operation **S560** of leads formed of an annealed, cold roller, thermally hardened, or work hardened 300 series stainless steel may include acid cleaning according to ASTM A 380 Table A2.1 Part II: Cleaning-passivation with Nitric Acid,

which includes cleaning and passivation with nitric acid. A solution of 20% to 30% nitric acid is applied to the leads at a temperature of about 120° F. to about 160° F. for about 10 minutes to about 30 minutes. If a surface of the leads are shiny, the process may include applying a solution of about 20% to about 40% nitric acid and about 2% to about 6% sodium dichromate to the leads at a temperature of about 120° F. to about 160° F. for about 10 minutes to about 30 minutes.

[0125] In another example embodiment, if the leads are formed of 200 or 300 series stainless steel, the cleaning operation S560 may include acid cleaning according to ASTM A 380 Table A2.1 Part III: Cleaning with other chemical solutions. A solution of 1% citric acid and 1% sodium nitrate may be applied at about 70° F. for about 60 minutes. Alternatively, a solution of about 5% to about 10% ammonium citrate may be applied at a temperature ranging from about 120° F. to about 160° F. for about 10 minutes to about 60 minutes. In another embodiment, an inhibited ammonia-neutralized solution of ethylenediaminetetraacetic acid (EDTA) at a temperature of up to about 250° F. at a temperature of about 6 hours followed by hot water rinse.

[0126] In at least one example embodiment, following any of the acid washes, the surface of the leads should be rinsed until the rinse water has a pH ranging from about 6 to about 8.

[0127] While a number of example embodiments have been disclosed herein, it should be understood that other variations may be possible. Such variations are not to be regarded as a departure from the spirit and scope of the present disclosure, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

Claims

1. A connector assembly of a cartridge of an electronic vaping device, the connector assembly comprising: a first connector body including, a first base defining a first orifice, the first orifice extending longitudinally through the first base; and at least two electrical leads each including a first end and a second end, the first end of each of the at least two electrical leads extending through the first base, at least a portion of the at least two electrical leads are in-molded within the first connector body; and a second connector body including, a second base defining a second orifice, the second orifice extending longitudinally through the second base, the second orifice configured to receive a portion of the first base of the first connector body and the second end of each of the at least two electrical leads such that the second end of each of the at least two electrical leads each abuts an inner surface of the second orifice.
2. The connector assembly of claim 1, wherein the at least two electrical leads are formed of stainless steel.
3. The connector assembly of claim 1, wherein the at least two electrical leads include a first electrical lead and a second electrical lead, and a distance between a furthest portion of the second end of the first electrical lead and the first base is greater than a distance between a furthest portion of the second end of the second electrical lead and the first base.
4. The connector assembly of claim 1, wherein the at least two electrical leads each include a perpendicular portion.
5. The connector assembly of claim 4, wherein the perpendicular portion is in-molded within the first base.
6. The connector assembly of claim 4, wherein the at least two electrical leads each includes a first electrical lead and a second electrical lead, the perpendicular portion of the first electrical lead is between the first end and the second end of the first electrical lead, and the perpendicular portion of the second electrical lead is between the first end and the second end of the second electrical lead.
7. The connector assembly of claim 6, wherein the second end of the second electrical lead is closer to the first orifice than the second end of the first electrical lead.
8. The connector assembly of claim 6, wherein the first electrical lead includes a first straight

portion extending in a longitudinal direction and a second straight portion extending in the longitudinal direction, the first straight portion and the second straight portion are spaced apart in a direction perpendicular to the longitudinal direction, and the second electrical lead includes a third straight portion extending the longitudinal direction and a fourth straight portion extending in the longitudinal direction, the third straight portion and the fourth straight portion are spaced apart in a direction perpendicular to the longitudinal direction.

9. The connector assembly of claim 8, wherein the first straight portion is oriented at a 180° angle about the first orifice relative to the second straight portion.

10. The connector assembly of claim 8, wherein the first straight portion is oriented at a 90° angle about the first orifice relative to the third straight portion.

11. The connector assembly of claim 10, wherein the first end of the first electrical lead is orientated at a 180° angle about the first orifice relative to the first end of the second electrical lead.

12. The connector assembly of claim 8, wherein the third straight portion is oriented at a 90° angle about the first orifice relative to the first end of the second electrical lead.

13. The connector assembly of claim 1, wherein a side wall of the second base defines an air inlet in fluid communication with the first orifice.

14. The connector assembly of claim 1, wherein the first connector body and the second connector body are formed of at least one polymer.

15. The connector assembly of claim 1, further comprising: a connector piece having a cup-shape surrounding the second connector body, a neck portion of the connector piece extending through the second orifice, the connector piece defining a third orifice that is longitudinally aligned with the second orifice of the second connector body.

16. The connector assembly of claim 15, further comprising: a metal liner between an outer surface of the of the second connector body and the connector piece.

17. The connector assembly of claim 15, wherein the connector piece further includes a conductive cylinder surrounding the neck portion of the connector piece, the conductive cylinder configured to contact the second end of one of the at least two electrical leads.

18. The connector assembly of claim 17, wherein the connector piece defines one or more fourth orifices surrounding the third orifice, and the conductive cylinder extends through at least one of the one or more fourth orifices.

19. The connector assembly of claim 15, wherein the connector piece further includes a conductive post extending through the third orifice.

20. The connector assembly of claim 1, wherein the at least two electrical leads include a generally U-shaped notch at the second end.
