# SAFETY DATA SHEET



LYSOL® Disinfectant Spray - Brand New Day™ Coconut Water & Sea Minerals

# 1. Product and company identification

Product name : LYSOL® Disinfectant Spray - Brand New Day™

Coconut Water & Sea Minerals

**Distributed by** : Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

Emergency telephone

number (Medical)

: 1-800-338-6167

Emergency telephone number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website: : http://www.rbnainfo.com

Product use : Disinfectant. spray

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

**SDS** # : D8375964 v2.0 **Formulation** # : 3138417 v1.0

**EPA ID No.** : 777-99

Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Consumer use

# 2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 2 GASES UNDER PRESSURE - Compressed gas

EYE IRRITATION - Category 2B

**GHS label elements** 

Hazard pictograms





Code # : 3138417 D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 1/14

### 2. Hazards identification

Signal word

: Warning

**Hazard statements** 

: Flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eve irritation.

**Precautionary statements** 

**General** 

: Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

**Prevention** 

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.

Response

: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Call a POISON CENTER or physician if you feel unwell.

**Storage** 

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

: Dispose of contents and container in accordance with all local regulations.

Disposal

: None known

Supplemental label

elements

: None known

**Hazards not otherwise** 

classified

: None known.

# 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
ethanol	≥30 - ≤60	64-17-5
butane	≥5 - ≤10	106-97-8
propane	>1 - <5	74-98-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. If irritation persists, get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Code # : 3138417\_D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 2/14

### 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes eye irritation.

Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact** : No specific data. Ingestion : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** 

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

### 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: Flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

3/14 Code # : 3138417 D8375964 SDS# : D8375964 v2.0 Date of issue : 05/05/2020

### 5. Fire-fighting measures

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

sulfur oxides

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible. absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Code # : 3138417 D8375964 SDS# : D8375964 v2.0 **Date of issue** : 05/05/2020 4/14

## 7. Handling and storage

### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**Exposure limits** 

# 8. Exposure controls/personal protection

#### **Control**

#### Occupational exposure limits

Ingredient name

mg. carone name	
ethanol	ACGIH TLV (United States, 3/2018).
	STEL: 1000 ppm 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m <sup>3</sup> 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 1000 ppm 10 hours.
	TWA: 1900 mg/m <sup>3</sup> 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 1000 ppm 8 hours.
	TWA: 1900 mg/m³ 8 hours.
butane	OSHA PEL 1989 (United States, 3/1989).
	TWA: 800 ppm 8 hours.
	TWA: 1900 mg/m <sup>3</sup> 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 800 ppm 10 hours.
	TWA: 1900 mg/m <sup>3</sup> 10 hours.
	ACGIH TLV (United States, 6/2013).
	STEL: 1000 ppm 15 minutes.
propane	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1800 mg/m <sup>3</sup> 8 hours.
	TWA: 1000 ppm 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 1000 ppm 10 hours.
	TWA: 1800 mg/m <sup>3</sup> 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 1000 ppm 8 hours.
	TWA: 1800 mg/m <sup>3</sup> 8 hours.
	ACGIH TLV (United States, 3/2018). Oxygen Depletion [Asphyxiant].
Code # · 3138417 D8375964 SDS # · D8375964	v2.0 Date of issue : 05/05/2020 5/14

Code # : 3138417 D8375964 : D8375964 v2.0 **Date of issue** : 05/05/2020 5/14

# 8. Exposure controls/personal protection

# Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. [Aerosol.]
Color : Water white

Odor : Fragrant.
Odor threshold : Not available.
pH : 10.5 to 11.8
Melting point : Not available.

Code # : 3138417\_D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 6/14

# 9. Physical and chemical properties

**Boiling point** : Not available.

Flash point Closed cup: 25.6°C (78.1°F)

**Evaporation rate** Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available.

**Relative density** 8.0

**Solubility** : Not available. Partition coefficient: n-: Not available.

octanol/water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available. : Not available. **Viscosity** 

**Aerosol product** 

Type of aerosol : Spray **Heat of combustion** : 18.7 kJ/g

# 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

**Hazardous decomposition** : Under normal conditions of storage and use, hazardous decomposition products should products

not be produced.

## 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m³ 7 g/kg	4 hours
butane Lysol Disinfectant Spray D8375964 (US)	LC50 Inhalation Vapor LC50 Inhalation Vapor	Rat Rat - Male, Female	658000 mg/m³ >2.75 mg/l	4 hours 6 hours
Opray_20070904 (US)	LD50 Dermal LD50 Oral	Rat - Male Rat - Male	>5050 mg/kg >5050 mg/kg	-

**Conclusion/Summary** 

: Not classified. \* Information is based on toxicity test result of a similar product.

Irritation/Corrosion

7/14 Code # : 3138417 D8375964 SDS# : D8375964 v2.0 Date of issue : 05/05/2020

# 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Moderate irritant	Rabbit	-	0.06666667 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Lysol Disinfectant Spray D8375964 (US)	Eyes - Mild irritant	Rabbit	-	-	21 days
, ,_ , ,	Skin - Primary dermal irritation index (PDII)	Rabbit	0	-	21 days

#### **Conclusion/Summary**

Skin : Non irritant. \* Information is based on toxicity test result of a similar product.

**Eyes** : Mild eye irritant. \* Information is based on toxicity test result of a similar product.

**Respiratory**: Based on available data, the classification criteria are not met.

#### **Sensitization**

3	Route of exposure	Species	Result
Lysol Disinfectant Spray_D8375964 (US)	skin	Mouse	Not sensitizing

#### **Conclusion/Summary**

**Skin**: Not sensitizer.\* Information is based on toxicity test result of a similar product.

**Respiratory**: Based on available data, the classification criteria are not met.

### **Mutagenicity**

Not available.

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

#### Carcinogenicity

Not available.

#### **Conclusion/Summary**

: Based on available data, the classification criteria are not met.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
ethanol	-	1	-

#### **Reproductive toxicity**

Not available.

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

**Teratogenicity** 

Not available.

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

Code # : 3138417\_D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 8/14

### 11. Toxicological information

### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely

Potential acute health effects

routes of exposure

: Not available.

**Eye contact** : Causes eye irritation.

Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> irritation watering redness

: Adverse symptoms may include the following: Inhalation

respiratory tract irritation

coughing

: No specific data. Skin contact : No specific data. Ingestion

### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. : No known significant effects or critical hazards. **Teratogenicity Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

9/14 Code # : 3138417 D8375964 SDS# : D8375964 v2.0 Date of issue : 05/05/2020

# 11. Toxicological information

#### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	( 3	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
ethanol	7000	N/A	N/A	124.7	N/A
butane	N/A	N/A	N/A	658	N/A

# 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 μg/l Fresh water Acute LC50 25500 μg/l Marine water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae	96 hours 48 hours 48 hours
	Acute LC50 11000000 µg/l Marine water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 100 ul/L Fresh water	Fish - Alburnus alburnus Algae - Ulva pertusa Daphnia - Daphnia magna - Neonate	96 hours 96 hours 21 days

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

#### Persistence and degradability

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low
butane	2.89	-	low
propane	1.09	-	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Code # : 3138417\_D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 10/14

# 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

# 14. Transport information

	TDG Classification	DOT Classification	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1	2.1
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

**Additional information** 

**DOT Classification**  Limited Quantity **TDG Classification** : Limited Quantity **IMDG** : Limited Quantity **IATA** : See DG list

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not available.

# 15. Regulatory information

U.S. Federal regulations : Clean Air Act (CAA) 112 regulated flammable substances: butane; propane

Clean Air Act Section 112

: Not listed

(b) Hazardous Air **Pollutants (HAPs)** 

Clean Air Act Section 602 : Not listed

**Class I Substances** 

Code # : 3138417 D8375964 SDS# : D8375964 v2.0 **Date of issue** : 05/05/2020 11/14

# 15. Regulatory information

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

SARA 304 RQ : not available

**SARA 311/312** 

Classification : FLAMMABLE AEROSOLS - Category 2

GASES UNDER PRESSURE - Compressed gas

EYE IRRITATION - Category 2B

### Composition/information on ingredients

Name	%	Classification
ethanol		FLAMMABLE LIQUIDS - Category 2
butane	≥5 - ≤10	EYE IRRITATION - Category 2A FLAMMABLE GASES - Category 1
propane	<1 - ≤5	GASES UNDER PRESSURE - Compressed gas FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Compressed gas

**State regulations** 

Massachusetts : The following components are listed: ETHYL ALCOHOL; DENATURED ALCOHOL;

**BUTANE**; PROPANE

**New York**: None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE;

**PROPANE** 

Pennsylvania: The following components are listed: DENATURED ALCOHOL; ETHANOL; BUTANE;

**PROPANE** 

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

**Label elements** 

**EPA** 

Signal word: : CAUTION

Hazard statements : FLAMMABLE AEROSOL.

Contents under pressure.
Causes moderate eye irritation.

No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Special Inert substance. : Precautionary measures :

Keep out of the reach of children. Do not spray in eyes, on skin or on clothing.

Code # : 3138417 D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 12/14

### 15. Regulatory information

Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Keep away from heat, sparks and open flame.

Do not puncture or incinerate container.

Exposure to temperatures above 130°F may cause bursting.

**Skin sensitizer** : No known significant effects or critical hazards.

Hazard statements :



Flammable

#### **Additional information / Recommendations**

Additional information : Store in original container in areas inaccessible to small children. Do not reuse empty

container. Do Not Puncture or Incinerate! (Replace cap and) Discard in trash or offer for

recycling if available.

Recommendations : No known significant effects or critical hazards.

Recommendations : No known significant effects or critical hazards.

### 16. Other information

#### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**National Fire Protection Association (U.S.A.)** 



#### NFPA (30B) aerosol Flammability 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Code # : 3138417\_D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 13/14

### 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations : ATE

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

Date of issue : 05/05/2020 Date of previous issue : 21/04/2020

Version : 2

Prepared by : Reckitt Benckiser India Ltd

Plot No 48 Sector - 32 Institutional Area Gurgaon, Haryana India - 122001

✓ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.

Code # : 3138417\_D8375964 SDS # : D8375964 v2.0 Date of issue : 05/05/2020 14/14