according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN SOF Number 60022

1. PRODUCT AND COMPANY IDENTIFICATION

**Product information** 

Product name : KIWI® CAMP DRY FABRIC PROTECTOR

**Recommended use** : Shoe Polish

**Restrictions on use** : Use only as directed on label

Manufacturer, importer,

supplier

: S.C. Johnson & Son, Inc.

1525 Howe Street

Racine WI 53403-2236

**Telephone** : +1-800-558-5252

**Emergency telephone** 

number

: 24 Hour Medical Emergency Phone: (866)231-5406 24 Hour International Emergency Phone: (703)527-3887

24 Hour Transport Emergency Phone: (800)424-9300

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Aerosol	Category 1	Extremely flammable aerosol.
Specific target organ toxicity - single exposure	Category 3	May cause drowsiness or dizziness.
Gases under pressure	Liquefied gas	Contains gas under pressure; may explode if heated.

#### Labelling

**Hazard symbols** 

Flame

**Exclamation mark** 

Signal word

Danger

according to Hazard Communication Standard; 29 CFR 1910.1200



## KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN SOF Number 60022

#### Hazard statements

Extremely flammable aerosol.

May cause drowsiness or dizziness.

#### **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Call a POISON CENTER/doctor if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Dispose of contents/ container to an approved incineration plant.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing spray.

Use only outdoors or in a well-ventilated area.

Other hazards : Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

Excessive exposure to spray mist, fog or vapour may cause

respiratory irritation.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Naphtha (petroleum), hydrotreated light	64742-49-0	60.00 - 100.00
Butane	106-97-8	10.00 - 30.00
Propane	74-98-6	5.00 - 10.00
N-Butyl acetate	123-86-4	1.00 - 5.00
Isobutane	75-28-5	1.00 - 5.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

according to Hazard Communication Standard; 29 CFR 1910.1200



## KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736

GEN\_SOF Number 60022

#### 4. FIRST AID MEASURES

#### **Description of first aid measures**

**Eye contact** : No special requirements

**Skin contact** : No special requirements

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER or doctor/physician if

you feel unwell.

**Ingestion** : No special requirements

## Most important symptoms and effects, both acute and delayed

Eyes : May irritate eyes.

Skin effect : No adverse effects expected when used as directed.

Inhalation : Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Excessive exposure to spray mist, fog or vapour may cause

respiratory irritation.

Ingestion : May cause irritation to mouth, throat and stomach.

May cause abdominal discomfort.

No adverse effects expected when used as directed.

#### Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

#### **5. FIREFIGHTING MEASURES**

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

according to Hazard Communication Standard; 29 CFR 1910.1200



## KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736

GEN\_SOF Number 60022

Specific hazards during

firefighting

Do not use a solid water stream as it may scatter and spread

fire. Aerosol Product - Containers may rocket or explode in

heat of fire.

**Further information** : Fight fire from maximum distance or protected area. Cool and

use caution when approaching or handling fire-exposed containers. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or

explosion do not breathe fumes.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Remove all sources of ignition.

Wash thoroughly after handling.

Environmental

precautions

: Outside of normal use, avoid release to the environment.

Methods and materials

for containment and

cleaning up

: If damage occurs to aerosol can:

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13). Use only non-sparking equipment.

Dike large spills.

Clean residue from spill site.

#### 7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Avoid contact with skin, eyes and clothing. For personal protection see section 8.

Use only as directed.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Pressurized container.

Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

**Advice on protection** : Keep away from sources of ignition - No smoking.

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN\_SOF Number 60022

against fire and explosion Do not spray on an open flame or other ignition source.

**Storage** 

Requirements for storage : areas and containers

Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/ 122 °F.

Keep in a dry, cool and well-ventilated place.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Occupational Exposure Limits**

Components	CAS-No.	mg/m3	ppm	Non- standard units	Basis
Butane	106-97-8	-	1,000 ppm	-	ACGIH STEL
Propane	74-98-6	1,800 mg/m3	1,000 ppm	-	OSHA TWA
Propane	74-98-6	-	-	-	ACGIH TWA
N-Butyl acetate	123-86-4	710 mg/m3	150 ppm	-	OSHA TWA
N-Butyl acetate	123-86-4	-	150 ppm	-	ACGIH STEL
N-Butyl acetate	123-86-4	-	50 ppm	-	ACGIH TWA
Isobutane	75-28-5	-	1,000 ppm	-	ACGIH STEL

Personal protective equipment

Respiratory protection : No special requirements.

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736

GEN\_SOF Number 60022

**Hand protection** : No special requirements.

**Eye protection** : No special requirements.

**Skin and body protection** : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : aerosol

Color : transparent

Odour : solvent-like

Odour Threshold : Test not applicable for this product type

**pH** : Test not applicable for this product type

**Melting point/freezing point**: Test not applicable for this product type

Initial boiling point and

boiling range

: Test not applicable for this product type

Flash point : -5.2 °C

22.64 °F

Method: Tag Closed Cup (TCC)

liquid -104.4 °C -155.92 °F Propellant -60 °C -76 °F Propellant

**Evaporation rate** : Test not applicable for this product type

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

SDS Number 350000032736 Revision Date 02/22/2018 GEN SOF Number 60022

Flammability (solid, gas) : Sustains combustion

explosive limits

**Upper/lower flammability or**: Test not applicable for this product type

Vapour pressure : Test not applicable for this product type

Vapour density : Test not applicable for this product type

Relative density : 0.699 g/cm3 at 25 °C

Solubility(ies) : insoluble

Partition coefficient: n-

octanol/water

: Test not applicable for this product type

Auto-ignition temperature : not auto-flammable

**Decomposition temperature**: Test not applicable for this product type

Viscosity, dynamic : Test not applicable for this product type

Viscosity, kinematic : Test not applicable for this product type

Oxidizing properties : Test not applicable for this product type

Volatile Organic : 97.6 % Compounds

- additional exemptions may apply \*as defined by US Federal and State Consumer Product

Total VOC (wt. %)\* Regulations

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN\_SOF Number 60022

Other information : None identified

10. STABILITY AND REACTIVITY

**Reactivity** : No dangerous reaction known under conditions of normal use.

**Chemical stability** : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

**Conditions to avoid** : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Thermal decomposition can lead to release of irritating gases

and vapours.

## 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 > 5000 mg/kg
Acute inhalation toxicity : LC50 > 10 mg/L

Acute dermal toxicity : LD50 2158 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN\_SOF Number 60022

Skin irritation	No classification proposed	-
Serious eye damage/eye irritation	No classification proposed	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	Category 3	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical

: None known.

Condition

## 12. ECOLOGICAL INFORMATION

**Product**: The product itself has not been tested.

## **Toxicity**

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

# Toxicity to fish

Components	End point	Species	Value	Exposure time
Naphtha (petroleum), hydrotreated light	LC50	Oncorhynchus mykiss (rainbow trout)	> 13.4 mg/l	96 h

according to Hazard Communication Standard; 29 CFR 1910.1200



# **KIWI® CAMP DRY FABRIC PROTECTOR**

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736

GEN\_SOF Number 60022

	NOELR	Pimephales promelas (fathead minnow)	2.6 mg/l	14 d
Butane	LC50 QSAR	Fish	27.98 mg/l	96 h
Propane	LC50	Fish	27.98 mg/l	96 h
N-Butyl acetate	flow- through test LC50	Pimephales promelas (fathead minnow)	18 mg/l	96 h
Isobutane	LC50 QSAR	Fish	27.98 mg/l	96 h

# Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Naphtha (petroleum), hydrotreated light	EC50	Daphnia magna (Water flea)	3 mg/l	48 h
	NOELR	Daphnia magna	2.6 mg/l	21 d
Butane	No data available			
Propane	LC50	Daphnid	14.22 mg/l	48 h
N-Butyl acetate	static test EC50	Daphnia (water flea)	44 mg/l	48 h

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN\_SOF Number 60022

NOEC Read-across (Analogy)

LC50 QSAR

Daphnia magna

23 mg/l

21 d

21 d

16.33 mg/l

48 h

## Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Naphtha (petroleum), hydrotreated light	EC50	Pseudokirchneriella subcapitata (green algae)	10 - 30 mg/l	72 h
Butane	EC50 QSAR	Green algae	7.71 mg/l	96 h
Propane	No data available			
N-Butyl acetate	static test EC50	Desmodesmus subspicatus (green algae)	674.7 mg/l	72 h
Isobutane	EC50 QSAR	Green algae	8.57 mg/l	96 h

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Naphtha (petroleum), hydrotreated light	No data available		Not readily biodegradable.
Butane	100 %	385.5 h	Readily biodegradable.
Propane	70 %	< 10 d	Readily biodegradable.
N-Butyl acetate	83 %	28 d	Readily biodegradable.
Isobutane	70 %	< 10 d	Readily biodegradable.

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN\_SOF Number 60022

## **Bioaccumulative potential**

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Naphtha (petroleum), hydrotreated light	No data available	No data available
Butane	No data available	2.89
Propane	No data available	2.36
N-Butyl acetate	No data available	2.3
Isobutane	1.57 - 1.97	2.8

## **Mobility**

Component	End point	Value
Naphtha (petroleum), hydrotreated light	log Koc	> 1.783 - < 2.36
Butane	No data available	
Propane	No data available	
N-Butyl acetate	No data available	
Isobutane	No data available	

#### PBT and vPvB assessment

Component	Results
Butane	Not fulfilling PBT and vPvB criteria
Propane	Not fulfilling PBT and vPvB criteria
N-Butyl acetate	Not fulfilling PBT and vPvB criteria
Isobutane	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

## 13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736

GEN\_SOF Number 60022

#### 14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

	Land transport	Sea transport	Air transport
UN number	1950	1950	1950
UN proper	AEROSOLS,	AEROSOLS,	AEROSOLS,
shipping name	Flammable	Flammable	Flammable
Transport hazard class(es)	2.1	2	2.1
Packing group	-	-	-
Environmental hazards	-	-	-
Special precautions for user	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Product not transported as bulk.	Product not transported as bulk.	Product not transported as bulk.

#### 15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

Notification status : All ingredients of this product comply with the New Substances

Notification requirements under the Canadian Environmental

Protection Act (CEPA).

according to Hazard Communication Standard; 29 CFR 1910.1200



# KIWI® CAMP DRY FABRIC PROTECTOR

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736 GEN SOF Number 60022

California Prop. 65 : This product is not subject to the reporting requirements under California's Proposition 65.

#### **16. OTHER INFORMATION**

#### **HMIS Ratings**

Health	1	
Flammability	4	
Reactivity	0	
NFPA Ratings		

Health	1	
Fire	4	
Reactivity	0	
Special	-	

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

#### **Further information**

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment &
	Regulatory Affairs (GSARA)

according to Hazard Communication Standard; 29 CFR 1910.1200



# **KIWI® CAMP DRY FABRIC PROTECTOR**

Version 2.0 Print Date 05/23/2018

Revision Date 02/22/2018 SDS Number 350000032736

GEN\_SOF Number 60022