according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product information** 

Product name : GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

**Recommended use** : Air Freshener

Manufacturer, importer, : S.C. Johnson & Son, Inc.

**supplier** 1525 Howe Street

Racine WI 53403-2236

**Telephone** : +18005585252

**Emergency telephone** : 24 Hour Medical Emergency Phone: (866)231-5406

**number** 24 Hour International Emergency Phone: (703)527-3887 24 Hour Transport Emergency Phone: (800)424-9300

## 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Flammable liquids	Category 4	Combustible liquid.

## Labelling

## **Hazard statements**

Combustible liquid.

#### **Precautionary statements**

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Store in a well-ventilated place. Keep cool.

Dispose of contents/ container to an approved incineration plant. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Wear protective gloves.

Other hazards : None identified

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Weight percent
Fragrance - Trade Secret	Mixture	60.00 - 100.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

#### 4. FIRST AID MEASURES

**Eye contact** : No special requirements

**Skin contact** : No special requirements

**Inhalation** : No special requirements.

**Ingestion** : No special requirements

## **5. FIREFIGHTING MEASURES**

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during

firefighting

: Flammable liquid. Vapors are heavier than air and may travel to a source of ignition and flash back. Liquid run-off to sewers

may create fire/explosion hazard. Do not use a solid water stream as it may scatter and spread fire. Container may melt

and leak in heat of fire.

**Further information** : Cool and use caution when approaching or handling fire-

exposed containers. For large quantities of flammable liquids, consider containment to prevent the spread of fire. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not

breathe fumes.

2/10

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions Remove all sources of ignition.

> Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Wear personal protective equipment. Wash thoroughly after handling.

**Environmental** precautions

Outside of normal use, avoid release to the environment.

Methods and materials for containment and

cleaning up

: Use only non-sparking equipment.

Dike large spills.

Clean residue from spill site.

#### 7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Avoid contact with skin, eyes and clothing. For personal protection see section 8.

Use only as directed.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Advice on protection against fire and explosion Keep away from sources of ignition - No smoking.

Storage

Requirements for storage :

areas and containers

Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Other data : Stable at normal ambient temperature and pressure.

Stable at normal ambient temperature and pressure.

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Occupational Exposure Limits**

ACGIH or OSHA exposure limits have not been established for this product or reportable ingredients unless noted in the table above.

#### Personal protective equipment

**Respiratory protection** : No special requirements.

**Hand protection** : No special requirements.

**Eye protection** : Safety glasses with side-shields

**Skin and body protection** : No special requirements.

**Hygiene measures** : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid

Color : light yellow

Odor : Herbal

Odour Threshold : Test not applicable for this product type

**pH** : Test not applicable for this product type

**Melting point/freezing point**: Test not applicable for this product type

Initial boiling point and

boiling range

: Test not applicable for this product type

Flash point : 81 °C

4/10

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

177.8 °F

Method: Tag Closed Cup (TCC)

**Evaporation rate** : Test not applicable for this product type

Flammability (solid, gas) : Sustains combustion

explosive limits

**Upper/lower flammability or** : Test not applicable for this product type

: 0.7346 hPa Vapour pressure

at 20 °C

Vapour density : Test not applicable for this product type

Relative density : 0.9970 g/cm3 at 25 °C

Solubility(ies) : negligible

Partition coefficient: n-

octanol/water

: Test not applicable for this product type

Auto-ignition temperature : not auto-flammable

**Decomposition temperature** : Test not applicable for this product type

Viscosity, dynamic : Test not applicable for this product type

Viscosity, kinematic : Test not applicable for this product type

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992

GEN\_SOF Number 54200

Oxidizing properties : Test not applicable for this product type

Volatile Organic : 92.7 % - additional exemptions may apply
Compounds \*as defined by US Federal and State Consumer Product

Total VOC (wt. %)\* Regulations

Other information : None identified :

#### 10. STABILITY AND REACTIVITY

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

**Conditions to avoid** : Heat, flames and sparks.

**Incompatible materials** : Strong oxidizing agents

Hazardous decomposition

products

: Thermal decomposition can lead to release of irritating gases

and vapours.

#### 11. TOXICOLOGICAL INFORMATION

**Emergency Overview** : Warning

Acute oral toxicity : No data available Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	-
Skin corrosion/irritation	No classification proposed	-
Serious eye damage/eye irritation	No classification proposed	-

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical

Condition

: None known.

## 12. ECOLOGICAL INFORMATION

**Product :** The product itself has not been tested.

#### **Toxicity**

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

## Toxicity to fish

Components	End point	Species	Value	Exposure time
Fragrance - Trade Secret	No data available			

#### Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure
				time

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1	Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

Fragrance - Trade Secret	No data available		

## Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Fragrance - Trade Secret	No data available			

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Fragrance - Trade Secret	No data available		

## Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)	
Fragrance - Trade Secret	No data available	No data available	

## **Mobility**

Component	End point	Value
Fragrance - Trade Secret	No data available	

#### PBT and vPvB assessment

Component	Results
Fragrance - Trade Secret	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

## 13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

where facilities exist.

#### 14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

#### Land transport

Not classified as dangerous in the meaning of transport regulations.

#### Sea transport

Not classified as dangerous in the meaning of transport regulations.

#### Air transport

Not classified as dangerous in the meaning of transport regulations.

#### 15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

#### **16. OTHER INFORMATION**

**HMIS Ratings** 

rimio itatings	
Health	2
Flammability	2
Reactivity	0

according to Hazard Communication Standard; 29 CFR 1910.1200



# GLADE® PLUG-INS® SCENTED OIL (ARUBA WAVE™)

Version 1.1 Print Date 04/07/2015

Revision Date 04/07/2015 SDS Number 350000023992 GEN\_SOF Number 54200

**NFPA Ratings** 

Health	2	
Fire	2	
Reactivity	0	
Special	-	

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

## **Further information**

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment &
	Regulatory Affairs (GSARA)