according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : PLEDGE® FLOOR GLOSS - ORIGINAL

Recommended use : Floor Polish/Cleaner

Manufacturer, importer,

supplier

: S.C. Johnson & Son, Inc.

1525 Howe Street

Racine WI 53403-2236

Telephone : +18005585252

Emergency telephone

number

24 Hour Medical Emergency Phone: (866)231-5406 24 Hour International Emergency Phone: (703)527-3887

24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

This product does not meet the criteria for classification in any hazard class according to regulation OSHA 29 CFR 1910.1200.

Labelling

Precautionary statements

Other hazards : None identified

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS-No. | Weight percent |
|--|------------|----------------|
| Diethylene glycol monoethyl ether | 111-90-0 | 1.00 - 5.00 |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | 52831-04-6 | 1.00 - 5.00 |
| Tributyoxyethyl phosphate | 78-51-3 | 1.00 - 5.00 |

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

Hydrogen Peroxide 7722-84-1 0.10 - 1.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Eye contact : No special requirements

Skin contact : No special requirements

Inhalation : No special requirements.

Ingestion : No special requirements

5. FIREFIGHTING MEASURES

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during

firefighting

: Container may melt and leak in heat of fire.

Further information : Fight fire with normal precautions from a reasonable distance.

Standard procedure for chemical fires. Wear full protective clothing and positive pressure self-contained breathing

apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wash thoroughly after handling.

Environmental precautions

: Outside of normal use, avoid release to the environment.

Methods and materials

for containment and

cleaning up

: Dike large spills.

Clean residue from spill site.

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Avoid contact with skin, eyes and clothing. For personal protection see section 8.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Advice on protection

against fire and explosion

: Normal measures for preventive fire protection.

Storage

Requirements for storage

areas and containers

: Keep container closed when not in use.

Other data : Stable under normal conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

| Components | CAS-No. | mg/m3 | ppm | Non- standard units | Basis |
|-------------------|-----------|-----------|-------|---------------------------|--------------|
| Hydrogen Peroxide | 7722-84-1 | 1.4 mg/m3 | 1 ppm | - | OSHA TWA |
| Hydrogen Peroxide | 7722-84-1 | - | 1 ppm | - | ACGIH TWA |

Personal protective equipment

Respiratory protection : No special requirements.

Hand protection : No special requirements.

Eye protection : No special requirements.

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid

Color clear transparent

Odor : pleasant

Odour Threshold : No data available

: 8.7 рΗ

Melting point/freezing point : No data available

Initial boiling point and

boiling range

: > 93 °C

Flash point : does not flash

Evaporation rate : No data available

Flammability (solid, gas) : The product is not flammable.

Upper/lower flammability or : No data available

explosive limits

Vapour pressure : No data available

Vapour density : No data available

Relative density : 1.026 g/cm3

Solubility(ies) : No data available

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Print Date 05/22/2018 Version 1.1

Revision Date 02/25/2015 SDS Number 350000003597

Partition coefficient: n-

octanol/water

: No data available

: No data available Auto-ignition temperature

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

: No data available Oxidizing properties

Volatile Organic

Compounds

Total VOC (wt. %)*

: 0.3 % - additional exemptions may apply

*as defined by US Federal and State Consumer Product

Regulations

Other information : None identified

10. STABILITY AND REACTIVITY

Possibility of hazardous

reactions

: If accidental mixing occurs and toxic gas is formed, exit area

immediately. Do not return until well ventilated.

Conditions to avoid : Direct sources of heat.

Incompatible materials : Do not mix with bleach or any other household cleaners.

Strong bases

Hazardous decomposition : Thermal decomposition can lead to release of irritating gases

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

products and vapours.

11. TOXICOLOGICAL INFORMATION

Emergency Overview : This product does not meet the criteria for classification in any

hazard class according to regulation OSHA 29 CFR

1910.1200.

Acute oral toxicity : LD50

estimated > 5,000 mg/kg

Acute inhalation toxicity : No data available

Acute dermal toxicity : LD50

estimated > 2,000 mg/kg

| GHS Properties | Classification | Routes of entry |
|--|----------------------------|-----------------|
| Acute toxicity | No classification proposed | - |
| Skin corrosion/irritation | No classification proposed | - |
| Serious eye damage/eye irritation | No classification proposed | - |
| Skin sensitisation | No classification proposed | - |
| Respiratory sensitisation | No classification proposed | - |
| Germ cell mutagenicity | No classification proposed | - |
| Carcinogenicity | No classification proposed | - |
| Reproductive toxicity | No classification proposed | - |
| Specific target organ toxicity - single exposure | No classification proposed | - |
| Specific target organ toxicity - repeated | No classification proposed | - |

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

| exposure | | |
|-------------------|----------------------------|---|
| Aspiration hazard | No classification proposed | - |
| | | |

Aggravated Medical

Condition

: None known.

12. ECOLOGICAL INFORMATION

Product : The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

| Components | End point | Species | Value | Exposure time |
|--|--|---|------------|---------------|
| Diethylene glycol monoethyl ether | flow- through test LC50 | Ictalurus punctatus | 6,010 mg/l | 96 h |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | No data available | | | |
| Tributyoxyethyl phosphate | semi- static test LC50 Measured | Oncorhynchus mykiss (rainbow trout) | 24 mg/l | 96 h |
| Hydrogen Peroxide | LC50 | Pimephales promelas (fathead minnow) | 16.4 mg/l | 96 h |

Toxicity to aquatic invertebrates

| Components | End point | Species | Value | Exposure |
|------------|-----------|---------|-------|----------|
| | | | | |

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

| | | | | time |
|--|---------------------------------|----------------------------|------------|------|
| Diethylene glycol monoethyl ether | static test EC50 | Daphnia magna (Water flea) | 1,982 mg/l | 48 h |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | No data available | | | |
| Tributyoxyethyl phosphate | static test EC50 Measured | Daphnia magna (Water flea) | 53 mg/l | 48 h |
| Hydrogen Peroxide | semi- static test LC50 | Daphnia pulex (Water flea) | 2.4 mg/l | 48 h |

Toxicity to aquatic plants

| Components | End point | Species | Value | Exposure time |
|--|---|---|---------------|---------------|
| Diethylene glycol monoethyl ether | static test EC50 Read- across (Analogy) | Desmodesmus subspicatus (green algae) | > 100 mg/l | 96 h |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | No data available | | | |
| Tributyoxyethyl phosphate | static test EC50 | Pseudokirchneriella subcapitata (green algae) | 61 mg/l | 72 h |
| Hydrogen Peroxide | static test EC50 | Skeletonema costatum | 1.38 mg/l | 72 h |

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

Persistence and degradability

| Component | Biodegradation | Exposure time | Summary |
|--|-------------------|---------------|-----------------------|
| Diethylene glycol monoethyl ether | 100 % | 28 d | Readily biodegradable |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | No data available | | |
| Tributyoxyethyl phosphate | 87 % | 28 d | Readily biodegradable |
| Hydrogen Peroxide | > 99 % | 30 min | Readily biodegradable |

Bioaccumulative potential

| Component | Bioconcentration factor (BCF) | Partition Coefficient n- Octanol/water (log) |
|--|-------------------------------|---|
| Diethylene glycol monoethyl ether | 3,162 | 0.54 |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | No data available | No data available |
| Tributyoxyethyl phosphate | 5.8 Measured | 3.75 Measured |
| Hydrogen Peroxide | No data available | -1.57 |

Mobility

| Component | End point | Value |
|--|-------------------|-------|
| Diethylene glycol monoethyl ether | No data available | |
| 2-Propenoic acid, polymer with ethenylbenzene and (1-methylethenyl)benzene | No data available | |
| Tributyoxyethyl phosphate | log Koc | 2.5 |
| Hydrogen Peroxide | No data available | |

PBT and vPvB assessment

| Component | Results |
|-----------------------------|--------------------------------------|
| Diethylene glycol monoethyl | Not fulfilling PBT and vPvB criteria |

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

| ether | |
|---------------------------|--------------------------------------|
| Tributyoxyethyl phosphate | Not fulfilling PBT and vPvB criteria |

Other adverse effects : None known.

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

Land transport

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

Notification status : All ingredients of this product comply with the New Substances

Notification requirements under the Canadian Environmental

Protection Act (CEPA).

California Prop. 65 : This product is not subject to the reporting requirements under

California's Proposition 65.

according to Hazard Communication Standard; 29 CFR 1910.1200



PLEDGE® FLOOR GLOSS - ORIGINAL

Version 1.1 Print Date 05/22/2018

Revision Date 02/25/2015 SDS Number 350000003597

16. OTHER INFORMATION

| HMIS | Ratin | qs |
|-------------|-------|----|
|-------------|-------|----|

| i iiiiio itatiiigo | | |
|--------------------|---|--|
| Health | 1 | |
| Flammability | 0 | |
| Reactivity | 0 | |

NFPA Ratings

| Health | 1 | |
|------------|---|--|
| Fire | 0 | |
| Reactivity | 0 | |
| Special | - | |

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

| Prepared by | SC Johnson Global Safety Assessment & |
|-------------|---------------------------------------|
| | Regulatory Affairs (GSARA) |