according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN SOF Number 76186

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE &

CEDAR

Recommended use : Air Freshener

Restrictions on use : Use only as directed on label

Manufacturer, importer,

supplier

S.C. Johnson & Son, Inc. 1525 Howe Street

Racine WI 53403-2236

Telephone : +1-800-558-5252

Emergency telephone

number

: 24 Hour Medical Emergency Phone: (866)231-5406 24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Aerosol	Category 1	Extremely flammable aerosol.
Eye irritation	Category 2B	Causes eye irritation.
Gases under pressure	Compressed gas	Contains gas under pressure; may explode if heated.

Labelling

Hazard symbols

Flame

Signal word

Danger

Hazard statements

Extremely flammable aerosol.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN SOF Number 76186

Causes eye irritation.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Other hazards : Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

Excessive exposure to spray mist, fog or vapour may cause

respiratory irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Acetone	67-64-1	30.00 - 60.00
Isobutane	75-28-5	30.00 - 60.00
Propane	74-98-6	5.00 - 10.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN SOF Number 76186

Skin contact : No special requirements

Inhalation : No special requirements.

Ingestion : No special requirements

Most important symptoms and effects, both acute and delayed

Eyes : May irritate eyes.

Skin effect : No adverse effects expected when used as directed.

May cause skin irritation.

Inhalation : Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

Excessive exposure to spray mist, fog or vapour may cause

respiratory irritation.

Ingestion : May cause abdominal discomfort.

No adverse effects expected when used as directed.

Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

5. FIREFIGHTING MEASURES

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during

firefighting

: Aerosol Product - Containers may rocket or explode in heat of

fire.

Further information : Fight fire from maximum distance or protected area. Cool and

use caution when approaching or handling fire-exposed containers. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or

explosion do not breathe fumes.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN SOF Number 76186

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Remove all sources of ignition.

Wash thoroughly after handling.

Environmental precautions

Outside of normal use, avoid release to the environment.

Methods and materials for containment and cleaning up

: If damage occurs to aerosol can:

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13). Use only non-sparking equipment.

Dike large spills.

Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

Avoid contact with skin, eyes and clothing. For personal protection see section 8.

Note: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. For more

information visit www.inhalant.org.

Use only as directed.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Pressurized container.

Do not pierce or burn, even after use. Wash thoroughly after handling.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Do not spray on an open flame or other ignition source.

Storage

Requirements for storage areas and containers

Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/ 122 °F.

Keep in a dry, cool and well-ventilated place.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN_SOF Number 76186

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non- standard units	Basis
Acetone	67-64-1	2,400 mg/m3	1,000 ppm	-	OSHA TWA
Acetone	67-64-1	-	500 ppm	-	ACGIH STEL
Acetone	67-64-1	-	250 ppm	-	ACGIH TWA
Isobutane	75-28-5	-	1,000 ppm	-	ACGIH STEL
Propane	74-98-6	1,800 mg/m3	1,000 ppm	-	OSHA TWA
Propane	74-98-6	-	-	-	ACGIH TWA

Personal protective equipment

Respiratory protection : No special requirements.

Hand protection : No special requirements.

Eye protection : No special requirements.

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : aerosol

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

SDS Number 350000042779 Revision Date 07/18/2022 GEN SOF Number 76186

Color colourless

Odour Woody

Odour Threshold : Test not applicable for this product type

рΗ : Test not applicable for this product type

Melting point/freezing point : Test not applicable for this product type

Initial boiling point and

boiling range

: Test not applicable for this product type

Flash point : -7 °C

19.4 °F Propellant -10 °C 14 °F

Method: Tag Closed Cup (TCC)

liquid

Evaporation rate : Test not applicable for this product type

Flammability (solid, gas) : Sustains combustion

explosive limits

Upper/lower flammability or: Test not applicable for this product type

Vapour pressure : Test not applicable for this product type

Vapour density : Test not applicable for this product type

Relative density : 0.695 g/cm3 at 20 °Cestimated

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN SOF Number 76186

Solubility(ies) : partly miscible

Partition coefficient: n-

octanol/water

: Test not applicable for this product type

Auto-ignition temperature : not auto-flammable

Decomposition temperature : Test not applicable for this product type

Viscosity, dynamic : Test not applicable for this product type

Viscosity, kinematic : Test not applicable for this product type

Oxidizing properties :

Volatile Organic Compounds Total VOC (wt. %)* : 42.3 % - additional exemptions may apply

*as defined by US Federal and State Consumer Product

Regulations

Other information : None identified :

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN_SOF Number 76186

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Thermal decomposition can lead to release of irritating gases

and vapours.

11. TOXICOLOGICAL INFORMATION

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin corrosion/irritation	No classification proposed	-
Eye irritation	Category 2B	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ	No classification proposed	-

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN_SOF Number 76186

toxicity - single		
exposure		
Specific target organ	No classification proposed	-
toxicity - repeated		
exposure		
Aspiration hazard	No classification proposed	-
·		

Aggravated Medical

Condition

: None known.

12. ECOLOGICAL INFORMATION

Product: The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Acetone	static test LC50	Oncorhynchus mykiss (rainbow trout)	6,210 mg/l	96 h
Isobutane	LC50 QSAR	Fish	27.98 mg/l	96 h
Propane	LC50 QSAR	Fish	49.9 mg/l	96 h

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Acetone	static test LC50	Daphnia pulex (Water flea)	8,800 mg/l	48 h

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779

GEN_SOF Number 76186

	NOEC	Daphnia magna	2,212 mg/l	28 d
Isobutane	LC50 QSAR	Daphnid	16.33 mg/l	48 h
Propane	LC50	Daphnid	27.14 mg/l	48 h

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Acetone	NOEC	Microcystis aeruginosa (blue-green algae)	530 mg/l	8 d
Isobutane	EC50 QSAR	Green algae	8.57 mg/l	96 h
Propane	EC50	Green algae	11.89 mg/l	96 h

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Acetone	90.9 %	28 d	Readily biodegradable.
Isobutane	70 %	< 10 d	Readily biodegradable.
Propane	70 %	< 10 d	Readily biodegradable.

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Acetone	0.69	-0.23

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779

GEN_SOF Number 76186

Isobutane	1.57 - 1.97	2.8
Propane	No data available	2.36

Mobility

Component	End point	Value
Acetone	No data available	
Isobutane	No data available	
Propane	No data available	

PBT and vPvB assessment

Component	Results
Acetone	Not fulfilling PBT and vPvB criteria
Isobutane	Not fulfilling PBT and vPvB criteria
Propane	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022 SDS Number 350000042779 GEN_SOF Number 76186

	Land transport	Sea transport	Air transport
UN number	1950	1950	1950
UN proper	AEROSOLS,	AEROSOLS,	AEROSOLS,
shipping name	Flammable	Flammable	Flammable
Transport hazard class(es)	2.1	2	2.1
Packing group	-	-	-
Environmental	-	-	-
hazards			
Special	Limited quantities	Limited quantities	Limited quantities
precautions for	derogation may be	derogation may be	derogation may be
user	applicable to this	applicable to this	applicable to this
	product, please check	product, please	product, please check
	transport documents.	check transport documents.	transport documents.
Transport in	Product not	Product not	Product not transported
bulk according	transported as bulk.	transported as bulk.	as bulk.
to Annex II of			
MARPOL 73/78			
and the IBC			
Code			

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

California Prop. 65 : This product is not subject to the reporting requirements under

California's Proposition 65.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - TWINKLING PINE & CEDAR

Version 1.0 Print Date 08/02/2023

Revision Date 07/18/2022

SDS Number 350000042779 GEN SOF Number 76186

16. OTHER INFORMATION

H١	ИIS	Rati	nas
----	-----	------	-----

Health	2	
Flammability	4	
Reactivity	0	

NFPA Ratings

NEFA Kalliys		
Health	2	
Fire	4	
Reactivity	0	
Special	-	

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment &
,	Regulatory Affairs (GSARA)